

14 OCT 2004

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
20 November 2003 (20.11.2003)


PCT

(10) International Publication Number
WO 2003/095007 A3

- (51) International Patent Classification⁷: **A61M 11/02**,
B05B 11/00
- (21) International Application Number:
PCT/EP2003/004858
- (22) International Filing Date: 7 May 2003 (07.05.2003)
- (25) Filing Language: English
- (26) Publication Language: English
- (30) Priority Data:
0210605.2 9 May 2002 (09.05.2002) GB
0217798.8 1 August 2002 (01.08.2002) GB
0219462.9 21 August 2002 (21.08.2002) GB
- (71) Applicant (for all designated States except US): **GLAXO GROUP LIMITED** [GB/GB]; Glaxo Wellcome House, Berkeley Avenue, Greenford, Middlesex UB6 0NN (GB).
- (72) Inventor; and
(75) Inventor/Applicant (for US only): **DAVIES, Michael, Birsha** [GB/GB]; GlaxoSmithKline, Park Road, Ware, Hertfordshire SG12 0DP (GB).
- (74) Agent: **RICE, Jason, Neale**; GlaxoSmithKline, 980 Great West Road, Brentford, Middlesex TW8 9GS (GB).
- (81) Designated States (national): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NI, NO, NZ, OM, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.
- (84) Designated States (regional): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE,

[Continued on next page]

(54) Title: A FLUID DISPENSING DEVICE



(57) Abstract: A fluid dispensing device (5, 105, 205, 305, 405, 505) is disclosed having a housing (9, 109, 209, 309, 409, 509) and a fluid discharge device (8, 108, 208, 308, 408, 508). The fluid discharge device (8, 108, 208, 308, 408, 508) is arranged to be actuated by one or more levers (20, 21; 120, 121; 170; 220, 221; 320, 321; 420, 421; 520) so as to apply a force transversely to the fluid discharge device (8, 108, 208, 308, 408, 508) which is used to move a container (30, 130, 230, 330, 430, 530) forming part of the fluid discharge device (8, 108, 208, 308, 408, 508) along a longitudinal axis of the fluid discharge device (8, 108, 208, 308, 408, 508) to cause actuation of a pump forming part of the fluid discharge device (8, 108, 208, 308, 408, 508). A pre-load means (28; 27, 28; 39, 40; 41, 42, 44; 144, 47a, 47b; 150, 152, 153; 224, 227; 342; 424x, 446; 425a; 427, 428; 560, 561) is used to prevent actuation of the pump until a pre-determined force is applied to each lever (20, 21; 120, 121; 170; 220, 221; 320, 321; 420, 421; 520) of sufficient magnitude to guarantee the production of a well developed efficient spray from the fluid dispensing device (5, 105, 205, 305, 405, 505).



162162



ACTION

WO 2003/095007 A3

WO 2003/095007 A3

ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO,
SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM,
GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

(88) Date of publication of the international search report:
1 April 2004

Published:

— with international search report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.