

Description

The invention relates to an assembly comprising a first element to which a second element is secured by means of an adhesive.

Such an assembly, in the form of an optical assembly, is known from European Patent Application 0,090,218 (herewith incorporated by reference). The known optical assembly comprises an optical component comprising two divider prisms and a part of an apparatus, an adhesive being applied in the gap between the optical component and said part.

Optical assemblies may be used in optical apparatuses, such as for example optical-disc players. In such apparatuses it is important that the various optical elements therein are positioned correctly relative to one another. For production reasons it is therefore essential that the optical elements in such assemblies are disposed at the correct predetermined location and in the correct position relative to, for example, a reference plane. Important in this respect is the positional accuracy in the direction of the optical axis (Z-direction) of the optical assembly, in the directions of two axes which extend perpendicularly to the optical axes and to one another (X-direction and Y-direction), and in the directions of rotation about the latter axes.

The known assembly has the drawback that inevitable shrinkage in the applied adhesive as it cures may give rise to comparatively large displacements of the optical component in the Z-direction. Moreover, the likelihood of the optical component being tilted about the X and Y axes is considerable as a result of shrinkage stresses arising in the adhesive layer. Said positioning problem can be reduced to some extent by making the adhesive layer thin in the Z direction, but the desired position of the optical component and the required strength and stability of the adhesive bond impose distinct restraints on this. A suitable choice of the adhesive may also reduce said problem but wholly eliminating shrinkage and shrinkage stresses is found to be impossible.

It is the object of the invention to improve the construction of an assembly of the type defined in the opening paragraph in such a way that it can be manufactured in a very accurate and reproducible manner, so that the assembly is suited for use in systems and apparatuses in which elements have to be positioned within very tight tolerances.

To this end the invention is characterized in that a wedge-shaped body having profiled surfaces facing the element is interposed between the first element and the second element, said surfaces comprising first surface portions against which said elements abut and second surface portions which together with the elements form adhesive gaps in which the adhesive by means of which the elements and the second surface portions are joined to each other is applied.

In the assembly in accordance with the invention the adhesive is present in predetermined narrow gaps between the wedge-shaped body and the elements, the cured adhesive ensuring that the elements are drawn against the two surface portions of the wedge-shaped body. This has the advantage that one element is located and positioned very accurately relative to the other element after curing of the adhesive. Shrinkage stresses arising during curing only have a negligible influence on the final position of the elements in the construction in accordance with the invention.

Assemblies in accordance with the invention may comprise first and second elements of widely varying nature, such as diodes, lenses, mirrors, and they comply with stringent tolerance requirements.

A suitable embodiment of the assembly in accordance with the invention is characterized in that the first surface portions and the second surface portions are separated from each other by grooves. For the sake of clarity it is to be noted that no adhesive is present between the first surface portions and the wedge-shaped body. An advantage of said grooves is that they facilitate the selective application of the adhesive. Moreover, during manufacture of the assembly the grooves prevent amounts of adhesive from migrating from the second to the first surface portions by capillary action.

A practical embodiment is characterized in that the wedge-shaped body comprises two limbs, said surfaces being disposed at an acute angle relative to one another. Suitably, one of the limbs of the wedge-shaped body is constructed as a leaf spring to compensate for minor displacements as a result of temperature variations.

Another favourable and stable embodiment is characterized in that during curing the adhesive applied in said gaps exhibits a shrinkage which is greater than the expansion of the cured adhesive in the temperature range for which the assembly is intended. Suitable types of adhesive are, for example, UV-curable adhesives such as acrylates.

An embodiment enabling material stresses to be minimised is characterized in that the wedge-shaped body and at least one of said elements are made of the same material.

The invention further relates to a device for recording and/or reading information in an information surface of a disc by means of a radiation spot, comprising a frame, a rotary drive means for the disc with a spindle which is rotatable about an axis of rotation, an optical system with a lens system which has an optical axis and which is movable parallel to and transversely of said axis of rotation, and a lens-system drive means. Such a device is known, for example, from British Patent Application 2,161,641 (PHN 11.088; herewith incorporated by reference).

The device in accordance with the invention is

characterized by the presence of the assembly in accordance with the invention, the first element of the assembly being formed by a mounting part connected to the frame and facing the wedge-shaped body and the second element comprising an optical or opto-electronic component, for example a read diode. The device in accordance with the invention has the advantage that the optical or opto-electronic component is mounted in the device exactly at the predetermined location with a high accuracy and stability and in a reproducible manner.

It is to be noted that from German Offenlegungsschrift 2.813.539 (herewith incorporated by reference) a construction is known to interconnect two hollow sections by means of two or more wedge-shaped connecting elements which cooperate with one another. The connecting elements are situated in the hollow sections and together they are clamped between the inner walls of the sections by means of embossed portions in the sections. They are connected both to each other and to one or both inner walls of the sections by means of an adhesive. The only resemblance of the assembly according to the invention with the known construction is that the body interposed between the first and the second element is wedge-shaped, like said known connecting elements.

An embodiment of the invention will now be described in more detail, by way of example, with reference to the accompanying drawings, in which

Fig. 1 shows schematically and partly in sectional view an embodiment of the device in accordance with the invention,

Fig. 2 is an enlarged-scale view of the assembly in accordance with the invention used in the device shown in Fig. 1,

Fig. 3A is a side view of the wedge-shaped body of the assembly shown in Fig. 2,

Fig. 3B is a view as indicated by the arrows IIIB-IIIB in Fig. 3A,

Fig. 3C is a view as indicated by the arrows IIIC-IIIC in Fig. 3A, and

Fig. 3D is a view as indicated by the arrows IIID-IIID in Fig. 3A.

The device shown in Fig. 1 serves for optically reading a disc 3, which is rotatable about an axis of rotation 1, by means of a radiation spot 5. The disc 3 comprises a transparent substrate whose upper side is provided with an information surface 9 which is coated with a reflecting layer. The disc may be, for example, a CD or a CDV.

The device comprises a frame 11 and a lens-system drive means 13 which is translatable relative to the frame along a radial path. The lens-system drive means 13 comprises a movable lens support 15 with a lens system 17 which is movable transversely of the disc 3. The rectilinear guide means of the lens-system drive means 13 comprises two parallel rods 19, of which only one rod is visible in Fig. 1, which rods are

secured to mounting faces 21 of the frame 11. The lens-system drive means 13 comprises magnets and coils, not shown, and is provided with sleeve bearings 23 by means of which the means 13 is movable over the rods. The lens support 15, which is provided with actuator coils, not shown, is supported on the lens-system drive means 13 by leaf springs 25 and 27 at its upper and lower side respectively, which leaf springs are secured to the lens support 15 and to the lens-system drive means 13 at their respective ends. The lens support 15 together with the lens system 17 is movable to a limited extent along the optical axis 18 of the lens system 17.

The lens system 17 is movable along its optical axis 25 under servo control to enable the movements of the disc 3 to be followed with the radiation spot 5 formed by a radiation beam 28. For a more comprehensive description of the lens-system drive means and the lens system reference is made to Netherlands Patent Application 8204366 (PHN 10.530; herewith incorporated by reference). The radiation beam 28 is emitted by a stationary radiation source 29, for example a semiconductor laser, and passes through a semi-transparent mirror 30. A semiconductor diode 33 arranged on a printed-circuit board 31 serves for converting the radiation-beam modulation into an electrical modulation. For a description of the construction and operation of optical systems suited for the conversion between optical and electrical modulations reference is made to the existing literature on this subject.

The frame 11, which may be manufactured by die-casting from a suitable material, has a substantial open box-shape with a profiled bottom 11A and side walls 11B. The frame 11 further comprises a frame portion 11C provided with an inclined surface 11C1, to which a wedge-shaped body 35 is glued. The said printed-circuit board 31 carrying the semiconductor diode 33 is glued to the wedge-shaped body 35. It is essential that the diode 33 is in the correct position relative to the radiation beam which is directed towards the printed circuit board 31 by the semi-transparent mirror 30. The assembly comprising the diode 31 mounted on the printed circuit board 31, the wedge-shaped body 35 and the frame portion 11C is shown to an enlarged scale in Fig. 2.

The device in accordance with the invention further comprises a drive means 41 for rotating the disc 3. The drive means 41 comprises a spindle 43 which is rotatable about the axis of rotation 1, on which spindle a turntable 45 for supporting the disc 3 is mounted. The rotatable spindle 43 is journaled in the frame 11 by means of two bearing bushes 47 and 49, which are clamped in the frame. In the present construction the spindle 43 also constitutes the motor shaft and carries a rotor 51. The rotor 51 has a cylindrical magnet 53 which cooperates with a stator 55 which is secured to the frame 11. The rotor 51 and the

stator 53 forms part of an electric-motor unit 57.

The wedge-shaped body 35 shown in Fig. 2 and Figs. 3A to 3D has two profiled surfaces 37 and 39, which are disposed at an acute angle to one another. The surface 37 faces the frame portion 11C, whilst the surface 39, which in the present example comprises two spatially separated parts, faces the printed circuit board 31. The surfaces 37 and 39 each comprise a first surface portion 37A and 39A respectively and two surface portions 37B and 39B respectively. The surface portions 37A and 37B and the surface portions 39A and 39B are spaced from each other by parallel grooves 59 in the surfaces 37 and 39. Together with the surface portions 37B and 39B the printed circuit board 31 and the frame portion 11C define gaps 61 in which a cured adhesive is present. The adhesive provides the connection of the elements 31 and 11C to the wedge-shaped body 35, whilst the wedge-shaped body 35 itself, by means of the surface portions 37A and 39A against which the elements 31 and 11C abut, ensures that the diode 33 occupies the desired position. During manufacture, before the adhesive is allowed to cure, the wedge-shaped body 35 is therefore moved in such a way relative to the frame portion 11C in the Z-direction (Fig. 2) and the printed circuit board 31 is moved in such a way relative to the wedge-shaped body 35 in the X-direction and in the Y-direction, that the diode 33 is situated at exactly the desired location.

In the present example, as is clearly visible in the drawings, the wedge-shaped body 35 comprises two limbs, one of the limbs 35A behaving as a leaf spring. The wedge-shaped body 35 and the frame portion 11C are manufactured from a metal. In the present example this metal is a magnesium alloy.

Obviously the invention is not limited to the embodiments shown. For example, it is possible to use the assembly in accordance with the invention in an optical device in which the objective is not movable parallel to the disc by means of a slide as shown in Fig. 1, but is movable by means of a pivotable element. Such a device is described in, for example, European Patent Application 0.143.483 (PHN 10.813; herewith incorporated by reference).

Claims

1. An assembly comprising a first element to which a second element is secured by means of an adhesive, characterized in that a wedge-shaped body (35) having profiled surfaces (37, 39) facing the elements is interposed between the first element and the second element, said surfaces comprising first surface portions (37A, 39A) against which said elements abut and second surface portions (37B, 39B) which together with the elements form adhesive gaps (61) in which the adhesive by means of which the elements

and the second surface portions are joined to each other is applied.

2. An assembly as claimed in Claim 1, characterized in that the first surface portions (37A, 39A) and the second surface portions (37B, 39B) are separated from each other by grooves (59).

3. An assembly as claimed in Claim 1 or 2, characterized in that the wedge-shaped body comprises two limbs (35A) the said surfaces being disposed at an acute angle relative to one another.

4. An assembly as claimed in Claim 3, characterized in that one of the limbs (35A) of the wedge-shaped body is constructed as a leaf spring.

5. An assembly as claimed in Claim 1, characterized in that during curing the adhesive applied in said gaps (61) exhibits a shrinkage which is greater than the expansion of the cured adhesive in the temperature range for which the assembly is intended.

6. An assembly as claimed in Claim 5, characterized in that the adhesive is of an UV-curable type.

7. An assembly as claimed in Claim 1, characterized in that the wedge-shaped body (31) and at least one of the said elements are made of the same material.

8. An assembly as claimed in Claim 1, characterized in that one of said elements forms part of a frame (11).

9. An assembly as claimed in any one of the preceding Claims, characterized in that at least one of said elements comprises an optical or opto-electronic component.

10. A device for recording and/or reading information in an information surface of a disc by means of a radiation spot, comprising a frame (11), a rotary drive means (41) for the disc with a spindle (43) which is rotatable about an axis of rotation (1), an optical system with a lens system (17) which has an optical axis (18) and which is movable parallel to and transversely of said axis of rotation, a lens-system drive means (13), and an assembly as claimed in Claim 9, the first element of the assembly being formed by a mounting part (11C) connected to the frame and facing the wedge-shaped body (35) and the second element comprising the optical or opto-electronic component.

11. A device as claimed in Claim 10, characterized in that the first element is a part of the frame (11) and the second element comprises a printed circuit board (31) carrying a read diode (33) and facing the wedge-shaped body (35).

Patentansprüche

1. Vorrichtung mit einem ersten Element, an dem ein zweites Element festgeklebt ist, dadurch gekennzeichnet, daß ein keilförmiger Körper (35) mit den Elementen zugewandten, profilierten Oberflächen (37,

stator 53 forms part of an electric-motor unit 57.

The wedge-shaped body 35 shown in Fig. 2 and Figs. 3A to 3D has two profiled surfaces 37 and 39, which are disposed at an acute angle to one another. The surface 37 faces the frame portion 11C, whilst the surface 39, which in the present example comprises two spatially separated parts, faces the printed circuit board 31. The surfaces 37 and 39 each comprise a first surface portion 37A and 39A respectively and two surface portions 37B and 39B respectively. The surface portions 37A and 37B and the surface portions 39A and 39B are spaced from each other by parallel grooves 59 in the surfaces 37 and 39. Together with the surface portions 37B and 39B the printed circuit board 31 and the frame portion 11C define gaps 61 in which a cured adhesive is present. The adhesive provides the connection of the elements 31 and 11C to the wedge-shaped body 35, whilst the wedge-shaped body 35 itself, by means of the surface portions 37A and 39A against which the elements 31 and 11C abut, ensures that the diode 33 occupies the desired position. During manufacture, before the adhesive is allowed to cure, the wedge-shaped body 35 is therefore moved in such a way relative to the frame portion 11C in the Z-direction (Fig. 2) and the printed circuit board 31 is moved in such a way relative to the wedge-shaped body 35 in the X-direction and in the Y-direction, that the diode 33 is situated at exactly the desired location.

In the present example, as is clearly visible in the drawings, the wedge-shaped body 35 comprises two limbs, one of the limbs 35A behaving as a leaf spring. The wedge-shaped body 35 and the frame portion 11C are manufactured from a metal. In the present example this metal is a magnesium alloy.

Obviously the invention is not limited to the embodiments shown. For example, it is possible to use the assembly in accordance with the invention in an optical device in which the objective is not movable parallel to the disc by means of a slide as shown in Fig. 1, but is movable by means of a pivotable element. Such a device is described in, for example, European Patent Application 0.143.483 (PHN 10.813; herewith incorporated by reference).

Claims

1. An assembly comprising a first element to which a second element is secured by means of an adhesive, characterized in that a wedge-shaped body (35) having profiled surfaces (37, 39) facing the elements is interposed between the first element and the second element, said surfaces comprising first surface portions (37A, 39A) against which said elements abut and second surface portions (37B, 39B) which together with the elements form adhesive gaps (61) in which the adhesive by means of which the elements

and the second surface portions are joined to each other is applied.

2. An assembly as claimed in Claim 1, characterized in that the first surface portions (37A, 39A) and the second surface portions (37B, 39B) are separated from each other by grooves (59).

3. An assembly as claimed in Claim 1 or 2, characterized in that the wedge-shaped body comprises two limbs (35A) the said surfaces being disposed at an acute angle relative to one another.

4. An assembly as claimed in Claim 3, characterized in that one of the limbs (35A) of the wedge-shaped body is constructed as a leaf spring.

5. An assembly as claimed in Claim 1, characterized in that during curing the adhesive applied in said gaps (61) exhibits a shrinkage which is greater than the expansion of the cured adhesive in the temperature range for which the assembly is intended.

6. An assembly as claimed in Claim 5, characterized in that the adhesive is of an UV-curable type.

7. An assembly as claimed in Claim 1, characterized in that the wedge-shaped body (31) and at least one of the said elements are made of the same material.

8. An assembly as claimed in Claim 1, characterized in that one of said elements forms part of a frame (11).

9. An assembly as claimed in any one of the preceding Claims, characterized in that at least one of said elements comprises an optical or opto-electronic component.

10. A device for recording and/or reading information in an information surface of a disc by means of a radiation spot, comprising a frame (11), a rotary drive means (41) for the disc with a spindle (43) which is rotatable about an axis of rotation (1), an optical system with a lens system (17) which has an optical axis (18) and which is movable parallel to and transversely of said axis of rotation, a lens-system drive means (13), and an assembly as claimed in Claim 9, the first element of the assembly being formed by a mounting part (11C) connected to the frame and facing the wedge-shaped body (35) and the second element comprising the optical or opto-electronic component.

11. A device as claimed in Claim 10, characterized in that the first element is a part of the frame (11) and the second element comprises a printed circuit board (31) carrying a read diode (33) and facing the wedge-shaped body (35).

Patentansprüche

1. Vorrichtung mit einem ersten Element, an dem ein zweites Element festgeklebt ist, dadurch gekennzeichnet, daß ein keilförmiger Körper (35) mit den Elementen zugewandten, profilierten Oberflächen (37,



39) zwischen das erste und zweite Element eingefügt ist, wobei diese Oberflächen erste Oberflächenteile (37A, 39A) aufweisen, an denen die genannten Elemente anliegen, und zweite Oberflächenteile (37B, 39B), die zusammen mit den Elementen Klebspalte (61) bilden, in denen ein Klebstoff, mit dessen Hilfe die Elemente und die zweiten Oberflächenteile aneinander befestigt sind, angebracht sind.

2. Vorrichtung nach Anspruch 1, dadurch gekennzeichnet, daß die ersten Oberflächenteile (37A, 39A) und die zweiten Oberflächenteile (37B, 39B) durch Rillen (59) voneinander getrennt sind.

3. Vorrichtung nach Anspruch 1 oder 2, dadurch gekennzeichnet, daß der keilförmige Körper zwei Schenkel (35A) aufweist, wobei die genannten Oberflächen in einem scharfen Winkel zueinander vorgesehen sind.

4. Vorrichtung nach Anspruch 3, dadurch gekennzeichnet, daß einer der Schenkel (35A) des keilförmigen Körpers als Blattfeder ausgebildet ist.

5. Vorrichtung nach Anspruch 1, dadurch gekennzeichnet, daß der in den Spalten (61) angebrachte Klebstoff beim Aushärten eine größere Schrumpfung aufweist als die Ausdehnung des ausgehärteten Klebstoffs, die in dem Temperaturbereich, für den die Vorrichtung gemeint ist, auftritt.

6. Vorrichtung nach Anspruch 5, dadurch gekennzeichnet, daß der Klebstoff vom UV-härtenden Typ ist.

7. Vorrichtung nach Anspruch 1, dadurch gekennzeichnet, daß der keilförmige Körper (31) und wenigstens eines der genannten Elemente aus dem gleichen Werkstoff hergestellt sind.

8. Vorrichtung nach Anspruch 1, dadurch gekennzeichnet, daß eines der Elemente einen Teil eines Rahmens (11) bildet.

9. Vorrichtung nach einem der vorstehenden Ansprüche, dadurch gekennzeichnet, daß wenigstens eines der Elemente ein optisches oder optoelektronisches Bauelement aufweist.

10. Vorrichtung zum Aufzeichnen und/oder Auslesen von Information in einer Informationsfläche einer Platte mittels eines Strahlungsbündels mit einem Rahmen (11), einem Drehantriebsmittel (41) für die Platte mit einer um die Drehungsachse (1) drehbaren Spindel (43), einem optischen System mit einem in paralleler und in Querrichtung der Drehungsachse verschiebbaren Linsensystem (17) mit einer optischen Achse (18), einem Linsensystemantriebsmittel (13) und einer Vorrichtung nach Anspruch 9, wobei das erste Element der Vorrichtung durch einen Konstruktionsteil (11C) gebildet ist, der mit dem Rahmen verbunden und dem keilförmigen Körper (35) zugewandt ist und wobei das zweite Element das optische oder optoelektronische Bauelement aufweist.

11. Vorrichtung nach Anspruch 10, dadurch gekennzeichnet, daß das erste Element ein Teil des

Rahmens (11) ist und das zweite Element eine Printplatte (31) mit einer dem keilförmigen Körper (35) zugewandten Auslesediode (33) aufweist.

Revendications

1. Ensemble comportant un premier élément auquel un second élément est fixé par un adhésif, caractérisé en ce qu'un corps en forme de coin (35) présentant des surfaces profilées (37, 39) situées vis-à-vis des éléments est interposé entre le premier élément et le second élément, lesdites surfaces comportant de premières parties (37A, 39A) contre lesquelles sont appuyés lesdits éléments et de secondes parties (37B, 39B) formant avec les éléments des interstices de collage (61) dans lesquels est introduit l'adhésif réunissant les éléments et les secondes parties les uns aux autres.

2. Ensemble selon la revendication 1, caractérisé en ce que les premières parties (37A, 37B) et les secondes parties (37B, 39B) sont séparées par des rainures (54).

3. Ensemble selon la revendication 1 ou 2, caractérisé en ce que le corps en forme de coin comporte deux ailes (35A), lesdites surfaces faisant un angle aigu l'une par rapport à l'autre.

4. Ensemble selon la revendication 3, caractérisé en ce que le corps en forme de coin comporte deux ailes, l'une des ailes (35A) se comportant comme ressort-lame.

5. Ensemble selon la revendication 1, caractérisé en ce que l'adhésif introduit dans lesdits interstices (61) présente, au cours de son durcissement, un retrait qui est supérieur à l'expansion de l'adhésif durci dans la gamme de températures à laquelle est destiné l'ensemble.

6. Ensemble selon la revendication 5, caractérisé en ce que l'adhésif est d'un type durcissable aux ultraviolets.

7. Ensemble selon la revendication 1, caractérisé en ce que le corps en forme de coin (31) et au moins l'un desdits éléments sont fabriqués à partir du même matériau.

8. Ensemble selon la revendication 1, caractérisé en ce que l'un desdits éléments fait partie d'un châssis (11).

9. Ensemble selon l'une quelconque des revendications précédentes, caractérisé en ce que l'un desdits éléments comporte au moins un constituant optique ou optoélectronique.

10. Un dispositif d'enregistrement et/ou de lecture d'information dans une surface d'information d'un disque par l'intermédiaire d'un spot de rayonnement, comportant un châssis (11), des moyens d'entraînement rotatifs (41) pour le disque munis d'un arbre (43) qui peut tourner autour d'un axe de rotation (1), un système optique pourvu d'un système de len-



lilles (17) présentant un axe optique (18) qui peut être déplacé parallèlement et transversalement audit axe de rotation, ainsi que des moyens d'entraînement de système de lentilles (13), et un ensemble selon la revendication 9, le premier élément de l'ensemble étant formé par un constituant de montage (11C) relié au châssis et faisant face au corps en forme de coin (35) et le second élément comportant un constituant optique ou optoélectronique.

11. Dispositif selon la revendication 10, caractérisée en ce que le premier élément est une partie du châssis (11) et en ce que le second élément comporte une carte de circuit imprimé (31) portant une diode de lecture (33) et faisant face au corps en forme de coin (35).

5

10

15

20

25

30

35

40

45

50

55

6

