

Description**Field of the Invention**

5 This invention relates to dough compositions for making improved baked goods. The invention particularly relates to pastries, biscuits, shortbreads and shortcakes having a more tender texture.

Background of the Invention

10 Several references disclose baked goods made with sucrose fatty acid esters. For example, U.S. Patent 4,461,782 of Robbins et al., issued July 24, 1984, discloses baked products comprising from about 12% to about 60% of a nonabsorbable, nondigestible liquid polyol polyester and from about 25% to about 85% microcrystalline cellulose or a mixture of microcrystalline cellulose and flour, in a weight ratio of cel-
 15 lulose:flour of at least 1:1. The preferred polyol polyesters are said to be sucrose hexaoleate, sucrose heptaoleate, and sucrose octaoleate. Specific examples of baked goods listed in the Robbins et al. patent are bread, cake, and wafers.

U.S. Patent 3,600,186 of Mattson et al., issued August 17, 1971, discloses low-calorie food composi-
 20 tions produced by replacing at least a portion of the fat content of a conventional food with a sugar fatty acid ester or sugar alcohol fatty acid ester having at least 4 fatty acid ester groups with each fatty acid having from 8 to 22 carbons. Sucrose fatty acid esters are preferred esters. Specific food examples given in the Mattson et al. patent include bread, cakes, and culinary mixes.

In a Journal article, Fallat et al. discuss a clinical in which intermediate melting sucrose fatty acid esters are used in baked foods. Fallat et al., "Short Term Study of Sucrose Polyester a Nonabsorbable Fat-like Material as a Dietary Agent for Lowering Plasma Cholesterol," The American Journal of Clinical Nutrition
 25 29, November 1976, pp. 1204-1215.

Glueck et al. disclose a clinical in which sucrose polyester is used to make baked foods. The sucrose polyester is a mixture of 43% octaester, 43% heptaester, and 14% hexaester. Glueck et al., "The Lowering of Plasma Cholesterol by Sucrose Polyester in Subjects Consuming Diets with 800, 300, or Less Than 500 Milligrams of Cholesterol per Day," The American Journal of Clinical Nutrition 32, August 1979, pp. 1636-
 30 1644.

U.S. Patent 4,034,083 of Mattson, issued July 5, 1977, discloses polyol fatty acid polyesters having at least 4 fatty acid ester groups fortified with fat-soluble vitamins and used in pharmaceutical compositions and low-calorie foods. The polyesters are said to be useful for breadmaking and cakemaking.

None of these references relates to pastries, biscuits, shortbreads or shortcakes, and none suggests
 35 that tenderness can be improved in these baked goods by the use of sucrose fatty acid esters instead of triglycerides.

It is therefore an object of the present invention to make novel pastry doughs, biscuit doughs, and shortbread and shortcake doughs, that can be baked to produce improved baked goods.

It is specifically an object of the present invention to make pastries, biscuits, shortbreads, and
 40 shortcakes having improved tenderness compared to like baked goods of the same recipe made with triglyceride shortenings.

It is a particular object of the present invention to make more tender pie crusts.

These and other objects of the present invention will become evident from the disclosure herein.

All percentages are by weight unless otherwise defined.

Summary of the Invention

The invention relates to dough compositions that can be baked to form pastries, biscuits, shortbreads and shortcakes having improved tenderness. This benefit is achieved by incorporating sucrose fatty acid
 50 esters of the invention into the dough formulations.

According to the present invention there is provided a pastry dough comprising a mixture of

a) a fat product,

b) flour, and

c) a liquid selected from water, milk and mixtures thereof,

55 said dough being made by a process employing a low shear method of mixing,

said pastry dough comprising from 20% to 50% of a), from 30% to 70% of b) and from 5% to 30% of c);

said biscuit dough comprising from 5% to 30% of a), from 35% to 60% of b), and from 25% to 45% of c);

said shortbread dough comprising from 25% to 55% of a), from 35% to 60% of b) and from 0% to 20% of

c);

and said shortcake dough comprising from 5% to 30% of a), from 30% to 65% of b) and from 20% to 50% of c);

characterised in that

- 5 said fat product comprises from 10% to 100% by weight of sucrose fatty acid esters having at least 4 fatty acid ester groups, wherein each fatty acid group has from 8 to 22 carbon atoms, and from 0% to 90% of other fat ingredients selected from shortenings, margarines, fats oils and mixtures thereof; wherein the fat product has a penetration between 120 mm/10 and 350 mm/10 at 21 °C and a Yield Point between 50 Pa and 1000 Pa at 21 °C.

10

Detailed Description of the Invention

Tenderness in baked goods is usually defined as the amount of force required to bite into a baked product, or the amount of force required to break the product into small pieces as it is chewed.

- 15 The strength of the gluten network formed when flour is wetted determines how tender a pastry biscuit shortbread or shortcake will be. The degree to which the fat and flour are mixed greatly impacts the strength of the gluten network. The more they are mixed, the more discontinuous the gluten network becomes, and the more tender the baked goods will be. However, overmixing makes the baked goods difficult to handle.

- 20 Surprisingly, shortenings containing the sucrose fatty acid esters of the invention have been found to be lower in yield point than triglyceride shortenings with similar penetrations. They have also unexpectedly been found to create pastries, biscuits, shortbreads and shortcakes which are more tender than similar baked goods of the same recipe made with triglyceride shortenings. While not intending to be limited by theory, it is believed that because the sucrose ester shortenings deform more easily than triglyceride
25 shortenings, the shortenings are more completely coated with flour for the same amount of mixing. This allows the baked good to be tender while avoiding a dough which is overmixed and difficult to handle.

- The tenderness benefit of the present invention is found in pastries, biscuits, shortbreads and shortcakes made from doughs containing the present sucrose fatty acid esters. These baked goods are distinguished from baked goods such as cookies, cakes, breads, wafers, etc. in at least two ways: the type
30 and level of ingredients and the method of ingredient mixing.

- The ingredients of pastries, biscuits, shortbreads and shortcakes are generally comprised of flour, fat, water or milk, some flavoring substance such as salt, and some coloring substance such as milk solids or corn sugars. Other ingredients which could be added are baking powder, eggs, and sugar, but at generally low levels, less than about 20%, for example. In the case of cakes, cookies, bread, wafers etc., the
35 ingredient systems tend to incorporate relatively high levels of sugar (greater than about 20%) and/or leavening agents, emulsifiers, etc. in addition to flour, fat, water or milk, flavoring and coloring agents. These additional ingredients generally have a profound impact on texture, making the baked goods aerated, or chewy, or cakey, etc. On the other hand, pastries and like baked goods, which do not use these additional ingredients, tend to be unaerated, flaky, tender, etc.

- 40 The mixing of baked goods such as cookies, cakes, bread, wafers, etc. is also fundamentally different from that of pastry doughs or like baked goods. Recipes for cookies, cakes, bread, wafers, etc. generally call for intimately mixing fat and sugar together in a cream, adding the liquid ingredients, adding flour and other dry ingredients and mixing with relatively high shear. This results in a much more intimately mixed fat than that in pastry doughs and other like baked goods, and differences in yield point of different fats which
45 may be used are overcome by this vigorous, high shear mixing.

- In pastry doughs and other like baked goods, a low shear method of mixing is employed. By "low shear method of mixing," as used herein, is meant methods of mixing such as cutting, folding, rubbing, layering or blending. In the case of pie crusts, for example, the fat is cut directly into the dry ingredients, and water or milk is added to this fat/dry ingredient mixture. In the case of puff pastry, the majority of the fat is layered
50 and/or folded between layers of a dough comprised of the remaining fat, dry ingredients and small amounts of liquid. With any of these methods of mixing employed, the result is much less intimate mixing, and the effects of differences in yield point of the fat are much more pronounced. In fact, if too much mixing is used in making the dough, it is not possible to properly handle the dough or form it into the desired shape, e.g. circle, without tearing, etc.

- 55 "Pastry doughs," as used herein, include but are not limited to pie crusts, tart shells, Fillo doughs, strudel, baklava, and the doughs of puff pastries such as patty shells, cream puffs, turnovers, eclairs. Danish pastry and French pastry. When baked, these doughs typically appear fragile blistery flaky and delicate, with a golden brown color.

"Biscuits," as used herein, are the flaky biscuits known to the art, such as wheat biscuits or buttermilk biscuits. The crusts typically appear fragile, crisp, and golden brown, and the insides are generally white, fluffy and flaky. Pastries and biscuits are described in Modern Encyclopedia of Cooking, Vol. 1, pp. 234-237 and Vol. 2, pp. 921-1027, J.G. Ferguson Publishing, Chicago, 1959.

5 "Shortbreads," as used herein, are the flaky baked goods resembling thick pie crusts. "Shortcakes" are the flaky, biscuit-like shortcakes, not the spongy aerated cakes sometimes called shortcakes.

It is important to note that certain baked goods may be called by the name of one of these categories, but on the basis of ingredients used or method of mixing, belong to the other category. For instance, some baked goods which are called cookies may in fact be more of a shortbread and fit the category of
10 shortbread in this invention because of the ingredients used and method of mixing.

The present invention, then, relates to pastry doughs, biscuit doughs, and shortbread and shortcake doughs which are comprised as follows:

Pastry doughs - from 20% to 50% of a fat product described in detail below, from 30% to 70% flour, and from 5% to 30% of a liquid selected from water, milk, and mixtures thereof.

15 Biscuit doughs - from 5% to 30% of the fat product, from 35% to 60% flour, and from 25% to 45% water and/or milk.

Shortbread doughs - from 25% to 55% of the fat product, from 35% to 60% flour, and from 0% to 20% water and/or milk.

20 Shortcake doughs - from 5% to 30% of the fat product, from 30% to 65% flour, and from 20% to 50% water and/or milk.

The doughs of these compositions are excellent pastry, biscuit, shortbread or shortcake doughs, particularly pie doughs, which produce baked goods having improved tenderness over baked goods of the same recipe made with triglyceride shortenings or other triglyceride fat products.

25 If the amount of fat product is less than the amounts allowed above for any of these doughs, the gluten network will not be shortened enough and the product baked from the dough will not be tender. If the fat product is more than the amounts allowed above for any of these doughs, the product baked from the dough will be too tender to handle.

The fat product portion of the dough comprises from 10% to 100% sucrose fatty acid esters, and from 0% to 90% other fat ingredients selected from shortenings, margarines, fats, oils, and mixtures thereof.

30 The sucrose fatty acid esters, or sucrose polyesters of the present invention are sucrose fatty acid esters esterified with at least four fatty acid groups. These compounds are prepared by reacting a sucrose with fatty acid as discussed below. The sucrose starting material must be esterified on at least four of the hydroxyl groups with a fatty acid containing from 8 to 22 carbon atoms, and preferably from 14 to 18 carbon atoms. Examples of such fatty acids include caprylic, capric, lauric, myristic, myristoleic, palmitic,
35 palmitoleic, stearic, oleic, ricinoleic, linoleic, linolenic, eleostearic, arachidic, arachidonic, behenic, and erucic acid. The fatty acids can be derived from naturally occurring or synthetic fatty acids; they can be saturated or unsaturated, including positional and geometrical isomers. The fatty acids esterified to the sucrose molecule can be the same or mixed.

40 The use of sucrose esters containing four or more fatty acid ester groups has the additional benefit of providing reduced calorie baked goods, because these esters are substantially non-digestible by the human body.

A preferred sucrose fatty acid ester for use in the present invention has: (a) a total content of octa-, hepta- and hexa-esters of not less than 95 percent; (b) an octa-ester content of not less than 70 percent; and (c) a content of the penta- and lower esters of not more than 3 percent.

45 The sucrose fatty acid esters of the present invention also preferably have a non-Newtonian plastic rheology at 100° F (37.8° C). In particular, the sucrose fatty acid esters preferably have a viscosity of not less than 15 poise (1.5Pa.S) at 100° F (37.8° C) after 10 minutes of steady shear at 10 sec⁻¹. The esters also preferably have a liquid/solid stability of not less than 90 percent at 100° F (37.8° C).

50 The sucrose fatty acid esters can be a single type of ester or a mixture of esters. For the preferred sucrose esters mentioned above, it is not critical that each type of ester has the above-mentioned physical properties as long as the sucrose esters as a whole have these physical properties.

Viscosity is a known rheological property and can be measured by use of an instrument such as a plate and cone viscometer (e.g., a Ferranti-Shirley viscometer, manufactured by Ferranti Electric, Inc., 87 Modular Ave., Commack, NY 11725). Additional details are provided below under the Analytical Methods section.

55 The basics of rheology are discussed in Idson, "Rheology" Fundamental Concepts," Cosmetics and Toiletries, Vol. 93, pp. 23-30 (July 1978).

The sucrose fatty acid esters suitable for use herein can be prepared by a variety of methods known to those skilled in the art. These methods include: transesterification of the sucrose with methyl, ethyl or

glycerol fatty acid esters using a variety of catalysts; acylation of the sucrose with a fatty acid chloride; acylation of the sucrose with a fatty acid anhydride; and acylation of the sucrose with a fatty acid, per se. As an example, the preparation of polyol fatty acid esters is described in U.S. Patent Nos. 3,963,699; 4,517,360; and 4,518,772.

5 In addition to the sucrose fatty acid esters detailed above, the fat product of the present doughs comprises from 0% to 90% other fat ingredients such as edible fats and oils, shortenings, margarines and mixtures thereof. Any of a variety of glyceride-based oil or fat materials can be used in the present invention provided that the impact on yield point and penetration is such as to be suitable for use in the fat product portion of the doughs. In addition, these glyceride oils or fats and the present fat products can be
10 processed with one or more of the following processes: hydrogenation, winterization, dewaxing, interesterification, etc. Any standard processing method can be used to make the present fat products.

The fats and oils comprise triglycerides, fatty acids, fatty alcohols, and esters of such acids and alcohols. Especially appropriate for use in the present invention are triglycerides of straight chain or branched chain, saturated or unsaturated, monocarboxylic acids having from 10 to 28 carbon atoms.
15 Suitable sources of such oils include: 1) vegetable fats and oils such as soybean, corn, sunflower, rapeseed, low erucic acid rapeseed, canola, cottonseed, olive, safflower and sesame seed; 2) meat fats such as tallow or lard; 3) marine oils; 4) nut fats and oils such as coconut, palm, palm kernel, or peanut; 5) milkfat, butterfat; 6) cocoa butter and cocoa butter substitutes such as shea, or illipe butter; and 7) synthetic fats.

The other fat ingredients can also be other noncaloric or reduced calorie fats, such as branched chain
20 fatty acid triglycerides, triglycerol ethers, polycarboxylic acid esters, sucrose polyethers, neopentyl alcohol esters, silicone oils/siloxanes, and dicarboxylic acid esters. Other partial fat replacements useful in the present compositions are medium chain triglycerides, highly esterified polyglycerol esters, acetin fats, plant sterol esters, polyoxyethylene esters, jojoba esters, mono-diglycerides of fatty acids, and mono-diglycerides of short-chain dibasic acids.

25 Polyol fatty acid polyesters can also be used as other fat ingredients in the fat product portion of the present doughs. Preferred polyol fatty acid polyesters are other sugar fatty acid polyesters, sugar alcohol fatty acid polyesters, and polyglycerol fatty acid polyesters, and mixtures thereof. The sugar fatty acid polyesters and sugar alcohol fatty acid polyesters preferably contain from 4 to 8 hydroxyl groups.

Various other additives can be used in the fat product portion of the invention provided that they are
30 edible and aesthetically desirable and do not have any detrimental effects on the fats. The fats and oils can normally contain minor amounts of optional flavourings; emulsifiers such as the lower sucrose esters, mono- and diglycerides and lactylated glycerides; anti-spattering agents; anti-sticking agents, anti-oxidants; or the like. As with standard shortenings, nitrogen can also be added to the fat product during processing to improve the lightness of color of the product.

35 The fat product can also be fortified with vitamins and minerals, particularly the fat-soluble vitamins. The fat-soluble vitamins include vitamin A, vitamin D, vitamin K, and vitamin E (tocopherol). Preferably, the fat product of this invention is fortified with 1.1 mg. d-alpha tocopheryl acetate per 1000 g sucrose fatty acid ester.

It is possible for the type of fat used to diminish the effect of the sucrose fatty acid ester. For example,
40 if a shortening is the fat used, and it contains too high a level of triglyceride hardstock, palm hardstock for example, the penetration of the fat product will be increased negating the presence of the sucrose ester structure. There are two ways to prevent this from occurring. One is by controlling penetration of the fat product, the other is by controlling yield point.

It is critical that the fat product have a penetration between 120 mm/10 and 350 mm/10 at 70°F
45 (21°C). If the penetration is below 120 mm/10, the fat will be too firm to properly mix and the tenderness benefit is lost. If the penetration is 350 mm/10, the product baked from the dough will be too tender to handle.

Preferably, the fat product has a penetration between about 180 mm/10 and 275 mm/10, and most preferably between 225 mm/10 and 265 mm/10.

50 The yield point of the fat product is also critical to providing the benefits of the present invention. If the yield point is below 500 dynes/cm² (50 Pa) at 70°F (21°C) the product baked from the dough will be too tender to handle. If the yield point is above 10,000 dynes/cm² (1000 Pa) the tenderness benefit is lost. The fat product preferably has a yield point between 3,000 dynes/cm² (300 Pa) and 9,000 dynes/cm² (900 Pa).

55 Flours suitable for use in the practice of this invention include any commonly used for pastry, biscuit, shortcake or shortbread doughs. All-purpose flour, unbleached pastry flour, bread flour and cake flours can all be used.

The amount of water and/or milk which can be used in the doughs of this invention can range as shown above. Higher or lower moisture levels result in doughs which are difficult to handle and form into desired

shapes.

A wide variety of other additives can be incorporated in the dough compositions of this invention. Albumin is frequently added in pastry doughs to prevent soggy crust bottoms in pie pans. It may be desirable to add materials such as milk solids or corn sugar solids to the doughs to promote a golden brown color, and up to about 12%, by weight of flour, may be added to the doughs for this purpose. The doughs may also contain salt or other of the numerous flavoring materials typically used in pastry, biscuit, shortbread and shortcake doughs.

Artificial sweeteners can also be added to the present dough compositions, alone or in combination with bulking agents, to provide an extra caloric reduction benefit. Noncaloric or reduced calorie sweeteners include, but are not limited to, aspartame, saccharin, alitame, thaumatin, dihydrochalcones, cyclamates, steviosides, glycyrrhizins, and synthetic alkoxy aromatics.

Edible preservatives also can be included in the dough compositions in amounts ranging from about 0.03% to about 0.3% by weight. Suitable edible preservatives include calcium propionate, propionic acid, sorbic acid, potassium sorbate and sodium benzoate.

A variety of methods can be used for preparing the doughs of this invention. One convenient method of preparation for pie crusts involves sifting the flour and other dry ingredients together, then adding the fat product to the dry ingredients. Using a pastry blender, for example, the fat product is cut directly into the flour mixture. Water is added in portions and mixed in with a fork, then stirred to form a dough ball. The dough is placed in a pie crust ring and rolled to fill the ring, then placed into a pie plate. Standard baking conditions are used, typically 15 minutes at 425° F (218° C) for pie crusts.

The pastry, biscuit, shortbread and shortcake doughs of this invention are prepared by methods known to the art for making these kinds of doughs. As explained above, it is critical to avoid the intimate mixing of the fat products with the other ingredients of the doughs that occurs during the preparation of cookies, cakes, breads, wafers, etc. By use of low shear mixing as described above, intimate mixing is avoided, and the tenderness benefit of the present invention is achieved. Various methods for preparing pastry and biscuit doughs are described in Modern Encyclopedia of Cooking, cited above. Examples of methods for preparing shortbread and shortcake doughs are described in Joy of Cooking, pp. 713 and 633, respectively. The Bobbs Merrill Co., Inc., Indianapolis/New York, 1975.

Analytical Methods

1. Measurement of Yield Point of the Fat Product:

The yield point is defined as the maximum force required in dynes/cm² (Pa) to initiate deformational flow. A Ferranti Shirley Cone and Plate Viscometer equipped with a 600 gm torque spring is used and the cone specifications are as follows:

Cone Radius (cm)	Cone Angle (Radians)	Range (dynes/cm ²)
3.5	0.006241979	0 - 5775
2.0	0.006062441	0 - 28,500

Either cone may be used.

The test conditions are as follows: 1) The fat product sample and viscometer cone and plate are at 70° F (21° C). 2) A linear shear rate vs. time scan of 0 to 800 sec⁻¹ in 60 seconds is used.

2. Measurement of Penetration of the Fat Product:

Penetration is a measure of the hardness or consistency of a fat. A standard method for measuring penetration of shortening is described in A.O.C.S. Official Method Cc 16-60. However, the method for measuring the penetration of shortenings of the present invention is modified in several respects, for example, by the use of a modified Precision Universal Penetrometer manufactured by Precision Scientific Co., Chicago, Illinois). The penetrating device comprising the shaft and needle (or "cone") are also modified. The same method applies to other fats such as margarines, with appropriate changes in tempering temperatures and amount of time the product is held at 70° F (21° C).

Apparatus:

Constant temperature boxes or room, automatically controlled to maintain the temperature at $85^{\circ}\text{F} \pm 1^{\circ}\text{F}$ ($29.5^{\circ}\text{C} \pm 0.5^{\circ}\text{C}$) and $70^{\circ} \pm 1^{\circ}\text{F}$ ($21.1^{\circ}\text{C} \pm 0.5^{\circ}\text{C}$).

A specially designed needle, shaft and collar weighing 47 grams total, and described below in detail.

A titer thermometer with a temperature range of 20° to 40°C (68°F to 104°F) or 15° to 35°C (59°F to 95°F), reading to 0.1°C (0.2°F).

A sample container, such as a 1 lb. or 3 lb. can.

A Precision Universal Penetrometer, modified as described below.

Specially Designed Shaft and Needle:

10

The penetrating device comprising a shaft and needle (or "cone") are described and illustrated in the A.O.C.S. Official Method. For the present invention, the penetrating device is modified as follows. A 9" (229mm) long hollow steel rod having a $3/16"$ (4.76mm) diameter is used for the shaft. At the end of the shaft is a 2" (50.8mm) long hollow stainless steel needle or cone. The point end of the needle has a $1/32"$ (0.79mm) diameter, and the enlarged end has a $19/32"$ (15.08mm) diameter. A cylindrical metal lid screws into the hollow enlarged end of the needle which can be used for holding weights. A magnesium collar with set screws is positioned around the shaft, $4\frac{1}{4}"$ (108 mm) from the end opposite the needle. The collar is $7/16"$ (11.8 mm) in diameter and $1/8"$ (1.6mm) thick. The penetrating device as a whole, including the collar, must weight 47 grams.

20

Precision Universal Penetrometer Modification:

In placing the needle in the housing of the instrument, the contact finger on the depth gauge is positioned below the collar. The collar is adjusted on the shaft so as to allow the depth gauge its full travel of 520 units. This is accomplished by moving the shaft upward until the cone is about two centimeters below the bottom of the housing and then sliding the collar up against the top of the housing and tightening the set screw. Next the shaft is lowered exactly two centimeters. Using the gauge block adjust the depth gauge contact finger all the way up against the collar using the adjuster screw. Remove the shaft and needle, pin the collar to the shaft and adjust the weight to 47 grams.

30

Conditioning of Sample:

The shortening sample is tempered at $85^{\circ} \pm 1^{\circ}\text{F}$ ($29.5^{\circ} \pm 0.5^{\circ}\text{C}$) for 24 hours and then stored at $70^{\circ} \pm 1^{\circ}\text{F}$ ($21.1^{\circ}\text{C} \pm 0.5^{\circ}\text{C}$) for 24 hours. Other types of fat, margarine for example, may be tempered at other temperatures and held at 70°F (21°C) for a shorter time. Refrigerated fats are generally softened before use in recipes by letting them set at room temperature for about 15 minutes. For the intent of the penetration measurement, penetrations of refrigerated products should be made after the product has first reached 70°F (21°C).

40

Checking the Penetrometer:

Check the needle rise against the 2 cm. gauge-block as follows: With the indicator and depth gauge in the zero position lower the penetrometer head by means of the coarse adjusting screw until the point of the needle just touches the pad block (large diameter block) then lock the screw in this position. Squeeze the clutch trigger and raise the needle to the extreme top position (collar touching the top of the housing). Check the distance between the needle point and pad by placing the 2 cm. gauge block on the pad and carefully passing it under the needle point; the needle point should just clear the 2 cm. gauge block. If the distance so determined is not exactly 2 cm., adjust the depth gauge adjusting screw until the rise and fall of the needle is exactly 2 cm. Set the depth gauge indicator needle to read zero by removing the face plate cover and loosening the knurled nut holding the needle in place. This check should be made once before each series of measurements.

Operation:

55 If possible make all penetrations in a room controlled at $70^{\circ} \pm 1^{\circ}\text{F}$ ($21.1^{\circ} \pm 0.5^{\circ}\text{C}$). If this is impossible, conduct the actual penetration operation immediately after the sample is removed from the 70°F (21.1°C) box. Smooth the surface of the sample by scraping, but do not disturb the contents of the can below about 0.25" of the original surface of the shortening. Immediately place the sample container on

the shelf of the penetrometer, which has been levelled previously by means of the leveling screws in the base. Penetrate each sample at three or more points at least one inch apart and at least one inch from the side of the container, being certain to clean the needle by wiping with a tissue between each penetration. Under no circumstances should the needle be removed from the shaft for cleaning purposes. (Insert the thermometer in the center of the sample up to its immersion mark and record temperature to 0.1 °C (0.2 °F). The temperature at which the penetration test is made should be 21.1 ° ± 0.5 °C [70 ° ± 1 °F]) The average of the penetrations is recorded as the uncorrected penetration. This value is corrected for penetration temperature deviation as follows: a correction of 0.5 points for every 0.1 °C (0.2 °F) above or below 21.1 °C (70 °F) should be made. If below 21.1 °C (70 °F), add the correction; if above, subtract.

Bring the indicator to zero by pulling up on the depth gauge until it stops, then squeeze the clutch trigger and again pull up on the depth gauge until it reaches zero. Release the clutch trigger. If the indicator does not read zero, adjust with the zero setting screw. By means of the coarse adjusting screw, bring the needle down until its point just touches the surface of the sample. Grasp the top of the needle, squeeze the clutch trigger and pull the needle up as far as it will go. This will raise the needle two centimeters above the sample. Release the clutch trigger. Push the depth gauge down as far as it will go.

Release the needle by squeezing the clutch trigger. In operating the clutch trigger, grasp the finger grip firmly with the forefinger, and with the thumb depress the clutch trigger quickly as far down as it will go. Pull the depth gauge up until it stops. Read the dial. The reading is the penetration in tenths of a millimeter (mm/10).

3. Viscosity Measurement of the Sucrose Fatty Acid Ester:

a. Sample Preparation

The sucrose fatty acid ester is heated until it completely melts and is thoroughly mixed. Ten grams of the melted sample is weighed into a pre-heated 20 ml glass vial. The sample is then allowed to recrystallize at 100 °F ± 5 °F (37.8 °C ± 3 °C) for 24 hours. After the 24 hour time period has elapsed, the sample is taken to the viscometer and viscosity is measured.

b. Ferranti-Shirley Viscometer Operation Procedure

A Ferranti-Shirley viscometer equipped with a 600 gm torque spring is used for the viscosity measurement of the sucrose fatty acid ester. A cone is put into place, and the viscometer temperature is adjusted to 100 °F (37.8 °C). The chart recorder is calibrated, and the gap between the cone and plate is set. The cone speed is checked, and the cone and plate temperatures are equilibrated to 100 °F (37.8 °C). The panel controls are set. Sufficient sample is placed between the plate and the cone so that the gap is completely filled. The temperature is allowed to stabilize at 100 °F (37.8 °C) for 30 seconds, and then the cone rotation and recording are started. A rheogram for the sucrose fatty acid ester is recorded and analyzed to determine the viscosity. Viscosity is measured at 10 seconds⁻¹ after 10 minutes of steady shear.

4. Liquid/Solid Stability Measurement of the Sucrose Fatty Acid Ester:

The sucrose fatty acid ester sample is heated until it completely melts and is thoroughly mixed. The sample is then poured into Beckman #344062 4.4 ml. centrifuge tubes. The tubes are immediately transferred to a 100 °F ± 5 °F (37.8 °C ± 3 °C) constant temperature room and allowed to recrystallize undisturbed for 24 hours. The samples are then centrifuged at 60,000 rpm for one hour at 100 °F (37.8 °C) (the centrifuge and centrifuge head is previously equilibrated at 100 °F [37.8 °C]). The force on the samples is 486,000 G's. The liquid/solid stability is then calculated as follows:

Liquid/Solid Stability =

$$\frac{100 \times (\text{total volume of sample} - \text{volume of liquid})}{\text{total volume of sample}}$$

Although the present invention has been described and illustrated with reference to specific examples, it will be understood that modifications and variations can be made without departing from the spirit and

scope of the invention.

Example 1

5 Pie crusts are prepared as follows:

10

Pie Crust Recipe:	
Flour	148 grams
Shortening	98 grams
Water	45 grams
Salt	2.5 grams

15

Method of Preparation

20

25

30

35

40

45

50

55

1. Sift flour and salt together.

2. Add shortening to flour and salt mixture. Using a pastry blender, cut shortening into flour with 20 strokes, scrape bowl 3 times, cut 20 strokes, and scrape bowl 3 times, cut 10 strokes, and scrape bowl 3 times.

3. Add about one-third of the water. Mix with a fork for 10 strokes. Repeat two more times until all the water has been added.

4. Stir mixture using a fork for 30 strokes to form a ball.

5. Tape a sheet of waxed paper to counter top and spread one-half a teaspoon of flour on paper.

6. Use a 3/32 inch (2.38mm) pie crust ring to roll out dough. Place ring on flour-coated paper. Place dough in center of ring and cover with a second piece of waxed paper.

7. Roll dough in all directions to fill the ring.

8. Place rolled dough into a 9 inch (229mm) glass pie plate. Crimp edges and prick dough with a fork.

9. Bake at 425° F (218° C) for 15 minutes.

Different types of shortening are used to make the pie crusts. Several groups of pie crusts are prepared using commercially available shortenings. Other groups are prepared using different kinds of sucrose fatty acid ester-containing shortenings. The sucrose fatty acid ester shortenings have the following composition:

Table 1
Sucrose Fatty Acid Ester Shortenings

<u>Component</u>	<u>Shortening A</u>	<u>Shortening B</u>	<u>Shortening C</u>	<u>Shortening D</u>
Unhardened soybean oil, IV about 130	61.5 (wt.%)	-	-	-
Partially hydrogenated soybean oil, IV about 107	-	58.5 (wt.%)	58.5 (wt.%)	58.5 (wt.%)
Sucrose fatty acid ester made from blend of partially and nearly completely hardened soybean oil methyl esters, IV about 45	29.0	28.0	28.0	28.0
Sucrose fatty acid ester made from nearly completely hardened soybean oil methyl esters, IV about 8	4.0	5.0	5.0	5.0
Emulsifier (mono- and diglycerides)	0.75	4.5	4.5	4.5
Nearly completely hardened palm oil, IV less than 4	$\frac{4.5}{100.0}$	$\frac{4.0}{100.0}$	$\frac{4.0}{100.0}$	$\frac{4.0}{100.0}$
Additional, Vitamin E as d-alpha tocopheryl acetate	-	-	-	1.1 mg/ 1000 g. sucrose fatty acid ester

(Table 1 continued)

Table 1Sucrose Fatty Acid Ester Shortenings

<u>Component</u>	<u>Shortening A</u>	<u>Shortening B</u>	<u>Shortening C</u>	<u>Shortening D</u>
% Nitrogen	20	12	20	12
Penetration (at 70°F [21°C], mm/10)	274	232	193	250
Yield Point (at 70°F [21°C], dynes/cm)	1150	7,900	7,400	4,100

The sucrose fatty acid esters with an IV of about 45 have the following ester distributions:

Shortening A - 91.8% octa, 8.2% hepta, less than 0.1% hexa, and less than 0.2% penta and lower. Shortenings B and C - 81.8% octa, 18.2% hepta, less than 0.1% hexa, and less than 0.2% penta and lower. Shortening D - 84.5% octa, 15.5% hepta, 0.1% hexa, and less than 0.2% penta and lower. The sucrose fatty acid esters with an IV of about 8 all have the following ester distribution: 92.4% octa, 7.6% hepta, less than 0.1% hexa, and less than 0.2% penta and lower.

The blend of sucrose fatty acid esters₁ used to make Shortening D have: a viscosity of 79 poise at 100°F (37.8°C), at 10 sec₁ and at t = 10 minutes; and a liquid/solid stability of 95% at 100°F (37.8°C), at 486,000 g and at 1 hour. The blend of sucrose fatty acid esters used to make shortenings A, B and C have viscosities and liquid/solid stabilities that fall within the ranges of the preferred sucrose fatty acid esters of the present invention.

The pie crusts are taste tested by two methods, expert panels and building panels:

55 Expert Panels

Results from several taste tests using expert panelists show that the sucrose fatty acid ester-containing shortenings make pie crusts that are more tender than pie crusts prepared with conventional triglyceride

shortenings. These panels are conducted with 5-10 judges.

Each test consists of a blind paired comparison of two pie crusts prepared with different shortenings. Panelists sample each pie crust. They are then asked to choose which sample is more tender and to rate the degree to which it is more tender by using the following 5-point scale:

- 5 0 = the products are equally tender
 1 = very slightly more tender
 2 = slightly more tender
 3 = more tender
 4 = a lot more tender

- 10 Each scale unit is referred to as a Panelist Score Unit. A t test analysis is performed on the data to determine if the products are statistically different.

Building Panels

- 15 Building panels are conducted using a much larger base size of panelists. These tests are also blind paired comparison taste tests of two pie crusts prepared with different shortenings.

Panelists taste each product and rate the products on a 9 point liking scale for several attributes, one of which is tenderness. Each product is graded on the following 9-Point Liking Scale for tenderness:

- 20 -4 = dislike the most possible
 -3 = dislike extremely
 -2 = dislike very much
 -1 = dislike
 0 = neutral
 1 = like
 2 = like very much
 3 = like extremely
 4 = like the most possible

The following types of commercially available shortenings are tested:

Commercial Shortening	Type of Shortening
E	premium, all vegetable
F	pre-creamed, part animal fat, part vegetable oils
G	low-cost store brand, part animal fat, part vegetable oils
H	animal fat
I	store brand, all vegetable
J	all vegetable

Results of Expert Panels		
Test Shortening	Control	Tenderness PSU
Commercial F	Commercial E	-0.50
Commercial G	E	-1.30
Sucrose fatty acid ester shortening A	E	2.07 s
Commercial H	E	-1.50
Commercial I	E	1.00
Commercial J	E	-1.00
Sucrose fatty acid ester shortening B	E	1.89 s
Sucrose fatty acid ester shortening C	E	1.60 s
Sucrose fatty acid ester shortening D	E	2.25 s
A negative PSU means the control product is more tender. A positive PSU means the test product is more tender.		
s = significance at 95% confidence		

20 Results of Building Panel

This test is conducted with sucrose fatty acid ester shortening D versus commercial shortening E.

(Base)	Sucrose Fatty Acid Ester Shortening D	(40)	Commercial Shortening E
Overall preference	70	s	30
9-Point Liking Scale			
Tenderness	2.22	s	0.92
Flakiness	2.07	s	1.05
Texture	2.07	s	1.05

The sucrose fatty acid ester shortening pie crust is significantly preferred over the commercial shortening E pie crust for tenderness, flakiness and texture.

Example 2

Puff Pastry is prepared as follows:

40 Ingredients

- 1 cup sucrose fatty acid ester shortening D (see Example 1)
- 1-1/2 cups all-purpose flour
- 1/2 cup sifted cake flour
- 1/4 teaspoon salt
- 3/4 cup cold water

Method of Preparation

Set 2 tablespoons of shortening aside. Place remaining shortening between two pieces of lightly floured waxed paper. Shape shortening into a 5-inch square slightly rounded edges. Wrap in plastic wrap. Refrigerate while making dough.

Combine flour and salt in a bowl. Work reserved 2 tablespoons shortening into flour by rubbing together between the fingers. Add water; stir with a fork until dry ingredients are moistened. Turn dough onto a lightly floured surface; knead 30 times. Cover by inverting bowl over dough. Let rest 10 minutes.

Lightly flour a smooth surface. Roll dough to an 8-inch circle. Mark a 6-inch square within circle of dough. Roll each side of square until dough resembles a flower with 4 petals. (Center of dough will be

thick)

Place chilled shortening square on center square of dough. Fold dough over shortening, one side at a time, bringing edges to center and overlapping slightly. Wrap in plastic wrap, and refrigerate 15 minutes.

Lightly flour surface, and add flour as necessary during following procedure. Place dough, flat side
5 down, on surface. Press rolling pin firmly on dough 7 times, once in center and 3 times above and below center to flatten dough and seal edges. Roll dough into a 14 x 16 inch rectangle, keeping thickness of dough as even as possible, and corners square.

Fold dough in thirds to resemble a folded letter. Give dough a quarter turn to the right. Press with rolling pin to seal edges. Repeat rolling and folding procedure, and refrigerate 15 minutes.

10 Repeat rolling and folding procedure 4 additional times, refrigerating dough for 15 minutes after every two turns. Dough will be rolled and folded a total of 6 turns. Refrigerate 15 minutes or longer before using in a recipe.

Form into pastry and fill as desired (before or after baking). Bake pastry dough at 500° F (260° C) for 5 minutes, reduce the heat to 375° F (191° C) and bake for about 25-35 minutes more.

15

Example 3

Roll biscuits are prepared as follows:

20 Ingredients

220 g flour (all-purpose flour) (2 cups)

65 g sucrose fatty acid ester shortening D of Example 1 (1/3 cup)

13.3 g baking powder (3-1/2 teaspoons)

25 5 g salt (1 teaspoon)

160 g whole milk (2/3 cup)

Method of Preparation

30 1. Cut shortening into sifted flour, baking powder and salt mixture with pastry blender until it looks like coarse cornmeal.

2. Remove one cup of dry mixture to small bowl and blend with milk just enough to hold dough together.

3. Combine remainder of dry mixture with dough.

4. Transfer to floured (1 tablespoon) board.

35 5. Knead lightly about 4 times.

6. Roll dough 1/2 inch thick and cut with floured cutter.

7. Place on cookie sheet and bake at 425° F (218° C) for 10 to 10-1/2 minutes.

Example 4

40

Shortbread is prepared as follows:

Ingredients

45 1 cup sucrose fatty acid ester shortening D (see Example 1)

2 cups sifted all-purpose flour

1/2 cup sifted confectioners' sugar

1/4 teaspoon salt

50 Method of Preparation

Preheat oven to 325° F (163° C). Blend the sifted dry ingredients into the shortening. Pat the stiff dough into an ungreased 9 x 9-inch pan and press edges down. Piece with a fork through the dough every half-inch. Bake 25 to 30 minutes.

55

Example 5

Shortcake is prepared as follows:

Ingredients

- 1-3/4 cups sifted all-purpose flour
 1 teaspoon salt
 5 3 teaspoons double-acting baking powder
 1 tablespoon sugar
 4 to 6 tablespoons sucrose fatty acid ester shortening D (see Example 1)
 3/4 cup milk

10 Method of Preparation

- Preheat oven to 450 °F (232 °C). Cut shortening into sifted dry ingredients, then make a well in the center. Add milk all at once. Stir until the dough is fairly free from the sides of the bowl. Turn the dough onto a lightly floured board. Knead gently and quickly, making about eight to ten folds. Roll with a lightly floured
 15 rolling pin, until the dough has the desired thickness. Cut with a biscuit cutter dipped in a very little flour. Place on an ungreased baking sheet. Bake until lightly browned - 12 to 15 minutes.

Claims

- 20 1. A pastry, biscuit, shortbread or shortcake dough comprising a mixture of
 a) a fat product,
 b) flour, and
 c) a liquid selected from water, milk and mixtures thereof,
 said dough being made by a process employing a low shear method of mixing,
 25 said pastry dough comprising from 20% to 50% of a), from 30% to 70% of b) and from 5% to 30% of
 c);
 said biscuit dough comprising from 5% to 30% of a), from 35% to 60% of b), and from 25% to 45% of
 c);
 said shortbread dough comprising from 25% to 55% of a), from 35% to 60% of b) and from 0% to
 30 20% of c);
 and said shortcake dough comprising from 5% to 30% of a), from 30% to 65% of b) and from 20% to
 50% of c);
 characterised in that
 said fat product comprises from 10% to 100% by weight of sucrose fatty acid esters having at least 4
 35 fatty acid ester groups, wherein each fatty acid group has from 8 to 22 carbon atoms, and from 0% to
 90% of other fat ingredients selected from shortenings, margarines, fats oils and mixtures thereof;
 wherein the fat product has a penetration between 120 mm/10 and 350 mm/10 at 21 °C and a Yield
 Point between 50 Pa and 1000 Pa at 21 °C.
- 40 2. A dough according to Claim 1 characterised in that the sucrose esters have:
 (i) a non-Newtonian plastic rheology at 37.8 °C, in particular a viscosity of not less than 1.5 Pa.s at
 37.8 °C after 10 minutes of steady shear at 10 sec.⁻¹, and
 (ii) a liquid/solid stability of not less than 90% at 37.8 °C.
- 45 3. A dough according to either one of claims 1 & 2 wherein the penetration of the fat product is between
 180 mm/10 and 275 mm/10, preferably between 225 mm/10 and 265 mm/10, at 21 °C.
4. A dough according to any one of claims 1-3 characterised in that the yield point of the fat product is
 between 300 Pa and 900 Pa at 21 °C.
- 50 5. A pastry dough according to any one of claims 1-4 wherein it comprises a pie dough.
6. A baked good made from the dough of any one of claims 1-5.

55 Patentansprüche

1. Konditorwaren-, Feingebäck-, Kuchen-, Torten-, Keks-, Mürbkuchen-, Teekuchen-, Mürbgebäckteig, der
 ein Gemisch aus:



Ingredients

- 1-3/4 cups sifted all-purpose flour
- 1 teaspoon salt
- 5 3 teaspoons double-acting baking powder
- 1 tablespoon sugar
- 4 to 6 tablespoons sucrose fatty acid ester shortening D (see Example 1)
- 3/4 cup milk

10 Method of Preparation

- Preheat oven to 450 °F (232 °C). Cut shortening into sifted dry ingredients, then make a well in the center. Add milk all at once. Stir until the dough is fairly free from the sides of the bowl. Turn the dough onto a lightly floured board. Knead gently and quickly, making about eight to ten folds. Roll with a lightly floured
- 15 rolling pin, until the dough has the desired thickness. Cut with a biscuit cutter dipped in a very little flour. Place on an ungreased baking sheet. Bake until lightly browned - 12 to 15 minutes.

Claims

- 20 1. A pastry, biscuit, shortbread or shortcake dough comprising a mixture of
- a) a fat product,
 - b) flour, and
 - c) a liquid selected from water, milk and mixtures thereof,
- said dough being made by a process employing a low shear method of mixing,
- 25 said pastry dough comprising from 20% to 50% of a), from 30% to 70% of b) and from 5% to 30% of c);
- said biscuit dough comprising from 5% to 30% of a), from 35% to 60% of b), and from 25% to 45% of c);
- said shortbread dough comprising from 25% to 55% of a), from 35% to 60% of b) and from 0% to
- 30 20% of c);
- and said shortcake dough comprising from 5% to 30% of a), from 30% to 65% of b) and from 20% to 50% of c);
- characterised in that
- said fat product comprises from 10% to 100% by weight of sucrose fatty acid esters having at least 4
- 35 fatty acid ester groups, wherein each fatty acid group has from 8 to 22 carbon atoms, and from 0% to 90% of other fat ingredients selected from shortenings, margarines, fats oils and mixtures thereof;
- wherein the fat product has a penetration between 120 mm/10 and 350 mm/10 at 21 °C and a Yield Point between 50 Pa and 1000 Pa at 21 °C.
- 40 2. A dough according to Claim 1 characterised in that the sucrose esters have:
- (i) a non-Newtonian plastic rheology at 37.8 °C, in particular a viscosity of not less than 1.5 Pa.s at 37.8 °C after 10 minutes of steady shear at 10 sec.⁻¹, and
 - (ii) a liquid/solid stability of not less than 90% at 37.8 °C.
- 45 3. A dough according to either one of claims 1 & 2 wherein the penetration of the fat product is between 180 mm/10 and 275 mm/10, preferably between 225 mm/10 and 265 mm/10, at 21 °C.
4. A dough according to any one of claims 1-3 characterised in that the yield point of the fat product is between 300 Pa and 900 Pa at 21 °C.
- 50 5. A pastry dough according to any one of claims 1-4 wherein it comprises a pie dough.
6. A baked good made from the dough of any one of claims 1-5.

55 Patentansprüche

1. Konditorwaren-, Feingebäck-, Kuchen-, Torten-, Keks-, Mürbkuchen-, Teekuchen-, Mürbgebäckteig, der ein Gemisch aus:



a) einem Fettprodukt,

b) Mehl und

c) einer aus Wasser, Milch und Gemischen hievon ausgewählten Flüssigkeit umfaßt,

wobei dieser Teig nach einem Verfahren hergestellt wird, bei welchem ein Mischverfahren unter Verwendung einer niedrigen Scherkraft zur Anwendung gelangt, und wobei

dieser Teig für Konditorwaren, Feingebäck, Kuchen und Torten 20 % bis 50 % von a), 30 % bis 70 % von b) und 5 % bis 30 % von c) enthält;

und wobei dieser Teig für Kekse oder Kleine, weiche Brötchen 5 % bis 30 % von a), 35 % bis 60 % von b) und 25 % bis 45 % von c) enthält;

und wobei dieser Teig für Mürbkuchen, Teekuchen, Mürbgebäck vom Typus "shortbreads" 25 % bis 55 % von a), 35 % bis 60 % von b) und 0 % bis 20 % von c) enthält,

und wobei dieser Teig für Mürbkuchen, Teekuchen, Mürbgebäck vom Typus "shortcakes" 5 % bis 30 % von a), 30 % bis 65 % von b) und 20 % bis 50 % von c) enthält;

dadurch gekennzeichnet, daß

das Fettprodukt 10 Gew.-% bis 100 Gew.-% Saccharosefettsäureester umfaßt, welche wenigstens 4 Fettsäureestergruppen aufweisen, wobei jede Fettsäuregruppe 8 bis 22 Kohlenstoffatome hat, und 0 % bis 90 % von anderen Fettbestandteilen umfaßt, welche aus Backfetten, Margarinen, Fettölen und Gemischen hievon ausgewählt sind;

und wobei das Fettprodukt einen Wert für die Eindringtiefe zwischen 120 mm/10 und 350 mm/10 bei 21 ° C und einen Wert für die Fließgrenze bzw. plastische Verformung zwischen 50 Pa und 1000 Pa bei 21 ° C aufweist.

2. Teig nach Anspruch 1, dadurch gekennzeichnet, daß die Saccharoseester

(i) Nicht-Newtonsche Eigenschaften hinsichtlich des plastischen Strömens bzw. der plastischen Verformbarkeit bei 37,8 ° C, insbesondere eine Viskosität von nicht weniger als 1,5 Pa.s bei 37,8 ° C nach 10 min konstantem Scheren mit 10 sec⁻¹ und

(ii) eine Flüssig-/Fest Stabilität von nicht weniger als 90 % bei 37,8 ° C aufweisen.

3. Teig nach Anspruch 1 oder 2, wobei der Wert des Fettproduktes für die Eindringtiefe zwischen 180 mm/10 und 275 mm/10, vorzugsweise zwischen 225 mm/10 und 265 mm/10, bei 21 ° C ausmacht.

4. Teig nach einem der Ansprüche 1 bis 3, dadurch gekennzeichnet, daß der Wert für die Fließgrenze bzw. plastische Verformung des Fettproduktes zwischen 300 Pa und 900 Pa bei 21 ° C beträgt.

5. Teig für Konditorwaren, Feingebäck, Kuchen und Torten nach einem der Ansprüche 1 bis 4, welcher aus einem Torten- bzw. Kuchenteig besteht.

6. Backwaren, die aus dem Teig nach einem der Ansprüche 1 bis 5 hergestellt worden sind.

Revendications

1. Pâte à pâtisserie, à biscuit, pâte à sablé ou pâte sablée comprenant un mélange

a) d'un produit gras,

b) de farine, et

c) d'un liquide choisi parmi l'eau, le lait et leurs mélanges,

ladite pâte étant fabriquée par un procédé employant un procédé de malaxage à faible cisaillement,

ladite pâte à pâtisserie comprenant de 20% à 50% de a), de 30% à 70% de b) et de 5% à 30% de c);

ladite pâte à biscuit comprenant de 5% à 30% de a), de 35% à 60% de b) et de 25% à 45% de c);

ladite pâte à sablé comprenant de 25% à 55% de a), de 35% à 60% de b) et de 0% à 20% de c);

et ladite pâte sablée comprenant de 5% à 30% de a), de 30% à 65% de b) et de 20% à 50% de c);

caractérisée en ce que

ledit produit gras comprend de 10% à 100% en poids d'esters d'acide gras et de saccharose

comportant au moins 4 groupes esters d'acides gras, dans lesquels chaque groupe acide gras possède

de 8 à 22 atomes de carbone, et de 0% à 90% d'autres ingrédients gras choisis parmi les graisses, les

margarines, les matières grasses, les huiles et leurs mélanges;

dans laquelle le produit gras a une pénétration comprise entre 120 mm/10 et 350 mm/10 à 21 ° C et un

seuil d'écoulement compris entre 50 Pa et 1000 Pa à 21 ° C.



2. Pâte selon la revendication 1, caractérisée en ce que les esters de saccharose possèdent :
- (i) une rhéologie plastique non newtonienne à 37,8 °C, en particulier une viscosité d'au moins 1,5 Pa.s à 37,8 °C au bout de 10 minutes de cisaillement régulier à 10 s⁻¹, et
 - (ii) une stabilité liquide/solide d'au moins 90% à 37,8 °C.
- 5
3. Pâte selon l'une quelconque des revendications 1 et 2, dans laquelle la pénétration du produit gras est comprise entre 180 mm/10 et 275 mm/10, de préférence entre 225 mm/10 et 265 mm/10, à 21 °C.
- 10
4. Pâte selon l'une quelconque des revendications 1-3, caractérisée en ce que le seuil d'écoulement du produit gras est compris entre 300 Pa et 900 Pa à 21 °C.
5. Pâte à pâtisserie selon l'une quelconque des revendications 1-4, qui comprend une pâte à tourte.
6. Pâtisserie faite à partir de la pâte selon l'une quelconque des revendications 1-5.

15

20

25

30

35

40

45

50

55