

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization
International Bureau



G00002

(43) International Publication Date
29 August 2002 (29.08.2002)

PCT

(10) International Publication Number
WO 02/066580 A1

(51) International Patent Classification⁷: **C10G 45/02**,
45/32, 65/04, 65/16

(21) International Application Number: PCT/US02/00304

(22) International Filing Date: 8 January 2002 (08.01.2002)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
09/785,909 16 February 2001 (16.02.2001) US

(71) Applicant: **CATALYTIC DISTILLATION TECHNOLOGIES** [US/US]; 10100 Bay Area Boulevard, Pasadena, TX 77507 (US).

(72) Inventors: **PODREBARAC, Gary, G.**; 10100 Bay Area Boulevard, Pasadena, TX 77507 (US). **GILDERT, Gary, R.**; 14507 Windy Ridge Lane, Houston, TX 77062 (US).

(74) Agent: **JOHNSON, Kenneth, H.**; P.O. Box 630708, Houston, TX 77263 (US).

(81) Designated States (*national*): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, TZ, UA, UG, UZ, VN, YU, ZA, ZW.

(84) Designated States (*regional*): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:


— with international search report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.



162162

(54) Title: PROCESS FOR SULFUR REDUCTION IN NAPHTHA STREAMS



(57) **Abstract:** A process for concurrently fractionating and treating of a full range naphtha stream. The full boiling range naphtha stream is first subjected to simultaneous thioetherification or selective hydrogenation and splitting into a light boiling range naphtha, an intermediate boiling range naphtha and a heavy boiling range naphtha. The intermediate boiling range naphtha containing thiophene and thiophene boiling range mercaptans, dienes or mixtures may be subjected to a second thioetherification or selective hydrogenation, depending on its make-up, and then passed on to a polishing hydrodesulfurization reactor or the entire intermediate stream may be passed directly to the polishing reactor. The bottoms are subjected to concurrent hydrodesulfurization and fractional distillation and the combined overheads and bottoms are fed to the polishing reactor. The effluent from the polishing reactor may be combined with the light boiling range naphtha to produce a new full boiling range naphtha containing substantially less total sulfur than the original feed. The object being to meet higher standards for sulfur removal, by treating the components of the naphtha feed with the process that preserves the olefinic while most expediently removing the sulfur compounds.

WO 02/066580 A1