

Description

BACKGROUND OF THE INVENTION

Field of the Invention

The field of the invention is that of nursing bottles for infants.

Description of the Prior Art

With respect to known prior art, reference is made to US-A- Nos. 357 439; 484 811; 1 056 113; 2 514 744; 3 145 867; to DE-C-249 076; and to FR-A- Nos. 1 464 902 and 807 247.

The devices of the prior art are subject to certain deficiencies and drawbacks constituting problems which have not been met and for which a solution has been needed. The prior art lacks capabilities and advantages to be identified hereinafter.

Typically, in the nursing of human infants, the nursing bottle may be held in hand of a person, such as the mother, or in fact, may be held in the hands of the infant itself. In either situation, there are disadvantages, whether the nipple at the end of the bottle is axially aligned with the axis of the bottle or whether the bottle has a neck carrying the nipple, the axis of which is inclined relative to axis of the body of the bottle.

If the infant is in a lying down position and holding the bottle itself, typically the body of the bottle has to be held in an inclined position upwardly from the infant's body in order for gravity to cause the contents of the bottle to feed to the nipple and to accommodate the position of the nipple to the infant's mouth. This is disadvantageous from the standpoint of being fatiguing for the infant or because of the inability of the infant to hold it in position.

The disadvantage just referred to is further aggravated in situations where an infant is in a sitting position, such as in a high chair, and whether the infant is holding the bottle itself or it is being held by another person. In either situation, it is difficult to hold the bottle in a proper feeding position, and it is tiring and fatiguing in either event, whether held by the infant or another person.

In either of the situations referred to, the drawback is present that the infant may take in an excessive amount of air while sucking the milk through the nipple. This can result from the position of the bottle and the level of milk in the bottle which may drop low enough so as to allow air, as well as milk, to enter through the nipple into the infant's mouth. That is, while the infant is nursing, the level in the bottle of course will drop, and then depending on the actual position of the bottle, the infant may be taking in air through the nipple, as

well as milk.

It is particularly significant that when the infant is being nursed in a sitting position, such as in the lap of an adult or in a highchair, typically it is necessary that the baby's head be thrown back in order to accommodate the position of the nipple to the infant's mouth. This is a stressful position for the muscles of the infant's throat and neck and may present difficulty to the infant in swallowing.

The foregoing referred-to drawbacks and disadvantages of prior art nursing bottles have not been met in the prior art, and it is the object of the invention herein, a preferred form of which is described in detail hereinafter, to overcome the said disadvantages and drawbacks and to provide significant capabilities not previously available.

The present invention provides a nursing bottle adapted for nursing an infant in different positions, the bottle comprising a main body having an open upper end and a closed lower end, the upper end having a nursing nipple fitted on to it, the body having a configuration including a bend at a position in the upper half of the body's length, so that the body is divided into an upper portion and a lower portion, the upper portion being shorter than the lower portion, the respective axes of said portions forming an acute angle with each other, characterized in that said upper and lower portions of the bottle's body are substantially uniform in diameter so as to form two distinct cylinders having the same diameter and matching together on a single plane along a circle whereat said bend takes place with a sharp change of direction of the body from one cylinder to the other, and in that said plane is at an angle to the axis of the upper portion and also at an angle the the axis of the lower portion.

In a preferred form, the nursing bottle of the herein invention is made of glass and the upper and lower portions are circular in cross-section. At the top or upper end, it is configured to receive a standard nursing nipple which may be of a type that engages the nursing bottle in threaded relationship, or it may be of a type that is attached by friction.

The angle between the top part of the body of the bottle and the lower part may be referred to as a bend in the bottle, and the character of this bend is that the bend constitutes a circular bend which is between a normal to the axis of the lower or longer part of the body and a normal to the axis of the upper part of the body. The exact angular position of the circular bend is not critical.

An advantage of a nursing bottle as in the foregoing is that it is capable of being usable in positions which adapt to, and are advantageous relative to, the position of the infant while nursing, whether the infant is lying down or being held in a sitting position.

It is also adapted to have the center of gravity of the bottle and its contents positioned to accommodate utilization of the bottle, whether the infant being nursed is lying down or is in a sitting position.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 is an elevational view of a preferred form of the invention;

FIG. 2 is a pictorial view illustrating utilization of the form of the invention shown in FIG. 1;

FIG. 3 is a side elevational view of a modified form of the invention wherein the bend in the body of the bottle is at a slightly different position; and

FIG. 4 is a pictorial view illustrating utilization of the form of the invention shown in FIG. 2.

DESCRIPTION OF A PREFERRED EMBODIMENT AND BEST MODE OF PRACTICE

Referring to FIG. 1, this figure shows a preferred form of the invention, and FIG. 2 shows its position in usage with an infant lying on its back. The bottle is identified by the numeral 10; preferably, it may be made of glass, having a uniform diameter. It has a bottom end 12 and an upper end 14. At the upper end is a nipple member 16 which may be of typical construction. As shown, it has a circular part which engages the upper end of the bottle 10 in threaded relationship, the nipple having a flexible nipple part 28 which the infant sucks.

At an intermediate part of the bottle, there is an angular bend in it, as identified by the numeral 26. In other words, the axis of the lower part of the body is at an angle to the upper part of the body, which angle is an acute angle which might be, for example, the angle as shown in the drawings.

The bend in the body of the bottle forms a circle around the bottle which, in the form of the invention shown, is identified by the numeral 26, the bend being at an angle to the axis of the main part of the body and also at an angle to the axis of the upper part of the body.

Preferably, the bend in the body of the bottle is nearer to the upper end than to the bottom end, and preferably, the position of the bend in the bottle is approximately in the range represented by the forms of the invention shown in FIGS. 1 and 3, or near this range.

FIG. 2 illustrates utilization of the improved bottle as shown in FIG. 1. In this view, the infant is lying on its back and holding the bottle itself. As can be seen, the lower part of the bottle is in a horizontal position. The upper part of the bottle forwardly of the angle in the bottle is in a position to accommodate the nipple to the infant's mouth.

As can be seen, the infant does not have to hold the weight of the bottle which can be resting directly on the infant. Thus, the infant is not subjected to the stress and fatigue of having to hold the weight of the bottle, and its head and mouth can remain in a perfectly normal position while the nipple continues to be accommodated to the position of the infant's mouth.

With respect to the level of the liquid, such as milk in the bottle, as can be seen in FIG. 1, the level will continue to cover the entrance to the nipple even while the level diminishes to a relatively low point.

Referring to FIG. 3 of the drawings, this figure shows a slightly modified form of the invention. A manner of utilization of this form of the invention is shown in FIG. 4. The bottle in this form of the invention is identified at 10', and parts that are the same as parts in the previous embodiment are identified by the same reference numerals. The bottle is shown in FIG. 3 in substantially the position it would be in when nursing an infant in a sitting position while being held by an adult as shown in FIG. 4 or while the infant is sitting in a highchair.

In this form of the invention, the bend in the bottle, that is, the angle in it, is spaced slightly further away from the top end of the bottle. The circle represented by the bend in the bottle is identified by the numeral 26'. As in the previous embodiment, this circle representing the bend is between a normal to the axis of the lower part of the body and a normal to the axis of the upper part of the body. In the form of the invention shown, it is in a position spaced farther from the top end of the bottle than it is in FIG. 1.

FIG. 4 illustrates utilization of the bottle of FIG. 3. As may be seen, because of the configuration of the bottle, when nursing the infant does not have to be held at such a steep, that is, acute, angle which would require the infant's head to be thrown backwardly or into a rearward position which is uncomfortable, both to the infant and to the person holding the bottle. Also, the purpose is accomplished that the liquid, such as milk, stays in contact with the entrance to the nipple so that air does not reach the baby's mouth along with the milk. Thus, the need for "burping" the infant after each feeding is eliminated or at least minimized.

From the foregoing, those skilled in the art will readily understand and appreciate the nature and construction of the invention and the manner in which it realizes and accomplishes all of the objects as set forth in the foregoing.

The foregoing disclosure is representative of preferred forms of the invention and is to be interpreted in an illustrative rather than a limiting sense, the invention to be accorded the full scope of the

claims appended hereto.

Claims

1. A nursing bottle (10) adapted for nursing an infant in different positions, the bottle comprising a main body having an open upper end (14) and a closed lower end (72), the upper end having a nursing nipple (28) fitted on to it, the body having a configuration including a bend (26,26') at a position in the upper half of the body's length, so that the body is divided into an upper portion and a lower portion, the upper portion being shorter than the lower portion, the respective axes of said portions forming an acute angle with each other, characterized in that said upper and lower portions of the bottle's body are substantially uniform in diameter so as to form two distinct cylinders having the same diameter and matching together on a single plane along a circle (26) whereat said bend takes place with a sharp change of direction of the body from one cylinder to the other, and in that said plane is at an angle to the axis of the upper portion and also at an angle to the axis of the lower portion. 5 10 15 20 25 30
2. A nursing bottle as in claim 1, the axis of the nipple coinciding with the axis of the upper part of the body. 35
3. A nursing bottle as in claim 1, wherein the bottle may be held with either the part below the angle in a substantially horizontal position or with the part above the angle in a substantially horizontal position in either position, the nursing nipple being at a lower level than the part below the angle so that the required amount of tipping of the bottle is reduced. 40
4. A nursing bottle as in claim 1 wherein the angle of said portions is about 30°. 45

Patentansprüche

1. Saugflasche (10) zum Füttern eines Kleinkindes in verschiedenen Stellungen, wobei die Flasche einen Hauptkörper mit einem offenen oberen Ende (14) und einem geschlossenen unteren Ende (72) aufweist, wobei das obere Ende einen Saugnuckel (28) aufweist, der darauf aufgepaßt ist, wobei der Körper eine Form hat, die eine Krümmung (26, 26') an einer Stelle der oberen Hälfte der Länge des Körpers einschließt, so daß der Körper in einen oberen Abschnitt und einen unteren Abschnitt unterteilt ist, wobei der obere Abschnitt kürzer 50 55

ist als der untere Abschnitt, wobei die entsprechenden Achsen der Abschnitte einen spitzen Winkel zueinander bilden, dadurch gekennzeichnet, daß der obere und der untere Abschnitt des Körpers der Flasche im wesentlichen einheitlichen Durchmesser haben, so daß sie zwei einzelne Zylinder mit dem gleichen Durchmesser bilden, die an einer Ebene entlang eines Kreises (26) aneinanderpassen, an dem die Krümmung verläuft, wobei eine steile Richtungsänderung des Körpers von einem Zylinder zum anderen vorhanden ist, und dadurch, daß sich die Ebene in einem Winkel zur Achse des oberen Abschnitts und ebenfalls in einem Winkel zur Achse des unteren Abschnitts befindet.

2. Saugflasche nach Anspruch 1, wobei die Achse des Nuckels mit der Achse des oberen Teils des Körpers zusammenfällt. 20
3. Saugflasche nach Anspruch 1, wobei die Flasche entweder so gehalten werden kann, daß sich der Teil unterhalb des Winkels in einer im wesentlichen horizontalen Position befindet, oder so, daß sich der Teil oberhalb des Winkels in einer im wesentlichen horizontalen Position befindet, wobei sich in beiden Positionen der Saugnuckel in einer niedrigeren Höhe befindet als der Teil unterhalb des Winkels, so daß das Maß verringert wird, in dem die Flasche schräg gehalten werden muß. 25 30 35
4. Saugflasche nach Anspruch 1, wobei der Winkel der Abschnitte ungefähr 30° beträgt. 40

Revendications

1. Biberon (10) conçu pour allaiter un nourrisson dans différentes positions, le biberon comprenant un corps principal présentant une extrémité supérieure ouverte (14) et une extrémité inférieure fermée (72), l'extrémité supérieure portant une tétine (28) ajustée, le corps ayant une configuration comprenant un coude (26, 26') à une position de la moitié supérieure de la longueur du corps, de sorte que le corps est divisé en une partie supérieure et une partie inférieure, la partie supérieure étant plus courte que la partie inférieure, les axes respectifs desdites parties formant entre eux un angle aigu, caractérisé en ce que lesdites parties supérieure et inférieure du corps du biberon ont un diamètre sensiblement uniforme de façon à former deux cylindres distincts ayant le même diamètre et s'ajustant sur un seul plan suivant un cercle (26) où ledit coude s'effectue avec un changement brusque de direction du 45 50 55



claims appended hereto.

Claims

1. A nursing bottle (10) adapted for nursing an infant in different positions, the bottle comprising a main body having an open upper end (14) and a closed lower end (72), the upper end having a nursing nipple (28) fitted on to it, the body having a configuration including a bend (26,26') at a position in the upper half of the body's length, so that the body is divided into an upper portion and a lower portion, the upper portion being shorter than the lower portion, the respective axes of said portions forming an acute angle with each other, characterized in that said upper and lower portions of the bottle's body are substantially uniform in diameter so as to form two distinct cylinders having the same diameter and matching together on a single plane along a circle (26) whereat said bend takes place with a sharp change of direction of the body from one cylinder to the other, and in that said plane is at an angle to the axis of the upper portion and also at an angle to the axis of the lower portion. 5 10 15
2. A nursing bottle as in claim 1, the axis of the nipple coinciding with the axis of the upper part of the body. 20 30
3. A nursing bottle as in claim 1, wherein the bottle may be held with either the part below the angle in a substantially horizontal position or with the part above the angle in a substantially horizontal position in either position, the nursing nipple being at a lower level than the part below the angle so that the required amount of tipping of the bottle is reduced. 35 40
4. A nursing bottle as in claim 1 wherein the angle of said portions is about 30°. 45

Patentansprüche

1. Saugflasche (10) zum Füttern eines Kleinkindes in verschiedenen Stellungen, wobei die Flasche einen Hauptkörper mit einem offenen oberen Ende (14) und einem geschlossenen unteren Ende (72) aufweist, wobei das obere Ende einen Saugnuckel (28) aufweist, der darauf aufgepaßt ist, wobei der Körper eine Form hat, die eine Krümmung (26, 26') an einer Stelle der oberen Hälfte der Länge des Körpers einschließt, so daß der Körper in einen oberen Abschnitt und einen unteren Abschnitt unterteilt ist, wobei der obere Abschnitt kürzer 50 55

ist als der untere Abschnitt, wobei die entsprechenden Achsen der Abschnitte einen spitzen Winkel zueinander bilden, dadurch gekennzeichnet, daß der obere und der untere Abschnitt des Körpers der Flasche im wesentlichen einheitlichen Durchmesser haben, so daß sie zwei einzelne Zylinder mit dem gleichen Durchmesser bilden, die an einer Ebene entlang eines Kreises (26) aneinanderpassen, an dem die Krümmung verläuft, wobei eine steile Richtungsänderung des Körpers von einem Zylinder zum anderen vorhanden ist, und dadurch, daß sich die Ebene in einem Winkel zur Achse des oberen Abschnitts und ebenfalls in einem Winkel zur Achse des unteren Abschnitts befindet.

2. Saugflasche nach Anspruch 1, wobei die Achse des Nuckels mit der Achse des oberen Teils des Körpers zusammenfällt.
3. Saugflasche nach Anspruch 1, wobei die Flasche entweder so gehalten werden kann, daß sich der Teil unterhalb des Winkels in einer im wesentlichen horizontalen Position befindet, oder so, daß sich der Teil oberhalb des Winkels in einer im wesentlichen horizontalen Position befindet, wobei sich in beiden Positionen der Saugnuckel in einer niedrigeren Höhe befindet als der Teil unterhalb des Winkels, so daß das Maß verringert wird, in dem die Flasche schräg gehalten werden muß.
4. Saugflasche nach Anspruch 1, wobei der Winkel der Abschnitte ungefähr 30° beträgt.

Revendications

1. Biberon (10) conçu pour allaiter un nourrisson dans différentes positions, le biberon comprenant un corps principal présentant une extrémité supérieure ouverte (14) et une extrémité inférieure fermée (72), l'extrémité supérieure portant une tétine (28) ajustée, le corps ayant une configuration comprenant un coude (26, 26') à une position de la moitié supérieure de la longueur du corps, de sorte que le corps est divisé en une partie supérieure et une partie inférieure, la partie supérieure étant plus courte que la partie inférieure, les axes respectifs desdites parties formant entre eux un angle aigu, caractérisé en ce que lesdites parties supérieure et inférieure du corps du biberon ont un diamètre sensiblement uniforme de façon à former deux cylindres distincts ayant le même diamètre et s'ajustant sur un seul plan suivant un cercle (26) où ledit coude s'effectue avec un changement brusque de direction du



corps d'un cylindre à l'autre et en ce que ledit plan forme un angle avec l'axe de la partie supérieure et également avec l'axe de la partie inférieure.

2. Biberon selon la revendication 1, l'axe de la tétine coïncidant avec l'axe de la partie supérieure du corps.

3. Biberon selon la revendication 1, dans lequel le biberon peut être maintenu avec soit la partie en dessous de l'angle dans une position sensiblement horizontale, soit la partie au-dessus de l'angle dans une position sensiblement horizontale dans l'une ou l'autre position, la tétine étant à un niveau inférieur à celui de la partie en dessous de l'angle, de sorte que la quantité d'inclinaison requise pour le biberon est diminuée.

4. Biberon selon la revendication 1, dans lequel l'angle desdites parties est d'environ 30°.

5

10

15

20

25

30

35

40

45

50

55

5