

Description

BACKGROUND OF THE INVENTION

The present invention relates to electrical connectors and, more particularly, to the electrical interconnection of a multi-row connector to a printed circuit board to provide controlled impedance paths for each circuit interconnection.

Various systems have been used to mate electrical connectors to printed circuit boards or other circuit bearing substrates. In the general case, the connector includes receptacles having pin-like 'tail' portions of selected length that are designed to be electrically connected with conductive pads or traces on the printed circuit board. The tail portions can extend linearly from the connectors, that is, along a line co-incident with its receptacle or at an angle relative to its receptacle. Where the connector is mounted on one of the flat sides of the circuit board, the tail portions pass through respective holes in the circuit board and are soldered to conductive pads on the opposite side of the circuit board. Since the connector is mounted on the flat surface of the circuit board, the number of conductive pads on the circuit board can readily match the number of tail portions of the connector. The soldering of the tail portions effects electrical connection and, in many cases, provides an adequate mechanical connection to affix the connector to the circuit board. Where necessary, mechanical fasteners, including threaded fasteners, clamps, brackets, frames, and the like, can be used to assist in effecting the mechanical attachment. The requirements for an edge-mounted connector are somewhat different in that the surface area available at the edge of the circuit board represents a constraint on the total number of circuit board traces and pads that can be provided for interconnection with the connector. The surface-area limitation is exacerbated where the edge-mounted connector is of the multi-row type, that is, parallel rows of pins or receptacles that form a matrix of interconnects. For example, U.S. Patent 4,659,155 to Walkup et al. discloses an edge connector for a circuit board having two rows of receptacles on each side of the circuit board in which equal length tail portions extend from the connector to respective contact pads aligned in a single row on the circuit board. While the Walkup et al. design represents a reasonable solution, this design is limited in the sense that a larger number of rows will increase the number of contact pads in the single row of contacts on the circuit board and increase the difficulty of assembly of the connector to the circuit board and make inspection of the various contacts more difficult.

One of the trends in electronic systems is the development of high speed digital circuits with a requirement for a relatively large number of circuit interconnects between circuit boards. In order to accommo-

date the requirement for a quantitatively large number of circuit interconnects, high pin count connector systems have been developed which locate the contact devices, either pins or receptacles, on relatively close centers, for example, 0.100 inches (2.54 mm.), in a multi-row matrix so that several hundred or more circuit connects are possible per connector. The tail portions of the connector can be connected to conductive traces on the printed circuit board by a flexible circuit fabricated from laminated Kapton layers with conductive traces extending between connection fields for the 'tail' portion of the receptacles of the connector and connection fields for the conductive pads or traces on the circuit board. While flexible circuit assemblies represent a reasonable design approach to the electrical interconnection of the connector and its circuit board, the closely adjacent conductive traces in high pin count applications provide different impedances, including resistive, capacitive, and inductive constituents, for the various circuits. While these impedance differences do not cause performance problems at low-frequencies, the relative impedance differences between circuits can cause problems at relatively high digital speeds, especially where the interconnects are part of a digital bus application in which all pulses must travel in a synchronous or quasi-synchronous manner with minimal relative degradation because of the impedance characteristics of the flexible circuit.

SUMMARY OF THE INVENTION

It is an object of the present invention to provide a connection interface or system for electrically mating electrical connectors to a circuit board in which the resistance and/or impedance presented by each electrical interconnect is substantially the same for all of the interconnects.

It is a further object of the present invention to provide a connection interface or system for electrically mating high pin count multi-row electrical connectors to a circuit board in which the circuit path length for each electrical interconnect is substantially the same for all of the interconnects.

In view of these objects, and others, the present invention provides a connection interface for electrically connecting a multi-row connector or header to a circuit bearing substrate; said interface comprising a flex circuit having a first field of connection areas for connection to a corresponding tail-portion field associated with the connector; another field associated with the circuit bearing substrate and electrically conductive traces each extending between corresponding ones of the connection areas of the first connection field and the connection areas of the other connection field, each of said traces presenting substantially the same impedance between its connection areas as the other of the traces.

In accordance with the invention a connection interface for electrically mating a multi-row connector with a printed circuit board can be made in such a way that the impedance of the interconnect circuitry, especially the resistance, is the same for each of the circuit paths.

The flex circuit can be in the form of a flexible polyimide substrate and cover or first and second layers and the conductive traces leading between the connection fields at the opposite ends of the traces for electrical connection to tail portions of connection devices on the connector and the conductive pads or pins on the circuit board.

The conductive traces can be made all of equal length to provide equal resistance paths for each of the circuit interconnects. For a multi-row connector having N rows of interconnects, i.e., either receptacles or pins, the flexible circuit is provided with N sets of conductive traces with each of the N sets having trace lengths that are equal to one another within the set and to the trace lengths of the other of the N sets of conductive traces.

The present invention advantageously provides an impedance controlled interface for effecting an electrical connection between a connector and its circuit board in such a way that the resistance and related impedance characteristics are substantially the same for each circuit interconnect.

Other features objects and further scope of applicability of the present invention will become apparent from the detailed description to follow, taken in conjunction with the accompanying drawings, in which like parts are designated by like reference characters.

BRIEF DESCRIPTION OF THE DRAWING

FIG. 1 is a partial, rear perspective view of a high pin count connector mounted to the edge of a printed circuit board with terminal pins of the connector connected to respective conductive pads on the printed circuit board by a flex circuit in accordance with the present invention;

FIG. 2 is a partial, cutaway, perspective view of the high pin count connector of FIG. 1 from the side opposite that shown in FIG. 1;

FIG. 3 is a side view of an exemplary flex circuit for interconnecting the terminal pins of the connector and the connection pads of the circuit board of FIGS. 1 and 2;

FIG. 3A is a detailed side view of a tail portion of a terminal pin extending through the flex circuit of FIG. 3 taken along line 3A-3A of FIG. 3;

FIG. 3B is a detailed side view of an exemplary interconnection between a conductive trace of the flex circuit and a conductive pad on a circuit board taken along line 3B-3B of FIG. 3;

FIG. 4 is a partial flat development view of the flex

circuit used in FIGS. 1-3 to effect an electrical interconnection between terminal pins on the connector and corresponding conductive pads on the printed circuit board and illustrating repeating sets of interdigitated conductive trace patterns; FIG. 5 is a partial flat development view of the matrix pattern of the conductive end portions of the flex circuit of FIG. 4;

FIG. 6 is an enlarged view of a single set of conductive traces of the flex circuit of FIG. 4; and FIG. 7 is a side view of a dual flex circuit application in which one flex circuit is mounted on one side of the circuit board and the other is mounted on the opposite side.

DESCRIPTION OF THE PREFERRED EMBODIMENT

An electrical connector, generally indicated by the reference character 10, is shown mounted to the edge of a printed circuit board 12 in FIGS. 1 and 2 with receptacles of the connector 10 interconnected with respective conductive pads P (represented in exemplary fashion in FIG. 1 by the reference character "P") on the circuit board 12 by flex circuits 14 and 14' having interconnects, described more fully below, which present substantially the same circuit impedance to each interconnect pair.

The connector 10 includes a body portion 16 molded from a rigid plastic and includes, as shown in FIG. 2, an upper set of entryways 18 arranged in a three-row rectangular pattern and a lower set of similarly arranged entryways 18. In the illustrated embodiment, the entryways 18 are formed on 0.100 inch (2.54 mm) centers with each entryway 18 leading to an internal passage (unnumbered) in which a multi-beam receptacle, generally indicated at 20, is retained in place to define an upper set of receptacles 20 and another, lower set of receptacles 20. Each receptacle 20 includes a forwardly facing portion for accepting a pin from a mating plug (not shown) and a rearwardly extending tail portion 22 that extends rearwardly of the molded body 16 and defines a connection terminal as described below. In the preferred embodiment, the connector 10 is a high pin count connector marketed under the HPC-XXXX series designation by DuPont Electronics of New Cumberland, PA 17070. The upper set of receptacles 20 are connected by the flex circuit 14 to corresponding connection pads P on the upper side of the circuit board 12 and the lower set of receptacles 20 are connected by the flex circuit 14' to connection pads P on the lower side (not shown) of the circuit board 12.

The body 16 of the connector 10 is provided with a slot 24 (FIG. 2) on the its rear side for accepting the edge of the circuit board 12. The slot 24 is provided with a width dimension 'X' that is sufficiently large to accommodate the expected range of circuit board

thicknesses. For most applications and as shown in FIG. 2, the width dimension 'X' is larger than the thickness dimension of the circuit board 12 to provide a clearance space. As shown in FIG. 1, the connector 10 is attached to the circuit board 12 using a fastener (unnumbered) cooperating with an integrally molded bracket at the ends of the connector 10. While receptacles 20 have been defined as part of the illustrated embodiment, as can be appreciated, cylindrical or squared-sided pins (not shown) can likewise be provided with appropriate modification of the body 16.

As represented in the side view of the flex circuit 14 in FIG. 3, the flex circuits 14 and 14' each include first and second laminae 26 and 28 that constrain a pattern of electrically conductive traces (not shown in FIG. 3) between the two laminae to effect connection between the connector 10 and the connection pads P on the printed circuit board 12. The laminae 26 and 28 are preferably preshaped to conform to the particular application, and, for the application shown in FIGS. 1 and 2, the laminae 26 and 28 are shaped at a right angle to permit convenient installation, with the vertical portion shown in FIG. 3 connected at positions A, B, and C to the three rows of tail portions 22 and the horizontal portion connected at positions A', B', and C' to three rows of connection pads P on the circuit board 12 as described below. As shown in the enlarged detail of FIG. 3A, individual conductive traces, as represented in general form by the reference character 30, are connected to their respective tail portions 22 by providing apertures 32 through the lamina 28 and the conductive trace 30 and through which the tail portion 22 of the receptacle 20 extends. The lamina 26 includes an enlarged opening 34 that exposes the conductive area at the end of the trace 30 in the area immediately adjacent the tail portion 22. Electrical and mechanical connection is effected by soldering, represented at 36, in the usual manner. The connection to the printed circuit board 12 is a function of the type of interconnection desired. In the illustrated embodiment and as shown in FIG. 3B, the conductive traces 30 of the flex circuit 14 are connected to their connection pads P on the circuit board 12 by providing an aperture 32' in the lamina 26 and an enlarged opening 34' in the lamina 28 with the enlarged opening 34' facing its connection pad P. Soldering, as indicated by the reference character 38, is effected between the connection pad P and the conductive trace 30 to provide the electrical connection. Where the circuit board 12 is provided with terminal pins (not shown), the configuration of FIG. 3A can be used to effect connection with the circuit board 12.

As shown in the partial, flat development view of the flex circuit 14 in FIG. 4, a recurring set of interdigitated conductive traces 30 are provided to effect connection from the connector 10 to the printed circuit board 12 with the opposite ends of the various traces 30 defining connection fields for connecting, respec-

tively, the tail portions 22 extending from the connector 10 and the connection pads P on the circuit board 12. As also shown in the enlarged view of FIG. 6, representing a single set of conductive traces 30, the upper ends of the conductive traces 30 are arranged in the rows A, B, and C that correspond to the spacing of the tail portions 22 of the receptacles 20, as shown in FIG. 3, and, in an analogous manner, the lower ends of the conductive traces are likewise located in rows A', B', and C' to define a set of traces A-A', B-B', and C-C' that are repeated on a recurring basis as a function of the total number of interconnects that must be effected. In FIG. 6, the traces have been redesignated as trace T1 connecting ends A and A', trace T2 connecting ends B and B', and trace T3 connecting ends C and C'. As shown, each of the traces is defined by at least first and second trace sub-portions in which the sum of the path lengths for the various trace sub-portions is equal. More specifically, the trace T1 is defined by trace sub-portions T1₁, T1₂, and T1₃; the trace T2 is defined by trace sub-portions T2₁ and T2₂; and the trace T3 is defined by trace sub-portions T3₁ and T3₂. The sums of the various trace sub-portions for each of the traces T1, T2, and T3 are equal, that is, for the illustrated embodiment, the following relationship holds:

$$(T1_1) + (T1_2) + (T1_3) = (T2_1) + (T2_2) = (T3_1) + (T3_2)$$

By providing equal length traces T1, T2, and T3, the resistance presented to the various signals is substantially the same and, additionally, the impedance of any interconnect is substantially the same as that of any other interconnect to provide a connection system well suited for digital bus applications. In addition to providing equal length traces T1, T2, and T3, equal length portions of the traces T1, T2, and T3 are positioned adjacent one another to provide equal capacitive/inductive interactions. In the embodiment illustrated in FIG. 6, trace sub-portions T1₃, a part of sub-portion T2₁, and sub-portion T3₁ are positioned adjacent one another. Since the traces T1, T2, and T3 of FIG. 6 are positioned in a series of such traces, the trace sub-portions T1₃ and T3₁ will be bounded, respectively, by the immediately adjacent trace sub-portions T3₁ and T1₃ of other sets of traces T1, T2, and T3.

As shown in FIG. 5, the end points A, A', B, B', C, and C' of the traces T1, T2, and T3 are located at positions in a predefined matrix to allow the trace configuration described above. More specifically and as shown in FIG. 5, the end points A, A', B, B', C, and C' are positioned on a rectangular matrix having row position numbers 1 through 6, corresponding to the rows of the connection fields for the tail portions 22 of the connector 10 and the connection pads P of the circuit board, and column position numbers 1, 2, 3, 4, 5, 6, 7, 8, ... corresponding to twice the total number of interconnect columns for the connector 10. As can be appreciated, the upper value of the column posi-

tion number depends upon the length of the connector 10 and the total number of interconnect columns. Using the row position and column position indices, all the traces T1, T2, and T3 start at odd column position numbers with the trace T1 beginning at position (1,3) and ending at position (4,5), the trace T2 beginning at position (2,3) and ending at position (5,4), and the trace T3 beginning at position (3,3) and ending at position (6,1). The row positions for each of the beginning and ending points for all the traces varies by three row positions with the column number varying by a relative +2 for the trace T1, the column number varying by a relative +1 for the trace T2, and the column number varying by relative -2 for the trace T3.

The trace configuration described above is well suited for high speed digital bus applications since the interconnection path length is the same for each interconnect within the series and provides substantially same resistance and impedance characteristics. While a single flex circuit 14 can be provided to effect the various interconnects, the preferred embodiment is as shown in the side view of FIG. 7 in which flex circuits 14 and 14' effect interconnection between the connector 10 (shown in dotted line illustration) and the upper and lower sides of the print circuit board 12.

In the illustrated embodiment, the distance between the tail portions of the C row of the connector 10 and the A' row is equal to the row inter-spacing. As can be appreciated, the distance between the C row and the A' row can be increased for different applications while maintaining equal paths lengths for the various traces. While the preferred embodiment has been illustrated in the context of a connector that includes receptacles, the invention is equally well suited for use with headers that include pins for mating with the receptacles of a connector.

As can be appreciated by those skilled in the art, the present invention advantageously provides an impedance controlled interface for effecting an electrical connection between a connector and its circuit board in such a way that the resistance and related impedance characteristics are substantially the same for each circuit interconnect.

Thus it will be appreciated from the above that as a result of the present invention, an impedance controlled connector interface is provided by which the principal objectives, among others, are completely fulfilled. It will be equally apparent and is contemplated that modification and/or changes may be made in the illustrated embodiment without departure from the invention. Accordingly, it is expressly intended that the foregoing description and accompanying drawings are illustrative of preferred embodiments only, not limiting, and that the scope of the present invention is defined by the appended claims.

Claims

1. A connection interface for electrically connecting a multi-row connector (10) or header to a circuit bearing substrate (12); said interface comprising a flex circuit (14, 14') having a first field of connection areas (A,B,C) for connection to a corresponding tail-portion field (22) associated with the connector (10); another field of connection areas (A',B',C') for connection to a corresponding connection field (P) associated with the circuit bearing substrate (12) and electrically conductive traces (30) each extending between corresponding ones of the connection areas (32) of the first connection field (22) and the connection areas (32') of the other connection field (P), each of said traces (30) presenting substantially the same impedance between its connection areas (32, 32') as the other of the traces (30).
2. The connection interface according to Claim 1, wherein each of said traces (30) is of equal length between their respective connection areas (A, B, C A',B',C').
3. The connection interface according to Claim 1, wherein each of said traces (30) is of equal electrical resistance.
4. The connection interface according to Claim 2 or 3, wherein each of said traces (30) is defined by at least first (T1, T2, T3) and second sub-portions (T1', T2', T3').
5. A connection system for connecting a multi-row connector (10) or header having at least two rows of connection devices (20) to a circuit bearing substrate (12); said system comprising:
 - a flex circuit (14, 14') defined by first (26) and second (28) layers of an insulating sheet material and having a first field of connection areas (A, B, C) for connection to a corresponding tail-portion field (22) defined by the connection devices (20) and another field of connection areas (A',B',C') for connection to a corresponding connection field (P) associated with the circuit bearing substrate (12), the first and second connection area fields (A, B, C, A',B',C') each being defined by a respective first row of connection areas (A',A') and a respective second row of connection areas (B', B'), said flex circuit (14, 14') having a first set of electrically conductive traces (30) extending between corresponding ones of the connection areas of the first rows (A, A') of the first and other connection fields and a second set of electrically conductive traces (30) extending between corresponding ones of the connection areas of the second row (B, B') of the first and



tion number depends upon the length of the connector 10 and the total number of interconnect columns. Using the row position and column position indices, all the traces T1, T2, and T3 start at odd column position numbers with the trace T1 beginning at position (1,3) and ending at position (4,5), the trace T2 beginning at position (2,3) and ending at position (5,4), and the trace T3 beginning at position (3,3) and ending at position (6,1). The row positions for each of the beginning and ending points for all the traces varies by three row positions with the column number varying by a relative +2 for the trace T1, the column number varying by a relative +1 for the trace T2, and the column number varying by relative -2 for the trace T3.

The trace configuration described above is well suited for high speed digital bus applications since the interconnection path length is the same for each interconnect within the series and provides substantially same resistance and impedance characteristics. While a single flex circuit 14 can be provided to effect the various interconnects, the preferred embodiment is shown in the side view of FIG. 7 in which flex circuits 14 and 14' effect interconnection between the connector 10 (shown in dotted line illustration) and the upper and lower sides of the print circuit board 12.

In the illustrated embodiment, the distance between the tail portions of the C row of the connector 10 and the A' row is equal to the row inter-spacing. As can be appreciated, the distance between the C row and the A' row can be increased for different applications while maintaining equal paths lengths for the various traces. While the preferred embodiment has been illustrated in the context of a connector that includes receptacles, the invention is equally well suited for use with headers that include pins for mating with the receptacles of a connector.

As can be appreciated by those skilled in the art, the present invention advantageously provides an impedance controlled interface for effecting an electrical connection between a connector and its circuit board in such a way that the resistance and related impedance characteristics are substantially the same for each circuit interconnect.

Thus it will be appreciated from the above that as a result of the present invention, an impedance controlled connector interface is provided by which the principal objectives, among others, are completely fulfilled. It will be equally apparent and is contemplated that modification and/or changes may be made in the illustrated embodiment without departure from the invention. Accordingly, it is expressly intended that the foregoing description and accompanying drawings are illustrative of preferred embodiments only, not limiting, and that the scope of the present invention is defined by the appended claims.

Claims

1. A connection interface for electrically connecting a multi-row connector (10) or header to a circuit bearing substrate (12); said interface comprising a flex circuit (14, 14') having a first field of connection areas (A,B,C) for connection to a corresponding tail-portion field (22) associated with the connector (10); another field of connection areas (A',B',C',) for connection to a corresponding connection field (P) associated with the circuit bearing substrate (12) and electrically conductive traces (30) each extending between corresponding ones of the connection areas (32) of the first connection field (22) and the connection areas (32') of the other connection field (P), each of said traces (30) presenting substantially the same impedance between its connection areas (32, 32') as the other of the traces (30).
2. The connection interface according to Claim 1, wherein each of said traces (30) is of equal length between their respective connection areas (A, B, C A',B',C').
3. The connection interface according to Claim 1, wherein each of said traces (30) is of equal electrical resistance.
4. The connection interface according to Claim 2 or 3, wherein each of said traces (30) is defined by at least first (T₁, T₂, T₃) and second sub-portions (T₁₂, T₂₂, T₃₂).
5. A connection system for connecting a multi-row connector (10) or header having at least two rows of connection devices (20) to a circuit bearing substrate (12); said system comprising:
a flex circuit (14, 14') defined by first (26) and second (28) layers of an insulating sheet material and having a first field of connection areas (A, B, C) for connection to a corresponding tail-portion field (22) defined by the connection devices (20) and another field of connection areas (A',B',C') for connection to a corresponding connection field (P) associated with the circuit bearing substrate (12), the first and second connection area fields (A, B, C, A',B',C') each being defined by a respective first row of connection areas (A,A') and a respective second row of connection areas (B', B'), said flex circuit (14, 14') having a first set of electrically conductive traces (30) extending between corresponding ones of the connection areas of the first rows (A, A') of the first and other connection fields and a second set of electrically conductive traces (30) extending between corresponding ones of the connection areas of the second row (B, B') of the first and



other connection fields, each of said traces (30) of said first and second sets of traces presenting substantially the same impedance to its connection areas as the other of the traces in its set and the traces of the other set.

6. A connection system for connecting a multi-row connector (10) or header having at least three rows of connection devices (20) to a circuit bearing substrate (12), said system comprising:

a flex circuit (14, 14') defined by first (26) and second (28) layers of an insulating sheet material and having a first field of connection areas (A, B, C) for connection to a corresponding tail-portion field (22) defined by the connection devices (20) and having another field of connection areas (A' B' C') for connection to a corresponding connection field (P) associated with the circuit bearing substrate (12), the first and second connection area field (A' B' C') of said flex circuit (14, 14') each being defined by a respective first row of connection areas (A, A'), a respective second row of connection areas (B, B'), and a respective third row of connection areas (C, C'), said flex circuit (14, 14') having a first set of electrically conductive traces (30) extending between corresponding ones of the connection areas of the first rows (A, A') of the first and second connection fields, a second set of electrically conductive traces (30) extending between corresponding ones of the connection areas of the second rows (B, B') of the first and second connection fields, and a third set of electrically conductive traces (30) extending between corresponding ones of the connection areas of the third rows (C, C') of the first and second connection fields, each of said traces (30) of said first, second, and third sets presenting substantially the same impedance to its connection areas as the other of the traces in its set and the traces of the other sets.

7. A connection system for connecting a multi-row connector (10) or header having at least six rows of connection devices (20) to opposite sides of a circuit bearing substrate (12) said system comprising:

a six row connector or header (10) attached to an edge (24) of a circuit bearing substrate (12) and having three rows of connection devices (20) associated with one side of the circuit bearing substrate (12) and three rows of connection devices (20) associated with the other side of the circuit bearing substrate (12), said circuit bearing substrate (12) having a connection field (P) on the one side for connection with the first-mentioned three rows of devices (20) and a connection field (P) on the opposite side for connection to the second-mentioned three rows of devices (20):

first (14) and second (14') flex circuits for connecting, respectively, the first-mentioned three rows of devices (20) to the first-mentioned connection field (P) of the circuit bearing substrate (12) and the second-mentioned three rows of devices (20) to the second-mentioned connection field (P) of the circuit bearing substrate (12), each flex circuit being defined by first (26) and second (28) layers of an insulating sheet material and having a first field of connection areas (A, B, C) for connection to a corresponding tail-portion field (22) defined by the associated connection devices (20) and having another field (A', B', C') of connection areas for connection to the corresponding connection field (P) associated with the circuit bearing substrate (12), the first and second connection area fields each defined by a respective first row of connection areas (A, A'), a respective second row of connection areas (B, B'), and a respective third row of connection areas (C, C'), said flex circuit having a first set of electrically conductive trace (30) extending between corresponding ones of the connection areas (A, A') of the first rows of the first and the other connection fields, a second set of electrically conductive traces (30) extending between corresponding ones of the connection areas (B, B') of the second rows of the first and the other connection fields, and a third set of electrically conductive traces (30) extending between corresponding ones of the connection (C, C') of the third rows of the first and the other connection fields, each of said traces (30) of said first, second, and third set presenting substantially the same impedance to its connection areas as the other of the traces in its set and the traces of the other sets.

8. The connection system according to Claim 5, 6 or 7, wherein each of said traces (30) is of equal length between their respective connection areas (A, B, C, A', B', C').

9. The connection system according to Claim 5, 6 or 7, wherein each of said traces (30) is of equal electrical resistance.

10. The connection system according to Claim 5, 6, 7, 8 or 9, wherein each of said traces is defined by at least first (T1₁, T2₁, T3₁) and second sub-portions (T1₂, T2₂, T3₂)

11. The connection system of Claim 5, wherein the first (A, A') and second B, B') rows of connection areas for the first connection area field and the second connection area field are separated by the same inter-row spacing.



12. The connection system according to Claim 6 or 7, wherein the first (A, A') second (B, B') and third (C, C') rows of connection areas for the first connection area field and the second connection area field are separated by the same inter-row spacing.

Patentansprüche

1. Verbindungs-Schnittstelle, um einen mehrreihigen Verbinder (10) oder Verteiler elektrisch mit einem eine Schaltung tragenden Substrat (12) zu verbinden, wobei die Schnittstelle eine flexible Schaltung (14, 14') mit einem ersten Feld von Anschlußbereichen (A, B, C) für eine Verbindung mit einem entsprechenden Schwanz-Abschnitt-Feld (22), welches dem Verbinder (10) zugeordnet ist, aufweist, ein weiteres Feld von Verbindungsbereichen (A', B', C') für eine Verbindung mit einem entsprechenden Anschlußfeld (P), welches dem die Schaltung tragenden Substrat (12) zugeordnet ist und mit elektrisch leitenden Bahnen (30) zu verbinden, von denen sich jede zwischen entsprechenden Verbindungsbereichen (32) des ersten Anschlußfeldes (22) und den Verbindungsbereichen (32') des anderen Verbindungsfeldes (P) erstreckt, wobei die Bahnen (30) im wesentlichen die gleiche Impedanz zwischen ihren Anschlußbereichen (32, 32') wie andere der Bahnen (30) haben.
2. Verbindungs-Schnittstelle nach Anspruch 1, bei der jede der Bahnen (30) zwischen deren jeweiligen Verbindungsbereichen (A, B, C, A', B', C') gleiche Länge aufweisen.
3. Verbindungs-Schnittstelle nach Anspruch 1, bei der jede der Bahnen (30) gleichen elektrischen Widerstand besitzt.
4. Verbindungs-Schnittstelle nach Anspruch 2 oder 3, bei der jede der Bahnen (30) durch wenigstens erste (T₁₁, T₂₁, T₃₁) und zweite Unterabschnitte (T₁₂, T₂₂, T₃₂) definiert ist.
5. Verbindungssystem zum Verbinden eines Mehrreihen-Verbinders (10) oder Verteilers mit wenigstens zwei Reihen von Anschlußvorrichtungen (20) mit einem eine Schaltung tragenden Substrat (12), wobei das System aufweist: eine flexible Schaltung (14, 14'), die durch erste (26) und zweite (28) Schichten eines isolierenden Blattmaterials definiert ist und ein erstes Feld von Anschlußbereichen (A, B, C) zum Anschließen an ein entsprechendes Schwanzabschnitt-Feld (22), welches durch die Anschlußvorrichtungen (20) definiert ist und ein anderes Feld von Verbindungs-

bereichen (A', B', C') besitzt, für den Anschluß an ein entsprechendes Anschlußfeld (P), welches dem die Schaltung tragenden Substrat (12) zugeordnet ist, wobei die ersten und zweiten Anschlußbereichsfelder (A, B, C, A', B', C') jeweils durch eine entsprechende erste Reihe von Anschlußbereichen (A', A') und eine entsprechende zweite Reihe von Anschlußbereichen (B', B') definiert sind, wobei ferner die flexible Schaltung (14, 14') einen ersten Satz von elektrisch leitenden Bahnen (30) aufweist, die sich zwischen entsprechenden der Anschlußbereiche der ersten Reihen (A, A') der ersten und weiteren Anschlußfelder erstrecken und einen zweiten Satz von elektrisch leitenden Bahnen (30) aufweist, die sie zwischen entsprechenden der Anschlußbereiche der zweiten Reihe (B, B') der ersten und weiteren Anschlußfelder erstrecken, wobei jede der Bahnen (30) des ersten und des zweiten Satzes der Bahnen im wesentlichen die gleiche Impedanz an ihren Anschlußbereichen bieten wie die andere der Bahnen in ihrem Satz und die Bahnen des anderen Satzes.

6. Anschlußsystem zum Verbinden eines Mehrreihen-Verbinders (10) oder Verteilers mit wenigstens drei Reihen von Anschlußvorrichtungen (20) zum Anschluß an ein eine Schaltung tragenden Substrat (12), wobei das System aufweist: eine flexible Schaltung (14, 14'), die durch erste (26) und zweite (28) Schichten eines isolierenden Blattmaterials definiert ist und ein erstes Feld von Anschlußbereichen (A, B, C) aufweist, um einen Anschluß an ein entsprechendes Schwanzabschnitt-Feld (22) zu realisieren, der durch die Anschlußvorrichtungen (20) definiert ist und ein weiteres Feld von Anschlußbereichen (A', B', C') besitzt für den Anschluß an ein entsprechendes Anschlußfeld (P), welches dem die Schaltung tragenden Substrat (12) zugeordnet ist, wobei das erste und das zweite Anschlußbereichsfeld (A', B', C') der flexiblen Schaltung (14, 14') je durch eine entsprechende erste Reihe von Anschlußbereichen (A, A'), eine jeweilige zweite Reihe von Anschlußbereichen (B, B') und eine jeweilige dritte Reihe von Anschlußbereichen (C, C') definiert ist, die flexible Schaltung (14, 14') einen ersten Satz von elektrisch leitenden Bahnen (30) aufweist, die sich zwischen entsprechenden der Anschlußbereiche der ersten Reihe (A, A') des ersten und des zweiten Anschlußfeldes erstrecken, einen zweiten Satz von elektrisch leitenden Bahnen (30) aufweist, die sich zwischen entsprechenden der Anschlußbereiche der zweiten Reihe (B, B') des ersten und des zweiten Anschlußfeldes erstrecken und einen dritten Satz von elektrisch leitenden Bahnen (30) aufweist, die sich zwischen entsprechenden der Anschluß-



bereiche der dritten Reihen (C, C') des ersten und des zweiten Anschlußfeldes erstrecken, wobei jede der Bahnen (30) des ersten, des zweiten und des dritten Satzes im wesentlichen die gleiche Impedanz für ihre Anschlußbereiche bietet wie die andere der Bahnen in ihrem Satz und wie die Bahnen der anderen Sätze.

7. Anschlußsystem zum Anschließen eines Vielreihen-Verbinders (10) oder Verteilers mit wenigstens sechs Reihen von Anschlußvorrichtungen (20) an sich gegenüberliegenden Seiten eines eine Schaltung tragenden Substrats (12), wobei das System aufweist:

einen sechs Reihen-Verbinder oder Verteiler (10), der an einem Rand (24) eines eine Schaltung tragenden Substrats (12) befestigt ist und drei Reihen von Anschlußvorrichtungen (20) besitzt, die einer Seite des die Schaltung tragenden Substrats (12) zugeordnet sind und drei Reihen von Anschlußvorrichtungen (20) besitzt, die der anderen Seite des die Schaltung tragenden Substrats (12) zugeordnet sind, wobei das die Schaltung tragende Substrat (12) ein Anschlußfeld (P) auf einer Seite aufweist, um eine Verbindung mit den ersterwähnten drei Reihen an Vorrichtungen (20) herzustellen und ein Anschlußfeld (P) auf der gegenüberliegenden Seite besitzt, um einen Anschluß mit den als zweiten erwähnten drei Reihen der Vorrichtungen (20) zu bewirken: erste (14) und zweite (14') flexible Schaltungen, für eine jeweilige Verbindung der ersterwähnten drei Reihen an Vorrichtungen (20) mit dem ersterwähnten Anschlußfeld (P) des die Schaltung tragenden Substrats (12) und um die zweiterwähnten drei Reihen an Vorrichtungen (20) mit dem an zweiter Stelle erwähnten Anschlußfeld (P) des die Schaltung tragenden Substrats (12) zu verbinden, wobei jede flexible Schaltung durch erste (26) und zweite (28) Schichten eines isolierenden Blattmaterials definiert ist und ein erstes Feld von Anschlußbereichen (A, B, C) besitzt für den Anschluß an ein entsprechendes Schwanz-Abschnitt-Feld (22), welches durch die zugeordneten Anschlußvorrichtungen (20) definiert ist und ein weiteres Feld (A', B', C') von Anschlußbereichen besitzt, für eine Verbindung mit einem entsprechenden Anschlußfeld (P), welches dem die Schaltung tragenden Substrat (12) zugeordnet ist, wobei das erste und das zweite Anschlußbereichsfeld jeweils durch eine entsprechende erste Reihe von Anschlußbereichen (A, A'), eine jeweilige zweite Reihe von Anschlußbereichen (B, B') und eine entsprechende dritte Reihe von Anschlußbereichen (C, C') definiert ist, wobei ferner die flexible Schaltung einen ersten Satz von elektrisch leitenden Bahnen (30) aufweist, die sich zwischen entsprechenden der Anschlußbe-

reiche (A, A') der ersten Reihen der ersten und weiterer Anschlußfelder erstrecken, einen zweiten Satz von elektrisch leitenden Bahnen (30) aufweist, die sich zwischen entsprechenden der Anschlußbereiche (B, B') der zweiten Reihen der ersten und weiterer Anschlußfelder erstrecken und einen dritten Satz von elektrisch leitenden Bahnen (30) aufweist, die sich zwischen entsprechenden der Anschlußbereiche (C, C') der dritten Reihen der ersten und weiterer Anschlußfelder erstrecken, wobei jede der Bahnen (30) des ersten, zweiten und dritten Satzes im wesentlichen die gleiche Impedanz hinsichtlich der Anschlußbereiche aufweist wie die andere der Bahnen in ihrem Satz und wie die Bahnen der anderen Sätze.

8. Anschlußsystem nach Anspruch 5, 6 oder 7, bei dem jede der Bahnen (30) von gleicher Länge zwischen den jeweiligen Anschlußbereichen (A, B, C, A', B', C') ist.
9. Anschlußsystem nach Anspruch 5, 6 oder 7, bei dem jede der Bahnen (30) einen gleichen elektrischen Widerstand besitzt.
10. Anschlußsystem nach Anspruch 5, 6, 7, 8 oder 9, bei dem jede der Bahnen durch wenigstens erste (T1, T2, T3) und zweite Unterabschnitte (T1', T2', T3') definiert ist.
11. Anschlußsystem nach Anspruch 5, bei dem die ersten (A, A') und zweiten (B, B') Reihen von Anschlußbereichen für das erste Anschlußbereichsfeld und das zweite Anschlußbereichsfeld durch den gleichen Zwischenreihenabstand getrennt sind.
12. Anschlußsystem nach Anspruch 6 oder 7, bei dem die erste (A, A'), die zweite (B, B') und die dritte (C, C') Reihe der Anschlußbereiche für das erste Anschlußbereichsfeld und das zweite Anschlußbereichsfeld durch den gleichen Zwischenreihenabstand getrennt sind.

Revendications

1. Une interface de connexion pour connecter électriquement un connecteur (10) ou une embase à rangées multiples à un substrat (12) comportant un circuit; ladite interface comprenant un circuit flexible (14, 14') comportant un premier champ de surfaces de connexion (A, B, C) pour la connexion à un champ correspondant (22) de partie de queue, associé au connecteur (10); un autre champ de surfaces de connexion (A', B', C') pour la connexion à un champ de connexion



- correspondant (P) associé au substrat (12) portant un circuit, et des traces électriquement conductrices (30) s'étendant chacune entre des surfaces correspondantes parmi les surfaces de connexion (32) du premier champ de connexion (22) et les surfaces de connexion (32') de l'autre champ de connexion (P), chacune desdites traces (30) présentant sensiblement la même impédance entre ses surfaces de connexion (32, 32') que l'autre desdites traces (30).
2. L'interface de connexion selon la revendication 1, dans laquelle chacune desdites traces (30) présente la même longueur entre ses surfaces de connexion (A, B, C; A', B', C').
 3. L'interface de connexion selon la revendication 1, dans laquelle chacune desdites traces (30) présente la même résistance électrique.
 4. l'interface de connexion selon la revendication 2 ou 3 dans laquelle chacune desdites traces (30) est définie par au moins une première (T₁, T₂, T₃) et une deuxième (T₁, T₂, T₃) sous-parties.
 5. Un système de connexion pour connecter un connecteur (10) ou une embase à rangées multiples comportant au moins deux rangées de dispositifs de connexion (20) à un substrat comportant un circuit (12); ledit système comprenant:
 - un circuit flexible (14, 14') défini par une première (26) et une deuxième (28) couches d'un matériau isolant en feuille et présentant un premier champ de surfaces de connexion (A, B, C) pour la connexion à un champ correspondant de partie de queue (22) défini par les dispositifs de connexion (20) et un autre champ de surfaces de connexion (A', B', C') pour la connexion à un champ de connexion correspondant (P) associé au substrat (12) portant le circuit, le premier et le deuxième champs de surfaces de connexion (A, B, C, A', B', C') étant défini chacun par une première rangée respective de surfaces de connexion (A', A') et une deuxième rangée respective de surfaces de connexion (B', B'), ledit circuit flexible (14, 14') présentant un premier jeu de traces électriquement conductrices (30) s'étendant entre des surfaces correspondantes des surfaces de connexion des premières rangées (A, A') du premier et des autres champs de connexion, et un deuxième jeu de traces électriquement conductrices (30) s'étendant entre les surfaces correspondantes parmi les surfaces de connexion de la deuxième rangée (B, B') du premier et des autres champs de connexion, chacune desdites traces (30) dudit premier et dudit deuxième jeux de traces présentant sensiblement la même impédance à ses surfaces de connexion que les autres parmi les traces dans son jeu et les traces de l'autre jeu.
 6. Un système de connexion pour connecter un connecteur (10) ou une embase à au moins trois rangées de dispositifs de connexion (20) à un substrat portant un circuit (12); ledit système comprenant:
 - un circuit flexible (14, 14') défini par une première (26) et une deuxième (28) couches d'un matériau isolant en feuille et présentant un premier champ de surfaces de connexion (A, B, C) pour la connexion à un champ de partie de queue correspondant (22) défini par les dispositifs de connexion (20) et présentant un autre champ de surfaces de connexion (A', B', C') pour la connexion à un champ de connexion correspondant (P) associé au substrat (12) portant le circuit, le premier et le deuxième champs de surfaces de connexion (A', B', C') dudit circuit flexible (14, 14') étant chacun défini par une première rangée respective de surfaces de connexion (A, A'), par une deuxième rangée respective de surfaces de connexion (B, B') et par une troisième rangée respective de surfaces de connexion (C, C'), ledit circuit flexible (14, 14') présentant un premier jeu de traces électriquement conductrices (30) s'étendant entre les surfaces de connexion correspondantes parmi les surfaces de connexion des premières rangées (A, A') des premier et deuxième champs de connexion, un deuxième jeu de traces électriquement conductrices (30) s'étendant entre les surfaces de connexion correspondantes parmi les surfaces de connexion des deuxième rangées (B, B') du premier et du deuxième champs de connexion, et un troisième jeu de traces électriquement conductrices (30) s'étendant entre les surfaces de connexion correspondantes parmi les surfaces de connexion des troisième rangées (C, C') du premier et du deuxième champs de connexion, chacune desdites traces (30) desdits premier, deuxième, et troisième jeux présentant sensiblement la même impédance à ses surfaces de connexion que les autres traces de son jeu, et que les traces des autres jeux.
 7. Un système de connexion pour connecter un connecteur (10) ou une embase à rangées multiples comportant au moins six rangées de dispositifs de connexion (20), à des faces opposées d'un substrat portant un circuit (12), ledit système comprenant:
 - un connecteur ou une embase (10) à six rangées et fixé à un bord (24) d'un substrat (12) portant un circuit et présentant trois rangées de dispositifs de connexion (20) associés à l'une des



faces du substrat (12) portant un circuit et trois rangées de dispositifs de connexion (20) associés à l'autre face du substrat (12) portant un circuit, ledit substrat portant un circuit (12) présentant un champ de connexion (P) sur l'une de ses faces pour la connexion aux trois rangées mentionnées en premier des dispositifs (20) et un champ de connexion (P) sur la face opposée pour la connexion aux trois rangées mentionnées en second des dispositifs (20);

un premier (14) et un second (14') circuits flexibles pour connecter, respectivement, les trois rangées mentionnées en premier des dispositifs (20) au champ de connexion mentionné en premier (P) du substrat (12) portant un circuit et les trois rangées mentionnées en second des dispositifs (20) au champ de connexion (P) mentionné en second du substrat (12) portant un circuit, chaque circuit flexible étant défini par une première (26) et une deuxième (28) couches d'un matériau isolant en feuilles et présentant un premier champ de surfaces de connexion (A, B, C,) pour la connexion à un champ de partie de queue correspondant (22) défini par les dispositifs de connexion associés (20), et présentant un autre champ (A', B', C') de surfaces de connexion pour la connexion au champ de connexion correspondant (P) associé au substrat (12) portant un circuit, le premier et le deuxième champs de surfaces de connexion étant chacun défini par une première rangée respective de surfaces de connexion (A, A'), par une deuxième rangée respective de surfaces de connexion (B, B') et par une troisième rangée respective de surfaces de connexion (C, C'), ledit circuit flexible présentant un premier jeu de traces électriquement conductrices (30) s'étendant entre les surfaces de connexion correspondantes (A, A') parmi les premières rangées du premier et des autres champs de connexion, un deuxième jeu de traces électriquement conductrices (30) s'étendant entre les surfaces de connexion correspondantes (B, B') parmi les deuxième rangées du premier et des autres champs de connexion, et un troisième jeu de traces électriquement conductrices (30) s'étendant entre les surfaces de connexion correspondantes (C, C') parmi les troisième rangées du premier et des autres champs de connexion, chacune desdites traces (30) desdits premier, deuxième, et troisième jeux présentant sensiblement la même impédance à ses surfaces de connexion que les autres traces de son jeu, et que les traces des autres jeux.

8. Le système de connexion selon la revendication 5, 6 ou 7, dans lequel chacune desdites traces (30) présente la même longueur entre ses surfaces de connexion respectives (A, B, C, A', B', C').

9. Le système de connexion selon la revendication 5, 6 ou 7, dans lequel chacune desdites traces (30) présente la même résistance électrique.

- 5 10. Le système de connexion selon la revendication 5, 6, 7, 8 ou 9, dans lequel chacune desdites traces est définie par au moins une première (T1₁, T2₁, T3₁) et une deuxième (T1₂, T2₂, T3₂) sous-parties.

- 10 11. Le système de connexion selon la revendication 5, dans lequel la première (A, A') et la deuxième (B, B') rangées de surfaces de connexion pour le premier champ de surfaces de connexion et pour le deuxième champ de surfaces de connexion sont séparées par le même pas d'espacement entre rangées.

- 15 12. Le système de connexion selon la revendication 6 ou 7, dans lequel la première (A, A'), la deuxième (B, B') et la troisième (C, C') rangées de surfaces de connexion pour le premier champ de surfaces de connexion et pour le deuxième champ de surfaces de connexion sont séparées par le même pas d'espacement entre rangées.

30

35

40

45

50

55

10