

Description

The invention relates to a monochrome cathode ray tube comprising at one end an electron gun and at the oppositely located end a display screen having a phosphor layer and a deflection unit provided around the neck of the display tube, and a magnetic focusing device which is provided between the electron gun and the deflection unit around the neck of the display tube and which comprises means to generate a static focusing field.

Upon focusing electrons in a cathode ray tube two types of lenses are used, electrostatic ones or magnetic ones. In order to achieve a high definition it is desired to reach a very good extent of focusing (=small electron spot c.q. high resolution). Magnetic lenses may generally be provided outside the neck of the tube, this in contrast with electrostatic lenses which are present in the neck of the tube. As a result of this the diameter of the magnetic lenses may be larger, which provides a better lens quality: the spherical aberration decreases when the lens diameter increases. A smaller spherical aberration leads to a smaller spot on the screen, which is required for high resolution guns. For higher resolution (projection) television tubes a magnetic focusing lens is hence preferably used.

When magnetic focusing lenses are used, there may be distinguished between two types: electromagnetic lenses, and magnetostatic lenses. In an electromagnetic lens a field is generated by a coil enclosed partly by a yoke. In a permanent magnetic lens the field is generated by a permanent magnetic material whether or not provided with a yoke (DE-PS 891 119). The electron beam is also moved over the screen by a deflection coil, the intensity of the beam being modulated to obtain a picture. The great beam angular aperture which is associated with the use of a focusing lens having a large diameter has for its result that upon deflecting the beam by the deflection coil the electron spot on the screen is not only enlarged but also distorted. As a result of this deflection defocusing an elliptical spot having a diameter which is larger than that in the centre of the display screen is formed at the edge of the screen.

In some applications of cathode ray tubes, for example projection television tubes or so-called data graphic display tubes, such a distortion cannot be tolerated.

It is the object of the invention to provide a cathode ray tube of the type having a magnetic focusing lens with means to correct said astigmatic errors. This object is achieved in a cathode ray tube according to the invention in that the means to generate the static focusing field directly adjoin the deflection unit and are constructed so as to generate higher order multipole fields to correct spot distortion errors as well.

The multipole correction fields are generated at the area where the beam diameter in the tube is largest. With this large beam diameter the influence of the multipole correction fields is greatest. This is the case at the area of the magnetic focusing lens. A further advantage of this way of generating the multipole correction fields is that the magnetic fo-

cusing lens directly adjoins the deflection unit and hence is placed as near as possible to the display screen. As a result of this an optimum resolution is maintained. When multipole correction means are provided between the magnetic focusing lens and the deflection coil, in itself a place which is not unusual for magnetic correction means, the resolution will no longer be optimum.

From FR-A 1 086 226 it is per se known to provide from correction coil having their axes parallel to the tube axis and surrounding the focussing coil also having its axis parallel to the tube axis.

The multipole correction fields may in particular be quadrupole fields (to correct astigmatism errors optionally in combination with six-pole fields (to correct higher order spot distortions) and they can be realised in various manners.

According to a first embodiment of the invention an integrated focusing and multipole correction unit is obtained by composing the yoke of the focusing device entirely or partly from eight equal parts each having a longitudinal coil. By energizing said longitudinal coils correctly a rotationally symmetrical focusing field can be generated on which a quadrupole field to correct astigmatism errors is superimposed.

An integrated focusing and multipole correction unit is alternatively obtained by composing the focusing device of eight coplanar bar magnets which are ordered for generating a static focusing field and by placing a coil around each bar magnet. When the coils are energized correctly in which two oppositely located coils always convey the same current, any desired quadrupole field may be generated to correct astigmatism errors.

A few embodiments of the invention will be explained in greater detail with reference to the drawing, in which

Figure 1 is a longitudinal sectional view through a cathode ray tube having an integrated focusing and multipole correction unit according to the invention;

Figure 2a is a longitudinal sectional view and

Figure 2b is a cross-sectional view taken on the line II-II through an integrated focusing multipole correction unit for the Figure 1 cathode ray tube (first embodiment);

Figure 3a is a longitudinal sectional view and Figure 3b a cross-sectional view through an integrated focusing multipole correction unit for the Figure 1 cathode ray tube (second embodiment);

Figure 4 shows a diagram for connecting a multipole correction coil.

An integrated focusing multipole correction unit 10 is assembled around the neck 1 of a cathode ray tube 3. The tube 3 has a cathode 4 to produce an electron beam 5 in cooperation with a heating element 6, a grid 7, and an anode 8. Deflection coils (not shown) are mounted on a deflection yoke 9 on the neck 2 of the tube 3.

Referring now to Figures 2A and 2B it is suggested to divide the yoke 11 of a focusing unit into eight segments. Each of the segments 12 as shown in Figures 2A and 2B is provided with a coil 13 in the case

of an electromagnetic focusing unit. In the alternative case of a permanent magnetic focusing unit it is suggested to place eight radial bar magnets 14 between a divided inner yoke 15 and an undivided outer yoke 16, as shown in Figures 3a and 3b. The inner yoke 15 is divided into eight parts. In this case, two gaps are formed which generate an opposite magnetic field. A coil 17 is wound around each of the bar magnets.

If an equal current is sent through the eight coils 13 in the electromagnetic case a static rotationally symmetrical focusing field is generated. If an extra current I is conveyed through A and A' and the current in the coils C and C' is reduced by I a quadrupole field superimposed upon the rotationally symmetrical focusing field is generated. By controlling the current through the coils B, B', D and D', the quadrupole field can be rotated in any desired direction. It is to be noted that the eight coils may advantageously be constructed so as to form two sub-coil systems, one having a high L value for a fixed adjustment of the focusing field (this system may optionally be replaced by a system of permanent magnets) and one having a low L value for a dynamic drive of the focusing field.

In the case of the permanent magnetic lens 18 (Figure 3B) the static focusing field is made by means of the eight bar magnets 14. If the strength of the focusing lens is to be varied, either an equal current can be sent through all the coils 17, or extra coils may be used which may be provided in the lens.

The quadrupole fields are generated by passing the desired current through the eight coils 17, always two oppositely located coils conveying the same current.

The end in view is reached by the configuration shown namely that the multipole corrections are made in the place where the beam has its largest diameter: in the focusing lens. Herewith it is always achieved that the two functions of focusing and spot correction take place in the same unit.

A multipole correction coil 27 can be switched as is shown in Figure 4. By energization of the supply lines such a quadrupole field can be generated that distortion of the spot is corrected. With equal currents through A-A' and B-B' the quadrupole shown is formed. The required corrections depend on the position of the electron spot on the screen and these currents are hence varied synchronously with the deflection current. The driving may take place both completely analogously and via a digital process (GB-A 2 085 698).

It is to be noted that the multipole coils in the figures are shown with single turns to produce the individual poles, the turns not overlapping each other. However, the invention also relates to the use of multipole coils which show a so-called cosinusoidal distribution of the turns in behalf of an improved homogeneity of the generated multipole field.

Claims

1. A monochrome cathode ray tube comprising at one end an electron gun and at the oppositely locat-

ed end a display screen having a phosphor layer and a deflection unit provided around the neck of the display tube, and a magnetic focusing device which is provided between the electron gun and the deflection unit around the neck of the display tube and which comprises means to generate a static focusing field, characterized in that the means to generate the static focusing field directly adjoin the deflection unit and are constructed so as to generate higher order multipole fields to correct spot distortion errors as well.

2. A cathode ray tube as claimed in Claim 1, characterized in that the focusing device comprises a yoke which is composed entirely or partly of eight equal parts, each part having a longitudinal coil, the eight coils being energizable in such manner as to generate a static focusing field on which a quadrupole field is superimposed to correct for astigmatism errors.

3. A cathode ray tube as claimed in Claim 1, characterized in that the eight coils constitute two sub-coil systems: a first set having a high impedance to generate the static focusing field and a second set having a low impedance to generate a dynamically varying focusing field.

4. A cathode ray tube as claimed in Claim 1, characterized in that the focusing device comprises eight coplanar bar magnets which are ordered to generate a static focusing field, each bar magnet supporting a coil and the eight coils being energizable in such manner as to generate a desired quadrupole field to correct for astigmatism errors.

Patentansprüche

1. Monochrome Kathodenstrahlröhre, die an einem Ende einen Elektronenstrahlerzeuger und an dem gegenüberliegenden Ende einen Wiederabgabeschirm mit einer Leuchtstoffschicht und eine um den Hals der Wiedergaberöhre angeordneten Ablenkeinheit sowie eine magnetische Fokussiereinheit enthält, die zwischen dem Elektronenstrahlerzeuger und der Ablenkeinheit um den Hals der Wiedergaberöhre angeordnet ist und Mittel zum Erzeugen eines statischen Fokussierfelds enthält, dadurch gekennzeichnet, daß die Mittel zum Erzeugen des statischen Fokussierfelds direkt an die Ablenkeinheit grenzen und derart aufgebaut sind, daß sie Mehrpolfelder höherer Ordnung zum zusätzlichen Korrigieren von Treffleckverformungsfehler erzeugen.

2. Kathodenstrahlröhre nach Anspruch 1, dadurch gekennzeichnet, daß die Fokussiereinrichtung ein Joch enthält, das vollständig oder teilweise aus acht gleichen Teilen zusammengesetzt ist, wobei jeder Teil eine Längsspule enthält und die acht Spulen derart mit Energie versorgt werden können, daß sie ein statisches Fokussierfeld erzeugen, dem zum Korrigieren von Astigmatismusfehlern ein Quadrupolfeld überlagert ist.

3. Kathodenstrahlröhre nach Anspruch 1, dadurch gekennzeichnet, daß die acht Spulen zwei Unterspulensysteme bilden, wobei eine erste Gruppe mit einer hohen Impedanz das statische Fokussier-

of an electromagnetic focusing unit. In the alternative case of a permanent magnetic focusing unit it is suggested to place eight radial bar magnets 14 between a divided inner yoke 15 and an undivided outer yoke 16, as shown in Figures 3a and 3b. The inner yoke 15 is divided into eight parts. In this case, two gaps are formed which generate an opposite magnetic field. A coil 17 is wound around each of the bar magnets.

If an equal current is sent through the eight coils 13 in the electromagnetic case a static rotationally symmetrical focusing field is generated. If an extra current I is conveyed through A and A' and the current in the coils C and C' is reduced by I a quadrupole field superimposed upon the rotationally symmetrical focusing field is generated. By controlling the current through the coils B, B', D and D', the quadrupole field can be rotated in any desired direction. It is to be noted that the eight coils may advantageously be constructed so as to form two sub-coil systems, one having a high L value for a fixed adjustment of the focusing field (this system may optionally be replaced by a system of permanent magnets) and one having a low L value for a dynamic drive of the focusing field.

In the case of the permanent magnetic lens 18 (Figure 3B) the static focusing field is made by means of the eight bar magnets 14. If the strength of the focusing lens is to be varied, either an equal current can be sent through all the coils 17, or extra coils may be used which may be provided in the lens.

The quadrupole fields are generated by passing the desired current through the eight coils 17, always two oppositely located coils conveying the same current.

The end in view is reached by the configuration shown namely that the multipole corrections are made in the place where the beam has its largest diameter: in the focusing lens. Herewith it is always achieved that the two functions of focusing and spot correction take place in the same unit.

A multipole correction coil 27 can be switched as is shown in Figure 4. By energization of the supply lines such a quadrupole field can be generated that distortion of the spot is corrected. With equal currents through A-A' and B-B' the quadrupole shown is formed. The required corrections depend on the position of the electron spot on the screen and these currents are hence varied synchronously with the deflection current. The driving may take place both completely analogously and via a digital process (GB-A 2 085 698).

It is to be noted that the multipole coils in the figures are shown with single turns to produce the individual poles, the turns not overlapping each other. However, the invention also relates to the use of multipole coils which show a so-called cosinusoidal distribution of the turns in behalf of an improved homogeneity of the generated multipole field.

Claims

1. A monochrome cathode ray tube comprising at one end an electron gun and at the oppositely locat-

ed end a display screen having a phosphor layer and a deflection unit provided around the neck of the display tube, and a magnetic focusing device which is provided between the electron gun and the deflection unit around the neck of the display tube and which comprises means to generate a static focusing field, characterized in that the means to generate the static focusing field directly adjoin the deflection unit and are constructed so as to generate higher order multipole fields to correct spot distortion errors as well.

2. A cathode ray tube as claimed in Claim 1, characterized in that the focusing device comprises a yoke which is composed entirely or partly of eight equal parts, each part having a longitudinal coil, the eight coils being energizable in such manner as to generate a static focusing field on which a quadrupole field is superimposed to correct for astigmatism errors.

3. A cathode ray tube as claimed in Claim 1, characterized in that the eight coils constitute two sub-coil systems: a first set having a high impedance to generate the static focusing field and a second set having a low impedance to generate a dynamically varying focusing field.

4. A cathode ray tube as claimed in Claim 1, characterized in that the focusing device comprises eight coplanar bar magnets which are ordered to generate a static focusing field, each bar magnet supporting a coil and the eight coils being energizable in such manner as to generate a desired quadrupole field to correct for astigmatism errors.

Patentansprüche

1. Monochrome Kathodenstrahlröhre, die an einem Ende einen Elektronenstrahlerzeuger und an dem gegenüberliegenden Ende einen Wiederabgabeschirm mit einer Leuchtstoffschicht und eine um den Hals der Wiedergaberöhre angeordneten Ablenkeinheit sowie eine magnetische Fokussiereinheit enthält, die zwischen dem Elektronenstrahlerzeuger und der Ablenkeinheit um den Hals der Wiedergaberöhre angeordnet ist und Mittel zum Erzeugen eines statischen Fokussierfelds enthält, dadurch gekennzeichnet, daß die Mittel zum Erzeugen des statischen Fokussierfelds direkt an die Ablenkeinheit grenzen und derart aufgebaut sind, daß sie Mehrpolfelder höherer Ordnung zum zusätzlichen Korrigieren von Treffleckverformungsfehler erzeugen.

2. Kathodenstrahlröhre nach Anspruch 1, dadurch gekennzeichnet, daß die Fokussiereinrichtung ein Joch enthält, das vollständig oder teilweise aus acht gleichen Teilen zusammengesetzt ist, wobei jeder Teil eine Längsspule enthält und die acht Spulen derart mit Energie versorgt werden können, daß sie ein statisches Fokussierfeld erzeugen, dem zum Korrigieren von Astigmatismusfehlern ein Quadrupolfeld überlagert ist.

3. Kathodenstrahlröhre nach Anspruch 1, dadurch gekennzeichnet, daß die acht Spulen zwei Unterspulensysteme bilden, wobei eine erste Gruppe mit einer hohen Impedanz das statische Fokussier-



feld und eine zweite Gruppe mit niedriger Impedanz ein dynamisch sich änderndes Fokussierfeld erzeugt.

4. Kathodenstrahlröhre nach Anspruch 1, dadurch gekennzeichnet, daß die Fokussiereinrichtung acht koplanare Stabmagnete enthält, die zum Erzeugen eines statischen Fokussierfelds angeordnet sind, wobei jeder Stabmagnet eine Spule trägt und die acht Spulen derart mit Energie versorgt werden können, daß sie ein gewünschtes Quadrupolfeld zum Korrigieren von Astigmatismusfehlern erzeugen.

Revendications

1. Tube à rayons cathodiques monochrome comportant à une extrémité un canon électronique et à l'extrémité opposée un écran image muni d'une couche luminescente et une unité de déviation disposée autour du col du tube image, et un dispositif de focalisation magnétique qui est disposé entre le canon électronique et l'unité de déviation autour du col du tube image et qui comporte des moyens pour engendrer un champ de focalisation statique, caractérisé en ce que les moyens servant à engendrer le champ de focalisation statique sont directement contigus à l'unité de déviation et sont réalisés de façon à engendrer des champs multipolaires d'ordre supérieur pour corriger aussi des défauts de distorsion de spot.
2. Tube à rayons cathodiques selon la revendication 1, caractérisé en ce que le dispositif de focalisation comporte une culasse qui est composée entièrement ou partiellement de huit parties égales, chaque partie présentant une bobine longitudinale, les huit bobines pouvant être excitées de façon à engendrer un champ de focalisation statique auquel est superposé un champ quadripolaire pour corriger des défauts d'astigmatisme.
3. Tube à rayons cathodiques selon la revendication 1, caractérisé en ce que les huit bobines constituent deux sous-systèmes de bobines: un premier présentant une impédance élevée pour engendrer le champ de focalisation statique et un second présentant une faible impédance pour engendrer un champ de focalisation variable de façon dynamique.
4. Tube à rayons cathodiques selon la revendication 1, caractérisé en ce que le dispositif de focalisation comporte huit aimants en forme de barre coplanaires qui sont disposés pour engendrer un champ de focalisation statique, chaque aimant en forme de barre supportant une bobine et les huit bobines pouvant être excitées de façon à engendrer un champ quadripolaire désiré pour corriger des défauts d'astigmatisme.

60

65

4



* C L M S *