Device for microbiological analysis

The present invention concerns a device for the microbiological analysis of supports that may contain microorganisms in order to detect the presence or absence of those microorganisms.

One way to analyze such supports consists of detecting the presence of the microorganisms by analysis of the fluorescence emitted by those microorganisms after they have been marked by what are referred to as flurogen or fluorophore markers.

These markers have the particularity of fluorescing only when they have been activated beforehand by an enzyme contained in the microorganisms.

These markers generally comprise a fluorophore group as well as a group capable of concealing or preventing the fluorescence of the fluorophore group from showing. When the microorganisms are present, the effect of the enzyme thereof is to modify that second group in order that the fluorescence of the first group may be detected.

Thus, as illustrated by the spectra 53 and 54 of Figure 7, when the microorganisms so marked are subjected to an appropriate excitation light, the fluorophore group is capable of absorbing light energy with an absorption spectrum 53 of which the crest 53' is at a wavelength λ_2 and of releasing that energy in the form of a characteristic fluorescent emission spectrum 54 of which the crest 54' is at a wavelength λ_3, distinct from λ_2.

For observing the fluorescence emitted by microorganisms in the presence of such markers, and as illustrated in Figure 9, devices (integrated into microscopes) for microbiological analysis are already known comprising illuminating means for emitting the exciting light and of which the spectrum 50 of Gaussian distribution form has a crest 50' at a wavelength λ_1 that is chosen equal to the wavelength λ_2 to excite the fluorophore with sufficient energy in order for it to emit, in the presence of microorganisms, light with its emission spectrum 54.

Such a device is provided with an input filter, disposed between the illuminating means and the support to illuminate, such as band-pass filter of which the spectrum 51 is illustrated in Figure 9, this filter having a very narrow passband centered on the wavelength λ_1 so as to select, given the wide spectral width of the illuminating means corresponding to the spectrum 50, only the wavelength that is useful to excite the fluorophore properly at the desired energy.

This device also comprises a filter disposed between the support to analyze and the zone for viewing the light coming from the support, the filter being illustrated by the spectrum 52 in Figure 9 (here, a band-pass filter of narrow passband centered on the wavelength λ_2), in order only to let pass the light which is emitted by the fluorophore in response to the excitation light, filtered of all the other extraneous wavelengths.

Devices having such an arrangement are for example described in the United States patent US 7,397,602.

The invention concerns the provision of a device for performing, like the device of the prior art, detection of fluorescence but which is both more economical and simpler while providing performance which is as good.

To that end it provides a device for the microbiological analysis of a support adapted to contain microorganisms marked by a fluorophore agent, said agent being adapted, on contact with said microorganisms, to absorb light energy with an absorption spectrum having a crest at a predetermined absorption wavelength (λ_2) and to release that energy by emitting fluorescent light with an emission spectrum having a crest at a predetermined emission wavelength (λ_3) distinct from said absorption wavelength (λ_2), said device comprising illuminating means adapted to illuminate said support in order for said marked microorganisms to emit, in response to the excitation light emitted by those illuminating means, light with said emission spectrum; characterized in that the spectrum of the excitation light coming from the illuminating means comprises a crest at a predetermined excitation wavelength (λ_1) distinct from said absorption (λ_2) and emission (λ_3) wavelengths of said fluorophore agent, such that said absorption wavelength (λ_2) is situated between said excitation

(λ_1) and emission (λ_3) wavelengths with a predetermined difference between the excitation (λ_1) and absorption (λ_2) wavelengths, by virtue of which it is made easy to discriminate the light emitted by said fluorophore agent from that coming from the illuminating means.

The spectral offset between the crests of the excitation and absorption spectra with the absorption wavelength λ_2 which is thus situated between the excitation λ_1 and emission λ_3 wavelengths makes it possible advantageously to situate, between those absorption and emission wavelengths, the portion of the spectrum of the excitation light situated beyond λ_1 in order to obtain light having quite high energy at the wavelength λ_2 to excite the fluorophore such that it emits light by fluorescence and to have small overlap of the excitation spectrum with the emission spectrum at the wavelength λ_3 (and at neighboring wavelengths) in order that the light which comes from the illuminating means and which is reflected on the support to analyze does not cause significant parasitic interference with the light emitted by the fluorophore agent in the presence of microorganisms such that it is made easy to discriminate the light emitted by the fluorophore agent from that coming from the illuminating means.

More particularly, the overlap between the excitation spectrum and the emission spectrum thus being small by virtue of the spectral offset of the device according to the invention, the crest of the emission spectrum of the fluorophore is more detached from the crest of the spectrum of the excitation light and the ratio between the parasite energy at the emission wavelength of the fluorophore (coming from the light emitted by the illuminating means at that wavelength) and the energy actually coming from the fluorescence of the marked microorganisms is considerably improved.

It is thus possible to easily detect on the support the bright points corresponding to the marked microorganisms with sufficient contrast for them to be clearly observable, and in particular with the naked eye.

This spectral offset thus makes it possible, even for illuminating means having a non-negligible spectral dispersion (such as that illustrated by the spectra 50 and 55 in Figures 7 and 9), to dispense with having the input

filter of the prior art devices without it being necessary nevertheless to replace such illuminating means by other illuminating means of which the spectral dispersion is lower (such as a laser for example, which is in general extremely costly).

This thus makes it possible to significantly reduce the manufacturing cost of such a device while minimizing the losses of light energy, since the presence of an input filter, in particular a filter with a narrow passband, necessarily leads to a substantial drop in energy throughput (and thus the quantity of light reaching the support to illuminate) for such a device.

As the light energy lost is less in the device according to the invention, it is thus possible, for the same electrical power consumed, to illuminate larger support surfaces to analyze (such as the surfaces of microporous filter membranes for example) than in the application to the microscope of the device of the prior art.

According to features that are preferred for reasons of simplicity and convenience for both manufacture and use:

- said excitation wavelength (λ_1) is shorter than said absorption wavelength (λ_2), itself shorter than said emission wavelength (λ_3);
- said spectrum of the excitation light comprises a peak of maximum light intensity centered on said excitation wavelength (λ_1);
- the difference between said excitation (λ_1) and absorption (λ_2) wavelengths is less than the difference between said absorption (λ_2) and emission (λ_3) wavelengths of said fluorophore agent;
- said device also comprises a window for viewing the light emitted by said fluorophore agent provided with a filter which is adapted to let the longest wavelengths pass and of which the cut-off wavelength is situated between said absorption wavelength (λ_2) and said emission wavelength (λ_3);
- said illuminating means comprise at least one base on which is mounted at least one group of light sources, with said sources of that group being regularly spaced from each other to form an illuminating array for said support;

- said illuminating means comprise two said bases inclined relative to each other in the direction of a predetermined location for reception of said support in the device;

- each said base is inclined by an angle between 40° and 50° relative to said predetermined location for reception of said support;

- said light sources are light emitting diodes; and/or

- said lighting means comprise a lamp adapted to emit polychromatic light and a filter adapted let pass the smallest wavelengths and of which the cut-off wavelength is situated between said absorption wavelength (λ_2) and said emission wavelength (λ_3).

The features and advantages of the invention will appear from the following description, given by way of preferred but non-limiting example, with reference to the accompanying drawings in which:

- Figure 1 is a diagram of a device according to the invention;

- Figure 2 is a perspective view of that device beside which is represented a filter unit to analyze in the device;

- Figures 3 and 4 are respectively a perspective view taken from below and a section view in elevation taken on a median plane of symmetry of that device;

- Figure 5 is a perspective view of one of the two printed circuit boards of that device on which are fixed two groups of light emitting diodes, each emitting light at a predetermined wavelength;

- Figure 6 is a perspective view of another embodiment of the device according to the invention;

- Figure 7 illustrates the spectral diagrams of different optical members of a device according to the invention as well as the spectral diagram of the fluorophore agent used with that device to mark the microorganisms, with a common scale of wavelengths along the x-axis and a common scale of relative light intensity along the y-axis;

- Figure 8 is a diagram of a part of still another embodiment of the device according to the invention; and

- Figure 9 illustrates spectral diagrams similar to those of Figure 7 but for a device according to the prior art described previously.

A description will now be given of a preferred embodiment of the device according to the invention with the help of Figures 1 to 5, before detailing its mode of operation with the help of the spectral diagrams illustrated in Figure 7.

The device 1 illustrated in Figures 1 to 5 comprises a casing 2, illuminating means 3 formed from two illuminating members 4, a sliding drawer 5 and a viewing window 7.

The casing is of parallelepiped general shape and has an upper wall 10 and four side walls 11 to 14, a portion of wall 14 being deliberately not shown in order to show the interior of the device.

The viewing window 7 is here constituted by a low-pass filter 6 (that is to say that it allows the lowest frequencies to pass, and thus the longest wavelengths), an opening 9 being formed in the upper wall 10 of the casing 2 to receive that filter 6 therein.

As will be seen below, the interior of this casing 2, delimited by the walls 10 to 14 and 30, forms an analysis chamber isolated from the surrounding light and in which the support to analyze is received.

The support to analyze is here a microporous membrane 41 belonging to a filter unit 40, here a unit commercialized by Millipore© under the trademark Milliflex®. This membrane 41 has a diameter of 55 mm and is surrounded by a body 42 of the filter unit.

The membrane 41 used here is of cellulose ester and has a pore size adapted to retain the microorganisms whose presence it is desired to detect, most often between 0.10 and 100 microns.

The drawer 5 has a body 30, a collar 31 and a grasping lug 32.

In the body 30 there is formed a cylindrical cavity 33 provided to receive a filter unit 40.

The illuminating means 3 will now be described with the help of Figures 3 to 5.

These means 3 comprise two separate illuminating members 4.

Each member 4 comprises a mounting 20 of trapezoidal section, a printed circuit board 21 on which two groups 27 and 28 of diodes 22 and 23 are disposed, a diffuser 24 covering those diodes and two black screens 26 between the edges of the board 21 and those of the diffuser 24.

The mountings 20 are fixed inside the casing 2 on the wall 10 of that casing, while the boards 21 are fixed to the mountings 20 on the inclined faces thereof, that are remote from those disposed against the wall 10 such that those boards are inclined towards each other in the direction of the reception zone 33 for the support 41.

Each mounting 20 is thus provided such that each plate 21 has an inclination A (Figure 1) of 45° relative to the wall 10 and to the predetermined location that the membrane 41 occupies, when the unit 40 is in the housing 33 of the device (Figure 1).

The upper edges 25 of the boards 21 are at a distance from each other equal to 100 mm while those edges 25 are at a distance of 23 mm from the wall 10.

The summits of light emitting diodes 22 and 23 are situated at a distance of 15 mm from the diffusers 24.

These diffusers 24 are here made from a plate of glass on which one of the faces is sandblasted (the face which is turned towards the diodes).

On each printed circuit board, and as illustrated in Figure 5, a first group 27 of diodes is disposed, constituted by sixteen diodes 22 as well as a second group 28 of diodes constituted by four diodes 23.

The diodes 22 are regularly spaced from each other and disposed in four equidistant rows of four diodes, such that each diode 22 is situated at a distance of 16 mm from the diodes 22 directly neighboring thereto. This group 27 thus forms an array of diodes making it possible to uniformly illuminate the membrane 41 when it is disposed in the casing 2 at its predetermined location, the center 29 of that array being situated at a height H of 54.75 mm from that predetermined location (Figure 1).

The diodes 23 are distributed in the four corners of a square interlaced in the center of the array of diodes 22, each diode 23 being situated

at a distance of 32 mm from the two diodes 23 neighboring thereto and at the center of a square at the corners of which are situated four diodes 22 (Figure 5). The center of this array coincides with the center 29 of the array constituted by the diodes 22.

The diodes 22 are diodes from the company LUMILED© commercialized under the reference LXHL-PB01 and of which the emission spectrum 55 is illustrated in Figure 7, this spectrum of Gaussian distribution form having a crest 55' at the wavelength λ_1 of 470 nm, thus emitting in blue.

The diodes 23 are diodes from the same company commercialized under the reference LXHL-PD01, of which the emission spectrum, not illustrated in the drawings, is also of Gaussian distribution form and has a crest at the wavelength of 625 nm thus emitting in red.

These diodes have a solid angle of emission of 140° for a relative intensity value of 25% and a solid angle of emission of 90° for a relative intensity value of 60%.

The diodes 23 have an emission power substantially four times greater than that of the diodes 22 such that they are four times less numerous than the diodes 22.

The arrays of diodes 22 and 23 are interlaced (that is to say nested within each other) so as to obtain the most homogenous light possible at the filter unit to be illuminated, whether the light comes from the diodes 22 or from the diodes 23.

Each group of diodes produces a light spectrum centered on a predetermined wavelength so as to be able to excite different predetermined types of fluorophore.

The conductive tracks on each board 21 are electrically linked to a command and control unit for the device (not shown).

The preparation of a sample to analyze will now briefly be described.

Prior to the actual detection step, the operator collects a sample to analyze (which may contain microorganisms) by filtration through a membrane 41 of a unit 40.

Once the microorganisms have been filtered and retained on the membrane, an optional step of growing the microorganisms in contact with an appropriate growth medium may be included. This growth medium is preferably a gel medium on which the membrane is deposited after filtration. This step, which is optional, enables colonies of each of the microorganisms initially filtered to be obtained, which increases the number of cells to detect.

The membrane and the microorganisms that it contains are then placed in contact with a composition for rendering the walls of the microorganisms permeable and the fluorophore markers are then incorporated into the permeable-rendering composition in order to enter the inside of the microorganisms to detect.

A description will now be given of the implementation of the determination of the presence or absence of microorganisms on a sample so prepared on the basis of the device according to the invention.

In a first phase, the drawer 5 is pulled and the operator places a filter unit 40 (which may possibly be covered by a transparent cover not illustrated to protect the membrane from exterior contamination) in the cavity 33 of that drawer. The drawer 5 is then pushed until the collar 31 abuts the wall 13 such that the membrane 41 is disposed in its predetermined location within the casing 2 in order to be illuminated.

Depending on the fluorophore which was used to mark the microorganisms, the operator next selects (for example via a switch not illustrated in the drawings) the corresponding diodes 22 or 23 to turn on (the diodes 22 in the example illustrated) so as to uniformly illuminate the whole of the surface of the membrane 41 and to excite, at the right wavelength, the fluorophore that served for the marking.

The diffusers 24 as well as the spatial distribution of the diodes on the boards 21 make it possible to have a particularly homogenous illumination of the whole surface of the membrane 41, whatever the group of diodes used.

As the boards 21 are disposed one on each side of the opening 9 receiving the filter 6, the light coming from the filter unit 40 which is emitted in response to the excitation light from the diodes passes through that filter as

illustrated in Figure 1 such that it is possible to observe the light response of the membrane 41 through the filter 6, with the naked eye or else via a camera.

The light response obtained in the presence of microorganisms using the different spectral diagrams illustrated in Figure 7 will now be detailed.

In Figure 7, the spectrum 55 is of Gaussian form and corresponds to the spectrum of the excitation light (here the spectrum produced by the diodes 22) and which has a peak of which the crest 55' corresponding to the maximum light intensity value is at the wavelength λ_1 equal to 470 nm.

The spectra 53 and 54 respectively correspond to the absorption spectrum and to the emission spectrum of the fluorophore chosen here to mark the microorganisms present on the membrane.

The fluorophore represented here is 5-6 CFDA (Carboxy-Fluorescein-Di-Acetate).

The absorption spectrum 53 has a crest 53' at the wavelength λ_2 greater than λ_1 and the emission spectrum 54 has a crest 54' at the wavelength λ_3 greater than λ_2.

In the example illustrated λ_2 is equal to 492 nm and λ_3 to 517 nm, the difference between λ_1 and λ_2 here being less than the difference between λ_2 and λ_3.

The excitation wavelength λ_1 is deliberately chosen to be less than λ_2 such that the crest 55' of the spectrum 55 is offset relative to the crest 53' of the spectrum 53, on the opposite side to the spectrum 54. This offset is chosen in order for the light coming from the illuminating means to have sufficient energy to excite the fluorophore without that light causing significant parasitic interference with that emitted by the fluorophore in response to that excitation light.

The spectrum 56 is that of the filter 6 of the viewing window, it cut-off frequency being chosen (here of the order of 550 nm) to let through essentially the light emitted by the fluorophore (spectrum 54) and to stop the light at shorter wavelengths, in particular those coming from the diodes 22 after reflection on the unit 40.

This output filter (a colored filter) is weakly selective to allow a sufficient quantity of light to return to the eyes of the user giving a generally bright scene and which is thus comfortable to observe while ensuring a level of contrast which is adapted for observation with the naked eye.

When the excitation light coming from the illuminating means 3 illuminates the membrane 41 of the filter unit 40, each location of that membrane having microorganisms marked by the fluorophore is rendered visible in the form of a bright spot of small size (a few hundreds of microns) directly observable with the naked eye coming out of the filter 6.

The values of the angle A and of the height H provide an optimum rendering for the reading of the bright spots on the membrane 41, whether with the naked eye or via a camera.

These values have been determined by applying a black mark and a fluorescent yellow mark to a control membrane and by seeking, for different values of that angle A and of that height H, the configurations A, H for which the brightness of the fluorescent band is maximum while minimizing the parasitic brightness on the black mark.

It has thus surprisingly proved that the range [40°-50°] for the angle A gave both a maximum light intensity for the fluorescent mark and practically an absence of parasite light for the black mark, which thus corresponds to an optimum in terms of reading comfort.

So as to have a certain safety margin relative to the play in mounting the device it is thus the average value of 45° which has been chosen here.

As regards the height value H, this is a function of the size of the object to illuminate, the different configurations tested have shown that for a membrane of a diameter of 55 mm and for a value range for the angle A between 40° and 50°, the best results were obtained for a height range between 39.75 and 69.75 mm. Similarly here, it is the average value of 54.75 mm which was chosen in this example.

The device is also adapted, by adjusting the height H, to illuminate types of sample other that membranes, and generally any support adapted to

contain microorganisms (whether on a surface or in a volume) and whose presence it is desired to detect by fluorescence.

Another embodiment of this device is represented in Figure 6.

Generally speaking, the same reference numbers increased by 100 are used for similar parts.

The device 101 has the same features as the device 1 apart from it lacking the drawer 5 (the filter unit 40 here being directly placed on a table for example) and for the fact that the viewing window 107 is here formed from a slide 108 of rectangular form disposed against the wall 110 of the casing 102 and from four filters 106 to 106''', each of the filters being housed in a corresponding opening of the slide 108.

Each optical filter is a low-pass filter, thus allowing the low frequencies to pass (the longest wavelengths) and of which the cut-off frequency is distinct from the other cut-off frequencies.

The slide 108 is engaged in a guide rail (not illustrated) of that device so as to be able to place any chosen one of the four filters 106 to 106''' in register with the opening 109 of the wall 110.

It is thus possible, depending on the fluorophore chosen and on the diodes which are turned on, to select from the four available filters the one which has the most adapted cut-off frequency (to obtain the best contrast for example).

In one embodiment not illustrated, the filter 6 is not a low-pass filter but a band-pass filter of which the passband is centered on the wavelength λ_2.

In still another embodiment illustrated diagrammatically in Figure 8, the crest of the spectrum of the illuminating means does not necessarily have to be localized and thus extends over a larger range of wavelengths by using for example as illuminating means 203, instead of the diodes, a lamp 204 of polychromatic light associated with a high-pass filter 234 adapted allow the highest frequencies to pass, that is to say the shortest wavelengths, which is less costly than the band-pass filter of the prior art and of which the cut-off wavelength λ_c is situated between the absorption wavelength λ_2nd the emission wavelength λ_3 (Figure 8).

Lastly, it will be noted that such an illuminating system may also be produced in different versions for many other applications such as analysis by microscope, scanning of biochips, reading of plates by fluorescence, cytometry, transilluminators, PCR real-time reading, the geometrical configuration of the device for each of these applications then being in a version specific to the application in question. The frame of the device to which the bases 21 are fixed is not necessarily a casing like the casing 2 illustrated; it may for example be a hoop surrounding the optics of a microscope.

The present invention is not limited to the embodiments described and represented, but encompasses any variant form thereof.

CLAIMS

1. A device for microbiological analysis of a support (41) configured to contain microorganisms marked by a fluorophore agent, characterized by the agent being configured to absorb light energy, on contact with the microorganisms, with an absorption wavelength (λ_2), and to release that energy by emitting fluorescent light with an emission spectrum (54) having a crest (54^1) at a predetermined emission wavelength (λ_3) distinct from the absorption wavelength (λ_2); the device being provided with illumination means (3) comprising diodes for generating an excitation light and not comprising a narrow band pass filter; these illumination means being configured so as to illuminate the support (41) in order for the marked microorganisms to emit, in response to the excitation light emitted by the illumination means (3), light with the emission spectrum (54); the spectrum (55) of the excitation light coming from the illumination means (3) comprising a crest (55') at a predetermined excitation wavelength (λ_1) distinct from the absorption (λ_2) and emission (λ_3) wavelengths of the fluorophore agent, such that the absorption wavelength (λ_2) is situated between the excitation (λ_1) and emission (λ_3) wavelengths with a predetermined difference between the excitation (λ_1) and absorption (λ_2) wavelengths, by virtue of which it is made easy to discriminate the light emitted by the fluorophore agent from the light coming from the illumination means (3); the excitation wavelength (λ_1) being shorter than the absorption wavelength (λ_2), the absorption wavelength (λ_2) itself being shorter than the emission wavelength (λ_3), the spectrum (55) of the excitation light comprising a peak (55') of maximum light intensity centered on the excitation wavelength (λ_1), the difference between the excitation wavelength (λ_1) and the absorption wavelength (λ_2) being smaller than the difference between the absorption (λ_2) and emission (λ_3) wavelengths of the fluorophore agent; the predetermined difference between the excitation (λ_1) and absorption (λ_2) wavelengths in the emission wavelength (λ_3) being selected so as to have a small overlap between the excitation spectrum (55) and the emission spectrum (54), so as not to cause parasitic interference between light coming from the illumination means and light generated by the fluorophore agent; provided with windows (7, 107) for viewing light emitted by the fluorophore agent, which is provided with filters (6,106) configured to allow the longest wavelengths to pass through and, moreover, selected so that the cutoff wavelength thereof allows light emitted by the fluorophore agent to pass through and stops the shorter wavelength light coming from the diodes.

2. The device according to claim 1, characterized by the illumination means (3) being provided with at least one base fitted with at least one group (27) of diodes (22), the diodes (22) of the group(s) (27) being positioned at regular intervals from each other to form an illumination array with respect to the support (41).

3. The device according to claim 2, characterized by the illumination means (3) being provided with two of the bases (21) inclined relative to one another in the direction of a predetermined location for reception of the support (41) in the device.

4. The device according to claim 3, characterized by each of the bases (21) being inclined at an angle (A) of 40° to 50° relative to the predetermined position for reception of the support (41).

5. A support (41) configured to contain microorganisms marked by a fluorophore agent, and an assembly including the device described in any one of claims 1-4.