

PATENT SPECIFICATION

(11) 1 542 253

78

1 542 253

- (21) Application No. 18897/76 (22) Filed 7 May 1976
 (23) Complete Specification Filed 9 May 1977
 (44) Complete Specification Published 14 Mar. 1979
 (51) INT. CL.² H01H 37/54
 (52) Index at Acceptance
 H1N 25Y 260 263 280 282 284 290 543
 646 700 704



(54) IMPROVEMENTS IN ELECTRIC SWITCHES

(71) I, JOHN CRAWSHAW TAYLOR, a British subject of 9, Holmfild Park, Ballasalla, near Castletown, Isle of Man, Great Britain, formerly of Edge Lee, Bishops Lane, Buxton, Derbyshire, do hereby declare the invention for which I pray that a patent may be granted to me, and the method by which it is to be performed, to be particularly described in and by the following statement:-

The present invention relates to an electric switch including a thermally responsive bimetallic snap-acting switch actuator.

The present invention is particularly concerned with such switches employing actuators of the type comprising a sheet or strip of flexible bimetallic material having a tongue released therefrom within a peripheral portion, the tongue being connected to the sheet or strip at one end and being free of the sheet or strip at the other end, and the sheet or strip being deformed so as to be movable with changes in temperature between two positions on either side of an intermediate unstable position with a snap-action. Such actuators are described in our British Patent 657434 and our British Patent Application 53847/74 (Serial No. 1542252) and hereinafter will be referred to as being "of the kind described."

The present invention provides an electrical switch including an electrically insulative body member, a pair of electrical terminals mounted on flat portions of one side of the body member, each of the terminals being secured to the body member by means of a pair of integral ears extending from opposite edges of the terminal and crimped about a portion of the body member, one of the terminals mounting a stationary electrical contact, and the other terminal mounting an actuator of the kind described, the actuator carrying a movable electrical contact.

Preferably, said actuator is mounted at the free end of the tongue and the movable

contact is mounted on the peripheral portion of the actuator, or the contact is mounted at the free end of the tongue and the actuator is mounted on the peripheral portion.

The switch provided in accordance with the invention lends itself to automatic assembly as a result of both terminals (which also serve to mount the switch components) being mounted to flat portions of the body member from the same side of the body member and engaging mechanically with the body member. The means whereby the terminals are mounted on the body member is simple and provides some resiliency to resist relaxation of the switch components as a result of heat cycling and/or bending of the terminals which might otherwise loosen the terminals from the body member.

The terminals are preferably formed from strip metal and are generally flat.

With the switch in accordance with the invention, the actuator may be mounted to a terminal preferably by spot welding, before the terminal is mounted on a body member. This has the advantage that there is no switch contact pressure tending to force the actuator out of engagement with the terminal whilst the mounting operation takes place, in contrast to known arrangements where the actuator is mounted to a terminal positioned in a body member. Since the actuator is mounted at only a single point, this makes for simplicity of assembly and also in use there is little heat loss from the actuator to the terminal, thereby making the actuator more sensitive to self heating and hence to currents flowing therethrough.

Whilst the method of crimping the terminals provides some resiliency of the system, since the body member may preferably be made of a thermo-plastics material which material may not be sufficiently resilient to resist forces arising from bending of the terminals, it is preferable to weaken the

50
55
60
65
70
75
80
85
90

terminals adjacent where the terminals extend from the insulative body member to make electrical connection with an external circuit such as by providing an aperture in the terminals whereby if the terminals are bent the terminals tend to bend at the weakened portion and stresses are not transmitted to the crimps.

As a result of mounting the two terminals on one side of the body member with the actuator mounted at a single point with a switch contact on the peripheral portion or on the central tongue of the actuator, it is possible to provide a thin body member and hence a thin overall switch whilst still providing sufficient creepage and clearance distances between the actuator and adjacent parts of the switch having opposite polarity to allow the switch to be used and approved by National Approval Authorities for use in dirty conditions.

A preferred embodiment of the invention will now be described with reference to the accompanying drawings wherein:-

Figure 1 is a plan view of an electric switch according to the invention; and

Figure 2 is a side view of a switch according to the invention.

Referring to the drawings, an electrically insulative thermo-plastics fibre reinforced body 2 rectangular in shape and thin in relation to its other dimensions has two flat portions 4 on one side of the body lying in a common plane on which electrical terminals 6, 8 are positioned. Terminals 6, 8 are formed from strips of brass and ends 10, 12 of the terminals extend from one end of the body and have apertures 10', 12' so that wires may be soldered therein for making electrical connection to an external circuit. Terminals 6, 8 have adjacent the one end of the body small apertures 14, 16 which serve to weaken the terminals in these regions so that bending forces on the terminals arising when the switch is fixed in an external circuit are not transmitted to means securing the terminals to the body, but instead the terminals tend to bend about the weakened regions.

The terminals 6, 8 each have two lateral ear portions 18 extending in opposite directions. Flat body portions 4 have slots 19 extending through to the other side of the body and defining therebetween bar portions 20. In assembly ears 18 are crimped around to encircle bar portions 20 thereby to secure terminals 6, 8 to the body 2. Such crimping provides resilience in the securing of the terminals. An end of terminal 8 mounts a stationary electrical contact 22. The other terminal 6 has an L-shaped end portion 23 with the free end being stepped at 24 and mounting at the free end a bi-metallic thermally responsive snap-acting switch actuator 26. Actuator 26 is of the

type disclosed in our co-pending application 53847/74 (Serial No. 1542252) and comprises a member of sheet bimetal having a generally U-shaped aperture 28 therein defining a tongue 30 free at one end, a peripheral area 32 surrounding said tongue and in relation to which the tongue 30, is centrally disposed having been deformed in a die pressing operation to conform in shape to a die of domed configuration, the domed area being such as to reverse its curvature with a snap action with change in temperature.

The free end of the tongue is spot welded to the end of terminal 6. A movable switch contact 34 is mounted on the periphery 32 of the actuator 26 at a point opposite the free end of the tongue so that under normal conditions the movable contact is in contact with the stationary contact 22.

An integral portion 36 of body 2 extends generally coextensively with the contact carrying end of terminal 8 but on the other side of body 2 and serves as a back stop for actuator 26.

A thin plastics cover is normally provided secured to one end of the body to cover the switch components.

In use of the switch the actuator may be exposed to heat from, for example, an air flow so that when the temperature of the air flow rises above a desired temperature the actuator 26 snap acts to an inverted configuration in which movable contact 34 is disengaged from stationary contact 22, thereby opening the switch.

Alternatively the switch may be used as a current sensitive circuit breaker in which electric current passing through actuator 26 self-heats the actuator above its operating temperature when excess current is present, thereby to disengage contact 34 from contact 22.

In the assembly of the above described switch, stationary contact 22 and actuator 26 are welded to their respective terminals 8, 6 prior to mounting the terminals on the body 2. For the actuator, this has the advantage that there is no switch contact pressure tending to force the actuator out of engagement with the terminal during the welding operation. The terminals can be crimped automatically in a single operation onto the flat portions 4 of the body, which lie in a common plane, with suitable apparatus. A particular advantage in employing crimping to secure the terminals to the body is that there is provided some resiliency in the securing and any relaxation in the thermo-plastics body arising from heat cycling of the switch during use is taken up by the resiliency of the securing means.

For sensing radiant heat, there is a large area of the bi-metallic actuator exposed to incoming radiation. In the construction

5 shown, only the small backstop 36 shields incoming radiation from the actuator. The sensitivity of the actuator is also helped by the small heat conductive capacity of the single weld point terminal: thus the switch has a fast response time to a change in conditions.

10 With both terminals on the same side of the bi-metallic actuator and the contact on the periphery of the actuator, there is provided, despite the thinness of the body 2 and hence the overall switch, adequate creepage and clearance distances between the actuator and adjacent parts of the switch having opposite polarity to allow the switch to be used and approved by National Approval Authorities for use in dirty conditions.

15 The temperature of the assembled switch may be checked automatically and if the operating temperature is higher than that desired, the operating temperature can be adjusted by increasing the switch contact pressure by deforming portion 23 of terminal 10, thereby to lower the operating temperature of the actuator.

WHAT WE CLAIM IS:-

20 1. An electrical switch including an electrically insulative body member, a pair of electrical terminals mounted on flat portions of one side of the body member, each of the terminals being secured to the body member by means of a pair of integral ears extending from opposite edges of the terminal and crimped about a portion of the body

member, one of the terminals mounting a stationary electrical contact, and the other terminal mounting an actuator of the kind described, the actuator carrying a movable electrical contact.

2. A switch as claimed in claim 1 wherein said actuator is mounted at the free end of the tongue and the movable contact is mounted on the peripheral portion of the actuator, or the movable contact is mounted at the free end of the tongue and the actuator is mounted on the peripheral portion.

3. A switch as claimed in claim 2 wherein, in the assembly of the switch, the actuator is mounted to the terminal before the terminal is mounted on the body member.

4. A switch as claimed in any preceding claim wherein the terminals are formed from strip metal.

5. A switch as claimed in any preceding claim wherein the terminals are weakened adjacent where the terminals extend from the body member to make connection with an external electrical circuit.

6. An electrical switch substantially as described with reference to the accompanying drawings.

For the Applicant,
Chartered Patent Agents,
Imperial House,
15-19, Kingsway,
London, WC2.



18

5 shown, only the small backstop 36 shields incoming radiation from the actuator. The sensitivity of the actuator is also helped by the small heat conductive capacity of the single weld point terminal: thus the switch has a fast response time to a change in conditions.

10 With both terminals on the same side of the bi-metallic actuator and the contact on the periphery of the actuator, there is provided, despite the thinness of the body 2 and hence the overall switch, adequate creepage and clearance distances between the actuator and adjacent parts of the switch having opposite polarity to allow the switch to be used and approved by National Approval Authorities for use in dirty conditions.

15 The temperature of the assembled switch may be checked automatically and if the operating temperature is higher than that desired, the operating temperature can be adjusted by increasing the switch contact pressure by deforming portion 23 of terminal 10, thereby to lower the operating temperature of the actuator.

WHAT WE CLAIM IS:-

20 1. An electrical switch including an electrically insulative body member, a pair of electrical terminals mounted on flat portions of one side of the body member, each of the terminals being secured to the body member by means of a pair of integral ears extending from opposite edges of the terminal and crimped about a portion of the body

member, one of the terminals mounting a stationary electrical contact, and the other terminal mounting an actuator of the kind described, the actuator carrying a movable electrical contact.

2. A switch as claimed in claim 1 wherein said actuator is mounted at the free end of the tongue and the movable contact is mounted on the peripheral portion of the actuator, or the movable contact is mounted at the free end of the tongue and the actuator is mounted on the peripheral portion.

3. A switch as claimed in claim 2 wherein, in the assembly of the switch, the actuator is mounted to the terminal before the terminal is mounted on the body member.

4. A switch as claimed in any preceding claim wherein the terminals are formed from strip metal.

5. A switch as claimed in any preceding claim wherein the terminals are weakened adjacent where the terminals extend from the body member to make connection with an external electrical circuit.

6. An electrical switch substantially as described with reference to the accompanying drawings.

For the Applicant,
Chartered Patent Agents,
Imperial House,
15-19, Kingsway,
London, WC2.