




INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification 7 : H04B 7/005		A1	(11) International Publication Number: WO 00/57576
			(43) International Publication Date: 28 September 2000 (28.09.00)
(21) International Application Number: PCT/US00/07556		(81) Designated States: AE, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CR, CU, CZ, DE, DK, DM, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, TZ, UA, UG, US, UZ, VN, YU, ZA, ZW, ARIPO patent (GH, GM, KE, LS, MW, SD, SL, SZ, TZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).	
(22) International Filing Date: 22 March 2000 (22.03.00)			
(30) Priority Data: 60/125,417 22 March 1999 (22.03.99) US 60/136,556 28 May 1999 (28.05.99) US 60/136,557 28 May 1999 (28.05.99) US			
(71) Applicant (for all designated States except US): INTERDIGITAL TECHNOLOGY CORPORATION [US/US]; Suite 527, 300 Delaware Avenue, Wilmington, DE 19801 (US).			
(72) Inventors; and		Published With international search report.	
(75) Inventors/Applicants (for US only): ZEIRA, Ariela [US/US]; 8 Old Oak Road, Trumbull, CT 06611 (US). SHIN, Sung-Hyuk [KR/US]; 1531 8th Street, Fort Lee, NJ 07024 (US). DICK, Steven, G. [US/US]; 61 Bobann Drive, Nesconset, NY 11767 (US).			
(74) Agents: VOLPE, Anthony, S. et al.; Volpe and Koenig, P.C., Suite 400, One Penn Center, 1617 John F. Kennedy Boulevard, Philadelphia, PA 19103 (US).			

(54) Title: OUTER LOOP/WEIGHTED OPEN LOOP POWER CONTROL IN A TIME DIVISION DUPLEX COMMUNICATION SYSTEM



(57) Abstract

Outer loop/weighted open loop power control controls transmission power levels in a spread spectrum time division duplex communication system. A first communication station (110) transmits a communication to a second communication station including target adjustment information generated at the first station on the basis of measured error rates of communications from the second station to the first station. The second station receives the communication and measures its received power level. Based on in part the received communication's power level and the communication's transmission power level, a path loss estimate is determined. A quality of the path loss estimate is also determined. The transmission power level for a communication from the second station to the first station is based on in part weighting the path loss estimate in response to the estimate's quality and based on the receive target adjusted by the target adjustment information transmitted from the first station.