

(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
7 February 2002 (07.02.2002)


PCT

(10) International Publication Number
WO 02/10786 A2

- (51) International Patent Classification⁷: **G01R 33/34** (74) Agents: **CLISE, Timothy, B.** et al.; Schwegman, Lundberg, Woessner & Kluth, P.O. Box 2938, Minneapolis, MN 55402 (US).
- (21) International Application Number: PCT/US01/24040
- (22) International Filing Date: 31 July 2001 (31.07.2001) (81) Designated States (*national*): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, TZ, UA, UG, US, UZ, VN, YU, ZA, ZW.
- (25) Filing Language: English
- (26) Publication Language: English
- (30) Priority Data: 60/222,144 31 July 2000 (31.07.2000) US
- (71) Applicant (*for all designated States except US*): **RE-AGENTS OF THE UNIVERSITY OF MINNESOTA** [US/US]; 450 McNamara Alumni Center, 200 Oak Street S.E., Minneapolis, MN 55455-2070 (US).
- (72) Inventors: **VAUGHAN, Thomas, J.** [US/US]; 504 South Fifth Street, Stillwater, MN 55082 (US). **ADRIANY, Gregor** [DE/US]; 139 Cecil Street S.E., Minneapolis, MN 55414 (US). **UGURBIL, Kamil** [US/US]; 2812 Benton Boulevard, Minneapolis, MN 55416 (US).
- (84) Designated States (*regional*): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).
- Published:**
— *without international search report and to be republished upon receipt of that report*

[Continued on next page]

(54) Title: RADIO FREQUENCY MAGNETIC FIELD UNIT



(57) Abstract: An apparatus comprises a radio frequency magnetic field unit to generate a desired magnetic field. In one embodiment, the radio frequency magnetic field unit includes a first aperture that is substantially unobstructed and a second aperture contiguous to the first aperture. In an alternative embodiment, the radio frequency magnetic field unit includes a first side aperture, a second side aperture and one or more end apertures. In one embodiment of a method, a current element is removed from a radio frequency magnetic field unit to form a magnetic field unit having an aperture. In an alternative embodiment, two current elements located opposite from one another in a radio frequency magnetic field unit are removed to form a magnetic field unit having a first side aperture and a second side aperture.



For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.