

TITLE

**EARTH-BORING TOOLS AND METHODS OF FORMING
SUCH EARTH-BORING TOOLS**

5

PRIORITY CLAIM

This application claims the benefit of the filing date of United States Patent Application Serial Number 13/101,840, filed May 5, 2011, for "EARTH-BORING TOOLS AND METHODS OF FORMING SUCH EARTH-BORING TOOLS." The
10 subject matter of this application is related to the subject matter of U.S. Application Serial No. 12/793,396 filed June 3, 2010, to Lyons et al. and U.S. Application Serial No. 13/022,288 filed February 7, 2011, to Lyons et al.

TECHNICAL FIELD

15 Embodiments of the disclosure relate generally to earth-boring tools and methods of forming earth-boring tools. Specifically, embodiments of the disclosure relate to earth-boring tools having only shearing cutting elements attached to at least one blade and only gouging cutting elements attached to at least another blade.

20

BACKGROUND

Earth-boring tools for forming wellbores in subterranean earth formations may include a plurality of cutting elements secured to a body. For example, fixed-cutter earth-boring rotary drill bits (also referred to as "drag bits") include a plurality of cutting elements that are fixedly attached to a bit body of the drill bit,
25 conventionally in pockets formed in blades and other exterior portions of the bit body. Rolling cone earth-boring drill bits include a plurality of cones attached to bearing pins on legs depending from a bit body. The cones may include cutting elements (sometimes called "teeth") milled or otherwise formed on the cones, which may include hardfacing on the outer surfaces of the cutting elements, or the cones
30 may include cutting elements (sometimes called "inserts") attached to the cones, conventionally in pockets formed in the cones.

The cutting elements used in such earth-boring tools often include polycrystalline diamond cutters (often referred to as "PDCs"), which are cutting elements that include a polycrystalline diamond (PCD) material. Such

polycrystalline diamond cutting elements are formed by sintering and bonding together relatively small diamond grains or crystals under conditions of high temperature and high pressure in the presence of a catalyst (such as, for example, cobalt, iron, nickel, or alloys and mixtures thereof) to form a layer of polycrystalline diamond material on a cutting element substrate. These processes are often referred to as high temperature/high pressure (or "HTHP") processes. The cutting element substrate may comprise a cermet material (*i.e.*, a ceramic-metal composite material) comprising a plurality of particles of hard material in a metal matrix, such as, for example, cobalt-cemented tungsten carbide. In such instances, catalyst material in the cutting element substrate may be drawn into the diamond grains or crystals during sintering and catalyze formation of a diamond table from the diamond grains or crystals. In other methods, powdered catalyst material may be mixed with the diamond grains or crystals prior to sintering the grains or crystals together in an HTHP process.

The working surface, sometimes called the cutting face, of cutting elements may have various shapes, such as, for example, planar, hemispherical, conic, and chisel-shaped. Conventionally, cutting elements having a planar working surface may remove an underlying earth formation using a shearing cutting mechanism. By contrast, cutting elements having dome-shaped, conic, and chisel-shaped working surfaces conventionally remove an underlying earth formation using a crushing and gouging cutting mechanism. Furthermore, cutting elements having a plow-shaped working surface conventionally remove an underlying earth formation using a plowing cutting mechanism.

Various earth-boring drill bits that employ a combination of shearing, gouging, and/or plowing cutting elements have been proposed. As disclosed in U.S. Application Publication No. 2008/0173482 published July 24, 2008 to Hall et al., a blade on a fixed-cutter drill bit may include both shearing cutting elements located in at least a shoulder region of the drill bit and cutting elements having a pointed geometry located in cone and nose regions of the drill bit. In addition, Hall discloses fixed-cutter drill bits having exclusively cutting elements having a pointed geometry attached to the blades thereof. U.S. Application Serial No. 12/793,396 filed June 3, 2010, to Lyons et al., discloses that shearing cutting elements and gouging cutting elements may be disposed adjacent one another on a common blade of a fixed-cutter

drill bit in various regions (*e.g.*, the cone region, the nose region, and the shoulder region). U.S. Application Serial No. 13/022288 filed February 7, 2011 to Lyons et al., discloses that gouging cutting elements may be disposed rotationally following shearing cutting elements (known in the art as a backup cutting element configuration) on a common blade of a fixed-cutter drill bit. U.K. Application Publication No. 2,086,451 published May 12, 1982 to Christensen, Inc., discloses a fixed-cutter drill bit having only cutting elements with a planar cutting face on some blades and only cutting elements having a divided cutting face at a mutual angle of less than 180° on other blades. The cutting elements with a divided cutting face engrave furrows (*i.e.*, plow) into the formation being drilled.

BRIEF DESCRIPTION OF THE DRAWINGS

While the specification concludes with claims particularly pointing out and distinctly claiming that which is regarded as the present invention, various features and advantages of embodiments of the disclosure may be more readily ascertained from the following description of embodiments of the disclosure when read in conjunction with the accompanying drawings, in which:

FIG. 1 is a perspective view of an earth-boring tool having shearing cutting elements attached to a greater number of blades than a number of blades to which gouging cutting elements are attached;

FIG. 2 depicts a plan view of the face of the earth-boring tool of FIG. 1;

FIG. 2A is a plan view of an alternate configuration for the face shown in FIG. 2;

FIG. 3 illustrates a plan view of a face of an earth-boring tool having gouging cutting elements attached to only one blade;

FIG. 4 is a plan view of a face of an earth-boring tool having three blades to which cutting elements are attached;

FIG. 5 depicts a plan view of a face of an earth-boring tool having five blades to which cutting elements are attached;

FIGS. 6A through 6D are simplified, schematic plan views of cutting paths for cutting elements attached to earth-boring tools;

FIG. 7 illustrates a perspective view of an earth-boring tool having gouging cutting elements attached to a greater number of blades than a number of blades to which shearing cutting elements are attached;

FIG. 8 is a plan view of the face of the earth-boring tool of FIG. 6;

5 FIG. 9 depicts a plan view of a face of an earth-boring tool having shearing cutting elements attached to only one blade;

FIG. 10 illustrates a plan view of an earth-boring tool having three blades to which cutting elements are attached;

10 FIG. 11 is a plan view of an earth-boring tool having five blades to which cutting elements are attached;

FIGS. 12A through 12D are simplified, schematic plan views of cutting paths for cutting elements attached to earth-boring tools;

FIG. 13 depicts a simplified cross-sectional view of a gouging cutting element and a shearing cutting element engaging an underlying earth formation;

15 FIGS. 14 through 19 illustrate cross-sectional views of gouging cutting elements that may be attached to an earth-boring tool; and

FIGS. 20 and 21 are cross-sectional views of shearing cutting elements that may be attached to an earth-boring tool.

20 MODE(S) FOR CARRYING OUT THE INVENTION

The illustrations presented herein are not meant to be actual views of any particular earth-boring tool or cutting element, but are merely idealized representations that are employed to describe the embodiments of the disclosure. Additionally, elements common between figures may retain the same or similar
25 numerical designation.

Embodiments of the disclosure relate to earth-boring tools having only shearing cutting elements attached to at least one blade and only gouging cutting elements attached to at least another blade. In some embodiments, a number of blades to which only shearing cutting elements are attached may be greater than a
30 number of blades to which only gouging cutting elements are attached. In other embodiments, a number of blades to which only gouging cutting elements are attached may be greater than a number of blades to which only shearing cutting elements are attached.

The terms “earth-boring tool” and “earth-boring drill bit,” as used herein, mean and include any type of bit or tool used for drilling during the formation or enlargement of a wellbore in a subterranean formation and include, for example, fixed-cutter bits, fixed-cutter core bits, fixed-cutter eccentric bits, fixed-cutter bicenter bits, hybrid bits, as well as fixed-cutter reamers, mills, and other fixed cutter drilling bits and tools known in the art.

As used herein, the term “polycrystalline material” means and includes any structure comprising a plurality of grains (*i.e.*, crystals) of material (*e.g.*, superabrasive material) that are bonded directly together by inter-granular bonds.

10 The crystal structures of the individual grains of the material may be randomly oriented in space within the polycrystalline material.

As used herein, the terms “inter-granular bond” and “interbonded” mean and include any direct atomic bond (*e.g.*, covalent, metallic, *etc.*) between atoms in adjacent grains of superabrasive material.

15 As used herein, the term “superabrasive material” means and includes any material having a Knoop hardness value of about 3,000 Kg/mm² (29,420 MPa) or more. Superabrasive materials include, for example, diamond and cubic boron nitride. Superabrasive materials may also be characterized as “superhard” materials.

As used herein, the term “tungsten carbide” means any material composition

20 that contains chemical compounds of tungsten and carbon, such as, for example, WC, W₂C, and combinations of WC and W₂C. Tungsten carbide includes, for example, cast tungsten carbide, sintered tungsten carbide, and macrocrystalline tungsten carbide.

As used herein, the term “shearing cutting element” means and includes any

25 cutting element having a primary cutting mechanism that involves shearing an underlying earth formation.

As used herein, the term “gouging cutting element” means and includes any cutting element having a primary cutting mechanism that involves gouging or crushing an underlying earth formation.

30 Referring to FIG. 1, an earth-boring tool 10 having only shearing cutting elements 12 attached to a greater number of blades 14 than a number of blades 14 to which only gouging cutting elements 16 are attached is shown. The earth-boring tool 10 comprises a bit body 18 and a plurality of radially extending blades 14

disposed at a face 20 thereof. The blades 14 may also extend longitudinally from the face 20 toward an end of the bit body 18 opposing the face 20, at which a shank 22 configured for attachment to a drill string may be disposed. The blades 14 may terminate at a gage region 24. Nozzles 26 located between the blades 14 may provide an outlet for drilling fluid, which may aid in removing cuttings and in cooling the earth-boring tool 10 and the components thereof. The nozzles 26 may be disposed in fluid courses 28 between the blades 14, and the fluid courses 28 may extend to junk slots 30 proximate the gage region 24.

Referring to FIG. 2, a plan view of the face 20 of the earth-boring tool 10 of FIG. 1 is shown. Some components, such as the nozzles 26 (see FIG. 1), have been omitted for the sake of simplicity. The total number of blades 14 extending from the body 18 of the earth-boring tool 10 may be even. For example, six blades 14 may extend from the body 18 of the earth-boring tool 10. Only shearing cutting elements 12 may be attached to a greater number of blades 14 than a number of blades 14 to which only gouging cutting elements 16 are attached. For example, only gouging cutting elements 16 may be attached to two blades 14 extending from the body 18 of the earth-boring tool 10. Thus, only shearing cutting elements 12 may be attached to at least three blades 14 extending from the body 18 of the earth-boring tool 10, and may be attached to each of the remaining four blades 14 where the total number of blades 14 is six. In other embodiments, only gouging cutting elements 16 may be attached to greater than two blades 14 extending from the body 18 of the earth-boring tool 10. In such embodiments, only shearing cutting elements 12 may be attached to greater than three blades 14 extending from the body 18 of the earth-boring tool 10.

The blades 14 extending from the body 18 of the earth-boring tool 10 may be disposed at angular positions that are spaced at least substantially equally apart. Locating the blades 14 at angular positions that are spaced at least substantially equally apart may aid in balancing the loads placed on the blades 14. For example, where the total number of blades 14 is six, each blade 14 may be about 60° from the blades 14 adjacent to it. Thus, both a rotationally leading and a rotationally following blade 14 may be about 60° from any selected blade 14 where the total number of blades 14 is six. The blades 14 to which only gouging cutting elements 16 are attached may be located at angular positions that are spaced at least

substantially equally from one another. Thus, where gouging cutting elements 16 are attached to two blades 14 and the total number of blades 14 is even, the blades 14 to which the gouging cutting elements 16 are attached may be located about 180° apart.

5 In some embodiments, it may be undesirable to dispose blades 14 at angular positions that are spaced exactly equally apart. For example, it is believed that spacing all the blades 14 of an earth-boring tool 10 exactly equally apart in terms of angular position may cause the resulting earth-boring tool 10 to become unstable. Thus, the blades 14 may be deliberately disposed at angular positions that are not
10 spaced exactly equally apart. For example, each blades 14 may be disposed at an angular position that is $\pm 1^\circ$, $\pm 5^\circ$, $\pm 10^\circ$, $\pm 15^\circ$, $\pm 20^\circ$, $\pm 30^\circ$, or even more or less from a location that would have placed the blades 14 exactly equally apart in some embodiments. Thus, when it is said that the blades 14 may be spaced “at least substantially equally apart” or are located “about” some number of degrees apart,
15 what is meant is that the blades 14 may be deliberately displaced from a location that would have placed the blades 14 exactly equally apart.

As a specific, non-limiting example, blades 14 to which only gouging cutting elements 16 are attached may be located at angular positions that are closer to immediately rotationally leading blades 14 to which only shearing cutting
20 elements 12 are attached than if all the blades 14 were spaced exactly equally apart, as depicted in FIG. 2A. The blades 14 to which only gouging cutting elements 16 are attached may be about 15° closer to the blades 14 to which only shearing cutting elements 12 are attached that immediately rotationally lead the blades 14 to which only gouging cutting elements 16 are attached. In such an example, the relative
25 proximity of the gouging cutting elements 16 to the shearing cutting elements 12 may enable the different cutting elements 12 and 16 to better balance the loading placed on each based on the application and/or the formation being drilled. Further, such a configuration may enable cuttings to be more easily removed from the cutting elements 12 and 16 and the blades 14 to which they are attached, thus reducing
30 balling of the cuttings that may otherwise occur. In addition, the gouging cutting elements 16 may limit the depth of cut of the shearing cutting elements 12, which may be desirable in embodiments where the shearing cutting elements 12 are oriented at aggressive back rake angles (*e.g.*, at low negative back rake angles, at a

neutral back rake angle, and at positive back rake angles). In other embodiments, however, the blades 14 may be disposed at angular positions that are spaced exactly equally apart.

5 Locating the blades 14 to which only gouging cutting elements 16 are attached at angular positions that are spaced at least substantially equally from one another may mean that a maximum possible number of blades 14 to which only shearing cutting elements 12 are attached are interposed between the blades 14 to which only gouging cutting elements 16 are attached. Thus, the number of blades 14 to which only shearing cutting elements 12 are attached on one side of a
10 blade 14 to which only gouging cutting elements 16 are attached may be equal to the number of blades 14 to which only shearing cutting elements 12 are attached on the other side of the blade 14 to which only gouging cutting elements 16 are attached in some embodiments. For example, where the total number of blades 14 is six and the number of blades 14 to which only gouging cutting elements 16 are attached is three,
15 one blade 14 to which only shearing cutting elements 12 are attached may be interposed between each rotationally adjacent pair of blades 14 to which only gouging cutting elements 16 are attached. In such an example, the blades 14 to which only gouging cutting elements 16 are attached may be located about 120° apart.

20 Referring to FIG. 3, a plan view of a face 20 of another earth-boring tool 10 is shown. The total number of blades 14 extending from the body 18 of the earth-boring tool 10 may be even. For example, six blades 14 may extend from the body 18 of the earth-boring tool 10. Only shearing cutting elements 12 may be attached to a greater number of blades 14 than a number of blades 14 to which only
25 gouging cutting elements 16 are attached. For example, only gouging cutting elements 16 may be attached to one blade 14 extending from the body 18 of the earth-boring tool 10. Thus, only shearing cutting elements 12 may be attached to at least two blades 14 extending from the body 18 of the earth-boring tool 10, and may be attached to each of the remaining five blades 14 where the total number of
30 blades 14 is six.

The blades 14 extending from the body 18 of the earth-boring tool 10 may be disposed at angular positions that are spaced at least substantially equally apart. For example, where the total number of blades 14 is six, each blade 14 may be about 60°

from the blades 14 adjacent to it. Thus, both a rotationally leading and a rotationally following blade 14 may be about 60° from any selected blade 14 where the total number of blades 14 is six.

Referring to FIG. 4, a plan view of a face 20 of yet another earth-boring tool 10 is shown. The total number of blades 14 extending from the body 18 of the earth-boring tool 10 may be odd. For example, three blades 14 may extend from the body 18 of the earth-boring tool 10. Only shearing cutting elements 12 may be attached to a greater number of blades 14 than a number of blades 14 to which only gouging cutting elements 16 are attached. For example, only gouging cutting elements 16 may be attached to one blade 14 extending from the body 18 of the earth-boring tool 10. Thus, only shearing cutting elements 12 may be attached to at least two blades 14 extending from the body 18 of the earth-boring tool 10, and may be attached to each of the remaining two blades 14 where the total number of blades 14 is three.

The blades 14 extending from the body 18 of the earth-boring tool 10 may be disposed at angular positions that are spaced at least substantially equally apart. For example, where the total number of blades 14 is three, each blade 14 may be about 120° from the blades 14 adjacent to it. Thus, both a rotationally leading and a rotationally following blade 14 may be about 120° from any selected blade 14 where the total number of blades 14 is three.

Referring to FIG. 5, a plan view of a face 20 of still another earth-boring tool 10 is shown. The total number of blades 14 extending from the body 18 of the earth-boring tool 10 may be odd. For example, five blades 14 may extend from the body 18 of the earth-boring tool 10. Only shearing cutting elements 12 may be attached to a greater number of blades 14 than a number of blades 14 to which only gouging cutting elements 16 are attached. For example, only gouging cutting elements 16 may be attached to two blades 14 extending from the body 18 of the earth-boring tool 10. Thus, only shearing cutting elements 12 may be attached to at least three blades 14 extending from the body 18 of the earth-boring tool 10, and may be attached to each of the remaining three blades 14 where the total number of blades 14 is five. In other embodiments, only gouging cutting elements 16 may be attached to greater than two blades 14 extending from the body 18 of the earth-boring tool 10. In such embodiments, only shearing cutting elements 12 may

be attached to greater than three blades 14 extending from the body 18 of the earth-boring tool 10.

The blades 14 extending from the body 18 of the earth-boring tool 10 may be disposed at angular positions that are spaced at least substantially equally apart. For example, where the total number of blades 14 is five, each blade 14 may be about 72° from the blades 14 adjacent to it. Thus, both a rotationally leading and a rotationally following blade 14 may be about 72° from any selected blade 14 where the total number of blades 14 is five. The blades 14 to which only gouging cutting elements 16 are attached may be located at angular positions that are spaced at least substantially equally from one another. Thus, where only gouging cutting elements 16 are attached to two blades 14 and the total number of blades 14 is five, the blades 14 to which only gouging cutting elements 16 are attached may be located about 144° apart in a direction of rotation of the earth-boring tool 10 and may be located about 216° apart in a direction opposing rotation of the earth-boring tool 10.

Locating the blades 14 to which only gouging cutting elements 16 are attached at angular positions that are spaced at least substantially equally from one another may mean that a maximum possible number of blades 14 to which only shearing cutting elements 12 are attached is interposed between the blades 14 to which only gouging cutting elements 16 are attached. Thus, the number of blades 14 to which only shearing cutting elements 12 are attached on one side of a blade 14 to which only gouging cutting elements 16 are attached may not be equal to the number of blades 14 to which only shearing cutting elements 12 are attached on the other side of the blade 14 to which only gouging cutting elements 16 are attached in some embodiments. For example, where the total number of blades 14 is seven and the number of blades 14 to which only gouging cutting elements 16 are attached is two, three blades 14 to which only shearing cutting elements 12 are attached may be interposed between the blades 14 to which only gouging cutting elements 16 are attached on one side and two blades 14 to which only shearing cutting elements 12 are attached may be interposed between the blades 14 to which only gouging cutting elements 16 are attached on the other side. In such an example, the blades 14 to which only gouging cutting elements 16 are attached may be located about 206° apart on the one side and may be located about 154° apart on the other side.

Attaching only shearing cutting elements 12 to a greater number of blades 14 than a number of blades 14 to which only gouging cutting elements 16 are attached on an earth-boring tool 10, such as, for example, any of the earth-boring tools 10 shown in FIGS. 1 through 5, may improve the performance of the earth-boring tool 10 particularly in mixed formations. For example, where an earth formation to be drilled includes at least some relatively soft regions, such as, for example, regions of sand, shale, or clay, and at least some relatively hard regions, such as, for example, regions of hard limestone, hard sandstone, dolomite, or anhydrite, attaching some cutting elements that remove the underlying earth formation using primarily a shearing cutting mechanism (*i.e.*, shearing cutting elements 12) and attaching some other cutting elements that remove the underlying earth formation using primarily a gouging or crushing cutting mechanism (*i.e.*, gouging cutting elements 16) may improve the efficiency of the earth-boring tool 10, may prevent damage to the earth-boring tool 10, and may more effectively distribute loads placed on the earth-boring tool 10. As a specific, non-limiting example, where a projected drilling path passes primarily through relatively soft earth formations and at least one relatively hard formation, the gouging cutting elements 16 may provide enhanced earth removal within the relatively hard formation and may reduce the wear that would otherwise occur on the shearing cutting elements 12. Thus, the gouging cutting elements 16 may enable an earth-boring tool 10 to drill more efficiently through a formation than if only shearing cutting elements 12 were attached to the earth-boring tool 10.

Referring to FIG. 6A, a rotationally leading shearing cutting element 12 and a rotationally following gouging cutting element 16 are shown. Though the cutting elements 12 and 16 may travel in a spiral (*e.g.*, helical) path when rotating in a borehole, the cutting elements 12 and 16 are illustrated with a linear path 17 for the sake of simplicity. As shown in FIG. 6A, a rotationally following gouging cutting element 16 may cut a kerf, also known in the art as a swath or groove, the center of which is at least substantially aligned with the center of the kerf of the rotationally leading shearing cutting element 12. Thus, each rotationally following gouging cutting element 16 attached to an earth-boring tool 10 (see FIGS. 1 through 5) may be at least substantially aligned with a corresponding rotationally leading shearing cutting element 12 in some embodiments. Such a cutting element configuration may

increase the stability of the earth-boring tool 10 (see FIGS. 1 through 5) to which the cutting elements 12 and 16 are attached and render the earth-boring tool 10 (see FIGS. 1 through 5) self-centering (*i.e.*, able to drill an at least substantially vertical borehole). In some embodiments, the cutting elements 12 and 16 may have equal or differing exposures (*i.e.*, the distance the cutting elements 12 and 16 extend above the blades 14 to which they are attached) and may have equal or differing backrake and siderake angles.

Referring to FIG. 6B, a rotationally leading shearing cutting element 12 and a rotationally following gouging cutting element 16 are shown. As shown in FIG. 6B, a rotationally following gouging cutting element 16 may cut a kerf, the center of which is offset from the center of the kerf of the rotationally leading shearing cutting element 12. Such a cutting element configuration may improve borehole cutting element coverage of the earth-boring tool 10 (see FIGS. 1 through 5) to which the cutting elements 12 and 16 are attached, which may be advantageous in applications where off-center rotation is necessary, such as, for example, in directional drilling, and cause the earth-boring tool 10 (see FIGS. 1 through 5) to wander (*i.e.*, drill a non-linear, such as, for example, helical, borehole). Up to one half of the diameter of the rotationally following gouging cutting element 16 may extend beyond the side of the rotationally leading shearing cutting element 12 in some embodiments. In some embodiments, the cutting elements 12 and 16 may have equal or differing exposures (*i.e.*, the distance the cutting elements 12 and 16 extend above the blades 14 to which they are attached) and may have equal or differing backrake and siderake angles.

Referring to FIG. 6C, a rotationally leading shearing cutting element 12 and a rotationally following gouging cutting element 16 are shown. As shown in FIG. 6C, a rotationally following gouging cutting element 16 may cut a kerf, the center of which is offset from the center of the kerf of the rotationally leading shearing cutting element 12. Greater than one half of the diameter of the rotationally following gouging cutting element 16 may extend beyond the side of the rotationally leading shearing cutting element 12 in some embodiments. In some embodiments, the cutting elements 12 and 16 may have equal or differing exposures (*i.e.*, the distance the cutting elements 12 and 16 extend above the blades 14 to which they are attached) and may have equal or differing backrake and siderake angles.

Referring to FIG. 6D, a rotationally leading shearing cutting element 12 and a rotationally following gouging cutting element 16 are shown. As shown in FIG. 6D, a rotationally following gouging cutting element 16 may cut a groove, the center of which is offset from the center of the groove of the rotationally leading shearing cutting element 12. None of the groove cut by the rotationally following gouging cutting element 16 may overlap with the groove cut by the rotationally leading shearing cutting element 12 in some embodiments. In some embodiments, the cutting elements 12 and 16 may have equal or differing exposures (*i.e.*, the distance the cutting elements 12 and 16 extend above the blades 14 to which they are attached) and may have equal or differing backrake and siderake angles.

Referring to FIG. 7, an earth-boring tool 10' having only gouging cutting elements 16 attached to a greater number of blades 14 than a number of blades 14 to which only shearing cutting elements 12 are attached is shown. The earth-boring tool 10' comprises a bit body 18 and a plurality of radially extending blades 14 disposed at a face 20 thereof. The blades 14 may also extend longitudinally from the face 20 toward an end of the bit body 18 opposing the face 20, at which a shank 22 configured for attachment to a drill string may be disposed, to a gage region 24. Nozzles 26 between the blades 14 may provide an outlet for drilling fluid, which may aid in removing cuttings and in cooling the earth-boring tool 10' and the components thereof. The nozzles 26 may be disposed in fluid courses 28 between the blades 14, and the fluid courses 28 may extend to junk slots 30 proximate the gage region 24.

Referring to FIG. 8, a plan view of the face 20 of the earth-boring tool 10' of FIG. 6 is shown. Some components, such as the nozzles 26 (see FIG. 6), have been omitted for the sake of simplicity. The total number of blades 14 extending from the body 18 of the earth-boring tool 10' may be even. For example, six blades 14 may extend from the body 18 of the earth-boring tool 10'. Only gouging cutting elements 16 may be attached to a greater number of blades 14 than a number of blades 14 to which only shearing cutting elements 12 are attached. For example, only shearing cutting elements 12 may be attached to two blades 14 extending from the body 18 of the earth-boring tool 10'. Thus, only gouging cutting elements 16 may be attached to at least three blades 14 extending from the body 18 of the earth-boring tool 10', and may be attached to each of the remaining four blades 14

where the total number of blades 14 is six. In other embodiments, only shearing cutting elements 12 may be attached to greater than two blades 14 extending from the body 18 of the earth-boring tool 10'. In such embodiments, only gouging cutting elements 16 may be attached to greater than three blades 14 extending from the
5 body 18 of the earth-boring tool 10'.

The blades 14 extending from the body 18 of the earth-boring tool 10' may be disposed at angular positions that are spaced at least substantially equally apart. Locating the blades 14 at angular positions that are spaced at least substantially
10 equally apart may aid in balancing the loads placed on the blades 14. For example, where the total number of blades 14 is six, each blade 14 may be about 60° from the blades 14 adjacent to it. Thus, both a rotationally leading and a rotationally following blade 14 may be about 60° from any selected blade 14 where the total
number of blades 14 is six. The blades 14 to which only shearing cutting elements 12 are attached may be located at angular positions that are spaced at least
15 substantially equally from one another. Thus, where only shearing cutting elements 12 are attached to two blades 14 and the total number of blades 14 is even, the blades 14 to which only shearing cutting elements 12 are attached may be
located about 180° apart.

Locating the blades 14 to which only shearing cutting elements 12 are
20 attached at angular positions that are spaced at least substantially equally from one another may mean that a maximum possible number of blades 14 to which only gouging cutting elements 16 are attached are interposed between the blades 14 to
which only shearing cutting elements 12 are attached. Thus, the number of
blades 14 to which only gouging cutting elements 16 are attached on one side of a
25 blade 14 to which only shearing cutting elements 12 are attached may be equal to the
number of blades 14 to which only gouging cutting elements 16 are attached on the
other side of the blade 14 to which only shearing cutting elements 12 are attached in
some embodiments. For example, where the total number of blades 14 is seven and
the number of blades 14 to which only shearing cutting elements 12 are attached is
30 three, one blade 14 to which only gouging cutting elements 16 are attached may be
interposed between each rotationally adjacent pair of blades 14 to which only
shearing cutting elements 12 are attached. In such an example, the blades 14 to

which only shearing cutting elements 12 are attached may be located about 120° apart.

Referring to FIG. 9, a plan view of a face 20 of another earth-boring tool 10' is shown. The total number of blades 14 extending from the body 18 of the earth-boring tool 10' may be even. For example, six blades 14 may extend from the body 18 of the earth-boring tool 10'. Only gouging cutting elements 16 may be attached to a greater number of blades 14 than a number of blades 14 to which only shearing cutting elements 12 are attached. For example, only shearing cutting elements 12 may be attached to one blade 14 extending from the body 18 of the earth-boring tool 10'. Thus, only gouging cutting elements 16 may be attached to at least two blades 14 extending from the body 18 of the earth-boring tool 10', and may be attached to each of the remaining five blades 14 where the total number of blades 14 is six.

The blades 14 extending from the body 18 of the earth-boring tool 10' may be disposed at angular positions that are spaced at least substantially equally apart. For example, where the total number of blades 14 is six, each blade 14 may be about 60° from the blades 14 adjacent to it. Thus, both a rotationally leading and a rotationally following blade 14 may be about 60° from any selected blade 14 where the total number of blades 14 is six.

In some embodiments, at least one of the blades 14 to which only gouging cutting elements 16 are attached may be canted to extend in a direction that forms an oblique angle θ with a line tangent at a point of intersection 34 of a central axis 36 of the blade 14 with a radially outer surface 32 of the bit body 18 from which the blade 14 protrudes. For example, at least one of the five blades 14 to which only gouging cutting elements 16 are attached may extend in a direction that forms an oblique angle θ with a line tangent to the radially outer surface 32 of the bit body 18. Thus, others of the blades 14 to which only gouging cutting elements 16 are attached may extend in a direction perpendicular to a line tangent to the radially outer surface 32 of the bit body 18. The oblique angle θ at which the blades 14 may be canted may be greater than 45° and less than 90°, for example. As specific, non-limiting examples, the oblique angle θ may be about 60°, about 70°, or about 80°. In some embodiments, the oblique angles θ at which each of the blades 14 to which only gouging cutting elements 16 are attached may be at least substantially

equal. In other embodiments, at least one blade 14 may be canted at an oblique angle θ that is different (e.g., greater than or smaller than) the oblique angle θ at which at least another blade 14 is canted. For example, each blade 14 may be canted at a unique oblique angle θ that is different from the oblique angle θ at which each other blade 14 is canted. Canting the blades 14 to which only gouging cutting elements 16 are attached may enable cuttings that have been removed from an underlying earth formation to more effectively be flushed from the gouging cutting elements 16 and the blades 14 to which they are attached. Thus, balling (*i.e.*, sticking) of the cuttings to the gouging cutting elements 16 and the blades 14 to which they are attached may be reduced as compared to embodiments where the blades 14 are not canted.

Referring to FIG. 10, a plan view of a face 20 of yet another earth-boring tool 10' is shown. The total number of blades 14 extending from the body 18 of the earth-boring tool 10' may be odd. For example, three blades 14 may extend from the body 18 of the earth-boring tool 10'. Only gouging cutting elements 16 may be attached to a greater number of blades 14 than a number of blades 14 to which only shearing cutting elements 12 are attached. For example, only shearing cutting elements 12 may be attached to one blade 14 extending from the body 18 of the earth-boring tool 10'. Thus, only gouging cutting elements 16 may be attached to at least two blades 14 extending from the body 18 of the earth-boring tool 10', and may be attached to each of the remaining two blades 14 where the total number of blades 14 is three.

The blades 14 extending from the body 18 of the earth-boring tool 10' may be disposed at angular positions that are spaced at least substantially equally apart. For example, where the total number of blades 14 is three, each blade 14 may be about 120° from the blades 14 adjacent to it. Thus, both a rotationally leading and a rotationally following blade 14 may be about 120° from any selected blade 14 where the total number of blades 14 is three.

Referring to FIG. 11, a plan view of a face 20 of still another earth-boring tool 10' is shown. The total number of blades 14 extending from the body 18 of the earth-boring tool 10' may be odd. For example, five blades 14 may extend from the body 18 of the earth-boring tool 10'. Only gouging cutting elements 16 may be attached to a greater number of blades 14 than a number of blades 14 to which only

shearing cutting elements 12 are attached. For example, only shearing cutting elements 12 may be attached to two blades 14 extending from the body 18 of the earth-boring tool 10'. Thus, only gouging cutting elements 16 may be attached to at least three blades 14 extending from the body 18 of the earth-boring tool 10', and
5 may be attached to each of the remaining three blades 14 where the total number of blades 14 is five. In other embodiments, only shearing cutting elements 12 may be attached to greater than two blades 14 extending from the body 18 of the earth-boring tool 10'. In such embodiments, only gouging cutting elements 16 may be attached to greater than three blades 14 extending from the body 18 of the
10 earth-boring tool 10'.

The blades 14 extending from the body 18 of the earth-boring tool 10' may be disposed at angular positions that are spaced at least substantially equally apart. For example, where the total number of blades 14 is five, each blade 14 may be about 72° from the blades 14 adjacent to it. Thus, both a rotationally leading and a
15 rotationally following blade 14 may be about 72° from any selected blade 14 where the total number of blades 14 is five. The blades 14 to which only gouging cutting elements 16 are attached may be located at angular positions that are spaced at least substantially equally from one another. Thus, where only gouging cutting elements 16 are attached to two blades 14 and the total number of blades 14 is five,
20 the blades 14 to which only gouging cutting elements 16 are attached may be located about 144° apart in a direction of rotation of the earth-boring tool 10 and may be located about 216° apart in a direction opposing rotation of the earth-boring tool 10.

In some embodiments, at least one of the blades 14 to which only gouging cutting elements 16 are attached may be canted to extend in a direction that forms an
25 oblique angle θ with a line tangent at a point of intersection 34 of a central axis 36 of the blade 14 with a radially outer surface 32 of the bit body 18 from which the blade 14 protrudes. For example, three of the five blades 14 to which only gouging cutting elements 16 are attached may extend in a direction that forms an oblique angle θ with a line tangent to the radially outer surface 32 of the bit body 18. Thus,
30 each of the blades 14 to which only gouging cutting elements 16 are attached may be canted. In other embodiments, at least one blade 14 to which only gouging cutting elements 16 are attached may extend in a direction perpendicular to a line tangent to the radially outer surface 32 of the bit body 18. The oblique angle θ at which the

blades 14 may be canted may be greater than 45° and less than 90° , for example. As specific, non-limiting examples, the oblique angle θ may be about 60° , about 70° , or about 80° . In some embodiments, the oblique angles θ at which each of the blades 14 to which only gouging cutting elements 16 are attached may be at least
5 substantially equal. In other embodiments, at least one blade 14 may be canted at an oblique angle θ that is different (e.g., greater than or smaller than) the oblique angle θ at which at least another blade 14 is canted. For example, each blade 14 may be canted at a unique oblique angle θ that is different from the oblique angle θ at which each other blade 14 is canted. Canting the blades 14 to which only gouging
10 cutting elements 16 are attached may enable cuttings that have been removed from an underlying earth formation to more effectively be flushed from the gouging cutting elements 16 and the blades 14 to which they are attached. Thus, balling (*i.e.*, sticking) of the cuttings to the gouging cutting elements 16 and the blades 14 to which they are attached may be reduced as compared to embodiments where the
15 blades 14 are not canted.

Attaching only gouging cutting elements 16 to a greater number of blades 14 than a number of blades 14 to which only shearing cutting elements 16 are attached on an earth-boring tool 10', such as, for example, any of the earth-boring tools 10' shown in FIGS. 6 through 10, may improve the performance of the earth-boring
20 tool 10' particularly in mixed formations. For example, where an earth formation to be drilled includes at least some relatively soft regions, such as, for example, regions of sand, shale, or clay, and at least some relatively hard regions, such as, for example, regions of hard limestone, hard sandstone, dolomite, or anhydrite, attaching some cutting elements that remove the underlying earth formation using
25 primarily a shearing cutting mechanism (*i.e.*, shearing cutting elements 12) and attaching some other cutting elements that remove the underlying earth formation using primarily a gouging or crushing cutting mechanism (*i.e.*, gouging cutting elements 16) may improve the efficiency of the earth-boring tool 10', may prevent damage to the earth-boring tool 10', and may more effectively distribute loads
30 placed on the earth-boring tool 10'. As a specific, non-limiting example, where a projected drilling path passes primarily through relatively hard earth formations and at least one relatively soft formation, the shearing cutting elements 12 may provide enhanced earth removal within the relatively soft formation and may reduce the

wear that would otherwise occur on the gouging cutting elements 16. Thus, the shearing cutting elements 12 may enable an earth-boring tool 10' to drill more efficiently through a formation than if only gouging cutting elements 16 were attached to the earth-boring tool 10'.

5 Referring to FIG. 12A, a rotationally leading gouging cutting element 16 and a rotationally following shearing cutting element 12 are shown. Though the cutting elements 12 and 16 may travel in a spiral (*e.g.*, helical) path when rotating in a borehole, the cutting elements 12 and 16 are illustrated with a linear path 17 for the sake of simplicity. As shown in FIG. 12A, a rotationally following shearing cutting
10 element 12 may cut a kerf, the center of which is at least substantially aligned with the center of the kerf of the rotationally leading gouging cutting element 16. Thus, each rotationally following shearing cutting element 12 attached to an earth-boring tool 10' (see FIGS. 7 through 11) may be at least substantially aligned with a corresponding rotationally leading gouging cutting element 16 in some
15 embodiments. In other embodiments, at least one rotationally following shearing cutting element 12 may be offset from a corresponding rotationally leading gouging cutting element 16. Such a cutting element configuration may increase the stability of the earth-boring tool 10' (see FIGS. 7 through 11) to which the cutting elements 12 and 16 are attached and render the earth-boring tool 10' (see FIGS. 7
20 through 11) self-centering (*i.e.*, able to drill an at least substantially vertical borehole). In some embodiments, the cutting elements 12 and 16 may have equal or differing exposures (*i.e.*, the distance the cutting elements 12 and 16 extend above the blades 14 to which they are attached) and may have equal or differing backrake and siderake angles.

25 Referring to FIG. 12B, a rotationally leading gouging cutting element 16 and a rotationally following shearing cutting element 12 are shown. As shown in FIG. 12B, a rotationally following shearing cutting element 12 may cut a kerf, the center of which is offset from the center of the kerf of the rotationally leading gouging cutting element 16. Up to one half of the diameter of the rotationally
30 following shearing cutting element 12 may extend beyond the side of the rotationally leading gouging cutting element 16 in some embodiments. Such a cutting element configuration may improve borehole cutting element coverage of the earth-boring tool 10 (see FIGS. 1 through 5) to which the cutting elements 12 and 16

are attached, which may be advantageous in applications where off-center rotation is necessary, such as, for example, in directional drilling, and cause the earth-boring tool 10 (see FIGS. 1 through 5) to wander (*i.e.*, drill a non-linear, such as, for example, helical, borehole). In some embodiments, the cutting elements 12 and 16
5 may have equal or differing exposures (*i.e.*, the distance the cutting elements 12 and 16 extend above the blades 14 to which they are attached) and may have equal or differing backrake and siderake angles.

Referring to FIG. 12C, a rotationally leading gouging cutting element 16 and a rotationally following shearing cutting element 12 are shown. As shown in
10 FIG. 12C, a rotationally following shearing cutting element 12 may cut a kerf, the center of which is offset from the center of the kerf of the rotationally leading gouging cutting element 16. Greater than one half of the diameter of the rotationally following shearing cutting element 12 may extend beyond the side of the rotationally leading gouging cutting element 16 in some embodiments. In some
15 embodiments, the cutting elements 12 and 16 may have equal or differing exposures (*i.e.*, the distance the cutting elements 12 and 16 extend above the blades 14 to which they are attached) and may have equal or differing backrake and siderake angles.

Referring to FIG. 12D, a rotationally leading gouging cutting element 16 and
20 a rotationally following shearing cutting element 12 are shown. As shown in FIG. 12D, a rotationally following shearing cutting element 12 may cut a groove, the center of which is offset from the center of the groove of the rotationally leading gouging cutting element 16. None of the groove cut by the rotationally following shearing cutting element 12 may overlap with the groove cut by the rotationally
25 leading gouging cutting element 16 in some embodiments. In some embodiments, the cutting elements 12 and 16 may have equal or differing exposures (*i.e.*, the distance the cutting elements 12 and 16 extend above the blades 14 to which they are attached) and may have equal or differing backrake and siderake angles.

Referring to FIG. 13, a simplified cross-sectional view of a gouging cutting
30 element 16 and a shearing cutting element 12 engaging an underlying earth formation 38 is shown. Shearing cutting elements 12 attached to blades 14 of earth-boring tools 10 may be oriented at negative back rake angles 40. Gouging cutting elements 16 attached to blades 14 of earth-boring tools 10 may be oriented at

positive rake angles 42. As the earth-boring tool 10 rotates within the borehole, at least some of the shearing and gouging cutting elements 12 and 16 may engage the underlying earth formation 38 to facilitate its removal. For example, gouging cutting elements 16 may gouge and crush, which may be particularly effective to
5 remove relatively harder portions, which may also be characterized as strata 44, of the earth formation 38. Shearing cutting elements 12, by contrast, may shear, which may be particularly effective to remove relatively softer portions 46 of the earth formation 38. In addition, gouging cutting elements 16 may damage the underlying earth formation 38, such as, for example, by crushing the hard portions thereof,
10 creating a damaged zone that has a greater depth than a damaged zone created by shearing cutting elements 12, as shown in FIG. 13.

Referring to FIGS. 14 through 19, cross-sectional views of gouging cutting elements 16 that may be attached to an earth-boring tool, such as, for example, any of the earth-boring tools 10 and 10' shown in FIGS. 1 through 5 and 7 through 11
15 are shown. The gouging cutting elements 16 may comprise a polycrystalline superabrasive material 48 attached to an end of a substrate 50 at an interface 52. The polycrystalline superabrasive material 48 may comprise various shapes configured to gouge and crush an earth formation, such as, for example, chisel-shaped, dome-shaped, cone-shaped, and other shapes known in the art. The
20 substrate 50 may comprise a shape configured to support the polycrystalline superabrasive material 48, such as, for example, cylindrical. The interface 52 between the polycrystalline superabrasive material 48 may be planar in some embodiments, as shown in FIG. 14 for example. In other embodiments, such as, for example, those shown in FIGS. 13 and 15 through 18, the interface 52 between the
25 polycrystalline superabrasive material 48 may comprise a non-planar interface design, such as, for example, a series of protrusions and recesses, concentric rings, radially extending spokes, and other non-planar interface designs known in the art.

Referring to FIGS. 20 and 21, cross-sectional views of shearing cutting elements 12 that may be attached to an earth-boring tool, such as, for example, any
30 of the earth-boring tools 10 and 10' shown in FIGS. 1 through 5 and 7 through 11, are shown. The shearing cutting elements 12 may comprise a polycrystalline superabrasive material 48 attached to an end of a substrate 50 at an interface 52. The polycrystalline superabrasive material 48 may comprise a shape configured to

shear an earth formation, such as, for example, disc-shaped, cylindrical, and other shapes known in the art. The substrate 50 may comprise a shape configured to support the polycrystalline superabrasive material 48, such as, for example, cylindrical. The interface 52 between the polycrystalline superabrasive material 48
5 may be planar in some embodiments, as shown in FIG. 19 for example. In other embodiments, as shown in FIG. 20 for example, the interface 52 between the polycrystalline superabrasive material 48 may comprise a non-planar interface design, such as, for example, a series of protrusions and recesses, concentric rings, radially extending spokes, and other non-planar interface designs known in the art.

10 The polycrystalline superabrasive material 48 may comprise, for example, synthetic diamond, natural diamond, a combination of synthetic and natural diamond, cubic boron nitride, carbon nitrides, and other polycrystalline superabrasive materials known in the art. In some embodiments, catalyst material used in a process for forming the polycrystalline superabrasive material 48
15 (conventionally a high temperature/high pressure “HTHP” process) may be disposed in interstitial spaces among the interbonded grains of superabrasive material. In other embodiments, at least some of the catalyst material may be removed (*e.g.*, leached using a leaching agent, such as, for example, *aqua regia*) from the interstitial spaces among the interbonded grains of superabrasive material of the
20 polycrystalline superabrasive material 48.

One example of an HTHP process for forming the polycrystalline superabrasive material may comprise pressing a plurality of particles (*e.g.*, grains or crystals) of the superabrasive material in a heated press at a pressure of greater than about 5.0 GPa and at temperatures greater than about 1,400 °C, although the exact
25 operating parameters of HTHP processes will vary depending on the particular compositions and quantities of the various materials being used. The pressures in the heated press may be greater than about 6.5 GPa (*e.g.*, about 7 GPa), and may even exceed 8.0 GPa in some embodiments. Furthermore, the materials being sintered may be held at such temperatures and pressures for a time period between
30 about 30 seconds and about 20 minutes.

The substrate 50 may comprise a hard material suitable for use in earth-boring applications. The hard material may comprise, for example, a ceramic-metal composite material (*i.e.*, a “cermet” material) comprising a plurality

of hard ceramic particles dispersed among a metal matrix material. The hard ceramic particles may comprise carbides, nitrides, oxides, and borides (including boron carbide (B_4C)). More specifically, the hard ceramic particles may comprise carbides and borides made from elements such as W, Ti, Mo, Nb, V, Hf, Ta, Cr, Zr, Al, and Si. By way of example and not limitation, materials that may be used to form hard ceramic particles include tungsten carbide, titanium carbide (TiC), tantalum carbide (TaC), titanium diboride (TiB_2), chromium carbides, titanium nitride (TiN), aluminum oxide (Al_2O_3), aluminum nitride (AlN), and silicon carbide (SiC). The metal matrix material of the ceramic-metal composite material may include, for example, cobalt-based, iron-based, nickel-based, iron- and nickel-based, cobalt- and nickel-based, and iron- and cobalt-based alloys. The matrix material may also be selected from commercially pure elements, such as, for example, cobalt, iron, and nickel. As a specific, non-limiting example, the hard material may comprise a plurality of tungsten carbide particles in a cobalt matrix, known in the art as cobalt-cemented tungsten carbide.

The bit body 18, including the blades 14 extending from the bit body 18, may comprise a material suitable for use in earth-boring applications. For example, the bit body 18 may comprise any of the hard materials described previously in connection with the substrate 50. Other materials are also contemplated, such as, for example, iron and steel. In some embodiments, particles of superabrasive material may be dispersed among and at least partially embedded within the bit body 18. In some embodiments, hardfacing may be applied to external surfaces of the earth-boring tool 10 or 10', such as for example, on the blades 14, within junk slots 30, and on the gage region 24.

The bit body 18 may be formed using conventional processes known in the art, such as, for example, machining, casting, and sintering. Likewise, shearing and gouging cutting elements 12 and 16 may be attached to the blades 14 of the earth-boring tool 10 or 10' by, for example, brazing, mechanical interference, and other attachment means known in the art.

While the present invention has been described herein with respect to certain embodiments, those of ordinary skill in the art will recognize and appreciate that it is not so limited. Rather, many additions, deletions, and modifications to the embodiments described herein may be made without departing from the scope of the

invention as hereinafter claimed, including legal equivalents. In addition, features from one embodiment may be combined with features of another embodiment while still being encompassed within the scope of the invention as contemplated by the inventor.

5

CONCLUSION

In some embodiments, earth-boring drill bits comprise a bit body having a plurality of radially extending blades and a plurality of cutting elements attached to the plurality of radially extending blades. Only gouging cutting elements are
10 attached to at least one blade of the plurality of radially extending blades. Only shearing cutting elements are attached to at least another blade of the plurality of radially extending blades. Only shearing cutting elements are attached to a number of blades of the plurality of radially extending blades that is different from a number of blades of the plurality of radially extending blades to which only gouging cutting
15 elements are attached.

In additional embodiments, methods of forming an earth-boring drill bit comprise forming a bit body including a plurality of radially extending blades. Only gouging cutting elements are attached to at least one blade of the plurality of radially extending blades. Only shearing cutting elements are attached to at least another
20 blade of the plurality of radially extending blades. Only shearing cutting elements are attached to a number of blades different from a number of blades to which only gouging cutting elements are attached.

Additional non-limiting, illustrative embodiments of the present disclosure are described below:

25 Embodiment 1: An earth-boring drill bit comprises a bit body having a plurality of radially extending blades and a plurality of cutting elements attached to the plurality of radially extending blades. Only gouging cutting elements are attached to at least one blade of the plurality of radially extending blades. Only shearing cutting elements are attached to at least another blade of the plurality of radially extending blades. Only
30 shearing cutting elements are attached to a number of blades of the plurality of radially extending blades that is different from a number of blades of the plurality of radially extending blades to which only gouging cutting elements are attached.

Embodiment 2: The earth-boring drill bit of Embodiment 1, wherein the number of blades of the plurality of radially extending blades to which only shearing cutting elements are attached is greater than the number of blades of the plurality of radially extending blades to which only gouging cutting elements are attached.

5 Embodiment 3: The earth-boring drill bit of Embodiment 2, wherein at least one blade to which only gouging cutting elements is attached is located at an angular position rotationally closer to an immediately rotationally leading blade to which only shearing cutting elements are attached than if all the blades were spaced exactly equally apart.

10 Embodiment 4: The earth-boring drill bit of Embodiment 2 or Embodiment 3, wherein only gouging cutting elements are attached to only one blade of the plurality of radially extending blades.

 Embodiment 5: The earth-boring drill bit of Embodiment 2 or Embodiment 3, wherein only gouging cutting elements are attached to at least two blades of the
15 plurality of radially extending blades.

 Embodiment 6: The earth-boring drill bit of Embodiment 5, wherein the at least two blades of the plurality of radially extending blades are located at angular positions that are spaced at least substantially equally from one another.

 Embodiment 7: The earth-boring drill bit of Embodiment 1, wherein the
20 number of blades of the plurality of radially extending blades to which only gouging cutting elements are attached is greater than the number of blades of the plurality of radially extending blades to which only shearing cutting elements are attached.

 Embodiment 8: The earth-boring drill bit of Embodiment 7, wherein only shearing cutting elements are attached to only one blade of the plurality of radially
25 extending blades.

 Embodiment 9: The earth-boring drill bit of Embodiment 7, wherein only shearing cutting elements are attached to at least two blades of the plurality of radially extending blades.

 Embodiment 10: The earth-boring drill bit of Embodiment 9, wherein the at
30 least two blades of the plurality of radially extending blades are located at angular positions that are spaced at least substantially equally from one another.

 Embodiment 11: The earth-boring drill bit of any one of Embodiments 7 through 10, wherein at least one blade of the plurality of blades to which only gouging

cutting elements are attached extends from the bit body in a direction that forms an oblique angle with a line tangent at a point of intersection of a central axis of the at least one blade with a radially outer surface the bit body from which the at least one blade protrudes.

5 Embodiment 12: The earth-boring drill bit of any one of Embodiments 1 through 11, wherein the gouging cutting elements comprise a polycrystalline superabrasive material that is at least one of dome-shaped, chisel-shaped, and cone-shaped.

10 Embodiment 13: The earth-boring drill bit of any one of Embodiments 1 through 12, wherein the shearing cutting elements comprise a polycrystalline superabrasive material that is disc-shaped.

15 Embodiment 14: The earth-boring drill bit of any one of Embodiments 1 through 13, wherein the plurality of cutting elements comprise a cutting structure comprising polycrystalline superabrasive material attached to an end of a substrate comprising a hard material.

 Embodiment 15: The earth-boring drill bit of any one of Embodiments 1 through 14, wherein only one of gouging cutting elements and shearing cutting elements is attached to each blade of the plurality of radially extending blades.

20 Embodiment 16: A method of forming an earth-boring drill bit comprises forming a bit body including a plurality of radially extending blades. Only gouging cutting elements are attached to at least one blade of the plurality of radially extending blades. Only shearing cutting elements are attached to at least another blade of the plurality of radially extending blades. Only shearing cutting elements are attached to a number of blades different from a number of blades to which only gouging cutting
25 elements are attached.

 Embodiment 17: The method of Embodiment 16, wherein attaching only gouging cutting elements to at least one blade of the plurality of radially extending blades comprises attaching only gouging cutting elements to at least two blades of the plurality of radially extending blades.

30 Embodiment 18: The method of Embodiment 17, further comprising positioning the at least two blades of the plurality of radially extending blades at angular positions that are spaced at least substantially equally from one another.

Embodiment 19: The method of Embodiment 17 or Embodiment 18, further comprising attaching only one of gouging cutting elements and shearing cutting elements to each blade of the plurality of radially extending blades.

- Embodiment 20: The method of any one of Embodiments 16 through 19,
- 5 further comprising forming at least one of the gouging cutting elements or the shearing cutting elements using an HTHP process comprising subjecting a plurality of particles comprising a superabrasive material to a pressure of at least 7.0 GPa and a temperatures of at least 1,400 °C for between 30 sec and 20 min.

CLAIMS

What is claimed is:

1. An earth-boring drill bit, comprising:
a bit body having a plurality of radially extending blades and a plurality of cutting elements attached to the plurality of radially extending blades;
wherein only gouging cutting elements are attached to at least one blade of the plurality of radially extending blades;
only shearing cutting elements are attached to at least another blade of the plurality of radially extending blades;
only gouging cutting elements or only shearing cutting elements are attached to each blade of the plurality of radially extending blades; and
only shearing cutting elements are attached to a number of blades of the plurality of radially extending blades that is different from a number of blades of the plurality of radially extending blades to which only gouging cutting elements are attached.
2. The earth-boring drill bit of claim 1, wherein the number of blades of the plurality of radially extending blades to which only shearing cutting elements are attached is greater than the number of blades of the plurality of radially extending blades to which only gouging cutting elements are attached.
3. The earth-boring drill bit of claim 2, wherein at least one blade to which only gouging cutting elements is attached is located at an angular position rotationally closer to an immediately rotationally leading blade to which only shearing cutting elements are attached than if all the blades were spaced exactly equally apart.
4. The earth-boring drill bit of claim 2, wherein only gouging cutting elements are attached to only one blade of the plurality of radially extending blades.
5. The earth-boring drill bit of claim 2, wherein only gouging cutting elements are attached to at least two blades of the plurality of radially extending blades.

6. The earth-boring drill bit of claim 5, wherein the at least two blades of the plurality of radially extending blades are located at angular positions that are spaced at least substantially equally from one another.

7. The earth-boring drill bit of claim 1, wherein the number of blades of the plurality of radially extending blades to which only gouging cutting elements are attached is greater than the number of blades of the plurality of radially extending blades to which only shearing cutting elements are attached.

8. The earth-boring drill bit of claim 7, wherein only shearing cutting elements are attached to only one blade of the plurality of radially extending blades.

9. The earth-boring drill bit of claim 7, wherein only shearing cutting elements are attached to at least two blades of the plurality of radially extending blades.

10. The earth-boring drill bit of claim 9, wherein the at least two blades of the plurality of radially extending blades are located at angular positions that are spaced at least substantially equally from one another.

11. The earth-boring drill bit of claim 7, wherein at least one blade of the plurality of blades to which only gouging cutting elements are attached extends from the bit body in a direction that forms an oblique angle with a line tangent at a point of intersection of a central axis of the at least one blade with a radially outer surface the bit body from which the at least one blade protrudes.

12. The earth-boring drill bit of claim 1, wherein the gouging cutting elements comprise a polycrystalline superabrasive material that is at least one of dome-shaped, chisel-shaped, and cone-shaped.

13. The earth-boring drill bit of claim 1, wherein the shearing cutting elements comprise a polycrystalline superabrasive material that is disc-shaped.

14. The earth-boring drill bit of claim 1, wherein the plurality of cutting elements comprise a cutting structure comprising polycrystalline superabrasive material attached to an end of a substrate comprising a hard material.

15. The earth-boring drill bit of claim 1, wherein a rotationally leading gouging cutting element of the at least one blade is positioned to travel in a helical path at least partially overlapping with a helical path in which a rotationally trailing shearing cutting element of the at least another blade is positioned to travel.

16. A method of forming an earth-boring drill bit, comprising:
forming a bit body including a plurality of radially extending blades;
attaching only gouging cutting elements to at least one blade of the plurality of radially extending blades;
attaching only shearing cutting elements to at least another blade of the plurality of radially extending blades;
attaching only gouging cutting elements or only shearing cutting elements to each blade of the plurality of radially extending blades; and
attaching only shearing cutting elements to a number of blades different from a number of blades to which only gouging cutting elements are attached.

17. The method of claim 16, wherein attaching only gouging cutting elements to at least one blade of the plurality of radially extending blades comprises attaching only gouging cutting elements to at least two blades of the plurality of radially extending blades.

18. The method of claim 17, further comprising:
positioning the at least two blades of the plurality of radially extending blades at angular positions that are spaced at least substantially equally from one another.

19. The method of claim 17, further comprising:
positioning a rotationally leading gouging cutting element of the at least one blade to travel in a helical path at least partially overlapping with a helical path in which a rotationally trailing shearing cutting element of the at least another blade is positioned to travel.

20. The method of claim 16, further comprising:
forming at least one of the gouging cutting elements or the shearing cutting elements using an
HTHP process comprising subjecting a plurality of particles comprising a superabrasive
material to a pressure of at least 7.0 GPa and a temperatures of at least 1,400 °C for
between 30 sec. and 20 min.