



- 1 -

PASSIVE TRANSMITTER RECEIVER DEVICE FED BY AN  
ELECTROMAGNETIC WAVE

The present invention relates to a passive receiver-  
5 transmitter device powered by an electromagnetic wave  
carrying information.

The operation of such devices relies on a transmission  
by induction between, on the one hand, a card or a  
10 label having an antenna in the form of a loop, the ends  
of which are linked to an electronic chip on the card  
or the label, and, on the other hand, a terminal  
capable of sending and receiving an electromagnetic  
wave carrying information. The antenna of the card or  
15 label captures the electromagnetic wave sent by the  
terminal and transmits the information to the chip  
which processes it before, if necessary, sending a  
response that is forwarded by the antenna and will be  
captured by the terminal. Thus, the latter can read  
20 and/or modify the information stored on the card.

Such devices are used to implement so-called  
"contactless" data transfer methods, used, for example,  
for remote identification systems, for anti-theft and  
25 transport ticket validation systems, and for  
identifying and tracking packages in a warehouse. These  
devices are normally known as radiofrequency  
identification devices (RFID).

30 One of the great advantages of these devices, besides  
the fact that they require no direct contact between  
the chip and the reader, is that they are passive, in  
other words, they require no independent electrical  
power source. In practice, when an electromagnetic  
35 wave, having a frequency adjacent to the resonance  
frequency of the antenna, passes through the antenna  
perpendicularly to the plane of the loop, it generates



an induced current which can then be used to feed an electronic circuit such as a chip.

However, the way in which these cards are fed also  
5 constitutes their main drawback. In practice, for an induced current to be generated, the magnetic field of the wave must be directed roughly perpendicularly to the plane of the loop. While the issue of the orientation of the magnetic field poses few problems  
10 for applications requiring a relatively determined position, such as identification validators or badges, the same does not apply when the object to be identified is in motion or has an unpredictable positioning. Such is in particular the case when there  
15 is a desire to apply this technology to the tracking of athletes in competitions or the identification of packages in a warehouse.

One first solution is to place a number of terminals so  
20 as to cover the maximum possible number of orientations of the antenna. This solution is expensive and requires a complex computerized management of the different terminals in order to avoid duplicate validations if the object to be detected is in motion.

25 Another solution is to place a label containing an electronic transponder chip on each side of the object to be detected so as to cover the three possible directions of incidence of the magnetic field sent by  
30 the terminal. Thus, the field will in all cases be sensed by at least one label. However, it is also possible for more than one label to react to the magnetic field and it is therefore necessary to also provide a controlling computerized facility with which,  
35 on the one hand, to collate the various labels glued to one and the same object and on the other hand, to manage any crossed detection. Moreover, if there is a desire to modify the information concerning the object, stored on the chip, it becomes necessary to modify the

chips of all the labels of the object. All the labels of one and the same object do not necessarily capture the electromagnetic wave, so such an updating of the chips is difficult to envisage.

5

Document FR 2 812 427 discloses another solution, in which an antenna is deployed on a number of separate adhesive supports, each comprising a winding disposed in a particular plane, the windings being disposed  
10 remotely to avoid one winding being disturbed in relation to another winding.

This device is satisfactory for a definitive installation on a large, pallet-type object.

15

However, it does not allow for the use of a small-size support, smaller than a meter and even more so smaller than 50 cm, that can be easily applied to an object or carried by an individual.

20

Furthermore, this antenna does not allow for detection in a plane perpendicular to the pallet.

The object of the present invention is to overcome the  
25 drawbacks described above, and, for this, consists of a passive receiver-transmitter device fed by electromagnetic wave, provided with an antenna comprising a loop associated with an electronic transponder chip, this loop being able on the one hand  
30 to feed the electronic chip with an induced current generated when it is passed through by a first electromagnetic wave carrying information, and on the other hand, to send a second electromagnetic wave carrying the response from the electronic chip,  
35 characterized in that the antenna is designed in such a way that the loop comprises at least two non-coplanar or non-parallel parts in a position of use.

In this way, the antenna has an overall, non-planar

receive surface, and is therefore capable of capturing electromagnetic waves in a number of directions. More specifically, the antenna can capture the waves with a magnetic field that has at least one component oriented  
5 roughly perpendicularly to a portion of the antenna. It should be understood that the term antenna denotes all or part of the radiofrequency system designed to radiate or capture the waves.

10 The present invention provides for a simple, small solution, which can easily be applied to an object or an individual.

Advantageously, the loop comprises at least two parts  
15 situated in roughly perpendicular planes. This configuration makes the device particularly well suited to the tracking of packages or packets.

According to a first embodiment of the invention, the  
20 loop is intended to be disposed in two planes roughly perpendicular to each other.

Advantageously, the loop is intended to be positioned in three planes roughly perpendicular to each other. In  
25 this way, the antenna covers the three directions of the space and can therefore capture the electromagnetic waves whatever their orientation.

Preferably, the antenna is incorporated in a support  
30 intended to be glued on several sides of one and the same object. Advantageously, the support is produced in the form of a self-adhesive label.

According to a second embodiment of the invention, the  
35 antenna comprises a loop produced in the form of an open cylindrical bracelet, obtained from a flat support formed by a flexible strip.

According to a third embodiment of the invention, the

antenna comprises a closed circular loop produced from a spiral-wound wire.

Advantageously, the loop has a diameter of between 4  
5 and 10 cm.

Such devices according to the second and third  
embodiments of the invention can easily be worn around  
the wrist or ankle of a person and are therefore  
10 particularly well suited to tracking athletes.  
Preferably, the loop has a diameter of between 4 and  
10 cm.

The invention will be better understood from the  
15 detailed description that is given below in light of  
the appended drawings in which:

Figure 1 is a diagrammatic view of a package on which  
is glued a device according to a first embodiment of  
20 the invention.

Figure 2 is an enlarged diagrammatic view of a device  
glued to the package represented in figure 1.

25 Figure 3 is a diagrammatic view of the device of figure  
2 before it is glued on the package.

Figure 4 diagrammatically represents the disposition of  
the loop of the device of figure 1.

30 Figure 5 is a curve representing the variation of the  
resonance frequency as a function of the distance from  
the loop to a corner of the packet around which the  
device of figure 1 is folded.

35 Figure 6 represents a variant of the device of  
figure 3.

Figure 7 is a diagrammatic view of a strip, comprising

a device according to the second embodiment of the invention, before it is shaped.

Figure 8 is a diagrammatic view of the strip  
5 represented in figure 7, after it is shaped around a cylinder.

Figure 9 is a curve representing the variation of the resonance frequency as a function of the diameter of  
10 the cylinder of figure 8.

Figure 10 is a diagrammatic top view of a device according to the third preferred embodiment of the invention.

15

Figure 11 is a diagrammatic perspective view of the device represented in figure 10, placed around a cylinder.

20 Figure 12 is a curve representing the variation of the resonance frequency as a function of the diameter of the cylinder represented in figure 10.

Figure 13 is a diagrammatic perspective view of a  
25 device according to a fourth preferred embodiment of the invention.

Figure 14 is a diagrammatic perspective view of a device according to a fifth preferred embodiment of the  
30 invention.

Figure 15 is a diagrammatic perspective view of a device according to a sixth preferred embodiment of the invention.

35

A parallelepipedal package 1, as represented in figure 1, has eight corners 2, each corner 2 being delimited by three sides 3, 4, 5 perpendicular to each other. A device 6 according to a first embodiment of the

invention is glued to one corner 2 so as to be in contact with the three sides 3, 4, 5, as represented in figure 2.

5 To do this, the device 6 takes the form of a flat label, represented in figure 3, comprising an adhesive support 7 in the shape of a bracket made of a foldable flexible material such as paper or polymer film. A  
10 conductive wire 8, having two ends, is deposited around the edge of the support 7 so as to form a loop also in the shape of a bracket. The conductive wire 8 can be joined to the support 7 or not. Alternatively, the loop can also be produced in the form of a conductive track obtained by metallic deposition or from a conductive  
15 ink.

The ends of the wire 8 are linked to the power supply terminals of an electronic transponder chip 9. Such an  
20 electronic chip 9 is known per se and is of the type used for RFIDs, designed to operate at frequencies above 10 MHz, normally 13.56 MHz, and the operating standards of which are mainly set by the ISO standards.

The electronic circuit comprising, on the one hand, the  
25 conductive wire 8 forming a loop, and on the other hand, the electronic transponder chip 9, is designed to form a resonator, the loop of which forms the antenna. This type of circuit is also known. The antenna is produced so that the resonance frequency of the system  
30 corresponds to the operating frequency of the chip, i.e. 13.56 MHz. If the capacity of the electronic chip 9 is insufficiently high compared to the inductance of the loop, a capacitor (not shown in the drawings), of appropriate rating, will be connected in parallel to  
35 the electronic chip 9.

Once the electronic circuit is placed on the support 7, a protective film (not represented) is applied.

Fold lines P1, P2 are then marked on the support 7 in the shape of a bracket. Each of the lines P1, P2 is situated on one branch of the support 7, so as to divide the label into three portions 11, 12, 13. Each of the portions 11, 12, 13 includes a part of the loop formed by the wire 8 representing approximately a third of the overall area of the loop. Thus, the three portions 11, 12, 13 have roughly identical receive surface areas.

10

It is important to choose the dimensions and the disposition of the loop in such a way as to obtain electromagnetic characteristics suited to the use in the chosen frequency range.

15

Thus, the following adjustment can, by way of example, be made, by imposing equality of the surface areas of the loop in the different planes.

20

Starting from an L-shaped structure as represented in figures 1 to 4, designed to be folded along two lines P1 and P2, three surface areas can be defined, respectively intended to be disposed in three different planes, the three surface areas S1, S2, S3 being separated by fold lines and roughly corresponding to a first branch of the L, the join area between the two branches of the L, and the second branch of the L.

25

The following conventions are used:

30

- d is the distance between a branch of the L and the intersection of the fold lines P1 and P2,
- L is the length of a branch of the L and the intersection of the fold lines P1 and P2,
- l is the width of the branches of the L.

35

Consequently:

$$S1 = Ll$$

$$S2 = (l+d)^2 - d^2 = l^2 + 2ld$$

$$S3 = Ll.$$

Since the magnetic field passes through one of the three surface areas S1, S2, S3, these three surface areas need to be roughly the same size.

5

By defining:

-  $L = kl$ , characteristic relationship of one side of the label,

10 -  $L + l + d = C$ , overall length of the side of the square in which the unfolded label fits.

To have  $S1=S2=S3$ , we obtain:

$$d = \frac{L - l}{2} = \left( \frac{k - 1}{2} \right) l$$

15  $C = l \frac{3k + 1}{2}$

Normally,  $k$  is fixed by the rectangular label format of one side. More often than not, it is equal to 1.3.

20 For example, if it is decided that  $C=2.5$  cm and  $k=1.3$ , then  $l=50/4.9 \sim 10.2$  cm;  $L=13.26$  cm and  $d=1.53$  cm.

The following measurements have also been made.

25 With the label designed flat, figure 5 shows how its resonance frequency changes when the label is distorted for different values of  $d$ .

30 Thus, the values of  $d$  that can be used to obtain a resonance frequency close to that required, which in the example is 13.56 MHz, are within a band of values  $\Delta d$  between 1.3 cm and 3.5 cm.

35 It therefore appears that the values of  $d$  that can be used include those determined by using the equal surface areas method.

Figure 6 represents an execution variant of the label of figure 3, in which the same elements are denoted by the same references as before. In this case, the label, when flat, has a rectangular shape.

5

In its condition of use, the part 11 is glued to the side 3, near to the corner 2, so that the lines P1, P2 are each situated on one edge of the corner. In this case, the line P1 is located on the edge between the side 3 and the side 4, and the line P2 is located on the edge between the side 3 and the side 5. The parts 12, 13 are then folded along their respective lines P1, P2 to be glued onto the sides 4, 5 of the package 1.

15 Once in place, the label therefore has three receiving surface areas perpendicular to each other, corresponding to the portions 11, 12, 13. Since each surface area is able to receive an electromagnetic wave oriented roughly perpendicularly to itself, the device therefore defines a three-dimensional orthogonal frame of reference covering all possible orientations. In practice, any electromagnetic wave will have components H1, H2 and H3 within this frame of reference and will therefore be captured by the loop. It is interesting to note that an excitation by a one-way magnetic field H1 or H2 or H3 is sufficient to make the entire loop resonate and to feed the chip 9 with sufficient energy to function.

30 A device 28, according to a second embodiment of the invention and as represented in figures 7 and 8, comprises a flat support 29 in the form of a flexible strip. A wire 30 is placed around the edge of the support 29 to form a rectangular loop and is connected to an electronic chip 9. The support 29 is covered by a protective film, then the device is glued onto an open bracelet 31 having dimensions close to those of the support 29. In conditions of use, the open bracelet 31 is placed around a roughly cylindrical body, such as a

wrist or an ankle so as to form a bracelet. The loop formed by the wire 30 then has an open bracelet structure and therefore presents receiving surface areas with which to capture the radially oriented waves  
5 Hr and the waves Ha oriented along the axis of the cylinder.

The fact that the bracelet 31 is an open bracelet means that the device 28 can easily be adapted to different  
10 diameters. The surprising particular feature of a loop with an open bracelet structure is that the resonance frequency and the overvoltage coefficient of the device vary little when its diameter changes slightly. The curve showing the variation of the frequency as a  
15 function of the diameter is represented in figure 10 for a bracelet 31 tuned to 13.56 MHz when its diameter is 8 cm. When the diameter of the bracelet varies between 7 and 10 cm, the resonance frequency remains around the nominal frequency of 13.56 MHz.

20

A device 33, produced according to the third preferred embodiment of the invention, is represented in figures 10 and 11. This device 33 comprises a spiral-wound wire 34 closed on itself so as to form a circular loop  
25 having two ends linked to an electronic chip 9. In conditions of use, this device 33 is placed around a body having roughly the shape of a cylinder, such as an ankle or a wrist, and presents receiving surface areas with which to essentially capture waves Ha oriented  
30 along the axis of the cylinder.

Moreover, the elasticity of the spiral means that the device 33 can easily be adapted to different diameters without any specific opening device. As for the device  
35 28, according to the third embodiment, it has been observed that the resonance frequency varies little with the diameter. The curve of the resonance frequency as a function of the diameter of the loop is represented in figure 12.

Figure 13 represents a device 35 according to a fourth embodiment, intended to be glued onto the corner of a package, as in the first embodiment, comprising a wire  
5 describing on each side of the packet two perpendicular sections, so as to form a left hexagon around one corner of the packet, the chip 37 being situated, for example, on a vertex of the hexagon.

10 Figure 14 represents a device 38 according to a fifth embodiment intended to be glued onto the corner of a package, as in the first embodiment, which is similar to the first embodiment except that its shape is not in the form of an L with straight line segments, but with  
15 a rounded outer shape.

Figure 15 represents a sixth embodiment of a device 39, the loop being formed by a rectangle which is twisted about a twist axis parallel to its length, in order to  
20 form a left surface area with which to receive waves in a number of directions.

Although the invention has been described in conjunction with particular exemplary embodiments, it  
25 is clearly obvious that it is by no means limited and that it includes all the technical equivalents of the means described, and their combinations if such enter into the context of the invention.

- 13 -

## CLAIMS

1. A passive receiver-transmitter device (6, 28, 33)  
fed by electromagnetic wave, provided with an  
5 antenna comprising a loop (7, 30, 34) associated  
with an electronic transponder chip (9), this loop  
being able on the one hand to feed the electronic  
chip with an induced current generated when it is  
passed through by a first electromagnetic wave  
10 (H1, H2, H3, Ha, Hr) carrying information, and on  
the other hand, to send a second electromagnetic  
wave carrying the response from the electronic  
chip, characterized in that the antenna is  
designed in such a way that the loop comprises at  
15 least two non-coplanar or non-parallel parts in a  
position of use.
2. The device as claimed in claim 1, characterized in  
that the loop comprises at least two parts  
20 situated in roughly perpendicular planes.
3. The device as claimed in claim 2, characterized in  
that the loop is intended to be disposed in two  
planes roughly perpendicular to each other.
- 25 4. The device (6) as claimed in claim 2,  
characterized in that the loop (7) is intended to  
be positioned in three planes (3, 4, 5) roughly  
perpendicular to each other.
- 30 5. The device (6) as claimed in any one of claims 1  
to 4, characterized in that the antenna is  
incorporated in a support (7) intended to be glued  
on several sides of an object (1).
- 35 6. The device (6) as claimed in claim 5,  
characterized in that the support (7) is produced

in the form of a self-adhesive label.

- 5        7.    The device (28) as claimed in claim 1,  
characterized in that the antenna comprises a loop  
(30) produced in the form of an open cylindrical  
bracelet, obtained from a flat support formed by a  
flexible strip.
- 10       8.    The device (33) as claimed in claim 1,  
characterized in that the antenna comprises a  
closed circular loop produced from a spiral-wound  
wire (34).
- 15       9.    The device (28, 33) as claimed in either of claims  
7 and 8, characterized in that the loop has a  
diameter of between 4 and 10 cm.