CLAIMS

1. Reusable container for the collection and/or movement of objects, comprising a body (2) and at least one removable layer (4) said body (2) and said removable layer (4) mutually cooperating in order to define a three-dimensional structure, said three-dimensional structure comprising a collection space (3) for a predetermined number of objects which can be placed in the container (1), the removable layer 4 comprising in an operating condition, a bottom wall (4a), and a predetermined number of side walls (4b) perimetrically connected to the bottom wall,

characterized in that the body (2) further comprises:

- a predetermined number of elongated elements (2a) defining edges of the bottom wall (4a) and/or upper edges of the side walls (4b);
- a predetermined number of angular elements (2b) interposed between two of said elongated elements (2a) placed along adjacent perimeter sides of the container (1), said angular elements (2b) further comprising gripping and handling means (5) suitable for allowing a grip by a user of the container (1); and
- means for engaging the removable layer (4) in the elongated elements (2a) and/or in the angular elements (2b), said means for engaging comprising insertion undercuts and/or recesses.

2. Container according to claim 1, wherein said at least one removable layer (4) comprises at least one planar element which can be configured, reversibly or repeatably, between a flattening condition in which it has a substantially two-dimensional development and in which it is separated from the body (2), and the operating condition in which it defines a three-dimensional volume open on at least one loading face and in which it is connected to the body (2).

3. Container according to claim 2, wherein the removable layer (4) comprises a predetermined number of programmed folding and/or deformation lines (5) adapted to change the geometrical configuration of

the removable layer (4) itself from the flattening condition to the operating condition

4. Container according to claim 3, wherein said programmed folding and/or deformation lines (5) are adapted to define, in the operating condition of the removable layer (4):

- the bottom wall (4a) of the container (1);
- the predetermined number of side walls (4b) of the container (1) perimetrically connected to said bottom wall (4a); and
- a predetermined number of perimeter corners (4c) interposed between two adjacent side walls (4b) of the container (1).

5. Container according to claim 4, wherein said perimeter corners (4c) are shaped according to three-dimensional prismatic portions.

6. Container according to claim 4, wherein the perimeter corners (4c) are shaped according to portions having one or more three-dimensional curvatures in space.

7. Container according to any one of the preceding claims, wherein the removable layer (4) comprises stiffening means (6) integrally made in the bottom wall (4a) and/or in the side walls (4b) and/or in the perimeter corners (4c), said stiffening means (6) being constituted by folds and/or ribs formed integrally and seamlessly in delimited portions of the removable layer (4) itself.

8. Container according to any one of the preceding claims, wherein there are also mechanical stabilization means (7) operating between adjacent parts or layers of the removable layer (4) and/or operating between the removable layer (4) and the body (2) to define at least the operating condition of the removable layer (4) itself.

9. Container according to claim 8, wherein said mechanical stabilization means (7) comprise:

- hooking systems, comprising clips and/or rivets and/or snap buttons and preferably made preferably of radio-transparent material; and/or
- localized shapings and/or folds and/or ultrasonic weldings interposed between adjacent parts or layers of the planar element constituting the removable layer (4).

10. Container according to any one of the preceding claims, wherein the removable layer (2) comprises further gripping and handling means (5) suitable for allowing a grip by a user of the container (1).

11. Container according to claim 10, wherein also present are:

- means for univocal identification of the container (1) and/or of the objects placed in the container (1), said means being preferably constituted by RFID and/or NFC devices; and
- means for static or dynamic display of messages and/or information reported on the surface of the removable layer (4) and/or on the body (2).