



- (51) International Patent Classification:
C12M 3/02 (2006.01) *C12M 1/00* (2006.01)
- (21) International Application Number:
PCT/US2012/059013
- (22) International Filing Date:
5 October 2012 (05.10.2012)
- (25) Filing Language: English
- (26) Publication Language: English
- (30) Priority Data:
61/544,416 7 October 2011 (07.10.2011) US
- (71) Applicant: **ATMI PACKAGING, INC.** [US/US]; 7 Commerce Drive, Danbury, CT 06810 (US).
- (72) Inventor: **PETHE, Vishwas**; 1668 Philipp Way, Shakopee, MN 55379 (US).
- (74) Agents: **HARGIS, Michael, S.** et al.; KING & SCHICKLI, PLLC, 247 North Broadway, Lexington, KY 40507 (US).
- (81) Designated States (*unless otherwise indicated, for every kind of national protection available*): AE, AG, AL, AM, AO, AT, AU, AZ, BA, BB, BG, BH, BN, BR, BW, BY, BZ, CA, CH, CL, CN, CO, CR, CU, CZ, DE, DK, DM,

DO, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT, HN, HR, HU, ID, IL, IN, IS, JP, KE, KG, KM, KN, KP, KR, KZ, LA, LC, LK, LR, LS, LT, LU, LY, MA, MD, ME, MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI, NO, NZ, OM, PA, PE, PG, PH, PL, PT, QA, RO, RS, RU, RW, SC, SD, SE, SG, SK, SL, SM, ST, SV, SY, TH, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, ZA, ZM, ZW.

- (84) Designated States (*unless otherwise indicated, for every kind of regional protection available*): ARIPO (BW, GH, GM, KE, LR, LS, MW, MZ, NA, RW, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, RU, TJ, TM), European (AL, AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT, LU, LV, MC, MK, MT, NL, NO, PL, PT, RO, RS, SE, SI, SK, SM, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

- with international search report (Art. 21(3))
- before the expiration of the time limit for amending the claims and to be republished in the event of receipt of amendments (Rule 48.2(h))

(54) Title: FLUID PROCESSING CONTROL SYSTEM AND RELATED METHODS




FIG. 1

(57) Abstract: In one aspect, a system for use in processing a fluid comprises a reservoir for holding the fluid and one or more bioreactors for receiving the fluid from the reservoir. One or more sensors are provided for sensing one or more parameters of the fluid, and corresponding control measures may be initiated. Regulators may also be provided for regulating various parameters of the fluid processing operation. Related systems and methods are also disclosed.