

Description

Background of the Invention

In conventional tank containers, the tank is disposed within a box-like framework the end parts of which are joined to each other via a base structure and upper longitudinal beams, so that the framework completely surrounds the tank.

DE-C-3 212 696 discloses a tank container in which the framework is reduced substantially to two rectangular end frames which are directly joined to the tank via end mounting structures, so that considerable savings in respect of material and weight are achieved.

With smaller tanks of for instance a maximum diameter of 1800 mm, as are used also as lift-on lift-off containers for dump body systems, frame structures of the specified kind are still unnecessarily heavy.

For lifting the known tank containers by means of cable lashings, grappler arms and spreaders, it is furthermore required that all four top corner fittings of the container framework or, respectively, all four grappler arm pockets provided on the framework should be engaged by the respective hoisting equipment. This entails corresponding expenditure of labour and time in the container handling.

A tank container with the features set forth in the first part of claim 1 is known from DE-A-2 532 492. In one embodiment illustrated in that document, the framework consists of a bottom structure and two end frames, each end frame including two supports slanting upwardly from the transverse beam of the bottom structure to form the shape of an equilateral triangle. In the transport and storage positions, the tank is rotated about its longitudinal axis within the framework by such an angle that the tank armatures including an upper manhole and a lower discharge funnel lie within those corners of the rectangular overall framework profile that are left free by the circular profile of the tank. This permits the tank to be made as large as possible within the available profile. Accordingly, the tank reaches the highest point of the framework profile in the transport and storage positions and extends beyond the framework profile in the filling and discharging positions.

The considerations underlying the known tank container are based on the usual box-shaped frame having a rectangular profile even though only triangular end frames are shown in one embodiment. If these are the only framework elements, the tank armatures are unprotected in all positions. Therefore, the known container is not suited in practice for handling by a number of usual hoisting equipments.

DE-A 2 736 449 discloses a transport tank with end frame structures each of which includes two legs that are inclined towards each other and are provided at their upper ends with fixtures that may be engaged by crane hooks. However, handling of this tank with most of the usually available equipment, such as grappler arms or spreaders, is not possible.

Summary of Invention

It is an object of the present invention to devise a tank container, particularly for smaller tank volumes which, while having the minimum possible weight, provides protection for the tank armatures and permits easy handling by the commonly available equipment.

According to the present invention, this object is met by the tank container defined in claim 1. Since the apices of the two frame structures are above the tank profile including its armatures, the latter are protected against damage. Further, the fittings which are also above the tank profile permit engagement by means of only two crane hooks or coupling to only two points of a spreader commonly used in container handling. Since the two framework top corners are disposed in the vertical central longitudinal plane which includes the center of gravity of the tank, the tank container can be lifted without any risk of tilting although being engaged at only two points.

The element interconnecting the legs of each framework structure further offers the possibility of lifting the tank container with only two grappler arms. Since each grappler arm pocket is limited at both ends by the two legs of the respective end frame structure, any lateral sliding-off of the grappler arm is excluded. Therefore, in contrast to conventional designs; the grappler arm pocket need be only slightly wider than commonly used grappler arms. The shorter the grappler arm pocket the further above the center of gravity can it be fitted into the framework structure; accordingly, lifting of the tank container by means of grapplers becomes increasingly safe against tilting. A further advantage resides in the fact that the grappler arm pocket fitted between the two legs of the framework structure reinforces the framework structure itself.

According to claim 2, further protection is achieved by the fact that the top corners of the framework structures are interconnected by means of a longitudinal beam which according to claim 3 is preferably detachable so that unhindered access to the tank connections will be possible if required. Such a longitudinal beam again improves the rigidity of the overall framework. The embodiments set out in claims 4 to 6 specify particularly simple and suitable solutions in respect of the detachability of the longitudinal beam and its anchoring to the framework structures.

The embodiment of the invention defined in claim 7 is particularly suitable for handling the tank container by means of a top spreader. Since the container has only two top fittings, only two of the total of four twistlocks provided on such a spreader will engage the container. Although the weight and design of these spreaders are such that they will function properly even under asymmetrical load, lifting the present tank container would result in a tilting within the twistlocks, which tilting is avoided by the measure of claim 7.

The structure of claim 8 is of particular advantage in that it ensures that the top fittings automatically return to their normal position when the con-

tainer is set down, so that the fittings will then be in their proper condition for being again engaged by spreader twistlocks or crane hooks. At the same time, the structure of claim 8 provides an abutment which limits the angle between the lower plane of the spreader and the plane of the tank container as determined by its weight.

In the further improvement of the invention according to claim 9, the bottom ends of the two legs of each framework structure are joined, preferably via respective corner fittings, to the ends of a bottom transverse beam of the framework.

On the other hand, according to claim 10 the concept of the invention can be used with a tank of an axial length that exceeds the spacing between the top framework corners as determined by the commonly used handling gear, due to the fact that the bottom ends of the two legs of each triangular framework structure are joined to a reinforcing ring surrounding the tank, which in its bottom region is joined via supports to a bottom transverse beam of the framework. The legs and also the supports may extend tangentially towards the reinforcing ring, or they may respectively be aligned with each other; in the latter case the individual framework structure is configured as a triangle which is interrupted by the circular shape of the tank cross-section.

The further developments set out in claims 11 to 13 concern additional advantageous measures for handling the tank container by means of the various conventional handling gear.

Brief Description of the Drawings

Figures 1 and 2 show an end view and a side view of a tank container,

Figures 3 and 4 show an end view and a side view of a tank container according to a second embodiment,

Figures 5 and 6 show a side view and an inner end view of the top right-hand corner portion, as viewed in Figures 2 and 4, of the container framework in a preferred configuration,

Figures 7 and 8 show a side view and an end view of a longitudinal beam joining the top corner portions, and

Figures 9 to 11 are partial views of an upper frame area according to another modification shown in three different operating positions.

Description of Preferred Embodiments

In the tank container illustrated in Figures 1 and 2, the framework is composed of two framework end structures 10 each being configured as an equilateral triangle and composed of two equal-length legs 11 and a bottom transverse beam 12. The bottom ends of the legs 11 are respectively joined to the extreme ends of the transverse beam 12 via a corner fitting 13. At the apex of the triangle, both legs 11 are welded to each other and are provided with a fitting 14 at their common top end. In its simplest form, the fitting 14 may be a horizontally extending plate provided

with an elongated opening for engagement by a twistlock as usually provided on spreaders, the plate being welded at its three sides to the three top edges of the legs 11, which are constituted by angle sections.

The tank 15, which as shown in the end view of Figure 1 has a circular-cylindrical cross-section, is joined to the legs 11 of the two framework structures 10 via end and mounting rings 16 extending from the tank ends. Such mounting structures composed of end and mounting rings are known from DE-C 3 232 696 in conjunction with rectangular end frames.

Between the bottom transverse beam 12 and the top corner fitting 14 at a level above the tank axis, the two legs 11 of each framework structure 10 are interconnected via a grapple arm pocket 17 the vertical plate of which is welded externally to the vertical flanges of the angle sections which constitute the legs 11.

As will be apparent from Figure 2, the two end framework structures 10 are further interconnected in the vicinity of their top apices by means of a preferably tubular longitudinal beam 18. The beam 18 extends above the tank armatures indicated at 19 and is detachably joined (not illustrated in detail) to the framework structures 10 so as to allow free access to said tank armatures. A preferred design for a detachable joint will be explained further below with reference to Figures 5 to 8.

The bottom transverse beams 12, which may be made from L-section material or square hollow-section material, are provided with two fork-lift channels 20. Furthermore, the bottom horizontal flange of each transverse beam 12 is provided with several openings for inserting twistlocks or other locking elements so that the tank container can be secured to a loading area not only at its bottom corner fittings 13 but also at intermediate locations. In the illustration of Figure 1, three locations are shown where such locking members may engage.

Each side of the tank 15 is provided with two cams 21 so that it can be used like a conventional lift-on lift-off tipping container in combination with dump body systems. The cams 21 are mounted on the tank shell by means of reinforcement plates 22. Reinforcing rings 23 which surround the bottom side of the tank also terminate at these plates 22. At their lowermost locations, the two reinforcing rings 23 are interconnected by means of a longitudinal beam 24 supporting the tank bottom. Two further forklift channels 25 extending perpendicularly to the tank axis are welded to the bottom side of said longitudinal beam 24 and reinforcing rings 23.

In the embodiment illustrated in Figures 3 and 4, the axial length of the tank 15 is greater than the length of the framework, which is based on the regular ISO spacing (2260 mm) of the twistlocks on ISO vehicles and ISO spreaders. Therefore the framework structures 30 - in contrast to the framework structures 10 of Figure 2 - are no longer provided endwise and joined to the tank ends but are connected to reinforcing rings 31 surrounding the tank shell. Basically, the framework structures 30 may have the same overall triangular configuration as the framework structures 10 of Figure 1, merely in-

interrupted by the tank 15. In that case (which is not illustrated) the top and bottom portions of each leg would lie on a straight line connecting the tip of the framework structure with the respective bottom corner fitting.

However, Figures 3 and 4 illustrate a design in which the top legs 32 of each framework structure extend at a less acute angle in comparison with Figure 1 and meet the reinforcing ring 31 approximately tangentially. The lower connection between the tank 15 and the bottom corner fittings 13 is effected by supports 33 which extend radially towards the tank and are likewise welded to the reinforcing rings. Alternatively, the supports 33 may extend vertically upwardly from the bottom corner fittings 13 and meet the reinforcing ring 31 tangentially.

As will be apparent from Figure 3, due to the larger angle included between the top legs 32 of the framework structure, the point where the grapple arm pocket 17 is inserted is still further above the tank 15.

When lifting the tank container by means of commonly used spreaders, two twistlocks thereof with their heads indicated in Figure 2 engage in top openings provided in the fittings 14. Since modern spreaders are provided with an automatic control which will only be operative when all four spreader twistlocks engage the usually four top corners of a container, provision must be made for correspondingly switching over said control so as to permit handling of the presently described tank containers. In any case the illustrated tank containers only require to be coupled to two points of the lifting gear, and due to the symmetric design relative to the vertical longitudinal center plane of the tank any risk of tilting is prevented. The same applies to lifting the tank container by means of two grapple arms engaging the grapple arm pockets 17.

The tank container may be lifted likewise without a risk of tilting by means of only two crane hooks. To this end it is advantageous when the top fitting 14 consists not only of a horizontal plate as illustrated in Figures 1 and 2 but is designed as a cuboid fitting 34 of the type illustrated in Figures 3 and 4, which is provided with an elongated hole not only in its upper surface but also in the surface remote from the opposite fitting.

In the preferred embodiment illustrated in detail in Figures 5 and 6, the fitting 44 provided at the tip of each framework structure 10 includes an ISO corner fitting 45 which in a direction transversely to the tank axis is made broader by means of a U-shaped plate 46 such that the outwardly and upwardly facing openings 47 and 49 are situated symmetrically with respect to the enlarged fitting 44. The plate 46 is welded to the surface which in the normal use of an ISO corner fitting would face the tank and which is opposite to the surface having a further opening 48.

In the surface of the fitting 44 which is opposite the opening 47 and in alignment therewith, there is provided a keyhole-shaped opening 50 which consists of a circular portion with an upwardly extending slot. As will be clearly apparent from Figure 6, the overall height of the opening 50 and the diame-

ter of the circular portion thereof are identical with the height and width of the elongated opening 47, respectively.

In conformity with the configuration of the fitting 44 shown in Figures 5 and 6, the end of the tubular longitudinal beam 18 illustrated in Figures 7 and 8 is designed like a key, wherein the "bit" includes two web portions 51, 52 mutually spaced by a distance which is slightly smaller than the wall thickness of the fitting 44 in the vicinity of the opening 50. The profile of this key-shaped end of the longitudinal beam 18 is dimensioned so that it can be inserted into the opening 50 of Figure 6. The two framework structures 10 and the two ends of the longitudinal beam 18 are designed to be symmetrical with respect to the central transverse plane of the tank container.

For assembly, one end of the longitudinal beam 18 is initially inserted into the opening 50 of a fitting 44 and is pushed through the outer opening 47 thereof until the other end is within the opposite framework structure 10 and can now be inserted into the fitting provided thereat by movement of the longitudinal beam 18 in the opposite direction. As soon as the web portion 51 at either end of the longitudinal beam 18 is outside of the respective fitting 44 and the web portion 52 is inside the same, the beam 18 will be locked by rotation to the position illustrated in Figure 5. Due to the weight of the web portions 51, 52 this anchoring cannot undo itself; additional locking means may be provided. Even with the beam 18 anchored, the openings 47 to 49 of both fittings 44 remain freely accessible for engagement of spreaders, crane hooks or other commonly used handling gear.

In the embodiment of Figures 9 to 11, the design of the upper area of each triangular framework structure 10 differs from that of the preceding embodiments in that the fitting 54 forms the upper wall member of a U-shaped bracket 55 of which only an outer wall is shown in Figures 9 to 11. The bracket 55 straddles a structural member 56 which forms the upper portion of the framework structure 10. A pivot pin 57 extending parallel to the tank axis is provided in the bracket 55 and penetrates an opening 58 provided in the member 56. In their upper portions, the two side wall members of the bracket 55 are provided with openings 47, 59 which are formed like the corresponding openings in the corner fitting 54 of Figures 5 and 6 and serve for detachably locking the longitudinal beam 18 (not shown).

The pin 57 has a peripheral surface which in its upper portion extending through e.g. 270° is formed circular-cylindrical and in its lower portion forms a rectangular V-shape. The opening 58 is formed as an elongated hole with its longest axis extending perpendicularly. In its upper portion, the opening 58 has a cylindrical surface extending through 180°, while its lower portion is provided with a V-groove shaped complementarily to the V-portion of the pivot pin 57.

In the partial representation of Figure 9, the tank container is shown in a set-down condition in which the bracket 55, due to its own weight, is in its lowermost position, and the pivot pin 57 rests in the lower-

most portion of the opening 58. The lower V-shapes of the pin 57 and opening 58 cause the bracket 55 to assume an upright position in which the upper wall member of the fitting 54 extends horizontally.

In this attitude, the fitting 54, which in its upper wall member has an opening similar to the opening 49 in the corner fitting 45 of Figures 5 and 6, may be lifted for instance by means of the twistlock of a spreader schematically shown at 59 in Figures 10 and 11. Figure 10 shows the condition in which the spreader 59 has lifted only the bracket 55, whereas the tank container itself is still supported from below. In this condition, the pin 57 has moved towards the upper surface of the opening 58. The two cylindrical surfaces of the pin 57 and opening 58 now cooperate to form a pivot having an axis parallel to the tank axis.

In Figure 11, the spreader 59 has lifted the tank container and now tilts due to the fact that the weight of the tank container suspends from only two of the total of four twistlocks, thus asymmetrically with respect to the axis of gravity of the spreader. (The tilting angle has been exaggerated in Figure 11 for the sake of clarity.) As shown in Figure 11, the pin 57 provided in the bracket 55 has rotated with respect to the opening 58. The maximum angle of rotation is limited by a side surface of the V-shaped lower portion of the pin 57 abutting against the corresponding vertical side surface of the opening 58.

While Figures 9 to 11 assume that the pin 57 is connected to the bracket 55 and the opening 58 is provided in the upper member 56 of the framework structure 10, it is alternatively possible to provide the member 56 with studs extending inwardly and outwardly and extending through corresponding openings provided in the bracket 55.

Claims

1. A tank container comprising a framework and a substantially cylindrical tank (15) defining a tank axis, said framework including two framework structures (10, 30) extending transversely of said tank axis and each having legs (11, 32) which form the upwardly extending sides of an imaginary equilateral triangle and have their upper ends interconnected at an apex disposed perpendicularly above said tank axis, said tank (15) having upper armature means (19) and being connected to said two framework structures (10, 30), characterized in that the apex of each said framework structure (10, 30) is positioned above the profile of said tank (15) including said upper armature means (19) and is provided with a top fitting (14, 34, 44, 54) for engagement by hoisting equipment, and that said legs (11, 32) of each said framework structure (10, 30) are joined to each other at a level intermediate said apex and the base line of said imaginary triangle via an element (17) adapted to be engaged by a grapple arm.

2. The tank container of claim 1, wherein said two framework structures (10, 30) are joined to each other at their apices via a longitudinal beam (18).

3. The tank container of claim 2, wherein said longitudinal beam (18) is detachably connected to said framework structures (10, 30).

4. The tank container of claim 3, wherein said longitudinal beam (18) has key-shaped configurations at both ends thereof for engagement in keyhole-shaped openings (50) formed in the mutually facing surfaces of said top fittings (44).

5. The tank container of claim 4, wherein each keyhole-shaped opening (50) has a slot extending upwardly from a circular portion, each end of the longitudinal beam (18) including first and second web portions (51, 52) which, when said beam end engages said opening (50) are disposed outside and inside of said opening, respectively.

6. The tank container of claim 4 or 5, wherein said fitting (44) is formed of an ISO corner fitting (45) having an opening (49) in its top surface and being widened by a structural part (46) attached to it in a direction transverse to the tank axis such that said upper opening (49) is disposed symmetrically with respect to the overall width of said fitting (44).

7. The tank container of any one of claims 1 to 6, wherein the top fittings (54) are each formed on a bracket (55) which is mounted at an upper portion (56) of the respective triangular framework structure (10) for pivotal movement about an axis parallel to said tank axis.

8. The tank container of claim 7, wherein said bracket (55) is mounted to said upper portion (56) by means of a pivot pin (57) rotatable in an opening (58), the engaging peripheral surfaces of the opening (58) and pin (57) are formed circular-cylindrical in their upper portions and have complementary V-shapes in their lower portions, said opening (58) being elongated in the perpendicular direction.

9. The tank container of any one of claims 1 to 8, wherein the lower ends of said legs (11) of each said framework structure (10) are joined to the ends of a bottom transverse beam (12) via respective corner fittings (13).

10. The tank container of any one of claims 1 to 8, wherein the lower ends of the two legs (32) of each said framework structure (30) are connected to a reinforcing ring (31) surrounding said tank (15), said reinforcing ring (31) being in turn connected via supports (33) to corner fittings (13) of bottom transverse beams (12) extending transversely of said tank axis.

11. The tank container of claim 9 or 10, wherein said bottom transverse beams (12) are provided with fork-lift pockets (20) and/or openings for engagement of locking elements.

12. The tank container of any one of claims 1 to 11, including fork-lift channels (25) extending transversely of said tank axis below said tank (15) and being supported by reinforcing rings (23) which at least partially surround said tank (15).

13. The tank container of any one of claims 1 to 12, wherein said tank (15) is provided with laterally projecting cams (21) for accommodation in dump body systems.

Patentansprüche

1. Tankcontainer mit einem Rahmen und einem eine Tankachse definierenden, im wesentlichen zylindrischen Tank (15), wobei der Rahmen zwei quer zur

most portion of the opening 58. The lower V-shapes of the pin 57 and opening 58 cause the bracket 55 to assume an upright position in which the upper wall member of the fitting 54 extends horizontally.

In this attitude, the fitting 54, which in its upper wall member has an opening similar to the opening 49 in the corner fitting 45 of Figures 5 and 6, may be lifted for instance by means of the twistlock of a spreader schematically shown at 59 in Figures 10 and 11. Figure 10 shows the condition in which the spreader 59 has lifted only the bracket 55, whereas the tank container itself is still supported from below. In this condition, the pin 57 has moved towards the upper surface of the opening 58. The two cylindrical surfaces of the pin 57 and opening 58 now cooperate to form a pivot having an axis parallel to the tank axis.

In Figure 11, the spreader 59 has lifted the tank container and now tilts due to the fact that the weight of the tank container suspends from only two of the total of four twistlocks, thus asymmetrically with respect to the axis of gravity of the spreader. (The tilting angle has been exaggerated in Figure 11 for the sake of clarity.) As shown in Figure 11, the pin 57 provided in the bracket 55 has rotated with respect to the opening 58. The maximum angle of rotation is limited by a side surface of the V-shaped lower portion of the pin 57 abutting against the corresponding vertical side surface of the opening 58.

While Figures 9 to 11 assume that the pin 57 is connected to the bracket 55 and the opening 58 is provided in the upper member 56 of the framework structure 10, it is alternatively possible to provide the member 56 with studs extending inwardly and outwardly and extending through corresponding openings provided in the bracket 55.

Claims

1. A tank container comprising a framework and a substantially cylindrical tank (15) defining a tank axis, said framework including two framework structures (10, 30) extending transversely of said tank axis and each having legs (11, 32) which form the upwardly extending sides of an imaginary equilateral triangle and have their upper ends interconnected at an apex disposed perpendicularly above said tank axis, said tank (15) having upper armature means (19) and being connected to said two framework structures (10, 30), characterized in that the apex of each said framework structure (10, 30) is positioned above the profile of said tank (15) including said upper armature means (19) and is provided with a top fitting (14, 34, 44, 54) for engagement by hoisting equipment, and that said legs (11, 32) of each said framework structure (10, 30) are joined to each other at a level intermediate said apex and the base line of said imaginary triangle via an element (17) adapted to be engaged by a grappeler arm.

2. The tank container of claim 1, wherein said two framework structures (10, 30) are joined to each other at their apices via a longitudinal beam (18).

3. The tank container of claim 2, wherein said longitudinal beam (18) is detachably connected to said framework structures (10, 30).

4. The tank container of claim 3, wherein said longitudinal beam (18) has key-shaped configurations at both ends thereof for engagement in keyhole-shaped openings (50) formed in the mutually facing surfaces of said top fittings (44).

5. The tank container of claim 4, wherein each keyhole-shaped opening (50) has a slot extending upwardly from a circular portion, each end of the longitudinal beam (18) including first and second web portions (51, 52) which, when said beam end engages said opening (50) are disposed outside and inside of said opening, respectively.

6. The tank container of claim 4 or 5, wherein said fitting (44) is formed of an ISO corner fitting (45) having an opening (49) in its top surface and being widened by a structural part (46) attached to it in a direction transverse to the tank axis such that said upper opening (49) is disposed symmetrically with respect to the overall width of said fitting (44).

7. The tank container of any one of claims 1 to 6, wherein the top fittings (54) are each formed on a bracket (55) which is mounted at an upper portion (56) of the respective triangular framework structure (10) for pivotal movement about an axis parallel to said tank axis.

8. The tank container of claim 7, wherein said bracket (55) is mounted to said upper portion (56) by means of a pivot pin (57) rotatable in an opening (58), the engaging peripheral surfaces of the opening (58) and pin (57) are formed circular-cylindrical in their upper portions and have complementary V-shapes in their lower portions, said opening (58) being elongated in the perpendicular direction.

9. The tank container of any one of claims 1 to 8, wherein the lower ends of said legs (11) of each said framework structure (10) are joined to the ends of a bottom transverse beam (12) via respective corner fittings (13).

10. The tank container of any one of claims 1 to 8, wherein the lower ends of the two legs (32) of each said framework structure (30) are connected to a reinforcing ring (31) surrounding said tank (15), said reinforcing ring (31) being in turn connected via supports (33) to corner fittings (13) of bottom transverse beams (12) extending transversely of said tank axis.

11. The tank container of claim 9 or 10, wherein said bottom transverse beams (12) are provided with fork-lift pockets (20) and/or openings for engagement of locking elements.

12. The tank container of any one of claims 1 to 11, including fork-lift channels (25) extending transversely of said tank axis below said tank (15) and being supported by reinforcing rings (23) which at least partially surround said tank (15).

13. The tank container of any one of claims 1 to 12, wherein said tank (15) is provided with laterally projecting cams (21) for accommodation in dump body systems.

Patentansprüche

1. Tankcontainer mit einem Rahmen und einem eine Tankachse definierenden, im wesentlichen zylindrischen Tank (15), wobei der Rahmen zwei quer zur



* C L M S *

Tankachse stehende Rahmengruppen (10, 30) mit jeweils zwei Schenkeln (11, 32) umfaßt, die die nach oben verlaufenden Seiten eines gedachten gleichschenkligen Dreiecks bilden und mit ihren oberen Enden an einer senkrecht über der Tankachse gelegenen Spitze miteinander verbunden sind, wobei der Tank (15) obere Armatureinrichtungen (19) aufweist und mit den Rahmengruppen (10, 30) verbunden ist, dadurch gekennzeichnet, daß die Spitzen jeder Rahmengruppe (10, 30) oberhalb des Profils des Tanks (15) einschließlich der oberen Armatureinrichtungen (19) liegt und mit einem oberen Beschlag (14, 34, 44, 54) zum Eingriff von Hebezeugen versehen ist, und daß die Schenkel (11, 32) jeder Rahmengruppe (10, 30) auf einer zwischen der Spitze und der Grundlinie des gedachten Dreiecks liegenden Höhe über ein für den Eingriff eines Greifarm geeignetes Bauelement (17) miteinander verbunden sind.

2. Tankcontainer nach Anspruch 1, wobei die beiden Rahmengruppen (10, 30) an ihren Spitzen über einen Längsholm (18) miteinander verbunden sind.

3. Tankcontainer nach Anspruch 2, wobei der Längsholm (18) lösbar mit den Rahmengruppen (10, 30) verbunden ist.

4. Tankcontainer nach Anspruch 3, wobei der Längsholm zum Eingriff in schlüsselloch-artige Öffnungen (50) in den einander zugewandten Flächen der Beschläge (44) an seinen beiden Enden schlüsselartig gestaltet ist.

5. Tankcontainer nach Anspruch 4, wobei jede schlüssellochartige Öffnung (50) einen an einen kreisrunden Teil oben ansetzenden Schlitz aufweist und jedes Ende des Längsholms (18) einen ersten und einen zweiten Stegteil (51, 52) enthält, die außerhalb bzw. innerhalb der Öffnung (50) liegen, wenn das Holmende in diese eingreift.

6. Tankcontainer nach Anspruch 4 oder 5, wobei der Beschlag (44) aus einem ISO-Eckbeschlag (45) aufgebaut ist, der in seiner oberen Fläche eine Öffnung (49) aufweist und durch ein Bauteil (46) verbreitert ist, das in Richtung quer zur Tankachse derart angesetzt ist, daß die obere Öffnung (49) bezüglich der Gesamtbreite des Beschlags (44) symmetrisch liegt.

7. Tankcontainer nach einem der Ansprüche 1 bis 6, wobei die oberen Beschläge (54) jeweils an einer Lasche (55) ausgebildet sind, die um eine zur Tankachse parallele Achse schwenkbar an einem oberen Bereich (56) der betreffenden dreieckigen Rahmengruppe (10) angelenkt ist.

8. Tankcontainer nach Anspruch 7, wobei die Lasche (55) an dem besagten oberen Bereich (56) mittels eines in einer Öffnung (58) drehbaren Zapfens (57) gelagert ist, wobei die ineinander greifenden Umfangsflächen von Öffnung (58) und Zapfen (57) in ihren oberen Teilen kreiszylindrisch ausgebildet sind und in ihren unteren Teilen komplementäre Keilformen bilden, und wobei die Öffnung (58) in der senkrechten Richtung länglich ist.

9. Tankcontainer nach einem der Ansprüche 1 bis 8, wobei die unteren Enden der Schenkel (11) jeder Rahmengruppe (10) über jeweils einen Eckbeschlag (13) mit den Enden eines unteren Querholms (12) verbunden sind.

10. Tankcontainer nach einem der Ansprüche 1 bis 8, wobei die unteren Enden der beiden Schenkel (32) jeder Rahmengruppe (30) mit einem den Tank (15) umgebenden Verstärkungsring (31) verbunden sind, der seinerseits über Stützen (33) mit Eckbeschlägen (13) von quer zur Tankachse verlaufenden unteren Querholmen (12) verbunden ist.

11. Tankcontainer nach Anspruch 9 oder 10, wobei die unteren Querholme (12) mit Gabelstapleröffnungen (20) und/oder Öffnungen zum Eingriff von Arretierungselementen versehen sind.

12. Tankcontainer nach einem der Ansprüche 1 bis 11, mit quer zur Tankachse unterhalb des Tanks (15) verlaufenden Gabelstaplerkanälen (25), die sich an den Tank (15) mindestens teilweise umgebenden Verstärkungsringen (23) abstützen.

13. Tankcontainer nach einem der Ansprüche 1 bis 12, wobei der Tank (15) mit seitlich herausragenden Nocken (21) zur Aufnahme in Kippmuldensystemen versehen ist.

Revendications

1. Conteneur-citerne comprenant un châssis et une citerne (15) sensiblement cylindrique et définissant un axe de citerne, ledit châssis comprenant deux structures de châssis (10, 30) s'étendant transversalement audit axe de citerne et comprenant chacune deux jambes (11, 32) qui forment les côtés s'étendant vers le haut d'un triangle équilatéral imaginaire et dont les extrémités supérieures sont interconnectées au niveau d'un sommet disposé perpendiculairement au-dessus dudit axe de citerne, ladite citerne (15) comprenant des moyens d'armature supérieurs (19) et étant reliée auxdites deux structures de châssis (10, 30) caractérisé en ce que le sommet de chacune desdites structures de châssis (10, 30) est situé au-dessus du profil de ladite citerne (15) y compris lesdits moyens d'armature supérieurs (19) et est muni d'une garniture supérieure (14, 34, 44, 54) pour coopérer avec un équipement de levage, et en ce que lesdites jambes (11, 32) de chacune desdites structures de châssis (10, 30) sont reliées l'une à l'autre à un niveau intermédiaire entre ledit sommet et ladite ligne de base dudit triangle imaginaire par un élément (17) adapté à être accroché par un bras à grappin.

2. Conteneur-citerne selon la revendication 1, dans lequel lesdites deux structures de châssis (10, 30) sont reliées l'une à l'autre à leurs sommets par une poutre longitudinale (18).

3. Conteneur-citerne selon la revendication 2, dans lequel ladite poutre longitudinale (18) est reliée de façon amovible auxdites structures de châssis (10, 30).

4. Conteneur-citerne selon la revendication 3, dans lequel ladite poutre longitudinale (18) présente des configurations en forme de clavettes à ses deux extrémités, destinées à s'engager dans des ouvertures en forme de trou de serrure (50) formées dans les surfaces mutuellement opposées desdites garnitures supérieures (14).

5. Conteneur-citerne selon la revendication 4, dans lequel chaque ouverture en forme de trou de serrure (50) comprend une fente s'étendant vers le



hal
mit
pre
qui,
dar
rieu
mer
6
5, c
une
ouv
ren
fixé
de
rieu
port
7
rev
péri
sole
rieu
resp
pivc
tem
8
dan
port
mer
les
l'ouv
laire
et p
dan
(58)
9
reve
rieu
stru
tés
l'int
(13)
1
rev
rieu
stru
de
dit
reli
(13)
s'é
de
10,
rier
fou
me
rev
(25)
sal
so
de
mo
rev

haut à partir d'une portion circulaire, chaque extrémité de la poutre longitudinale (18) comprenant des première et seconde portions de nervures (51, 52) qui, lorsque ladite extrémité de poutre s'engage dans ladite ouverture (50), sont disposées à l'extérieur et à l'intérieur de ladite ouverture, respectivement.

6. Conteneur-citerne selon la revendication 4 ou 5, dans lequel ladite garniture (44) est formée par une garniture d'équerre ISO (45) comprenant une ouverture (49) dans sa surface supérieure et étant rendue plus large par une pièce structurelle (46) fixée à elle dans une direction transversale à l'axe de la citerne de manière que ladite ouverture supérieure (49) soit disposée symétriquement par rapport à la largeur d'ensemble de ladite garniture (44).

7. Conteneur-citerne selon l'une quelconque des revendications 1 à 6, dans lequel les garnitures supérieures (54) sont chacune formées sur une console (55) qui est montée dans une portion supérieure (56) de la structure de châssis triangulaire respective (10) de façon à effectuer un mouvement pivotant autour d'un axe parallèle audit axe de citerne.

8. Conteneur-citerne selon la revendication 7, dans lequel ladite console (55) est montée sur ladite portion supérieure (56) au moyen d'un axe de pivotement (57) pouvant tourner dans une ouverture (58), les surfaces périphériques d'engagement de l'ouverture (58) et de l'axe (57) ont une forme circulaire et cylindrique dans leurs portions supérieures et présentent des formes complémentaires en V dans leurs portions inférieures, ladite ouverture (58) étant allongée dans la direction perpendiculaire.

9. Conteneur-citerne selon l'une quelconque des revendications 1 à 8, dans lequel les extrémités inférieures desdites jambes (11) de chacune desdites structures de châssis (10) sont reliées aux extrémités d'une poutre transversale inférieure (12) par l'intermédiaire de garnitures d'équerre respectives (13).

10. Conteneur-citerne selon l'une quelconque des revendications 1 à 8, dans lequel les extrémités inférieures des deux jambes (32) de chacune desdites structures de châssis (30) sont reliées à un anneau de renforcement (31) entourant ladite citerne (15), ledit anneau de renforcement (31) étant de son côté relié par des supports (33) aux garnitures d'équerre (13) de poutres transversales inférieures (12) s'étendant transversalement par rapport audit axe de citerne.

11. Conteneur-citerne selon la revendication 9 ou 10, dans lequel lesdites poutres transversales inférieures (12) sont munies de poches pour élévateur à fourche (20) et/ou d'ouvertures d'engagement d'éléments de verrouillage.

12. Conteneur-citerne selon l'une quelconque des revendications 1 à 11, comprenant des passages pour élévateur à fourche s'étendant transversalement par rapport audit axe de citerne au-dessus de ladite citerne (15) et étant supportés par des anneaux de renforcement (23) entourant au moins en partie ladite citerne (15).

13. Conteneur-citerne selon l'une quelconque des revendications 1 à 12, dans lequel ladite citerne (15)

est munie de saillies (21) s'étendant latéralement et prévues pour se loger dans des systèmes à bac basculant.

