



INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁶ : C07D 303/16, C08G 59/12	A1	(11) International Publication Number: WO 98/52932 (43) International Publication Date: 26 November 1998 (26.11.98)
(21) International Application Number: PCT/EP98/03018 (22) International Filing Date: 19 May 1998 (19.05.98) (30) Priority Data: 97201532.5 22 May 1997 (22.05.97) EP (34) Countries for which the regional or international application was filed: AT et al. (71) Applicant: SHELL INTERNATIONALE RESEARCH MAATSCHAPPIJ B.V. [NL/NL]; Carael van Bylandtlaan 30, NL-2596 HR The Hague (NL). (72) Inventors: VAN DOORN, Johannes, Adrianus; Badhuisweg 3, NL-1031 CM Amsterdam (NL). SMITS, Jozef, Jacobus, Titus; Badhuisweg 3, NL-1031 CM Amsterdam (NL).		(81) Designated States: AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CU, CZ, DE, DK, EE, ES, FI, GB, GE, GH, GM, GW, HU, ID, IL, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, UA, UG, UZ, VN, YU, ZW, ARIPO patent (GH, GM, KE, LS, MW, SD, SZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, ML, MR, NE, SN, TD, TG). Published <i>With international search report.</i> <i>Before the expiration of the time limit for amending the claims and to be republished in the event of the receipt of amendments.</i>
(54) Title: GLYCIDYLESTER AND THERMOSETTING RESIN COMPOSITION COMPRISING THE GLYCIDYLESTER (57) Abstract A glycidylester of general formula (I) in which R₁ and R₄ are the same or different C₁-C₆ alkyl or C₆-C₁₀ cycloalkyl groups, and R₂ and R₃ are the same or different and are H or C₁-C₆ alkyl or C₆-C₁₀ cycloalkyl groups. The glycidylester is used in a thermosetting resin composition, comprising also a curing compound and preferably an advanced resin product. The thermosetting resin composition can be applied for outdoor durable coatings, having excellent resistance against acid rain. (I)		