

MEANS FOR EMPTYING PACKAGES

The Technical Field

The present invention relates to means for cutting
5 sacks in order to empty a more or less powder shaped
content into a container means, such as for example a bag
or the like. More specifically, the invention relates to a
means for emptying the content out of a package at an
offshore location, comprising a means for cutting up the
10 package, means for separating the content in the sacks
from the sacks and means for removing the emptied
packages. The means for separating the content at least
from the package comprises a means for cutting up the
package, one or more transporting screws and a rotating
15 drum provided with openings, through which the separated
content of the packages is allowed to escape out of the
drum.

Background for the Invention

20 During drilling of offshore wells a drill liquid is
required. Such drill liquid may be water based or oil
based. The drill liquid consists of a mixture of a number
of different chemicals and compounds, and several of these
ingredients represent a risk for the human being. The
25 chemicals are commonly supplied in sacks of 25-30 kg and
the content of the sacks is fed into a mixer and mixed
into a circulating drill fluid. The drill fluid has to be
tailor made to the specific requirements at any time, the
need for different mixtures often being changed. On this
30 basis it is thus required that the mixing of the drill
liquid is executed on the platform as an integral part of
the drilling operation.

The problem to be solved is thus how to cut up the
sacks and empty these in order to mix the content of the

sacks into the circulating drill liquid in a most efficient manner. Such mixing should, amongst other due to the health hazards, but also from an economical point of view, be automatic and without representing a health risk for the operator.

A large number of different machines, performing such operations, are already available on the market.

US 4,930,968 describes a sack cutting machine comprising a unit for cutting up the sack so that the powder inside may be released, a first transporting screw for transport of the powder and the sack; a drum for separating the powder from the sack, the first transport screw being concentrically arranged in the drum; a feeding screw arranged below the drum and in open communication with the drum for transport of the powder to a separate location and a means for collecting ripped, empty sacks, arranged at the opposite side of the drum and said first feeding screw, seen with respect to the feeding opening for filled sacks. According to this solution an intact sack with its powder content is fed into the machine at the end of the sack cutting means, whereupon the sack by means of the first transporting screw is moved in a direction towards a stopper whereby the sack is cut and the content released, whereupon the direction of rotation is reversed.

EP 1 123 868 describes a sack cutting machine in the form of a feeding screw, arranged in a tray, provided with fixed knives for cutting the sack, and a drum arranged at one end of the feeding screw, the content being separated from the sack in said drum. At the opposite end an opening directing towards a tray for collection of empty sacks is arranged.

Summary of the Invention

An object of the invention is to provide a solution

suitable for being placed on an offshore platform, such solution also must be reliable and eliminating, or at least substantially reducing, the health risks for the operator.

5 A second object is to provide a machine securing correct quality of the drill liquid in an efficient and cost optimal way.

 A still further object is to provide a machine which quickly may adjust or change the content or mixture of the
10 drill liquid.

 The objects are achieved by means of a solution as further defined by the characterized part of the independent claim.

 According to the invention, the drum is suspended and
15 floats freely without being supported by shafts and bearings, the drum being suspended by at least one belt extending around the drum, said belt also running over at least one in respect to the drum, separated, rotating driving shaft.

20 According to one embodiment, said at least one belt is a chain belt running over a correspondingly configured wheel on said at least one driving shaft.

 The chain belt may for example be a sphere or ball string running over a correspondingly configured wheel on
25 said at least one driving shaft.

 According to a further embodiment the drum may be provided with corresponding tracks extending around the periphery of the drum and co-functioning with said belt in order to cause said rotation of the drum. In connection
30 with the drum, a guiding means may be provided, securing that the drum is kept in proper position during rotation.

 Such guiding means may comprise rotating wheels which runs in contact against the outer surface of the drum, at the upper part and possibly also at the lower part of the

drum. At last four rotatably arranged wheels may for example be used at the upper end, and possibly also with wheels arranged at the lower end of the drum. In stead of, or in addition, guiding means may be in the form of at least one rail shaped guide having a curved support surface corresponding to the outer shape of the drum. One or more guides may also lie in contact with the lower external surface of the drum.

In order to prevent axial displacement of the drum, the drum may lie on contact with one or more stopping surfaces or means.

With a solution according to the present invention a solution is provided being so compact that the footprint is reduced as much as possible, so that the unit is well suited for being installed on an offshore platform.

Short Description of the Drawings

In the following an embodiment of the invention shall be described in closer detail, referring to the drawings, where:

Figure 1 shows schematically a side view of an embodiment of the invention;

Figure 2 shows a vertical section through the sack cutting means, seen along the line A-A in Figure 1;

Figure 3 shows a vertical section through the sack cutting means, seen along the line B-B in Figure 1; and

Figure 4 shows a vertical section through the sack cutting means, seen along the line C-C in Figure 1.

Detailed Description of the Invention

Figure 1 shows schematically a side view of a preferred embodiment of a sack cutting means 10 according to the invention. The sack cutting means 10 comprises four main elements. These are the cutting means 11, a separa-

tion means 21, a transporting means 38 and a compressing means 20.

The cutting means 1 consists of a housing or casing 25 with a rotatable cutting screw 22. The screw is in the form of a central shaft 12 and a helical blade body 13 twisting along the central shaft 12. The blade body 11 is rigidly fixed to the central shaft 12. The screw means 11 is powered by a driving unit 14, such as an electro motor and preferably a gear. At least one end of the screwing means 11 is supported in the housing 15. The housing 15 may preferably surround the screw 13, so that a tray 16 is formed at least at the lower side of the housing. The tray 16 is along its bottom part provided with openings 26 allowing the content of the sacks to escape, so that said content is allowed fall out of the tray 16. The perforated grating in the tray 16 may preferably be suspended on rubber rails or similar dampening means, allowing a degree of vibration of the tray if required, without transferring possible vibrations to the remaining parts of the machine. Such vibration secures that the content from the sacks is transported out of the tray. A means (not shown) for transferring the content from the sacks for example to a mixing container is arranged below the perforated tray. Such means for transportation may be of any suitable type, well known to the person skilled in the art.

At the end of the housing 15 where the screw 13 is connected to the powering unit 14, the upper part of the housing is provided with an inlet opening 27. The inlet opening 27 may preferably be provided with a preferably dustproof lid, the lid being connected to a switch so that the screw is not allowed to rotate when the lid is not in a closed position. In such way dust and powder is prevented from escaping uncontrolled from the unit and the possibility of causing injury to the operator is eliminated.

At the opposite end of the housing 15 the separating means 21 is arranged. The separating means 21 comprises a house or a casing comprising a cylindrical, rotatably arranged grating or drum 17, separating the remaining part of the powder and the packaging. The separating means is orientated in such way with respect to the cutting screw 22 that the cutting screw 22 is partly projecting into the rotatably arranged grating 17. The grating 17 is provided with openings so that the powder or the fine graded material is fed into the grating by the cutting screw 22, is allowed to fall out through said openings 18, while the ripped sack (not shown) is transported axially out through the rotating drum in any suitable way. The rotatable drum 17 is made of grating or of a perforated plate and is suspended by one or more belts or chains 28 which is suspended on a rotatably shaft 29, connected to a power unit (not shown), such as an electro motor or the like, and preferably a gear. In order to prevent sideways displacement of the drum 17, the drum 17 is kept in place by means of a plurality of guiding wheels 30. Four guiding wheels 30 may for example be used, arranged in pairs in spaced relation from each other at the upper side of the drum 17. Guiding wheels may optionally also be arranged at the lower side of the drum 17. The drum 17 may optionally also be supported against axial movement or displacement by a contact surface or the like (not shown) at each end of the drum 17. Internally in the drum 17 blades 23 are arranged forcing the package around and at the same time moving the package in axial direction out of the drum 17.

Below that part of the sack cutter 10 a compressing means 20 is arranged. Said compressing means 20 comprises a housing 24 containing a rotatable screw 32 rotating in a duct ending at an outlet. This end may be connected to a collecting means, such as a bag for receipt of emptied

packages as such emptied sacks are forced out of a transfer pipe 24 and into the collecting means by means of the rotating screw 32. The rotating screw 32 is powered by a driving unit (not shown), such as an electro motor. The outlet 24 is arranged below the sack cutting means and the screw 34 is configured in such way that the emptied sack moves from right towards left in the Figure. An emptied sack exits the drum 21 at the free end and is then fed or falling down through an opening 40 down onto the screw 34, moving the emptied sack back under the drum and out through the opening 24 at the opposite end of the screw 14.

The content in the sacks, which often is in the form of powder, is transported out of the unit 10 through the exit pipe 31, arranged at the end of the unit 10 and communicating with the screw 38.

As shown in Figure 1 the sack cutting means 10 is supported by a plurality of legs 39.

Figure 2 shows a vertical section through the screw cutting means 11, seen along the line A-A in Figure 1. As shown in Figure 1, a feeding table 35 provided with a cover comprising a dust proof lid 36 is arranged in conjunction with the opening 27. Further, the entire sack cutting means 10 may be completely enclosed in its own housing 37, so that the entire unit is enclosed, thus avoiding emission of dust to the environment. Further, along the bottom of the entire sack cutting unit 30 along its entire length a transport means 38 is arranged for transport of the content of the sacks out of the sack cutting means 10. Said transport means 38 may for example be in the form of a screw or the like, preferably rotating in such direction that the content of the sacks is transported out of the machine. The transport means 38 is arranged at the bottom of a tray shaped channel, the

channel being in open communication with a tray 16 above through openings communication with the sack cutting screw 22 and the perforated drum 21. It should be appreciated, however, that in certain cases it may be desirable to provide the sack cutting means with a reservoir comprising a feed in stead of a transport screw.

Figure 3 shows a vertical section through the part of the sack cutting means 10 where the drum 17 is arranged, while Figure 4 shows a vertical section seen along the line C-C in Figure 1. As shown in Figure 4, an open channel 40 leads the emptied sack down into the compressing unit 20. As indicated in Figure 4 the compression unit is sideways displaced with respect to the drum 17 and the axis of the cutting blades 13.

The functioning of the sack cutting means according to the invention shall in the following be described in further details.

The sack with its content, for example in the form of a powder or a fine, uniformly graded material, is fed into the sack cutting means 10 through the opening 27. The cutting screw 22 starts and rotates in a direction so that the sack is screwed towards the rotating grating 17. On its way towards the grating 17, the sack is cut open by means of the cutting screw 11, which also transports the opened sack in direction towards the rotating grating 17, while the main part of the content of the sack falls down through the openings 26. According to the invention, the sack is cut into pieces by the helically shaped blades 13 on the screw 11, the blade edges cutting through the sack material. The blades may be provided with knives, securing proper cutting of the sacks. The sack is fed into one end of the rotating grating 17, where the sack is turned around by means of internally arranged blades 23 inside the grating 17. The blades 23 move also the emptied sacks

further through the grating 17 and out of the grating 17 at the opposite end. The emptied sack falls down into the compression unit 20 which comprises a compression screw 34. The screw catches the emptied sack and compresses the emptied sack into a collecting means. Such collecting means may for example be a bag or the like.

Even if the cutting screw 11 with its cylindrical core 12 is shown, it should be appreciated that the core 12 of the cutting screw 11 may be conical, having a decreasing diameter in direction towards the drum 17, whereby the sack is compressed more and more and/or cut open more and more in direction towards the drum 17. Further, it should be noted that knives securing proper cutting of the sacks may be used, securing improved opening of the sack, so that the remaining content in the sack more easily may escape out of the sack prior to the sack being fed towards the drum 17. In order to improve the cutting and emptying effect the light openings at the opening between the cutting screw 11 and the drum 17 may also be made as small as possible.

According to the present invention the gradient between the blades of the sack cutting screw may be increased, for example so that the gradient may be reduced, i.e. the distance between the blades being smallest where the sack firstly hits the screw and larger towards the drum 17. This will contribute to stretching of the sack and hence to improved emptying.

Further, it should be appreciated that the grating, used in the bottom of the respective trays, preferably may be replaceable.

In order to secure that dust does not escape uncontrolled, a fan may be arranged inside the unit, thereby establishing a vacuum inside the housing.

C l a i m s

1. Sack cutting means for offshore emptying of content from a package, comprising a means for cutting up the package, means for separating the package from its content and means for removing the emptied package from the cutting means, said means for separating the content at least from the package comprising means for ripping the package open, one or more transporting means and a rotating drum provided with openings through which the content separated from the package is allowed to leave the drum,
c h a r a c t e r i z e d i n that the sack cutting screw is separated from the drum and that below both the sack cutting screw and the drum, a means for collecting and transporting away the content of the sacks is arranged, said means being configured in such way that the content of the package is removed at one end, while the waste package is removed at the other end of said sack cutting means.
2. Sack cutting means according to claim 1, wherein the drum is floating freely and is only suspended by means of at least one belt extending around the drum, said belt also running around at least one rotating driving shaft.
3. Sack cutting means according to claim 2, wherein said at least one belt is a chain belt running over a correspondingly configured wheel on said at least one driving shaft.
4. Sack cutting means according to claim 2 or 3, wherein said at least one belt is a ball stringed belt running over a correspondingly configured wheel on said at least

one driving shaft.

5. Sack cutting means according to one of the claims 1-4, wherein the drum is correspondingly configured with grooves extending around the periphery of the drum and co-functioning with said belt in order to rotate the drum.

6. Sack cutting means according to one of the claim 1-5, wherein guiding means are arranged in conjunction with the drum, securing control of the drum, keeping the drum in position during rotation.

7. Sack cutting means according to claim 6, wherein the guiding means is in the form of rotating wheels lying in contact with the exterior of the drum.

8. Sack cutting means according to claim 7, wherein at least four rotating wheels are used.

9. Sack cutting means according to claim 5 or 6, wherein at least one guiding means is arranged at the lower side of the drum.

10. Sack cutting means according to claim 6, wherein the guiding means is in the form of a guide rail having a curved support surface corresponding to the curved shape of the drum.

11. Sack cutting means according to claim 6 or 10, wherein the lower side of the drum runs in sliding contact with a correspondingly configured guide rail, the contact being configured to be friction free.

12. Sack cutting means according to one of the claims 1-

11, wherein the drum runs in contact with one or more supporting means preventing axial movement of the drum during rotation.