

DOOR EDGE CONSTRUCTION

SPECIFICATION

CROSS-REFERENCE TO RELATED APPLICATIONS

- 5 This application claims priority to U.S. Serial No. 10/686,325 filed October 14, 2003 entitled "Door Edge Construction".

FIELD OF THE INVENTION

- 10 The present invention relates generally to door constructions and more particularly, to replaceable door edge arrangements.

BACKGROUND OF THE INVENTION

- 15 One popular form of vertically hung doors typically comprises a wooden frame defining outer dimensions of the door, panels of sheet material, such as plywood, plastic or metal covering the frame or both sides, and a core within the frame, which may be solid or hollow.

- 20 In certain high traffic environments, for example, schools, hospitals and other types of health care institutions, doors are often subjected to impacts from carts, wagons, dollies, etc. which take their toll on the doors, particularly along their free edges and the hinged edges. Nicks, gouges and cracks produced along door edges by such impacts compromise a door's ability to effect a secure closure, which is particularly important where the door serves as a fire barrier as well as a closure, and mar its aesthetic appearance.

- 25 Heretofore, when a door edge was severely damaged, it was necessary either to replace the door in its entirety or to refinish it. With the latter expedient, the door panels may also have to be replaced and, in any event, the door will have to be refinished as well. The cost of maintaining the structural integrity and appearance of the many doors in a hospital, for example, can become substantial.

SUMMARY OF THE INVENTION

The object of the present invention is to minimize the necessity of replacing or refinishing doors that have been severely damaged along their edges by enabling a damaged door edge to be simply and inexpensively restored.

5 The foregoing object is achieved by constructing a door with a replaceable edge strip or stile which, when damaged, can be readily removed and replaced with a new one, thereby restoring the door's integrity and appearance. In accordance with the invention, this is achieved by so constructing the door such that the replaceable edge strip or the replaceable stile can be removed and replaced
10 without affecting the door frame or door slab, thus eliminating the need for otherwise replacing or refinishing the door. The stile is so configured that it can be covered with a plastic cap that provides an extra layer of protection against damage and helps maintain a snug seal against a doorway or an opposite door.

 Another feature of the invention is the incorporation in the replaceable
15 door edge assembly of an intumescent (heat expanding) material such that in case of fire, the edge is expanded outwardly to effect a tighter seal with the surrounding doorway or opposite door. The fire safety rating of the door is thus improved.

 Still another feature of the invention is the incorporation in the door edge construction of an accent material to provide a reveal, or line of color different
20 than the door panel color, for aesthetic and/or identification purposes.

BRIEF DESCRIPTION OF THE DRAWINGS

The foregoing and other features and advantages of the invention will become apparent from the following detailed description thereof, taken in conjunction
25 with the appended drawing, in which:

FIG. 1 is an oblique view partially cut away, of a door incorporating the present invention;

FIG. 2 is a cross-section of the door of FIG. 1, taken along the line 2-2;

FIG 3 is an enlarged view of the right-hand portion of the cross-section
30 view of FIG. 2 showing the door edge construction of the invention in greater detail;

FIGS. 4A, 4B and 4C illustrate modifications of the door edge construction of FIG. 3;

FIG. 5 is an enlarged cross-sectional view similar to FIG. 3 illustrating the incorporation of an intumescent strip in the door edge construction of the invention;

FIG. 6 illustrates a modification of the door edge construction of FIG. 5;

FIGS. 7A, 7B, 7C and 7D illustrate the replaceable door edge construction of the invention incorporating various types of accent strips or reveals;

FIGS 8A and 8B illustrate variations of the invention embodying an alternate tongue and groove arrangement for securing the replaceable stile to the door edge;

FIG. 9 illustrates a variation of the invention in which the tongue and groove members are covered with metal channels;

FIG. 10 illustrates a modification of the arrangement of FIG. 9;

FIGS. 11 and 12 illustrate variations of the arrangement of FIG. 9; and

FIG. 13 illustrates a replaceable stile arrangement in accordance with the invention in which the width of the replaceable stile is adjustable.

DETAILED DESCRIPTION OF THE INVENTION

Turning now to the drawings, in particular FIGS. 1, 2 and 3, a door of the type commonly used in health care facilities and the like, but incorporating the present invention, is shown. Such a door 20 typically comprises vertical stiles 22 and top and bottom rails 24, surrounding a core 26. The stiles 22 and rails 24 preferably are made of hardwood and the core 26 of particle board, although other materials may be used to provide the necessary strength and rigidity.

Finish panels 28 cover the particle board core, top and bottom rails and stiles on both sides to provide strength, impact resistance and aesthetic appeal. As seen best in FIG. 3, the panels 28 may comprise a hardboard layer 28a covered by a decorative plastic cladding 28b such as of ACROVYN®, a vinyl acrylic plastic manufactured by Construction Specialties, Inc., Lebanon, NJ. The layers 26, 28a and b are laminated together to form a 5-ply construction. Doors of the type illustrated are manufactured, for example, by Jeld-Wen, Inc.

Doors 20 may be made in dimensions to fit various size doorways in which they are mounted. As will be appreciated, the door 20 may be hinged to swing around along either vertical edge to suit the application. In a typical installation often found in health care facilities, a pair of such doors are hinged at opposite edges to close a wide hallway and are swingable in both directions so that rolling beds, carts, etc may be pushed through without the need to hold the door open.

As discussed above, such doors are subjected to repeated, severe impact by beds, carts, etc., as they are pushed through the doors, often resulting in significant damage to the free vertical edges of the doors. Not only is the appearance of the door thus marred, the integrity of the closure and its fire resistance capability are degraded. Heretofore, in the case of significant edge damage, it was necessary to completely replace a damaged door with a new one to restore the closure's appearance and integrity, at substantial cost.

In accordance with the present invention, the vertical edges of a door such as described herein are fabricated with separable edge assemblies that can be readily replaced if damaged, thereby avoiding the necessity of complete door replacement and greatly reducing the cost of restoring the door's appearance and integrity.

A preferred embodiment of the removal door edge arrangement of the invention is shown in FIGS. 1, 2 and 3; most clearly in the enlarged section through a door edge of FIG. 3. The vertical door stile is indicated at 22 and the replaceable edge assembly indicated at 30. The latter comprises replaceable stile 32, preferably of hardwood, extending the full length of the edge stile 22 and a plastic cover 34 secured over replaceable stile 32. Stile 22 is milled with a longitudinal tapered groove 22a and replaceable stile 32 with a longitudinally extending complementary tapered spline 32a, forming a snug tongue-and-groove mating of stile 22 and replaceable stile 32. A plurality, e.g., 4, of screws 36, spaced along the door edge, firmly but releasably secure replaceable stile 32 to stile 22. If desired, spots of glue may also be applied between stile 22 and replaceable stile 32 to more firmly hold them together, while still allowing replaceable stile 32 to be removed when required.

Cover 34 may be formed of ACROVYN® or other relatively hard but resilient material, such as aluminum or stainless steel, with inwardly directed flanges 34a along both edges. Cover 34 is formed to be of the same shape as the outer surface

of replaceable stile 32, e.g., generally rectangular with rounded corners. Replaceable stile 32 is provided with rectangular indents 32b along both inner longitudinal edges, such that when stile 22 and replaceable stile 32 are joined, rectangular grooves 32b are formed therebetween extending the full length of the door. These grooves snugly
5 receive the flanges 34a of cover 34. To remove a damaged cover from a door, one of the flanges 34a is pried out of its groove and the cover bent away to release the other flange. To install a new cover, one of the flanges is inserted into its groove and the cover pressed toward the outer surface of replaceable stile 32 until the other flange snaps into the other groove.

10 It will be understood that the curvature of the corners of the stile and cover combination discussed and illustrated may be varied to suit the particular application. For example, for paired swinging doors, such as often found across hospital passageways, the corner curvature will be of greater radius than single doors, to provide the required clearance.

15 It will also be understood that the cover 34 need not be removable, but may be permanently secured to its replaceable stile 32, such as by a suitable adhesive. In such an arrangement, flanges 34a and indents 32b may be unnecessary.

FIGS. 4A, 4B and 4C illustrate alternative forms of the tongue-and-groove coupling of FIG. 3, with the screws omitted for the sake of clarity. In FIG.
20 4A, a dovetail spline 42 mates with a corresponding groove 44; in FIG 4B, the spline 46 has a partially circular cross-section to mate with a partially circular groove 48; and in FIG. 4C, the spline 50 and groove 52 are rectangular in cross-section. It will be understood that other variations of the tongue-and-groove cross-sections may be used as desired.

25 FIG. 5 illustrates another embodiment which further enhances the fire resistance advantages of doors of the invention. A heat-expansion or intumescent strip 52 extends the full length of the door edge and is adhered in a groove 54 milled along the outer edge of replaceable stile 32. Cover 34 may have a complementary groove along its inner surface to accommodate the strip as well. The strip 52 is
30 covered by outer cover 34 when the latter is snapped in place. At normal room temperatures, strip 52 maintains its normal thickness. In case of fire or extreme heat adjacent the door, strip 52 expands, pushing cover 34 outwardly to tighten the seal

between the edge of the door and an adjacent door or doorframe, thus increasing the fire resistance rating of the door.

A variation of the arrangement of FIG. 5 is illustrated in FIG. 6 wherein the intumescent strip 52 is adhered in a groove 34a formed in the outer edge of cover 34, the inward extension of the cover 34 fitting in a groove milled along the
5 outer edge of replaceable stile 32.

It will be understood that in the embodiments of FIGS. 5 and 6, any of the tongue-and-groove couplings described above may be used in place of the configurations illustrated.

10 To improve the appearance of the door, an accent strip or reveal, of a contrasting or complementary color to the remainder of the door surface, may be incorporated in the door edge arrangements of FIGS. 3 to 6. In the embodiment of FIG. 7A, longitudinal grooves 60 are milled along opposite sides of replaceable stile 32, inwardly of its interior face, for receiving the flanges 34a of cover 34, leaving
15 exposed narrow longitudinal surfaces 62 on opposite sides of the stile, between cover 34 and the panels 28. These exposed surfaces 62 may be painted in any aesthetically pleasing color.

The reveal or accent strip may also be provided by insertion of a suitably colored strip of accent material in a slot provided between the stile 22 and
20 replaceable stile 32, as shown in FIG. 7B. As seen, stepped indents 64 are provided along each inner corner of replaceable stile 32 to receive the flanges of cover 34 and accent strips 66. The strips 66 may be of PVC plastic, aluminum, stainless steel or other material having their outer surfaces ridged and slightly thicker than the grooves created upon joinder of replaceable stile 32 to stile 22. The strips 66 are pressed into
25 the grooves after cover 34 is inserted and the ridged surfaces resist any tendency of the strips to move out of the grooves.

A variation of the accent strip of FIG. 7B is illustrated in FIG. 7C. In this modification, the inside longitudinal edges of replaceable stile 32 are milled to provide both stepped indents and longitudinal grooves for receiving L-shaped accent
30 strips 68. One leg of each accent strip extends outwardly to just below the respective outer surface of the door with its edge exposed when replaceable stile 32 is joined to stile 22 with the accent strip in place.

In the embodiment of FIG. 7D, the accent strips comprise opposite exposed edges 70 of a strip 72 sandwiched between stile 22 and replaceable stile 32.

The accent strips of FIGS. 7B-D may be made of any suitable material, including PVC plastic, aluminum and stainless steel.

5 FIGS. 8A and 8B illustrate variations of the tongue and groove arrangements of the invention shown in the previous embodiments. In both variations, the groove in the stile 22 is rectangular (as in FIG. 4C) and lined with a U-shaped channel 80 having longitudinal ridges 82 formed along both interior sides of the channel. Channel 80 is secured in the rectangular groove milled in stile 22 by
10 screw 84.

 Adhered along the inner surface of replaceable stile 32 is a tongue plate 86 having integral longitudinal extending flanges 88 with longitudinally extending ridges 90 formed along their outer surfaces. The pair of flanges 88 and channel 80 are dimensioned such that the flanges are snugly received within the
15 channel and the respective ridges 82, 90 engaged to secure replaceable stile 32 to stile 22. Tongue plate 86 may extend the full width of stile 32, with rounded edges extending slightly beyond the door panel as in FIG. 8A, or be narrower than the width of the stile and received in a depression milled in the inner surface of replaceable stile 32, as in FIG. 8B. In the embodiment of FIG. 8A, the rounded extensions of the
20 tongue plate 86 may serve as accent strips. In FIG. 8B, accent strips are provided by inserts 92 between the edges of cover 34 and stile 22. In both embodiments, intumescent strips 52 may be provided.

 Channel 80 and tongue plate 86 may be made of aluminum or other metal or plastic, as desired.

25 In the embodiment of FIG. 9, a dovetail tongue and groove coupling between stile 22 and replaceable stile 32 with screw 36, such as shown in FIG. 4A, has both tongue 94 and groove 96 covered with channels of thin aluminum, steel, or other material providing low friction slideable surfaces, 98a and 98b, respectively, which extend to the outer surfaces of the door. The covered channels facilitate the
30 insertion and removal of replaceable stile 32 on stile 22.

 A variation of the embodiment of FIG. 9 is shown in FIG. 10, in which the extents of the metal channels 100a and 100b are limited to the extents of the groove and tongue, respectively. This variation of the embodiment includes cover 34

and may include intumescent strip 52. The space left between stile 22 and replaceable stile 32 is filled with tapered inserts 102, which serve to wedge the members 22, 32 apart and also to provide accent strips.

In FIG. 11, a single metal channel 110 is applied to the dovetail tongue
5 element only and in FIG. 12, the single metal channel 112 is extended outwardly between stile 22 and replaceable stile 32 to the door faces with rounded outer edges 114 which provide accent strips.

To accommodate different door thicknesses, the adjustable width
replaceable stile of FIG. 13 is advantageous. In this embodiment, the replaceable stile
10 is made up of two separate longitudinal elements 132a and 132b, each having a generally L-shaped cross-section overlying and nesting with each other to be slideable away from each other between a minimum width arrangement wherein the respective longitudinal edges of elements 132a and 132b are in contact with each other and a maximum width configuration wherein the respective longitudinal edges are
15 separated. Opening 134 is of greater diameter than screw 36 to allow for varying amounts of separation.

It will be seen from the foregoing that the present invention provides a simple, inexpensive way of repairing damaged doors by allowing replacement only of a removable door edge assembly, thereby saving the considerable exposure of
20 replacing an entire door. Although a number of specific embodiments of the invention above have been illustrated, various modifications thereof will be apparent to those skilled in the art within the spirit of the invention. For example, replaceable stile 32 and cover 34 may be made as a single integral member and joined to stile 22 as shown. Also, the tongue-and-groove coupling between replaceable stile 32 and
25 stile 22 may be eliminated, if desired and any of these variations may be provided with or without intumescent strips. Accordingly, it will be evident that the scope of the invention is to be limited only as set forth in the appended claims.

CLAIMS:

1. Edge construction for a door, the door having a first edge and a second edge, the edge construction comprising:

a first straight member forming a permanent part of said door, and

a second straight member disposed adjacent and exterior to one of the first or second edges of said door, the second straight member being removably attached to said first member,

whereby said second member may be readily removed from said door and replaced with a member similar to said second member,

a cover having outer edges, said cover disposed over at least part of an outer surface of said second member,

wherein the outer edges of said cover are spaced from said first member, leaving exposed strips of the outer surface of said second member between said first member and said cover.

2. The door edge construction of claim 1 wherein said exposed strips are of a color different than the colors of said cover and the remainder of the door.

3. Edge construction for a door, the door having a first edge and a second edge, the edge construction comprising:

a first straight member forming a permanent part of said door, and

a second straight member disposed adjacent and exterior to one of the first or second edges of said door, the second straight member being removably attached to said first member,

whereby said second member may be readily removed from said door and replaced with a member similar to said second member,

a cover having outer edges, said cover disposed over at least part of an outer surface of said second member, wherein the outer edges of said cover are spaced from said first member, and

further comprising slots formed on both sides of said second member in the spaces between said cover and said first member, and

strips of material inserted in said slots.

4. The door edge construction of claim 3 wherein said strips of material have exposed edges of a color different than the colors of said cover and the remainder of said door.
5. Edge construction for a door, the door having a first edge and a second edge, the edge construction comprising:
 - a first straight member forming a permanent part of said door, and
 - a second straight member disposed adjacent and exterior to one of the first or second edges of said door, the second straight member being removably attached to said first member, whereby said second member may be readily removed from said door and replaced with a member similar to said second member, and
 - a cover having outer edges, said cover disposed over at least part of an outer surface of said second member, and
 - a strip of material sandwiched between said first and second members, said strip of material having exposed edges disposed between said cover and said first member.
6. The door edge construction of claim 5 wherein said exposed edges are of a color different than the colors of said cover and the remainder of said door.
7. The door edge construction of any one of claims 1, 3, or 5, wherein said first and second members are of the same length.
8. The door edge construction of any one of claims 1, 3, or 5, wherein said first and second members are coupled by a tongue-and-groove connection extending along their lengths.
9. The door edge construction of any one of claims 1, 3, or 5, wherein said cover is removable from said second member.
10. The door edge construction of any one of claims 1, 3, or 5, further comprising a strip of intumescent material extending the length of said second member between said second member and said cover.

11. The door edge construction of any one of claims 1, 3, or 5, further comprising a strip of intumescent material secured to the outer surface of said cover along its entire length.

12. In a rectangular door having vertical and horizontal edges, an edge construction for a vertical edge of said door comprising:

a longitudinal groove formed in an outer surface of said vertical edge,

a separate stile member disposed adjacent and exterior to the vertical edge of said door and having a length substantially the same as said vertical edge and having a longitudinal spline formed along one surface thereof,

said spline mating with said groove in said vertical edge to form a tongue-and-groove coupling between said vertical edge and said separate stile member, and

a cover member over an extension surface of said stile member,

wherein said cover member is formed with inwardly extending flanges along its outer edges, and said stile member has longitudinal slots on either side thereof adapted to receive said flanges.

13. The door edge construction of claim 12 wherein said slots are disposed inwardly of the surface of said stile member abutting said door edge, leaving strips on either side of said stile member exposed.

14. The door edge construction of claim 13 wherein said exposed strips are of a color different than the colors of said cover and of the remainder of said door.

15. The door edge construction of claim 13 further comprising an additional slot in each of said strips extending along the length thereof, and an insert of a color different than the colors of said cover and of the remainder of said door received in each of said additional slots.

16. The door edge construction of claim 15 wherein said additional slots and said inserts have L-shaped cross-sections.

17. In a rectangular door having vertical and horizontal edges, an edge construction for a vertical edge of said door comprising:

a longitudinal groove formed in an outer surface of said vertical edge,

a separate stile member disposed adjacent and exterior to the vertical edge of said door and having a length substantially the same as said vertical edge and having a longitudinal spline formed along one surface thereof,

said spline mating with said groove in said vertical edge to form a tongue-and-groove coupling between said vertical edge and said separate stile member, and

a cover member over an extension surface of said stile member, and

an additional member sandwiched between said door edge and said stile member with its outer edge exposed between said door edge and said cover member, said outer edges of said additional member being of a color different than the colors of said cover and of the remainder of said door.

18. In a rectangular door having vertical and horizontal edges, an edge construction for a vertical edge of said door comprising:

a longitudinal groove formed in an outer surface of said vertical edge,

a separate stile member disposed adjacent and exterior to the vertical edge of said door and having a length substantially the same as said vertical edge and having a longitudinal spline formed along one surface thereof,

said spline mating with said groove in said vertical edge to form a tongue-and-groove coupling between said vertical edge and said separate stile member, and

a cover member over an extension surface of said stile member,

wherein said longitudinal groove comprises generally a U-shaped channel having longitudinal ridges formed along opposing inner surfaces thereof, and said spline comprises a

generally U-shaped channel having longitudinal ridges formed along respective outer surfaces thereof.

19. In a rectangular door having vertical and horizontal edges, an edge construction for a vertical edge of said door comprising:

a longitudinal groove formed in an outer surface of said vertical edge,

a separate stile member disposed adjacent and exterior to the vertical edge of said door and having a length substantially the same as said vertical edge and having a longitudinal spline formed along one surface thereof,

said spline mating with said groove in said vertical edge to form a tongue-and-groove coupling between said vertical edge and said separate stile member, and

a cover member over an extension surface of said stile member,

wherein said separate stile member comprises a pair of nesting longitudinal members, each having an L-shaped cross-section, said members being moveable between a first position in which an outer longitudinal edge of one arm of one of said L-shaped members is in contact with an inner surface of one arm of the other of said L-shaped members and a second position in which said one arm of said one of said L-shaped members is separated from said inner surface, and

aligned openings in said one arm of said one of said L-shaped members and the other arm of the other of said L-shaped members, the opening in the said one arm of said one of said L-shaped members being larger than the opening said other arm of said other of said L-shaped members.

20. The door edge construction of any one of claims 12, 17, 18 or 19, further comprising a longitudinally extending strip of intumescent material between said cover and said stile member.

21. The door edge construction of any one of claims 12, 17, 18 or 19, further comprising a longitudinally extending strip of intumescent material secured to the outer surface of said cover.

22. The door assembly of any one of claims 12, 17, 18 or 19, wherein said door comprises a rectangular frame having a pair of spaced stiles and top and bottom rails surrounding a flat core, and one or more layers of sheet material laminated to each side of said rectangular frame and core combination, and wherein said vertical edge comprises the outside edge of one of said stiles.
23. The door edge construction of any one of claims 12, 17, 18 or 19, wherein at least one of said groove and said spline is covered with a low friction slideable material.
24. The door edge construction of claim 23 wherein both of said groove and said spline are covered with said low friction slideable material.
25. The door edge construction of any one of claims 12, 17, 18 or 19, further comprising removable fastening means releasably securing said stile member to said vertical edge.
26. The door edge construction of any one of claims 12, 17, 18 or 19, wherein said cover member is formed of a resilient material shaped to conform to the outer contour of said stile member.