

Handling Systems, Containers for food and beverage, and Carriers

5

Field of the Invention

The invention relates to handling systems, Containers for food and beverage, and
10 carriers. Optionally, the invention relates to cups.

Background to the Invention

The modern lifestyle appears to require an ever-growing consumption of hot or cold
15 beverages. A dense network of suppliers exists providing a one-off solution in the
form of disposable single-use cups or single-use food and beverage packaging
primarily for takeaway. In order to withstand the often very hot beverage contained
in these disposable cups or containers, these are typically made at least in part of
non-biodegradable plastics which have negative environmental impacts as they go
20 to landfill and sometimes clog up our environment requiring extensive energy
consuming waste collection programmes. Whilst compostable containers also exist
these require separation and industrial composting. These negative environmental
impacts are even worse when considering the extensive energy requirement in
producing large volumes of single use packaging solutions.

25

One of the aspects of this invention is to seek to deal with the complexities arising
from the almost infinite end destinations of takeaway cups or other such food and
beverage containers and provide a system which can improve collection and reuse
of cups or other such containers.

30

One of the approaches concerns the cup or container itself. There are literally
thousands of prior packaging proposals dealing with hot beverage cups.

One aspect of the invention seeks to introduce a reversal of conventional thinking in this field and then propose how improved containers may be advantageously integrated in handling systems with minimal environmental damage arising from their use and reuse.

5

Summary of the Invention

In a first broad independent aspect, the invention provides a handling system suitable for interaction with both a plurality of containers suitable for carrying hot
10 beverages and a plurality of carriers suitable for carrying a plurality of containers; the plurality of containers comprising a base; a walled portion upwardly extending from the base; and a lid for attachment to the walled portion; the plurality of carriers comprising at least one compartment for receiving at least part of the containers; wherein both the containers and the carriers comprise a remotely interrogatable
15 tag for respectively identifying the container and the carrier; wherein the system further comprises a remote processing module; and a plurality of points of interaction with the remotely interrogatable tags; the points of interaction providing one or more of the following factors: a date and time stamp of an interaction, an identification of the point, an identification of an individual
20 interacting with the system and an identification of the container or carrier which interacts with the system; and a communication link for dispatching signals representative of the factors to the remote processing module.

Whilst containers may be suitable for both hot and cold beverages. The
25 temperature level of a hot beverage may be greater than 70 degrees Celsius. Preferably, the temperature level of a hot beverage may be greater than 80 degrees Celsius.

In a subsidiary aspect, the points of interaction comprise one or more scanners
30 for scanning the remotely interrogatable tag.

In a further subsidiary aspect, the container comprises one or more remotely interrogatable tags integrated with one or more of the base, the upwardly extending walled portion, and/or the lid.

- 5 In a further subsidiary aspect, the container comprises a tag located within its base.

In a further subsidiary aspect, the container further comprises a remotely interrogatable tag integrated within its lid.

- 10 In a further subsidiary aspect, the interrogatable tag is embedded within the moulded plastics of either the container or the carrier.

- 15 In a further subsidiary aspect, the lid has an outer surface and an inner surface; said inner surface comprising a recessed portion for securing the remotely interrogatable tag to the lid.

- In a further subsidiary aspect, the container comprises an annular band which extends at least partly around the upwardly extending walled portion and protrudes therefrom.

- 20 In a further subsidiary aspect, the lid incorporates a rim with an aperture through which beverage may, in use, exit the container and a part-spherical recessed portion located within the rim; a through hole being located in the part-spherical recessed portion.

- 25 In a further subsidiary aspect, the carrier comprises a remotely interrogatable tag for identifying the carrier; and at least one compartment for receiving lids and at least a second compartment for receiving containers; the second compartment being segregated from the first compartment and having upwardly extending walls
30 for facilitating the stacking of the containers in a closely contiguous configuration.

In a further subsidiary aspect, the carrier comprises at least one parallelepipedal case.

5 In a further subsidiary aspect, the carrier comprises a plurality of stacked parallelepipedal cases.

In a further subsidiary aspect, the carrier comprises one or more beams which act as a junction member between adjacent stacked cases.

10 In a further subsidiary aspect, the carrier comprises a lid with at least two kinds of apertures; a first kind of aperture being sized and shaped to allow the insertion of a container and a second kind of aperture being sized and shaped to allow the insertion of a lid and prevent the insertion of a container.

15 In a further subsidiary aspect, the first aperture is substantially circular and comprises one or more projections projecting radially inwards.

In a further subsidiary aspect, the first aperture comprises diametrically oppositely disposed projections.

20

In a further subsidiary aspect, at least one of the interaction points collates one or more of the following additional factors: the location of the point of sale, the time of sale, the kind of beverage/food, and the quantity of beverage/food.

25 In a further subsidiary aspect, the remote processing module aggregates the data to determine a profile for one or more of the following: an individual, a container, and a point of sale.

30 In a further subsidiary aspect, the system further comprises a location of a carrier; and a module for calculating the distance between a point of an initial interaction with the container and a location of a carrier.

In a further broad aspect, the invention provides a cup suitable for carrying hot beverages comprising a base; a walled portion upwardly extending from the base; and a lid for attachment to the walled portion; wherein the cup comprises one or
5 more remotely interrogatable tags integrated with one or more of the base, the upwardly extending walled portion, and/or the lid.

In a subsidiary aspect, the cup comprises a tag located within its base.

10 In a further subsidiary aspect, the cup comprises a further remotely interrogatable tag integrated within its lid.

In a further subsidiary aspect, the tag comprises a disc which is embedded into the moulded plastics material of the cup.

15

In a further subsidiary aspect, the further tag is embedded into the moulded plastics material of the lid.

In a further subsidiary aspect, the cup comprises an annular band which extends
20 at least partly around the upwardly extending walled portion and protrudes therefrom.

In a further subsidiary aspect, the lid incorporates a rim with an aperture through which beverage may, in use, exit the cup and a part-spherical recessed portion
25 located within the rim; a through hole being located in the part-spherical recessed portion.

In a further subsidiary aspect, the invention provides a carrier suitable for carrying a plurality of cups in accordance with any of the preceding aspects, wherein the
30 carrier comprises a remotely interrogatable tag for identifying the carrier; and at least one compartment for receiving lids and at least a second compartment for

receiving cups; the second compartment being segregated from the first compartment and having upwardly extending walls for facilitating the stacking of the cups in a closely contiguous configuration.

- 5 In a further subsidiary aspect, the carrier comprises at least one parallelepipedal case.

In a further subsidiary aspect, the carrier comprises a plurality of stacked parallelepipedal cases.

10

In a further subsidiary aspect, the carrier comprises one or more beams which act as a junction member between adjacent stacked cases.

- 15 In a further subsidiary aspect, the carrier comprises a lid with at least two kinds of apertures; a first kind of aperture being sized and shaped to allow the insertion of a cup and a second kind of aperture being sized and shaped to allow the insertion of a lid and prevent the insertion of a cup.

- 20 In a further subsidiary aspect, the first aperture is substantially circular and comprises one or more projections projecting radially inwards.

In a further subsidiary aspect, the first aperture comprises diametrically oppositely disposed projections.

- 25 In a further broad independent aspect, the invention provides a cup suitable for carrying hot beverages comprising a base; a walled portion upwardly extending from the base and a lid for attachment to the walled portion; wherein the cup comprises one or more remotely interrogatable tag integrated within one or more of the base, the upwardly extending walled portion, and/or the lid. This configuration is particularly advantageous because it allows minimal change to the configuration of a cup whilst allowing it to integrate with a remote processing
- 30

module which can reduce the complexity inherent in the distribution of takeaway cups. It also allows for a particularly robust structure which avoids the one-shot use of the prior art as the cup may be used for many cycles. In certain preferred embodiment, the cup and any other washable products detailed in this application
5 have been optimised for commercial scale washing, including the cup, lid and drop point cases. In certain embodiment, the cup and lid allow optimal washing and quick drying on an industrial scale. Optionally, any crevices are absent in the lid and the cup where water may otherwise sit or gather during the washing cycle.

10 In a subsidiary aspect, the tag is located within the base. This provides an advantageous structure because it allows in certain embodiments for improved communication with a point of sale interface as it may facilitate improved reading of the tag as the cup is rested against a touch pad at a point of sale. It also provides greater stability for the cup due to its increased density.

15 In a subsidiary aspect a further remotely interrogatable tag is integrated within the lid. This allows the benefits outlined with respect to the cup portion to apply to an even more complex structure formed in certain embodiments of two separable components.

20 In certain embodiments when the tag is in the lid, it also particularly advantageous because it is convenient for consumers to scan with their smart phone device or other personal digital assistant. In certain embodiments, it allows the scanning of the lid which facilitates media interaction with the consumer in the form of media files selected from the group comprising one or more of the following: image, text,
25 animation or music.

In a subsidiary aspect, the tag comprises a disc which is welded to the cup; and the cup comprises a recessed portion for receiving the disc and for retaining therein the disc; whereby the disc may be secured to the cup. This improves the
30 attachment of the disc to the cup which is particularly advantageous for high cycles of use and reuse.

In a subsidiary aspect, the lid has an outer surface and an inner surface which comprises a recessed portion for securing the further remotely interrogatable tag to the lid.

5

In a subsidiary aspect, the tag comprises a disc with a threaded perimeter, and the cup comprises a recessed portion with a correspondingly threaded diameter; whereby the disc may be releasably secured to the cup. This provide advantageous protection of the readable tag to withstand tampering whilst at the same time allowing the tag to be retrofitted into a re-usable cup.

10

In a subsidiary aspect, the disc comprises an outer surface with a recessed portion suitable for receiving a correspondingly shaped driver for driving the rotation of the disc when securing the disc to a cup. This configuration is particularly advantageous for further resisting tampering and to better selectively allow the disc to be released from the cup if appropriate.

15

In a further subsidiary aspect, the lid has an outer surface and an inner surface which comprises a recessed portion for releasably securing the further remotely interrogatable tag to the lid. In this configuration, the tag is advantageously further shielded from any tampering as it is not accessible from the outside of a cup with its lid is secured following its purchase.

20

In a further subsidiary aspect, the cup comprises an annular band which extends at least partly around the upwardly extending walled portion and protrudes therefrom. This configuration is particularly advantageous in terms of reducing the thermal conduction to a carrier of the cup.

25

In a further subsidiary aspect, the lid incorporates a rim with an aperture through which beverage, in use, may exit the cup and a part-spherical recessed portion located within the rim; a through hole being located in the part-spherical recessed

30

portion. This configuration is particularly robust and increases the resilience of the lid of the cup for advantageous attachment to the walled portion of the cup. This is also advantageous as it allows drainage after or as part of the cleaning process which the lid would undergo prior to reuse.

5

In a further broad aspect, the invention provides a carrier suitable for carrying a plurality of cups in accordance with the preceding aspects, wherein the carrier comprises a remotely interrogatable tag for identifying a carrier; and at least one compartment for receiving lids and at least a second compartment for receiving
10 cups; a second compartment being segregated from the first compartment and having upwardly extending walls for facilitating the stacking of the cup in a closely contiguous configuration. This configuration is particularly advantageous in order to prepare the disassembled cup and lid for recycling through a cleaning process in order to minimise handling of the cups. It also provides a particularly compact
15 storage for maximum capacity for transportation.

In a subsidiary aspect, the carrier comprises at least one parallelepipedal case. This is advantageous in terms of stacking the carrier and in terms of increasing the quantity of transportable used cups and lids prior to cleaning.

20

In a further subsidiary aspect, the carrier comprises a plurality of stacked parallelepipedal cases. This further increases the capacity for transportation purposes.

25 In a further subsidiary aspect, the carrier comprises one more beams which act as a junction member between adjacent stacked cases. This further allows greater numbers of cups and lids to be transported and therefore improves the efficiency of the transportation of these.

30 In a further subsidiary aspect, the carrier comprises a lid with at least two kinds of apertures; a first kind of aperture being sized and shaped to allow the insertion of

a cup and a second kind of aperture being sized and shaped to allow the insertion of a lid and prevent the insertion of a cup.

5 In a further subsidiary aspect, the first aperture is substantially circular but comprises one or more projections projecting radially inwards. This configuration is particularly advantageous as it renders very difficult the extraction of the cups and therefore prevents undue tampering with used cups.

10 In a further subsidiary aspect, the first aperture comprises diametrically oppositely disposed projections. This further improves the retention of the cups within the carrier.

15 In a further broad aspect, the invention provides a cup handling system comprising a plurality of cups in accordance with any one of the preceding aspects, a remote processing module and a plurality of remotely disposed interaction points which provide one or more of the following factors: a date and time stamp of an interaction with the interaction points, an identification of the point, an identification of an individual interacting with the system and an identification of the cup; and which dispatch signals representative of the factors to the remote processing module.
20 This provides a solution for the complex re-patriation of the cups taken away from various premises and allows these to be managed in order to minimise any waste going to landfill whilst the cups cycle through the system.

25 In a subsidiary aspect, at least one of the remotely disposed interaction points collates one or more of the following additional factors: location of the point of sale, the time of sale, the kind of beverage, and the quantity of beverage.

In a further subsidiary aspect, the remote processing module aggregates the data to determine a profile for one or more of the following: an individual, a cup, and a
30 point of sale.

In a further subsidiary aspect, the cup handling system further comprises an interaction point for providing a date and time stamp of an interaction, and an identification of a carrier in accordance with any one of the preceding aspects. This further simplifies the handling of this otherwise highly complex and random process.

In a further subsidiary aspect, the cup handling system further comprises a location of a carrier; and a module for calculating the distance between a point of initial interaction with the cup and a location of the carrier.

In a further subsidiary aspect, the cup handling system further comprises a module for calculating the time of travel of the cup between points of interaction.

Detailed Description of the Figures

Figure 1 shows a side elevation view of an embodiment of a cup.

Figure 2 shows a perspective view of the embodiment of Figure 1.

Figure 3 shows a perspective exploded view of the embodiments of Figure 1 and Figure 2.

Figure 4 shows a cross-section of the cup of Figures 1 to 3.

Figures 5 show a perspective view, a side elevation view and a further perspective view of a carrier suitable for collecting cups of the kind in question.

Figure 6 shows an embodiment of a point of sale device.

Figure 7 shows a side elevation view of a further embodiment of a cup.

Figure 8 shows the underside of a perspective of the cup of the embodiment of Figure 7.

Figure 9 shows a perspective view of the embodiment of Figures 7 and 8.

5

Figure 10 shows a perspective view of a further embodiment of a carrier.

Figure 11 shows a perspective view of the embodiment of Figure 10.

10 Figure 12 shows a top perspective view of the embodiment of Figures 10 and 11.

Figure 13 shows a flow chart of the interaction between the processing module and the various components which interact with it.

15 Figure 14 shows a side elevation of a food/beverage container in accordance with a further embodiment.

Figure 15 shows a perspective view of the container of figure 14.

20 Figure 16 shows an exploded perspective view of the container of figure 14.

Figure 17 shows an exploded perspective view of a further embodiment of the invention.

25 Figure 18 shows a further perspective view of the container of figure 14.

Figure 19 shows a perspective view of the container of figure 14 with its lid removed.

30 Figure 20 shows a perspective view of the lid of the container of figure 14.

Figure 21 shows an exploded perspective view of the embodiment of figure 14.

Figure 22 shows a perspective view of the lid.

5 Figure 23 shows a cross-sectional view of the lid.

Figure 24 shows an exploded perspective view of the lid.

Figure 25 shows a perspective view of the carrier.

10

Figure 26 shows an exploded perspective view of the carrier.

Figure 27 shows a perspective view of part of the underside of the carrier lid or upper panel.

15 Figure 28 also shows an exploded perspective view of part of the underside of the carrier lid or upper panel.

Figure 29 shows a flow chart of an embodiment of the handling system.

20 Detailed Description of the Figures

Figure 1 shows a cup generally referenced 1 suitable for carrying hot beverages. It comprises a base 2 and a walled portion 3 upwardly extending from the base. A lid 4 is attached to the upper most portion of the upwardly extending walled portion.

25 In a preferred embodiment, an annular band 5 extends at least partly around the upwardly extending walled portion and protrudes there from. This band may be a separate component from the cup itself or may be integrally formed. In a preferred embodiment, the material of the band has a lower thermal conductivity than the wall of the cup itself. With reduced thermal conduction, the provision of the annular
30 band allows for more comfortable handling of the cup. A gap 6 may be provided between two sections of the band.

In a preferred embodiment, the cup also has measure lines to denote 8oz, 10oz and 12oz drink portions. In a further preferred embodiment, the cup may be suitable for containing 16oz and may have a line denoting a 14oz and/or a 16oz portion.

5

Optionally, any of the embodiments considered may involve a surface of a component with a texture for reducing surface water retention so that little or no water droplets collect on the surface of cup and lid after washing.

10 Figure 2A shows further detail of the lid where a crescent shaped recessed portion 7 is provided within a rim 8 which extends about the perimeter of the lid. Within the boundaries of the rim, an aperture which may be preferably of oblong shape is provided. Aperture 9 facilitates the flow of beverage out of the cup dependent upon the mode of use. The addition of a through hole made within the lid to facilitate the
15 equalising of the pressure within the cup during the drinking process.

Figure 2B is a driver generally referenced 10 with a cylindrical stem 11 and a knurled outer surface to facilitate advantageous gripping of the driver. The driver has a widening head portion 12 with a front surface 13 comprising projections 14
20 which are sized and shaped to correspond with the recesses of disc 15 as shown in figure 3.

Figure 3 shows base 2 in greater detail where it is envisaged that it has a recessed portion 16 in what would otherwise be a substantially flat lower base surface.
25 Recessed portion 16 is disc-shaped and coaxial with the cup. The recessed portion has an inner wall which is internally threaded in order to mate with the correspondingly threaded perimeter of cap 17. A tag 18 may similarly be disc-shaped to also fit within the recessed portion 16 and be retained therein once the cap 17 is screwed into place. Whilst the cap 17 incorporates recessed portions
30 corresponding to the projections 14 in the driver 10, the engagement with the correspondingly threaded wall of the base of the cup may preferably be such that

it is difficult to reverse in order to allow the tag to be secured within the boundary of the cup for the entire life cycle of the cup. The tag may preferably be a so-called passive tag which may be read or interrogated when in proximity to a reader. In preferred embodiments, the tag may comprise a radio frequency (RF) identification in order to allow remote interrogation of the tag such as at a point of interest.

In a preferred embodiment the cup not only has a tag in its base but also as shown in Figure 4 a tag as part of the lid 4. This second tag 19 may be secured on the inside of the lid by a cap 20 of similar configuration to the cap described in Figure 3. This figure shows the interaction between the threaded portion 21 of disc 20 and the threaded portion provided in the recessed portion on the underside of the lid. The tag may be integrally formed with the cap and/or may sit in a further recessed portion located on the upper surface of cap 20. A through hole 22 is also shown in addition to the main oblong aperture 9.

15

Figure 5 shows a carrier generally referenced 23 for carrying a plurality of cups of the kind described with respect to the previous figures. The carrier may also comprise a remotely interrogatable tag for identifying the carrier itself. A number of compartments as shown in Figure 5C such as compartment 24 are provided for receiving the cups and the lids as appropriate. These compartments are elongate in the vertical direction and correspond largely with the width of a cup in order to encourage the stacking of cups in a closely contiguous configuration. This is particularly advantageous in terms of providing relatively compact carriers for maximum transport of large volumes of used cups and lids. In order to encourage the separation of the cups from the lids, a lid 25 comprises two different kinds of apertures. A first kind of aperture such as aperture 26 is sized and shaped to allow the insertion of a cup whilst a second kind of aperture 27 is sized and shaped to allow the insertion of a lid and prevent the insertion of a cup. Aperture 26 has a generally circular configuration whilst aperture 27 is rectangular. The carrier incorporates two triangular supporting members 28 and 29 which elevate the carrier above the ground as shown in Figure 5B. A rectangular junction member 30

is provided to secure the carrier to the side legs. The external walls such as wall 31 of the carrier may be of relatively flexible material in order to allow for transportation in a collapsed form. One or more handles may be provided such as handle 32 which may pivot relative to the external wall of the carrier in order to allow an operator's hand to relatively straightforwardly grab the carrier for further processing.

Figure 6 shows a potential interaction point generally referenced 33. This interaction point may be found at a sales point and may incorporate an RF tag reader 34 which allows the cup handling system to read a cup's unique identifying number whilst also allowing an operator to input on a touch screen 35 the selection of hot drink in order to allow the cup handling system to receive at a remote processing module (not shown in the figure) signals representative of at least one or more of the following factors: a date and time stamp of an interaction, an identification of the point of sale, an identification of an individual interaction with the system and an identification of the cup.

In preferred embodiments, the signals representative of the factors are dispatched to a cloud-based application where the remote processing module resides and where a profile of various interactions is progressively built up. The point of sale device 33 may also provide information with respect to its location, the time and date of purchase, the kind of beverage, and the quantity of beverage. The input obtained from the point of sale device may also feed into the remote processing module which would aggregate the data to determine a profile for one or more of the following: an individual cup, and a point of sale.

Furthermore, the remote processing module may obtain information feeds from the location of a carrier which may also be associated with a number of cups in need of cleaning and further processing. In this context, the module may be adapted or configured to calculate the distance between a point of initial interaction such as at the point of sale device and the recorded location of the carrier. This would allow

the return events to be monitored and analysed. This may for example allow push notifications to be sent with appropriate notifications with potential awards for having returned the cup or alternatively notifications with the dispatch of a penalty charge notice for non-returns. This would also allow more accurate promotional and marketing activities to be developed.

Figures 7 to 9 show a further embodiment of the invention where identical reference numerals to those in Figures 1 to 4 have been retained for simplicity. In this embodiment however the profile of the lid 4 is different as it increases in height across its width. At its highest point as shown by numerical reference 37 in Figure 7, aperture 9 is provided through which beverage may exit the cup. Advantageously, in this embodiment a part-spherical recessed portion 36 (as shown in figure 9) is located within rim 8. Furthermore, the annular projecting band 5 extends about the perimeter of a section of the walled portion of the cup. The upper and lower edges 38 and 39 (as shown in figure 7) extend in a plane perpendicular to the longitudinal axis of the cup; whereby advantageously they may be suitable for stacking. Furthermore, in this embodiment, the disc with its separate tag or with its integral tag will be sonically welded into the base of the cup, meaning that once welded in position it can't be removed. Therefore, the discs would not require any perimeter threads as in a previous embodiment.

A further carrier embodiment is shown in Figure 10, 11 and 12. In preferred embodiments, the carrier may incorporate a plurality of stacked substantially parallelepipedal cases. The carrier of Figure 10 comprises cases 41 and 42. Each case has a lid such as lid 43 with the plurality of apertures of the kind described in a previous embodiment. In addition, however, instead of simply incorporating a circular aperture for the cup compartments, the circular apertures such as aperture 44 is provided with at least one projection 45 which projects radially inwards and presents a barrier for any attempted removal of a cup once placed within the case. Furthermore, this system also encourages the removal of the lid of the cup so that these may more appropriately be inserted through their rectangular apertures such

as aperture 46. Each carrier may also incorporate a remotely interrogatable tag for identifying the particular case or carrier. The embodiment of Figure 11 envisages that the lid of the case or carrier may incorporate an oblong slot for the insertion of a key or disc 47 which may incorporate a housing and a readable RF ID component
 5 located within the housing. Preferably, the key insert releases the lid from the case allowing contents to then be removed and washed. It is envisaged that the RF ID tag may be specific to the case or carrier in question and may also optionally have information with regard to its location. In addition, the various stacked carriers or cases may be held together by one or more beams 48 and 49 which may be
 10 provided through appropriately sized tunnels through a side wall of the cases. These beams 48 and 49 may pass through a plurality of cases in order to act as a junction member between adjacent stacked cases.

Figure 12 shows in greater detail the various tubular compartments which serve to
 15 segregate the cups and lids in order to optimise their stacking and retention within the case. The apertures may also present more than one radial projections for example in aperture 44 two diametrically opposite projections 45 and 50 are envisaged.

20 Having described in detail various components of the system, several advantages arise when considering their interaction with an appropriate cup handling system.

The cup handling system as shown in figure 13:

- 25 • improves the efficiency of handling the cycle of purchasing a beverage filled cup,
- facilitates the consumption of the beverage in an almost infinite number of locations and thereafter a recuperation of the cups at a smart drop point for cleaning and further processing and then returning to a point of sale; thus
 30 providing an efficient environmentally friendly cycle of re-usable cups; Optionally, the system provides RFID enabled trackable cups or RFID

enabled trackable food and beverage packaging which may be optimised for return and reuse;

- oversees this complex process and allows the precise quantifying of these complex moving components;
- 5 • enables the understanding of supply and demand of food and beverage and forecasts volumes over time; and/or
- facilitates the receipt and the pushing of information to and from several critical points of interaction; in preferred embodiments, the system facilitates the pushing of information to or from a IoT cloud platform. The IoT cloud
- 10 platform may be a REST-style API built using Laravel 5.6 on PHP 7.2 and MySQL.

As has already been described in detail one of the points of interaction may be a point of sale device which may be configured to:

- 15 • Assign a cup ID /name;
- Assign a module for counting down the uses for a cup;
- Assign a member ID for a particular cup at a particular time;
- Associate a drink-type;
- 20 • Log a time and date stamp;
- Log a location coordinate;
- Receive regular update;
- allowing digital media interaction during the sale process as a marketing opportunity for brands.

25 The system may be configured as a REST+JSON-style API. It may be configured to allow the submission of requests for standard CRUD operations via standard HTTP verbs GET (retrieve), POST (create), PUT (update), Delete. It may also be configured to allow the submission of query parameters as regular HTTP params,

30 not as JSON.

A postman configuration file may be available which includes example requests for all endpoints, which is very useful for inspecting the API and testing requests interactively.

5

With respect to potential HTTP set up, the live service may be found at <https://api.cupclub.com/>. The initial service also uses a versioning prefix of /v1 , and all requests may include that. All requests shown in these docs may be relative to this base URL. The API may optionally only be available via JSON; there is no browser-compatible interface. All requests should set the following HTTP headers: Accept: application/json; Content-Type: application/x-www-form-urlencoded; and Cache-Control: no-cache.

10

This also indicates that all request bodies (which inherently does not apply to GET requests, for which the Content-Type header is not applicable) must use

15

the standard x-www-form-urlencoded format. The live server supports HTTP/2 and requires TLS encryption, which has a very strict configuration that only supports TLS 1.2 with AEAD ciphers. Any modern HTTP client should have no problem with this, but older ones might, for example Java 6.

In one embodiment with respect to authentication, most endpoints require authentication before any other requests. Requests should be sent as a POST request to the /authenticate endpoint and include email and password parameters, for example:

20

```
POST /v1/authenticate HTTP/1.1; Host: api.cupclub.com; Accept: application/json;
Content-Type: application/x-www-form-urlencoded; Cache-Control: no-cache;
email=admin%40example.com&password=correct+horse+battery+staple.
```

25

In one embodiment, a successful response to this request includes information about the user that logged in, like this:

```
{
  "id": 1,
  "created_at": "2018-03-17 16:11:13",
```

30

```

"updated_at": "2018-03-17 15:11:56",
"type": "admin",
"email": "admin@example.com",
"verified": 1,
5  "name": "Alice Admin",
   "cctoken": null,
   "api_token":
   "CINEGtuw8MTS9ORINvI5OxzNqL5DOGU9pQ1LDaFqP73a21S6N7tzKglriekV",
   "yearofbirth": null,
10  "preferences": null
   }

```

Clients should extract the `api_token` value and include it in all subsequent requests in an authorization bearer header of the form:

```

15  Authorization: Bearer <api_token>

```

Any request without a valid token to an endpoint that requires authorization will receive an HTTP 401 Unauthorized error code. The postman configuration file has built-in support for this mechanism, so follow that as an example. To terminate a session, clients can call the `/logout` endpoint, after which the `api_token` value will no longer be accepted.

In test configurations (for example when running locally), the following user accounts are defined, all using the same password "correct horse battery staple" (for reference):

25	User	type	email;	admin	admin@example.com;	consumer
			consumer@example.com;	retailer	retailer@example.com;	posdevice
			posdevice@example.com;	location	location@example.com;	depot
			depot@example.com			

30 In one embodiment, there are 6 entity types: Users; Retailers; Locations; Posdevices; Cups

Transactions. These all support the standard GET/POST/PUT/DELETE HTTP verbs, but some require specific authorization via an appropriate user type associated with the current login.

- 5 There are a few endpoints that are not associated with specific entities: Post/authenticate used to request permission to connect to the API as a specific user. See the authentication section for more details; Post/logout terminates the validity of the api_token obtained via /authenticate , effectively logging the user out; Post/register used to create new consumer-type accounts. Accepts email,
10 password, password_confirmation (which should contain the same value as password) and name parameters.

Example request:

POST /v1/register HTTP/1.1

15 Host: api.cupclub.com

Accept: application/json

Content-Type: application/x-www-form-urlencoded

Cache-Control: no-cache

email=user%40example.com&password=H3lloo&password_confirmation=H3lloo

20 &name=Joe+User

Response:

{

"email": "user@example.com",

25 "name": "Joe User",

"updated_at": "2018-03-13 21:51:04",

"created_at": "2018-03-13 21:51:04",

"id": 36,

"api_token":

30 "TNLtKWYyKg5ANGIe5KCpcx5KOITYwRn7wdVPpGqvHqmTA9MvQyimD7i22P
v"

}

This endpoint will send a message to the provided email address containing a link that will verify the account, and that must be done before the newly defined user
5 can log in.

GET/verify/{confirmation_code} is used to verify newly created accounts, and is the URL used in the email messages sent to new users. This is the only endpoint that is accessible via a browser, and does not require an Accept header. Valid requests
10 to this endpoint will only work once as the confirmation code is deleted after use.

Users are the users of the system. These cover all user types, each having different capabilities for which they may be authorized. The user types are: consumer; retailer; location; posdevice; depot; admin.

15 In one embodiment, each entity type will usually have an associated user that can be used for logins, for example a retailer entity will have an associated retailer-type user account that has retailer-specific privileges that a consumer-type account does not have.

20 POST/users
This is how new users are created; this end point may only be called by an admin user; normal users will be created via the /register endpoint.

GET/users
25 This provides a complete list of all users in the system. This endpoint may only be called by admin users.

GET/users/{id}
This provides information about a specific user, using their internal ID value, which can be obtained via the /users endpoint, or in the response to /authenticate . Admin
30 users can request information about any user; everyone else can only request information about their own ID.

GET/users/{id}transactions

This provides a list of transactions relating to a specific user, using their internal ID value. Admin users can request information about any user; everyone else can only request information about their own ID.

5 GET/users/{id}statistics

This provides account statistics relating to a specific user, using their internal ID value. Admin users can request information about any user; everyone else can only request information about their own ID. At present this only includes a transaction count.

10 GET/users/me

This provides information about the user currently logged in.

GET/users/me/transactions

Retrieve a list of transactions for the currently logged-in user.

GET/users/me/statistics

15 Retrieve account statistics for the currently logged-in user. At present this only includes a transaction count.

PUT/users/{id}

Updates properties of a user via its internal ID. May only be called by an admin, or a user with a matching user ID.

20 DELETE/users/{id}

Deletes the specified user ID. May only be called by an admin, or a user with a matching user ID. Note that deletes are real and permanent.

Retailers represent the owners of Locations. These are just simple containers with only a name attribute.

25 POST/retailers

Creates a new retailer entity. May only be called by an admin. Requires only a unique name parameter:

POST /v1/retailers/ HTTP/1.1

Host: api.cupclub.com

30 Accept: application/json

Content-Type: application/x-www-form-urlencoded

Authorization:

Bearer

FtMiD3Uj4dkeVc0e0zpJd0VrKHylu1eO2ky6SpqXecZWvy8VWtlzGFuvJNd9

Cache-Control: no-cache

name=New+Retailer+123

5 Response:

```
{
  "name": "New Retailer 123",
  "updated_at": "2018-03-18 15:31:28",
  "created_at": "2018-03-18 15:31:28",
```

10 "id": 4

```
}
```

GET/retailers

Retrieves info about all retailers. This endpoint is accessible to all and does not require a login, so it can be used to obtain a public list of retailers.

15 GET/retailers/{id}

Retrieves info about a single retailer with this ID. This endpoint is accessible to all and does not require a login.

GET/retailers/{id}/locations

20 Retrieves info about all locations owned by a retailer with this ID. This endpoint is accessible to all and does not require a login.

PUT/retailers/{id}

Updates the specified retailer. See POST for available params. May only be called by an admin or a retailer with a matching ID.

25 DELETE/retailers/{id}

Deletes the specified retailer. May only be called by an admin or a retailer with a matching ID.

30 Locations are the places that vend products using Cup Club cups. Every location is associated with one Retailer.

POST/locations

Creates a new location entity. Requires valid `retailer_id` , `name` , `address` (optional), `type` , `longitude` and `latitude` params. This may be called by admins, but also by a retailer user with a matching `retailer_id` , or by a location user with a matching ID. The `type` parameter

5 should be one of: store; drop point; cup club hub

Example request:

POST /v1/locations/ HTTP/1.1

Host: api.cupclub.com

10 Accept: application/json

Content-Type: application/x-www-form-urlencoded

Cache-Control: no-cache

`name=Coffee+Shop+1&address=1%2C+the+road%2C+Newtown&type=store&retailer_id=1&location=%7B%22type%22%3A%22Point%22%2C%22coor`

15

GET/locations

Retrieves info about all locations. This endpoint is accessible to all and does not require a login, so it can be used to obtain a public list of locations.

GET/locations/{id}

20 Retrieves info about a single location with this ID. This endpoint is accessible to all and does not require a login.

GET/locations/{id}/posdevices

Retrieves info about all posdevices associated with a location with this ID. This may be called by admins, but also by a retailer user with a matching `retailer_id` , or by a location user with a matching ID.

25

PUT/locations/{id}

Updates the specified location. See POST for available params. This may be called by admins, but also by a retailer user with a matching `retailer_id` , or by a location user with a matching ID.

30

DELETE/locations/{id}

Deletes the specified location. This may be called by admins, but also by a retailer user with a matching `retailer_id` , or by a location user with a matching ID.

POSDEVICES

- 5 These represent point-of-sale devices that ultimately will create links between a consumer and the use of a particular cup at a particular location. This may or may not be associated with a financial transaction.

POST/posdevices

- Creates a new posdevice entity. Requires valid `type` , `location_id` , and version parameters, where `type` is one of: `type1`; `type2`; `type3`. This may be called by
10 admins, but also by a retailer user with a matching `retailer_id` , or by a location user with a matching ID.

Example request: POST /v1/posdevices/ HTTP/1.1; Host: api.cupclub.com

Accept: application/json; Content-Type: application/x-www-form-urlencoded

- 15 Authorization: Bearer
FtMiD3Uj4dkeVc0e0zpJd0VrKHylu1eO2ky6SpqXecZWvy8VWtlzGFuvJNd9
Cache-Control: no-cache
type=type1&location_id=1&version=1234

- 20 Response:

- ```
"type": "type1",
"location_id": "1",
"version": "1234",
25 "updated_at": "2018-03-18 16:22:31",
"created_at": "2018-03-18 16:22:31",
"id": 31,
"location": {
 "id": 1,
30 "created_at": "2018-03-18 15:31:07",
 "updated_at": "2018-03-18 16:22:31",
```

```

"type": "drop point",
"name": "Balistreri PLC",
"retailer_id": 2,
"address": "9352 Dare Crest Suite 996\nKeenanfort, AR 62349-9297",
5 "user_id": 7,
 "longitude": -0.118092,
 "latitude": 51.509865
}
}

```

10

This particular example included the details of the location associated with this posdevice; this information may not always be present, but can save a roundtrip if it is.

GET/posdevices

15 Retrieve a list of all defined posdevices for all locations. May only be called by admins.

GET/posdevices/{id}

Retrieve info on a single posdevice. This may be called by admins, but also by a retailer user with a matching retailer\_id , or by a location user with a matching ID.

20 GET/posdevices/{id}/transactions

Retrieve a list of transactions for this posdevice. This may be called by admins, but also by a retailer user with a matching retailer\_id , or by a location user with a matching ID.

GET/posdevices/{id}/statistics

25 Retrieve account statistics for this posdevice. At present this only includes a transaction count. This may be called by admins, but also by a retailer user with a matching retailer\_id , or by a location user with a matching ID.

PUT/posdevices/{id}

30 Updates the specified posdevice. See POST for available params. This may be called by admins, but also by a retailer user with a matching retailer\_id , or by a location user with a matching ID.

DELETE/posdevices/{id} deletes the specified posdevice. This may be called by admins, but also by a retailer user with a matching retailer\_id , or by a location user with a matching ID.

5

#### POST/cups

Creates a new posdevice entity. Requires valid status and rfid parameters, where status is one of: pending (default, for new cups); in use; end of life. The rfid parameter is free-form case-sensitive ASCII up to 255 chars, but must be unique and should conform to whatever coding scheme has been defined.

10

This may be called by admins and depot users.

Example request:

POST /v1/cups/ HTTP/1.1

15

Host: api.cupclub.com

Accept: application/json

Content-Type: application/x-www-form-urlencoded

Authorization:

Bearer

FtMiD3Uj4dkeVc0e0zpJd0VrKHylu1eO2ky6SpqXecZWvy8VWtlzGFuvJNd9

20

Cache-Control: no-cache

status=pending&rfid=12345567892

Response:

{

25

"status": "pending",

"rfid": "12345567892",

"updated\_at": "2018-03-18 16:35:14",

"created\_at": "2018-03-18 16:35:14",

"id": 21

30

}

GET/cups/

Retrieve a list of all defined cups. May only be called by admins and depot users.

GET/cups/{id}

Retrieve info on a single cup by its internal ID. May only be called by admins and  
5 depot users.

GET/cups/rfid/{rfid}

Retrieve info on a single cup by its rfid value. May only be called by admins and  
depot users.

10 GET/cups/{id}/transactions

Retrieve a list of transactions for this cup. May only be called by admins and depot  
users.

GET/cups/{id}/statistics

Retrieve account statistics for this cup. At present this only includes a transaction  
15 count. May only be called by admins and depot users.

Transactions record events and interactions between users, locations, posdevices,  
and cups. Getting specific transactions directly is generally only available to  
admins, but most entities have an endpoint for retrieving all transactions relating to  
20 them.

POST/transactions

Creates a new transaction entity. Requires valid type and optionally any of  
posdevice\_id , location\_id , cup\_id , user\_id , plus info-only orderinfo and receipt\_id  
25 parameters, where type is one of: deliver to location; loan; return; wash; end of life.

This may be called by admins, posdevice, and depot users.

Example request:

30 POST /v1/transactions/ HTTP/1.1

Host: api.cupclub.com

Accept: application/json

Content-Type: application/x-www-form-urlencoded

Authorization: Bearer

FtMiD3Uj4dkeVc0e0zpJd0VrKHylu1eO2ky6SpqXecZWvy8VWtlzGFuvJNd9

5 Cache-Control: no-cache

type=loan&orderinfo=abcxyz&receipt\_id=abc1234&posdevice\_id=1&cup\_id=1&location\_id=1&user\_id=1

Response:

```

10 {
 "type": "loan",
 "orderinfo": "abcxyz",
 "receipt_id": "abc1234",
 "posdevice_id": "1",
15 "cup_id": "1",
 "location_id": "1",
 "user_id": "1",
 "updated_at": "2018-03-18 16:57:15",
 "created_at": "2018-03-18 16:57:15",
20 "id": 51
 }
```

GET/transactions/

Retrieve a list of all defined transactions. May only be called by admins.

25 GET/transactions/{id}

Retrieve info on a single transaction by its internal ID. This may only be called by admins.

PUT/transactions/{id}

Updates the specified transaction. See POST for available params. May only be  
 30 called by admins.

DELETE/transactions/{id}

Deletes the specified transaction. May only be called by admins.

### Example scenarios

These are some API call sequences for typical operations.

#### 5 NEW BATCH OF CUPS ARRIVES AT DEPOT:

1. POST /authenticate As admin or depot user.
2. Scan cups with RFID reader
3. POST /cups Create a new record for each cup, including scanned RFID value and a status of pending .

- 10 4. POST /transactions Repeat for each cup, creating a wash -type record (new cups are sent straight to wash). ### Batch of cups sent to location

5. POST /authenticate As admin or depot user.

6. Scan cups with RFID reader

7. GET /cups/rfid/{rfid} Use RFIDs to look up internal cup\_id of each cup.

- 15 8. POST /transactions Repeat for each cup, creating a deliver to location -type record including the appropriate location\_id and

- cup\_id values. ### Batch of cups arrives back from location

9. POST /authenticate As admin or depot user.

10. Scan cups with RFID reader

- 20 11. GET /cups/rfid/{rfid} Use RFIDs to look up internal cup\_id of each cup.

12. POST /transactions Repeat for each cup, creating a wash -type record including the appropriate cup\_id values.

- 25 The point of sale device may also be connected to the retailer's point of sale interface in order to provide appropriate cost and promotion information. Connecting the system's POS to a retailer point of sale, also allows the system to link retailer data with the system's data. This may be done either in real-time or through data stitching.

The point of sale device may be configured to dispatch signals representative of a number of factors to the remote processing module. These may include but are not necessarily limited to:

- 5       • Member ID confirmation;
- Cup ID;
- Number of uses remaining for cup;
- Drink types and quantities;
- Time and data log;
- 10      • Maintenance information such as a tampering event.

The remote processing module may send feedback to the point of sale device in terms of validation of a member ID. It may alternatively also reject a non-member. The remote processing module may also dispatch system and software updates as  
15      appropriate.

Another point of interaction may be when a user drops off the cup once it is used at an appropriate drop point. This interaction is optionally processed at another location where RF ID reading devices are provided such as at a collection point (in  
20      a transport vehicle) or a cleaning station where the used cup may be interrogated and signals representative of several factors may be once again sent to the remote processing module. In further embodiments, the system may be configured to know in real-time where products i.e. containers have been returned in real-time. These several factors may include for example:

- 25      • A cup check-in information;
- A cup ID;
- A time and data log;
- An indication of a status of tampering.

The remote processing module (which may be part of a cloud platform) may also interact with this kind of interaction point by providing system and software updates as appropriate.

- 5 It is possible that the RF ID device also assigns a location to a carrier or a case. It may also be that a drop point ID is assigned.

In addition to these bespoke interaction points a user interface may be provided in the form of an application on a smart device allowing a user to input factors such

10 as:

- Their name;
- Their email address;
- Their preferred payment details;
- 15 • A retail sign-up location;
- Answers to tailored questions;
- Other kinds of information such as complaints.

The remote processing module may also provide the user with member ID  
20 confirmation and any appropriate system updates and software updates. In addition, notifications may be pushed to the user in the form of promotions or marketing information; notification /penalty charges for non-returns and impact metrics which provide the user with a sense of contribution to the beneficial process from an environmental point of view. In addition, in further embodiments, a user  
25 interface may be provided via an API integration with a third party application on a smart device. The system may be configured to provide integration as a so called “white label” where existing applications are already successful.

In addition, the application may require further information about gender and age.

30 It may also provide specific promotions for a particular profile. It may also provide

group memberships dependent upon education, workplace, office or retail. It can also provide accurate drinking habits and trends information.

The invention also envisages a GPS enabled functionality to associate geographic marketing campaigns based on customers' physical locations.

Using the labels of figure 13:

Label A:

10

AUTHENTICATION:

- Requests member ID confirmation

CUP CHECK-OUT INFORMATION

- Cup ID and uses remaining for cup
- 15 • Drink type(s) and quantities (price check)
- Time and date log

MAINTENANCE:

- Tampering

20 Label B:

AUTHENTICATION:

- Sends member ID confirmation or rejects non member

MAINTENANCE:

- 25 • Systems update/software update

Label C:

REGISTRATION:

- 30 • Member name

- Member email
- Member payment details
- Retailer signup location

## CRM:

- 5
- Q&A
  - Complaints

## AUTHENTICATION:

- Relays member ID

10 Label D:

## COMMS:

- Notifications/penalty charge for non-returns
- Promo/marketing and content
- Impact metrics

15 MAINTENANCE:

- Systems update/software update

Label E:

## MAINTENANCE:

- 20
- Systems update/software update

Label F:

## DATA:

- Drop point ID

25

Label G:

## CUP CHECK-IN INFORMATION:

- Cup ID
- Time and date log

30 MAINTENANCE:

- Tampering

Label H:

DATA:

- Cup ID

5

Label J:

DATA:

- Assign Cup ID/name (One off)
- Uses remaining for cup
- Member ID assigned
- Drink type
- Time and date log
- Location Log

10

MAINTENANCE:

- Systems update

15

Label K:

AUTHENTICATION:

- Member ID confirmation/rejection

20

Label L:

DATA:

- Cup ID/name
- Cup travel time/distance
- Impact metrics
- Drink type(s) and quantities

25

Label M:

COMMS:

- Content

30

- Gifts

Label N:

DATA:

- 5
  - Assign location

Label P:

DATA:

- Cup ID

10

Figures 14 and 15 show a cup generally referenced 101 suitable for carrying hot beverages. It comprises a base 102 and a walled portion 103 upwardly extending from the base. A lid 104 is attached to the upper most portion of the upwardly extending walled portion.

15

In a preferred embodiment, the cup also has measure lines such as line 105 as shown in figure 19 to denote 8oz, 10oz and 12oz drink portions. In a further preferred embodiment, the cup may be suitable for containing 16oz and may have a line denoting a 14oz and/or a 16oz portion.

20

Optionally, any of the embodiments considered may involve a surface of a component with a texture for reducing surface water retention so that little or no water droplets collect on the surface of cup and lid after washing.

25

Figure 15 shows further detail of the lid where a semi-spherical recessed portion 107 is provided within a rim 108 which extends about the perimeter of the lid. Within the boundaries of the rim, an aperture 109 which may be preferably of oblong shape is provided. Aperture 109 facilitates the flow of beverage out of the cup dependent upon the mode of use. The addition of a through hole 106 made within the lid to  
30 facilitate the equalising of the pressure within the cup during the drinking process.

Figure 16 shows base 102 in greater detail where it is envisaged that it has a recessed portion 116 in what would otherwise be a substantially flat lower base surface. Recessed portion 116 is disc-shaped and coaxial with the cup. The recessed portion has an inner wall 110 which may be internally threaded in order to mate with a correspondingly threaded perimeter of cap 117. In a preferred embodiment, the cap is adhered to or welded to the base. The tag 118 may be rectangular as in figure 16 or similarly be disc-shaped as 118' to also fit within the recessed portion 116 as in figure 17. The cap 117 may also include an annular portion 111 which is of lower thickness than a central portion as shown in figure 16.

The cap 117 incorporates recessed portions 113 which may correspond to the projections 14 in the driver 10 of a previous embodiment. The tag 118 (or 118') may preferably be a so-called passive tag which may be read or interrogated when in proximity to a reader. In preferred embodiments, the tag may comprise a radio frequency (RF) identification in order to allow remote interrogation of the tag such as at a point of interest.

Figure 18 shows the cup upside down. The lid 104 incorporates a lateral or radial projection or tab 114. The tab 114 has a tapered upper portion and may optionally be located towards the lower most region of the lid.

In a preferred embodiment, the cup not only has a tag in its base but also as shown in Figure 20 a tag as part of the lid 104. As shown in figure 21, this second tag 119 may be secured on the inside of the lid by a cap 120 of similar configuration to the cap described in previous figures. This figure shows the interaction between a receiving portion 121 and the disc 120. The receiving portion has cylindrical walls which define a chamber for receiving the tag 119.

In further embodiments, the tag may be integrally formed with the cap. A through hole 122 is also shown in addition to the main oblong aperture previously described.

Figure 22 shows a cover portion 120' which is secured over a tag of the kind described above. The tag 119' may be embedded in the plastics material as shown in figure 23.

5

Figure 24 shows an exploded view of lid 104, tag 119' and cover portion 120'.

Figure 25 shows a carrier generally referenced 123 for carrying a plurality of cups of the kind described with respect to the previous figures. The carrier may also comprise a remotely interrogatable tag for identifying the carrier itself. A number  
 10 of compartments as shown in Figure 26 such as compartment 124 are provided for receiving the cups and the lids as appropriate. These compartments are elongate in the vertical direction and correspond largely with the width of a cup in order to encourage the stacking of cups in a closely contiguous configuration. This is particularly advantageous in terms of providing relatively compact carriers for  
 15 maximum transport of large volumes of used cups and lids. Each compartment may be bounded by walls which form hexagonal compartments when viewed in cross-section. In order to encourage the separation of the cups from the lids, a lid 125 comprises two different kinds of apertures. A first kind of aperture such as aperture 126 is sized and shaped to allow the insertion of a cup whilst a second kind of  
 20 aperture 127 is sized and shaped to allow the insertion of a lid and prevent the insertion of a cup. Aperture 126 has a generally circular configuration whilst aperture 127 is rectangular. One or more side recessed portion 132 allow an operator's hand to relatively straightforwardly grab the carrier for further processing. A castellation 128 protrudes upwards and may help locate the lid or  
 25 allow the stacking of a plurality of carriers on top of each other. An upper panel 133 is provided as an upper cover for lid 125. The circular apertures have a flexible annular membrane to allow the insertion into the compartments and resist the removal of cups thereafter. Similarly, the rectangular apertures have an inner perimeter with a flexible  
 30 portion to allow the insertion into the compartments and resist the removal of the lids thereafter.

The carriers of figures 25 and 26 may also incorporate an RFID tag 134 located as part of the upper panel 133. The RFID tag 134 may be located in its own compartment 135 which is formed between side walls 136 and a cap 137 as shown  
5 in figure 28. The compartment may either protrude on the underside of the lid or the top of the lid.

The cups may potentially interact with an interaction point which may be found at a sales point and may incorporate an RFID tag reader of the kind previously  
10 described which allows the cup handling system to read a cup's unique identifying number whilst also allowing an operator to input on a touch screen or other input means the selection of hot drink in order to allow the cup handling system to receive at a remote processing module (not shown in the figure) signals representative of at least one or more of the following factors: a date and time stamp of an interaction,  
15 an identification of the point of sale, an identification of an individual interaction with the system and an identification of the cup.

In preferred embodiments, carriers may interact with an interaction point which may be provided by RFID readers at a system hub.  
20

In preferred embodiments, the signals representative of the factors are dispatched to a cloud-based application where the remote processing module resides and where a profile of various interactions is progressively built up. The point of sale devices may also provide information with respect to its location, the time and date  
25 of purchase, the kind of beverage, and the quantity of beverage. The input obtained from the point of sale device may also feed into the remote processing module which would aggregate the data to determine a profile for one or more of the following: an individual cup, and a point of sale.

30 Furthermore, the remote processing module may obtain information feeds from the location of a carrier which may also be associated with a number of cups in need

of cleaning and further processing. In this context, the module may be adapted or configured to calculate the distance between a point of initial interaction such as at the point of sale device and the recorded location of the carrier. This would allow the return events to be monitored and analysed. This may for example allow push notifications to be sent with appropriate notifications with potential awards for having returned the cup or alternatively notifications with the dispatch of a penalty charge notice for non-returns. This would also allow more accurate promotional and marketing activities to be developed.

Figure 29 shows a preferred system structure with an HTTP REST API which is an application program interface using HTTP requests to get, put, post and delete data.

A two-way communication interface allowing upload and download to a database is envisaged. An administration web-based user interface is provided. In addition, the system provides user and customer-facing web and mobile applications.

Primary and secondary interaction points are provided respectively with a first RFID scanner and a second RFID scanner. The first RFID scanner may be a hub scanner whereas the second RFID scanner may be a mobile scanner. Either a cup or a carrier may interact with either the first or the second RFID scanner. Alternatively, both the cup and the carrier may interact with either of the first and second RFID scanner. Embodiments of the invention envisage a network of RFID scanners forming a network of interaction points.

### Other Embodiments

In further embodiments, a handling system may be configured to handle a plurality of food or beverage containers. The food or beverage containers may comprise a base, a walled portion upwardly extending from the base; and a lid for attachment to the walled portion; wherein the container comprises one or more remotely interrogatable tags integrated with one or more of the base, the upwardly extending

walled portion, and the lid. In a preferred embodiment, the container comprises a tag located within its base.

5 Optionally, the container comprises a remotely interrogatable tag integrated within its lid.

Optionally, the tag comprises a disc which is secured to the container to prevent its removal. This may preferably include a welding junction between the tag and the container or another permanent fastener.

10

Optionally, the tag comprises a disc with a threaded perimeter, and the container comprises a recessed portion with a correspondingly threaded diameter; whereby the disc may be releasably secured to the container. Preferably, the disc comprises an outer surface with a recessed portion suitable for receiving a correspondingly  
15 shaped driver for driving the rotation of the disc when securing the disc to the container.

Preferably, the container's lid has an outer surface and an inner surface which comprises a recessed portion for releasably securing the further remotely  
20 interrogatable tag to the lid. Preferably, the carrier comprises a remotely interrogatable tag for identifying the carrier; and at least one compartment for receiving lids and at least a second compartment for receiving a container; said second compartment being segregated from the first compartment and having upwardly extending walls for facilitating the stacking of the containers in a closely  
25 contiguous configuration.

Optionally, the carrier comprises at least one parallelepipedal case. Preferably, the carrier comprises a plurality of stacked parallelepipedal cases.

30 Preferably, the carrier comprises one or more beams which act as a junction member between adjacent stacked cases.

Preferably, the carrier comprises a lid with at least two kinds of apertures; a first kind of aperture being sized and shaped to allow the insertion of a container and a second kind of aperture being sized and shaped to allow the insertion of a lid and prevent the insertion of a container.

Preferably, the first aperture is substantially circular and comprises one or more projections projecting radially inwards.

10 Preferably, the first aperture comprises diametrically oppositely disposed projections.

A further embodiment envisages, a handling system comprising a plurality of container in accordance with any one of the preceding aspects, a remote processing module and a plurality of remotely disposed interaction points which provide one or more of the following factors: a date and time stamp of an interaction, an identification of the point, an identification of an individual interacting with the system and an identification of the container; and which dispatch signals representative of the factors to the remote processing module.

20

Optionally, at least one of the remotely disposed interaction points collates one or more of the following additional factors: the location of the point of sale, the time of sale, the kind of beverage/food, and the quantity of beverage/food.

25 Optionally, the remote processing module aggregates the data to determine a profile for one or more of the following: an individual, a container, and a point of sale.

30 Optionally, the system further comprises an interaction point for providing a date and time stamp of an interaction, and an identification of a carrier in accordance with any one of the preceding claims.

Optionally, the system further comprises a location of a carrier; and a module for calculating the distance between a point of initial interaction with the container and a location of the carrier.

CLAIMS

1. A handling system suitable for interaction with both a plurality of containers  
5 suitable for carrying hot beverages and a plurality of carriers suitable for  
carrying a plurality of containers; said plurality of containers comprising a  
base; a walled portion upwardly extending from said base; and a lid for  
attachment to said walled portion; said plurality of carriers comprising at  
least one compartment for receiving at least part of said containers;  
wherein both said containers and said carriers comprise a remotely  
10 interrogatable tag for respectively identifying said container and said carrier;  
wherein said system further comprises a remote processing module; and a  
plurality of points of interaction with said remotely interrogatable tags; said  
points of interaction providing one or more of the following factors: a date  
and time stamp of an interaction,  
15 an identification of the point, an identification of an individual interacting with  
the system and an identification of the container or carrier which interacts  
with said system; and a communication link for dispatching signals  
representative of said factors to said remote processing module;  
and wherein said carrier comprises a remotely interrogatable tag for  
20 identifying said carrier; and at least one compartment for receiving lids and  
at least a second compartment for receiving containers; said second  
compartment being segregated from said first compartment and having  
upwardly extending walls for facilitating the stacking of said containers in a  
closely contiguous configuration.  
25
2. handling system according to claim 1, wherein said points of interaction  
comprise one or more scanners for scanning said remotely interrogatable  
tag.
- 30 3. A handling system according to either claim 1 or claim 2, wherein said one  
or more remotely interrogatable tags of said container are integrated with

one or more of said base of said container, said upwardly extending walled portion of said container, and/or said lid of said container.

- 5 4. A handling system according to any one of the preceding claims, wherein said remotely interrogatable tag of said container is located within its base.
5. handling system according to any of the preceding claims, wherein said remotely interrogatable tag of said container is integrated within its lid.
- 10 6. A handling system according to any of the preceding claims, wherein said interrogatable tag is embedded within the moulded plastics of either said container or said carrier.
- 15 7. A handling system according to any of the preceding claims, wherein said lid has an outer surface and an inner surface; said inner surface comprising a recessed portion for securing said remotely interrogatable tag to said lid.
- 20 8. A handling system according to any one of the preceding claims, wherein said container comprises an annular band which extends at least partly around the upwardly extending walled portion and protrudes therefrom.
- 25 9. A handling system according to any one of the preceding claims, wherein said lid incorporates a rim with an aperture through which beverage may, in use, exit said container and a part-spherical recessed portion located within said rim; a through hole being located in said part-spherical recessed portion.
- 30 10. A handling system according to any of the preceding claims, wherein said carrier comprises at least one parallelepipedal case.

11. A handling system according to claim 10, wherein said carrier comprises a plurality of stacked parallelepipedal cases.
- 5 12. A handling system according to either claim 10 or claim 11, wherein said carrier comprises one or more beams which act as a junction member between adjacent stacked cases.
- 10 13. A handling system according to any of the preceding claims, wherein said carrier comprises a lid with at least two kinds of apertures; a first kind of aperture being sized and shaped to allow the insertion of a container and a second kind of aperture being sized and shaped to allow the insertion of a lid and prevent the insertion of a container.
- 15 14. A handling system according to claim 13, wherein said first aperture is substantially circular and comprises one or more projections projecting radially inwards.
- 20 15. A handling system according to claim 14, wherein said first aperture comprises diametrically oppositely disposed projections.
- 25 16. A handling system according to any of the preceding claims, wherein at least one of the interaction points collates one or more of the following additional factors: the location of the point of sale, the time of sale, the kind of beverage/food, and the quantity of beverage/food.
- 30 17. A handling system according to any of the preceding claims, wherein the remote processing module aggregates the data to determine a profile for one or more of the following: an individual, a container, and a point of sale.
18. A handling system according to any of the preceding claims, wherein the system further comprises a location of a carrier; and a module for calculating

the distance between a point of an initial interaction with the container and a location of a carrier.

5 19. A carrier suitable for carrying a plurality of cups; each said cup comprising a base; a walled portion upwardly extending from said base; and a lid for attachment to said walled portion; wherein said cup comprises one or more remotely interrogatable tags integrated with one or more of said base, said upwardly extending walled portion, and/or said lid.

10 , wherein said carrier comprises a remotely interrogatable tag for identifying said carrier; and at least one compartment for receiving lids and at least a second compartment for receiving cups; said second compartment being segregated from said first compartment and having upwardly extending walls for facilitating the stacking of said cups in a closely contiguous configuration.

15

20. A carrier according to claim 19, wherein said carrier comprises at least one parallelepipedal case.

20

21. A carrier according to claim 20, wherein said carrier comprises a plurality of stacked parallelepipedal cases.

22. carrier according to claim 21, wherein said carrier comprises one or more beams which act as a junction member between adjacent stacked cases.

25

23. A carrier according to any of claims 19 to 22, wherein said carrier comprises a lid with at least two kinds of apertures; a first kind of aperture being sized and shaped to allow the insertion of a cup and a second kind of aperture being sized and shaped to allow the insertion of a lid and prevent the insertion of a cup.

30

24. A carrier according to claim 23, wherein said first aperture is substantially circular and comprises one or more projections projecting radially inwards.

5 25. A carrier according to claim 24, wherein said first aperture comprises diametrically oppositely disposed projections.

10

15

20

25

ABSTRACTHandling Systems, Containers for food and beverage, and Carriers

5

A handling system suitable for interaction with both a plurality of containers suitable for carrying hot and cold beverages and a plurality of carriers suitable for carrying a plurality of containers; said plurality of containers comprising a base; a walled portion upwardly extending from said base; and a lid for attachment to said walled portion; said plurality of carriers comprising at least one compartment for receiving lids and at least a second compartment for receiving containers; wherein both said carriers and said containers comprise a remotely interrogatable tag for respectively identifying said carrier and said container; wherein said system further comprises a remote processing module; and a plurality of points of interaction with said remotely interrogatable tags which provide one or more of the following factors: a date and time stamp of an interaction, an identification of the point, an identification of an individual interacting with the system and an identification of the container or carrier which interacts with said system; and a communication link for dispatching signals representative of said factors to said remote processing module.

20

Figure 29 illustrates the invention.

25