



INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification 7 : G01F 15/06		A1	(11) International Publication Number: WO 00/36380
			(43) International Publication Date: 22 June 2000 (22.06.00)
(21) International Application Number: PCT/US99/29830		(81) Designated States: AE, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CR, CU, CZ, DE, DK, DM, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KB, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, TZ, UA, UG, US, UZ, VN, YU, ZA, ZW, ARIPO patent (GH, GM, KE, LS, MW, SD, SL, SZ, TZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).	
(22) International Filing Date: 15 December 1999 (15.12.99)			
(30) Priority Data: 09/212,176 15 December 1998 (15.12.98) US			
(63) Related by Continuation (CON) or Continuation-in-Part (CIP) to Earlier Application US 09/212,176 (CIP) Filed on 15 December 1998 (15.12.98)			
(71) Applicant (for all designated States except US): DANIEL INDUSTRIES, INC. [US/US]; 9753 Pine Lake Drive, Houston, TX 77055 (US).		Published With international search report.	
(72) Inventors; and (75) Inventors/Applicants (for US only): LAMBERT, J., David, A., [GB/US]; 24703 Lakebriar Drive, Katy, TX 77494 (US). MALIK, Vipin [IN/US]; 17202 Hamilwood Drive, Houston, TX 77095 (US). HEUER, Rick [US/US]; 21315 Park Orchard, Katy, TX 77450 (US).			
(74) Agents: ROSE, David, A. et al.; Conley, Rose & Tayon, p.c., P.O. Box 3267, Houston, TX 77253-3267 (US).			

(54) Title: INTERNET ENABLED NETWORK FLOW COMPUTER SYSTEM

(57) Abstract

An improved network flow system includes an Internet/intranet enabled network flow computer with at least one flow measurement device and a host computer capable of communicating using Internet technology or through local connection to the flow computer. In one embodiment, the Internet enabled network flow computer receives flow measurement data, in raw or calculated form, from one or more measurement devices. The host computer connects to the network flow computer via the Internet, an intranet or local connections. The host computer transmits or receives data from the network flow computer, including the capability to view flow data results in web page format on the host computer and the capability to remotely or locally configure and control the flow computer from the host computer.

