

Description

This invention relates to dye laser amplifiers.

Dye lasers are a known type of laser in which a dye cell pumped with energy causes a laser action from the cell. The dye cell is a vessel containing a gaseous liquid or solid dye and is often arranged between reflectors forming a laser cavity. An advantage of dye lasers is that their frequency can be readily changed. For example one of the cavity reflectors may be a reflective grating. Varying the angle of this grating to the cavity varies the dye laser output frequency. Output power is a function of pumping power. The limit of output power is reached when the pumping power is sufficient to cause a total population inversion the dye and the optical design of the laser allows all of the stored energy to be extracted from the dye. Large output powers may be achieved by increasing the size of the laser, but this is often not desirable. Instead a relatively lower power laser may be used and its output amplified.

Laser amplifiers are useful because they allow the maximum optical extraction to be achieved from a laser medium. A normal laser requires feedback in order to sustain the laser oscillations. The feedback is usually provided with partially reflective mirrors and it is only the transmitted portion of the beam that forms the laser beam that emerges from the device. No matter how low the reflectivity of the exit mirror becomes, the output beam can never be 100% since some portion is required to provide the feedback. A laser amplifier has no mirrors to provide a transmission loss, but instead relies on there being a laser beam present from another laser. Providing that this beam is intense enough, it can cause all of the amplifier energy to be extracted.

Laser amplifiers are also useful in other areas; for instance, if a high power laser is required to be built using some components which are sensitive to laser damage, then a low power laser can be designed and then amplified without affecting the original beam qualities. In this way the sensitive optical components are not exposed to damaging power levels.

There are many sorts of amplifiers that are currently used in conjunction with dye lasers but the two most used employ dye as the gain medium. These amplifiers are flashlamp pumped and laser pumped. Additionally, laser pumping may be either transverse in geometry (pumping beams is at some angle, usually 90°, to the extracted dye laser beams) or longitudinal in geometry (pumping beam is coaxial to the extracted dye laser beams).

A disadvantage of using amplifiers is added system complexity, ie additional optics, dye cells and support mounts.

Both dye lasers and amplifiers are described for example in Dye Lasers, edited by F P Schäffer, second edition, published by Springer - Verlag, 1977.

One problem with existing amplifiers is that they amplify or broaden the bandwidth, ie the output consists of a wider range of frequencies. Typically a single longitudinal mode (SLM) dye laser has a bandwidth of less than 1 GHz and after amplification it increases to much greater than 1 GHz. It is highly desirable to amplify the output of a dye laser and maintain a narrow bandwidth.

As used in this specification the term light includes electromagnetic radiation in the visible, infra red, ultra violet, and nearby wavelengths.

Statement of invention.

According to this invention a dye laser amplifier incorporates a stimulated Brillouin scattering (SBS) medium with a laser dye; this improves bandwidth, beam uniformity, and allows a plurality of amplifiers to be cascaded to provide a very high degree of amplification with a few components and hence improved reliability and ruggedness.

According to this invention a dye laser amplifier comprises a dye cell, means for supplying a dye laser beam to be amplified, means for supplying a pumping beam, means for directing the dye laser beam into the dye cell, means for directing the pump beam into the dye cell and means for directing the amplified dye laser beam from the amplifier,

Characterised in that said dye cell is a stimulated Brillouin scattering (SBS) dye cell, comprising a laser dye material dissolved in a SBS medium contained between the cell walls, such that when the dye laser and pumping beams are focused in it, a phase conjugate amplified dye laser beam is produced.

The dye laser beam and pump beam may be arranged to enter the SBS cell coaxially. Alternatively, the pump beam may enter the SBS cell transversely to the dye laser beam. The pump beam may be a beam from a laser or flashlamp pump.

According to a further aspect of this invention output from the amplifier may be used as the dye laser beam input to a further dye laser amplifier.

In this manner two or more amplifiers may be arranged in series to progressively amplify the original dye laser beam. A large amount of amplification can be achieved because the laser amplifier automatically corrects for distortions which are produced in laser dye medium when pumped by strong pump beams. Strong pump beams are necessary in order to maximise the optical gain within the dye medium.

5 The SBS medium is chosen to be a solvent for the particular laser dye. For example the SBS medium may be methanol, acetone, isopropyl alcohol, etc either alone or as a mixture. One specific example of a SBS mixture is 20% methanol, 70% n-hexane, and 10% isopropyl alcohol. The relative amounts of the components may be varied.

The SBS medium may also be in gaseous or solid form. A suitable gas is a heated dye vapour and methane. 10 A suitable solid is an amorphous solid e.g. solgel or polymethylmethacrylate (PMMA) containing the laser dye.

The terms stimulated Brillouin scattering and phase conjugate reflection are described for example in Non-linear Optical Phase Conjugation, by D M Pepper, Optical Engineering, March/April 1982, vol 21, no 2 pages 156-182.

15 The invention will now be described by way of example only with reference to the accompanying drawings of which:-

Figure 1 is a diagrammatic view of an SBS dye laser amplifier;

Figure 2 is a diagrammatic view of six of the SBS amplifiers of Figure 1 connected together in series to increase the amount of amplification;

20 Figure 3 is a schematic block diagram showing an arrangement of optical components in a dye laser plus four amplifier embodiment; and

Figures 4, 5 are modifications of Figure 1 with different pump arrangements.

As shown in Figure 1 a dye laser amplifier comprises a dichroic mirror 1 through which a dye laser beam 2 passes via a polarising beam splitter 3, a quarter wave plate 4, lens 5, on its way to a stimulated Brillouin scattering (SBS) dye cell 6. A pump laser beam 7 is incident on the mirror 1 and is reflected coaxially with the 25 dye laser beam 2 into the SBS cell 6. The mirror 1 is made to reflect at the pump laser beam wavelength. The polariser 3 transmits linear polarised light of say vertical polarisation, and reflects horizontally polarised light. The quarter wavelength plate 4 converts linear polarised light to circularly polarised light and visa versa. The lens 5 focusses light to a point within the cell 6.

30 This cell 6 is typically a tube 8 with a glass front face 9 and a glass rear face 10. In one cell the walls were 2mm thick, the front and rear faces 9, 10 were 22mm diameter and 1.5mm thick, with a spacing between faces 9, 10 of 100mm. The faces 9, 10 may be normal to the beams 2, 7, or at an angle suitable to prevent unwanted reflections being superimposed onto the amplified beam. Inside the cell 6 is a laser dye material dissolved in a mixture of 20% methanol, 70% n-hexane, and 10% isopropyl alcohol. Suitable dyes are, eg Rhodamine 6G, Rhodamine B, Coumarin 523, etc, typically mixed in the proportion of 10mg dye: 1 litre solute. This proportion 35 varies according to the dye and solvent used, and the input pump power density. Advantageously dye is flowed through the cell 6 or the dye in the cell is stirred.

The cell 6 is a SBS medium, it produces a phase conjugate beam ie an input beam with optical distortions will be returned with those distortions temporally reversed. Thus any optical distortions in the dye beam 2, pump beam 7, plus any introduced by the mirror 1, polariser 3, quarter wave plate 4, lens 5 and the front face 40 9 will be reversed so that the polariser and reflector 3 will receive from the cell 6 an optically corrected and amplified beam. Details and an explanation of phase conjugate reflection are given in Nonlinear Optical Phase Conjugation, by D M Pepper, Optical Engineering, March/April 1982, vol 21, No 2, pages 156-182.

The dye laser beam 2 is typically of 570nm wavelength, 40µJ energy in an 18nsec pulse, and has a near transform limited bandwidth of about 64MHz.

45 The pump laser beam 7 is typically of 532nm wavelength, 13.5mJ energy in a 20nsec pulse, either a single longitudinal mode (SLM) or broadband laser. The output bandwidth of an amplified dye laser will be slightly narrower if a SLM pump is used due to the absence of modulation broadening arising from pump mode beating.

In operation a vertically polarised dye laser beam 2 passes through the mirror 1 and polarising beam splitter 3. The quarter waveplate 4 converts the beams to circular polarisation and the lens focusses into the cell 6. 50 Likewise the pump beam 7 is reflected off the mirror 1 and is focussed into the cell 6. The focussing of the two beams 2, 7 concentrates their energy causing inversion and laser amplification of the laser dye in the cell 6. Since the gain is available in both directions within the cell 6 a weak dye laser beam which would normally be below the SBS threshold intensity can now be phase conjugated by virtue of the forward amplification. Increasing the power density increases the lasing intensity.

55 Due to the narrow linewidth requirements of the SBS process, amplified spontaneous emission, which is broad band, is not reflected. This allows the dye laser beam to be effectively amplified without gaining broad band noise, which is a severe limitation of conventional dye laser amplifiers. Some laser energy is released forwards to exit through the rear cell wall 10, but more importantly a phase conjugated beam will be emitted

from the SBS due cell 6 towards the polarising beam splitter 3, and reflect off the beam splitter 3 to form the output beam 11. Amplification of the dye laser beam 2 can occur in both directions of travel within the SBS dye cell 6, i.e. the dye laser beam 2 can be amplified in its original form and as a phase conjugate.

In one example a dye laser beam of 66w power and 64MHz bandwidth was amplified to 155kW with a bandwidth of 64MHz in a single amplifier as shown in Figure 1, an equivalent energy gain of 2350 times.

Due to the ability of the amplifier to amplify without gaining broad band noise, it can be cascaded with further amplifiers to obtain large amounts of gain. Additionally, the SBS process also acts to limit the bandwidth of the amplified conjugate, thereby limiting the increase in bandwidth associated with non-noise related broadening mechanisms.

This is shown diagrammatically in Figure 2 where six amplifiers are cascaded to make a "daisy chain" amplifier. This amplifier comprises six SBS cells 15, 16, 17, 18, 19, 20; three polarising beam splitters 21, 22, 23; six dichroic mirrors 24, 25, 26, 27, 28, 29; six quarter waveplates 30, 31, 32, 33, 34, 35; six lenses 36, 37, 38, 39, 40, 41; a dye beam 42; and two pump beams 43, 44 all arranged as shown. Each component is as in Figure 1.

Operation is as follows. A portion of the dye laser beam 42 is reflected by the beam splitter 21 and into the dye cell 15 where it is joined by the pump beam 43 after reflection from the dichroic mirror 24. Amplified dye laser light from the cell 15 forms the dye laser input to the cell 16 which receives pump beam 44 reflected from the dichroic mirror 25. Amplified (by two times) output from the cell 16 is reflected by the beam splitter 21 to form a dye beam for further amplification.

Similarly the twice amplified dye beam 42 passes from the beam splitter 21 via the beam splitter 22 and into the cell 17. A portion of the pump beam 43 passes through the dichroic mirror 24 and is reflected by mirror 26 into the cell 17. Amplified dye laser light from cell 17 is directed into the cell 18 where it meets a portion of pump beam 44 transmitted through the mirror 25 and reflected off mirror 27. Four times amplified dye beam light exits from the cell 18 to be reflected off the beam splitter 22 to form the input to the last two amplifiers.

The dye beam 42 (now amplified four times) passes from the beam splitter 22 and is reflected from the beam splitter 23 into the cell 19. A portion of the pump beam 43 passes through the dichroic mirrors 24, 26 and is reflected by mirror 28 into the cell 19. Amplified dye laser light from cell 19 is directed into the cell 20 where it meets a portion of pump beam 44 transmitted through mirrors 25, 27 and reflected off mirror 29. Six times amplified light exits from the cell 18 to be reflected off the beam splitter 22 to form the finally amplified beam 45.

Further SBS cell pairs and associated optical components may be added to give further amplification.

Figure 3 is a schematic block diagram showing arrangement of optical components in a dye laser and four amplifier embodiment. As shown there is an optical path 50 along which lie the following components in serial order: a reflection grating 51, a positive lens 52, a negative lens 53, a dichroic beam splitter 54, a first coupling mirror 55, an oscillator dye cell 56, a second coupling mirror 57, a negative lens 58, a positive lens 59, a half wave plate 60, a first polarising beam splitter 61, and a second polarising beam splitter 62.

The positive lens 52 and negative lens 53 act to provide a beam expanding telescope to give a high magnification in order to maximise the resolving power of the reflection grating 51 which is used as a tuning element. Additional improvements may be achieved by a pin hole aperture 97 arranged between the two lenses 52, 53, and by insertion of a low finesse etalon 98 between the lens 52 and grating 51.

The dye cell 56 may be formed by eg Rhodamine B dye in methanol at a concentration of about 1.3×10^{-4} Molar. The cell walls may be 1mm thick fused quartz plates spaced about 5mm apart, and the whole cell tilted at about 20° to reduce unwanted feedback. Other suitable dyes are Rhodamine 6G, Sulphorhodamine B, Kiton red, Rhodamine 575, Rhodamine 560, DCM, etc. The cell 56 may be 7mm x 7mm x 32mm high x 1mm thick fused quartz material. Both the top and bottom of the dye cell have a 10mm long 5mm outside diameter glass tube 95, 96 onto which a flexible pipe is fitted to flow dye through the cell.

A dye laser 63 is formed by the components between the reflection grating 51 the first coupling mirror 55 and the second coupling mirror 57 which define a resonantly reflecting laser cavity. Energy for this dye laser 63 is from a laser pump beam 64 through a half wave plate 65, a beam splitter 66, and positive lens 67 onto the dichroic beam splitter 54. Part of the pump energy incident on this dichroic beam splitter 54 is reflected off into the dye cell where lasing of dye occurs. Dye cell 56 light output oscillates between the first and second coupling mirrors 56, 57, and reflection grating 51 at a wavelength dependent upon the, adjustable, angle of the grating 51.

Four dye laser amplifiers are constructed as in Figure 1. Each comprise a SBS dye cell 69, 70, 71, 72 with associated quarter wave plate 73, 74, 75, 76, positive lens 77, 78, 79, 80. Additionally cells 69, 70 are associated with dichroic beam splitters 81, 82, and cells 71, 72 are associated with dichroic mirrors 83, 84. Further components are a negative lens 85, mirror 86, and positive lens 87 all of which receive a portion of pump beam 64 transmitted through the dichroic beam splitter 54.

The dye cells 69, 70, 71, 72 are fused quartz flow-through cuvettes, 22mm diameter, 103mm long, fitted with a flexible flow tube of 6mm diameter at each end on the top of the cuvette.

Details of other components are as follows: The reflection grating 51 may be a holographic type with 2400 lines per mm, blazed for 590nm, 30mm x 30mm x 6mm thick and used at first order in a Littrow (TM) mount; described by T W Hansch, Applied Optics, vol 11, 1972, page 895. Positive lens 52, +150mm focal length plano-convex, anti reflection coated for 590nm, 15mm diameter. Positive lens 53, acting as a high power microscope objective lens, 4mm focal length, working distance = 0.8mm, numerical aperture = 0.5. Dichroic beam splitter 54, 94% transmission at 532nm, 100% transmission at 590nm 45° incidence, P-polarisation, 15mm diameter, positioned at 45° to the two optic axes with the front face centred on the intersection of the two optic axes. Coupling mirrors 55, 57, one face uncoated giving a reflectivity of about 4-6%, the other anti reflection coated, 0.5° wedged coupling mirrors, 15mm diameter 10mm thick. Negative lens 58 -10mm focal length, plano-concave lens, anti reflection coated for 590nm, 3mm diameter. Positive lens 59, +50mm or +51mm focal length, bi-convex lens, anti reflection coated for 590nm, 15mm diameter.

Half wave plates 60, 65 zero order, anti reflection coated for 590nm, 15mm diameter 2-3mm thick. Polarizers 61, 62 air spaced calcite Glan-Taylor cube polariser, anti reflection coated for 590nm, 10mm x 10mm x 12mm (xyz) cemented into an optical mount. Beam splitter 66, 65% reflection at 532nm, 45° angle of incidence, 25mm diameter, 6mm thick. Positive lens 67, +100mm focal length plano-convex lens, anti reflection coated for 532nm, 15mm diameter. Quarter wave plates 73, 74, 75, 76, zero order, anti reflection coated for 590nm, 15mm diameter, 2-3mm thick. Positive lenses 77, 78, 79, 80, either +100mm or +80mm focal length plano-convex or bi-convex lens, anti reflection coated for 590nm, 15mm diameter.

Dichroic beam splitter 81, 20% reflection at 532nm, anti reflection coated at 590nm, 54° angles of incidence with respect to the surface of the component (ie 72° between the incident and reflected beams), 25mm diameter, 6mm thick. Dichroic beam splitter 82, 20% reflection at 532nm, anti reflection coated at 590nm, 36° angles of incidence with respect to the surface of the component (ie 108° between the incident and reflected beams), 25mm diameter, 6mm thick. Dichroic mirror 83, 100% reflection at 532nm, anti reflection coated at 590nm, 54° angle of incidence with respect to the surface of the component (ie 72° between the incident and reflected beams), 25mm diameter, 6mm thick. Dichroic mirror 84, 100% reflection at 532nm, anti reflection coated at 590nm, 36° angle of incidence with respect to the surface of the component (ie 108° between the incident and reflected beams), 25mm diameter, 6mm thick. Negative lens 85, -40mm focal length bi-convex lens, anti reflection coated for 532nm. Mirror 86, 100% reflectance at 532nm, 45° incidence, 25mm diameter. Positive lens 87, +200mm focal length plano-convex lens, anti reflectance coated for 532nm, 25mm diameter, 2mm edge thickness.

Operation to generate and amplify a dye laser beam is as follows. The pump beam 64 is generated by a second harmonic from a Nd:YAG laser, or similar laser (not shown) to give a beam of light typically at 532nm, 250mJ, 20nsec duration. A portion, about 2.1%, of this pump beam 64 is transmitted through the beam splitters 66, 54 into the dye laser 63 and into the dye cell 56 causing a lasing action. Typically the dye laser light is at 590nm. Typically about 65% and 29% remainder of the pump beam 64 energy is reflected off each of the beam splitter 66 and mirror 86 respectively to form pump energy for the amplifiers.

Output from the dye laser 63 is via the lenses 58, 59, half wave plate 60, first polarising beam splitter 61 and then into the SBS dye cell 69. Simultaneously a portion, about 20%, of the remaining pump beam 64 energy from the mirror 86 is reflected by the dichroic beam splitter 81 into the SBS cell 69. As described above with reference to Figure 1, amplified dye laser light is emitted back from the SBS cell 69 and is directed via the dichroic beam splitter 81, quarter wave plate 73, polarising beam splitter 61, quarter wave plate 74, and dichroic beam splitter 82 into the SBS cell 70. Pump beam energy for the SBS cell 70 is from the beam splitter 66 and dichroic beam splitter 82.

Twice amplified dye laser beam is directed from the SBS cell 70 via dichroic beam splitter 82, quarter wave plate 74, polarising beam splitters 61, 62, quarter wave plate 75, and dichroic mirror 83 into the SBS cell 71. Pump energy for this SBS cell 83 is from the dichroic beam splitter 81 and dichroic mirror 83. Amplified, three times, dye laser light is directed from the SBS cell 71 via dichroic mirror 83, quarter wave plate 75, polarising beam splitter 62, quarter wave plate 76, and dichroic mirror 84 into the SBS cell 72. Pump beam energy for this SBS cell 72 is from the dichroic beam splitter 82 and dichroic mirror 84. Amplified, four times, dye laser light is directed from the SBS cell 72 via the dichroic mirror 84, quarter wave plate 76, and polarising beam splitter 62 along the optical path 50 to form the finally amplified dye laser beam.

Typically this finally amplified dye laser beam is 120mJ in 17nsec pulse width, ≤ 64 MHz bandwidth, approximately transform limited.

Further amplification may be achieved using additional SBS cells.

An advantage of the arrangement shown in Figure 3 is the relatively few components used to provide generation and a four stage amplification of a variable wavelength dye laser beam; eg a 120,000 times amplifi-

cation, from about 1 μ J to 120mJ. In one known prior art laser amplifier (Versatile high power single longitudinal mode pulsed dye laser, F Bos, Applied Optics, vol 20, No 10, pages 1886-1890, 15 May 1981), only 114 times amplification was achieved with a similar number of components. The reduced number of components used in the present invention provides a system that is relatively easy to set up and align, and once aligned is robust and insensitive to vibration.

Figure 4 is a modification of Figure 1 where a pump beam 91 enters a dye cell 6 transversely through a cylindrical lens 92. As in Figure 1 a dye laser beam 2 passes through a polarising beam splitter 3, a quarter wave plate 4, a lens 5 and into an SBS dye cell 6. This cell 6 is moved from that of Figure 1 so that the beam 2 enters off axis to allow maximum volume for inter-action with the pump beam.

Figure 5 is another modification of Figure 1 where a pump beam, is provided by a flash lamp source 93 surrounded by reflector 94. Other components are as Figure 4. The cell 6 is arranged co-axially with the dye laser beam 2. The flashlamp 93 may be linear tubes, coaxial i.e. an annular surrounding the cell 6 with or without triaxial or quadaxial adaptations, or helical. Flash lamp pulses are short, typically around 1 μ s.

Claims

1. A dye laser amplifier comprising a dye cell (6), means for supplying a dye laser beam (2) to be amplified, means for supplying a pumping beam (7), means (5) for directing the dye laser beam into the dye cell, means (1,5) for directing the pump beam into the dye cell and means (3,5) for directing the amplified dye laser beam (11) from the amplifier,
Characterised in that said dye cell is a stimulated Brillouin scattering (SBS) dye cell, comprising a laser dye material dissolved in a SBS medium contained between the cell walls, such that when the dye laser and pumping beams are focused in it, a phase conjugate amplified dye laser beam is produced.
2. The amplifier of claim 1 wherein the dye laser beam and pump beam are arranged to enter the SBS cell coaxially.
3. The amplifier of claim 1 wherein the pump beam is arranged to enter the SBS cell transversely to the dye laser beam.
4. The amplifier of claim 1 wherein the pump beam is a beam from a laser.
5. The amplifier of claim 1 wherein the pump beam is a beam from a flashlamp pump.
6. The amplifier of claim 1 comprising a plurality of dye laser amplifiers cascaded together so that the output of a first amplifier is used as the dye laser beam input to the following dye laser amplifier.
7. The amplifier of claim 1 wherein the means for supplying a dye laser beam to be amplified and the means for supplying a pumping beam are separate lasers.
8. The amplifier of claim 1 wherein the means for supplying a dye laser beam to be amplified is provided by a dye laser pumped by a laser that is also the means for supplying a pumping beam.
9. The amplifier of claim 1 wherein the SBS cell comprises a SBS medium that is a solvent for the laser dye material.
10. The amplifier of claim 5 wherein the SBS medium is one selected from one or more of:- methanol, acetone, isopropyl alcohol, ethanol, n-hexane.
11. The amplifier of claim 6 wherein the SBS medium is a mixture of 15-25% of methanol, 65-75% of n-hexane, and 5-15% of isopropyl mixed to give substantially 100% mixture of methanol, n-hexane, and isopropyl.

Patentansprüche

1. Farbstofflaser-Verstärker, der eine Farbstoffzelle (6), Vorrichtung für die Erzeugung eines zu verstärken-

cation, from about 1 μ J to 120mJ. In one known prior art laser amplifier (Versatile high power single longitudinal mode pulsed dye laser, F Bos, Applied Optics, vol 20, No 10, pages 1886-1890, 15 May 1981), only 114 times amplification was achieved with a similar number of components. The reduced number of components used in the present invention provides a system that is relatively easy to set up and align, and once aligned is robust and insensitive to vibration.

Figure 4 is a modification of Figure 1 where a pump beam 91 enters a dye cell 6 transversely through a cylindrical lens 92. As in Figure 1 a dye laser beam 2 passes through a polarising beam splitter 3, a quarter wave plate 4, a lens 5 and into an SBS dye cell 6. This cell 6 is moved from that of Figure 1 so that the beam 2 enters off axis to allow maximum volume for inter-action with the pump beam.

Figure 5 is another modification of Figure 1 where a pump beam, is provided by a flash lamp source 93 surrounded by reflector 94. Other components are as Figure 4. The cell 6 is arranged co-axially with the dye laser beam 2. The flashlamp 93 may be linear tubes, coaxial i.e. an annular surrounding the cell 6 with or without triaxial or quadaxial adaptations, or helical. Flash lamp pulses are short, typically around 1 μ s.

Claims

1. A dye laser amplifier comprising a dye cell (6), means for supplying a dye laser beam (2) to be amplified, means for supplying a pumping beam (7), means (5) for directing the dye laser beam into the dye cell, means (1,5) for directing the pump beam into the dye cell and means (3,5) for directing the amplified dye laser beam (11) from the amplifier,
Characterised in that said dye cell is
a stimulated Brillouin scattering (SBS) dye cell, comprising a laser dye material dissolved in a SBS medium contained between the cell walls, such that when the dye laser and pumping beams are focused in it, a phase conjugate amplified dye laser beam is produced.
2. The amplifier of claim 1 wherein the dye laser beam and pump beam are arranged to enter the SBS cell coaxially.
3. The amplifier of claim 1 wherein the pump beam is arranged to enter the SBS cell transversely to the dye laser beam.
4. The amplifier of claim 1 wherein the pump beam is a beam from a laser.
5. The amplifier of claim 1 wherein the pump beam is a beam from a flashlamp pump.
6. The amplifier of claim 1 comprising a plurality of dye laser amplifiers cascaded together so that the output of a first amplifier is used as the dye laser beam input to the following dye laser amplifier.
7. The amplifier of claim 1 wherein the means for supplying a dye laser beam to be amplified and the means for supplying a pumping beam are separate lasers.
8. The amplifier of claim 1 wherein the means for supplying a dye laser beam to be amplified is provided by a dye laser pumped by a laser that is also the means for supplying a pumping beam.
9. The amplifier of claim 1 wherein the SBS cell comprises a SBS medium that is a solvent for the laser dye material.
10. The amplifier of claim 5 wherein the SBS medium is one selected from one or more of:-
methanol, acetone, isopropyl alcohol, ethanol, n-hexane.
11. The amplifier of claim 6 wherein the SBS medium is a mixture of 15-25% of methanol, 65-75% of n-hexane, and 5-15% of isopropyl mixed to give substantially 100% mixture of methanol, n-hexane, and isopropyl.

Patentansprüche

1. Farbstofflaser-Verstärker, der eine Farbstoffzelle (6), Vorrichtung für die Erzeugung eines zu verstärken-



den Farbstofflaserstrahl (2), Vorrichtung für die Erzeugung eines Pumpstrahls (7), Vorrichtung (5) für Ablenkung des Farbstofflaserstrahls in die Farbstoffzelle, Vorrichtungen (1, 5) für Ablenkung des Pumpstrahls in die Farbstoffzelle und Vorrichtungen (3, 5) für Ablenkung des verstärkten Farbstofflaserstrahls (11) aus dem Verstärker umfaßt,

5 dadurch gekennzeichnet, daß die besagte Farbstoffzelle eine Stimulierte-Brillouin-Streuung-Farbstoffzelle (SBS) ist, in der sich Laser-Farbstoffmaterial befindet, das in einem SBS-Medium gelöst ist, das sich zwischen den Zellwänden befindet, so daß, wenn der Farbstofflaser und der Pumpstrahl darin fokussiert sind, ein phasenkonjugierter verstärkter Farbstofflaserstrahl erzeugt wird.

10 2. Verstärker nach Anspruch 1, bei dem Farbstofflaserstrahl und Pumpenstrahl so angeordnet sind, daß sie koaxial in die SBS-Zelle koaxial eintreten.

3. Verstärker nach Anspruch 1, bei dem der Pumpstrahl so angeordnet ist, daß er in die SBS-Zelle transversal zu dem Farbstofflaserstrahl eintritt.

15 4. Verstärker nach Anspruch 1, bei dem der Pumpstrahl ein Laserstrahl ist.

5. Verstärker nach Anspruch 1, bei dem der Pumpstrahl ein Strahl einer Pumpblitzlampe ist.

20 6. Verstärker nach Anspruch 1, der eine Vielzahl von Farbstofflaserverstärkern umfaßt, die miteinander eine Kette bilden, so daß der Ausgang eines ersten Verstärkers verwendet wird als Farbstofflasereingangsstrahl für den folgenden Farbstofflaserverstärker.

25 7. Verstärker nach Anspruch 1, bei dem die Vorrichtung zur Erzeugung eines Farbstofflaserstrahls, der verstärkt werden soll, und die Vorrichtung für die Erzeugung eines Pumpstrahls separate Laser sind.

8. Verstärker nach Anspruch 1, bei dem die Vorrichtung für die Erzeugung eines zu verstärkenden Farbstofflaserstrahls ein Laser-gepumpter Farbstofflaser ist, der gleichfalls die Vorrichtung für die Erzeugung eines Pumpstrahls darstellt.

30 9. Verstärker nach Anspruch 1, bei dem die SBS-Zelle ein SBS-Medium umfaßt, das ein Lösungsmittel für den Laser-Farbstoff darstellt.

10. Verstärker nach Anspruch 5, bei dem das SBS-Medium einem oder mehreren von: Methanol, Aceton, Isopropylalkohol, Ethanol, n-Hexan entspricht.

35 11. Verstärker nach Anspruch 6, bei dem das SBS-Medium eine Mischung aus 15-25 % Methanol, 65-75 % n-Hexan und 5-15 % Isopropyl ist, so gemischt, daß sich im wesentlichen eine 100 %-Mischung aus Methanol, n-Hexan und Isopropyl ergibt.

Revendications

1. Amplificateur laser à colorant, comprenant une cellule à colorant (6), un dispositif destiné à transmettre un faisceau (2) de laser à colorant à amplifier, un dispositif destiné à transmettre un faisceau de pompage (7), un dispositif (5) destiné à diriger le faisceau laser à colorant dans la cellule à colorant, un dispositif (1, 5) destiné à diriger le faisceau de pompage dans la cellule à colorant, et un dispositif (3, 5) destiné à diriger le faisceau laser à colorant amplifié (11) provenant de l'amplificateur, caractérisé en ce que la cellule à colorant est une cellule à colorant à diffusion simulée de Brillouin (SBS), comprenant une matière de colorant laser dissoute dans un milieu SBS contenu entre les parois de la cellule afin que, lorsque les faisceaux de pompage et du laser à colorant sont focalisés à l'intérieur, un faisceau du laser à colorant amplifié et conjugué en phase soit produit.

2. Amplificateur selon la revendication 1, dans lequel le faisceau laser à colorant et le faisceau de pompage sont destinés à pénétrer coaxialement dans la cellule SBS.

3. Amplificateur selon la revendication 1, dans lequel le faisceau de pompage est destiné à pénétrer dans la cellule SBS en direction transversale au faisceau laser à colorant.



4. Amplificateur selon la revendication 1, dans lequel le faisceau de pompage est un faisceau provenant d'un laser.
5. Amplificateur selon la revendication 1, dans lequel le faisceau de pompage est un faisceau provenant d'une pompe à lampe à éclair.
6. Amplificateur selon la revendication 1, comprenant plusieurs amplificateurs lasers à colorants montés en cascade les uns avec les autres de manière que la sortie d'un premier amplificateur soit utilisée comme entrée de faisceau laser à colorant d'un amplificateur laser à colorant suivant.
7. Amplificateur selon la revendication 1, dans lequel le dispositif destiné à transmettre le faisceau laser à colorant à amplifier et le dispositif destiné à transmettre un faisceau de pompage sont des lasers séparés.
8. Amplificateur selon la revendication 1, dans lequel le dispositif destiné à transmettre le faisceau laser à colorant à amplifier provient d'un laser à colorant pompé par un laser qui constitue aussi le dispositif destiné à transmettre un faisceau de pompage.
9. Amplificateur selon la revendication 1, dans lequel la cellule SBS comprend un milieu SBS qui est un solvant pour la matière colorante du laser.
10. Amplificateur selon la revendication 5, dans lequel le milieu SBS est choisi parmi un ou plusieurs milieux comprenant le méthanol, l'acétone, l'alcool isopropylique, l'éthanol et le n-hexane.
11. Amplificateur selon la revendication 6, dans lequel le milieu SBS est un mélange de 15 à 25 % de méthanol, 65 à 75 % de n-hexane et 5 à 15 % d'alcool isopropylique, mélangés afin qu'ils donnent un mélange de 100 % pratiquement de méthanol, de n-hexane et d'alcool isopropylique.

