Method and system for the real-time calculation of the amount of energy transported in a non-refrigerated, pressurised, liquefied natural gas tank.

The present invention relates in general to a method and system for the real-time calculation of the amount of residual chemical energy in a non-refrigerated, pressurised tank, containing liquefied natural gas (LNG), without the composition of the LNG having to be determined.

The LNG fuel is a simple and effective alternative to conventional fuels, from the standpoint of CO_2 emissions, polluting particles and the energy density. An increasing number of actors are turning to the use thereof, such as road, sea or rail carriers.

However, contrary to conventional fuels, the volume energy density du LNG, i.e. the energy contained per volume unit of LNG, is not constant. This can be explained by two separate phenomena. Firstly, the temperature of the LNG will increase all throughout its storage in a non-refrigerated, pressurised tank due to the residual inputs of heat. This rise in temperature will then generate a thermal expansion of the fluid (that can range up to more than a 20% increase in volume) and therefore a drop in its energy density.

The second phenomenon that explains the variation in the energy density of the LNG is the variation in its composition. LNG is not a refined product, therefore its composition in hydrocarbons can vary according to the deposits used.

The variability in the volume energy density of the LNG stored in a non-refrigerated reservoir can be a problem in systems that require fine monitoring of the fuel consumption. Typically, in the case of lorries running on LNG, it can be observed, for the same reservoir containing 600 L of LNG, a difference in volume energy density of the LNG of about 15 to 20% for an identical composition of LNG, according to whether

the LNG is heavy and cold or whether it is light and hot. This in practice results in a difference of hundred or so kilometres over the number of kilometres travelled, for the same amount of LNG introduced at the start, as shown in the comparative example.

Currently there is no solution to inform the operator of a pressurised tank in real-time of the remaining energy contained in the tank of LNG. The only information available to the operator is the pressure of the gas compositions, the temperature of the LNG (in the best of cases), as well as the level of filling of the tank.

Generally during the filling of the tank by the fuel supplier, an energy calculation is made in accordance with the international standard ISO 6976.1995 using the latest known composition of LNG (and given by the supplier) and of the transferred mass of LNG. This calculation is used as a reference for the financial transaction. Thus, through this calculation at the combustion temperature of the LNG, the gross calorific value GCV_{mass} of the LNG is determined, according to the equation (1), by making the hypothesis that the LNG is substantially comprised of methane, ethane, propane, isobutane, n-butane, iso-pentane, n-pentane and nitrogen:

$$(1) \qquad GCV_{mass}(T_c) = \sum_j (x_j \times \frac{M_j}{M}).GCV_{mass_j}(T_c)$$

Where: - GCV_{mass} represents the calorific value of the LNG,

- T_c the combustion temperature at which the GCV is calculated,
- x_j the mole fraction of the component j in the mixture,
- M_j the molar mass of the component j,
- M the molar mass of the LNG, given by the standard NF EN ISO 6976, and
- GCV_{mass_j} the gross calorific value of the component j given by the charts of ISO 6976.1995.

However, this calculation depends on the composition du LNG. However, this composition can be complex to determine. Indeed, the installation of a chromatograph is necessary.

The absence of information in real time on the energy contained in the tank is a problem for several raisons:

- Supply management: currently, the management of the supply of LNG for certain tanks (in particular those of lorries) is based solely on the volume of liquid remaining in the reservoir. However, management based on the energy demanded by the units connected to the tank would be more coherent, because this is the piece of data is needed, for example to estimate the number of kilometres that can still be travelled;
- Avoiding shortages and running out of fuel: according to the energy density of the LNG, the volume consumption of the units can vary abruptly upwards because a greater amount of LNG is then required in order to obtain the same amount of energy. This variation which is not planned by the operators could cause an unanticipated shortage of fuel and therefore a running out of fuel;
- Training of the operators: the LNG fuel market is of relatively small size. The actors in the market are for the most part professionals that have received training suitable for handling LNG and good practices. However, if the market were to grow quickly, actors with less training would need to handle and/or manage the consumption of LNG. Knowing the amount of energy contained in the tank could make it possible to simply calculate magnitudes that can be understood easily by these operators (for example the number of remaining kilometres).

With this in mind, in order to ensure the development of LNG fuel, the applicant has set up a solution that makes it possible to better plan the energy content thereof in real time

using only thermodynamic parameters measured inside the tank (density of the LNG, temperature and level of the layer of LNG in the tank), and this without knowing the composition of the LNG contained in the tank.

In particular, the present invention has for object a method for the real-time calculation of the residual chemical energy E contained in a non-refrigerated, pressurised tank, defined by its shape and its dimensions and containing a layer of liquefied natural gas (LNG), said layer of LNG being defined at a given instant t, by its temperature T, its density ρ, and its level h in said tank;

said method consisting of an algorithm that comprises, at a given instant *t*, the following steps:

A. Acquisition of the characteristic parameters of the layer of LNG by measurement:
   - of the level *h* of the layer of LNG in the tank, using a level sensor;
   - of the temperature T using a temperature sensor; and
   - of the density ρ using a density sensor; and

B. Determination of the total mass m_t of the LNG contained in the tank;

said method being characterised in that said algorithm further comprises, for each instant *t*, the following steps:

C. Calculation of the mass gross calorific value GCV_{mass} of the LNG using a function f taking as parameters the temperature and the density of the liquid according to the formula:

$$GCV_{mass} = f(T, \rho)$$

D. Calculation of the residual chemical energy E according to the formula:

$$E = GCV_{mass} * m_t$$

The term mass gross calorific value of the natural gas means in terms of the present invention, the amount of heat delivered by the complete combustion of a mass unit of the natural gas concerned contained in the air at a constant pressure and a given temperature. It is expressed as an amount of heat per mass unit of fuel (in the framework of the present invention in kWh/m^3)

With input information such as the shape and the dimension of the tank, the temperature, the level of the layer of LNG and the density of the LNG, the algorithm of the method according to the invention makes it possible to calculate the actual amount of residual chemical energy contained in any tank instantly.

Furthermore, setting up this method is simple because it does not require determining the composition of the LNG, which would require the use a chromatograph or of a calorimeter in order to determine the GCV_{mass} of the LNG. Indeed, usually, the mass GCV of an LNG is calculated according to its composition, generally by making the approximation that it is comprised solely of methane, ethane, propane, isobutane, n-butane, iso-pentane, n-pentane and nitrogen.

With the method according to the invention the error committed by not taking as a base the exact composition of the LNG is at most about 3%: this is the difference observed between the GCV_{mass} of a heavy LNG (containing more than 10% of hydrocarbons other than methane) and the GCV_{mass} of a light LNG (containing more than 99% of pure methane) at the same temperature as that of the composition concerned.

In comparison, the error that would be committed with a method different from the invention in order to determine the GCV_{mass} du LNG can rapidly reach a value of about 20% if the GCV_{mass} of the LNG is determined at an incorrect temperature, including and even if the composition is correct.

Advantageously, said algorithm can be either reiterated at the request of an operator using said tank, or be carried out automatically, as soon as a given interval of time Δt has

elapsed, this interval able to be for example of about one second or where applicable defined optimally to take account of the latency delays according to the sensor technology used.

Determining the total mass of LNG can be carried out in different ways.

According to a first method for determining, the total mass m_t of LNG contained in the tank can be done advantageously by direct measurement using a balance or stress gauges.

According to another advantageous embodiment, determining the total mass m_t of LNG contained in the tank can be carried out by a calculation according to the formula:

$$m_t = \rho * g(h)$$

where:

- h is the level of the layer of LNG in the tank,
- ρ is the density of the LNG, and
- g is a function linked to the shape of the tank, giving a homogeneous value to a volume.

This method of determining the total mass m_t can in particular be used in the case where the direct measurement of the mass is complicated to implement on the tank, for example when the latter is in motion during the measurement.

Advantageously, the function f that connects the mass gross calorific value GCV_{mass} to the parameters T and ρ can be of the form:

$$f(T, \rho) = A(T) + B * \rho$$

where:

- A is a constant value for a given temperature;
- B is a constant independent of the composition.

The values of the two constants present in the function f are defined in the trade publications, such as LNG Industry magazine 2014, or in the scientific literature.

The present invention also has for object a system for calculating in real time, according to the method of the invention, the residual chemical energy E contained in a

pressurised tank defined by its shape and its dimensions and containing a layer of liquefied natural gas (LNG), said layer of LNG being defined at a given instant t, by its temperature T, its density ρ, and its level h in said tank;

said system being characterised in that it comprises:

- a calculator intended to be connected to level, temperature, and density sensors of which said tank is provided with, said calculator being able to execute the algorithm of the method according to the invention,
- an MMI interface interacting with said calculator, in order to report to the operator the amount of residual chemical energy obtained by the algorithm of the method according to the invention, when it is implemented by means of a calculator connected to an MMI interface.

The term MMI interface means, in terms of the present invention, a Man-Machine interface that allows a user to view or to be notified via any audible or mechanical signal of the information on the amount of energy remaining, for the purpose of taking the appropriate decisions for action.

As an MMI interface that can be used within the framework of the present invention, mention can be made in particular of the dashboards of vehicles, computer keyboards, LED indicator lights, touchscreens and tablets, loudspeakers, etc.

According to an advantageous embodiment of the system according to the invention, the latter can be an onboard system in which:

- the calculator can be an onboard calculator connected to said level, temperature and density sensors, the calculator being specifically designed to execute the algorithm of the method according to the invention,
- the MMI interface can also be on board or alternatively offset (if for example the vehicle is connected to a control centre,

this MMI interface, if it is on board, can be of the vehicle onboard dashboard type, interacting specifically with said onboard calculator in order to report to the operator (here the driver) the duration of the autonomy calculated according to the method of the invention.

The term calculator specifically designed to execute the algorithm of the method according to the invention means, in terms of the present invention, an onboard computer comprising a processor combined with a dedicated storage memory and with an interface motherboard; with all of these elements being assembled in such a way as to provide the robustness of the "onboard computer" unit in terms of mechanical, thermodynamic and electromagnetic resistance, and as such allow for the adaptation thereof for a use in a LNG vehicle.

The system according to the invention makes it possible to easily make available to an operator the value of the amount of residual chemical energy contained in the tank, and this, even if the latter has not received any training adapted to the handling of LNG. It also makes it possible to provide this value to a third-party system, such as an onboard computer.

Advantageously, the system can further comprise a balance or stress gauges in order to directly measure the total mass of the LNG contained in the tank.

Finally, the present invention further has for object a vehicle (land, sea or air) comprising a pressurised tank containing a layer of liquefied natural gas and being provided with level, temperature, and density sensors, said vehicle being characterised in that it further comprises a system according to the invention.

Thanks to the system according to the invention, this vehicle can be used easily by an operator that does not have any in-depth training on handling LNG. Indeed, this system makes it possible to either display the value of the remaining energy in the tank or to transmit the value of the residual energy to a

computer that can then deduce therefrom the remaining number of kilometres before another filling of the tank is necessary.

Other advantages and particularities of the present invention shall result from reading the following description, given as a non-limiting example and in reference to the accompanying figures:

- Figure 1 shows the result of several measurements of the calorific value of the LNG according to the density of the liquid natural gas for a given temperature and composition;
- Figure 2 shows the diagram of a particular embodiment of the measuring system according to the invention;
- Figure 3 shows the drawing of an example of a non-refrigerated, pressurised tank that can be used in the framework of the present invention (case of a cylindrical and horizontal tank), whereon are shown the various parameters making it possible to determine the function g(h) that makes it possible to calculate the mass of LNG contained in this tank.
- Figure 4 shows the diagram of an example of a non-refrigerated, pressurised tank that can be used in the framework of the present invention (case of a spherical tank), whereon are shown the various parameters making it possible to determine the function g(h) that makes it possible to calculate the mass of LNG contained in this tank.
- Figures 5 to 7 are screen captures of dashboards of a vehicle each transporting a tank of LNG that is cylindrical and horizontal, showing the input data used for the calculation of the residual chemical energy E according to the method of the invention, as well as the result of this calculation.

Figure 1 shows the result of a set of measurements of gross calorific value taken for different values of density of LNG at

a given temperature (-160°C). These measurement points can be connected satisfactorily (with a correlation coefficient R^2=0.957) via a regression line that, in this particular case at -160°C, has for equation $f(\rho) = 0.0283\rho - 0.7791$. This equation f can therefore be used as a correlation function in order to determine the GCV_{mass} of the LNG when the latter is at the temperature of -160°C.

Figure 2 shows the simplified diagram of a particular embodiment of the invention in the case where the tank 1 is cylindrical and vertical. When a measurement is taken, which can be done continuously, after a time interval Δt has elapsed or after an order from the operator 7, the density 4, temperature 3 and level 2 sensors present in the tank read the values of the temperature of the liquid, of the density as well as level of this liquid in the tank. This information is then sent to the calculator 5 wherein the operator 7 has entered beforehand, via a man-machine interface (MMI) 6, the shape of the tank 1 as well as the characteristic dimensions thereof, in this particular case its radius. This allows the calculator 5 to define the function g(h) used for the determination of the total mass m_t of LNG contained in the tank.

Figure 3 shows the diagram of a cylindrical tank placed horizontally. In this case, the calculation of the volume of a layer of LNG in this tank is similar to calculating the area of a segment of a disc. The function g(h) is then:

$$g(h) = (\mathrm{R}^2 \times \cos^{-1}(\frac{\mathrm{R}-\mathrm{h}}{\mathrm{R}}) - (\mathrm{R}-\mathrm{h}) \times \sqrt{(\mathrm{R}^2 - (\mathrm{R}-\mathrm{h})^2)} \times L$$

If the tank is placed vertically, g(h) is then simply $g(h) = \pi \times \mathrm{R}^2 \times \mathrm{h}$

Figure 4 has a spherical tank. In this case, the calculation of the volume of a layer of LNG in this tank is similar to calculating a spherical cap. The function g(h) is then:

$$V_h = \pi \times (2R - h)^2 \times \frac{(R + h)}{3}$$

Using this information, the calculator 5 then calculates the total mass m_t of LNG contained in the tank 1 and the gross calorific value GCV_{mass} of the LNG, with these values then allowing the calculator to obtain the value of the residual energy E contained in the tank at the time of the measurement. The value of the residual energy E can then be supplied to the operator via the MMI 6 or be reprocessed in order to obtain information that can be understood easily, such as the number of kilometres remaining.

The invention is shown in more detail in the examples hereinafter.

EXAMPLES

EXAMPLE 1 (COMPARATIVE)

This example shows the variability in the volume energy density of the LNG stored in a non-refrigerated reservoir.

For this, through a calculation using the equation (1) of standard ISO 6976:1995, the residual chemical energy E is determined in a reservoir containing 600 L (i.e. 0.6 m^3) of LNG in the case of a heavy and cold LNG (case a): balance at 3 bars) and in the case of an LNG of the same composition but light and hot (case b): balance at 14 bars).

Case a) of a heavy and cold LNG (balance 3 bars)

The hypothesis is made that the LNG has the following composition, indicated hereinafter in table 1.

Table 1

Compound	**Portion of the compound in the LNG as molar percentages**
methane	88.034
ethane	8.243
propane	2.097
i-butane	0.294
n-butane	0.407
nitrogen	0.925

- Combustion conditions:
    - Combustion temperature T_c = 0°C
    - Pressure: 1.01325 bar

- Mass GCV (T_c) = 14.99 kWh/kg, calculated according to the equation of standard ISO 6976:1995
- Temperature of the LNG T = -147.07°C
- Density = 443.7153 kg/m^3

$$E = 0.6 * \text{density} * GCV_{mass} = 3990\text{kWh}$$

Case b) of a light and hot LNG (balance at 14 bars)

The LNG has the same composition as that given in table 2 hereinafter.

Table 2

Compound	**Portion of the compound in the LNG as molar percentages**
methane	96.367
ethane	2.623
propane	0.689
i-butane	0.17
n-butane	0.15
nitrogen	0.01

- Combustion conditions:
    - Combustion temperature T_c = 0°C
    - Pressure: 1.01325 bar
- Mass GCV (T_c) = 15.37 kWh/kg calculated according to the equation of standard ISO 6976:1995
- Temperature of the LNG T = -112.5°C
- Density = 355.65 kg/m^3

$$E = 0.6 * \text{density} * GCV_{mass} = 3279\ \text{kWh}$$

A difference is therefore observed of more than 17% between the energy values E calculated respectively in the cases a) and b). In other terms, for the same initial volume of LNG of 600 litres, this difference in energy can lead to a hundred kilometres travelled in addition if the LNG introduced into the reservoir is cold and heavy (case a), in relation to the number of kilometres travelled in the case b).

EXAMPLE 2 (ACCORDING TO THE INVENTION)

Figures 5 to 7 are screen captures of dashboards of a vehicle each transporting a tank of LNG that is cylindrical and horizontal, showing the input data used for the calculation of the residual chemical energy E according to the method of the invention, as well as the result of this calculation.

In particular, figure 5 is a screen capture of a dashboard showing the input data that is specific to the tank:

- Shape: cylinder, arranged horizontally in the vehicle carrying it;
- Dimensions:
  - length: 1.2 m;
  - diameter: 0.7 m

Figure 6 is a screen capture of a dashboard showing the input data specific to the layer of LNG:

- temperature T: -152.2°C;
- density ρ: 420.2 kg/m^3;
- level h: 0.501 m.

CLAIMS

1. A method for the real-time calculation of a residual chemical energy E contained in a pressurised tank (1) defined by its shape and its dimensions and containing a layer of liquefied natural gas (LNG), said layer of LNG being defined at a given instant t, by its temperature T, its density ρ, and its level h in said tank;

said method consisting of an algorithm that comprises, at the given instant *t*, the following steps:

A. Acquisition of characteristic parameters of the layer of LNG by measurement:
   - of the level *h* of the layer of LNG in the tank, using a level sensor (2);
   - of the temperature T using a temperature sensor (3); and
   - of the density ρ using a density sensor (4); and

B. Determination of a total mass m_t of the LNG contained in the tank (1);

said method being characterised in that said algorithm further comprises, for each instant *t*, the following steps:

C. Calculation of a mass gross calorific value GCV_{mass} of the LNG using a function f taking as parameters the temperature and the density of the liquid according to the formula:

$$\mathrm{GCV_{mass}} = \mathrm{f(T, \rho)}$$

D. Calculation of the residual chemical energy E according to the formula:

$$E = \mathrm{GCV_{mass}} * m_t$$

wherein the function f that connects the mass gross calorific value GCV_{mass} to the parameters T and ρ is of the form:

$$f(T, \rho) = A(T) + B * \rho$$

where:

- A is a constant value for a given temperature
- B is a constant independent of the composition.

2. The method according to claim 1, wherein:

- either said algorithm is reiterated as requested by an operator (7) using said tank (1);
- or said algorithm is carried out automatically, as soon as a given interval of time Δt has elapsed.

3. The method according to claims 1 or 2, wherein the determination of the total mass m_t of LNG contained in the tank (1) is carried out via a direct measurement using a balance or strain gauges.

4. The method according to claims 1 or 2, wherein the determination of the total mass m_t of LNG contained in the tank (1) is carried out via a calculation according to the formula:

$$m_t = \rho * g(h)$$

where:

- h is the level of the layer of LNG in the tank,
- ρ is the density of the LNG, and
- g is a function linked to the shape of the tank.

5. A system for the real-time calculation, according to the method defined according to any of claims 1 to 4, the residual chemical energy E contained in a pressurised tank (1)

defined by its shape and its dimensions and containing a layer of liquefied natural gas (LNG), said layer of LNG being defined at a given instant t, by its temperature T, its density ρ, and its level h in said tank;

said system being characterised in that it comprises:

- a calculator (5) intended to be connected to level (2), temperature (3), and density (4) sensors of which said tank (1) is provided with, said calculator (5) being able to execute the algorithm of the method defined according to any of claims 1 to 5,
- an MMI interface (6), interacting with said calculator (5) in order to report to the operator, the amount of residual chemical energy obtained by the algorithm of the method defined according to any of claims 1 to 4,

wherein said system is an onboard system in which:

- the calculator (5) is an onboard calculator connected to said level (2), temperature (3), and density (4) sensors, said calculator (5) being specifically designed to execute the algorithm of the method according to any of claims 1 to 4,
- the MMI interface (6) is an onboard interface of the vehicle onboard dashboard type or an offset interface.

6. A vehicle comprising a pressurised tank (1) containing a layer of liquefied natural gas and being provided with level (2), temperature (3) and density (4) sensors, said vehicle being characterised in that it further comprises the system defined according to claim 5.