

METHOD, DEVICE, AND TERMINAL DEVICE FOR EXTRACTING DATA

[0001] The present application claims priority to Chinese Patent No. 201610399225.8, filed with the Chinese Patent Office on June 7, 2016 and entitled
5 "METHOD, DEVICE, AND TERMINAL DEVICE FOR EXTRACTING DATA", which is incorporated herein by reference in its entirety.

TECHNICAL FIELD

[0002] The present invention relates to the field of communications technologies, and in particular, to a method, a device, and a terminal device for extracting data.

10 BACKGROUND

[0003] As terminal devices such as mobile phones and tablet computers are quickly developed and widely used, more and more users prefer to use terminal devices for work, life, and learning. Therefore, methods used by the terminal devices to obtain data are increasing too, for example, obtain a verification code used for registration or
15 password retrieval by a mobile phone, and obtain a predetermined part of a certain article on a tablet computer.

[0004] A specific process of obtaining data is described below by using an example in which a verification code used for registration or password retrieval is obtained by using a touchscreen phone. On the touchscreen phone side, when a user performs an
20 operation such as registration or password retrieval, a server sends, by using an SMS message, the verification code to a mobile phone specified by the account to confirm the identity of an operator, and the user needs to perform registration or retrieve the password by using the verification code in the SMS message. Currently, there are two operation methods to obtain the authentication code in the SMS message. Method 1:
25 The user needs to exit an operation interface for registration or password retrieval, enables an SMS message function, and manually selects the verification code on a touchscreen and copy the verification code to obtain the verification code. Method 2:

The user does not use the method of exiting the operation interface for registration or password retrieval, but obtains the verification code by checking a notification message on the mobile phone and learn it in mind.

5 [0005] Generally, to ensure the security of the verification code, the verification code has a certain length and complexity, for example, the verification code includes a combination of uppercase characters, lowercase characters, and numbers, to prevent the verification code to be stolen by unauthorized users and then harming the interests of the users. Although the authentication code with a certain length and complexity can ensure the security of the verification code, in Method 1, the user has to switch between
10 different applications, such operation process is complex, and manually selecting the verification code easily causes an error; in Method 2, it is difficult for the user to learn complex verification codes, and an error is easily to be caused.

SUMMARY

15 [0006] Implementations of the present invention provide a method and a device for extracting data, and a terminal device, and mainly aim to resolve disadvantages in existing technology that an operation process is complex and an error rate is high in a process of extracting data, so as to quickly and accurately extract pending data.

[0007] To achieve the previously described objectives, the present invention provides the following technical solutions:

20 [0008] According to one aspect, the present invention provides a method for extracting data, including: receiving a pressing operation instruction on a touchscreen, and determining a pressing operation position on the touchscreen based on the pressing operation instruction; determining, based on the pressing operation position, a data area from which data needs to be extracted; determining a corresponding data extraction rule
25 based on the data in the data area; and parsing specific data in the data area based on the data extraction rule, to extract the pending data, where the specific data is some or all data in the data area.

[0009] According to another aspect, the present invention provides a device for extracting data, including: a receiving unit, configured to receive a pressing operation
30 instruction on a touchscreen; a first determining unit, configured to determine a pressing operation position on the touchscreen based on the pressing operation instruction received by the receiving unit; a second determining unit, configured to determine,

based on the pressing operation position determined by the first determining unit, a data area from which data needs to be extracted; a third determining unit, configured to determine a corresponding data extraction rule based on the data in the data area determined by the second determining unit; and an extraction unit, configured to parse
5 specific data in the data area based on the data extraction rule determined by the third determining unit, to extract the pending data, where the specific data is some or all data in the data area.

[0010] According to a third aspect, the present invention provides a terminal device, and the terminal device includes the previously described device for extracting data.

10 **[0011]** By using the previously described technical solutions, the technical solutions provided in the implementations of the present invention have at least the following advantages:

[0012] According to the method and the device for extracting data, and the terminal device that are provided in the present invention, the terminal device receives a pressing
15 operation instruction on a touchscreen, determines a pressing operation position on the touchscreen based on the pressing operation instruction, determines, based on the pressing operation position, a data area from which data needs to be extracted; based on the data in the data area, determines a corresponding data extraction rule, and parses specific data in the data area based on the data extraction rule, to extract the pending
20 data, where the specific data is some or all data in the data area. Compared with existing technology, in the present invention, the data extraction rule corresponding to the data area can be used in the data area that is determined by a user based on the pressing operation position on the touchscreen, so that the pending data can be quickly, accurately, and automatically extracted. The operation process described in this
25 application is simple and easy, and also decreases error rate.

[0013] The previous descriptions are merely an overview of the technical solutions of the present invention. To better understand the technical means of the present invention, the previous descriptions can be implemented based on the content of the specification, and to make the previous and other objectives, features, and advantages
30 of the present invention more obvious and comprehensible, specific implementations of the present invention are provided below as examples.

BRIEF DESCRIPTION OF DRAWINGS

[0014] It becomes clear for a person skilled in the art to learn various other advantages and benefits by reading detailed description of the following preferred implementations. The accompanying drawings are merely used for showing the preferred implementations, but not considered as a limitation on the present invention. In all the accompanying drawings, the same reference symbol is used to indicate the same part. In the accompanying drawings:

[0015] FIG. 1 is a flowchart illustrating a method for extracting data, according to an implementation of the present invention;

10 [0016] FIG. 2 is a schematic diagram illustrating how to determine a data area on a browser web page of a tablet computer, according to an implementation of the present invention;

[0017] FIG. 3 is a schematic diagram illustrating how to output prompt information for determining/reselecting pending data, according to an implementation of the present invention;

[0018] FIG. 4 is a schematic diagram illustrating how to determine a data area of a smartphone, according to an implementation of the present invention;

[0019] FIG. 5 is a compositional block diagram illustrating a device for extracting data, according to an implementation of the present invention; and

20 [0020] FIG. 6 is a compositional block diagram illustrating another device for extracting data, according to an implementation of the present invention.

DESCRIPTION OF IMPLEMENTATIONS

[0021] Example implementations of the present application are described in more detail below with reference to the accompanying drawings. Although the example implementations of the present application are displayed in the accompanying drawings, it should be understood that the present application can be implemented in various forms, and shall not be limited by the implementations described here. Instead, these implementations are provided to provide a more thorough understanding of the present application and to convey the scope of the present application to a person skilled in the art.

[0022] An implementation of the present invention provides a method for

extracting data. The method is used on a terminal device side. As shown in FIG. 1, the method includes the following steps.

[0023] 101: Receive a pressing operation instruction on a touchscreen, and determine a pressing operation position on the touchscreen based on the pressing operation instruction.

[0024] When a user needs to extract pending data from a terminal device, the user performs a pressing operation on a touchscreen of the terminal device, and the pressing operation is transmitted to the terminal device by using a capacitive touch sensor or a pressure touch sensor on the touchscreen of the terminal device, and the terminal device parses the pressing operation as a pressing operation instruction for the terminal device, and determines a pressing operation position on the touchscreen based on the pressing operation instruction.

[0025] The user usually performs the pressing operation on the touchscreen by using fingers. However, different users have different habits. Some users tend to press the touchscreen by using middle fingers, and some users tend to press the touchscreen by using index fingers. Regardless of the finger used to press the touchscreen, a pressing point is generated on the touchscreen. The terminal device receives the pressing operation instruction for the touchscreen based on the pressing point, and determines the pressing operation position on the touchscreen based on the pressing point. The finger used by the user to trigger the pressing operation instruction and a specific pressing position on the touchscreen of the terminal device are not limited in the present implementation of the present invention.

[0026] It is worthwhile to note that, to distinguish whether the user taps the touchscreen, or extracts data based on the pressing operation position on the touchscreen, in the present implementation of the present invention, a pressing operation used by the user to trigger the touchscreen needs to be predetermined, so that the terminal device determines the pressing operation of the user as an instruction to trigger data extraction. A smartphone is used as an example for description. If the smartphone uses an ANDROID system, after the user holds or drags a touchscreen, it is determined that the user's pressing operation on the touchscreen is a predetermined data extraction operation. If the smartphone uses an iOS system, and the system supports force touch, after the user slightly presses or heavily presses a touchscreen, it is determined that the pressing operation on the touchscreen is a predetermined data extraction operation. The previous description is merely an example. A pressing

operation method of triggering to extract data on the terminal device is not limited in the present implementation of the present invention.

5 [0027] In the present implementation of the present invention, the terminal device needs to include a touchscreen. The terminal device can include but is not limited to a touchscreen smartphone, a tablet computer, a touchscreen personal computer, a touchscreen multimedia teaching apparatus, etc. A specific type of the terminal device is not limited in the present implementation of the present invention.

[0028] 102: Determine, based on the pressing operation position, a data area from which data needs to be extracted.

10 [0029] The terminal device determines an actual coverage area of the pressing operation position by using a pressing point of the user on the touchscreen as a center, and the actual coverage area is the data area from which data is to be extracted.

[0030] Because users use different fingers to press the touchscreen, data areas determined based on pressing operation positions on the touchscreen have different sizes. In addition, even assume all users use index fingers to press the touchscreen, the determined data areas are still different because of the different index fingers of the users. A size of the data area from which data needs to be extracted is determined based on the pressing operation position on the touchscreen is not limited in the present implementation of the present invention.

20 [0031] In actual applications, because fingers of users of the terminal device have different sizes, an actual coverage area of the finger may fail to cover the pending data. Therefore, a predetermined tolerance region is set. To determine the data area, the terminal device combines the actual coverage area and the predetermined tolerance region, so that the data area is larger than the actual coverage area determined based on the pressing operation position, so as to improve the accuracy of extracting the pending data.

[0032] 103: Determine a corresponding data extraction rule based on the data in the data area.

30 [0033] The corresponding data extraction rule is determined based on the data in the data area determined in step 101 from which data needs to be extracted. In the present implementation of the present invention, the data in the data area includes data such as numbers, upper cases and lower cases in English, graphs, Chinese characters, websites feature characters, and formulas. Because the data in the data area is unknown, the data extraction rule needs to be determined based on different data types of the data

in the data area and attribute information of different data.

[0034] In the present implementation of the present invention, different users have different requirements for extracting the pending data. Therefore, a rule that is specified for different attribute information of the data and a data extraction priority rule that is specified for different data types of the data are generated. The purpose of the present step is to determine an appropriate data extraction rule based on a data type and attribute information of data selected from the data area.

[0035] In actual applications, considering convenience and practicability of using the terminal device, the user usually does not use a terminal device that includes a touchscreen to extract relatively long data, for example, extract all text data included in the entire article. On a touchscreen terminal device side, application scenarios of extracting the pending data usually include extracting a verification code in a smartphone SMS message to verify the user identity, extracting a website from web page content to jump to the web page, extracting an order number in a smartphone SMS message to check the order, extracting a formula on a web page to paste and use the formula, extracting a verification code in an SMS message function on a smartphone notification bar, etc. However, it should be clear that the previous application scenarios for extracting the pending data are merely examples, and are not intended to limit a specific application scenario of the present implementation of the present invention.

[0036] 104. Parse specific data in the data area based on the data extraction rule, to extract the pending data.

[0037] The specific data is some or all data in the data area. When parsing the data in the data area, relevant data that the user wants to extract can be extracted by using only some data in the data area, or the data that the user wants to extract can be extracted by using all the data in the data area. In different data areas, different amounts of specific data are parsed to determine the data extraction rule. This is not limited in the present implementation of the present invention.

[0038] When the terminal device extracts the pending data based on the data extraction rule, to ensure the accuracy of the extracted data, after extracting the pending data, the terminal device outputs and displays the extracted pending data, so that the user can determine the accuracy of the pending data.

[0039] According to the method for extracting data provided in the present invention, the terminal device receives a pressing operation instruction on a touchscreen, determines a pressing operation position on the touchscreen based on the pressing

operation instruction; determines, based on the pressing operation position, a data area from which data needs to be extracted; determines a corresponding data extraction rule based on the data in the data area, and parses specific data in the data area based on the data extraction rule, to extract the pending data, where the specific data is some or all data in the data area. Compared with existing technology, in the present invention, the data extraction rule corresponding to the data area can be used in the data area that is determined by a user based on the pressing operation position on the touchscreen, so that the pending data can be quickly, accurately, and automatically extracted, an operation process is simple and easy, and an error rate is low.

[0040] Further, for better understanding of the method shown in FIG. 1, as details and extension to the previous implementations, the steps in FIG. 1 are described in detail in the present implementation of the present invention.

[0041] In step 103, the corresponding data extraction rule is determined based on the data in the data area, and data included in the data area is uncertain. Therefore, when determining the data extraction rule, the data extraction rule for extracting the pending data can be determined by using the following two methods:

[0042] Method 1: Determine a type of data in the data area, and determine a corresponding data extraction rule based on the data type.

[0043] The data extraction rule in the present implementation of the present invention has different priorities for different data types. Therefore, the type of data in the area can be determined by determining the type of data, so as to determine, based on the priority of the data extraction rule, the data extraction rule used to extract the data.

[0044] In Method 1, the type of data in the data area needs to be determined before the data extraction rule is determined. A type of each piece of data in the data area is determined based on a character input status of the data during compilation. A specific implementation process includes: sequentially parsing all the data in the data area, determining whether the character input status of each piece of data is double-byte or single-byte, and determining the type of each piece of data based on the character input status. The double-byte means that one character occupies two standard character positions, and the double-byte usually includes Chinese characters, stipulated double-byte English characters, graphic symbols and special characters in the GB2312-80, etc. The single-byte means that one character occupies one standard character position, and the single-byte usually includes English letters, numbers, and symbols of the Western

languages.

[0045] In actual applications, the data in the data area consists of a plurality of continuous characters. In addition, based on the number of standard character positions occupied by the double-byte or the single-byte, during determining of the character input status of each piece of data, the type of the data can be determined by determining a standard character position occupied by each character in the data area.

[0046] Method 2: Obtain attribute information of the data in the data area, and determine a data extraction rule based on the attribute information.

[0047] In Method 2, the attribute information of the data in the data area can be obtained by using the following method. For example, all the data in the data area is segmented into words, data obtained after word segmentation is searched for data that matches a predetermined keyword, and attribute information of the data is determined based on the predetermined keyword. The predetermined keyword is in one-to-one mapping relationship with the attribute information, and is used to identify the attribute information. In the present implementation of the present invention, when the data in the data area is segmented into words, references can be made to any word segmentation method in existing technology, and the word segmentation method is not described here again in the present implementation of the present invention.

[0048] In actual applications, a current application scenario of the data can be determined based on the attribute information (the predetermined keyword) of the data in the data area. For example, when the predetermined keyword of the data is an SMS message verification code or a mobile phone confirmation code, it can be determined that a current application scenario of data extracted by the terminal device is an SMS message application of a smartphone. When the predetermined keyword of the data is content such as "http://", ".com", or ".cn", it can be determined that a current application scenario of data extracted by the terminal device is webpage browsing. The previous descriptions are merely examples, and do not limit an application scenario for extracting the data in the data area.

[0049] For example, Table 1 shows a mapping relationship between attribute information and a data extraction rule, according to an implementation of the present invention. When data obtained after word segmentation in the data area matches any predetermined keyword in Table 1, a data extraction rule corresponding to the predetermined keyword is determined. A predetermined keyword (order number *) in Table 1 is used as an example for description. * represents any one or more pieces of

data after the order number. When data obtained after word segmentation includes data such as "an order number is", "order number", and "order number:", all of them can match the predetermined keyword. Therefore, it is determined that a data extraction rule is to extract continuous digit data after the order number * and before the punctuation mark.

Table 1

Predetermined keyword	Data extraction rule	Notes
http://*	Extract the entire website	
*.com/.cn		
Shipping number *, order number *	Extract continuous digit data before the order number * and before the punctuation mark	
Verification code */verification information */mobile phone confirmation code */confirmation code *	Extract continuous character string data after the verification code */verification information */mobile phone confirmation code */confirmation code * and before the punctuation mark	
Formula */area */size *	Extract a formula after the formula */area */size * and before the punctuation mark	
Phone number */telephone number *	Extract continuous character string information after the phone number/telephone number and before the punctuation mark	
@.cn/*@*.com	Extract the mailbox address that includes the corresponding predetermined keyword	
...	...	

[0050] Further, the implementation of the present invention can automatically, quickly, and accurately extract data on the terminal device, and after the corresponding data extraction rule is determined based on the data in the data area, the data is extracted based on the data extraction rule. When the data extraction rule is the data extraction rule determined based on Method 1, the pending data is extracted based on a data extraction rule with the highest priority, and after the pending data is extracted, the prompt information used for displaying the determined pending data is output, so that the user determines whether the pending data is data that the user wants to extract. If

the user determines that the pending data is correct, a confirm button in the prompt information is triggered, and the terminal device receives a predetermined confirmation instruction, automatically copies the pending data to a system clipboard, and outputs prompt information indicating that the pending data is successfully obtained, so that the user can use the pending data. If the user determines that the pending data is incorrect, the user triggers a reselection button in the prompt information, and the terminal device receives a predetermined reselection instruction, and continues to extract the data in the data area by using a data extraction rule with the second highest priority. After the data is extracted, prompt information for confirming the pending data is displayed until the terminal device receives a predetermined confirmation instruction, to obtain the pending data after re-extraction.

[0051] When the data extraction rule is the data extraction rule determined based on Method 2, extracting the pending data from the data area based on the determined data extraction rule includes: directly extracting the pending from the data area based on the determined data extraction rule. It is worthwhile to note that, in Method 2, the determined data extraction rule is in one-to-one mapping relationship with the attribute information. That is, when the attribute information of the data in the data area is confirmed, the data is extracted based on the data extraction rule corresponding to the attribute information (the predetermined keyword), and a priority of the data extraction rule is not set. Two examples are provided below to describe data extraction rules determined when data in different application scenarios is extracted. Example 1: If it is determined that the data in the data area is verification code information in an SMS message, the terminal device performs word segmentation and semantic parsing on all the data in the data area. When obtaining a predetermined keyword verification code, the terminal device automatically obtains substantive data of the verification code, for example, :123abc. Example 2: If it is determined that the data area includes a certain website link or a part of a certain website link, the terminal device analyzes the attribute information of the data and extracts the website link because the data area determined by the user based on the pressing operation position on the touchscreen is smaller than the website link or the part of the website link. The previous two examples are merely examples. In the present implementation of the present invention, a specific application scenario corresponding to the data area is not limited.

[0052] It is worthwhile to note that, when the terminal device determines the corresponding data extraction rule based on Method 1 or Method 2, if the data

extraction rule cannot be determined based on Method 1, the data extraction rule can be determined based on Method 2, and if the data extraction rule cannot be determined based on Method 2, the data extraction rule can be determined based on Method 1. In the present implementation of the present invention, a method used for determining the data extraction rule is not limited, and the data extraction rule needs to be determined based on the data in the data area.

[0053] For example, as shown in FIG. 2, the user uses a browser in a tablet computer to browse a web page, to extract data `http://ABCd.com` on the web page, and the terminal device determines the data area shown in FIG. 2 based on the pressing operation instruction of the user. The data in the data area includes "`http://`", the terminal device parses the data `http://`, determines a character input status of each piece of data has only a single-byte. Thus, based on the type of data, the data extraction rule is to extract only a single-byte character. After extracting the pending data "`http://`", as shown in FIG. 3, the terminal device outputs prompt information used for displaying "determine/reselect pending data" by using a dialog box. After tapping a reselect button, the user re-obtains the pending data. All the data in the data area is segmented into words, data obtained after word segmentation is matched with the predetermined keyword. The predetermined keyword is in one-to-one mapping relationship with the attribute information of the data. The determined attribute information of the data is a website. It is determined based on the attribute information that the data extraction rule is to extract the entire website, and after pending data "`http://www.ABCd.com`" is extracted, prompt information used for determining or reselecting the pending data is displayed, and after the user triggers a confirm button, `http://www.ABCd.com` is automatically copied to a system clipboard for the user to use.

[0054] Optionally, when extracting the pending data by parsing the data in the data area based on the data extraction rule, first remove redundant data between the data in the data area, and then extracts, based on the data extraction rule, pending data obtained after the redundant data is removed. The redundant data can include but is not limited to space, punctuation marks, etc.

[0055] Further, before determining the corresponding data extraction rule based on the data in the data area, the data extraction rule is generated, and the data extraction rule is configured. The data extraction rule can be configured by using the following method. For example, a priority of the data extraction rule is configured based on different data types; or the data extraction rule is configured based on the attribute

information of the data. Generally, when the data extraction rule is configured based on the attribute information, the attribute information and the data extraction rule are in one-to-one mapping relationship.

[0056] For example, when the priority of the data extraction rule is configured based on different data types, a data extraction rule in which extracted characters include a single-byte character is set to the highest priority; or if data types in the data area include both a double-byte character and a single-byte character, the amount of data corresponding to the single-byte character and the amount of data corresponding to the double-byte character are separately counted, and characters with the larger amount between the single-byte characters and double-byte characters are extracted; or a data extraction rule in which extracted characters include only numbers is set. The previous description is merely an example, and a specific method for configuring the data extraction rule is not limited in the present implementation of the present invention.

[0057] Further, because users' fingers are of different sizes, determined data areas may have different sizes or may be incomplete. Therefore, the terminal device sets a predetermined tolerance region to resolve the previous problem. When setting the predetermined tolerance region, the terminal device can set the predetermined tolerance region as a fixed area, or set the predetermined tolerance region to a predetermined percentage of the actual coverage area of the pressing operation position on the touchscreen. When determining, based on the pressing operation position on the touchscreen, the data area from which data needs to be extracted, the terminal device determines the actual coverage area of the pressing operation position on the touchscreen, obtains the predetermined tolerance region, and combines the actual coverage area and the predetermined tolerance region, to determine the data area. A specific method for setting the predetermined tolerance region is not limited in the present implementation of the present invention.

[0058] For example, to describe in detail a process of determining the data area, supplementary descriptions are provided below as examples. For example, FIG. 4 is a schematic diagram illustrating how a mobile phone determines a data area, according to an implementation of the present invention. As shown in FIG. 4, it is assumed that the terminal device is a smartphone. A user of the terminal device wants to obtain verification code information in an SMS message. The user obtains the verification code through touching and holding. An actual coverage area of a pressing operation position on a touchscreen is shown by dotted lines in the figure. After the actual

coverage area and a predetermined tolerance region are combined, a solid line area in the figure, that is, a data area, is determined. It is worthwhile to note that, FIG. 4 is merely an example, and a position from which the user extracts data is not limited in the present implementation of the present invention.

5 **[0059]** Further, to help the user use the successfully extracted data, after extracting the pending data, the terminal device outputs prompt information indicating that the pending data is successfully obtained. When the prompt information indicating that the pending data is successfully obtained is output, the prompt information can be displayed by popping out a dialog box; or after successfully obtaining the pending data, the user
10 of the terminal device is notified through audio broadcasting. The form of the prompt information indicating that the pending data is successfully obtained is not limited in the present implementation of the present invention.

[0060] A process of extracting pending data from the terminal device is described in detail above. It is worthwhile to note that, in the method provided in the present
15 implementation of the present invention, data such as numbers, letters, and special symbols is extracted in a Chinese language scenario, and the data can be quickly and accurately extracted. However, if a Chinese character is to be extracted in the Chinese language scenario, the data cannot be accurately and automatically extracted by using the method provided in the present invention. The Chinese can be extracted in the
20 Chinese language scenario by using a method of manually selecting pending data in the existing technology. Similarly, data such as Chinese characters and special symbols in an application scenario of English and other languages can also quickly and accurately extracted, but data of the same language may not be accurately and automatically extracted in the application scenario of English and other languages.

25 **[0061]** Further, as implementation of the method shown in FIG. 1, another device for extracting data is provided according to an implementation of the present invention. The device implementation is corresponding to the previous method implementations. For ease of reading, detailed content in the method implementations is not repeatedly described in the present device implementation, but it should be clear that the device in
30 the present implementation can correspondingly implement all content in the previous method implementations.

[0062] An implementation of the present invention provides a device for extracting data. As shown in FIG. 5, the device includes: a receiving unit 51, configured to receive a pressing operation instruction on a touchscreen; a first determining unit 52, configured

to determine a pressing operation position on the touchscreen based on the pressing operation instruction received by the receiving unit 51; a second determining unit 53, configured to determine, based on the pressing operation position determined by the first determining unit 52, a data area from which data needs to be extracted; a third
5 determining unit 54, configured to determine a corresponding data extraction rule based on the data in the data area determined by the second determining unit 53; and an extraction unit 55, configured to parse specific data in the data area based on the data extraction rule determined by the third determining unit 54, to extract the pending data, where the specific data is some or all data in the data area.

10 **[0063]** Further, as shown in FIG. 6, the third determining unit 54 includes: a first determining module 541, configured to determine a data type of the data in the data area; and a second determining module 542, configured to determine the data extraction rule corresponding to the data type based on the data type determined by the first determining module 541, where the data extraction rule has different priorities for
15 different data types.

[0064] Further, as shown in FIG. 6, the first determining module 541 includes: a parsing submodule 5411, configured to sequentially parse all the data in the data area; a first determining submodule 5412, configured to determine a character input status of each piece of data in a process in which the parsing submodule 5411 sequentially parses
20 all the data in the data area, where the character input status includes double-byte and single-byte; and a second determining submodule 5413, configured to determine a type of each piece of data based on the character input status determined by the first determining submodule 5412.

[0065] Further, the extraction unit 55 parses the specific data in the data area based
25 on a data extraction rule with the highest priority to extract the pending data.

[0066] Further, as shown in FIG. 6, the extraction unit 55 includes: a display unit 551, configured to display prompt information for confirming the pending data; an acquisition module 552, configured to obtain the pending data if a predetermined confirmation instruction is received; and a processing module 553, configured to
30 continue to extract the specific data in the data area based on a data extraction rule priority until a predetermined confirmation instruction is received, to obtain the pending data after re-extraction if a predetermined reselection instruction is received.

[0067] Further, as shown in FIG. 6, the third determining unit 54 further includes: an acquisition module 543, configured to obtain attribute information of the data in the

data area; and a third determining module 544, configured to determine the data extraction rule based on the attribute information obtained by the acquisition module 543.

[0068] Further, as shown in FIG. 6, the acquisition module 543 includes: a word segmentation submodule 5431, configured to segment all the data in the data area into words; a searching submodule 5432, configured to search data obtained after the word segmentation submodule 5431 performs word segmentation for data that matches a predetermined keyword, where the predetermined keyword is used to identify the attribute information; and a determining submodule 5433, configured to determine attribute information of the data based on the predetermined keyword identified by the searching submodule 5432.

[0069] Further, as shown in FIG. 6, the device further includes: a generating unit 56, configured to generate the data extraction rule before the third determining unit 54 determines the corresponding data extraction rule based on the data in the data area; and a configuration unit 57, configured to configure the data extraction rule generated by the generating unit 56.

[0070] Further, as shown in FIG. 6, the configuration unit 57 includes: a first configuration module 571, configured to set a priority of the data extraction rule based on different data types; and a second configuration module 572, configured to configure the data extraction rule based on the attribute information of the data.

[0071] Further, as shown in FIG. 6, the first determining unit 52 includes: a first determining module 521, configured to determine an actual coverage area of the pressing operation position on the touchscreen; a combination module 522, configured to combine the actual coverage area determined by the first determining module 521 and a predetermined tolerance region; and a second determining module 523, configured to determine the data area after the combination module 522 combines the actual coverage area and the predetermined tolerance region.

[0072] Further, as shown in FIG. 6, the device further includes: a display output unit 58, configured to extract the pending data, and output prompt information indicating that the pending data is successfully obtained after the extraction unit 55 parses the data in the data area based on the data extraction rule.

[0073] Further, an implementation of the present invention further provides a terminal device, and the terminal device includes the device for extracting data shown in either FIG. 5 or FIG. 6.

[0074] According to the device for extracting data and the terminal device that are provided in the implementations of the present invention, the terminal device receives a pressing operation instruction on a touchscreen, determines a pressing operation position on the touchscreen based on the pressing operation instruction, determines,
5 based on the pressing operation position, a data area from which data needs to be extracted, determines a corresponding data extraction rule based on the data in the data area, and parses data in the data area based on the data extraction rule, to extract the pending data, where the specific data is some or all data in the data area. Compared with existing technology, in the implementations of the present invention, the data
10 extraction rule corresponding to the data area can be used in the data area that is determined by a user based on the pressing operation position on the touchscreen, so that the pending data can be quickly, accurately, and automatically extracted, an operation process is simple and easy, and an error rate is low.

[0075] The data generation device includes a processor and a memory, and the first
15 determining unit, the second determining unit, the third determining unit, and the extraction unit are stored in the memory as program units, and the processor executes the previously described program units stored in the memory to implement corresponding functions.

[0076] The processor includes a kernel, and the kernel invokes a corresponding
20 program unit from the memory. One or more kernels can be set, to resolve disadvantages in existing technology that an operation process is complex and an error rate is high in a process of extracting data, so as to quickly and accurately extract pending data.

[0077] The memory can include a non-permanent memory in a computer readable
25 medium, a random access memory (RAM) and/or a non-volatile memory, such as a read-only memory (ROM) or a flash memory (flash RAM), and the memory includes at least one storage chip.

[0078] The present application further provides a computer program product. When
executed on a data processing device, the computer program product is suitable for
30 executing program code including the following method steps: receiving a pressing operation instruction on a touchscreen, and determining a pressing operation position on the touchscreen based on the pressing operation instruction; determining, based on the pressing operation position, a data area from which data needs to be extracted; determining a corresponding data extraction rule based on the data in the data area; and

parsing specific data in the data area based on the data extraction rule, to extract the pending data, where the specific data is some or all data in the data area.

[0079] A person skilled in the art should understand that the implementations of the present application can be provided as a method, a system, or a computer program product. Therefore, the present application can use hardware only implementations, software only implementations, or implementations with a combination of software and hardware. In addition, the present application can use a form of a computer program product that is implemented on one or more computer-usable storage media (including but not limited to a magnetic disk storage, a CD-ROM, and an optical memory) that include computer-usable program code.

[0080] The present application is described with reference to the flowcharts and/or block diagrams of the graph display method, the device, and the computer program product according to the implementations of the present application. It should be understood that computer program instructions can be used to implement each process and/or each block in the flowcharts and/or the block diagrams and a combination of a process and/or a block in the flowcharts and/or the block diagrams. These computer program instructions can be provided for a general-purpose computer, a dedicated computer, an embedded processor, or a processor of another programmable data processing device to generate a machine, so that the instructions executed by the computer or the processor of the another programmable data processing device generate an apparatus for implementing a specific function in one or more processes in the flowcharts and/or in one or more blocks in the block diagrams.

[0081] These computer program instructions can be stored in a computer readable memory that can instruct the computer, or the another programmable data processing device to work by using a specific method, so that the instructions stored in the computer readable memory generate an artifact that includes an instruction device. The instruction device implements a specific function in one or more processes in the flowcharts and/or in one or more blocks in the block diagrams.

[0082] These computer program instructions can be loaded onto the computer or the another programmable data processing device, so that a series of operations and steps are performed on the computer or the another programmable device, thereby generating computer-implemented processing. Therefore, the instructions executed on the computer or the another programmable device provide steps for implementing a specific function in one or more processes in the flowcharts and/or in one or more

blocks in the block diagrams.

[0083] In a typical configuration, a computing device includes one or more processors (CPU), an input/output interface, a network interface, and a memory.

5 **[0084]** The memory can include a non-permanent memory in a computer readable medium, a random access memory (RAM) and/or a non-volatile memory, such as a read-only memory (ROM) or a flash memory (flash RAM). The memory is an example of the computer readable medium.

10 **[0085]** The computer readable medium includes persistent, non-persistent, movable, and unmovable media that can implement information storage by using any method or technology. Information can be a computer readable instruction, a data structure, a program module, or other data. Examples of a computer storage medium include but are not limited to: a phase-change random access memory (PRAM), a static random access memory (SRAM), a dynamic random access memory (DRAM) or another type of random access memory (RAM), a read-only memory (ROM), an electrically erasable
15 programmable read-only memory (EEPROM), a flash memory or another memory technology, a compact disc read-only memory (CD-ROM), a digital versatile disc (DVD) or another optical storage, a magnetic cassette, a magnetic tape, a magnetic tape/magnetic disk memory or another magnetic storage device, or any other non-transmission medium that can be used to store information that can be accessed by a
20 computing device. Based on the definition in the present specification, the computer readable medium does not include transitory computer-readable media (transitory media), for example, a modulated data signal and carrier.

[0086] The above-mentioned descriptions are merely the implementations of the present application, but are not intended to limit the present application. For a person
25 skilled in the art, the present application can have various modifications and changes. Any modifications, equivalent substitutions, improvements, etc. made in the spirit and principle of the present application shall fall in the scope of the claims in the present application.

CLAIMS

What is claimed is:

1. A method for extracting data, comprising:

receiving a pressing operation instruction on a touchscreen, and determining a
5 pressing operation position on the touchscreen based on the pressing operation instruction;

determining, based on the pressing operation position, a data area from which data needs to be extracted;

determining a corresponding data extraction rule based on the data in the data area;

10 and

parsing specific data in the data area based on the data extraction rule, to extract the pending data, wherein the specific data is some or all data in the data area.

2. The method according to claim 1, wherein the determining a corresponding data extraction rule based on the data in the data area comprises:

15 determining a type of the data in the data area; and

determining the data extraction rule corresponding to the data type based on the data type, wherein the data extraction rule has different priorities for different data types.

3. The method according to claim 2, wherein the determining a type of the data in the data area comprises:

20 sequentially parsing all the data in the data area, and determining a character input status of each piece of data, wherein the character input status comprises double-byte and single-byte; and

determining a type of each piece of data based on the character input status.

4. The method according to claim 2, wherein the parsing specific data in the data
25 area based on the data extraction rule, to extract the pending data comprises:

parsing the specific data in the data area based on a data extraction rule with the highest priority, to extract the pending data.

5. The method according to claim 4, wherein the parsing the specific data in the data area based on a data extraction rule with the highest priority, to extract the pending
30 data comprises:

displaying prompt information for confirming the pending data;

if a predetermined confirmation instruction is received, obtaining the pending data;

and

if a predetermined reselection instruction is received, continuing to extract the specific data in the data area based on a data extraction rule priority until a predetermined confirmation instruction is received, to obtain the pending data after re-extraction.

6. The method according to claim 2, wherein the determining a corresponding data extraction rule based on the data in the data area further comprises:

obtaining attribute information of the data in the data area; and

determining the data extraction rule based on the attribute information.

7. The method according to claim 6, wherein the obtaining attribute information of the data in the data area comprises:

segmenting all the data in the data area into words;

searching data obtained after word segmentation for data that matches a predetermined keyword, wherein the predetermined keyword is used to identify the attribute information; and

determining attribute information of the data based on the predetermined keyword.

8. The method according to claim 7, wherein before the determining a corresponding data extraction rule based on the data in the data area, the method further comprises:

generating the data extraction rule, and configuring the data extraction rule.

9. The method according to claim 8, wherein the configuring the data extraction rule comprises:

configuring a priority of the data extraction rule based on different data types; or

configuring the data extraction rule based on the attribute information of the data.

10. The method according to any one of claims 1 to 9, wherein the determining, based on the pressing operation position, a data area from which data needs to be extracted comprises:

determining an actual coverage area of the pressing operation position on the touchscreen; and

combining the actual coverage area and a predetermined tolerance region, to determine the data area.

11. The method according to claim 10, wherein after the parsing specific data in the data area based on the data extraction rule, to extract the pending data, the method further comprises:

outputting prompt information indicating that the pending data is successfully obtained.

12. A device for extracting data, comprising:

5 a receiving unit, configured to receive a pressing operation instruction on a touchscreen;

a first determining unit, configured to determine a pressing operation position on the touchscreen based on the pressing operation instruction received by the receiving unit;

10 a second determining unit, configured to determine, based on the pressing operation position determined by the first determining unit, a data area from which data needs to be extracted;

a third determining unit, configured to determine a corresponding data extraction rule based on the data in the data area determined by the second determining unit; and

15 an extraction unit, configured to parse specific data in the data area based on the data extraction rule determined by the third determining unit, to extract the pending data, wherein the specific data is some or all data in the data area.

13. The device according to claim 12, wherein the third determining unit comprises:

20 a first determining module, configured to determine a type of the data in the data area; and

a second determining module, configured to determine the data extraction rule corresponding to the data type based on the data type determined by the first determining module, wherein the data extraction rule has different priorities for different data types.

25 14. The device according to claim 13, wherein the first determining module comprises:

a parsing submodule, configured to sequentially parse all the data in the data area;

30 a first determining submodule, configured to determine a character input status of each piece of data in a process in which the parsing submodule sequentially parses all the data in the data area, wherein the character input status comprises double-byte and single-byte; and

a second determining submodule, configured to determine a type of each piece of data based on the character input status determined by the first determining submodule.

15. The device according to claim 13, wherein the extraction unit parses the

specific data in the data area based on a data extraction rule with the highest priority, to extract the pending data.

16. The device according to claim 15, wherein the extraction unit comprises:

a display unit, configured to display prompt information for confirming the pending data;

an acquisition module, configured to obtain the pending data if a predetermined confirmation instruction is received; and

a processing module, configured to continue to extract the specific data in the data area based on a data extraction rule priority until a predetermined confirmation instruction is received, to obtain the pending data after re-extraction if a predetermined reselection instruction is received.

17. The device according to claim 13, wherein the third determining unit further comprises:

an acquisition module, configured to obtain attribute information of the data in the data area; and

a third determining module, configured to determine the data extraction rule based on the attribute information obtained by the acquisition module.

18. The device according to claim 17, wherein the acquisition module comprises:

a word segmentation submodule, configured to segment all the data in the data area into words;

a searching submodule, configured to search data obtained after the word segmentation submodule performs word segmentation for data that matches a predetermined keyword, wherein the predetermined keyword is used to identify the attribute information; and

a determining submodule, configured to determine attribute information of the data based on the predetermined keyword identified by the searching submodule.

19. The device according to claim 18, wherein the device further comprises:

a generating unit, configured to generate the data extraction rule before the third determining unit determines the corresponding data extraction rule based on the data in the data area; and

a configuration unit, configured to configure the data extraction rule generated by the generating unit.

20. The device according to claim 19, wherein the configuration unit comprises:

a first configuration module, configured to set a priority of the data extraction rule

based on different data types; and

a second configuration module, configured to configure the data extraction rule based on the attribute information of the data.

21. The device according to any one of claims 12 to 20, wherein the first
5 determining unit comprises:

a first determining module, configured to determine an actual coverage area of the pressing operation position on the touchscreen;

a combination module, configured to combine the actual coverage area determined by the first determining module and a predetermined tolerance region; and

10 a second determining module, configured to determine the data area after the combination module combines the actual coverage area and the predetermined tolerance region.

22. The device according to claim 21, wherein the device further comprises:

a display output unit, configured to extract the pending data, and output prompt
15 information indicating that the pending data is successfully obtained after the extraction unit parses the data in the data area based on the data extraction rule.

23. A terminal device, wherein the terminal device comprises the device for extracting data according to any one of claims 12 to 22.