

Description

The invention relates to an apparatus for mixing two or more flowable materials to obtain a uniform mixture. Materials which may be mixed include liquids, gases, or finely divided solids, for example in the form of a fluid/solid slurry. The invention relates in particular to a mixing apparatus comprising a tubular vessel internally provided with a plurality of mixing guides, for example in the form of baffles, which interfere with and cause turbulence in the flow of the materials in the apparatus.

Mixing apparatus of the above type is widely applied for a great variety of purposes, such as the production of uniform mixtures of liquids, gases and finely divided solids and the production of compounds, such as for example resins, from reactive liquids.

Upon flowing materials through such an apparatus the mixing guides constitute obstructions in the flow, which obstructions cause turbulence in the flowing materials, resulting in mixing of the various components in the flowing materials. Dependent on the compositions of the materials, the result of flowing through the apparatus may be a uniform mixture, or it may be a compound if the components in the flow are reactive with one another.

Increase of the turbulence in the flow is, however, accompanied by an increase of the pressure drop over the mixing apparatus.

In the conventional mixing apparatus of the above type, the mixing guides are fixedly mounted in the passage for the flow, and may have various shapes, for example the shape of a helix. These known mixing apparatuses are sometimes called static mixers.

A consequence of the application of fixedly mounted mixing guides is a limitation on the range of applicability of a static mixer, as discussed below. It is this limitation that is avoided by the present invention.

At low flow velocities in a static mixer of the conventional kind, the resistance caused by the mixing guides will be rather low, so that turbulence of the fluid (and therefore uniform mixing) will not readily occur, especially with rather viscous materials. On the other hand, at high flow velocities wherein the velocity itself generates turbulence in the flow, the mixing guides are not needed to contribute to the turbulence. Further, the resistance caused by the mixing guides at such high velocities easily becomes so great that the pressure drop over the mixing apparatus increases dramatically. Such a high pressure drop will cause a decrease of the pumping capacity of the supply pump(s) resulting in a lower capacity of the mixer.

The object of the present invention, therefore, is to provide an apparatus for mixing two or more flowable materials, wherein optimal mixing can be obtained at a wide range of flow velocities without an inadmissible pressure drop over the apparatus.

The apparatus for mixing flowable materials according to the invention comprises a tubular vessel having an inlet for supplying materials to be mixed and an outlet for discharging the said materials after mixing, a plurality of axially spaced apart mixing guides arranged within the vessel between the inlet and the outlet, characterised in that each mixing guide is rotatable about an axis transverse to the tubular vessel and means for changing the angular position of each mixing guide.

As the mixing guides are rotatably mounted in the vessel according to the invention, the angular position of the mixing guides can be adjusted to the flow velocity and to the characteristics of the materials passing through the vessel. In this manner an intense mixing can be obtained at relatively low flow velocities, whereas at high velocities the pressure drop over the vessel can be restricted by repositioning the mixing guides. Thus the range of applicability of such a mixer is significantly extended.

The invention will be further elucidated by way of example with reference to the accompanying drawing showing an isometric projection of a mixing apparatus according to the invention.

The mixing apparatus shown in the drawing comprises an elongated cylindrical vessel 1 being open at both ends to form an inlet 2 and an outlet 3. The vessel is further provided with flanges 4 and 5 for connecting the vessel to (for example) a pipeline system (not shown).

The interior of the vessel 1 is provided with a plurality of mixing guides 6 which are spaced apart from each other along the longitudinal axis 8 of the vessel 1.

Each mixing guide 6 has a respective axis of rotation 7. The axes of rotation 7 are substantially perpendicular to the longitudinal axis 8 of the vessel 1. Preferably the axes 7 are not parallel to each other; in the embodiment as shown, the axes of rotation 7 of successive mixing guides 6 cross each other at angles of about 90 degrees.

Each mixing guide 6 comprises two flat semi-circular baffles 9, rotatably interconnected by means of a pivot located at 10. The baffles 9 are each provided with a shaft 11 passing through a respective opening through the wall of the vessel 1. Each shaft 11 is rotatable about a respective axis 7. Each shaft 11 is provided with a handle 12, for changing the angular position of each baffle 9. In this embodiment the shafts 11 are provided with handles 12; it should be understood (as will be discussed below) that other means of rotation may be used.

Upon passing of a flow of materials introduced via inlet 2 through the interior of the vessel 1, the flow is divided into two streams A and B due to the obstructions formed by the baffles 9 of each mixing guide 6. The part of the flow stream reaching the upper baffle 9 of a vertically arranged mixing guide 6 is deflected in downward direction (stream A), whereas the part of the flow reaching the lower baffle 9 is deflected in upward direction (stream B). Upon passing

(11)

through the restricted openings between the flat ends of the baffles 9, streams A and B are forced together resulting in a mixing of the components of streams A and B with one another. When passing each further mixing guide 6 the flow is again split and redirected causing a further mixing and redistribution over the cross section of the vessel 1.

In other words the presence of the mixing guides 6, forming obstructions for the flow causes turbulence in the flow, so that the components in the flow are intensively mixed.

When the flow velocity in the vessel is rather low and/or the components of the flow are rather viscous so that the incoming flow tends to remain substantially laminar and can only with some difficulty made turbulent, the baffles 9 of each mixing guide 6 are set nearly perpendicular to the general direction of flow, resulting in a substantial re-direction of flow and the generation of turbulence, thereby achieving the desired mixing at low flow rates.

When the flow velocity in the vessel is rather high and/or the components of the flow are less viscous, so that the incoming material may already be in turbulence, or easily caused to be turbulent, the baffles 9 are not required to contribute to the turbulence. Under this condition the baffles 9 are repositioned in such a manner that they hardly form obstructions to the flow, so that the pressure drop over the vessel 1 due to the mixing guides 6 is kept relatively low. Thus, the mixer can remain effective without being limited to pressure drop.

In the most extreme case the baffles 9 are put in such angular positions that they are parallel to the main flow direction in the vessel, so that the flow is not hindered by the baffles 9. In this case the baffles 9 of each mixing guide 6 are aligned with each other.

The number of mixing guides 6 applied in the vessel 1 depends in first instance on the purpose for which the apparatus is intended to be used. When the apparatus is applied for mixing reactive materials to obtain a compound, the required contact time between the materials determines the length of the vessel. The number of mixing guides 6 in any application is determined by the flow properties of the flowable materials, more mixing guides 6 being required for flows which are made turbulent only with difficulty.

The invention is not restricted to a vessel with a single common inlet as shown in the drawing. Instead, the vessel may be provided with separate inlets for the various materials to be mixed in the vessel.

Instead of mixing guides 6 composed of two baffles 9 as shown in the drawing, the vessel may be equipped with mixing guides composed of only one or more than two baffles. It should, however, be noted that the shown construction of the mixing guides is advantageous over the alternatives, since this construction is rather simple compared to more than two baffles and

yields a better mixing of materials than mixing guides consisting of only one baffle.

In the shown embodiment of the invention the mixing guides are manually rotatable. The rotation of the mixing guides can be readily mechanized or automated. To this end the mixing guides may, for example, be activated by an actuator coupled to a control device which is coupled in its turn to a flow, pressure drop or viscosity measuring device.

The control device chosen for a particular application is designed to move the mixing guides into positions which provide the desired degree of mixing while minimizing pressure drops.

Claims

1. An apparatus for mixing flowable materials comprising a tubular vessel having an inlet for supplying materials to be mixed and an outlet for discharging the said materials after mixing, a plurality of axially spaced apart mixing guides arranged within the vessel between the inlet and the outlet, characterized in that each mixing guide is rotatable about an axis transverse to the tubular vessel and means for changing the angular position of each mixing guide.

2. The apparatus as claimed in claim 1, characterized in that the arrangement is such that the angular positions of the mixing guides can be changed independently of each other.

3. The apparatus as claimed in claim 1, characterized in that the axis of rotation of each mixing guide is substantially perpendicular to the longitudinal axis of the vessel.

4. The apparatus as claimed in any one of the claims 1 to 3, characterized in that the axes of rotation of successive mixing guides are arranged in different planes.

5. The apparatus as claimed in claim 4, characterized in that the axes of rotation of successive mixing guides cross each other at an angle of about 90 degrees.

6. The apparatus as claimed in any one of the claims 1 to 5, characterized in that each mixing guide comprises at least two baffles which have a common axis of rotation.

7. The apparatus as claimed in claim 6, characterized in that a pivot is arranged between the said at least two baffles.

8. The apparatus as claimed in any one of the claims 1 to 7, characterized in that the means for changing the angular position of a mixing guide comprises a shaft connected to the mixing guide and passing through the wall of the vessel, wherein said shaft is provided with rotating means outside the vessel.

9. The apparatus as claimed in claim 8, characterized in that said rotating means is a handle.

10. The apparatus as claimed in claim 8, characterized in that the said rotating means is a non-manual actuator.

11. The apparatus as claimed in claim 10, characterized in that a flow measuring device is



(11)

through the restricted openings between the flat ends of the baffles 9, streams A and B are forced together resulting in a mixing of the components of streams A and B with one another. When passing each further mixing guide 6 the flow is again split and redirected causing a further mixing and redistribution over the cross section of the vessel 1.

In other words the presence of the mixing guides 6, forming obstructions for the flow causes turbulence in the flow, so that the components in the flow are intensively mixed.

When the flow velocity in the vessel is rather low and/or the components of the flow are rather viscous so that the incoming flow tends to remain substantially laminar and can only with some difficulty made turbulent, the baffles 9 of each mixing guide 6 are set nearly perpendicular to the general direction of flow, resulting in a substantial re-direction of flow and the generation of turbulence, thereby achieving the desired mixing at low flow rates.

When the flow velocity in the vessel is rather high and/or the components of the flow are less viscous, so that the incoming material may already be in turbulence, or easily caused to be turbulent, the baffles 9 are not required to contribute to the turbulence. Under this condition the baffles 9 are repositioned in such a manner that they hardly form obstructions to the flow, so that the pressure drop over the vessel 1 due to the mixing guides 6 is kept relatively low. Thus, the mixer can remain effective without being limited to pressure drop.

In the most extreme case the baffles 9 are put in such angular positions that they are parallel to the main flow direction in the vessel, so that the flow is not hindered by the baffles 9. In this case the baffles 9 of each mixing guide 6 are aligned with each other.

The number of mixing guides 6 applied in the vessel 1 depends in first instance on the purpose for which the apparatus is intended to be used. When the apparatus is applied for mixing reactive materials to obtain a compound, the required contact time between the materials determines the length of the vessel. The number of mixing guides 6 in any application is determined by the flow properties of the flowable materials, more mixing guides 6 being required for flows which are made turbulent only with difficulty.

The invention is not restricted to a vessel with a single common inlet as shown in the drawing. Instead, the vessel may be provided with separate inlets for the various materials to be mixed in the vessel.

Instead of mixing guides 6 composed of two baffles 9 as shown in the drawing, the vessel may be equipped with mixing guides composed of only one or more than two baffles. It should, however, be noted that the shown construction of the mixing guides is advantageous over the alternatives, since this construction is rather simple compared to more than two baffles and

yields a better mixing of materials than mixing guides consisting of only one baffle.

In the shown embodiment of the invention the mixing guides are manually rotatable. The rotation of the mixing guides can be readily mechanized or automated. To this end the mixing guides may, for example, be activated by an actuator coupled to a control device which is coupled in its turn to a flow, pressure drop or viscosity measuring device.

The control device chosen for a particular application is designed to move the mixing guides into positions which provide the desired degree of mixing while minimizing pressure drops.

Claims

1. An apparatus for mixing flowable materials comprising a tubular vessel having an inlet for supplying materials to be mixed and an outlet for discharging the said materials after mixing, a plurality of axially spaced apart mixing guides arranged within the vessel between the inlet and the outlet, characterized in that each mixing guide is rotatable about an axis transverse to the tubular vessel and means for changing the angular position of each mixing guide.

2. The apparatus as claimed in claim 1, characterized in that the arrangement is such that the angular positions of the mixing guides can be changed independently of each other.

3. The apparatus as claimed in claim 1, characterized in that the axis of rotation of each mixing guide is substantially perpendicular to the longitudinal axis of the vessel.

4. The apparatus as claimed in any one of the claims 1 to 3, characterized in that the axes of rotation of successive mixing guides are arranged in different planes.

5. The apparatus as claimed in claim 4, characterized in that the axes of rotation of successive mixing guides cross each other at an angle of about 90 degrees.

6. The apparatus as claimed in any one of the claims 1 to 5, characterized in that each mixing guide comprises at least two baffles which have a common axis of rotation.

7. The apparatus as claimed in claim 6, characterized in that a pivot is arranged between the said at least two baffles.

8. The apparatus as claimed in any one of the claims 1 to 7, characterized in that the means for changing the angular position of a mixing guide comprises a shaft connected to the mixing guide and passing through the wall of the vessel, wherein said shaft is provided with rotating means outside the vessel.

9. The apparatus as claimed in claim 8, characterized in that said rotating means is a handle.

10. The apparatus as claimed in claim 8, characterized in that the said rotating means is a non-manual actuator.

11. The apparatus as claimed in claim 10, characterized in that a flow measuring device is



(12)

5

0 095 791

6

coupled via a control device to the actuator.

12. The apparatus as claimed in claim 10, characterized in that a viscosity measuring device is coupled via a control device to the actuator.

13. The apparatus as claimed in claim 10, characterized in that a pressure-measuring device is coupled via a control device to the actuator.

Revendications

1. Appareil destiné à mélanger des matières fluides ou semi-fluides, comprenant un récipient tubulaire qui possède une entrée pour l'introduction des matières à mélanger et une sortie pour le déchargement de ces matières après le mélange, une pluralité de guides de mélange espacés axialement, disposés dans le récipient entre l'entrée et la sortie, caractérisé en ce que chaque guide de mélange peut tourner autour d'un axe transversal au récipient tubulaire et en ce que des moyens sont prévus pour modifier la position angulaire de chaque guide de mélange.

2. Appareil selon la revendication 1, caractérisé en ce que l'arrangement est tel que les positions angulaires des guides de mélange puissent être modifiées indépendamment l'une de l'autre.

3. Appareil selon la revendication 1, caractérisé en ce que l'axe de rotation de chaque guide de mélange est sensiblement perpendiculaire à l'axe longitudinal du récipient.

4. Appareil selon l'une quelconque des revendications 1 à 3, caractérisé en ce que les axes de rotation des guides de mélange successifs sont disposés dans des plans différents.

5. Appareil selon la revendication 4, caractérisé en ce que les axes de rotation des guides de mélange successifs se croisent mutuellement à un angle d'environ 90°.

6. Appareil selon l'une quelconque des revendications 1 à 5, caractérisé en ce que chaque guide de mélange comprend au moins deux chicanes qui ont un axe de rotation commun.

7. Appareil selon la revendication 6, caractérisé en ce qu'un pivot est disposé entre au moins deux desdites chicanes.

8. Appareil selon l'une quelconque des revendications 1 à 7, caractérisé en ce que les moyens servant à modifier la position angulaire d'un guide de mélange comprennent un arbre relié aux guides de mélange et qui passe à travers la paroi du récipient, ledit arbre étant muni de moyens de rotation situés à l'extérieur du récipient.

9. Appareil selon la revendication 8, caractérisé en ce que lesdits moyens de rotation sont une poignée.

10. Appareil selon la revendication 8, caractérisé en ce que lesdits moyens de rotation sont un actionneur manuel.

11. Appareil selon la revendication 10, caractérisé en ce qu'un dispositif de mesure du débit est couplé à l'actionneur par l'intermédiaire d'un dispositif de commande.

12. Appareil selon la revendication 10, caractérisé en ce qu'un dispositif de mesure de la

viscosité est couplé à l'actionneur par l'intermédiaire d'un dispositif de commande.

13. Appareil selon la revendication 10, caractérisé en ce qu'un dispositif de mesure de la pression est couplé à l'actionneur par l'intermédiaire d'un dispositif de commande.

Patentansprüche

1. Vorrichtung zum Mischen fließbaren Materials mit einem einen Einlaß für die Zufuhr des zu mischenden Materials und einen Auslaß für den Abfluß des Materials nach Mischung aufweisenden rohrförmigen Behälter, einer Vielzahl von axial in dem Behälter zwischen Einlaß und Auslaß mit Abstand angeordneten Mischführungen, dadurch gekennzeichnet, daß jede Mischführung um eine transversale Achse zum rohrförmigen Behälter drehbar ist und daß Vorrichtungen vorgesehen sind, um die Winkelposition jeder Mischführung zu verändern.

2. Vorrichtung nach Anspruch 1, dadurch gekennzeichnet, daß bei dieser Anordnung die Winkelpositionen der Mischführungen unabhängig voneinander verändert werden können.

3. Vorrichtung nach Anspruch 1, dadurch gekennzeichnet, daß die Rotationsachse jeder Mischführung im wesentlichen senkrecht zur Längsachse des Behälters ausgerichtet ist.

4. Vorrichtung nach einem der Ansprüche 1 bis 3, dadurch gekennzeichnet, daß die Rotationsachse aufeinanderfolgender Mischführungen in verschiedenen Ebenen angeordnet sind.

5. Vorrichtung nach Anspruch 4, dadurch gekennzeichnet, daß die Rotationsachsen aufeinanderfolgender Mischführungen einander mit einem Winkel von ungefähr 90° kreuzen.

6. Vorrichtung nach einem der Ansprüche 1 bis 5, dadurch gekennzeichnet, daß jede Mischführung zumindest zwei Lenkbleche mit einer gemeinsamen Rotationsachse aufweist.

7. Vorrichtung nach Anspruch 6, dadurch gekennzeichnet, daß ein Drehzapfen zwischen zumindest zwei Lenkblechen angeordnet ist.

8. Vorrichtung nach einem der Ansprüche 1 bis 7, dadurch gekennzeichnet, daß die Vorrichtung für die Veränderung der Winkelposition einer Mischführung eine mit der Mischführung verbundene Achse umfaßt, die durch die Wand des Behälters reicht, und daß die Achse mit einer außerhalb des Behälters angeordneten Rotationsvorrichtung versehen ist.

9. Vorrichtung nach Anspruch 8, dadurch gekennzeichnet, daß die Rotationsvorrichtung ein Griff ist.

10. Vorrichtung nach Anspruch 8, dadurch gekennzeichnet, daß die Rotationsvorrichtung ein nichtmanueller Betätiger ist.

11. Vorrichtung nach Anspruch 10, dadurch gekennzeichnet, daß eine Strömungsmeßvorrichtung über eine Steuervorrichtung mit dem Betätiger gekoppelt ist.

12. Vorrichtung nach Anspruch 10, dadurch gekennzeichnet, daß eine Viskositätsmeßvor-

10

15

20

25

30

35

40

45

50

55

60

65

4

7

0 095 791

8

richtung über eine Steuervorrichtung mit dem
Betätiger gekoppelt ist.
13. Vorrichtung nach Anspruch 10, dadurch ge-

kennzeichnet, daß eine Druckmeßvorrichtung
über eine Steuervorrichtung mit dem Betätiger
gekoppelt ist.

5

10



15

20

25

30

35

40

45

50

55

60

65

5