(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization
International Bureau

(43) International Publication Date
23 December 2004 (23.12.2004)

PCT

(10) International Publication Number
WO 2004/112137 A3

(51) International Patent Classification[7]: H01L 27/146

(21) International Application Number:
PCT/US2004/017714

(22) International Filing Date: 4 June 2004 (04.06.2004)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
10/456,585 9 June 2003 (09.06.2003) US

(71) Applicant: **MICRON TECHNOLOGY, INC.** [US/US]; 8000 S. Federal Way, Boise, ID 83707-0006 (US).

(72) Inventors: **HIATT, William, M.**; 1137 West Stafford Drive, Eagle, ID 83616 (US). **BOETTIGER, Ulrich, C.**; 5109 North Lakemont Lane, Boise, ID 83703 (US). **MCKEE, Jeffrey, A.**; 3891 S. Gideon Place, Meridian, ID 83642 (US).


(74) Agent: **D'AMICO, Thomas, J.**; Dickstein Shapiro Morin & Oshinsky LLP, 2101 L Street NW, Washington, DC 20037-1526 (US).

(81) Designated States *(unless otherwise indicated, for every kind of national protection available)*: AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(84) Designated States *(unless otherwise indicated, for every kind of regional protection available)*: ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI,

[Continued on next page]

(54) Title: IMAGER WITH TUNED COLOR FILTER



(57) Abstract: An optimized color filter array is formed in, above or below a one or more damascene layers. The color filter array includes filter regions which are configured to optimize the combined optical properties of the layers of the device to maximize the intensity of the particular wavelength of light incident to a respective underlying photodiode.

WO 2004/112137 A3

FR, GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

— *with international search report*

— *before the expiration of the time limit for amending the claims and to be republished in the event of receipt of amendments*

(88) Date of publication of the international search report:
14 April 2005

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.