

PCT

WORLD INTELLECTUAL PROPERTY ORGANIZATION
International Bureau

INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁶ : H03D 3/06, H03H 7/18		A1	(11) International Publication Number: WO 97/01218
			(43) International Publication Date: 9 January 1997 (09.01.97)
(21) International Application Number: PCT/IB96/00515		(81) Designated States: CN, JP, SG, European patent (AT, BE, CH, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE).	
(22) International Filing Date: 28 May 1996 (28.05.96)		Published With international search report. Before the expiration of the time limit for amending the claims and to be republished in the event of the receipt of amendments.	
(30) Priority Data: 95201672.3 21 June 1995 (21.06.95) EP (34) Countries for which the regional or international application was filed: NL et al.			
(71) Applicant: PHILIPS ELECTRONICS N.V. [NL/NL]; Groenewoudseweg 1, NL-5621 BA Eindhoven (NL).			
(71) Applicant (for SE only): PHILIPS NORDEN AB [SE/SE]; Kottbygatan 7, Kista, S-164 85 Stockholm (SE).			
(72) Inventor: MOHINDRA, Rishi; Groenewoudseweg 1, NL-5621 BA Eindhoven (NL).			
(74) Agent: MAK, Theodorus, N.; International Octrooibureau B.V., P.O. Box 220, NL-5600 AB Eindhoven (NL).			



REPLACED SHEETS SG

- ☐ Description : paged to paged
☒ Claim(s) : paged to paged
☐ Drawing(s) : paged to paged
☐ Abstract : paged to paged

(54) Title: A DIGITAL RADIO SYSTEM, A DIGITAL RADIO DEVICE, AND A QUADRATURE DEMODULATOR

(57) Abstract

Known is a digital radio system comprising a digital radio device for phase or frequency modulated digital signals with a substantial amplitude roll-off at the relevant operating range. A digital radio device is provided with a quadrature demodulator not having such an amplitude roll-off. This is obtained by a phase shifting network in a quadrature branch of the demodulator having a series arrangement of a resistor and a capacitor coupled to an inductor coupled to ground. A junction between the series arrangement and the inductor forms the output of the quadrature branch. Alternative embodiments are provided. The demodulator avoids asymmetric digital signal distortion which can have deteriorating effects, in particular to GFSK-signals or $\pi/4$ -DQPSK signals, or the like, and further noise shift of data which is of particular importance in low [S/N]-systems such as paging systems.



FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AM	Armenia	GB	United Kingdom	MW	Malawi
AT	Austria	GE	Georgia	MX	Mexico
AU	Australia	GN	Guinea	NE	Niger
BB	Barbados	GR	Greece	NL	Netherlands
BE	Belgium	HU	Hungary	NO	Norway
BF	Burkina Faso	IE	Ireland	NZ	New Zealand
BG	Bulgaria	IT	Italy	PL	Poland
BJ	Benin	JP	Japan	PT	Portugal
BR	Brazil	KE	Kenya	RO	Romania
BY	Belarus	KG	Kyrgyzstan	RU	Russian Federation
CA	Canada	KP	Democratic People's Republic of Korea	SD	Sudan
CF	Central African Republic			SE	Sweden
CG	Congo	KR	Republic of Korea	SG	Singapore
CH	Switzerland	KZ	Kazakhstan	SI	Slovenia
CI	Côte d'Ivoire	LI	Liechtenstein	SK	Slovakia
CM	Cameroon	LK	Sri Lanka	SN	Senegal
CN	China	LR	Liberia	SZ	Swaziland
CS	Czechoslovakia	LT	Lithuania	TD	Chad
CZ	Czech Republic	LU	Luxembourg	TG	Togo
DE	Germany	LV	Latvia	TJ	Tajikistan
DK	Denmark	MC	Monaco	TT	Trinidad and Tobago
EE	Estonia	MD	Republic of Moldova	UA	Ukraine
ES	Spain	MG	Madagascar	UG	Uganda
FI	Finland	ML	Mali	US	United States of America
FR	France	MN	Mongolia	UZ	Uzbekistan
GA	Gabon	MR	Mauritania	VN	Viet Nam