

A method for producing identity cards

The present invention relates to a method for producing identity cards according to the preamble of claim 1. The invention also relates to an identity card.

Identity cards with integrated circuits are used increasingly in the form of credit cards, bank cards, cash cards and the like in a great variety of services sectors, for example in cashless money transfer and in the in-company area. A large number of identity cards are produced by the so-called "mounting technique". In this method a card body with a recess is prepared in which the integrated circuit is incorporated by means of a carrier element and fastened for example by means of an adhesive layer.

DE-A 31 22 981 discloses e.g. a method for producing an identity card with a penny-like carrier element. First a card body comprising a core layer and front and back cover layers is provided. The card body is prepared by the laminating technique and has no recess yet. Between the core layer and the back cover layer there is a separation layer in certain areas that prevents the core layer from bonding with the back cover layer during lamination. The separation layer is utilized to stamp a penny-like plug out of the finished card body and to remove it so as to create a blind hole-shaped recess in the card body. In the recess the penny-like carrier element is connected all over the bottom of the recess by means of an adhesive layer. The dimensions of the recess correspond to the shape and size of the carrier element.

EP-A1 0 493 738 discloses for example a method for producing an identity card with a carrier element. The carrier element has at least one integrated circuit connected electroconductively via connecting elements with coupling elements used for communication of the integrated circuit with external devices. The integrated circuit and the elec-

✓
✓1/6
1/41/2
-

troconductive connecting elements are cast with a casting compound. The carrier element is glued into a specially provided two-step recess in the card body with the aid of a thermally activated adhesive layer. The dimensions of the two-step recess are selected so as to correspond to the shape and size of the carrier element.

The stated publications show that the dimensions of the recess correspond exactly to the shape and size of the particular carrier element to be inserted in the recess, the carrier elements being connected directly with the card bodies by means of an adhesive layer.

Since different recesses must be produced in the card bodies for carrier elements with different integrated circuits varying in size and shape, a tool specially adapted to the shape and size of the carrier element to be used must be provided for producing the card recess. For example a special injection mold is required for producing the recess if the card body is produced by injection molding. Furthermore the stock keeping of card bodies with different recesses is difficult since one cannot foresee whether the shape and size of the integrated circuits to be used will change, resulting in useless remaining stock of card bodies with special recesses. Also, the different recesses in the card bodies make it difficult to change over easily in the production of identity cards with differently shaped carrier elements, since neither the necessary tools for producing the special recesses in the card bodies nor corresponding stock in store are available. Finally high costs can arise for small series of identity cards with a special carrier element, since the recess in the card body must be prepared separately with a special tool.

All this means that the production of a special recess adapted to the dimensions of the carrier element impairs the flexibility in producing identity cards with different carrier elements. Also, the direct connection of the carrier elements with the card body by means of an adhesive layer

has the disadvantage that it results in a relatively rigid compound of the carrier element and card body that leads to high mechanical loads on the integrated circuit and electric link conductors when there is bending stress on the card.

The invention is thus based on the problem of improving the production of identity cards with respect to the incorporation of different carrier elements with integrated circuits in the card bodies.

This problem is solved by the features stated in the independent claims.

The basic idea of the invention is to provide the card bodies of the identity cards with a uniform recess independently of the shape and size of the integrated circuits to be inserted in the identity cards, and to provide flexible adapter elements for receiving the different integrated circuits, the outer dimensions of said adapter elements being adapted to the shape and size of the standardized recess in the card bodies.

For receiving the carrier elements the adapter elements can be provided with openings that correspond in shape and size substantially to the outer dimensions of the particular carrier element being used. The adapter elements formed with uniform outer dimensions can thus also be used for incorporating different carrier elements in the uniform recess in the card bodies.

The advantages obtained with the invention consist particularly in that the production of identity cards with different carrier elements can be designed flexibly by the use of a standardized starting product with a uniform card recess in conjunction with an adapter element. This makes it possible to produce and store prefabricated card bodies with recesses in any desired piece numbers since they can be used independently of the carrier element to be incorporated. Furthermore the providing of card bodies with uniform recesses and the corresponding adapter elements makes it unnecessary to provide special tools, so that the production

cost of the identity cards can ultimately be lowered, in particular for small series. Furthermore the standardized recess in the card bodies can have a simple shape so that it can be prepared economically with low tolerance dependencies in a simple way. The abovementioned advantages are obtained without quality losses during the production of identity cards.

According to a preferred embodiment example of the invention the carrier element is connected with the adapter element to form a module corresponding in shape and size substantially to the dimensions of the standardized recess in the card body. The resulting module comprising carrier element and adapter element is fastened in the recess of the card body with the aid of an adhesive layer. In this embodiment example the adapter element is an integrated part of the electronic module. However it is also possible to glue the adapter element into the standardized recess in the card body first as a separate element, thereby creating a recess in the card body adapted to the shape and size of the particular carrier element to be inserted. The carrier element can then be connected with the adapter element e.g. by an adhesive layer.

The material for the adapter element can be selected independently of the materials used for producing the carrier element, which must meet certain requirements. For the adapter element one preferably selects an elastic or plastically very deformable material, for example soft PVC foam, polyethylene foam or elastomer foam. By using an elastic, very deformable material for the adapter element one relieves the integrated circuit and electroconductive connecting elements from the circuit to the contact surfaces during production of the identity card. Also, the elastic buffer effect of the adapter element relieves the integrated circuit together with the conductor wires when there is bending stress on the card in daily use, thereby ensuring high electric reliability of the identity card. Relief of

the integrated circuit from bending stress with the aid of the adapter element is also possible since the latter is connected with the card body only partly, i.e. in articulated fashion.

Further embodiments and advantages of the invention can be found in the subclaims and in the drawings, in which:

Fig. 1 shows the plan view of an identity card with an electronic module,

Figs. 2 to 4 show various embodiment examples of an identity card each in cross section,

Fig. 5 shows a metal band with a prestamped contact layout,

Fig. 6 shows an electronic module in cross section,

Figs. 7a and 7b show the semifinished product fabrication of electronic modules,

Fig. 8 shows a method for producing identity cards.

Fig. 1 shows identity card 1 with electronic module 3 in a plan view. Electronic module 3 has coupling elements 5 used for communication with external devices.

Fig. 2 shows a greatly enlarged cross section not true to scale along broken line A-A through identity card 1 in Fig. 1. Card body 7 has standardized recess 9 that always has the same shape and size independently of the shape and dimensions of the carrier element to be inserted in the recess. Card body 7 with uniform recess 9 can be prepared by a great variety of techniques, e.g. injection molding, whereby the recess can already be taken into consideration during the injection molding operation by means of a corresponding casting mold, or the recess can be milled into the finished card body later. It is of course also possible to produce the card body by the laminating technique, and to make the recess in the card body by stamping or else milling. The above list does not lay claim to completeness; the expert is familiar with further techniques for producing a card body with a recess.

In standardized recess 9 carrier element 4 is connected with the card body with the aid of adapter element 25. Carrier element 4 shown in Fig. 2 consists e.g. of carrier film 11 made of Kapton having contact surfaces 5 on one side. Carrier film 11 has accordingly positioned windows 15 for receiving integrated circuit 17 and guiding through electroconductive connecting elements 19 from circuit 17 to contact surfaces 5. For protection from mechanical loads the integrated circuit and electroconductive connecting elements are cast with casting compound 21. The carrier element is connected with adapter element 25 e.g. by adhesive layer 22. The adapter element shown in Fig. 2 has e.g. two-step opening 26, whereby shoulder portions 27 of the opening substantially receive carrier film 11 and deeper part 28 of the opening substantially receives casting compound 21. Adhesive layer 22 glues the part of the carrier element free from casting compound to the shoulder portions of the adapter element. The adapter element can in turn be connected with the card body by means of adhesive layer 29 on the bottom of standardized recess 9 in said card body.

In the card shown in Fig. 3, carrier element 4 differs from that shown in Fig. 2 since integrated circuit 17 is clearly larger, so that the extent of casting compound 21 and thus the outer shape and size of carrier element 4 are also different. Despite these differences the carrier element can be inserted in standardized recess 9 of card body 7 with the aid of adapter element 25 adapted to the dimensions of carrier element 4 and provided e.g. with corresponding opening 26 for receiving the carrier element. Opening 26 of the adapter element shown in Fig. 3 is formed in such a way that not only the part of the carrier element which is free from casting compound 21 but also at least part of the casting compound can be connected with the adapter element with the aid of adhesive layer 22. This permits a good bond between the carrier element and the adapter element even when the part of the carrier element free from casting com-

pound constitutes a relatively small surface, as in the example shown. The adapter element can in turn be connected with the bottom of standardized recess 9 in the card body e.g. by means of adhesive layer 29.

Fig. 4 shows very schematically an identity card under bending stress, carrier element 4 being connected with card body 7 in recess 9 in articulated fashion with the aid of adapter element 25. The carrier element is formed by very large chip 4 in this embodiment example. The adapter element is connected all over with the bottom of the recess in the card body. The connection with the card body can be effected e.g. by means of contact adhesive layer 29 located on the adapter element. On the side facing the carrier element the adapter element is connected with the chip only partially, e.g. in the middle area, in order to obtain the articulated connection with the chip. This articulated connection can be realized in the middle area by means of a thermally activated adhesive layer disposed on the adapter element. The connection of adapter element 25 with chip 4 to form a module is preferably effected during the semifinished product fabrication of the module, i.e. before the module is incorporated in the card body. The articulated connection of the chip with the adapter element obtains effective relief of the chip when there are high bending stresses on the card. The embodiment of the adapter element shown here is advantageous in particular with large chips. Due to the buffer effect produced by the adapter element, which consists e.g. of a PET film, no point-shaped deformations can arise on the thin-walled card bottom, e.g. from gluing points.

Fig. 5 shows a plan view of metal band 31 with suitably prestamped contact surfaces 5, as can be used for producing the standardized electronic modules by the lead frame technique. Contact surfaces 5 of the metal band, which has e.g. a thickness of about 50 to 100 microns, are first connected with the metal band via bars 35. The connecting bars are later severed when the individual electronic modules are

stamped out. The metal band can have perforations 37 for clocked transport, like all bands shown in the following.

Fig. 6 shows an electronic module in cross section. Adapter element 25 is provided here e.g. with through opening 26 of constant diameter. The through opening is dimensioned so that there is room for constantly thick casting compound 21 of the carrier element completely within the opening of the adapter element. The form of the casting compound shown here thus permits simple production of the opening of the adapter element. Contact surfaces 5 of electronic module 3 are obtained in this embodiment example e.g. by being suitably stamped out of a metal band, as shown in Fig. 5, by the lead frame technique. Integrated circuit 17 is glued by means of an electroconductive adhesive to a central area of the contact surfaces. This central contact area can be used as a connection to ground. This technique has the advantage that no separate carrier film is needed for receiving the contact surfaces and the integrated circuit, as shown in Figs. 2 and 3. Finally it should be mentioned that the design of the electronic module according to Fig. 6 is selected only by way of example. The electronic module can of course also be constructed differently, but the standardized outer dimensions of the module are maintained to permit simple production of the recess in the card body adapted to the outer dimensions of the module.

Figs. 7a and 7b show schematically an embodiment example for the semifinished product fabrication of electronic modules. Metal band 31, in which the contact layout shown in Fig. 5 is prestamped with a stamping die not shown, is wound off roll 39. In a further processing unit likewise not shown, integrated circuit 17 is applied to a central area of contact surfaces 5 and connected conductively with the contact surfaces by electroconductive connecting elements 19. Parallel to the abovementioned method steps, flexible band 47 fed in the form of endless material, from which adapter elements 25 are prepared, is unwound from roll 43. For pro-

ducing the adapter elements the band can be provided on at least one side 43 with an adhesive layer covered by protective film 45. The flexible band fed in the form of endless material can be provided with openings 26 which are produced by means of a processing unit not shown, for example by stamping, boring or other techniques. Protective film 45 is removed from the flexible band provided with openings and wound onto roll 51. Metal band 31 provided with integrated circuits 17 is brought together with the band provided with openings 26 in such a way that at least integrated circuits 17 and electroconductive connecting elements 19 lie within openings 26. The flexible band is glued to the metal band by means of an adhesive layer located on side 43. Resulting compound 50 can then be brought together and lightly glued on bottom side 52 with lightly adhesive band 53 which is wound off roll 55. Band 53 covers the side of the metal band opposite the integrated circuits in such a way that integrated circuits 17 and electroconductive connecting elements 19 can be cast with casting compound 21 in a processing unit not shown, without the casting compound being able to flow through the interruptions in the contact layout of contact surfaces 5 onto the latter. During casting the walls of openings 26 serve as a limiting frame for the casting compound so as to prevent the casting compound from flowing off laterally. After this method step band 53 can be removed from compound 50 again and wound onto roll 59. Finally compound 50 can be provided on upper side 61 with two-side adhesive strip 63, from one side of which protective film 65 is removed beforehand and wound onto roll 67 so that adhesive strip 63 can be glued to the compound. The other side of the adhesive strip is still provided with a protective film. Compound 50 now finished can be wound onto roll 69 or else immediately processed further.

Fig. 7b shows the further processing of compound 50 to individual electronic modules which are incorporated in the recesses in the card bodies. In first unit 60 the contour of

individual electronic modules 3 is stamped from compound 50. The stamping takes place here in such a way that the connecting bars shown in Fig. 5 and adhesive strip 63 are severed in accordance with the desired contour of the electronic modules but protective film 65 is not severed. Grid 77 remaining after the stamping operation can be wound onto roll 79 so that only individual modules 3 remain on the protective film.

Finally it should be mentioned that, instead of the metal band shown, one can also provide a band already equipped with integrated circuits. As the carrier film for the already wired and cast integrated circuits one can of course also use Kapton. The integrated circuits and the electroconductive connections are preferably surrounded by a casting compound for better protection, but the casting of the integrated circuits and electroconductive connections is not absolutely necessary.

Fig. 8 shows schematically a method for producing identity cards. Flexible band 47 fed in the form of endless material is provided with openings 26 in stamping unit 20 and connected, after removal of upper protective film 45, by means of adhesive layer 22 with carrier elements 4 fed in the form of endless material. In stamping unit 30 the desired module contour is prestamped. This prestamping permits the carrier elements to be stamped out more easily with the adapter elements subsequently in stamping unit 40, whereby the latter are then surrounded only by a stamping grid. Bottom protective film 46 of the flexible band is not stamped at the same time. Stamped-out electronic modules 3 comprising carrier element and adapter element can then be removed from this protective film by means of vacuum gripper 42 and inserted in the card recess. The electronic modules can be removed directly by the vacuum gripper from the stamping grid, thereby e.g. exposing a further adhesive layer of the flexible band by means of which the modules can then be incorporated in the card recess. However it is also

possible first to remove the stamping grid from protective film 46 and wind it onto a roll not shown, and then to remove the electronic modules remaining on protective film 46 at regular intervals and incorporate them in the card recesses.

To enlarge the adhesive surfaces, as shown e.g. in Fig. 3, the adapter element can also be preformed in accordance with the dimensions of the cast integrated circuits in a unit not shown and then provided with a through hole smaller than the cast integrated circuits. This has the advantage that the cast integrated circuit is exposed to no mechanical overstressing during assembly.

Claims

1. A method for producing identity cards which uses card bodies with standardized outer dimensions and wherein carrier elements with different dimensions are incorporated in the card bodies, the carrier elements having at least one integrated circuit connected electroconductively with coupling elements used for communication of the integrated circuit with external devices, characterized in that

adapter elements formed with uniform outer dimensions are provided for receiving the different carrier elements,

for receiving the adapter elements the card bodies are provided with recesses corresponding in shape and size substantially to the outer dimensions of the adapter elements, and

the carrier elements are connected with the card body via the adapter elements.

2. The method of claim 1, characterized in that the adapter elements are first inserted in the recesses in the card bodies and connected at least partly with the card bodies, and the carrier elements are then inserted and connected with the adapter elements.

3. The method of claim 1, characterized in that the carrier elements are first connected with the adapter elements by means of an adhesive layer to form modules, and these modules are then incorporated in the specially provided recesses in the card bodies in such a way that said modules are connected at least partly with the card bodies.

4. The method of claim 3, characterized in that the carrier elements are provided in the form of endless material,

a flexible band is fed in the form of endless material from which the adapter elements are prepared,

the flexible band is provided at regular intervals with openings for receiving the carrier elements,



the band provided with openings is brought together with the carrier elements positioned in such a way that the integrated circuits and electroconductive connections lie completely within the openings of the band,

the carrier elements are glued to the flexible band to form a compound, and

the electronic modules are then stamped out of the compound.

5. The method of claim 4, characterized in that the stamped-out modules are removed with the aid of a vacuum gripper and incorporated in the recesses in the card bodies by means of an adhesive layer.

6. The method of claim 4, characterized in that a metal band is provided as endless material for the carrier elements.

7. The method of claim 6, characterized in that the contact layout intended for the contact surfaces of the electronic modules is prestamped from the metal band, the contact surfaces first remaining connected with the metal band via bars,

the integrated circuits are glued electroconductively to the central areas of the contact surfaces and connected electroconductively with the contact surfaces,

the metal band and the flexible band are glued to form a compound,

the compound is provided with stampings at regular intervals in accordance with the contour of the electronic modules in such a way that the remaining bars of the metal band and the flexible band are severed so as to form individual electronic modules surrounded by a stamping grid.

8. The method of claim 7, characterized in that the compound is provided, before stamping, with a protective film on the contact surface side and the integrated circuits and electroconductive connections are cast with a casting compound, the contact surface side of the modules being covered by the protective film during casting.



9. An identity card (1) having a carrier element (4) which is disposed in a recess (9) in the card body (7) of the identity card and has at least one integrated circuit (17) connected electroconductively via connecting elements (19) with coupling elements (5) which are used for communication of the integrated circuit with external devices, characterized in that the recess (9) in the card body has standardized dimensions in which an adapter element (25) having two main surfaces is disposed, and one of the main surfaces of the adapter element (25) is connected with the bottom of the recess (9) in the card body (7) and the other main surface of the adapter element (25) is connected at least partly with the carrier element (4).

10. The identity card of claim 9, characterized in that the adapter element (25) is connected with the carrier element (4) and the card body (7) by means of adhesive layers (22, 29) disposed on both sides of the adapter element (25).

11. The identity card of claim 10, characterized in that the adhesive layers (22, 29) are contact adhesive or thermally activated adhesive.


12. The identity card of claim 11, characterized in that the adapter element (25) is glued to the carrier element (4) only in the middle area.

13. The identity card of any of claims 9 to 12, characterized in that the integrated circuit (17) and electroconductive connecting elements (19) of the carrier element (4) are surrounded by a casting compound (21) connected at least partly with the adapter element (25).


14. The identity card of any of claims 9 to 13, characterized in that the main surfaces of the adapter element (25) are formed asymmetrically.

15. The identity card of any of claims 9 to 14, characterized in that the adapter element (25) consists of soft PVC foam or polyethylene foam or elastomer foam or a PET film.








1 Fig. 1




7 Fig. 2

This Sheet Has Been Replaced





This Sheet Has Been Replaced






Fig. 5





Fig. 6


This Sheet Has Been Replaced





This Sheet Has Been Replaced





This Sheet Has Been Replaced






Fig. 8



Abstract

A method for producing identity cards which uses card bodies with standardized outer dimensions and wherein carrier elements with different dimensions are incorporated in the card bodies, the carrier elements having at least one integrated circuit connected electroconductively with coupling elements used for communication of the integrated circuit with external devices, characterized in that

adapter elements formed with uniform outer dimensions are provided for receiving the different carrier elements,

for receiving the adapter elements the card bodies are provided with recesses corresponding in shape and size substantially to the outer dimensions of the adapter elements, and

the carrier elements are connected with the card body via the adapter elements.

This Sheet Has Been Replaced







Fig. 1



✓



1/2
1/1

1/2
-

21/8/96



This is the replacement sheet

Date: 21 AUG 1996



This is the replacement sheet

Date: 21 AUG 1996



this is the reference sheet

Date: 21 AUG 1994




Fig. 7a

This is the replacement sheet

Date: 21 AUG 1996




Fig. 7b




Fig. 8

This is the replacement sheet

7-1-1946

1946

Title: A Method For Producing Identity Cards

Abstract

A method for producing identity cards which uses card bodies with standardized outer dimensions and wherein carrier elements with different dimensions are incorporated in the card bodies, the carrier elements having at least one integrated circuit connected electroconductively with coupling elements used for communication of the integrated circuit with external devices, characterized in that

adapter elements formed with uniform outer dimensions are provided for receiving the different carrier elements,

for receiving the adapter elements the card bodies are provided with recesses corresponding in shape and size substantially to the outer dimensions of the adapter elements, and

the carrier elements are connected with the card body via the adapter elements.

Figure 1

This is the replacement sheet.

Date: 21 AUG 1996