

– or to Figure out how to connect or disconnect different parts of the device. Other users may have motor-control issues that make it difficult to actually perform the actions necessary to connect or disconnect different parts of the device.

Furthermore, most users, even those without any cognitive or motor-control issues, dislike it when a physiological monitoring device breaks and needs to be repaired.

[0005] All of these challenges apply particularly to an adhesive patch device comprising a reusable component and a disposable component. The user has to know how to connect the reusable component to the disposable component; the user has to enter environments involving water; the user has to change the device's battery and adhesive; and the user needs a reliable device that does not break.

[0006] A need exists for a durable, reliable, easy to use wearable physiological monitoring device that is safe to use around water and that is easy to maintain and easy to connect and disconnect.

SUMMARY

[0006a] According to an aspect, the present disclosure refers to a wearable physiological monitoring device, comprising: a disposable component comprising: a first electrode; a second electrode; a cradle, comprising: a battery; a first electrical contact and a second electrical contact, both the first and second electrical contacts being electrically coupled to the battery; a third electrical contact electrically coupled to the first electrode; a fourth electrical contact electrically coupled to the second electrode; a battery disconnect switch located between the first electrical contact and the battery, said battery disconnect switch comprising: a first trace electrically coupled to the first electrical contact, said first trace comprising a first free end; a second trace electrically coupled to the battery, said second trace comprising a second free end, wherein the first free end is electrically isolated from the second free end; a button that is spring-loaded comprising a bottom side in proximity to the first trace and to the second trace; and a conductive plate located on the bottom

side of the button, so that in a first configuration, the conductive plate is not in electrical contact with the first free end and the second free end, and in a second configuration when pressure is applied to the button, the conductive plate comes into electrical contact with the first free end and the second free end so as to electrically couple the first free end to the second free end; and a reusable component configured to be secured to the disposable component, the reusable component comprising: an electronics module; and an electrical interface associated with the electronics module and configured to interface with at least one of the first, second, third, and fourth electrical contacts of the disposable component.

[0006b] According to an example, the present disclosure refers to a wearable physiological monitoring device, comprising: a disposable component comprising: a first electrode; a second electrode; a cradle, wherein the cradle comprises: a battery; a first electrical contact and a second electrical contact, both the first and second electrical contacts being electrically coupled to the battery; a third electrical contact electrically coupled to the first electrode; a fourth electrical contact electrically coupled to the second electrode; and a disposable component latching system; and a reusable component configured to be secured to the disposable component, the reusable component comprising: a reusable component latching system configured to operably engage the disposable component latching system; an electronics module; an electrical interface associated with the electronics module, wherein the electrical interface comprises a fifth electrical contact for electrically coupling the electronics module to the first electrical contact, a sixth electrical contact for electrically coupling the electronics module to the second electrical contact, a seventh electrical contact for electrically coupling the electronics module to the third electrical contact, and an eighth electrical contact for electrically coupling the electronics module to the fourth electrical contact; wherein each of the fifth electrical contact, sixth electrical contact, seventh electrical contact, and eighth electrical contact are spring loaded electrical connectors; wherein each one of the first electrical contact, second electrical contact, third electrical contact, and fourth electrical contact comprises a multilayered ink

contact comprising a first ink layer and a second ink layer, further wherein the first ink layer has a higher conductivity than the second ink layer, and the second ink layer is made up of material with a smaller particle size than the first ink layer.

[0006c] According to another example, the present disclosure refers to a method of assembling a device comprising a plastic housing and a printed circuit board assembly (PCBA) located inside the plastic housing, wherein the plastic housing comprises a top half and a bottom half, the method comprising: placing the PCBA on the bottom half of the plastic housing in such a way that the PCBA is not mechanically coupled to the bottom half; placing the top half on the bottom half of the plastic housing in such a way that the PCBA is not mechanically coupled to the top half; and ultrasonically welding the top half to the bottom half.

[0007] In some examples, a device of the present disclosure comprises a disposable component and a reusable component. The disposable component comprises two electrodes intended to make connection with a user's skin, and a cradle comprising a battery and electrical contacts connected to the battery and to the electrodes. The cradle also comprises a latching system for the reusable component to latch onto. The reusable component comprises an electrical interface to the cradle and a reusable component latching system configured to engage the disposable component latching system. In some examples, the cradle also comprises a battery disconnect switch connected between the first electrical contact and the battery, such that the battery disconnect switch disconnects the battery from the first electrical contact when no pressure is applied to the battery disconnect switch, and connects the battery to the first electrical contact when pressure is applied to the battery disconnect switch. In some examples, the reusable

Claims

1. A wearable physiological monitoring device, comprising:
 - a disposable component comprising:
 - a first electrode;
 - a second electrode;
 - a cradle, comprising:
 - a battery;
 - a first electrical contact and a second electrical contact, both the first and second electrical contacts being electrically coupled to the battery;
 - a third electrical contact electrically coupled to the first electrode;
 - a fourth electrical contact electrically coupled to the second electrode;
 - a battery disconnect switch located between the first electrical contact and the battery, said battery disconnect switch comprising:
 - a first trace electrically coupled to the first electrical contact, said first trace comprising a first free end;
 - a second trace electrically coupled to the battery, said second trace comprising a second free end, wherein the first free end is electrically isolated from the second free end;
 - a button that is spring-loaded comprising a bottom side in proximity to the first trace and to the second trace; and
 - a conductive plate located on the bottom side of the button, so that in a first configuration, the conductive plate is not in electrical contact with the first free end and the second free end, and in a second configuration when pressure is applied to the button, the conductive plate comes into electrical contact with the first free end and the second free end so as to electrically couple the first free end to the second free end; and
 - a reusable component configured to be secured to the disposable component, the reusable component comprising:
 - an electronics module; and
 - an electrical interface associated with the electronics module and configured to interface with at least one of the first, second, third, and fourth electrical contacts of the disposable component.
2. The device of claim 1, wherein the reusable component is configured to apply pressure to the button when the reusable component is connected to the disposable component.

3. The device of claim 1, wherein the reusable component comprises a protrusion configured to apply pressure to the button when the reusable component is connected to the disposable component.
4. The device of claim 1, wherein the disposable component further comprises a disposable component latching system; and the reusable component further comprises a reusable component latching system configured to operably engage the disposable component latching system.
5. The device of claim 1, wherein the electrical interface of the reusable component comprises a fifth electrical contact for electrically coupling the electronics module to the first electrical contact, a sixth electrical contact for electrically coupling the electronics module to the second electrical contact, a seventh electrical contact for electrically coupling the electronics module to the third electrical contact, and an eighth electrical contact for electrically coupling the electronics module to the fourth electrical contact.
6. The device of claim 5, further comprising:
 - a gasket, wherein the gasket comprises a first individual enclosure around the fifth electrical contact that does not enclose any other electrical contact, a second individual enclosure around the sixth electrical contact that does not enclose any other electrical contact, a third individual enclosure around the seventh electrical contact that does not enclose any other electrical contact, and a fourth individual enclosure around the eighth electrical contact that does not enclose any other electrical contact, in such a way that water cannot enter or exit any individual enclosures when the reusable component is engaged with the disposable component.
7. The device of claim 6, wherein the gasket comprises a top half attached to the reusable component and a bottom half attached to the disposable component.
8. The device of claim 6, wherein each one of the first, second, third, and fourth individual enclosure is cylindrical in shape.