

METHOD AND SYSTEM OF CONTROLLING A TEMPERATURE WITHIN A MELT TRAY ASSEMBLY OF A DISTILLATION TOWER

CROSS REFERENCE TO RELATED APPLICATIONS

- 5 **[0001]** This application claims the priority benefit of United States Patent Application No. 62/067,342, filed October 22, 2014, entitled METHOD AND SYSTEM OF CONTROLLING A TEMPERATURE WITHIN A MELT TRAY ASSEMBLY OF A DISTILLATION TOWER, the entirety of which is incorporated by reference herein.

BACKGROUND

10 Fields of Disclosure

[0002] The disclosure relates generally to the field of fluid separation. More specifically, the disclosure relates to a method and system of controlling a temperature within a melt tray assembly of a distillation tower.

Description of Related Art

- 15 **[0003]** This section is intended to introduce various aspects of the art, which may be associated with the present disclosure. This discussion is intended to provide a framework to facilitate a better understanding of particular aspects of the present disclosure. Accordingly, it should be understood that this section should be read in this light, and not necessarily as admissions of prior art.

- 20 **[0004]** The production of natural gas hydrocarbons, such as methane and ethane, from a reservoir oftentimes carries with it the incidental production of non-hydrocarbon gases. Such gases include contaminants, such as at least one of carbon dioxide (“CO₂”), hydrogen sulfide (“H₂S”), carbonyl sulfide, carbon disulfide, and various mercaptans. When a stream being produced from a reservoir includes these contaminants mixed with hydrocarbons, the stream
25 is oftentimes referred to as “sour gas.”

[0005] Many natural gas reservoirs have relatively low percentages of hydrocarbons and relatively high percentages of contaminants. Contaminants may act as a diluent and lower the heat content of the produced hydrocarbon stream. Additionally, in the presence of liquid water, some contaminants can become corrosive to carbon steel.

- 30 **[0006]** It is desirable to remove contaminants from a stream containing hydrocarbons to produce sweet and concentrated hydrocarbons. Specifications for pipeline quality natural gas typically call for a maximum of 2 – 4% CO₂ and ¼ grain H₂S per 100 standard cubic feet (scf) (i.e., 4 parts per million volume (ppmv)) or 5 milligrams per Normal meter cubed

(mg/Nm³) H₂S). Specifications for lower temperature processes such as natural gas liquefaction plants or nitrogen rejection units typically require less than 50 parts per million (ppm) CO₂.

5 [0007] The separation of contaminants from hydrocarbons is difficult and consequently significant work has been applied to the development of hydrocarbon/contaminant separation methods. These methods can be placed into three general classes: absorption by solvents (physical, chemical and hybrids), adsorption by solids, and distillation.

10 [0008] Separation by distillation of some gas mixtures can be relatively simple and, as such, is widely used in the natural gas industry. However, distillation of mixtures of natural gas hydrocarbons, primarily methane, and one of the most common contaminants in natural gas, carbon dioxide, can present significant difficulties. Conventional distillation principles and conventional distillation equipment are predicated on the presence of only vapor and liquid phases throughout the distillation tower. The separation of CO₂ from methane by
15 of CO₂ if a pipeline or better quality hydrocarbon product is desired. The required temperatures are cold temperatures typically referred to as cryogenic temperatures.

[0009] Certain cryogenic distillations can overcome the above mentioned difficulties. These cryogenic distillations provide the appropriate mechanism to handle the formation and subsequent melting of solids during the separation of solid-forming contaminants from
20 hydrocarbons. For example, the formation of solid contaminants in equilibrium with vapor-liquid mixtures of hydrocarbons and contaminants at particular conditions of temperature and pressure may take place in a controlled freeze zone section of a distillation tower.

[0010] The controlled freeze zone section typically comprises a melt tray assembly that collects and warms solids that form in the controlled freeze zone section. Liquid in the melt
25 tray assembly helps conduct heat to warm the solids and create a liquid slurry. The melt tray assembly provides adequate heat transfer to melt the solids and facilitate liquid slurry draw-off to a stripper section of the distillation tower.

[0011] Maintaining the liquid in the melt tray assembly at a steady-state conditions is important for overall process stability within the distillation tower. Too high of a temperature
30 can result in decreased separation performance of the contaminants from the stream containing the hydrocarbons in the controlled freeze zone section, which in turn can result in higher contaminant content in the stream flowing through a rectifier section of the distillation tower and/or can lead to solid formation in the rectifier section. Solid formation in the

rectifier section can cause a disruption within the distillation process and prevent adequate removal of the contaminants from the stream. Conversely, too low of a temperature can result in solid formation in the melt tray assembly, which can stop flow of the liquid slurry into the stripper section, thereby disrupting operation within the distillation process.

- 5 Therefore, a melt tray assembly with unsteady temperatures can negatively affect the rate of removal of contaminants from the stream in the controlled freeze zone section, which may detrimentally affect the purity of the recovered hydrocarbons and may increase the operational costs of the distillation process.

[0012] Maintaining the distillation tower in a distillation process in a way such that there
10 is not a sudden change in melt tray assembly duty requirements is important for overall process stability of the distillation tower. A sudden change in melt tray assembly duty requirements may occur when abnormal operation occurs in the distillation process such as, but not limited to, when there is an upset in a reboiler within the distillation process, unexpected solid accumulation within the distillation tower and/or an upset in spray rate
15 within the controlled freeze zone section from a spray assembly. When the sudden change occurs, the distillation tower must be modified to return to normal operation.

[0013] Conventional controlled freeze zone sections comprise a melt tray assembly with a melt tray heat exchange device having a single-phase heat transfer fluid. The melt tray heat exchange device is used to facilitate the warming of the solids, formed by a spray assembly in
20 the controlled freeze zone section, in the melt tray assembly. However, disadvantages can result when using a single-phase heat transfer fluid. For example, the single-phase heat transfer fluid can cause a temperature differential between an inlet and an outlet of the melt tray assembly, which can make it difficult to hold a steady temperature within the melt tray assembly. Further, sudden changes in the melt tray assembly duty requirements can result in
25 rapid changes in the necessary single-phase heat transfer fluid flow rate needed, thereby making it difficult for the desired temperature to be maintained in the melt tray assembly.

[0014] A need exists for improved technology that can better facilitate heat transfer within the melt tray assembly, can maintain steady-state conditions within the melt tray assembly, does not generate a substantial temperature differential within the melt tray
30 assembly, and/or can effectively manage rapidly changing heat duty requirements within the controlled freeze zone section.

SUMMARY

[0015] The present disclosure provides a method and system for controlling a temperature within a melt tray assembly of a distillation tower.

[0016] A method of controlling a temperature within a melt tray assembly of a distillation tower may comprise maintaining a melt tray assembly, within a controlled freeze zone section of a distillation tower that forms a solid and a vapor from a stream that enters the distillation tower, that comprises a melt tray fluid and a melt tray heat exchanging device within the melt tray fluid; providing a phase changing fluid, to the melt tray heat exchanging device, that is configured to be a dual-phase heat transfer fluid; determining a melt tray fluid composition of the melt tray fluid; determining a melt tray fluid temperature of the melt tray fluid; determining if the melt tray fluid temperature is within an expected melt tray fluid temperature range for the melt tray fluid composition, wherein the expected temperature has an expected melt tray fluid temperature range upper limit and an expected melt tray fluid temperature range lower limit; and decreasing the melt tray fluid temperature if the melt tray fluid temperature is greater than the expected melt tray fluid temperature range upper limit, increasing the melt tray fluid temperature if the melt tray fluid temperature is less than the expected melt tray fluid temperature range lower limit, and maintaining the melt tray fluid temperature if the melt tray fluid temperature is within the expected melt tray fluid temperature range.

[0017] A method of producing hydrocarbons from a distillation tower may comprise maintaining a controlled freeze zone section of the distillation tower that forms a solid and a vapor from a stream that enters the distillation tower; maintaining a melt tray assembly, within the controlled freeze zone section, that comprises a melt tray fluid and a melt tray heat exchanging device within the melt tray fluid; providing a phase changing fluid, to the melt tray heat exchanging device, that is configured to be a dual-phase heat transfer fluid; determining a melt tray fluid composition of the melt tray fluid; determining a melt tray fluid temperature of the melt tray fluid; determining if the melt tray fluid temperature is within an expected melt tray fluid temperature range for the melt tray fluid composition, wherein the expected temperature has an expected melt tray fluid temperature range upper limit and an expected melt tray fluid temperature range lower limit; decreasing the melt tray fluid temperature if the melt tray fluid temperature is greater than the expected melt tray fluid temperature range upper limit, increasing the melt tray fluid temperature if the melt tray fluid temperature is less than the expected melt tray fluid temperature range lower limit, maintaining the melt tray fluid temperature if the melt tray fluid temperature is within the

expected melt tray fluid temperature range; and producing hydrocarbon fluids from the distillation tower.

[0018] A system of controlling a temperature within a melt tray assembly of a distillation tower may comprise a distillation tower configured to process a stream, wherein the distillation tower comprises a controlled freeze zone section that separates the stream into solids and vapor, the controlled freeze zone section having a melt tray assembly including a melt tray fluid and a melt tray heat exchanging device within the melt tray fluid, wherein the melt tray heat exchanging device holds a phase changing fluid that is a dual-phase heat transfer fluid; a control system that determines if a melt tray fluid temperature of the melt tray fluid is within an expected melt tray fluid temperature range for a melt tray fluid composition of the melt tray fluid; and a melt tray temperature conditioning system that feeds the phase changing fluid to the melt tray heat exchanging device and is configured to modify a melt tray fluid temperature of the melt tray fluid if the melt tray fluid temperature is outside of the expected melt tray fluid temperature range.

[0019] The foregoing has broadly outlined the features of the present disclosure so that the detailed description that follows may be better understood. Additional features will also be described herein.

BRIEF DESCRIPTION OF THE DRAWINGS

[0020] These and other features, aspects and advantages of the disclosure will become apparent from the following description, appending claims and the accompanying drawings, which are briefly described below.

[0021] Figure 1 is a schematic diagram of a distillation tower with a closed loop refrigeration system.

[0022] Figure 2 is a schematic diagram of a distillation tower with a closed loop refrigeration system.

[0023] Figure 3A is a schematic diagram of a portion of Figure 2.

[0024] Figure 3B is a schematic diagram of a portion of Figure 2.

[0025] Figure 4 is a schematic diagram of a distillation tower with an open loop refrigeration system.

[0026] Figure 5 is a schematic diagram of a distillation tower with an open loop refrigeration system.

[0027] Figure 6A is a schematic diagram of a portion of Figure 5.

[0028] Figure 6B is a schematic diagram of a portion of Figure 5.

[0029] Figure 7 is a top view of a heat exchanging device.

[0030] Figure 8 is a schematic diagram of a method according to the present disclosure.

[0031] It should be noted that the figures are merely examples and no limitations on the scope of the present disclosure are intended thereby. Further, the figures are generally not
5 drawn to scale, but are drafted for purposes of convenience and clarity in illustrating various aspects of the disclosure.

DETAILED DESCRIPTION

[0032] For the purpose of promoting an understanding of the principles of the disclosure, reference will now be made to the features illustrated in the drawings and specific language
10 will be used to describe the same. It will nevertheless be understood that no limitation of the scope of the disclosure is thereby intended. Any alterations and further modifications, and any further applications of the principles of the disclosure as described herein are contemplated as would normally occur to one skilled in the art to which the disclosure relates. It will be apparent to those skilled in the relevant art that some features that are not relevant
15 to the present disclosure may not be shown in the drawings for the sake of clarity.

[0033] At the outset, for ease of reference, certain terms used in this application and their meaning as used in this context are set forth below. To the extent a term used herein is not defined below, it should be given the broadest definition persons in the pertinent art have given that term as reflected in at least one printed publication or issued patent. Further, the
20 present processes are not limited by the usage of the terms shown below, as all equivalents, synonyms, new developments and terms or processes that serve the same or a similar purpose are considered to be within the scope of the present disclosure.

[0034] As used herein, the term “closed loop refrigeration system” refers to a configuration where the overhead stream of a distillation process having a controlled freeze
25 zone section is chilled and partially condensed with an external working fluid. The external working fluid does not physically mix with the overhead stream. The external working fluid cools the overhead stream. The overhead stream is the stream exiting a top of an upper section of the distillation tower. A closed loop melt tray temperature conditioning system in the distillation process is part of a closed loop refrigeration system.

[0035] As used herein, the term “open loop refrigeration system” refers to a configuration where the overhead stream is used to assist in providing cooling. A compressor may be used to assist in providing the cooling. An open loop melt tray temperature conditioning system in the distillation process is part of an open loop refrigeration system.

[0036] As used herein, the term “fluid” refers to gases, liquids, and combinations of gases and liquids.

[0037] As used herein, the term “hydrocarbon fluids” refers to a hydrocarbon or mixtures of hydrocarbons that are gases or liquids. For example, hydrocarbon fluids may include a hydrocarbon or mixtures of hydrocarbons that are gases or liquids at formation conditions, at
5 processing conditions or at standard conditions (15° Celsius (C) and 1 atmosphere (atm) pressure). Hydrocarbon fluids may include, for example, oil, natural gas, coal bed methane, shale oil, pyrolysis oil, pyrolysis gas, a pyrolysis product of coal, and other hydrocarbons that are in a gaseous or liquid state.

10 [0038] The term “mass transfer device” refers to any object that receives fluids to be contacted, and passes those fluids to other objects, such as through gravitational flow.

[0039] As used herein, the term “subsurface” refers to geologic strata occurring below the earth's surface.

[0040] A “reservoir” or “subterranean reservoir” is a subsurface rock or sand formation
15 from which a production fluid or resource can be harvested. The rock formation may include sand, granite, silica, carbonates, clays, and organic matter, such as bitumen, heavy oil (e.g., bitumen), gas, or coal, among others. Reservoirs can vary in thickness from less than one foot (0.3048 meter (m)) to hundreds of feet (hundreds of meters).

[0041] The term “steady-state condition” refers to when the key distillation process
20 operating variables – pressure, temperature, composition and flows – have not fluctuated substantially for some period of time (e.g., hours). The period of time may range from greater than or equal to 15 minutes. The period of time may be any number within or bounded by the preceding range. When not at steady-state conditions, the distillation process may be at a transient state on its way to normal operation. Normal operation is when a melt
25 tray fluid is at steady-state conditions. Abnormal operation is when the melt tray fluid is not at steady-state conditions.

[0042] The terms “substantial,” “approximate” and “about” when used in reference to a quantity or amount of a material, or a specific characteristic thereof, refer to an amount that is sufficient to provide an effect that the material or characteristic was intended to provide. The
30 exact degree of deviation allowable may in some cases depend on the specific context.

[0043] As referenced in this application, the terms “stream,” “gas stream,” “vapor stream,” and “liquid stream” refer to different stages of a feed stream as the feed stream is processed in a distillation tower that separates methane, the primary hydrocarbon in natural

gas, from contaminants. Although the phrases “gas stream,” “vapor stream,” and “liquid stream,” refer to situations where a gas, vapor, and liquid is mainly present in the stream, respectively, there may be other phases also present within the stream. For example, a gas may also be present in a “liquid stream.” In some instances, the terms “gas stream” and
5 “vapor stream” may be used interchangeably.

[0044] A “temperature differential” is a change in temperature from an inlet to an outlet of the fluid that exchanges heat with the melt tray fluid.

[0045] A “temperature glide” is a refrigerant property. The temperature glide for a refrigerant is the change in temperature from a first droplet of condensation to the last bubble
10 of vapor collapsing. For a pure refrigerant or an azeotrope, the temperature glide is zero, for a near-azeotrope the temperature glide is a small number that is close to zero and for a typical mixed-refrigerant the temperature glide is a large number. The small number may be any temperature that is less than 10° (degrees) F (Fahrenheit) or -12.2° (degrees) C (Celcius). The small number may be any number within the previous range. The large number may be any
15 temperature that is greater than or equal to 10° Fahrenheit (-12.2° Celcius). The large number may be any number within or bounded by the previous range. As it pertains to a distillation tower, the temperature glide is the temperature change between when the refrigerant enters and exits the distillation tower.

[0046] A “flow controlling device” refers to any suitable device that can control pressure and
20 flow. A flow controlling device being “open” refers to the flow controlling device being anywhere from partially open to completely open.

[0047] The articles “the”, “a” and “an” are not necessarily limited to mean only one, but rather are inclusive and open ended so as to include, optionally, multiple such elements.

[0048] “At least one,” in reference to a list of one or more entities should be understood
25 to mean at least one entity selected from any one or more of the entity in the list of entities, but not necessarily including at least one of each and every entity specifically listed within the list of entities and not excluding any combinations of entities in the list of entities. This definition also allows that entities may optionally be present other than the entities specifically identified within the list of entities to which the phrase “at least one” refers,
30 whether related or unrelated to those entities specifically identified. Thus, as a non-limiting example, “at least one of A and B” (or, equivalently, “at least one of A or B,” or, equivalently “at least one of A and/or B”) may refer, to at least one, optionally including more than one, A, with no B present (and optionally including entities other than B); to at least one, optionally including more than one, B, with no A present (and optionally including entities

other than A); to at least one, optionally including more than one, A, and at least one, optionally including more than one, B (and optionally including other entities). In other words, the phrases “at least one,” “one or more,” and “and/or” are open-ended expressions that are both conjunctive and disjunctive in operation. For example, each of the expressions
5 “at least one of A, B and C,” “at least one of A, B, or C,” “one or more of A, B, and C,” “one or more of A, B, or C” and “A, B, and/or C” may mean A alone, B alone, C alone, A and B together, A and C together, B and C together, A, B and C together, and optionally any of the above in combination with at least one other entity.

[0049] The disclosure relates to a system and method for controlling a temperature within
10 a melt tray assembly of a distillation tower and a method of producing hydrocarbons. Figures 1-8 of the disclosure display various aspects of the system and method.

[0050] The system and method may separate a feed stream, having hydrocarbons (e.g., methane) and contaminants, in a distillation tower. Referring to Figures 1-2 and 4-5, the system may comprise the distillation tower **104, 204** which may separate contaminant(s) from
15 the methane.

[0051] The distillation tower **104, 204** may be separated into three functional sections: a lower section **106**, a middle controlled freeze zone section **108** and an upper section **110**. The distillation tower **104, 204** may incorporate three functional sections when the upper section **110** is needed and/or desired.

[0052] The distillation tower **104, 204** may incorporate only two functional sections when
20 the upper section **110** is not needed and/or desired. When the distillation tower does not include an upper section **110**, a portion of vapor leaving the middle controlled freeze zone section **108** may be condensed in a condenser/evaporator **122** and returned as a liquid stream via a spray assembly **129**. Moreover, lines **18** and **20** may be eliminated, elements **124** and
25 **126** may be one and the same, and elements **150** and **128** may be one and the same. The stream in line **14**, now taking the vapors leaving the middle controlled freeze section **108**, may direct these vapors to the condenser/evaporator **122**.

[0053] The lower section **106** may interchangeably be referred to as a stripper section. The middle controlled freeze zone section **108** may interchangeably be referred to as a
30 controlled freeze zone section. The upper section **110** may interchangeably be referred to as a rectifier section.

[0054] The sections **106, 108, 110** of the distillation tower **104** may be housed within a single vessel (Figures 1 and 4). For example, the lower section **106**, the middle controlled

freeze zone section **108**, and the upper section **110** may be housed within a single vessel **164**.

[0055] The sections of the distillation tower **204** may be housed within a plurality of vessels **254**, **264** to form a split-tower configuration (Figures 2 and 5). Each of the vessels may be separate from the other vessels. Piping **41**, **341** and/or another suitable mechanism
5 **342** may connect one vessel to another vessel. In this instance, the lower section **106**, middle controlled freeze zone section **108** and upper section **110** may be housed within two or more vessels. For example, as shown in Figures 2 and 5, the upper section **110** may be housed within a single vessel **254** and the lower and middle controlled freeze zone sections **106**, **108** may be housed within a single vessel **264**. When this is the case, a liquid stream exiting the
10 upper section **110** to the middle controlled freeze zone section **108**, may exit the upper section **110** via a liquid outlet bottom **260**. The liquid outlet bottom **260** is at the bottom of the upper section **110**. Although not shown, each of the sections may be housed within its own separate vessel, or one or more section may be housed within separate vessels, or the upper and middle controlled freeze zone sections may be housed within a single vessel and
15 the lower section may be housed within a single vessel, etc. When sections of the distillation tower are housed within vessels, the vessels may be side-by-side along a horizontal line and/or above each other along a vertical line. The split tower configuration may utilize a sump **331** of the upper section as a liquid receiver for the pump **128**, therefore obviating the need for the holding vessel **126** in Figures 1 and 4. Further, in the split tower configuration,
20 fluid may exit the middle controlled freeze zone section **108** through piping **343**.

[0056] The system may include a heat exchanger **100** (Figures 1-2 and 4-5). The feed stream **10** may enter the heat exchanger **100** before entering the distillation tower **104**, **204**. The feed stream **10** may be cooled within the heat exchanger **100**. The heat exchanger **100** helps drop the temperature of the feed stream **10** to a level suitable for introduction into the
25 distillation tower **104**, **204**.

[0057] The system may include an expander device **102** (Figures 1-2 and 4-5). The feed stream **10** may enter the expander device **102** before entering the distillation tower **104**, **204**. The feed stream **10** may be expanded in the expander device **102** after exiting the heat exchanger **100**. The expander device **102** can help drop the temperature and pressure of the
30 feed stream **10** to a level suitable for introduction into the distillation tower **104**, **204**. The expander device **102** may be any suitable device, such as a valve. If the expander device **102** is a valve, the valve may be any suitable valve that may aid in cooling the feed stream **10** before it enters the distillation tower **104**, **204**. For example, the valve **102** may comprise a

Joule-Thomson (J-T) valve.

[0058] The system may include a feed separator (not shown). The feed stream may enter the feed separator before entering the distillation tower **104, 204**. The feed separator may separate a feed stream having liquid and vapor into a liquid stream and a vapor stream. Lines **12** may extend from the feed separator to the distillation tower **104, 204**. One of the lines **12** may receive the vapor stream from the feed separator. Another one of the lines **12** may receive the liquid stream from the feed separator. Each of the lines **12** may extend to the same and/or different sections (i.e. middle controlled freeze zone, and lower sections) of the distillation tower **104, 204**. The expander device **102** may or may not be downstream of the feed separator. The expander device **102** may comprise a plurality of expander devices **102** such that each line **12** has an expander device **102**. If the system includes the feed separator, the line **12** may comprise a plurality of lines **12**. Each line may be the same line as one of the lines that extends from the feed separator to a specific portion of the distillation tower **104, 204**.

[0059] The system may include a dehydration unit **261** (Figures 1-2 and 4-5). The feed stream **10** may enter the dehydration unit **261** before entering the distillation tower **104, 204**. The feed stream **10** enters the dehydration unit **261** before entering the heat exchanger **100** and/or the expander device **102**. The dehydration unit **261** removes water from the feed stream **10** to prevent water from later presenting a problem in the heat exchanger **100**, expander device **102**, feed separator, or distillation tower **104, 204**. The water can present a problem by forming a separate water phase (i.e., ice and/or hydrate) that plugs lines, equipment or otherwise negatively affects the distillation process. The dehydration unit **261** dehydrates the feed stream to a dew point sufficiently low to ensure a separate water phase will not form at any point downstream during the rest of the process. The dehydration unit may be any suitable dehydration mechanism, such as a molecular sieve or a glycol dehydration unit.

[0060] The system may include a filtering unit (not shown). The feed stream **10** may enter the filtering unit before entering the distillation tower **104, 204**. The filtering unit may remove undesirable solid and/or liquid phase contaminants from the feed stream before the feed stream enters the distillation tower **104, 204**. Depending on what contaminants are to be removed, the filtering unit may be before or after the dehydration unit **261** and/or before or after the heat exchanger **100**.

[0061] The system may include line **12** (Figures 1-2 and 4-5). The line may

interchangeably be referred to as an inlet channel **12**. The feed stream **10** may be introduced into the distillation tower **104, 204** through the line **12**. The line **12** may extend to the lower section **106** or the middle controlled freeze zone section **108** of the distillation tower **104, 204**. For example, the line **12** may extend to the lower section **106** such that the feed stream **10** may enter the lower section **106** of the distillation tower **104, 204**. The line **12** may directly or indirectly extend to the lower section **106** or the middle controlled freeze zone section **108**. The line **12** may extend to an outer surface of the distillation tower **104, 204** before entering the distillation tower **104, 204**.

[0062] The lower section **106** is constructed and arranged to separate the feed stream **10** into a liquid stream and a vapor stream. The lower section **106** separates the feed stream at a temperature and pressure at which no solids form. The liquid stream may comprise a greater quantity of contaminants than methane. The vapor stream may comprise a greater quantity of methane than contaminants. In any case, the vapor stream is lighter than the liquid stream. As a result, the vapor stream rises from the lower section **106** and the liquid stream falls to the bottom of the lower section **106**.

[0063] The lower section **106** may include and/or connect to equipment that separates the stream. The equipment may comprise any suitable equipment for separating methane from contaminants. Generally speaking, the suitable equipment comprises some type of mass transfer device. For example, the suitable equipment may comprise one or more packed sections **181**, or one or more distillation trays with perforations, downcomers, and weirs (Figures 1-2 and 4-5).

[0064] The suitable equipment may include components that apply heat to the stream to form the vapor stream and the liquid stream. For example, the equipment may comprise a first reboiler **112** that applies heat to the stream. The first reboiler **112** may be located outside of the distillation tower **104, 204**. The equipment may also comprise a second reboiler **172** that applies heat to the stream. The second reboiler **172** may be located outside of the distillation tower **104, 204**. Line **117** may lead from the distillation tower **104, 204** to the second reboiler **172**. Line **17** may lead from the second reboiler **172** to the distillation tower **104, 204**. Additional reboilers, set up similarly to the second reboiler described above, may also be used.

[0065] The first reboiler **112** may apply heat to the liquid stream that exits the lower section **106** via a liquid outlet **160** of the lower section **106**. The liquid stream may travel from the liquid outlet **160** through line **28** to reach the first reboiler **112** (Figures 1-2 and 4-5).

The amount of heat applied to the liquid stream by the first reboiler **112** can be increased to separate more methane from contaminants. The more heat applied by the reboiler **112** to the stream, the more methane separated from the liquid contaminants, though more contaminants will also be vaporized.

5 **[0066]** The first reboiler **112** may also apply heat to the stream within the distillation tower **104, 204**. Specifically, the heat applied by the first reboiler **112** warms up the lower section **106**. This heat travels up the lower section **106** and supplies heat to warm solids entering a melt tray assembly **139** (Figures 1-2 and 4-5) of the middle controlled freeze zone section **108** so that the solids form a liquid slurry.

10 **[0067]** The second reboiler **172** applies heat to the stream within the lower section **106**. This heat is applied closer to the middle controlled freeze zone section **108** than the heat applied by the first reboiler **112**. As a result, the heat applied by the second reboiler **172** reaches the middle controlled freeze zone section **108** faster than the heat applied by the first reboiler **112**. The second reboiler **172** may be configured to help with energy integration.

15 **[0068]** The suitable equipment may include one or more chimney assemblies **135** (Figures 1-2 and 4-5). While falling to the bottom of the lower section **106**, the liquid stream may encounter one or more of the chimney assemblies **135**.

[0069] Each chimney assembly **135** includes a chimney tray **131** that collects the liquid stream within the lower section **106**. The liquid stream that collects in the chimney tray **131**
20 may be fed to the second reboiler **172**. After the liquid stream is heated in the second reboiler **172**, the stream may return to the middle controlled freeze zone section **108** to supply heat to the middle controlled freeze zone section **108** and/or the melt tray assembly **139**. Unvaporized stream exiting the second reboiler **172** may be fed back to the distillation tower **104, 204** below the chimney tray **131**. Vapor stream exiting the second reboiler **172** may be
25 routed under or above the chimney tray **131** when the vapor stream enters the distillation tower **104, 204**.

[0070] The chimney tray **131** may include one or more chimneys **137**. The chimney **137** serves as a channel that the vapor stream in the lower section **106** traverses. The vapor stream travels through an opening in the chimney tray **131** at the bottom of the chimney **137**
30 to the top of the chimney **137**. The opening in the chimney tray **131** is closer to the bottom of the lower section **106** than it is to the bottom of the middle controlled freeze zone section **108**. The top of the chimney **137** is closer to the bottom of the middle controlled freeze zone section **108** than it is to the bottom of the lower section **106**.

[0071] Each chimney 137 has attached to it a chimney cap 133. The chimney cap 133 covers a chimney top opening 138 of the chimney 137. The chimney cap 133 prevents a liquid stream from entering the chimney 137. The vapor stream exits the chimney assembly 135 via the chimney top opening 138.

5 [0072] After falling to the bottom of the lower section 106, the liquid stream may exit the distillation tower 104, 204 through the liquid outlet 160. The liquid outlet 160 is within the lower section 106 (Figures 1-2 and 4-5). The liquid outlet 160 may be located at the bottom of the lower section 106.

10 [0073] After exiting through the liquid outlet 160, the feed stream may travel via line 28 to the first reboiler 112. The feed stream may be heated by the first reboiler 112 and vapor may then re-enter the lower section 106 through line 30. Unvaporized liquid may continue out of the distillation tower 104, 204 via line 24.

[0074] The system may include an expander device 114 (Figures 1-2 and 4-5). After entering line 24, the liquid stream may be expanded in the expander device 114. The
15 expander device 114 may be any suitable device, such as a valve. The valve 114 be any suitable valve, such as a J-T valve.

[0075] The system may include a heat exchanger 116 (Figures 1-2 and 4-5). The liquid stream heated by the first reboiler 112 may be cooled or heated by the heat exchanger 116. After exiting the expander device 114, the liquid stream may enter the heat exchanger 116.
20 The heat exchanger 116 may be a direct heat exchanger or an indirect heat exchanger. The heat exchanger 116 may comprise any suitable heat exchanger. The liquid stream may then exit the heat exchanger through line 26.

[0076] The vapor stream in the lower section 106 rises from the lower section 106 to the middle controlled freeze zone section 108. The middle controlled freeze zone section 108
25 may be constructed and arranged to separate the feed stream 10 introduced into the middle controlled freeze zone section into the solids and the vapor stream (not shown). The middle controlled freeze zone section 108 may receive a liquid stream to form solids, liquids and/or a vapor stream in the middle controlled freeze zone section 108. The solids, liquids and/or vapor stream are formed in the middle controlled freeze zone section 108 when the liquid
30 stream is injected into the middle controlled freeze zone section 108 at a temperature and pressure at which the solids, liquids and/or vapor stream form from the liquid stream sprayed into the middle controlled freeze zone section 108. The solids may comprise carbon dioxide. The carbon dioxide solids may trap more contaminants than they trap methane. The vapor

stream may comprise more methane than contaminants. The vapor stream may rise in the middle controlled freeze zone section **108**.

[0077] The vapor stream that rises in the middle controlled freeze zone section **108** and does not form solids or otherwise fall to the bottom of the middle controlled freeze zone section **108**, rises to the upper section **110**. The upper section **110** operates at a temperature and pressure and contaminant concentration at which no solids form at normal operation. At abnormal operation, the heat exchanging device **134** may assist the upper section **110** in operating at a temperature and a pressure and contaminant concentration at which no solids form. The upper section **110** is constructed and arranged to cool the vapor stream to separate the methane from the contaminants. Reflux in the upper section **110** cools the vapor stream and absorbs contaminants. The reflux is introduced into the upper section **110** via line **18**. Line **18** may extend to the upper section **110**. Line **18** may extend from an outer surface of the distillation tower **104, 204**.

[0078] After contacting the reflux in the upper section **110**, the stream may form a vapor stream and a liquid stream. The vapor stream mainly comprises methane. The liquid stream comprises relatively more contaminants. The vapor stream rises in the upper section **110** and the liquid falls to a bottom of the upper section **110**.

[0079] To facilitate separation of the methane from the contaminants when the stream contacts the reflux, the upper section **110** may include one or more mass transfer devices **176**. Each mass transfer device **176** helps separate the methane from the contaminants. Each mass transfer device **176** may comprise any suitable separation device, such as a tray with perforations, or a section of random or structured packing **176** to facilitate contact of the vapor and liquid phases within the stream.

[0080] The system may include a reflux accumulator **124** (Figures 1-2 and 4-5). The reflux accumulator **124** may be any suitable reflux accumulator that can separate a stream into a liquid stream and a vapor stream, such as a reflux drum. The reflux accumulator may serve as a holding unit for the cooled stream entering the reflux accumulator **124**. The reflux accumulator **124** may hold liquid and/or vapor. The liquid within the reflux accumulator **124** may be referred to as reflux. The liquid reflux may comprise methane. The liquid reflux may also comprise contaminants. The contaminants may comprise at least one of carbon dioxide and hydrogen sulfide.

[0081] The liquid reflux may exit the reflux accumulator **124** via line **571** and be fed to the upper section **110** via line **18** (Figures 1-2 and 4-5). The liquid reflux may travel to the

upper section **110** via any suitable mechanism, such as a reflux pump **150** (Figures 1-2 and 4-5) or gravity. Before the liquid of the reflux is fed to the upper section **110**, the liquid may pass through flow controlling device **471**. Flow controlling device **471** may help to control the amount of liquid that travels from the reflux accumulator **124** to the upper section **110**.

5 [0082] As shown in Figures 4-5, a stream may be fed to the reflux accumulator **124** via line **491**. The stream fed to the reflux accumulator **124** via line **491** may be a two phase stream. For example, the stream may comprise a vapor and a liquid. The stream may be fed to the reflux accumulator **124** after exiting a heat exchanging device **245**. After exiting the heat exchanging device **245**, the stream may enter a pressure controlling/reducing device **258**
10 so as to decrease the pressure and temperature of the stream before being sent to the reflux accumulator **124**. The pressure controlling/reducing device **258** may be any suitable device such as but not limited to a valve or an expander. Once in the reflux accumulator **124**, any vapor within the stream may exit the reflux accumulator **124** via line **492**. The vapor **492** exiting the reflux accumulator **124** may be fed to the heat exchanging device **245**. As shown
15 in Figures 4 and 5, stream **492** may be mixed with stream **14** or may be fed into heat exchanger **245** as a separate stream before being fed into the downstream pressure increasing device **1260**.

[0083] The middle controlled freeze zone section **108** includes a lower section **40** and an upper section **39** (Figures 1-2 and 4-5). The lower section **40** is below the upper section **39**.
20 The lower section **40** directly abuts the upper section **39**. The lower section **40** is primarily but may not exclusively be a heating section of the middle controlled freeze zone section **108**. The upper section **39** is primarily a cooling section of the middle controlled freeze zone section **108**.

[0084] The middle controlled freeze zone section **108** may comprise a melt tray assembly
25 **139** that is maintained in the middle controlled freeze zone section **108**, **501** (Figure 8). The melt tray assembly **139** is within the lower section **40** of the middle controlled freeze zone section **108**. The melt tray assembly **139** is not within the upper section **39** of the middle controlled freeze zone section **108**.

[0085] The melt tray assembly **139** is constructed and arranged to melt solids formed in
30 the middle controlled freeze zone section **108**. When the vapor stream rises from the lower section **106** to the middle controlled freeze zone section **108**, the vapor stream immediately encounters the melt tray assembly **139** and is cooled.

[0086] The melt tray assembly **139** may comprise a melt tray **118** and a melt tray heat

exchanging device **134**. The melt tray assembly may also comprise at least one of a melt tray fluid **130** and a bubble cap **132**.

[0087] The melt tray **118** may collect a liquid slurry. The melt tray **118** divides at least a portion of the middle controlled freeze zone section **108** from the lower section **106**. The melt tray **118** is at the bottom **40** of the middle controlled freeze zone section **108** (Figures 1-2 and 4-5).

[0088] The melt tray heat exchanging device **134** may heat up the melt tray fluid **130** to facilitate melting of the solids into the liquid slurry. The melt tray heat exchanging device **134** may cool down the melt tray fluid **130** to reduce a contaminant concentration entering the upper section **110**. The melt tray heat exchanging device(s) **134** may be located anywhere within the melt tray assembly **139**. For example, as shown in Figures 1-2 and 4-5, a melt tray heat exchanging device **134** may be located around the bubble caps **132**.

[0089] The melt tray heat exchanging device **134** holds a phase changing fluid. The phase changing fluid is a dual-phase heat transfer fluid. The dual-phase heat transfer fluid may be any fluid having a characteristic that comprises at least one of a substantially low reactivity, non-toxicity, a substantially low viscosity, a substantially low de-sublimation temperature or melting point, a substantially low flammability, a substantially low greenhouse warming potential (GHWP), a substantially low odor, a substantially high latent heat of vaporization and a substantially low temperature glide. Substantially low reactivity may mean that the phase changing fluid does not substantially react with air or does not react with air. A substantially low viscosity may be equal to less than a few centipoise at the lowest operating temperature. A substantially low sublimation temperature may be equal to a substantially low sublimation temperature or melting point, such that dual-phase heat transfer fluid does not freeze during abnormal operation or normal operation. A substantially low flammability may be equal to a flammability rating of no more than 0-4 on the Hazardous Materials Identification System point scale. A substantially low GHWP may be equal to being less than 100 times that of carbon dioxide. The GHWP of carbon dioxide is 1. A substantially low odor may refer to an odor that is tolerable at a few percent concentration. Examples of non-substantially low odor include, but are not limited to, ammonia and sulfur dioxide. A substantially high latent heat of vaporization may be equal to at least 100 BTU/lb. (British thermal unit per pound).

[0090] The dual-phase heat transfer fluid may have a critical temperature of greater than -50 °F (-45.6°C), a normal boiling point of less than -100 °F (-73.3°C), and a melting point of less than the boiling

point. The aforementioned ranges include any number within or bounded by the preceding examples, respectively. Examples of suitable dual-phase heat transfer fluids comprise, but are not limited to, one of a single-component fluid and an azeotropic blend. Examples of single component fluids include, but are not limited to, propane, carbon dioxide, ammonia, a
5 single halogenated hydrocarbon, ethane, ethylene and trifluoromethane. Examples of azeotropic blends include, but are not limited to, an azeotrope of carbon dioxide and ethane and a combination of components with a temperature glide that allows the intended purpose of the present disclosure to work. With respect to the combination of components with the temperature glide, the temperature glide may be less than or equal to 10 °C or 18 °F. The
10 temperature glide may be any number within and/or bounded by the preceding temperature range. The ethane may be used as an azeotrope with carbon dioxide.

[0091] The melt tray heat exchanging device **134** may receive the phase changing fluid from a working fluid reservoir **194, 294**. The working fluid reservoir **194, 294** holds the phase changing fluid. When the melt tray heat exchanging device **134** receives the phase
15 changing fluid from the working fluid reservoir **194, 294**, the phase changing fluid may comprise a portion of the working fluid. The working fluid reservoir **194, 294** provides the phase changing fluid to the melt tray heat exchanging device **134, 502** (Figure 8). The working fluid reservoir **194, 294** provides the phase changing fluid during normal operation and during abnormal operation.

[0092] At normal operation, the melt tray heat exchanging device **134** receives working fluid vapor from the working fluid reservoir **194, 294** via line **316** (Figures 1-6). The working fluid vapor condenses in the melt tray heat exchanging device **134** to form working fluid liquid, thereby warming the melt tray fluid **130**. The temperature of the working fluid vapor as it condenses may remain constant and the pressure of the working fluid vapor may
20 be held steady. Condensation may occur at a constant temperature if the pressure of the working fluid is held constant if the fluid is an azeotrope or a pure component. For a pure component (e.g., propane), vapor may condense at about or at -44 °F (-42.2°C) as long as the pressure is held constant at about or at 1 atmosphere (atm.). There may be enough inventory in the distillation system that the pressure may remain constant. The working fluid liquid
25 returns to the working fluid reservoir **194** via line **317** (Figures 1-6).

[0093] The system may include a melt tray temperature conditioning system **330, 430**. The melt tray temperature conditioning system **330, 430** may be configured to modify the melt tray fluid temperature of the melt tray fluid **130**. The melt tray temperature conditioning

system **330, 430** may be configured to modify the melt tray fluid temperature of the melt tray fluid **130** if the melt tray fluid temperature is outside of an expected melt tray fluid temperature range. The melt tray temperature conditioning system **330, 430** may feed the phase changing fluid to the melt tray heat exchanging device **134** to modify the melt tray fluid temperature of the melt tray fluid **130**. The melt tray temperature conditioning system **330, 430** may comprise one of a closed loop melt tray temperature conditioning system **330** (Figures 1-3) and an open loop melt tray temperature conditioning system **430** (Figures 4-6).

[0094] The expected melt tray fluid temperature range is a range of temperatures from an expected melt tray fluid temperature that are indicative of normal operation. The expected melt tray fluid temperature range has an expected melt tray fluid temperature range upper limit and an expected melt tray fluid temperature range lower limit. The expected melt tray fluid temperature range may be any suitable temperature range. For example, the expected melt tray fluid temperature range may be between -65 °F (-53.9°C) and -100 °F (-73.3°C). The aforementioned range may include any number bounded or included within the range. The expected melt tray fluid temperature is the temperature of the melt tray fluid **130** at normal operation.

[0095] If the melt tray fluid temperature of the melt tray fluid **130** is greater than the expected melt tray fluid temperature range upper limit, the distillation tower **104, 204** is at an abnormal operation and the melt tray fluid **130** is too warm. If the melt tray fluid temperature of the melt tray fluid **130** is less than the expected melt tray fluid temperature range lower limit, the distillation tower **104, 204** is at an abnormal operation and the melt tray fluid **130** is too cold.

[0096] The closed loop melt tray temperature conditioning system **330** (Figures 1-3) may comprise a working fluid reservoir **194**. The working fluid reservoir **194** holds the working fluid that is fed to the melt tray heat exchanging device **134**. Working fluid is fed to the melt tray heat exchanging device **134** via lines **316, 317**. The working fluid reservoir **194** may receive fluid from the melt tray heat exchanging device **134** via lines **316, 317**. The melt tray heat exchanging device **134** may receive fluid from the working fluid reservoir **194**.

[0097] The working fluid in the working fluid reservoir **194** may comprise any suitable working fluid. For example, the working fluid may comprise one of propane, carbon dioxide, ethane, ammonia, ethylene, an azeotrope of carbon dioxide and ethane, a single halogenated hydrocarbon and a combination of components with a temperature glide that allows the intended purpose of the present disclosure to work. With respect to the combination of components with the temperature glide, the temperature glide may be less than or equal to

10 °C or 18 °F. The temperature glide may be any number within and/or bounded by the preceding temperature range. The ethane may be used as an azeotrope with carbon dioxide.

[0098] The closed loop melt tray temperature conditioning system **330** may include the overhead refrigeration refrigerant accumulator **193**. The overhead refrigeration refrigerant accumulator **193** holds refrigerant. The refrigerant comprises working fluid. In the closed loop melt tray temperature conditioning system **330**, the refrigerant is the working fluid and therefore the refrigerant may interchangeably be referred to as working fluid.

[0099] The overhead refrigeration refrigerant accumulator is configured to selectively feed the refrigerant to the working fluid reservoir **194**. The overhead refrigeration refrigerant accumulator **193** connects to the working fluid reservoir **194** via line **296**. The overhead refrigeration refrigerant accumulator **193** is able to selectively feed the refrigerant to the working fluid reservoir **194** because the line **296** may include a flow controlling device **196**. The flow controlling device **196** may be any suitable device, such as but not limited to a valve. When the flow controlling device **196** is open, the overhead refrigeration refrigerant accumulator **193** feeds refrigerant to the working fluid reservoir **194**. When the flow controlling device **196** is closed, the working fluid reservoir **194** does not receive refrigerant from the overhead refrigeration refrigerant accumulator **193** because the flow controlling device **196** prevents the overhead refrigeration refrigerant accumulator **193** from feeding refrigerant to the working fluid reservoir **194**.

[0100] The overhead refrigeration refrigerant accumulator **193** may connect to a condenser/evaporator **122**. Refrigerant from the overhead refrigeration refrigerant accumulator **193** may be fed to the condenser/evaporator **122** after undergoing a pressure drop to cool the stream exiting the rectifier section **110**, thereby forming a cooled stream. The condenser/evaporator **122** at least partially condenses the stream exiting the rectifier section **110**. The refrigerant fed to the condenser/evaporator **122** may change from a liquid to a vapor as it cools the stream exiting the rectifier section **110**. The stream fed from the rectifier section **110** to the condenser/evaporator **122** may be fed to the condenser/evaporator **122** via line **14**. Line **14** may emanate from an upper part of the upper section **110**. The line **14** may extend from an outer surface of the upper section **110**, such as through exit 401. The stream exiting the rectifier section **110** and entering the line **14** is a vapor stream.

[0101] The overhead refrigeration refrigerant accumulator **193** may be configured to selectively feed working fluid to the condenser/evaporator **122** via line **295**. The overhead refrigeration refrigerant accumulator **193** is able to selectively feed refrigerant to the

condenser/evaporator **122** via line **295** because the line **295** may include a flow controlling device **195**. The flow controlling device **195** may be any suitable device that can modify pressure and flow, such as but not limited to a valve. When the flow controlling device **195** is open, the overhead refrigeration refrigerant accumulator **193** feeds refrigerant to the condenser/evaporator **122**; when the flow controlling device **195** is closed, the overhead refrigeration refrigerant accumulator **193** does not feed refrigerant to the condenser/evaporator **122**. When the refrigerant is fed from the overhead refrigeration refrigerant accumulator **193** to the condenser/evaporator **122**, the flow controlling device **195** facilitates a pressure drop within the refrigerant, thereby causing a decrease in the pressure and temperature of the refrigerant.

[0102] The condenser/evaporator **122** may receive working fluid directly from the working fluid reservoir **194** via lines **297**, **298**, **299**. The condenser/evaporator **122** may be configured to selectively receive working fluid from the working fluid reservoir **194**. The condenser/evaporator **122** may be so configured because the lines **297**, **298** may include flow controlling device **197** and flow controlling device **198**, respectively. When flow controlling device **197** is open, the condenser/evaporator **122** may receive vapor from the working fluid reservoir **194** via lines **297**, **299**. When flow controlling device **198** is open, the condenser/evaporator **122** may receive liquid from the working fluid reservoir **194** via lines **298**, **299**. The working fluid fed to the condenser/evaporator **122** may mix with the refrigerant that is fed to the condenser/evaporator **122** to exchange heat with the stream exiting the upper section **110**, thereby cooling the stream so the stream exits the condenser/evaporator **122** as a cooled stream.

[0103] Multiple streams may exit the condenser/evaporator **122**. One of these streams may enter the reflux accumulator **124**. Once separated, the vapor stream may exit the reflux accumulator **124** as sales product via line **16** for subsequent sale to a pipeline and/or condensation to be liquefied natural gas. Once separated, the liquid stream may return to the upper section **110** as described above.

[0104] The liquid stream that falls to the bottom of the upper section **110** may collect at the bottom of the upper section **110**. The liquid may collect on tray **183** (Figure 1) or at the bottommost portion of the upper section **110** (Figure 2).

[0105] The liquid may exit the distillation tower **104**, **204** through line **20** (Figure 1) or outlet **260** (Figure 2). The line **20** may emanate from the upper section **110**. The line **20** may emanate from a bottom end of the upper section **110**. The line **20** may extend from an outer

surface of the upper section **110**. The line **20** and/or outlet **260** may connect to a line **41**. The line **41** leads to the spray assembly **129** in the middle controlled freeze zone section **108**. The line **41** may extend to an outer surface of the middle controlled freeze zone section **108**.

[0106] The line **20** and/or outlet **260** may directly or indirectly (Figures 1-2) connect to the line **41**. When the line **20** and/or outlet **260** directly connect to the line **41**, the liquid spray may be pumped to the spray nozzle(s) **120** via any suitable mechanism, such as the spray pump **128** or gravity. When the line **20** and/or outlet **260** indirectly connect to the line **41**, the lines **20**, **41** and/or outlet **260** and line **41** may directly connect to a holding vessel **126** (Figure 1).

[0107] The holding vessel **126** may house at least some of the liquid spray before it is sprayed by the spray nozzle(s). The liquid spray may be pumped from the holding vessel **126** to the spray nozzle(s) **120** via any suitable mechanism, such as the spray pump **128** (Figure 1) or gravity. The holding vessel **126** may be needed when there is not a sufficient amount of liquid stream at the bottom of the upper section **110** to feed the spray nozzles **120**. A multiple vessel distillation tower **204** (Figure 2) may or may not include a holding vessel **126**.

[0108] The refrigerant that exchanges heat with the stream cooled in the condenser/evaporator **122** may exit the condenser/evaporator **122** and enter a separator **190**. The separator **190** may separate the refrigerant and/or working fluid exiting the condenser/evaporator **122** into a vapor stream and a liquid stream. The refrigerant and/or working fluid exiting the condenser/evaporator **122** may substantially be a vapor stream, but to ensure that only vapor enters the compressor **191**, the separator **190** may be used. The separator **190** may be any suitable separator, such as but not limited to a vertical, horizontal or inclined separator. The separator may include, but is not limited to, knock out drums, demister pads or cyclonic devices.

[0109] The separator **190** may connect to a compressor **191**. The compressor **191** may receive the vapor stream from the separator **190**. The compressor **191** may increase the pressure and temperature of the vapor stream.

[0110] The vapor stream exiting the compressor **191** may enter a heat exchanger **192**. The heat exchanger **192** may modify the temperature of the vapor before it is fed to the overhead refrigeration refrigerant accumulator **193**. The heat exchanger **192** may modify the temperature of the vapor by cooling and condensing the vapor before it is fed to the overhead refrigeration refrigerant accumulator **193**.

[0111] The closed loop melt tray temperature conditioning system **330** may include a

subcooler **200** (Figure 3B). The subcooler **200** may ensure that refrigerant exiting the overhead refrigeration refrigerant accumulator **193** is cooled down to minimize vapor formation from the liquid. Refrigerant exiting the overhead refrigeration refrigerant accumulator **193** to the subcooler **200** travels to the condenser/evaporator **122**, from the
5 condenser/evaporator **122** to the separator **190**, from the separator **190** to the compressor **191**, from the compressor **191** to the heat exchanger **192** and then back to the overhead refrigeration refrigerant accumulator **193**.

[0112] At normal operation, the overhead refrigeration refrigerant accumulator **193** feeds the refrigerant to the working fluid reservoir **194**. A small stream of the refrigerant may be
10 fed to the working fluid reservoir **194**. The small stream may be a stream that does not substantially affect the overhead refrigeration system. Before being introduced into the working fluid reservoir **194**, the refrigerant may undergo a pressure and temperature drop across flow controlling device **196**. Because of the pressure drop, some of the refrigerant may form a vapor stream. The vapor stream may flow into the melt tray heat exchanging
15 device **134**, thereby supplying heat to the melt tray fluid **130**. The vapor stream may flow into the melt tray heat exchanging device **134**, thereby supplying heat to the melt tray fluid **130** if the vapor condenses. Working fluid within the melt tray heat exchanging device **134**, which is formed due to condensation in the melt tray heat exchanging device **134**, may be removed from the working fluid reservoir **194** via line **298**, **299** and introduced into the
20 condenser/evaporator **122** after undergoing a pressure and temperature drop. The liquid may undergo a pressure and temperature drop after going through flow controlling device **198**.

[0113] At normal operation, the flow rate of refrigerant being fed from the overhead refrigeration refrigerant accumulator **193** to the working fluid reservoir **194** may be adjusted. The flow rate may be adjusted so that the vapor stream generated due to the pressure and
25 temperature drop across valve **196** is wholly condensed in the melt tray heat exchanging device **134** and the heat of condensation is equal to the heat supply necessary at the melt tray assembly **139** to melt solids within the liquid slurry that would plug the liquid outlet **22**.

[0114] At normal operation, a working fluid amount of working fluid fed from the overhead refrigeration refrigerant accumulator **193** to the working fluid reservoir **194** may
30 remain constant. The working fluid amount may remain constant because the melt tray fluid temperature is within the expected melt tray fluid temperature range.

[0115] At an abnormal operation, which results in a decrease in the melt tray fluid temperature such that the melt tray fluid temperature is less than the expected melt tray fluid

temperature range lower limit, there may be a higher amount of working fluid vapor condensed in the melt tray heat exchanging device **134** than during the normal operation, thereby causing a decrease in a working fluid operating pressure. The working fluid operating pressure may interchangeably be referred to as the working fluid pressure. The working fluid temperature and pressure may be increased by increasing a phase changing fluid pressure of the phase changing fluid by increasing the working fluid amount of working fluid fed to the working fluid reservoir **194**. The melt tray fluid temperature may be increased by increasing the flow rate of the refrigerant fed from the overhead refrigeration refrigerant accumulator **193** to the working fluid reservoir **194**. Because the flow rate is increased, the amount of refrigerant fed to the working fluid reservoir **194** may increase, thereby increasing the working fluid pressure of the working fluid. Increasing the working fluid pressure may increase the temperature at which the working fluid changes phase. When the working fluid pressure is high enough, condensation of the working fluid in the melt tray heat exchanging device **134** may occur, thereby providing more heat to the melt tray fluid and allowing the melt tray fluid temperature to increase to a melt tray fluid temperature within the expected melt tray fluid temperature range. Because the flow rate is increased during abnormal operation, the amount of working fluid in the working fluid reservoir may increase and the liquid level of the working fluid in the working fluid reservoir **194** may increase. After the melt tray fluid temperature returns to being within the expected melt tray fluid temperature range, the flow rates and pressures may return to those at normal operation.

[0116] When the melt tray heat exchanging device **134** is a component that allows for separation of the liquid and vapor within the dual phase changing fluid, the liquid removal rate of the working fluid exiting the working fluid reservoir **194** may or may not be increased. If the melt tray heat exchanging device **134** does not allow for separation of liquid and vapor within the dual phase changing fluid, the liquid removal rate of the working fluid exiting the working fluid reservoir **194** may need to be increased to ensure that the working fluid reservoir **194** continues to hold liquid and vapor.

[0117] At an abnormal operation, which results in an increase in the melt tray fluid temperature such that the melt tray fluid temperature is greater than the expected melt tray fluid temperature range upper limit, the liquid stream in the melt tray heat exchanging device may start evaporating to cause an increase in the amount of vapor in the melt tray heat exchanging device **134** and an increase in the working fluid pressure. The flow configuration may reverse, thereby causing liquid to enter the bottom of the melt tray heat exchanging

device **134** and vapor to exit from the top of the melt tray heat exchanging device **134**. As a result of the higher melt tray fluid temperature, more of the working fluid fed to the melt tray heat exchanging device **134** may vaporize than if the melt tray fluid temperature was within the expected melt tray fluid temperature range, thereby resulting in an increase in the amount of working fluid that is a vapor stream in the working fluid reservoir **194**. To decrease the melt tray fluid temperature, vapor stream from the working fluid reservoir **194** may be fed to the condenser/evaporator **122** via lines **297**, **299** to reduce working fluid pressure and temperature; liquid from the overhead refrigeration refrigerant accumulator **193** may be fed to the working fluid reservoir **194** via lines **196**, **296** to supply more liquid to cool the melt tray heat assembly. When the melt tray heat exchanging device **134** is a component that allows for separation of the liquid stream and vapor stream within the dual phase changing fluid, the liquid removal rate of the refrigerant being fed to the working fluid reservoir **194** from the overhead refrigeration refrigerant accumulator **193** may or may not be increased. If the melt tray heat exchanging device **134** does not allow for separation of liquid stream and vapor stream within the dual phase changing fluid, the liquid removal rate of the refrigerant being fed to the working fluid reservoir **194** from the overhead refrigeration refrigerant accumulator **193** may need to be increased to ensure that the working fluid reservoir **194** continues to hold the liquid stream and vapor stream and to decrease the pressure and temperature of the working fluid in the working fluid reservoir **194**.

[0118] The open loop melt tray temperature conditioning system **430** (Figures 6A and 6B) may comprise a working fluid reservoir **294**. The working fluid reservoir **294** holds the working fluid that is fed to the melt tray heat exchanging device **134**. Working fluid is fed to the melt tray heat exchanging device **134** via lines **316**, **317**. The working fluid reservoir **294** may receive fluid from the melt tray heat exchanging device **134** via lines **316**, **317**. The working fluid may comprise any suitable working fluid. For example, the working fluid may comprise one of propane, carbon dioxide, ethane, ammonia, ethylene, an azeotrope of carbon dioxide and ethane, a single halogenated hydrocarbon and a combination of components with a temperature glide that allows the intended purpose of the present disclosure to work. With respect to the combination of components with the temperature glide, the temperature glide may be less than or equal to 10 °C or 18 °F. The temperature glide may be any number within and/or bounded by the preceding temperature range. The ethane may be used as an azeotrope with carbon dioxide.

[0119] The open loop melt tray temperature conditioning system **430** shown in Figures

- 6A and 6B may include the heat exchanging device **245** shown in Figures 4 and 5. The heat exchanging device **245** may fluidly connect with the upper section **110**. The vapor stream that rises to the top of the upper section **110** may exit the upper section **110** through line **14**. The vapor stream that exits the upper section **110** may be fed directly to the heat exchanging device **245**. The vapor stream fed to the heat exchanging device **245** may be heated in the heat exchanging device **245**. After being heated, the stream may exit the heat exchanging device **245** and be fed to a first compressor **1260**. The stream may be compressed in the first compressor **1260**, then fed to a first cooler **238** to be cooled in a first cooler **238**, then fed to a second compressor **1261** to be further compressed in the second compressor **1261**, then fed to a second cooler **241** to be further cooled in the second cooler **241**, then fed to a third compressor **262** to be further compressed by the third compressor **262**, then fed to a third cooler **240** to be further cooled by the third cooler **240** and then sent to sales via line **16**. More or fewer of the consecutive coolers **238**, **241**, **240** and/or compressors **1260**, **1261**, **262** may be employed.
- 15 **[0120]** Some of the vapor stream may be transported to the heat exchanging device **245** via line **208** instead of being sent to sales via line **16**. The vapor stream transported to the heat exchanging device **245** instead of being sent to sales via line **16** may heat the stream sent to the consecutive coolers **238**, **241**, **240** and compressors **1260**, **1261**, **262** and be cooled by the stream sent to the consecutive coolers **238**, **241**, **240** and compressors **1260**, **1261**, **262**.
- 20 After being cooled by the stream sent to the consecutive coolers **238**, **241**, **240** and compressors **1260**, **1261**, **262**, the stream may be sent to the pressure controlling/reducing device **258**.
- [0121]** Some of the vapor stream sent to be cooled in the heat exchanging device **245** may be transported to cool the working fluid within the working fluid reservoir **294** instead of being sent to the pressure controlling/reducing device **258**. The stream may travel to the working fluid reservoir **294** via line **372**. The stream may be transported to cool the working fluid reservoir **294** when the melt tray fluid temperature is within the expected melt tray fluid temperature range. The stream may cool the working fluid by exchanging heat with the working fluid within the working fluid reservoir **294**. The stream may not mix with the working fluid. In other words, the exchange of heat may be a non-contact process.
- 30 **[0122]** The line **372** may include a flow controlling device **271** that controls how much and/or at what flow rate the stream travels to the working fluid reservoir **294**. When the flow controlling device **271** is open, the stream travels to the working fluid reservoir **294**; when the

flow controlling device **271** is closed, the stream does not travel to the working fluid reservoir **294**. After exchanging heat with the working fluid in the working fluid reservoir **294**, the stream may return to the compressor **1260** via line **371**.

[0123] The open loop melt tray temperature conditioning system **430** (Figures 6A and 6B) may include a feed refrigeration refrigerant accumulator **497**. The feed refrigeration refrigerant accumulator **497** may house a feed refrigeration refrigerant. The feed refrigeration refrigerant may comprise any suitable feed refrigeration refrigerant such as but not limited to ethane, ethylene, R404a, R410a, triufluoromethane, propane, ammonia, carbon dioxide or a combination of components with a temperature glide that allows the intended purpose of the present disclosure to work. With respect to the combination of components with the temperature glide, the temperature glide may be less than or equal to 10 °C or 18 °F. The temperature glide may be any number within and/or bounded by the preceding temperature range. The ethane may be used as an azeotrope with carbon dioxide. The R-# in R404a and R410 refers to a numbering system developed by DuPont that systematically identifies the molecular structure of refrigerants made with a single halogenated hydrocarbon. The number in the R-# is derived by subtracting 90 from concatenated numbers of carbon, hydrogen and fluorine atoms, respectively. A suffix of lower-case letter a, b or c indicates increasingly unsymmetrical isomers. R-404a is a “nearly azeotropic” blend of 52 weight percent R-143a, 44 weight percent R-125 and 4 weight percent R-134a while R-410a is a near-azeotropic blend of R-32 and R-125. The feed refrigeration refrigerant accumulator **497** may comprise any suitable vessel that is able to operate at super-ambient pressures. For example, the feed refrigeration refrigerant accumulator **497** may comprise a pressure-containing vessel or a separator.

[0124] The feed refrigeration refrigerant in feed refrigeration refrigerant accumulator **497** may be used to heat the working fluid when the melt tray fluid temperature is below the expected melt tray fluid temperature range. The feed refrigeration refrigerant in the feed refrigeration refrigerant accumulator **497** may travel to the working fluid reservoir **294** via line **384**. The feed refrigeration refrigerant may heat the working fluid by exchanging heat with the working fluid. The feed refrigeration refrigerant may not mix with the working fluid. In other words, the exchange of heat may be a non-contact process.

[0125] The line **384** may include a flow and pressure controlling device **284** that controls how much the feed refrigeration refrigerant exchanges heat with the working fluid in the working fluid reservoir **294**. When the flow controlling device **284** and **285** are open, the

feed refrigeration refrigerant exchanges heat with the working fluid in the working fluid reservoir **294**; when the flow controlling device **284** is closed, the feed refrigeration refrigerant does not exchange heat with the working fluid reservoir **294**.

[0126] After exchanging heat with the working fluid in the working fluid reservoir **294**,
5 the feed refrigeration refrigerant may travel to heat exchanger **280**. The feed refrigeration refrigerant may travel to the heat exchanger **280** and mix with feed refrigeration refrigerant coming from line **383**. The feed refrigeration refrigerant coming from line **384** may travel to line **383** via line **385**. The line **385** may include a flow controlling device **285** that controls how much and/or at what flow rate and pressure feed refrigeration refrigerant travels to the
10 heat exchanger **280** via line **380**. When the flow controlling device **284** and **285** are open, the feed refrigeration refrigerant continues to the heat exchanger **280**; when the flow controlling device **285** is closed, the feed refrigeration refrigerant does not continue to the heat exchanger **280**.

[0127] Feed refrigeration refrigerant from the feed refrigeration refrigerant accumulator
15 **497** may exchange heat with the stream **10** before the stream **10** enters the distillation tower **104**, **204**. The feed refrigeration refrigerant may be fed to a heat exchanger **280** via line **380** to exchange heat with the stream **10**. The line **380** may include the flow controlling valve **283**. The flow controlling valve **283** may control how much feed and/or at what flow rate refrigeration refrigerant is fed to the stream **10**. After exchanging heat with the stream **10**, the
20 feed refrigeration refrigerant may be fed to a compressor **1200** through line **500**. The feed refrigeration refrigerant may be compressed to a higher pressure and a higher temperature by being fed to compressor **1200**. After exiting compressor **1200**, the feed refrigeration refrigerant may be fed to a cooler **1201**. The feed refrigeration refrigerant may be condensed in the cooler **1201**. After exiting the cooler **1201**, the feed refrigeration refrigerant may be
25 fed to refrigeration refrigerant accumulator **497**.

[0128] The open-loop melt tray temperature conditioning system **430** may comprise a working fluid make-up tank **496**. The working fluid make-up tank **496** may be configured to receive the working fluid from the working fluid reservoir **294** and to feed working fluid to the working fluid reservoir **294** when the melt tray fluid temperature is outside of the
30 expected melt tray fluid temperature range. The working fluid make-up tank **496** may contain working fluid.

[0129] The working fluid make-up tank **496** may connect to the working fluid reservoir **294** via lines **395**, **451**, **398**. The line **395** may include a flow controlling device **295** that

controls how much working fluid is fed to the working fluid make-up tank **496** from the working fluid reservoir **294**. The line **451** may include a flow controlling device **351** that controls how much working fluid is fed to the working fluid make-up tank **496** from the working fluid reservoir **294**. The line **398** may include a flow controlling device **498** that
5 controls how much working fluid is fed to the working fluid reservoir **294** and/or at what flow rate from the working fluid make-up tank **496**. Before reaching the flow controlling device **498**, the working fluid from the working fluid make-up tank **496** may enter a compressor **281**, to increase the pressure and temperature of the working fluid, and a condenser **282** to cool the working fluid.

10 **[0130]** At normal operation, heat may be supplied to the working fluid reservoir **294** to heat the working fluid, thereby vaporizing some of the working fluid within the working fluid reservoir **294**. The heat may be supplied by the feed refrigeration refrigerant accumulator **497**. The vaporized working fluid may be fed to the melt tray heat exchanging device **134** to supply heat to the melt tray fluid so that the melt tray fluid temperature remains with the
15 expected melt tray temperature range. The feed refrigeration refrigerant that exchanges heat with the working fluid may not mix with the working fluid. In other words, the exchange of heat may be a non-contact process. While exchanging heat with the working fluid in the working fluid reservoir **294**, the feed refrigeration refrigerant condenses. After exchanging heat with the working fluid in the working fluid reservoir, the feed refrigeration refrigerant
20 travels to heat exchanger **280** via line **380**. The flow rate of the feed refrigeration refrigerant to the working fluid reservoir **294** may be such that the heat of condensation of this stream is substantially equal to the heat needed to heat the melt tray fluid to a melt tray fluid temperature within the expected melt tray fluid temperature range during normal operation.

[0131] At an abnormal operation, which results in a decrease in the melt tray fluid
25 temperature such that the melt tray fluid temperature is less than the expected melt tray fluid temperature range lower limit, the melt tray fluid temperature may be increased to a temperature within the expected melt tray temperature range. When there is a decrease in the melt tray fluid temperature, a higher amount of vapor may be condensed in the melt tray heat exchanging device **134**, which in turn results in a decrease in the melt tray heat exchanging
30 device operating pressure. To recover from this abnormal operation, a flow rate of feed refrigeration refrigerant, from the feed refrigeration refrigerant accumulator **497**, that exchanges heat with the working fluid may be increased. As a result, a higher amount of vapor may be generated in the working fluid reservoir **294**, which increases pressure and

concomitant higher flow rate to provide more heat to the melt tray heat exchanging device **134** to facilitate recovery of normal operating temperatures. The flow configuration inside the melt tray heat exchanging device **134** may remain the same through this abnormal operation. The flow configuration remaining the same means that vapor enters the top part of the melt tray heat exchanging device **134** while liquid exits from the bottom part of the melt tray heat exchanging device **134** where the bottom part is closer to the lower section **106** than the top part. Once the abnormal operation terminates, the flow rate of the feed refrigeration refrigerant may return to its flow rate at normal operation.

[0132] If the increased feed refrigeration refrigerant flow rate does not provide enough heat to the working fluid to return the melt tray fluid temperature to one within the expected melt tray fluid temperature range, the working fluid make-up tank **496** can supply additional working fluid to the working fluid reservoir **294** via line **398**. Before entering the working fluid reservoir **294**, the working fluid from the working fluid make-up tank **496** may be pressurized via compressor **281** and cooled but not fully condensed in exchanger **282** so that the working fluid from the working fluid make-up tank **496** can warm the working fluid within the working fluid reservoir **294**. Any excess working fluid generated due to condensation in the melt tray heat exchanging device **134** may be returned to the working fluid make-up tank **496** via line **395**.

[0133] At an abnormal operation, which results in an increase in the melt tray fluid temperature such that the melt tray fluid temperature is greater than the expected melt tray fluid temperature range upper limit, the melt tray fluid temperature may be decreased. When there is an increase in the melt tray fluid temperature, liquid in the melt tray heat exchanging device **134** may start evaporating which may result in an increase in the vapor inventory within the working fluid reservoir **294** and melt tray heat exchanging device pressure. When there is an increase in the melt tray fluid temperature, the flow configuration may reverse, thereby causing liquid to enter the bottom of the melt tray heat exchanging device **134** and vapor to exit from the top of the melt tray heat exchanging device **134**. To recover from this abnormal operation, a flow rate of the stream from heat exchanging device **245** may be increased. The increased reflux flow rate results in reducing the vapor inventory in the working fluid reservoir **294** and lowering the operating pressure and temperature of the melt tray fluid in the melt tray heat exchanging device **134**. Similar to the feed refrigeration refrigerant, the reflux does not mix with the working fluid. In other words, the exchange of heat from the reflux is a non-contact process.

[0134] If the increased reflux flow rate does not provide enough cooling to the working fluid to return the melt tray fluid temperature to one within the expected melt tray fluid temperature range, excess vapor generated in the melt tray heat exchanging device **134** may be removed from the top of the working fluid reservoir **294** and fed to the working fluid make-up tank **496** via line **451**. This results in a reduction in the amount of working fluid in the melt tray heat exchanging device **134**, thereby decreasing the liquid level in the working fluid reservoir **294**. The liquid level in the working fluid reservoir **294** may be increased by introducing working fluid from the working fluid make-up tank **496** via line **398**. The liquid level may be defined as set forth above.

[0135] A control system **321** (Figures 3A-3B and 6A-6B) may determine if the distillation tower **104, 204** is at normal operation or abnormal operation. The control system **321** may help the distillation tower **104, 204** remain at normal operation. The control system **321** may help the distillation tower **104, 204** return to normal operation if operating at abnormal operation. The control system **321** may receive input from a pressure sensor **201**, a temperature sensor **202**, a composition analyzer **206** and a temperature indicating controller **302**. The pressure sensor **201** may detect a pressure of the melt tray fluid **130**. The temperature sensor **202** may detect a temperature of the melt tray fluid **130**. The composition analyzer **206** may analyze a melt tray fluid composition of the melt tray fluid **130**. The temperature indicating controller **302** may determine a temperature of the working fluid in a working fluid reservoir **194, 294**.

[0136] The control system **321** may receive the melt tray fluid composition of the melt tray fluid **130, 503** (Figure 8). Receiving the melt tray fluid composition may include analyzing a sample of the melt tray fluid with the composition analyzer **206**. The sample of (i.e., some portion of) the melt tray fluid **130** may be extracted from the melt tray assembly **139**. Receiving the melt tray fluid composition may include determining a percentage of the components within the melt tray fluid based on the analysis conducted with the composition analyzer **206**. The components may include at least one of methane, hydrogen sulfide and carbon dioxide. The composition analyzer **206** may be any suitable analyzer, such as for example, a gas chromatograph or Fourier Transform Infra-Red Analyzer.

[0137] The control system **321** may receive the melt tray fluid pressure of the melt tray fluid **130, 510** (Figure 8). The control system **321** may receive the melt tray fluid pressure of the melt tray fluid **130** from the pressure sensor **201**. The pressure sensor **201** may determine the melt tray fluid pressure by detecting the melt tray fluid pressure (Figures 1-3B and 6A-

6B). The pressure sensor **201** may be any suitable sensor, such as, at least one of but not limited to a piezoresistive strain gauge, a capacitive measurement, electromagnetic, piezoelectric optical and/or potentiometric.

[0138] The control system **321** may receive the melt tray fluid temperature of the melt tray fluid **130**, **504** (Figure 8). The control system **321** may receive the melt tray fluid temperature of the melt tray fluid **130** from the temperature sensor **202**. The temperature sensor **202** may determine the melt tray fluid temperature by detecting the melt tray fluid temperature (Figures 1-3B and 6A-6B). The temperature sensor **202** may be any suitable sensor, such as, at least one of a thermocouple, a thermowell and a resistance temperature detector.

[0139] The melt tray fluid composition and/or the melt tray fluid pressure may help determine the expected melt tray fluid temperature of the melt tray fluid **130**. The expected melt tray fluid temperature may be greater than a melt tray fluid freezing temperature. The melt tray fluid freezing temperature is the temperature at which the melt tray fluid freezes. There are several ways in which the melt tray fluid composition and/or the melt tray fluid pressure may determine the expected melt tray fluid temperature. Examples include, but are not limited to, using look-up tables, activity coefficient models, equations of state, thermodynamic databases and/or thermodynamic software packages.

[0140] The control system **321** may compare the melt tray fluid temperature to the expected melt tray fluid temperature range to determine if the melt tray fluid temperature is within or outside of the melt tray fluid temperature range.

[0141] The control system **321** may determine if the melt tray fluid temperature detected by the temperature sensor **202** is within the expected melt tray fluid temperature range for the melt tray fluid composition of the melt tray fluid **130** detected by the composition analyzer **206**, **505** and/or the melt tray fluid pressure detected by the pressure sensor **201**, **501** (Figure 8).

[0142] After determining if the melt tray fluid temperature is within the expected melt tray fluid temperature range, the control system **321** may assist in decreasing the melt tray fluid temperature if the melt tray fluid temperature is greater than the expected melt tray fluid temperature range upper limit, increasing the melt tray fluid temperature if the melt tray fluid temperature is less than the expected melt tray fluid temperature range lower limit, and maintaining the melt tray fluid temperature if the melt tray fluid temperature is within the temperatures of expected melt tray fluid temperature range, **506** (Figure 8). Specifically, if

the melt tray fluid temperature is greater than the expected temperate range upper limit, the control system **321** may communicate with the melt tray temperature conditioning system **330, 430** to decrease the melt tray fluid temperature; if the melt tray fluid temperature is less than the expected melt tray fluid temperature range lower limit, the control system **321** may communicate with the melt tray temperature conditioning system **330, 430** to increase the melt tray fluid temperature; and if the melt tray fluid temperature is within the expected melt tray fluid temperature range, the control system **321** may communicate with the melt tray temperature conditioning system **330, 430** to maintain the melt tray fluid temperature.

[0143] As shown in Figures 3A and 6A, the control system **321** may also receive input from a pressure indicating controller **301a** and a liquid level indicating controller **303a**. The pressure indicating controller **301a** may determine a pressure of the working fluid in the working fluid reservoir **194, 294**. The pressure indicating controller **301a** may assist the control system **321** in communicating with flow controlling device(s) to adjust the pressure of the working fluid. The liquid level indicating controller **303a** may determine a liquid level of the working fluid in the working fluid reservoir **194, 294**. The liquid level indicating controller **303a** may assist the control system **321** in communicating with flow controlling device(s) to adjust the liquid level of the working fluid. The liquid level indicating controller **303a** may be any suitable indicator, such as but not limited to, a level gauge, a differential pressure indicator or a guided wave radar device. The liquid level in the working fluid reservoir **194, 294** is the point of intersection between the liquid and vapor within the working fluid reservoir **194, 294**. As shown in Figures 3A and 6A, the control system **321** may use the inputs from at least one of the pressure sensor **201**, the temperature sensor **202**, the composition analyzer **206**, the temperature indicating controller **302**, the pressure indicating controller **301a** and the liquid level indicating controller **303a** to determine if the distillation tower **104** is at normal operation or abnormal operation.

[0144] Based on detections and/or analysis from at least one of the pressure sensor **201**, the temperature sensor **202**, the composition analyzer **206**, the temperature indicating controller **302**, the pressure indicating controller **301a** and the liquid level indicating controller **303a**, the control system **321** may determine whether a modification needs to occur (Figures 3A and 6A) for the melt tray fluid temperature to be within the expected melt tray fluid temperature range. For example but not limited to, based on detections from the temperature indicating controller **302** and/or the pressure indicator **301a**, the control system **321** may determine that the flow rate of the working fluid needs to be increased or decreased.

When this occurs, the control system **321** may include a control algorithm that controls the flow rate of the working fluid by communicating with the melt tray temperature conditioning system, **330, 430**.

[0145] For a closed loop melt tray temperature conditioning system (Figure 3A) and an open loop melt tray temperature conditioning system (Figure 6A), the control system **321** may receive the liquid level in the working fluid reservoir **194, 294**. The control system **321** may receive the liquid level from a liquid level indicating controller **303a**. The liquid level determined by the liquid level indicating controller **303a** may be analyzed by the control system **321** and, based on the analysis, the control system **321** may determine the flow rate of the working fluid entering the working fluid reservoir; it may determine the flow rate of working fluid vapor and working fluid liquid leaving the working fluid reservoir. The control system **321** may determine that the liquid level needs to be modified using the liquid level indicating controller **303a**, the pressure indicating controller **301a** and/or the temperature indicating controller **302**.

[0146] For the closed loop melt tray temperature conditioning system (Figure 3A), flow controlling devices **196, 197, 198** may help modify the liquid level once the control system **321** determines that the liquid level needs to be modified. The control system **321** may send signals to the flow controlling devices **196, 197, 198** to modify the liquid level. If the control system **321** receives a signal from the temperature indicating controller **302** that the temperature needs to be increased, flow controlling device **196** opens up which increases the pressure within the working fluid reservoir **194** and the pressure indicating controller **301a** reads that. The increased pressure within the working fluid reservoir **194** may result in an increased temperature within the working fluid reservoir **194**, which in turn may result in increased heat transfer rate to the melt tray assembly. The increased heat transfer to the melt tray assembly may help cause the working fluid to condense and the liquid level to rise. The liquid level indicating controller **303a** reads the raised liquid level and flow controlling device **198** opens up to decrease the liquid level. If the control system **321** receives a signal from the temperature indicating controller **302** that the temperature needs to be decreased, flow controlling device **197** opens up to remove vapor from the working fluid reservoir **194**. Opening up the flow controlling device **197** to remove the vapor from the working fluid reservoir **194**, may lower the working fluid pressure and working fluid temperature. Lowering the working fluid pressure and the working fluid temperature may result in evaporation of working fluid in the melt tray heat exchange device. The evaporation of the

working fluid in the melt tray heat exchanging device may cause the melt tray assembly to cool down.

[0147] For the closed loop melt tray temperature conditioning system (Figure 3A), the control system **321** may determine whether the flow rate of refrigerant being fed from an overhead refrigeration refrigerant accumulator **193** to the working fluid reservoir **194** and/or the working fluid being fed from the working fluid reservoir **194** to the condenser/evaporator **122** needs to be changed. To determine whether the flow rate of refrigerant being fed from the overhead refrigeration refrigerant accumulator **193** to the working fluid reservoir **194** needs to be changed, the control system **321** may analyze at least one of the melt tray fluid temperature detected by the temperature sensor **202**, the melt tray fluid pressure detected by the pressure sensor **201**, the liquid level within the working fluid reservoir **194** detected by the liquid level indicating controller **303a**, the melt tray fluid composition detected by the composition analyzer **206**, the temperature of the working fluid within the working fluid reservoir **194** detected by the temperature indicating controller **302** and the pressure of the working fluid within the working fluid reservoir **194** detected by the pressure indicating controller **301a**. Analyzing one or more of these components helps in determining how close to freezing the melt tray fluid is. To determine whether the flow rate of working fluid being fed from the working fluid reservoir **194** needs to be changed, the control system **321** may analyze at least one of the melt tray fluid temperature detected by the temperature sensor **202**, the melt tray fluid pressure detected by the pressure sensor **201**, the liquid level within the working fluid reservoir **194** detected by the liquid level indicating controller **303a**, the melt tray fluid composition detected by the composition analyzer **206**, the temperature of the working fluid within the working fluid reservoir **194** detected by the temperature indicating controller **302** and the pressure of the working fluid within the working fluid reservoir **194** detected by the pressure indicating controller **301a**.

[0148] For the open loop melt tray temperature conditioning system (Figure 6A), flow controlling devices **271**, **284**, **285**, **295** may help modify the liquid level once the control system **321** determines that the liquid level needs to be modified. The control system **321** may send signals to the flow controlling devices **271**, **284**, **285**, **295**, **498** to modify the liquid level. If the control system **321** receives a signal from the temperature indicating controller **302** that the temperature needs to be increased, flow controlling device **271** open up which increases the pressure within the working fluid reservoir **294** and the pressure indicating controller **301a** reads that. The increased pressure within the working fluid reservoir **294**

may result in increased temperature within the working fluid reservoir **294**, which in turn may result in increased heat transfer rate to the melt tray assembly. The increased heat transfer to the melt tray assembly may help cause the working fluid to condense and the liquid level to rise. The liquid level indicating controller **303a** reads the raised liquid level and flow controlling device **295** open up to decrease the liquid level. If the control system **321** receives a signal from the temperature indicating controller **302** that the temperature needs to be decreased, flow controlling device **351** opens up to remove vapor from the working fluid reservoir **294**. Opening up the flow controlling device **351** to remove the vapor from the working fluid reservoir **294** may lower the working fluid pressure and working fluid temperature. Lowering the working fluid pressure and the working fluid temperature may result in evaporation of working fluid in the melt tray heat exchange device. The evaporation of the working fluid in the melt tray heat exchanging device may cause the melt tray assembly to cool down.

[0149] For the open loop melt tray temperature conditioning system (Figure 6A), the control system **321** may determine whether the flow rate of refrigerant being fed from the feed refrigeration refrigerant accumulator **497** to the working fluid reservoir **294** needs to be changed. To determine whether the flow rate of refrigerant being fed from the feed refrigeration refrigerant accumulator **497** to the working fluid reservoir **294** needs to be changed and/or the flow rate of the stream being fed from the heat exchanging device **245** to the working fluid reservoir **294** needs to be changed, the control system **321** may analyze at least one of the melt tray fluid temperature detected by the temperature sensor **202**, the melt tray fluid pressure detected by the pressure sensor **201**, the liquid level within the working fluid reservoir **294** detected by the liquid level indicating controller **303a**, the melt tray fluid composition detected by the composition analyzer **206**, the temperature of the working fluid within the working fluid reservoir **194** detected by the temperature indicating controller **302** and the pressure of the working fluid within the working fluid reservoir **294** detected by the pressure indicating controller **301a**. Analyzing one or more of these components helps in determining how close to freezing the melt tray fluid is. To determine whether the flow rate of refrigerant fed from the working fluid reservoir **294** needs to be changed, the control system **321** may analyze at least one of the melt tray fluid temperature detected by the temperature sensor **202**, the melt tray fluid pressure detected by the pressure sensor **201**, the liquid level within the working fluid reservoir **294** detected by the liquid level indicating controller **303a**, the melt tray fluid composition detected by the composition analyzer **206**,

the temperature of the working fluid within the working fluid reservoir **294** detected by the temperature indicating controller **302** and the pressure of the working fluid within the working fluid reservoir **294** detected by the pressure indicating controller **301a**.

[0150] As shown in Figures 3B and 6B and unlike what is shown in Figures 3A and 6A,
5 the control system **321** may not receive input from a pressure indicating controller **301b** and a liquid level indicating controller **303b**. The temperature indicating controller **302** may assist the control system **321** in communicating with the pressure indicating controller **301b** and the liquid level indicating controller **303b**. The pressure indicating controller **301b** may determine a pressure of the working fluid in the working fluid reservoir **194**, **294**. The
10 pressure indicating controller **301b** may communicate with a flow controlling device(s) to adjust the pressure of the working fluid after receiving a signal from the temperature indicating controller **302**. The liquid level indicating controller **303b** may determine a liquid level of the working fluid in the working fluid reservoir **194**, **294**. The liquid level indicating controller **303a** may communicate with flow controlling device(s) to adjust the liquid level of
15 the working fluid after receiving a signal from the temperature indicating controller **302**. The liquid level indicating controller **303b** may be any suitable indicator, such as but not limited to, a level gauge, a differential pressure indicator or a guided wave radar device. The liquid level in the working fluid reservoir **194**, **294** is the point of intersection between the liquid and vapor within the working fluid reservoir **194**, **294**. As shown in Figures 3B and 6B, the
20 control system **321** may use the inputs from at least one of the pressure sensor **201**, the temperature sensor **202**, the composition analyzer **206**, and the temperature indicating controller **302** to determine if the distillation tower **104** is at normal operation or abnormal operation.

[0151] Based on readings from at least one of the pressure sensor **201**, the temperature
25 sensor **202**, the composition analyzer **206** and the temperature indicating controller **302**, the control system **321** may determine whether a modification needs to occur (Figures 3B and 6B) for the melt tray fluid temperature to be within the expected melt tray fluid temperature range. For example, but not limited to, based on readings from the temperature indicating controller **302**, the control system **321** may determine that the pressure of the working fluid
30 needs to be increased or decreased. When this occurs, the control system **321** may include a control algorithm that controls the pressure by communicating with the melt tray temperature conditioning system **330**, **430**.

[0152] For a closed loop melt tray temperature conditioning system (Figure 3B) and an

open loop temperature conditioning system (Figure 6B), the control system **321** may determine the temperature of the working fluid using the temperature indicating controller **302**. Based on the temperature of the working fluid, the melt tray fluid temperature, the melt tray fluid pressure and/or the melt tray fluid composition, the control system **321** may determine that the temperature of the working fluid needs to be modified (e.g., increased or decreased) and/or the pressure of the working fluid needs to be modified for the melt tray fluid temperature to be within the expected melt tray fluid temperature range. The control system **321** may send this determination to the temperature indicating controller **302**. The temperature indicating controller **302** may communicate with the pressure indicating controller **301b** and/or the liquid level indicating controller **303b** as necessary. When the temperature indicating controller **302** communicates with the pressure indicating controller **301b** it may tell the pressure indicating controller **301b** that the working fluid pressure needs to be increased or decreased. When the temperature indicating controller **302** communicates with the liquid level indicating controller **303b** it may tell the liquid level indicating controller **303b** that the liquid level of the working fluid needs to be increased or decreased.

[0153] For a closed loop melt tray temperature conditioning system, when the temperature indicating controller **302** communicates with the pressure indicating controller **301b**, the pressure indicating controller **301b** communicates with flow controlling device **196** and/or flow controlling device **197** so that the flow controlling device **196** and/or flow controlling device **197** can open more or close more as needed to modify the working fluid pressure and, therefore, the melt tray fluid temperature. When the temperature indicating controller **302** communicates with the liquid level indicating controller **303b**, the liquid level indicating controller **303b** communicates with flow controlling device **198** and/or flow controlling device **196** as needed to modify the liquid level, and therefore, the melt tray fluid temperature. For example, if the control system **321** determines the melt tray fluid temperature needs to increase for the melt tray fluid temperature to be within the expected melt tray fluid temperature range, the control system **321** may communicate with temperature indicating controller **302**. In turn, the temperature indicating controller **302** may communicate to the pressure indicating controller **301b** that the pressure needs to increase; the temperature indicating controller **302** may communicate to the liquid level indicating controller **303b** that the liquid level needs to remain the same. As a result, pressure indicating controller **301b** communicates with flow controlling device **196** to open up more resulting in more working fluid entering the working fluid reservoir and increasing the

pressure of the working fluid. However, as liquid and vapor enter the working fluid reservoir, the liquid level within the working fluid reservoir may rise. As a result, the liquid level indicating controller **303b** may communicate with flow controlling device **198** to open up more. As another example, if the control system **321** determines that the melt tray fluid temperature needs to decrease for the melt tray fluid temperature to be within the expected melt tray fluid temperature range, the control system **321** may communicate with the temperature indicating controller **302**. In turn, the temperature indicating controller **302** may communicate to the pressure indicating controller **301b** that the pressure needs to decrease and communicates to the liquid level indicator **303b** so that the liquid level remains the same. As a result, pressure indicating controller **301b** communicates with flow controlling device **197** to open up more. However, this may cause some of the liquid to flash into vapor, potentially resulting in a drop in the liquid level within the reservoir. Therefore, liquid level indicating controller **303b** may communicate with flow controlling device **196** to open up more.

[0154] For an open loop melt tray temperature conditioning system (Figure 6B), when the temperature indicating controller **302** communicates with the pressure indicating controller **301b**, the pressure indicating controller **301b** communicates with a flow controlling device **271, 284, 285** and/or **498** so that the flow controlling device **271, 284, 285** and/or **498** can open more or close more as needed to modify the working fluid pressure. When the temperature indicating controller **302** communicates with the liquid level indicating controller **303b**, the liquid level indicating controller **303b** communicates with flow controlling device **295** and/or compressor **281** as needed to modify the liquid level. For example, if the control system **321** determines that melt tray fluid temperature needs to increase for the melt tray fluid temperature to be within the expected melt tray fluid temperature range, temperature indicating controller **302** communicates to the pressure indicating controller **301b** that the pressure needs to increase. As a result, pressure indicating controller **301b** communicates with flow controlling device **284** and/or **285** to open up more. As another example, if the control system **321** determines that pressure needs to decrease for the melt tray fluid temperature to be within the expected melt tray fluid temperature range, temperature indicating controller **302** communicates to the pressure indicating controller **301b** that the pressure needs to decrease. As a result, pressure indicating controller **301b** communicates with flow controlling device **271** to open up more and/or flow controlling device **351** to open up more, while closing flow controlling device **284** more.

[0155] For abnormal operations, similar to what is described above for the open loop and closed loop melt tray temperature conditioning systems **330**, **430** the liquid level may or may not be compensated for if the melt tray heat exchanging device **134** comprises a component that allows for separation of the liquid and vapor within the dual phase changing fluid.

5 [0156] The melt tray heat exchanging device **134** may be any suitable device that can hold a phase changing fluid. For example, the melt tray heat exchanging device may comprise a melt coil, plates or finned, serpentine tubes.

[0157] The melt tray heat exchanging device **134** may comprise a component, such as but not limited to a wick, that allows for contact of the liquid and vapor within the dual phase
10 changing fluid. The wick (Figure 7) may comprise a substantially liquid core portion **1302** and a substantially vapor core portion **303**. At normal operation, the substantially liquid core portion **302** may receive liquid that is in the phase changing fluid. At normal operation, the substantially vapor core portion **303** may receive vapor that is in the phase changing fluid. At normal operation, the substantially liquid core portion **303** may be located within an inner
15 portion **304** of the wick. At normal operation, the substantially vapor core portion **303** may be located within an outer portion **305** of the wick. At normal operation, the outer portion **305** may surround the inner portion **304**. At normal operation of the distillation tower **104**, **204**, vapor within the substantially vapor core portion **303** may condense and flow from the outer portion **305** and through the wick to the substantially liquid core portion **1302** in the
20 inner portion **304**. At an abnormal operation of the distillation tower **104**, **204** where the temperature of the melt tray fluid **130** needs to be increased to ensure adequate melting of the solids, vapor within the substantially vapor core portion **303** may flow from the outer portion **305** and through the wick to the substantially liquid core portion **1302** in the inner portion **304**. At abnormal operation where the temperature of the melt tray fluid **130** needs to be
25 decreased to ensure adequate separation performance of the contaminants from the hydrocarbons within the stream, liquid within the substantially liquid core portion **1302** may flow from the inner portion **304** and through the wick to the substantially vapor core portion **303** in the outer portion **305**. When liquid flows from the substantially liquid core portion **1302** to the substantially vapor core portion **1302**, more liquid evaporates.

30 [0158] If the melt tray heat exchanging device **134** comprises a wick, the orientation of the melt tray heat exchanging device **134** with respect to the working fluid reservoir **194**, **294** may be such that the wick is one of substantially at a same vertical location and not substantially at a same vertical location with the working fluid reservoir **194**, **294**. The

orientation of the melt tray heat exchanging device **134** with respect to the working fluid reservoir **194, 294** may also be such that the horizontal location of the melt tray heat exchanging device **134** to the working fluid reservoir **194, 294** is unimportant. The vertical location refers to a location along a longitudinal axis **310-310** of the distillation tower **104, 204** (Figures 1-2 and 4-5). The horizontal location refers to a location along a lateral axis of the distillation tower **104, 204** where the lateral axis is perpendicular to the longitudinal axis **310-310**. The melt tray heat exchanging device **134** may be in any vertical and/or horizontal location with respect to the working fluid reservoir **194, 294** because the wick allows for the mixing of vapor and liquid due to the wick's substantially vapor core portion **303** and substantially liquid core portion **302**.

[0159] If the melt tray heat exchanging device **134** does not comprise a device, such as a wick, that allows for mixing of vapor and liquid, the orientation of the melt tray heat exchanging device **134** with respect to the working fluid reservoir **194, 294** may be one where the melt tray heat exchanging device **134** is at a same vertical location or substantially a same vertical location with the working fluid reservoir **194, 294**. The melt tray heat exchanging device **134** may be at a same vertical location or substantially a same vertical location with the working fluid reservoir **194, 294** because the center **313** of the melt tray heat exchanging device **134** may be at a same vertical location or substantially a same vertical location as the center **312** of the working fluid reservoir **194, 294**. If the melt tray heat exchanging device **134** is not at the same vertical location or substantially the same vertical location with the working fluid reservoir **194, 294**, when the melt tray heat exchanging device **134** does not allow for mixing of vapor and liquid, only a single phase of the dual phase changing fluid may be within the melt tray heat exchanging device **134**, thereby leading to the disadvantages associated with a single phase fluid heat exchanging device.

[0160] The melt tray fluid **130** may be heated by at least one of the vapor stream rising from the lower section **106** and the melt tray heat exchanging device **134**. The melt tray fluid **130** helps melt the solids formed in the middle controlled freeze zone section **108** into the liquid slurry. Specifically, the heat transferred by the vapor stream heats up the liquid, thereby enabling the heat to melt the solids.

[0161] One or more bubble caps **132** may act as a channel for the vapor stream rising from the lower section **106** to the middle controlled freeze zone section **108**. Each bubble cap **132** may provide a path for the vapor stream that forces the vapor stream up the riser **140**

and then down and around the riser **140** to the melt tray **118**. The riser **140** is covered by a cap **141**. The cap **141** prevents the melt tray fluid **130** from travelling into the riser **140**. The cap **141** helps prevent solids from travelling into the riser **140**. The vapor stream's traversal through the bubble cap **132** allows the vapor stream to transfer heat to the melt tray fluid **130** within the melt tray assembly **139**.

[0162] The middle controlled freeze zone section **108** may comprise a spray assembly **129**. The spray assembly **129** cools the vapor stream that rises from the lower section **40**. The spray assembly **129** sprays liquid, which is cooler than the vapor stream, on the vapor stream to cool the vapor stream. The spray assembly **129** is within the upper section **39** of the middle controlled freeze zone section **108**. The spray assembly **129** is not within the lower section **40** of the middle controlled freeze zone section **108**. The spray assembly **129** is above the melt tray assembly **139**. In other words, the melt tray assembly **139** is below the spray assembly **129**.

[0163] The temperature of the vapor stream falls as it travels from the bottom of the middle controlled freeze zone section **108** to the top of the middle controlled freeze zone section **108**. The concentration of methane in the vapor stream rises as it moves from the middle controlled freeze zone section **108** to the upper section **110**. Some contaminants may remain in the methane and also rise. Substantially all contaminants in the vapor stream tend to condense or solidify with the colder temperatures and fall to the bottom of the middle controlled freeze zone section **108**.

[0164] The solids form the liquid slurry when in the melt tray fluid **130**. The liquid slurry flows from the middle controlled freeze zone section **108** to the lower distillation section **106**. The liquid slurry mix flows from the bottom of the middle controlled freeze zone section **108** to the top of the lower section **106** via line **22** (Figures 1-4). The line **22** may be an exterior line. The line **22** may extend from the distillation tower **104**, **204**. The line **22** may extend from the middle controlled freeze zone section **108**. The line may extend to the lower section **106**.

[0165] The steps depicted in Figure 8 are provided for illustrative purposes only and a particular step may not be required to perform the inventive methodology. Moreover, Figure 8 may not illustrate all the steps that may be performed. The claims, and only the claims, define the inventive system and methodology.

[0166] Disclosed aspects may be used in hydrocarbon management activities. As used herein, "hydrocarbon management" or "managing hydrocarbons" includes hydrocarbon

extraction, hydrocarbon production 507 (Figure 8), hydrocarbon exploration, identifying potential hydrocarbon resources, identifying well locations, determining well injection and/or extraction rates, identifying reservoir connectivity, acquiring, disposing of and/ or abandoning hydrocarbon resources, reviewing prior hydrocarbon management decisions, and
5 any other hydrocarbon-related acts or activities. The term “hydrocarbon management” is also used for the injection or storage of hydrocarbons or CO₂, for example the sequestration of CO₂, such as reservoir evaluation, development planning, and reservoir management. The disclosed methodologies and techniques may be used in extracting hydrocarbons from a subsurface region and processing the hydrocarbons. Hydrocarbons and contaminants may be
10 extracted from a reservoir and processed. The hydrocarbons and contaminants may be processed, for example, in the distillation tower previously described. After the hydrocarbons and contaminants are processed, the hydrocarbons may be extracted from the processor, such as the distillation tower, and produced. The contaminants may be discharged into the Earth, etc. For example, as shown in Figure 8, the method for producing
15 hydrocarbons may include producing the hydrocarbon-enriched vapor stream extracted from the distillation tower. The method may also include removing the hydrocarbon-enriched vapor stream from the distillation tower before producing the hydrocarbon-enriched vapor stream. The initial hydrocarbon extraction from the reservoir may be accomplished by drilling a well using hydrocarbon drilling equipment. The equipment and techniques used to
20 drill a well and/or extract these hydrocarbons are well known by those skilled in the relevant art. Other hydrocarbon extraction activities and, more generally, other hydrocarbon management activities, may be performed according to known principles.

[0167] It should be understood that the numerous changes, modifications, and alternatives to the preceding disclosure can be made without departing from the scope of the disclosure.
25 The preceding description, therefore, is not meant to limit the scope of the disclosure. Rather, the scope of the disclosure is to be determined only by the appended claims and their equivalents. It is also contemplated that structures and features in the present examples can be altered, rearranged, substituted, deleted, duplicated, combined, or added to each other.

CLAIMS

1. A method of controlling a temperature within a melt tray assembly of a distillation tower, comprising:

maintaining a controlled freeze zone section of the distillation tower that forms a solid and a vapor from a stream that enters the distillation tower;

maintaining a melt tray assembly, within the controlled freeze zone section, that comprises a melt tray fluid and a melt tray heat exchanging device within the melt tray fluid;

providing a phase changing fluid, to the melt tray heat exchanging device, that is configured to be a dual-phase heat transfer fluid;

determining a melt tray fluid composition of the melt tray fluid;

determining a melt tray fluid pressure of the melt tray fluid;

determining a melt tray fluid temperature of the melt tray fluid;

determining if the melt tray fluid temperature is within an expected melt tray fluid temperature range for the melt tray fluid composition and the melt tray fluid pressure, wherein the expected melt tray fluid temperature range has an expected melt tray fluid temperature range upper limit and an expected melt tray fluid temperature range lower limit;

decreasing the melt tray fluid temperature if the melt tray fluid temperature is greater than the expected melt tray fluid temperature range upper limit, increasing the melt tray fluid temperature if the melt tray fluid temperature is less than the expected melt tray fluid temperature range lower limit, and maintaining the melt tray fluid temperature if the melt tray fluid temperature is within the expected melt tray fluid temperature range.

2. The method of claim 1, wherein the phase changing fluid comprises a single-component fluid.

3. The method of claim 2, wherein the single-component fluid comprises one of ethane, ethylene, and trifluoromethane.

4. The method of claim 1, wherein determining the melt tray fluid composition comprises extracting a sample of the melt tray fluid; analyzing the sample of the melt tray fluid with a composition analyzer; and determining a percentage of components within the melt tray fluid.

5. The method of claim 4, wherein the components comprise at least one of methane, hydrogen sulfide, and carbon dioxide.
6. The method of claim 1, wherein determining the melt tray fluid temperature comprises sensing the melt tray fluid temperature with a temperature indicating controller.
7. The method of claim 6, wherein the temperature indicating controller comprises at least one of a thermocouple, thermowell, and resistance temperature detector.
8. The method of claim 1, wherein decreasing the melt tray fluid temperature comprises one of (i) decreasing a phase changing fluid pressure of the phase changing fluid and (ii) increasing a flow rate of reflux, from a reflux accumulator, exchanging heat with a working fluid.
9. The method of claim 8, wherein (i) occurs in a closed loop refrigeration system and (ii) occurs in an open loop refrigeration system.
10. The method of claim 1, wherein increasing the melt tray fluid temperature comprises one of (i) increasing a phase changing fluid pressure of the phase changing fluid and (ii) increasing a flow rate of feed refrigeration refrigerant, from a feed refrigeration refrigerant accumulator, exchanging heat with a working fluid.
11. The method of claim 10, wherein (i) occurs in a closed loop refrigeration system and (ii) occurs in an open loop refrigeration system.
12. The method of claim 1, wherein maintaining the melt tray fluid temperature comprises one of (i) maintaining a working fluid amount fed to the phase changing fluid and (ii) maintaining a flow rate of reflux, from a reflux accumulator, and feed refrigeration refrigerant, from a feed refrigeration refrigerant accumulator, to a fixed-volume phase changing fluid system.

13. The method of claim 12, wherein (i) occurs in a closed loop refrigeration system and (ii) occurs in an open loop refrigeration system.
14. The method of claim 1, wherein the expected melt tray fluid temperature range is between -65 °F (-53.9 °C) to -100 °F (-73.3°C).
15. The method of claim 1, further comprising:
producing hydrocarbon fluids from the distillation tower.
16. The method of claim 1, wherein the melt tray heat exchanging device comprises a wick.
17. The method of claim 16, wherein the wick comprises a substantially liquid core portion and a substantially vapor portion, wherein the substantially liquid core portion receives liquid of the phase changing fluid and the substantially vapor portion receives vapor of the phase changing fluid.
18. The method of claim 16, wherein the wick is substantially at a same vertical location as a working fluid reservoir.
19. The method of claim 16, wherein the wick is not substantially at the same vertical location as a working fluid reservoir.
20. The method of claim 1, wherein the phase changing fluid comprises an azeotropic blend.
21. A system of controlling a temperature within a melt tray assembly of a distillation tower, comprising:
a distillation tower configured to process a stream, wherein the distillation tower comprises a controlled freeze zone section that separates the stream into solids and vapor, the controlled freeze zone section having a melt tray assembly including a melt tray fluid and a melt tray heat exchanging device within the melt tray fluid, wherein the melt tray heat

exchanging device holds a phase changing fluid that is a dual-phase heat transfer fluid;

a control system that determines if a melt tray fluid temperature of the melt tray fluid is within an expected melt tray fluid temperature range for a melt tray fluid composition and pressure of the melt tray fluid; and

a melt tray temperature conditioning system that feeds the phase changing fluid to the melt tray heat exchanging device and is configured to modify a melt tray fluid temperature of the melt tray fluid if the melt tray fluid temperature is outside of the expected melt tray fluid temperature range.

22. The system of claim 21, wherein the phase changing fluid comprises a single-component fluid.

23. The system of claim 21, wherein the expected melt tray fluid temperature range is between -65 °F (-53.9 °C) to -100 °F (-73.3°C).

24. The system of claim 21, wherein the melt tray temperature conditioning system comprises a closed loop melt tray temperature conditioning system.

25. The system of claim 24, wherein the closed loop melt tray temperature conditioning system comprises a working fluid reservoir, that holds working fluid and that feeds the working fluid to the melt tray heat exchanging device, an overhead refrigeration refrigerant accumulator, that holds the working fluid and is configured to selectively feed the working fluid to the working fluid reservoir, and an heat exchanger that is configured to selectively receive the working fluid from the working fluid reservoir.

26. The system of claim 25, wherein the working fluid comprises one of ethane, propane, carbon dioxide, and a single halogenated hydrocarbon.

27. The system of claim 21, wherein the melt tray heat exchanging device comprises a wick.

28. The system of claim 27, wherein the wick comprises a substantially liquid core

portion an a substantially vapor portion, wherein the substantially liquid core portion receives liquid of the phase changing fluid and the substantially vapor portion receives vapor of the phase changing fluid.

29. The system of claim 21, wherein the phase changing fluid comprises an azeotropic blend.

30. The system of claim 21, wherein the melt tray temperature conditioning system comprises an open loop melt tray conditioning system.

31. The system of claim 30, wherein the open loop melt tray temperature conditioning system comprises a refrigerant accumulator, the refrigerant accumulator comprising reflux that is configured to cool a working fluid reservoir, and a feed refrigeration refrigerant accumulator, the feed refrigeration refrigerant accumulator comprising refrigerant that is configured to heat the working fluid reservoir, when the melt tray fluid temperature is below the expected melt tray fluid temperature range.

32. The system of claim 31, wherein the feed refrigeration refrigerant accumulator comprises a pressure-containing vessel.

33. The system of claim 30, wherein the open loop melt tray temperature conditioning system further comprises a working fluid make-up tank that is configured to one of receive the working fluid from the working fluid reservoir and to feed the working fluid to the working fluid reservoir, when the melt tray fluid temperature is below of the expected melt tray fluid temperature range.