

PROCESSING MATERIALS

CROSS REFERENCE TO RELATED APPLICATIONS

This application claims priority from the following provisional applications:

- 5 USSN 61/774,684, filed March 8, 2013; USSN 61/774,773, filed March 8, 2013; USSN 61/774,731, filed March 8, 2013; USSN 61/774,735, filed March 8, 2013; USSN 61/774,740, filed March 8, 2013; USSN 61/774,744, filed March 8, 2013; USSN 61/774,746, filed March 8, 2013; USSN 61/774,750, filed March 8, 2013; USSN 61/774,752, filed March 8, 2013; USSN 61/774,754, filed March 8, 2013; USSN 10 61/774,775, filed March 8, 2013; USSN 61/774,780, filed March 8, 2013; USSN 61/774,761, filed March 8, 2013; USSN 61/774,723, filed March 8, 2013; and USSN 61/793,336, filed March 15, 2013. The full disclosure of each of these provisional applications is incorporated by reference herein.

15

BACKGROUND

Many potential lignocellulosic feedstocks are available today, including agricultural residues, woody biomass, municipal waste, oilseeds/cakes and seaweed, to name a few. At present, these materials are often under-utilized, being used, for example, as animal feed, biocompost materials, burned in a co-generation facility or even 20 landfilled.

Lignocellulosic biomass includes crystalline cellulose fibrils embedded in a hemicellulose matrix, surrounded by lignin. This produces a compact matrix that is difficult to access by enzymes and other chemical, biochemical and/or biological processes. Cellulosic biomass materials (*e.g.*, biomass material from which the lignin 25 has been removed) is more accessible to enzymes and other conversion processes, but even so, naturally-occurring cellulosic materials often have low yields (relative to theoretical yields) when contacted with hydrolyzing enzymes. Lignocellulosic biomass is even more recalcitrant to enzyme attack. Furthermore, each type of lignocellulosic biomass has its own specific composition of cellulose, hemicellulose and lignin.

30

SUMMARY

Generally the inventions relate to methods, equipment and systems for processing materials, such as biomass. For example, processes are disclosed herein for saccharifying or liquifying a biomass material, *e.g.*, cellulosic, lignocellulosic and/or starchy feedstocks, by converting biomass material to low molecular weight sugars, *e.g.*, saccharifying the feedstock using an enzyme, *e.g.*, one or more cellulase and/or amylase. The invention also relates to converting a feedstock to a product, *e.g.*, by bioprocessing, such as fermentation. Novel systems, methods and equipment for conveying and/or cooling materials, such as biomass materials, that have been treated, *e.g.*, to reduce their recalcitrance are described herein. Cooling (which can occur during conveying) materials after any treatment or processes described herein can enhance processing rates and can prepare the materials for additional treatments or processes without delay. For example, if it is desired to treat a biomass material to a total dose that would exceed its decomposition temperature if treated without sufficient cooling, it is advantageous to parse the total dose into two or more doses with cooling between doses.

In one aspect the invention relates to a method of handling materials, *e.g.*, biomass, including conveying a recalcitrance-reduced biomass along the interior portions of a screw conveyor. The methods can include delivering the biomass to a feed inlet and also optionally discharging the biomass through an outlet of the screw conveyor. Optionally, the method includes treating the biomass with accelerated electrons to reduce its recalcitrance, for example, wherein the electrons have an energy between about 0.3 MeV and about 5 MeV, such as between about 0.5 MeV and about 3.5 MeV, or between about 0.8 MeV and about 2 MeV. Optionally, prior to conveying (*e.g.*, with the screw conveyor), the biomass receives a dose between about 0.5 Mrad and about 50 Mrad, such as between about 1 Mrad and 20 Mrad, between about 1 Mrad and about 15 Mrad, or between about 5 Mrad and about 15 Mrad.

In some implementation the interior portions along which the biomass is conveyed, such as screw shaft, flighting and/or housing, are cooled. For example, the interior portions are cooled using a chilled liquid, such as water or glycol water mixtures. Optionally, the chilled water is chilled utilizing a cooling tower and/or geothermal cooling.

In some other implementations, the conveyor has a biomass inlet and a biomass discharge and the difference in temperature between the biomass at the inlet and the

discharge is less than about 110 °C (*e.g.*, less than about 75 °C, less than about 50 °C, less than about 25 °C).

In other implementations, the method further includes comminuting the biomass material while conveying the biomass material *e.g.*, by shredding and/or shearing.

- 5 Optionally an additive is combined with the biomass material prior to, during or after conveying the treated biomass material, for example, the additive can include, water, an acid, such as sulfuric or hydrochloric or phosphoric acid, a base, a metal, a resin, an inorganic material, and mixtures of these.

- 10 In another aspect the invention relates to a method of processing a material, *e.g.*, a biomass material, including providing a material to a first treatment cell equipped with a first electron beam device, and irradiating the material using the first electron beam device. The method also includes cooling and conveying the material with a screw conveyor from the first treatment cell. Optionally, the method further includes conveying (*e.g.*, while cooling) the material with the screw conveyor from the first treatment cell to
- 15 a second treatment cell equipped with a second electron beam generator and irradiating the material with an electron beam using the second electron beam device. The screw conveyor can include interior portions such as screw shaft, flighting and/or housing that is cooled, *e.g.*, cooled using a chilled liquid, such as water or glycol water mixtures. Optionally cooling reduces the temperature of the material by between about 1 °C and
- 20 about 110 °C (*e.g.*, between about 10 °C and about 75 °C, between about 10 °C and about 50 °C). Optionally the total dose delivered by the irradiation is between about 1 and 200 Mrad (*e.g.*, between about 10 and about 200 Mrad, between about 10 Mrad and about 50 Mrad, between about 20 Mrad and about 40 Mrad, between about 25 and about 35 Mrad). In some cases, the temperature (*e.g.*, the temperature of the biomass) during
- 25 the irradiation does not exceed about 200 °C (*e.g.*, does not exceed about 180 °C, does not exceed about 160 °C, does not exceed about 150 °C, does not exceed about 140 °C, does not exceed about 130 °C, does not exceed about 120 °C, does not exceed about 110 °C). Optionally, the temperature of the material during irradiation increases by
- 30 between about 10 °C and about 250 °C (*e.g.*, between about 10 °C and about 150 °C, between about 50 °C and about 150 °C, between about 75 °C and about 150 °C).

Optionally the screw conveyors described in the methods and systems herein can include two or more screws.

- 35 In some implementations of the inventions described herein, the material includes biomass material such as cellulosic and/or lignocellulosic material. For example, the biomass can be selected from the group consisting of wood, particle board, sawdust,

agricultural waste, sewage, silage, grasses, rice hulls, bagasse, cotton, jute, hemp, flax, bamboo, sisal, abaca, straw, corn cobs, corn stover, switchgrass, alfalfa, hay, coconut hair, seaweed, algae and mixtures of these.

Implementations of the invention can optionally include one or more of the
5 following summarized features. In some implementations, the selected features can be applied or utilized in any order while in other implementations a specific selected sequence is applied or utilized. Individual features can be applied or utilized more than once in any sequence and even continuously. In addition, an entire sequence, or a portion of a sequence, of applied or utilized features can be applied or utilized once, repeatedly
10 or continuously in any order. In some optional implementations, the features can be applied or utilized with different, or where applicable the same, set or varied, quantitative or qualitative parameters as determined by a person skilled in the art. For example, parameters of the features such as size, individual dimensions (*e.g.*, length, width, height), location of, degree (*e.g.*, to what extent such as the degree of
15 recalcitrance), duration, frequency of use, density, concentration, intensity and speed can be varied or set, where applicable as determined by a person of skill in the art.

Features, for example, include: a method of handling and/or processing material; conveying recalcitrance-reduced material along interior portions of a screw conveyor; delivering a material to a feed inlet of a screw conveyor; discharging a material through
20 an outlet of the screw conveyor; treating a material with accelerated electrons to reduce its recalcitrance; treating a material with accelerated electrons having an energy between about 0.3 MeV and about 5 MeV; treating a material with accelerated electrons having an energy between about 0.5 MeV and about 3.5 MeV; treating a material with accelerated electrons having an energy between about 0.8 MeV and about 2 MeV;
25 irradiating a material with dose between about 0.5 Mrad and about 20 Mrad and then conveying the material; irradiating a material with dose between about 1 Mrad and about 15 Mrad and then conveying the material; irradiating a material with dose between about 5 Mrad and about 15 Mrad and the conveying the material; conveying a material with a screw conveyor wherein interior portions of a screw conveyor along which
30 material is conveyed are cooled; conveying a material with a screw conveyor wherein the screw shaft of the screw conveyor is cooled; conveying a material with a screw conveyor wherein the flighting of the screw conveyor is cooled; conveying a material with a screw conveyor wherein the housing of the screw conveyor is cooled; conveying a material with a screw conveyor wherein interior portions of the screw are cooled using a chilled
35 liquid; conveying a material with a screw conveyor wherein the interior portions of a

screw conveyor are cooled using water; conveying a material with a screw conveyor wherein interior portions of the screw conveyor are cooled using a glycol water mixture; cooling of chilled water used for cooling a screw conveying material is chilled utilizing a cooling tower and/or geothermal cooling; a conveyer having a material inlet and a material discharge and the difference in temperature between the material at the inlet and the discharge is less than about 110°C; a conveyer having a material inlet and a material discharge and the difference in temperature between the material at the inlet and the discharge is less than about 75°C; a conveyer having a material inlet and a material discharge and the difference in temperature between the material at the inlet and the discharge is less than about 50°C; a conveyer having a material inlet and a material discharge and the difference in temperature between the material at the inlet and the discharge is less than about 25°C; comminuting a material while conveying the material; shredding a material while conveying the material; shearing a material while conveying the material; water is combined with a material prior to conveying the material; water is combined with a material after conveying the material; water is combined with a material during conveying the material; an acid is combined with a material prior to conveying the material; an acid is combined with a material after conveying the material; an acid is combined with a material while conveying the material; a base is combined with a material prior to conveying the material; a base is combined with a material after conveying the material; a base is combined with a material during conveying the material; a metal is combined with a material prior to conveying the material; a metal is combined with a material after conveying the material; a metal is combined with a material during conveying the material; a resin is combined with a material prior to conveying the material; a resin is combined with a material after conveying the material; a resin is combined with a material while conveying the material; an inorganic material is combined with a material prior to conveying the material; an inorganic material is combined with a material after conveying the material; an inorganic material is combined with a material during conveying the material; sulfuric acid is combined with a material prior to conveying the material; sulfuric acid is combined with a material after conveying the material; sulfuric acid is combined with a material during conveying the material; hydrochloric acid is combined with a material prior to conveying the material; hydrochloric acid is combined with a material after conveying the material; hydrochloric acid is combined with a material while conveying the material; phosphoric acid is combined with a material prior to conveying the material; phosphoric acid is combined with a material after conveying the material; phosphoric acid is combined with a material

while conveying the material; a material is provided to a first treatment cell equipped with a first electron beam device; irradiating a material in a first treatment cell with an electron beam using a first electron beam device; conveying a material with a screw conveyor from a first treatment cell; conveying a material to a second treatment cell

5 equipped with a second electron beam device and irradiating the material with a second electron beam; cooling a material using a screw conveyor by between about 1°C and 110°C; cooling a material using a screw conveyor by between about 10°C and about 75 °C; cooling a material using the screw conveyor by between about 10°C and about 50°C; delivering a total dose of irradiation between about 1 and 200 Mrad to a material;

10 delivering a total dose of irradiation between about 10 Mrad and about 50 Mrad to a material is; delivering a total dose of irradiation between about 20 Mrad and about 40 Mrad to a material; irradiating a material wherein the temperature of the material during the irradiation does not exceed about 200°C; irradiating a material wherein the temperature of the material during the irradiation does not exceed about 180°C;

15 irradiating a material wherein the temperature of the material during the irradiation does not exceed about 160°C; irradiating a material wherein the temperature of the material during the irradiation does not exceed about 150°C; irradiating a material wherein the temperature of the material during the irradiation does not exceed about 140°C;

irradiating a material wherein the temperature of the material during the irradiation does not exceed about 130°C; irradiating a material wherein the temperature of the material during the irradiation does not exceed about 120°C; irradiating a material wherein the temperature of the material during the irradiation does not exceed about 110°C;

20 irradiating a material wherein the temperature of the material during irradiation increases by between about 10°C and about 250°C; irradiating a material wherein the temperature of the material during irradiation increases by between about 10 °C and about 150°C;

25 irradiating a material wherein the temperature of the material during irradiation increases by between about 50°C and about 150°C; irradiating a material wherein the temperature of the material during irradiation increases by between about 75°C and about 150°C;

processing a biomass material; processing a lignocellulosic material; processing wood;

30 processing particle board; processing sawdust; processing agricultural waste; processing sewage; processing silage; processing grasses; processing rice hulls; processing bagasse; processing cotton; processing jute; processing hemp; processing flax; processing bamboo; processing sisal; processing abaca; processing straw; processing corn cobs; processing corn stover; processing switchgrass; processing alfalfa; processing hay;

processing coconut hair; processing seaweed; processing algae; conveying a material using two or more screw conveyors.

All publications, patent applications, patents, and other references mentioned herein or attached hereto are incorporated by reference in their entirety for all that they
5 contain.

DESCRIPTION OF THE DRAWINGS

FIG. 1A is a diagrammatic view showing an example of a cooling system according to one embodiment. FIG. 1B is a detailed view of a portion of the cooling
10 system.

FIG. 2A is an enlarged cross sectional view of a portion of the cooling system shown in FIG. 1. FIG. 2B is an enlarged cross sectional view of another possible embodiment of a portion of the cooling system.

DETAILED DESCRIPTION

Using the methods described herein, many materials such as biomass (*e.g.*, plant biomass, animal biomass, paper, and municipal waste biomass) can be processed to produce useful intermediates and products such as sugars, sugar alcohols, organic acids,
20 salts of organic acids, anhydrides, esters of organic acids and fuels, *e.g.*, fuels for internal combustion engines or feedstocks for fuel cells. Included herein are many methods that involve saccharification of biomass to produce sugars, and in some cases fermentation of the resulting sugars to form other products and/or intermediates. Methods and materials described herein include controlling the temperatures during and/or after treatment steps
25 to reduce or eliminate destruction (*e.g.*, decomposition) of the treated material.

Cooling biomass materials that have been treated, *e.g.*, treated to reduce their recalcitrance, are described herein. For example, the material can be irradiated as described herein which can increase the temperature of the biomass, for example, increasing the temperature of the biomass by between about 10 °C and about 250 °C
30 (*e.g.*, between about 10 °C and 200 °C, between about 10 °C and 150 °C, between about 10 °C and 100 °C, between about 20 °C and about 100 °C, between about 20 and 75 °C, between about 50 °C and about 200 °C, between about 50 °C and 150 °C, between about 75 °C and about 150 °C).

Cooling materials after any such treatment or process described herein can
35 enhance processing rates and reduce losses, *e.g.*, losses due to thermal decomposition, and

can prepare the treated or processed material for additional treatments or processes without delay. Referring to FIG. 1A, cooling water can be piped to an inlet **10** of a geothermal ground loop **12**, which further removes heat above that obtained from a cooling water tower. The geothermal ground loop **12** includes a tortuous length of pipe **14** (e.g., copper or plastic) that is embedded through foundation **30**. In some instances, the pipe **14** is installed when the foundation is poured, and the foundation is used in an area of the plant that requires a thick foundation pad, for example an area containing the irradiation equipment discussed below. In some alternative embodiments the geothermal ground loop is located in another area, for example, away from any buildings, equipment and/or foundations so that it can be easy to access (e.g., dug out). For example, the geothermal ground loop can be in an area that would not serve for other construction, such as under a pond. In some alternative embodiments an open geothermal loop or a closed geothermal loop can be utilized. Open and closed geothermal loop options are discussed in "Recommendations for Geothermal Heating and Cooling Systems", Ohio Water Resources Council, State Coordinating Committee on Ground Water, Feb. 2012, accessed online at the website <http://wwwapp.epa.ohio.gov/ddagw/SCCGW/Documents/GHCS.pdf>, March 3, 2013 the entire disclosure of which is herein incorporated by reference. Foundation **30** is shown in FIG. 1A supporting a vault for irradiation of biomass, while ground is not shown so as not to obscure the views of the foundation and buried tubing. In some embodiments the geothermal loop can be completely embedded in the foundation. Water leaves the geothermal ground loop **12** at exit **20**, at a temperature of about 55°F, and enters the casing of conveyor **16**, e.g., an ash cooler, the structure of which will be discussed below with reference to FIG. 2A and B, through an inlet **17**. A motor for driving the shaft of **16** can be enclosed in enclosure **60**. The temperature of the water entering the ash cooler **16** is sufficiently low so that the water will be able to cool biomass that has been heated to a temperature of about 75 to 150 °F, which enters the ash cooler through an inlet **18**. Cooled biomass, at a temperature of about 73°F, exits the ash cooler **16** through a biomass outlet **19** while the cooling water, which has now returned to an elevated temperature, exits through a water outlet tube **22**. The temperature difference between the inlet and outlet of the cooler can be less than about 110 deg. C (e.g., less than about 75 deg. C, less than about 50 deg. C, less than about 25 deg. C). The material can be cooled, for example, by between about 1 °C and about 110 °C (e.g., between about 10 °C and about 75 °C, between about 10 °C and about 50 °C).

FIG. 1B is a detailed front view of a bag filter in fluid communication with a closed loop air conveyor and ash cooler **16**. Biomass is conveyed in a gas (*e.g.*, air by pneumatic conveying) to the bag filter through pneumatic pipe **46**. The bag filter traps fine biomass particles and allows larger biomass particles to drop through the inlet **18** of the ash cooler **16** as indicated by the arrow. A rotary valve positioned at **50** and driven by motor **52** can control the flow of biomass and gases. Gas is returned to complete the circuit of the closed air loop conveyor by pipe **48**. Gas is also drawn off into flow chamber **40**. Optionally, flow chamber **40** can include gas abatement systems (such as air pollution control technologies), *e.g.*, a carbon filter, for removal of ozone, volatile organic carbon compounds and/or hazardous air pollutants. A fan **42** (*e.g.*, an axial fan) draws air through the flow chamber in the direction shown by the arrows drawn in chamber **40** and out into the atmosphere through outlet **44**. Optionally the outlet air flows through chamber **40** at a rate of about 300 ft³/min (*e.g.* between about 20 and 1000 ft³/min, between about 50 and 500 ft³/min, between about 100 and 400 ft³/min). Air flow in the closed loop air conveyor is from about the same as the air flow exiting outlet **44**, to higher than the flow in the closed loop conveyor. The air flow exiting the outlet can be about 1 to 10 times higher than the flow of air in the closed air loop conveyor (*e.g.*, 1 to 6 times, 1 to 3 times, 1 to 2 times).

Referring to FIG. 2A which is a side cross-sectional view of a cooling conveyor, cooling water flows through a casing **23**, which includes an inner shell **25** and an outer shell **27** that define a space there between for fluid flow. Hot biomass (*e.g.*, at a temperature T₁) is conveyed through **16** (*e.g.*, ash cooler) by a screw conveyor that comprises a rotating screw **24**. The shaft **26** and flight **28** of the screw **24** are hollow, and are also cooled by recirculating water from the geothermal ground loop **12**. A drive motor (not shown) is mechanically connected to the shaft providing the torque needed to rotate the shaft and screw.

In **16**, the biomass particles are subjected to continuous movement by the helices of the screw **25** and are constantly changing location. This causes them, as they move through the conveyor, to come into frequent and repeated contact with the internal surfaces of the conveyor that are cooled because they are in thermal communication with the cooling water, *e.g.*, the outer surface of screw **24** and inner shell **25**. The rotation, conveying, interfolding and dispersing action increases the heat exchange between the biomass and the cooling fluids in the screw and casing. Therefore, the temperature of the biomass exiting the screw cooler (T₂) is lower than the temperature of the biomass entering the screw cooler (*e.g.*, T₁>T₂).

In some embodiments the ash cooler includes more than one screw. For example, FIG 2B is a top cross-sectional view of a cooling screw conveyor with two screws. The screw conveyors can intermesh as shown. The dual screw conveyor has similar components as the single screw conveyor but has a larger internal volume containing the two screws. Hot biomass enters (*e.g.*, drops into) the cooler through inlet **218** on the top of the conveyor and moves through the cooler, for example as shown by the arrows, due to the screwing/turning/conveying action of the screws **224**. The cooled biomass exits (*e.g.*, drops out of) the screw conveyor through outlet **220** disposed on the underside of the conveyor. Cooling water flows through casing **223**, which includes inner shell **225** and outer shell **227** that define a space there between for fluid flow. The shafts **226** and flights **228** of the screws **224** are hollow, and are cooled by recirculating water from geothermal ground loop **12**. In other embodiments, three, four, five, six or even more screws can be used in the cooling conveyor. As, in the single screw embodiment, the temperature of the biomass entering the screw cooler (T1) is greater than the temperature of the biomass (T2) exiting the screw cooler.

The conveyors (*e.g.*, the flights, shaft, inner shell of a screw cooler) can be made of or coated with corrosion resistant materials. For example, the conveyors can utilize structural materials that include stainless steel (*e.g.*, 304, 316 stainless steel, HASTELLOY® ALLOYS and INCONEL® Alloys). For example, HASTELLOY® Corrosion-Resistant alloys from Hynes (Kokomo, Indiana, USA) such as HASTELLOY® B-3® ALLOY, HASTELLOY® HYBRID-BC1® ALLOY, HASTELLOY® C-4 ALLOY, HASTELLOY® C-22® ALLOY, HASTELLOY® C-22HS® ALLOY, HASTELLOY® C-276 ALLOY, HASTELLOY® C-2000® ALLOY, HASTELLOY® G-30® ALLOY, HASTELLOY® G-35® ALLOY, HASTELLOY® N ALLOY and HASTELLOY® ULTIMET® alloy. For example, some coatings that can be utilized and corresponding microhardness are listed here: Titanium nitride (TiN: 2300 HV 0.05), Aluminum Chromium Nitride (AlCrN: 3200 HV 0.05), Titanium Carbide Nitride (TiCN: 3000 HV 0.05), Tungsten Carbide/Carbon (WC/C: 1500HV0.05/1000 HV 0.05), Chromium Nitride (CrN: 1750 HV 0.05), Diamond-Like Carbon (DLC: >2000 HV 0.05), Titanium Aluminum Nitride (TiAlN: 3300 HV 0.05 and TiAlNx: 3400 HV 0.05), Titanium Chromium Nitride (TiCrN: 2100 HV 0.05). In some embodiments, a coating process known as TDX is used which is a process is ideally suited for severe applications. The TDX coating is applied in a molten salt bath resulting in a very uniform and smooth layer of carbides. The TDX carbides are metallurgically bonded to the tooling resulting in extremely high adhesion strength and peel resistance.

The hardness values of TDX coatings are about 4200 Vickers. For example, some optional coatings can be provided by Tool Dynamics Inc (Columbus, IN) such as TDX Supreme I, TDX Supreme II and TDX Supreme III.

Coatings can be applied by methods such as physical vapor deposition (PVD),
5 Thermal spray, HVOF (a high velocity, low temperature coating process), plasma spray, Arc spray and electroplating. The coatings can provide protection for various kinds of wear, for example, impact wear, abrasion, erosion, compression, cavitation, galling, corrosion and oxidation.

Conveyors that can be used for the methods herein described (*e.g.*, cooling
10 conveyors, ash coolers, heat exchange conveyors) include conveyors that can be purchased. For example from AFM Bruns (Germany), Zhengzhou Yufeng Heavy Machinery Co., Ltd. (China), Therma-Flite Inc. (USA) Qingdao Shongdian Energy Equipment Co., Ltd. (China), Magalidi Industrie S.R.L (Italy), Quigdao Zhongdian Energy equipment Co. Ltd. (China) and Jiangsu Hongbang Environment Engineering
15 Co. Ltd. (China), Xinxian Shengxiang Material Trading Co. Ltd and Thomas Conveyor (USA). The conveyors can be purchased and also modified (*e.g.*, with coatings, etc.)

The cooling water can be replaced by other cooling fluids, for example, an oil and/or an alcohol (*e.g.*, ethanol, butanol and/or glycol). Mixtures of water and alcohols can also be utilized, *e.g.*, water with ethanol, water with glycol. For example, water
20 glycol mixtures with between about 5% and 80% glycol can be used (*e.g.*, between 5 and 20%, between about 10 and 50%, between about 10 and 30%, between about 40 and 60%). Other additives can be added, for example bactericides, bacteriostatic agents and or anti-corrosion agents.

In some implementations, an additive is combined with the treated biomass
25 material either prior to, during or after, conveying the treated material. For example, the additive may be an additive selected from the group consisting of water, an acid, a base, a metal, a resin, an inorganic material, and a mixture of these.

In some implementations, the biomass and or other material may be comminuted (*e.g.*, shredding, ripping and/or tearing the materials) in/by the ash cooler. For example,
30 the flight can be notched or the gap between the flight and the inner shell **25** of the screw conveyor is large enough to grind material there between. In configurations where more than one screw are used, the screws can be positioned to increase and/or decrease shearing and ripping, for example, by intermeshing the screws and/or bringing the surfaces of the flights closer or further to each other. Alternatively, the screw conveyor
35 can extrude material through a mesh (*e.g.*, wire mesh) or plate with holes.

The ash cooler can also be utilized for heating the biomass or any material conveyed therein. For example, by flowing a heating fluid (*e.g.*, oil or water) in the hollow screws, shaft and casing of the screw conveyors. For example, wherein the temperature of the biomass is increased by at least 20 °C (*e.g.*, at least 30 °C, at least 50 °C, at least 100 °C). After cooling, the biomass material may be returned to the recalcitrance treatment area for further treatment, *e.g.*, irradiation, or may be transferred to another processing step, such as saccharification.

In some embodiments, the cooling fluid from the screw cooler is coupled to a head exchanger that transfers energy to other processes, such as, a saccharification process. In such an embodiment, the heating due to processing of biomass is transferred to a saccharification step, *e.g.*, to heat the biomass, water and cellulase mixture to between about 40 °C and 60 °C.

Some more details and reiterations of processes for treating a feedstock that can be utilized, for example, with the embodiments already discussed above, or in other embodiments, are described in the following disclosures. In particular, the cooling systems discussed herein can be utilized, for example, in processes that include the feedstock treatment and processing steps described in the following sections.

SYSTEMS FOR TREATING A FEEDSTOCK

Processes for conversion of a feedstock to sugars and other products, in which the conveying methods discussed above may be used, can include, for example, optionally physically pre-treating the feedstock, *e.g.*, to reduce its size, before and/or after this treatment, optionally treating the feedstock to reduce its recalcitrance (*e.g.*, by irradiation), and saccharifying the feedstock to form a sugar solution. Saccharification can be performed by mixing a dispersion of the feedstock in a liquid medium, *e.g.*, water with an enzyme, as will be discussed in detail below. During or after saccharification, the mixture (if saccharification is to be partially or completely performed en route) or solution can be transported, *e.g.*, by pipeline, railcar, truck or barge, to a manufacturing plant. At the plant, the solution can be bioprocessed, *e.g.*, fermented, to produce a desired product or intermediate, which can then be processed further, *e.g.*, by distillation. The individual processing steps, materials used and examples of products and intermediates that may be formed will be described in detail below.

RADIATION TREATMENT

The feedstock can be treated with radiation to modify its structure to reduce its recalcitrance. Such treatment can, for example, reduce the average molecular weight of the feedstock, change the crystalline structure of the feedstock, and/or increase the surface area and/or porosity of the feedstock. Radiation can be by, for example electron beam, ion beam, 100 nm to 28 nm ultraviolet (UV) light, gamma or X-ray radiation. Radiation treatments and systems for treatments are discussed in U.S. No. Patent 8,142,620 and U.S. Patent Application Series No. 12/417,731, the entire disclosures of which are incorporated herein by reference.

Each form of radiation ionizes the biomass via particular interactions, as determined by the energy of the radiation. Heavy charged particles primarily ionize matter via Coulomb scattering; furthermore, these interactions produce energetic electrons that may further ionize matter. Alpha particles are identical to the nucleus of a helium atom and are produced by the alpha decay of various radioactive nuclei, such as isotopes of bismuth, polonium, astatine, radon, francium, radium, several actinides, such as actinium, thorium, uranium, neptunium, curium, californium, americium, and plutonium. Electrons interact via Coulomb scattering and bremsstrahlung radiation produced by changes in the velocity of electrons.

When particles are utilized, they can be neutral (uncharged), positively charged or negatively charged. When charged, the charged particles can bear a single positive or negative charge, or multiple charges, *e.g.*, one, two, three or even four or more charges. In instances in which chain scission is desired to change the molecular structure of the carbohydrate containing material, positively charged particles may be desirable, in part, due to their acidic nature. When particles are utilized, the particles can have the mass of a resting electron, or greater, *e.g.*, 500, 1000, 1500, or 2000 or more times the mass of a resting electron. For example, the particles can have a mass of from about 1 atomic unit to about 150 atomic units, *e.g.*, from about 1 atomic unit to about 50 atomic units, or from about 1 to about 25, *e.g.*, 1, 2, 3, 4, 5, 10, 12 or 15 atomic units.

Gamma radiation has the advantage of a significant penetration depth into a variety of material in the sample.

In embodiments in which the irradiating is performed with electromagnetic radiation, the electromagnetic radiation can have, *e.g.*, energy per photon (in electron volts) of greater than 10^2 eV, *e.g.*, greater than 10^3 , 10^4 , 10^5 , 10^6 , or even greater than 10^7 eV. In some embodiments, the electromagnetic radiation has energy per photon of

between 10^4 and 10^7 , *e.g.*, between 10^5 and 10^6 eV. The electromagnetic radiation can have a frequency of, *e.g.*, greater than 10^{16} Hz, greater than 10^{17} Hz, 10^{18} , 10^{19} , 10^{20} , or even greater than 10^{21} Hz. In some embodiments, the electromagnetic radiation has a frequency of between 10^{18} and 10^{22} Hz, *e.g.*, between 10^{19} to 10^{21} Hz.

5 Electron bombardment may be performed using an electron beam device that has a nominal energy of less than 10 MeV, *e.g.*, less than 7 MeV, less than 5 MeV, or less than 2 MeV, *e.g.*, from about 0.5 to 1.5 MeV, from about 0.8 to 1.8 MeV, or from about 0.7 to 1 MeV. In some implementations the nominal energy is about 500 to 800 keV.

10 The electron beam may have a relatively high total beam power (the combined beam power of all accelerating heads, or, if multiple accelerators are used, of all accelerators and all heads), *e.g.*, at least 25 kW, *e.g.*, at least 30, 40, 50, 60, 65, 70, 80, 100, 125, or 150 kW. In some cases, the power is even as high as 500 kW, 750 kW, or even 1000 kW or more. In some cases the electron beam has a beam power of 1200 kW or more, *e.g.*, 1400, 1600, 1800, or even 3000 kW.

15 This high total beam power is usually achieved by utilizing multiple accelerating heads. For example, the electron beam device may include two, four, or more accelerating heads. The use of multiple heads, each of which has a relatively low beam power, prevents excessive temperature rise in the material, thereby preventing burning of the material, and also increases the uniformity of the dose through the thickness of the
20 layer of material.

It is generally preferred that the bed of biomass material has a relatively uniform thickness. In some embodiments the thickness is less than about 1 inch (*e.g.*, less than about 0.75 inches, less than about 0.5 inches, less than about 0.25 inches, less than about 0.1 inches, between about 0.1 and 1 inch, between about 0.2 and 0.3 inches).

25 It is desirable to treat the material as quickly as possible. In general, it is preferred that treatment be performed at a dose rate of greater than about 0.25 Mrad per second, *e.g.*, greater than about 0.5, 0.75, 1, 1.5, 2, 5, 7, 10, 12, 15, or even greater than about 20 Mrad per second, *e.g.*, about 0.25 to 2 Mrad per second. Higher dose rates allow a higher throughput for a target (*e.g.*, the desired) dose. Higher dose rates generally
30 require higher line speeds, to avoid thermal decomposition of the material. In one implementation, the accelerator is set for 3 MeV, 50 mA beam current, and the line speed is 24 feet/minute, for a sample thickness of about 20 mm (*e.g.*, comminuted corn cob material with a bulk density of 0.5 g/cm^3).

In some embodiments, electron bombardment is performed until the material
35 receives a total dose of at least 0.1 Mrad, 0.25 Mrad, 1 Mrad, 5 Mrad, *e.g.*, at least 10,

20, 30 or at least 40 Mrad. In some embodiments, the treatment is performed until the material receives a dose of from about 10 Mrad to about 50 Mrad, *e.g.*, from about 20 Mrad to about 40 Mrad, or from about 25 Mrad to about 30 Mrad. In some implementations, a total dose of 25 to 35 Mrad is preferred, applied ideally over a couple
5 of passes, *e.g.*, at 5 Mrad/pass with each pass being applied for about one second. Cooling methods, systems and equipment can be used before, during, after and in between radiations, for example utilizing a cooling screw conveyor and/or a cooled vibratory conveyor.

Using multiple heads as discussed above, the material can be treated in multiple
10 passes, for example, two passes at 10 to 20 Mrad/pass, *e.g.*, 12 to 18 Mrad/pass, separated by a few seconds of cool-down, or three passes of 7 to 12 Mrad/pass, *e.g.*, 5 to 20 Mrad/pass, 10 to 40 Mrad/pass, 9 to 11 Mrad/pass. As discussed herein, treating the material with several relatively low doses, rather than one high dose, tends to prevent overheating of the material and also increases dose uniformity through the thickness of
15 the material. In some implementations, the material is stirred or otherwise mixed during or after each pass and then smoothed into a uniform layer again before the next pass, to further enhance treatment uniformity.

In some embodiments, electrons are accelerated to, for example, a speed of greater than 75 percent of the speed of light, *e.g.*, greater than 85, 90, 95, or 99 percent of
20 the speed of light.

In some embodiments, any processing described herein occurs on lignocellulosic material that remains dry as acquired or that has been dried, *e.g.*, using heat and/or reduced pressure. For example, in some embodiments, the cellulosic and/or lignocellulosic material has less than about 25 wt. % retained water, measured at 25°C
25 and at fifty percent relative humidity (*e.g.*, less than about 20 wt.%, less than about 15 wt.%, less than about 14 wt.%, less than about 13 wt.%, less than about 12 wt.%, less than about 10 wt.%, less than about 9 wt.%, less than about 8 wt.%, less than about 7 wt.%, less than about 6 wt.%, less than about 5 wt.%, less than about 4 wt.%, less than about 3 wt.%, less than about 2 wt.%, less than about 1 wt.%, or less than about 0.5
30 wt.%.

In some embodiments, two or more ionizing sources can be used, such as two or more electron sources. For example, samples can be treated, in any order, with a beam of electrons, followed by gamma radiation and UV light having wavelengths from about 100 nm to about 280 nm. In some embodiments, samples are treated with three ionizing
35 radiation sources, such as a beam of electrons, gamma radiation, and energetic UV light.

The biomass is conveyed through the treatment zone where it can be bombarded with electrons.

It may be advantageous to repeat the treatment to more thoroughly reduce the recalcitrance of the biomass and/or further modify the biomass. In particular, the process parameters can be adjusted after a first (*e.g.*, second, third, fourth or more) pass depending on the recalcitrance of the material. In some embodiments, a conveyor can be used which includes a circular system where the biomass is conveyed multiple times through the various processes described above. In some other embodiments, multiple treatment devices (*e.g.*, electron beam generators) are used to treat the biomass multiple (*e.g.*, 2, 3, 4 or more) times. In yet other embodiments, a single electron beam generator may be the source of multiple beams (*e.g.*, 2, 3, 4 or more beams) that can be used for treatment of the biomass.

The effectiveness in changing the molecular/supramolecular structure and/or reducing the recalcitrance of the carbohydrate-containing biomass depends on the electron energy used and the dose applied, while exposure time depends on the power and dose. In some embodiments, the dose rate and total dose are adjusted so as not to destroy (*e.g.*, char or burn) the biomass material. For example, the carbohydrates should not be damaged in the processing so that they can be released from the biomass intact, *e.g.* as monomeric sugars.

In some embodiments, the treatment (with any electron source or a combination of sources) is performed until the material receives a dose of at least about 0.05 Mrad, *e.g.*, at least about 0.1, 0.25, 0.5, 0.75, 1.0, 2.5, 5.0, 7.5, 10.0, 15, 20, 25, 30, 40, 50, 60, 70, 80, 90, 100, 125, 150, 175, or 200 Mrad. In some embodiments, the treatment is performed until the material receives a dose of between 0.1-100 Mrad, 1-200, 5-200, 10-200, 5-150, 50-150 Mrad, 5-100, 5-50, 5-40, 10-50, 10-75, 15-50, 20-35 Mrad.

In some embodiments, relatively low doses of radiation are utilized, *e.g.*, to increase the molecular weight of a cellulosic or lignocellulosic material (with any radiation source or a combination of sources described herein). For example, a dose of at least about 0.05 Mrad, *e.g.*, at least about 0.1 Mrad or at least about 0.25, 0.5, 0.75, 1.0, 1.5, 2.0, 2.5, 3.0, 3.5, 4.0, or at least about 5.0 Mrad. In some embodiments, the irradiation is performed until the material receives a dose of between 0.1 Mrad and 2.0 Mrad, *e.g.*, between 0.5 Mrad and 4.0 Mrad or between 1.0 Mrad and 3.0 Mrad. It also can be desirable to irradiate from multiple directions, simultaneously or sequentially, in order to achieve a desired degree of penetration of radiation into the material. For example, depending on the density and moisture content of the material,

such as wood, and the type of radiation source used (*e.g.*, gamma or electron beam), the maximum penetration of radiation into the material may be only about 0.75 inch. In such cases, a thicker section (up to 1.5 inch) can be irradiated by first irradiating the material from one side, and then turning the material over and irradiating from the other side.

- 5 Irradiation from multiple directions can be particularly useful with electron beam radiation, which irradiates faster than gamma radiation but typically does not achieve as great a penetration depth.

RADIATION OPAQUE MATERIALS

10

As previously discussed, the invention can include processing the material in a vault and/or bunker that is constructed using radiation opaque materials. In some implementations, the radiation opaque materials are selected to be capable of shielding the components from X-rays with high energy (short wavelength), which can penetrate
15 many materials. One important factor in designing a radiation shielding enclosure is the attenuation length of the materials used, which will determine the required thickness for a particular material, blend of materials, or layered structure. The attenuation length is the penetration distance at which the radiation is reduced to approximately $1/e$ (e =
Eulers number) times that of the incident radiation. Although virtually all materials are
20 radiation opaque if thick enough, materials containing a high compositional percentage (*e.g.*, density) of elements that have a high Z value (atomic number) have a shorter radiation attenuation length and thus if such materials are used a thinner, lighter shielding can be provided. Examples of high Z value materials that are used in radiation
shielding are tantalum and lead. Another important parameter in radiation shielding is
25 the halving distance, which is the thickness of a particular material that will reduce gamma ray intensity by 50%. As an example for X-ray radiation with an energy of 0.1 MeV the halving thickness is about 15.1 mm for concrete and about 2.7 mm for lead, while with an X-ray energy of 1 MeV the halving thickness for concrete is about 44.45 mm and for lead is about 7.9 mm. Radiation opaque materials can be materials that are
30 thick or thin so long as they can reduce the radiation that passes through to the other side. Thus, if it is desired that a particular enclosure have a low wall thickness, *e.g.*, for light weight or due to size constraints, the material chosen should have a sufficient Z value and/or attenuation length so that its halving length is less than or equal to the desired wall thickness of the enclosure.

In some cases, the radiation opaque material may be a layered material, for example having a layer of a higher Z value material, to provide good shielding, and a layer of a lower Z value material to provide other properties (*e.g.*, structural integrity, impact resistance, etc.). In some cases, the layered material may be a "graded-Z"

5 laminate, *e.g.*, including a laminate in which the layers provide a gradient from high-Z through successively lower-Z elements. In some cases the radiation opaque materials can be interlocking blocks, for example, lead and/or concrete blocks can be supplied by NIELCO Worldwide (Burlington, MA), and reconfigurable vaults can be utilized.

A radiation opaque material can reduce the radiation passing through a structure
10 (*e.g.*, a wall, door, ceiling, enclosure, a series of these or combinations of these) formed of the material by about at least about 10 %, (*e.g.*, at least about 20%, at least about 30%, at least about 40%, at least about 50%, at least about 60%, at least about 70%, at least about 80%, at least about 90%, at least about 95%, at least about 96%, at least about 97%, at least about 98%, at least about 99%, at least about 99.9%, at least about 99.99%,
15 at least about 99.999%) as compared to the incident radiation. Therefore, an enclosure made of a radiation opaque material can reduce the exposure of equipment/system/components by the same amount. Radiation opaque materials can include stainless steel, metals with Z values above 25 (*e.g.*, lead, iron), concrete, dirt, sand and combinations thereof. Radiation opaque materials can include a barrier in the
20 direction of the incident radiation of at least about 1mm (*e.g.*, 5 mm, 10mm, 5 cm, 10 cm, 100cm, 1m, 10m).

RADIATION SOURCES

25 The type of radiation determines the kinds of radiation sources used as well as the radiation devices and associated equipment. The methods, systems and equipment described herein, for example, for treating materials with radiation, can utilized sources as described herein as well as any other useful source.

Sources of gamma rays include radioactive nuclei, such as isotopes of cobalt, calcium, technetium, chromium, gallium, indium, iodine, iron, krypton, samarium,
30 selenium, sodium, thallium, and xenon.

Sources of X-rays include electron beam collision with metal targets, such as tungsten or molybdenum or alloys, or compact light sources, such as those produced commercially by Lyncean.

Alpha particles are identical to the nucleus of a helium atom and are produced by the alpha decay of various radioactive nuclei, such as isotopes of bismuth, polonium, astatine, radon, francium, radium, several actinides, such as actinium, thorium, uranium, neptunium, curium, californium, americium, and plutonium.

5 Sources for ultraviolet radiation include deuterium or cadmium lamps.

Sources for infrared radiation include sapphire, zinc, or selenide window ceramic lamps.

Sources for microwaves include klystrons, Slevin type RF sources, or atom beam sources that employ hydrogen, oxygen, or nitrogen gases.

10 Accelerators used to accelerate the particles (e.g., electrons or ions) can be DC (e.g., electrostatic DC or electrodynamic DC), RF linear, magnetic induction linear or continuous wave. For example, various irradiating devices may be used in the methods disclosed herein, including field ionization sources, electrostatic ion separators, field ionization generators, thermionic emission sources, microwave discharge ion sources,
15 recirculating or static accelerators, dynamic linear accelerators, van de Graaff accelerators, Cockroft Walton accelerators (e.g., PELLETRON® accelerators), LINACS, Dynamitrons (e.g., DYNAMITRON® accelerators), cyclotrons, synchrotrons, betatrons, transformer-type accelerators, microtrons, plasma generators, cascade accelerators, and folded tandem accelerators. For example, cyclotron type accelerators are available from
20 IBA, Belgium, such as the RHODOTRON™ system, while DC type accelerators are available from RDI, now IBA Industrial, such as the DYNAMITRON®. Other suitable accelerator systems include, for example: DC insulated core transformer (ICT) type systems, available from Nissin High Voltage, Japan; S-band LINACs, available from L3-PSD (USA), Linac Systems (France), Mevex (Canada), and Mitsubishi Heavy Industries
25 (Japan); L-band LINACs, available from Iotron Industries (Canada); and ILU-based accelerators, available from Budker Laboratories (Russia). Ions and ion accelerators are discussed in Introductory Nuclear Physics, Kenneth S. Krane, John Wiley & Sons, Inc. (1988), Krsto Prelec, FIZIKA B 6 (1997) 4, 177–206, Chu, William T., “Overview of Light-Ion Beam Therapy”, Columbus-Ohio, ICRU-IAEA Meeting, 18-20 March 2006,
30 Iwata, Y. et al., “Alternating-Phase-Focused IH-DTL for Heavy-Ion Medical Accelerators”, Proceedings of EPAC 2006, Edinburgh, Scotland, , and Leitner, C.M. et al., “Status of the Superconducting ECR Ion Source Venus”, Proceedings of EPAC 2000, Vienna, Austria. Some particle accelerators and their uses are disclosed, for example, in U.S. Pat. No. 7,931,784 to Medoff, the complete disclosure of which is incorporated
35 herein by reference.

Electrons may be produced by radioactive nuclei that undergo beta decay, such as isotopes of iodine, cesium, technetium, and iridium. Alternatively, an electron gun can be used as an electron source via thermionic emission and accelerated through an accelerating potential. An electron gun generates electrons, which are then accelerated
5 through a large potential (*e.g.*, greater than about 500 thousand, greater than about 1million, greater than about 2 million, greater than about 5 million, greater than about 6 million, greater than about 7 million, greater than about 8 million, greater than about 9 million, or even greater than 10 million volts) and then scanned magnetically in the x-y plane, where the electrons are initially accelerated in the z direction down the accelerator
10 tube and extracted through a foil window. Scanning the electron beams is useful for increasing the irradiation surface when irradiating materials, *e.g.*, a biomass, that is conveyed through the scanned beam. Scanning the electron beam also distributes the thermal load homogenously on the window and helps reduce the foil window rupture due to local heating by the electron beam. Window foil rupture is a cause of significant
15 down-time due to subsequent necessary repairs and re-starting the electron gun.

Various other irradiating devices may be used in the methods disclosed herein, including field ionization sources, electrostatic ion separators, field ionization generators, thermionic emission sources, microwave discharge ion sources, recirculating or static accelerators, dynamic linear accelerators, van de Graaff accelerators, and folded tandem
20 accelerators. Such devices are disclosed, for example, in U.S. Pat. No. 7,931,784 to Medoff, the complete disclosure of which is incorporated herein by reference.

A beam of electrons can be used as the radiation source. A beam of electrons has the advantages of high dose rates (*e.g.*, 1, 5, or even 10 Mrad per second), high throughput, less containment, and less confinement equipment. Electron beams can also
25 have high electrical efficiency (*e.g.*, 80%), allowing for lower energy usage relative to other radiation methods, which can translate into a lower cost of operation and lower greenhouse gas emissions corresponding to the smaller amount of energy used. Electron beams can be generated, *e.g.*, by electrostatic generators, cascade generators, transformer generators, low energy accelerators with a scanning system, low energy accelerators with
30 a linear cathode, linear accelerators, and pulsed accelerators.

Electrons can also be more efficient at causing changes in the molecular structure of carbohydrate-containing materials, for example, by the mechanism of chain scission. In addition, electrons having energies of 0.5-10 MeV can penetrate low density materials, such as the biomass materials described herein, *e.g.*, materials having a bulk
35 density of less than 0.5 g/cm³, and a depth of 0.3-10 cm. Electrons as an ionizing

radiation source can be useful, *e.g.*, for relatively thin piles, layers or beds of materials, *e.g.*, less than about 0.5 inch, *e.g.*, less than about 0.4 inch, 0.3 inch, 0.25 inch, or less than about 0.1 inch. In some embodiments, the energy of each electron of the electron beam is from about 0.3 MeV to about 2.0 MeV (million electron volts), *e.g.*, from about 0.5 MeV to about 1.5 MeV, or from about 0.7 MeV to about 1.25 MeV. Methods of irradiating materials are discussed in U.S. Pat. App. Pub. 2012/0100577 A1, filed October 18, 2011, the entire disclosure of which is herein incorporated by reference.

Electron beam irradiation devices may be procured commercially or built. For example, elements or components such inductors, capacitors, casings, power sources, cables, wiring, voltage control systems, current control elements, insulating material, microcontrollers and cooling equipment can be purchased and assembled into a device. Optionally, a commercial device can be modified and/or adapted. For example, devices and components can be purchased from any of the commercial sources described herein including Ion Beam Applications (Louvain-la-Neuve, Belgium), Wasik Associates Inc. (Dracut, MA), NHV Corporation (Japan), the Titan Corporation (San Diego, CA), Vivirad High Voltage Corp (Billerica, MA) and/or Budker Laboratories (Russia). Typical electron energies can be 0.5 MeV, 1 MeV, 2 MeV, 4.5 MeV, 7.5 MeV, or 10 MeV. Typical electron beam irradiation device power can be 1 kW, 5 kW, 10 kW, 20 kW, 50 kW, 60 kW, 70 kW, 80 kW, 90 kW, 100 kW, 125 kW, 150 kW, 175 kW, 200 kW, 250 kW, 300 kW, 350 kW, 400 kW, 450 kW, 500 kW, 600 kW, 700 kW, 800 kW, 900 kW or even 1000 kW. Accelerators that can be used include NHV irradiators medium energy series EPS-500 (*e.g.*, 500 kV accelerator voltage and 65, 100 or 150 mA beam current), EPS-800 (*e.g.*, 800 kV accelerator voltage and 65 or 100 mA beam current), or EPS-1000 (*e.g.*, 1000 kV accelerator voltage and 65 or 100 mA beam current). Also, accelerators from NHV's high energy series can be used such as EPS-1500 (*e.g.*, 1500 kV accelerator voltage and 65 mA beam current), EPS-2000 (*e.g.*, 2000 kV accelerator voltage and 50 mA beam current), EPS-3000 (*e.g.*, 3000 kV accelerator voltage and 50 mA beam current) and EPS-5000 (*e.g.*, 5000 and 30 mA beam current). Tradeoffs in considering electron beam irradiation device power specifications include cost to operate, capital costs, depreciation, and device footprint. Tradeoffs in considering exposure dose levels of electron beam irradiation would be energy costs and environment, safety, and health (ESH) concerns. Typically, generators are housed in a vault, *e.g.*, of lead or concrete, especially for production from X-rays that are generated in the process. Tradeoffs in considering electron energies include energy costs.

The electron beam irradiation device can produce either a fixed beam or a scanning beam. A scanning beam may be advantageous with large scan sweep length and high scan speeds, as this would effectively replace a large, fixed beam width. Further, available sweep widths of 0.5 m, 1 m, 2 m or more are available. The scanning
5 beam is preferred in most embodiments described herein because of the larger scan width and reduced possibility of local heating and failure of the windows.

ELECTRON GUNS – WINDOWS

10 The extraction system for an electron accelerator can include two window foils. The cooling gas in the two foil window extraction system can be a purge gas or a mixture, for example, air, or a pure gas. In one embodiment, the gas is an inert gas such as nitrogen, argon, helium and/or carbon dioxide. It is preferred to use a gas rather than a liquid since energy losses to the electron beam are minimized. Mixtures of pure gas
15 can also be used, either pre-mixed or mixed in line prior to impinging on the windows or in the space between the windows. The cooling gas can be cooled, for example, by using a heat exchange system (*e.g.*, a chiller) and/or by using boil off from a condensed gas (*e.g.*, liquid nitrogen, liquid helium). Window foils are described in PCT/US2013/64332 filed October 10, 2013 the full disclosure of which is incorporated by reference herein.

20

HEATING AND THROUGHPUT DURING RADIATION TREATMENT

Several processes can occur in biomass when electrons from an electron beam interact with matter in inelastic collisions. For example, ionization of the material, chain
25 scission of polymers in the material, cross linking of polymers in the material, oxidation of the material, generation of X-rays (“Bremsstrahlung”) and vibrational excitation of molecules (*e.g.*, phonon generation). Without being bound to a particular mechanism, the reduction in recalcitrance can be due to several of these inelastic collision effects, for example ionization, chain scission of polymers, oxidation and phonon generation. Some
30 of the effects (*e.g.*, especially X-ray generation), necessitate shielding and engineering barriers, for example, enclosing the irradiation processes in a concrete (or other radiation opaque material) vault. Another effect of irradiation, vibrational excitation, is equivalent to heating up the sample. Heating the sample by irradiation can help in recalcitrance reduction, but excessive heating can destroy the material, as will be explained below.

The adiabatic temperature rise (ΔT) from adsorption of ionizing radiation is given by the equation: $\Delta T = D/C_p$: where D is the average dose in kGy, C_p is the heat capacity in J/g °C, and ΔT is the change in temperature in °C. A typical dry biomass material will have a heat capacity close to 2. Wet biomass will have a higher heat capacity dependent on the amount of water since the heat capacity of water is very high (4.19 J/g °C). Metals have much lower heat capacities, for example, 304 stainless steel has a heat capacity of 0.5 J/g °C. The temperature change due to the instant adsorption of radiation in a biomass and stainless steel for various doses of radiation is shown in Table 1. At the higher temperatures biomass will decompose causing extreme deviation from the estimated changes in temperature.

Table 1: Calculated Temperature increase for biomass and stainless steel.

Dose (Mrad)	Estimated Biomass ΔT (°C)	Steel ΔT (°C)
10	50	200
50	250 (Decomposition)	1000
100	500 (Decomposition)	2000
150	750 (Decomposition)	3000
200	1000 (Decomposition)	4000

High temperatures can destroy and or modify the biopolymers in biomass so that the polymers (*e.g.*, cellulose) are unsuitable for further processing. A biomass subjected to high temperatures can become dark, sticky and give off odors indicating decomposition. The stickiness can even make the material hard to convey. The odors can be unpleasant and be a safety issue. In fact, keeping the biomass below about 200°C has been found to be beneficial in the processes described herein (*e.g.*, below about 190°C, below about 180°C, below about 170°C, below about 160°C, below about 150°C, below about 140°C, below about 130°C, below about 120°C, below about 110°C, between about 60°C and 180°C, between about 60°C and 160°C, between about 60°C and 150°C, between about 60°C and 140°C, between about 60°C and 130°C, between about 60°C and 120°C, between about 80°C and 180°C, between about 100°C and 180°C, between about 120°C and 180°C, between about 140°C and 180°C, between about 160°C and 180°C, between about 100°C and 140°C, between about 80°C and 120°C).

It has been found that irradiation above about 10 Mrad is desirable for the processes described herein (*e.g.*, reduction of recalcitrance). A high throughput is also

desirable so that the irradiation does not become a bottle neck in processing the biomass. The treatment is governed by a Dose rate equation: $M = FP/D \cdot \text{time}$, where M is the mass of irradiated material (Kg), F is the fraction of power that is adsorbed (unit less), P is the emitted power ($\text{kW} = \text{Voltage in MeV} \times \text{Current in mA}$), time is the treatment time (sec) and D is the adsorbed dose (kGy). In an exemplary process where the fraction of adsorbed power is fixed, the Power emitted is constant and a set dosage is desired, the throughput (*e.g.*, M , the biomass processed) can be increased by increasing the irradiation time. However, increasing the irradiation time without allowing the material to cool, can excessively heat the material as exemplified by the calculations shown above. Since biomass has a low thermal conductivity (less than about $0.1 \text{ Wm}^{-1}\text{K}^{-1}$), heat dissipation is slow, unlike, for example, metals (greater than about $10 \text{ Wm}^{-1}\text{K}^{-1}$) which can dissipate energy quickly as long as there is a heat sink to transfer the energy to.

ELECTRON GUNS – BEAM STOPS

In some embodiments, the systems and methods include a beam stop (*e.g.*, a shutter). For example, the beam stop can be used to quickly stop or reduce the irradiation of material without powering down the electron beam device. Alternatively the beam stop can be used while powering up the electron beam, *e.g.*, the beam stop can stop the electron beam until a beam current of a desired level is achieved. The beam stop can be placed between the primary foil window and a secondary foil window. For example, the beam stop can be mounted so that it is movable, that is, so that it can be moved into and out of the beam path. Even partial coverage of the beam can be used, for example, to control the dose of irradiation. The beam stop can be mounted to the floor, to a conveyor for the biomass, to a wall, to the radiation device (*e.g.*, at the scan horn), or to any structural support. Preferably the beam stop is fixed in relation to the scan horn so that the beam can be effectively controlled by the beam stop. The beam stop can incorporate a hinge, a rail, wheels, slots, or other means allowing for its operation in moving into and out of the beam. The beam stop can be made of any material that will stop at least 5% of the electrons, *e.g.*, at least 10%, 20%, 30%, 40%, 50%, 60%, 70%, at least 80%, 85%, 90%, 91%, 92%, 93%, 94%, 95%, 96%, 97%, 98%, 99% or even about 100% of the electrons.

The beam stop can be made of a metal including, but not limited to, stainless steel, lead, iron, molybdenum, silver, gold, titanium, aluminum, tin, or alloys of these, or

laminates (layered materials) made with such metals (*e.g.*, metal-coated ceramic, metal-coated polymer, metal-coated composite, multilayered metal materials).

The beam stop can be cooled, for example, with a cooling fluid such as an aqueous solution or a gas. The beam stop can be partially or completely hollow, for example with cavities. Interior spaces of the beam stop can be used for cooling fluids and gases. The beam stop can be of any shape, including flat, curved, round, oval, square, rectangular, beveled and wedged shapes.

The beam stop can have perforations so as to allow some electrons through, thus controlling (*e.g.*, reducing) the levels of radiation across the whole area of the window, or in specific regions of the window. The beam stop can be a mesh formed, for example, from fibers or wires. Multiple beam stops can be used, together or independently, to control the irradiation. The beam stop can be remotely controlled, *e.g.*, by radio signal or hard wired to a motor for moving the beam into or out of position.

15

BEAM DUMPS

The embodiments disclosed herein can also include a beam dump when utilizing a radiation treatment. A beam dump's purpose is to safely absorb a beam of charged particles. Like a beam stop, a beam dump can be used to block the beam of charged particles. However, a beam dump is much more robust than a beam stop, and is intended to block the full power of the electron beam for an extended period of time. They are often used to block the beam as the accelerator is powering up.

Beam dumps are also designed to accommodate the heat generated by such beams, and are usually made from materials such as copper, aluminum, carbon, beryllium, tungsten, or mercury. Beam dumps can be cooled, for example, using a cooling fluid that can be in thermal contact with the beam dump.

BIOMASS MATERIALS

Lignocellulosic materials include, but are not limited to, wood, particle board, forestry wastes (*e.g.*, sawdust, aspen wood, wood chips), grasses, (*e.g.*, switchgrass, miscanthus, cord grass, reed canary grass), grain residues, (*e.g.*, rice hulls, oat hulls, wheat chaff, barley hulls), agricultural waste (*e.g.*, silage, canola straw, wheat straw, barley straw, oat straw, rice straw, jute, hemp, flax, bamboo, sisal, abaca, corn cobs, corn stover, soybean stover, corn fiber, alfalfa, hay, coconut hair), sugar processing residues

35

(*e.g.*, bagasse, beet pulp, agave bagasse), algae, seaweed, manure, sewage, and mixtures of any of these.

In some cases, the lignocellulosic material includes corncobs. Ground or hammermilled corncobs can be spread in a layer of relatively uniform thickness for
5 irradiation, and after irradiation are easy to disperse in the medium for further processing. To facilitate harvest and collection, in some cases the entire corn plant is used, including the corn stalk, corn kernels, and in some cases even the root system of the plant.

Advantageously, no additional nutrients (other than a nitrogen source, *e.g.*, urea
10 or ammonia) are required during fermentation of corncobs or cellulosic or lignocellulosic materials containing significant amounts of corncobs.

Corncoobs, before and after comminution, are also easier to convey and disperse, and have a lesser tendency to form explosive mixtures in air than other cellulosic or lignocellulosic materials such as hay and grasses.

15 Cellulosic materials include, for example, paper, paper products, paper waste, paper pulp, pigmented papers, loaded papers, coated papers, filled papers, magazines, printed matter (*e.g.*, books, catalogs, manuals, labels, calendars, greeting cards, brochures, prospectuses, newsprint), printer paper, polycoated paper, card stock, cardboard, paperboard, materials having a high α -cellulose content such as cotton, and
20 mixtures of any of these. For example, paper products as described in U.S. App. No. 13/396,365 ("Magazine Feedstocks" by Medoff *et al.*, filed February 14, 2012), the full disclosure of which is incorporated herein by reference.

Cellulosic materials can also include lignocellulosic materials which have been partially or fully de-lignified.

25 In some instances other biomass materials can be utilized, for example starchy materials. Starchy materials include starch itself, *e.g.*, corn starch, wheat starch, potato starch or rice starch, a derivative of starch, or a material that includes starch, such as an edible food product or a crop. For example, the starchy material can be arracacha, buckwheat, banana, barley, cassava, kudzu, oca, sago, sorghum, regular household
30 potatoes, sweet potato, taro, yams, or one or more beans, such as favas, lentils or peas. Blends of any two or more starchy materials are also starchy materials. Mixtures of starchy, cellulosic and or lignocellulosic materials can also be used. For example, a biomass can be an entire plant, a part of a plant or different parts of a plant, *e.g.*, a wheat plant, cotton plant, a corn plant, rice plant or a tree. The starchy materials can be treated
35 by any of the methods described herein.

Microbial materials that can be used as feedstock can include, but are not limited to, any naturally occurring or genetically modified microorganism or organism that contains or is capable of providing a source of carbohydrates (*e.g.*, cellulose), for example, protists, *e.g.*, animal protists (*e.g.*, protozoa such as flagellates, amoeboids, ciliates, and sporozoa) and plant protists (*e.g.*, algae such as alveolates, chlorarachniophytes, cryptomonads, euglenids, glaucophytes, haptophytes, red algae, stramenopiles, and viridaplantae). Other examples include seaweed, plankton (*e.g.*, macroplankton, mesoplankton, microplankton, nanoplankton, picoplankton, and femtoplankton), phytoplankton, bacteria (*e.g.*, gram positive bacteria, gram negative bacteria, and extremophiles), yeast and/or mixtures of these. In some instances, microbial biomass can be obtained from natural sources, *e.g.*, the ocean, lakes, bodies of water, *e.g.*, salt water or fresh water, or on land. Alternatively or in addition, microbial biomass can be obtained from culture systems, *e.g.*, large scale dry and wet culture and fermentation systems.

In other embodiments, the biomass materials, such as cellulosic, starchy and lignocellulosic feedstock materials, can be obtained from transgenic microorganisms and plants that have been modified with respect to a wild type variety. Such modifications may be, for example, through the iterative steps of selection and breeding to obtain desired traits in a plant. Furthermore, the plants can have had genetic material removed, modified, silenced and/or added with respect to the wild type variety. For example, genetically modified plants can be produced by recombinant DNA methods, where genetic modifications include introducing or modifying specific genes from parental varieties, or, for example, by using transgenic breeding wherein a specific gene or genes are introduced to a plant from a different species of plant and/or bacteria. Another way to create genetic variation is through mutation breeding wherein new alleles are artificially created from endogenous genes. The artificial genes can be created by a variety of ways including treating the plant or seeds with, for example, chemical mutagens (*e.g.*, using alkylating agents, epoxides, alkaloids, peroxides, formaldehyde), irradiation (*e.g.*, X-rays, gamma rays, neutrons, beta particles, alpha particles, protons, deuterons, UV radiation) and temperature shocking or other external stressing and subsequent selection techniques. Other methods of providing modified genes is through error prone PCR and DNA shuffling followed by insertion of the desired modified DNA into the desired plant or seed. Methods of introducing the desired genetic variation in the seed or plant include, for example, the use of a bacterial carrier, biolistics, calcium phosphate precipitation, electroporation, gene splicing, gene silencing, lipofection,

microinjection and viral carriers. Additional genetically modified materials have been described in U.S. Application Serial No 13/396,369 filed February 14, 2012, the full disclosure of which is incorporated herein by reference.

Any of the methods described herein can be practiced with mixtures of any
5 biomass materials described herein.

OTHER MATERIALS

Other materials (*e.g.*, natural or synthetic materials), for example polymers, can
10 be treated and/or made utilizing the methods, equipment and systems described herein. For example polyethylene (*e.g.*, linear low density ethylene and high density polyethylene), polystyrenes, sulfonated polystyrenes, poly (vinyl chloride), polyesters (*e.g.*, nylons, DACRON™, KODEL™), polyalkylene esters, poly vinyl esters, polyamides (*e.g.*, KEVLAR™), polyethylene terephthalate, cellulose acetate, acetal,
15 poly acrylonitrile, polycarbonates (*e.g.*, LEXAN™), acrylics [*e.g.*, poly (methyl methacrylate), poly(methyl methacrylate), polyacrylonitrile, Poly urethanes, polypropylene, poly butadiene, polyisobutylene, polyacrylonitrile, polychloroprene (*e.g.* neoprene), poly(cis-1,4-isoprene) [*e.g.*, natural rubber], poly(trans-1,4-isoprene) [*e.g.*, gutta percha], phenol formaldehyde, melamine formaldehyde, epoxides, polyesters, poly
20 amines, polycarboxylic acids, polylactic acids, polyvinyl alcohols, polyanhydrides, poly fluoro carbons (*e.g.*, TEFLON™), silicones (*e.g.*, silicone rubber), polysilanes, poly ethers (*e.g.*, polyethylene oxide, polypropylene oxide), waxes, oils and mixtures of these. Also included are plastics, rubbers, elastomers, fibers, waxes, gels, oils, adhesives, thermoplastics, thermosets, biodegradable polymers, resins made with these polymers,
25 other polymers, other materials and combinations thereof. The polymers can be made by any useful method including cationic polymerization, anionic polymerization, radical polymerization, metathesis polymerization, ring opening polymerization, graft polymerization, addition polymerization. In some cases the treatments disclosed herein can be used, for example, for radically initiated graft polymerization and cross linking.
30 Composites of polymers, for example with glass, metals, biomass (*e.g.*, fibers, particles), ceramics can also be treated and/or made.

Other materials that can be treated by using the methods, systems and equipment disclosed herein are ceramic materials, minerals, metals, inorganic compounds. For example, silicon and germanium crystals, silicon nitrides, metal oxides, semiconductors,
35 insulators, cements and or conductors.

In addition, manufactured multipart or shaped materials (*e.g.*, molded, extruded, welded, riveted, layered or combined in any way) can be treated, for example cables, pipes, boards, enclosures, integrated semiconductor chips, circuit boards, wires, tires, windows, laminated materials, gears, belts, machines, combinations of these. For
5 example, treating a material by the methods described herein can modify the surfaces, for example, making them susceptible to further functionalization, combinations (*e.g.*, welding) and/or treatment can cross link the materials.

BIOMASS MATERIAL PREPARATION – MECHANICAL TREATMENTS

10

The biomass can be in a dry form, for example, with less than about 35% moisture content (*e.g.*, less than about 20 %, less than about 15 %, less than about 10 % less than about 5 %, less than about 4%, less than about 3 %, less than about 2 % or even less than about 1 %). The biomass can also be delivered in a wet state, for example,
15 as a wet solid, a slurry or a suspension with at least about 10 wt.% solids (*e.g.*, at least about 20 wt.%, at least about 30 wt. %, at least about 40 wt.%, at least about 50 wt.%, at least about 60 wt.%, at least about 70 wt.%).

The processes disclosed herein can utilize low bulk density materials, for example cellulosic or lignocellulosic feedstocks that have been physically pretreated to
20 have a bulk density of less than about 0.75 g/cm³, *e.g.*, less than about 0.7, 0.65, 0.60, 0.50, 0.35, 0.25, 0.20, 0.15, 0.10, 0.05 or less, *e.g.*, less than about 0.025 g/cm³. Bulk density is determined using ASTM D1895B. Briefly, the method involves filling a measuring cylinder of known volume with a sample and obtaining a weight of the sample. The bulk density is calculated by dividing the weight of the sample in grams by
25 the known volume of the cylinder in cubic centimeters. If desired, low bulk density materials can be densified, for example, by methods described in U.S. Pat. No. 7,971,809 published July 5, 2011, the entire disclosure of which is hereby incorporated by reference.

In some cases, the pre-treatment processing includes screening of the biomass
30 material. Screening can be through a mesh or perforated plate with a desired opening size, for example, less than about 6.35 mm (1/4 inch, 0.25 inch), (*e.g.*, less than about 3.18 mm (1/8 inch, 0.125 inch), less than about 1.59 mm (1/16 inch, 0.0625 inch), is less than about 0.79 mm (1/32 inch, 0.03125 inch), *e.g.*, less than about 0.51 mm (1/50 inch, 0.02000 inch), less than about 0.40 mm (1/64 inch, 0.015625 inch), less than about 0.23
35 mm (0.009 inch), less than about 0.20 mm (1/128 inch, 0.0078125 inch), less than about

0.18 mm (0.007 inch), less than about 0.13 mm (0.005 inch), or even less than about 0.10 mm (1/256 inch, 0.00390625 inch)). In one configuration the desired biomass falls through the perforations or screen and thus biomass larger than the perforations or screen are not irradiated. These larger materials can be re-processed, for example by
5 comminuting, or they can simply be removed from processing. In another configuration material that is larger than the perforations is irradiated and the smaller material is removed by the screening process or recycled. In this kind of a configuration, the conveyor, such as a vibratory conveyor, itself (for example, a part of the conveyor) can be perforated or made with a mesh. For example, in one particular embodiment the
10 biomass material may be wet and the perforations or mesh allow water to drain away from the biomass before irradiation.

Screening of material can also be by a manual method, for example by an operator or mechanoid (*e.g.*, a robot equipped with a color, reflectivity or other sensor) that removes unwanted material. Screening can also be by magnetic screening wherein a
15 magnet is disposed near the conveyed material and the magnetic material is removed magnetically.

Optional pre-treatment processing can include heating the material. For example, a portion of a conveyor conveying the biomass or other material can be sent through a heated zone. The heated zone can be created, for example, by IR radiation, microwaves,
20 combustion (*e.g.*, gas, coal, oil, biomass), resistive heating and/or inductive coils. The heat can be applied from at least one side or more than one side, can be continuous or periodic and can be for only a portion of the material or all the material. For example, a portion of the conveying trough can be heated by use of a heating jacket. Heating can be, for example, for the purpose of drying the material. In the case of drying the
25 material, this can also be facilitated, with or without heating, by the movement of a gas (*e.g.*, air, oxygen, nitrogen, He, CO₂, Argon) over and/or through the biomass as it is being conveyed.

Optionally, pre-treatment processing can include cooling the material. Cooling material is described in U.S. Pat. No. 7,900,857 published March 8, 2011, the disclosure
30 of which is incorporated herein by reference. For example, cooling can be by supplying a cooling fluid, for example water (*e.g.*, with glycerol), or nitrogen (*e.g.*, liquid nitrogen) to the bottom of the conveying trough. Alternatively, a cooling gas, for example, chilled nitrogen can be blown over the biomass materials or under the conveying system.

Another optional pre-treatment processing method can include adding a material
35 to the biomass or other feedstocks. The additional material can be added by, for

example, by showering, sprinkling and/or pouring the material onto the biomass as it is conveyed. Materials that can be added include, for example, metals, ceramics and/or ions as described in U.S. Pat. App. Pub. 2010/0105119 A1 (filed October 26, 2009) and U.S. Pat. App. Pub. 2010/0159569 A1 (filed December 16, 2009), the entire disclosures of which are incorporated herein by reference. Optional materials that can be added include acids and bases. Other materials that can be added are oxidants (*e.g.*, peroxides, chlorates), polymers, polymerizable monomers (*e.g.*, containing unsaturated bonds), water, catalysts, enzymes and/or organisms. Materials can be added, for example, in pure form, as a solution in a solvent (*e.g.*, water or an organic solvent) and/or as a solution. In some cases the solvent is volatile and can be made to evaporate *e.g.*, by heating and/or blowing gas as previously described. The added material may form a uniform coating on the biomass or be a homogeneous mixture of different components (*e.g.*, biomass and additional material). The added material can modulate the subsequent irradiation step by increasing the efficiency of the irradiation, damping the irradiation or changing the effect of the irradiation (*e.g.*, from electron beams to X-rays or heat). The method may have no impact on the irradiation but may be useful for further downstream processing. The added material may help in conveying the material, for example, by lowering dust levels.

Biomass can be delivered to conveyor (*e.g.*, vibratory conveyors that can be used in the vaults herein described) by a belt conveyor, a pneumatic conveyor, a screw conveyor, a hopper, a pipe, manually or by a combination of these. The biomass can, for example, be dropped, poured and/or placed onto the conveyor by any of these methods. In some embodiments the material is delivered to the conveyor using an enclosed material distribution system to help maintain a low oxygen atmosphere and/or control dust and fines. Lofted or air suspended biomass fines and dust are undesirable because these can form an explosion hazard or damage the window foils of an electron gun (if such a device is used for treating the material).

The material can be leveled to form a uniform thickness between about 0.0312 and 5 inches (*e.g.*, between about 0.0625 and 2.000 inches, between about 0.125 and 1 inches, between about 0.125 and 0.5 inches, between about 0.3 and 0.9 inches, between about 0.2 and 0.5 inches between about 0.25 and 1.0 inches, between about 0.25 and 0.5 inches, 0.100 +/- 0.025 inches, 0.150 +/- 0.025 inches, 0.200 +/- 0.025 inches, 0.250 +/- 0.025 inches, 0.300 +/- 0.025 inches, 0.350 +/- 0.025 inches, 0.400 +/- 0.025 inches, 0.450 +/- 0.025 inches, 0.500 +/- 0.025 inches, 0.550 +/- 0.025 inches, 0.600 +/- 0.025

inches, 0.700 +/- 0.025 inches, 0.750 +/- 0.025 inches, 0.800 +/- 0.025 inches, 0.850 +/- 0.025 inches, 0.900 +/- 0.025 inches, 0.900 +/- 0.025 inches.

Generally, it is preferred to convey the material as quickly as possible through the electron beam to maximize throughput. For example, the material can be conveyed at rates of at least 1 ft/min, *e.g.*, at least 2 ft/min, at least 3 ft/min, at least 4 ft/min, at least 5 ft/min, at least 10 ft/min, at least 15 ft/min, 20, 25, 30, 35, 40, 45, 50 ft/min. The rate of conveying is related to the beam current, for example, for a ¼ inch thick biomass and 100 mA, the conveyor can move at about 20 ft/min to provide a useful irradiation dosage, at 50 mA the conveyor can move at about 10 ft/min to provide approximately the same irradiation dosage.

After the biomass material has been conveyed through the radiation zone, optional post-treatment processing can be done. The optional post-treatment processing can, for example, be a process described with respect to the pre-irradiation processing. For example, the biomass can be screened, heated, cooled, and/or combined with additives. Uniquely to post-irradiation, quenching of the radicals can occur, for example, quenching of radicals by the addition of fluids or gases (*e.g.*, oxygen, nitrous oxide, ammonia, liquids), using pressure, heat, and/or the addition of radical scavengers. For example, the biomass can be conveyed out of the enclosed conveyor and exposed to a gas (*e.g.*, oxygen) where it is quenched, forming carboxylated groups. In one embodiment the biomass is exposed during irradiation to the reactive gas or fluid. Quenching of biomass that has been irradiated is described in U.S. Pat. No. 8,083,906 published Dec. 27, 2011, the entire disclosure of which is incorporate herein by reference.

If desired, one or more mechanical treatments can be used in addition to irradiation to further reduce the recalcitrance of the carbohydrate containing material. These processes can be applied before, during and or after irradiation.

In some cases, the mechanical treatment may include an initial preparation of the feedstock as received, *e.g.*, size reduction of materials, such as by comminution, *e.g.*, cutting, grinding, shearing, pulverizing or chopping. For example, in some cases, loose feedstock (*e.g.*, recycled paper, starchy materials, or switchgrass) is prepared by shearing or shredding. Mechanical treatment may reduce the bulk density of the carbohydrate-containing material, increase the surface area of the carbohydrate-containing material and/or decrease one or more dimensions of the carbohydrate-containing material.

Alternatively, or in addition, the feedstock material can be treated with another treatment, for example chemical treatments, such as with an acid (HCl, H₂SO₄, H₃PO₄), a

base (*e.g.*, KOH and NaOH), a chemical oxidant (*e.g.*, peroxides, chlorates, ozone), irradiation, steam explosion, pyrolysis, sonication, oxidation, chemical treatment. The treatments can be in any order and in any sequence and combinations. For example, the feedstock material can first be physically treated by one or more treatment methods, *e.g.*,
5 chemical treatment including and in combination with acid hydrolysis (*e.g.*, utilizing HCl, H₂SO₄, H₃PO₄), radiation, sonication, oxidation, pyrolysis or steam explosion, and then mechanically treated. This sequence can be advantageous since materials treated by one or more of the other treatments, *e.g.*, irradiation or pyrolysis, tend to be more brittle and, therefore, it may be easier to further change the structure of the material by
10 mechanical treatment. As another example, a feedstock material can be conveyed through ionizing radiation using a conveyor as described herein and then mechanically treated. Chemical treatment can remove some or all of the lignin (for example chemical pulping) and can partially or completely hydrolyze the material. The methods also can be used with pre-hydrolyzed material. The methods also can be used with material that
15 has not been pre hydrolyzed. The methods can be used with mixtures of hydrolyzed and non-hydrolyzed materials, for example with about 50% or more non-hydrolyzed material, with about 60% or more non- hydrolyzed material, with about 70% or more non-hydrolyzed material, with about 80% or more non-hydrolyzed material or even with 90% or more non-hydrolyzed material.

20 In addition to size reduction, which can be performed initially and/or later in processing, mechanical treatment can also be advantageous for “opening up,” “stressing,” breaking or shattering the carbohydrate-containing materials, making the cellulose of the materials more susceptible to chain scission and/or disruption of crystalline structure during the physical treatment.

25 Methods of mechanically treating the carbohydrate-containing material include, for example, milling or grinding. Milling may be performed using, for example, a hammer mill, ball mill, colloid mill, conical or cone mill, disk mill, edge mill, Wiley mill, grist mill or other mill. Grinding may be performed using, for example, a cutting/impact type grinder. Some exemplary grinders include stone grinders, pin
30 grinders, coffee grinders, and burr grinders. Grinding or milling may be provided, for example, by a reciprocating pin or other element, as is the case in a pin mill. Other mechanical treatment methods include mechanical ripping or tearing, other methods that apply pressure to the fibers, and air attrition milling. Suitable mechanical treatments

further include any other technique that continues the disruption of the internal structure of the material that was initiated by the previous processing steps.

Mechanical feed preparation systems can be configured to produce streams with specific characteristics such as, for example, specific maximum sizes, specific length-to-
5 width, or specific surface areas ratios. Physical preparation can increase the rate of reactions, improve the movement of material on a conveyor, improve the irradiation profile of the material, improve the radiation uniformity of the material, or reduce the processing time required by opening up the materials and making them more accessible to processes and/or reagents, such as reagents in a solution.

10 The bulk density of feedstocks can be controlled (*e.g.*, increased). In some situations, it can be desirable to prepare a low bulk density material, *e.g.*, by densifying the material (*e.g.*, densification can make it easier and less costly to transport to another site) and then reverting the material to a lower bulk density state (*e.g.*, after transport). The material can be densified, for example from less than about 0.2 g/cc to more than
15 about 0.9 g/cc (*e.g.*, less than about 0.3 to more than about 0.5 g/cc, less than about 0.3 to more than about 0.9 g/cc, less than about 0.5 to more than about 0.9 g/cc, less than about 0.3 to more than about 0.8 g/cc, less than about 0.2 to more than about 0.5 g/cc). For example, the material can be densified by the methods and equipment disclosed in U.S. Pat. No. 7,932,065 to Medoff and International Publication No. WO 2008/073186
20 (which was filed October 26, 2007, was published in English, and which designated the United States), the full disclosures of which are incorporated herein by reference. Densified materials can be processed by any of the methods described herein, or any material processed by any of the methods described herein can be subsequently densified.

25 In some embodiments, the material to be processed is in the form of a fibrous material that includes fibers provided by shearing a fiber source. For example, the shearing can be performed with a rotary knife cutter.

For example, a fiber source, *e.g.*, that is recalcitrant or that has had its recalcitrance level reduced, can be sheared, *e.g.*, in a rotary knife cutter, to provide a first
30 fibrous material. The first fibrous material is passed through a first screen, *e.g.*, having an average opening size of 1.59 mm or less (1/16 inch, 0.0625 inch), provide a second fibrous material. If desired, the fiber source can be cut prior to the shearing, *e.g.*, with a shredder. For example, when a paper is used as the fiber source, the paper can be first cut into strips that are, *e.g.*, 1/4- to 1/2-inch wide, using a shredder, *e.g.*, a counter-
35 rotating screw shredder, such as those manufactured by Munson (Utica, N.Y.). As an

alternative to shredding, the paper can be reduced in size by cutting to a desired size using a guillotine cutter. For example, the guillotine cutter can be used to cut the paper into sheets that are, *e.g.*, 10 inches wide by 12 inches long.

5 In some embodiments, the shearing of the fiber source and the passing of the resulting first fibrous material through a first screen are performed concurrently. The shearing and the passing can also be performed in a batch-type process.

For example, a rotary knife cutter can be used to concurrently shear the fiber source and screen the first fibrous material. A rotary knife cutter includes a hopper that can be loaded with a shredded fiber source prepared by shredding a fiber source.

10 In some implementations, the feedstock is physically treated prior to saccharification and/or fermentation. Physical treatment processes can include one or more of any of those described herein, such as mechanical treatment, chemical treatment, irradiation, sonication, oxidation, pyrolysis or steam explosion. Treatment methods can be used in combinations of two, three, four, or even all of these technologies (in any
15 order). When more than one treatment method is used, the methods can be applied at the same time or at different times. Other processes that change a molecular structure of a biomass feedstock may also be used, alone or in combination with the processes disclosed herein.

Mechanical treatments that may be used, and the characteristics of the
20 mechanically treated carbohydrate-containing materials, are described in further detail in U.S. Pat. App. Pub. 2012/0100577 A1, filed October 18, 2011, the full disclosure of which is hereby incorporated herein by reference.

SONICATION, PYROLYSIS, OXIDATION, STEAM EXPLOSION

25 If desired, one or more sonication, pyrolysis, oxidative, or steam explosion processes can be used instead of or in addition to irradiation to reduce or further reduce the recalcitrance of the carbohydrate-containing material. For example, these processes can be applied before, during and or after irradiation. These processes are described in
30 detail in U.S. Pat. No. 7,932,065 to Medoff, the full disclosure of which is incorporated herein by reference.

INTERMEDIATES AND PRODUCTS

Using the processes described herein, the biomass material can be converted to one or more products, such as energy, fuels, foods and materials. For example, intermediates and products such as organic acids, salts of organic acids, anhydrides, esters of organic acids and fuels, *e.g.*, fuels for internal combustion engines or feedstocks for fuel cells can be produced. Systems and processes are described herein that can use as feedstock cellulosic and/or lignocellulosic materials that are readily available, but often can be difficult to process, *e.g.*, municipal waste streams and waste paper streams, such as streams that include newspaper, Kraft paper, corrugated paper or mixtures of these.

Specific examples of products include, but are not limited to, hydrogen, sugars (*e.g.*, glucose, xylose, arabinose, mannose, galactose, fructose, disaccharides, oligosaccharides and polysaccharides), alcohols (*e.g.*, monohydric alcohols or dihydric alcohols, such as ethanol, n-propanol, isobutanol, *sec*-butanol, *tert*-butanol or n-butanol), hydrated or hydrous alcohols (*e.g.*, containing greater than 10%, 20%, 30% or even greater than 40% water), biodiesel, organic acids, hydrocarbons (*e.g.*, methane, ethane, propane, isobutene, pentane, n-hexane, biodiesel, bio-gasoline and mixtures thereof), co-products (*e.g.*, proteins, such as cellulolytic proteins (enzymes) or single cell proteins), and mixtures of any of these in any combination or relative concentration, and optionally in combination with any additives (*e.g.*, fuel additives). Other examples include carboxylic acids, salts of a carboxylic acid, a mixture of carboxylic acids and salts of carboxylic acids and esters of carboxylic acids (*e.g.*, methyl, ethyl and n-propyl esters), ketones (*e.g.*, acetone), aldehydes (*e.g.*, acetaldehyde), alpha and beta unsaturated acids (*e.g.*, acrylic acid) and olefins (*e.g.*, ethylene). Other alcohols and alcohol derivatives include propanol, propylene glycol, 1,4-butanediol, 1,3-propanediol, sugar alcohols (*e.g.*, erythritol, glycol, glycerol, sorbitol, threitol, arabitol, ribitol, mannitol, dulcitol, fucitol, iditol, isomalt, maltitol, lactitol, xylitol and other polyols), and methyl or ethyl esters of any of these alcohols. Other products include methyl acrylate, methylmethacrylate, D-lactic acid, L-lactic acid, pyruvic acid, poly lactic acid, citric acid, formic acid, acetic acid, propionic acid, butyric acid, succinic acid, valeric acid, caproic acid, 3-hydroxypropionic acid, palmitic acid, stearic acid, oxalic acid, malonic acid, glutaric acid, oleic acid, linoleic acid, glycolic acid, gamma-hydroxybutyric acid, and mixtures thereof, salts of any of these acids, mixtures of any of the acids and their respective salts.

Any combination of the above products with each other, and/or of the above products with other products, which other products may be made by the processes described herein or otherwise, may be packaged together and sold as products. The products may be combined, *e.g.*, mixed, blended or co-dissolved, or may simply be
5 packaged or sold together.

Any of the products or combinations of products described herein may be sanitized or sterilized prior to selling the products, *e.g.*, after purification or isolation or even after packaging, to neutralize one or more potentially undesirable contaminants that could be present in the product(s). Such sanitation can be done with electron
10 bombardment, for example, by at a dosage of less than about 20 Mrad, *e.g.*, from about 0.1 to 15 Mrad, from about 0.5 to 7 Mrad, or from about 1 to 3 Mrad.

The processes described herein can produce various by-product streams useful for generating steam and electricity to be used in other parts of the plant (co-generation) or sold on the open market. For example, steam generated from burning by-product
15 streams can be used in a distillation process. As another example, electricity generated from burning by-product streams can be used to power electron beam generators used in pretreatment.

The by-products used to generate steam and electricity are derived from a number of sources throughout the process. For example, anaerobic digestion of wastewater can
20 produce a biogas high in methane and a small amount of waste biomass (sludge). As another example, post-saccharification and/or post-distillate solids (*e.g.*, unconverted lignin, cellulose, and hemicellulose remaining from the pretreatment and primary processes) can be used, *e.g.*, burned, as a fuel.

Other intermediates and products, including food and pharmaceutical products,
25 are described in U.S. Pat. App. Pub. 2010/0124583 A1, published May 20, 2010, to Medoff, the full disclosure of which is hereby incorporated by reference herein.

LIGNIN DERIVED PRODUCTS

30 The spent biomass (*e.g.*, spent lignocellulosic material) from lignocellulosic processing by the methods described are expected to have a high lignin content and in addition to being useful for producing energy through combustion in a Co-Generation plant, may have uses as other valuable products. For example, the lignin can be used as captured as a plastic, or it can be synthetically upgraded to other plastics. In some

instances, it can also be converted to lignosulfonates, which can be utilized as binders, dispersants, emulsifiers or as sequestrants.

When used as a binder, the lignin or a lignosulfonate can, *e.g.*, be utilized in coal briquettes, in ceramics, for binding carbon black, for binding fertilizers and herbicides, as a dust suppressant, in the making of plywood and particle board, for binding animal feeds, as a binder for fiberglass, as a binder in linoleum paste and as a soil stabilizer.

When used as a dispersant, the lignin or lignosulfonates can be used, *e.g.*, concrete mixes, clay and ceramics, dyes and pigments, leather tanning and in gypsum board.

When used as an emulsifier, the lignin or lignosulfonates can be used, *e.g.*, in asphalt, pigments and dyes, pesticides and wax emulsions.

When used as a sequestrant, the lignin or lignosulfonates can be used, *e.g.*, in micro-nutrient systems, cleaning compounds and water treatment systems, *e.g.*, for boiler and cooling systems.

For energy production lignin generally has a higher energy content than holocellulose (cellulose and hemicellulose) since it contains more carbon than homocellulose. For example, dry lignin can have an energy content of between about 11,000 and 12,500 BTU per pound, compared to 7,000 and 8,000 BTU per pound of holocellulose. As such, lignin can be densified and converted into briquettes and pellets for burning. For example, the lignin can be converted into pellets by any method described herein. For a slower burning pellet or briquette, the lignin can be crosslinked, such as applying a radiation dose of between about 0.5 Mrad and 5 Mrad. Crosslinking can make a slower burning form factor. The form factor, such as a pellet or briquette, can be converted to a "synthetic coal" or charcoal by pyrolyzing in the absence of air, *e.g.*, at between 400 and 950 °C. Prior to pyrolyzing, it can be desirable to crosslink the lignin to maintain structural integrity.

SACCHARIFICATION

In order to convert the feedstock to a form that can be readily processed the glucan- or xylan-containing cellulose in the feedstock can be hydrolyzed to low molecular weight carbohydrates, such as sugars, by a saccharifying agent, *e.g.*, an enzyme or acid, a process referred to as saccharification. The low molecular weight carbohydrates can then be used, for example, in an existing manufacturing plant, such as

a single cell protein plant, an enzyme manufacturing plant, or a fuel plant, *e.g.*, an ethanol manufacturing facility.

The feedstock can be hydrolyzed using an enzyme, *e.g.*, by combining the materials and the enzyme in a solvent, *e.g.*, in an aqueous solution.

- 5 Alternatively, the enzymes can be supplied by organisms that break down biomass, such as the cellulose and/or the lignin portions of the biomass, contain or manufacture various cellulolytic enzymes (cellulases), ligninases or various small molecule biomass-degrading metabolites. These enzymes may be a complex of enzymes that act synergistically to degrade crystalline cellulose or the lignin portions of biomass.
- 10 Examples of cellulolytic enzymes include: endoglucanases, cellobiohydrolases, and cellobiases (beta-glucosidases).

During saccharification a cellulosic substrate can be initially hydrolyzed by endoglucanases at random locations producing oligomeric intermediates. These intermediates are then substrates for exo-splitting glucanases such as cellobiohydrolase

15 to produce cellobiose from the ends of the cellulose polymer. Cellobiose is a water-soluble 1,4-linked dimer of glucose. Finally, cellobiase cleaves cellobiose to yield glucose. The efficiency (*e.g.*, time to hydrolyze and/or completeness of hydrolysis) of this process depends on the recalcitrance of the cellulosic material.

Therefore, the treated biomass materials can be saccharified, by combining the

20 material and a cellulase enzyme in a fluid medium, *e.g.*, an aqueous solution. In some cases, the material is boiled, steeped, or cooked in hot water prior to saccharification, as described in U.S. Pat. App. Pub. 2012/0100577 A1 by Medoff and Masterman, published on April 26, 2012, the entire contents of which are incorporated herein.

The saccharification process can be partially or completely performed in a tank

25 (*e.g.*, a tank having a volume of at least 4000, 40,000, or 500,000 L) in a manufacturing plant, and/or can be partially or completely performed in transit, *e.g.*, in a rail car, tanker truck, or in a supertanker or the hold of a ship. The time required for complete saccharification will depend on the process conditions and the carbohydrate-containing material and enzyme used. If saccharification is performed in a manufacturing plant

30 under controlled conditions, the cellulose may be substantially entirely converted to sugar, *e.g.*, glucose in about 12-96 hours. If saccharification is performed partially or completely in transit, saccharification may take longer.

It is generally preferred that the tank contents be mixed during saccharification, *e.g.*, using jet mixing as described in International App. No. PCT/US2010/035331, filed

May 18, 2010, which was published in English as WO 2010/135380 and designated the United States, the full disclosure of which is incorporated by reference herein.

The addition of surfactants can enhance the rate of saccharification. Examples of surfactants include non-ionic surfactants, such as a Tween® 20 or Tween® 80

5 polyethylene glycol surfactants, ionic surfactants, or amphoteric surfactants.

It is generally preferred that the concentration of the sugar solution resulting from saccharification be relatively high, *e.g.*, greater than 40%, or greater than 50, 60, 70, 80, 90 or even greater than 95% by weight. Water may be removed, *e.g.*, by evaporation, to increase the concentration of the sugar solution. This reduces the volume to be shipped,
10 and also inhibits microbial growth in the solution.

Alternatively, sugar solutions of lower concentrations may be used, in which case it may be desirable to add an antimicrobial additive, *e.g.*, a broad spectrum antibiotic, in a low concentration, *e.g.*, 50 to 150 ppm. Other suitable antibiotics include amphotericin B, ampicillin, chloramphenicol, ciprofloxacin, gentamicin, hygromycin B, kanamycin, neomycin, penicillin, puromycin, streptomycin. Antibiotics will inhibit growth of
15 microorganisms during transport and storage, and can be used at appropriate concentrations, *e.g.*, between 15 and 1000 ppm by weight, *e.g.*, between 25 and 500 ppm, or between 50 and 150 ppm. If desired, an antibiotic can be included even if the sugar concentration is relatively high. Alternatively, other additives with anti-microbial or preservative properties may be used. Preferably the antimicrobial additive(s) are food-
20 grade.

A relatively high concentration solution can be obtained by limiting the amount of water added to the carbohydrate-containing material with the enzyme. The concentration can be controlled, *e.g.*, by controlling how much saccharification takes
25 place. For example, concentration can be increased by adding more carbohydrate-containing material to the solution. In order to keep the sugar that is being produced in solution, a surfactant can be added, *e.g.*, one of those discussed above. Solubility can also be increased by increasing the temperature of the solution. For example, the solution can be maintained at a temperature of 40-50°C, 60-80°C, or even higher.

30

SACCHARIFYING AGENTS

Suitable cellulolytic enzymes include cellulases from species in the genera *Bacillus*, *Coprinus*, *Myceliophthora*, *Cephalosporium*, *Scytalidium*, *Penicillium*,
35 *Aspergillus*, *Pseudomonas*, *Humicola*, *Fusarium*, *Thielavia*, *Acremonium*,

Chrysosporium and *Trichoderma*, especially those produced by a strain selected from the species *Aspergillus* (see, e.g., EP Pub. No. 0 458 162), *Humicola insolens* (reclassified as *Scytalidium thermophilum*, see, e.g., U.S. Pat. No. 4,435,307), *Coprinus cinereus*, *Fusarium oxysporum*, *Myceliophthora thermophila*, *Meripilus giganteus*, *Thielavia terrestris*, *Acremonium* sp. (including, but not limited to, *A. persicinum*, *A. acremonium*, *A. brachyphenium*, *A. dichromosporum*, *A. obclavatum*, *A. pinkertoniae*, *A. roseogriseum*, *A. incoloratum*, and *A. furatum*). Preferred strains include *Humicola insolens* DSM 1800, *Fusarium oxysporum* DSM 2672, *Myceliophthora thermophila* CBS 117.65, *Cephalosporium* sp. RYM-202, *Acremonium* sp. CBS 478.94, *Acremonium* sp. CBS 265.95, *Acremonium persicinum* CBS 169.65, *Acremonium acremonium* AHU 9519, *Cephalosporium* sp. CBS 535.71, *Acremonium brachyphenium* CBS 866.73, *Acremonium dichromosporum* CBS 683.73, *Acremonium obclavatum* CBS 311.74, *Acremonium pinkertoniae* CBS 157.70, *Acremonium roseogriseum* CBS 134.56, *Acremonium incoloratum* CBS 146.62, and *Acremonium furatum* CBS 299.70H. Cellulolytic enzymes may also be obtained from *Chrysosporium*, preferably a strain of *Chrysosporium lucknowense*. Additional strains that can be used include, but are not limited to, *Trichoderma* (particularly *T. viride*, *T. reesei*, and *T. koningii*), alkalophilic *Bacillus* (see, for example, U.S. Pat. No. 3,844,890 and EP Pub. No. 0 458 162), and *Streptomyces* (see, e.g., EP Pub. No. 0 458 162).

In addition to or in combination to enzymes, acids, bases and other chemicals (e.g., oxidants) can be utilized to saccharify lignocellulosic and cellulosic materials. These can be used in any combination or sequence (e.g., before, after and/or during addition of an enzyme). For example strong mineral acids can be utilized (e.g. HCl, H₂SO₄, H₃PO₄) and strong bases (e.g., NaOH, KOH).

25

SUGARS

In the processes described herein, for example after saccharification, sugars (e.g., glucose and xylose) can be isolated and/or purified. For example sugars can be isolated and/or purified by precipitation, crystallization, chromatography (e.g., simulated moving bed chromatography, high pressure chromatography), electrodialysis, centrifugation, extraction, any other isolation method known in the art, and combinations thereof.

30

HYDROGENATION AND OTHER CHEMICAL TRANSFORMATIONS

The processes described herein can include hydrogenation. For example, glucose
5 and xylose can be hydrogenated to sorbitol and xylitol respectively. Hydrogenation can
be accomplished by use of a catalyst (*e.g.*, Pt/gamma-Al₂O₃, Ru/C, Raney Nickel, or
other catalysts known in the art) in combination with H₂ under high pressure (*e.g.*, 10 to
12000 psi). Other types of chemical transformation of the products from the processes
described herein can be used, for example, production of organic sugar derived products
10 (*e.g.*, furfural and furfural-derived products). Chemical transformations of sugar derived
products are described in USSN 13/934,704 filed July 3, 2013, the entire disclosure of
which is incorporated herein by reference in its entirety.

FERMENTATION

15

Yeast and *Zymomonas* bacteria, for example, can be used for fermentation or
conversion of sugar(s) to alcohol(s). Other microorganisms are discussed below. The
optimum pH for fermentations is about pH 4 to 7. For example, the optimum pH for
yeast is from about pH 4 to 5, while the optimum pH for *Zymomonas* is from about pH 5
20 to 6. Typical fermentation times are about 24 to 168 hours (*e.g.*, 24 to 96 hrs) with
temperatures in the range of 20°C to 40°C (*e.g.*, 26°C to 40°C); however thermophilic
microorganisms prefer higher temperatures.

In some embodiments, *e.g.*, when anaerobic organisms are used, at least a portion
of the fermentation is conducted in the absence of oxygen, *e.g.*, under a blanket of an
25 inert gas such as N₂, Ar, He, CO₂ or mixtures thereof. Additionally, the mixture may
have a constant purge of an inert gas flowing through the tank during part of or all of the
fermentation. In some cases, anaerobic conditions can be achieved or maintained by
carbon dioxide production during the fermentation and no additional inert gas is needed.

In some embodiments, all or a portion of the fermentation process can be
30 interrupted before the low molecular weight sugar is completely converted to a product
(*e.g.*, ethanol). The intermediate fermentation products include sugar and carbohydrates
in high concentrations. The sugars and carbohydrates can be isolated via any means
known in the art. These intermediate fermentation products can be used in preparation of
food for human or animal consumption. Additionally or alternatively, the intermediate
35 fermentation products can be ground to a fine particle size in a stainless-steel laboratory

mill to produce a flour-like substance. Jet mixing may be used during fermentation, and in some cases saccharification and fermentation are performed in the same tank.

Nutrients for the microorganisms may be added during saccharification and/or fermentation, for example the food-based nutrient packages described in U.S. Pat. App.

5 Pub. 2012/0052536, filed July 15, 2011, the complete disclosure of which is incorporated herein by reference.

“Fermentation” includes the methods and products that are disclosed in application Nos. PCT/US2012/71093 published June 27, 2013, PCT/US2012/71907 published June 27, 2012, and PCT/US2012/71083 published June 27, 2012 the contents
10 of which are incorporated by reference herein in their entirety.

Mobile fermenters can be utilized, as described in International App. No. PCT/US2007/074028 (which was filed July 20, 2007, was published in English as WO 2008/011598 and designated the United States) and has a US issued Patent No. 8,318,453, the contents of which are incorporated herein in its entirety. Similarly, the
15 saccharification equipment can be mobile. Further, saccharification and/or fermentation may be performed in part or entirely during transit.

FERMENTATION AGENTS

20 The microorganism(s) used in fermentation can be naturally-occurring microorganisms and/or engineered microorganisms. For example, the microorganism can be a bacterium (including, but not limited to, *e.g.*, a cellulolytic bacterium), a fungus, (including, but not limited to, *e.g.*, a yeast), a plant, a protist, *e.g.*, a protozoa or a fungus-like protest (including, but not limited to, *e.g.*, a slime mold), or an alga. When the
25 organisms are compatible, mixtures of organisms can be utilized.

Suitable fermenting microorganisms have the ability to convert carbohydrates, such as glucose, fructose, xylose, arabinose, mannose, galactose, oligosaccharides or polysaccharides into fermentation products. Fermenting microorganisms include strains of the genus *Saccharomyces spp.* (including, but not limited to, *S. cerevisiae* (baker's
30 yeast), *S. distaticus*, *S. uvarum*), the genus *Kluyveromyces*, (including, but not limited to, *K. marxianus*, *K. fragilis*), the genus *Candida* (including, but not limited to, *C. pseudotropicalis*, and *C. brassicae*), *Pichia stipitis* (a relative of *Candida shehatae*), the genus *Clavispora* (including, but not limited to, *C. lusitaniae* and *C. opuntiae*), the genus *Pachysolen* (including, but not limited to, *P. tannophilus*), the genus *Bretannomyces*
35 (including, but not limited to, *e.g.*, *B. clausenii* (Philippidis, G. P., 1996, Cellulose

- bioconversion technology, in Handbook on Bioethanol: Production and Utilization, Wyman, C.E., ed., Taylor & Francis, Washington, DC, 179-212)). Other suitable microorganisms include, for example, *Zymomonas mobilis*, *Clostridium spp.* (including, but not limited to, *C. thermocellum* (Philippidis, 1996, *supra*), *C.*
- 5 *saccharobutylacetonicum*, *C. tyrobutyricum*, *C. saccharobutylicum*, *C. Puniceum*, *C. beijerinckii*, and *C. acetobutylicum*), *Moniliella spp.* (including but not limited to *M. pollinis*, *M. tomentosa*, *M. madida*, *M. nigrescens*, *M. oedocephali*, *M. megachiliensis*), *Yarrowia lipolytica*, *Aureobasidium sp.*, *Trichosporonoides sp.*, *Trigonopsis variabilis*, *Trichosporon sp.*, *Moniliellaacetoabutans sp.*, *Typhula variabilis*, *Candida magnoliae*,
- 10 *Ustilaginomycetes sp.*, *Pseudozyma tsukubaensis*, yeast species of genera *Zygosaccharomyces*, *Debaryomyces*, *Hansenula* and *Pichia*, and fungi of the dematioid genus *Torula* (e.g., *T. corallina*).

Additional microorganisms include the *Lactobacillus* group. Examples include *Lactobacillus casei*, *Lactobacillus rhamnosus*, *Lactobacillus delbrueckii*, *Lactobacillus*

15 *plantarum*, *Lactobacillus coryniformis*, e.g., *Lactobacillus coryniformis subspecies torquens*, *Lactobacillus pentosus*, *Lactobacillus brevis*. Other microorganisms include *Pediococcus penosaceus*, *Rhizopus oryzae*.

Several organisms, such as bacteria, yeasts and fungi, can be utilized to ferment biomass derived products such as sugars and alcohols to succinic acid and similar

20 products. For example, organisms can be selected from; *Actinobacillus succinogenes*, *Anaerobiospirillum succiniciproducens*, *Mannheimia succiniciproducens*, *Ruminococcus flaverfaciens*, *Ruminococcus albus*, *Fibrobacter succinogenes*, *Bacteroides fragilis*, *Bacteroides ruminicola*, *Bacteroides amylophilus*, *Bacteriodes succinogenes*, *Mannheimia succiniciproducens*, *Corynebacterium glutamicum*, *Aspergillus niger*,

25 *Aspergillus fumigatus*, *Byssoschlamys nivea*, *Lentinus degener*, *Paecilomyces varioti*, *Penicillium viniferum*, *Saccharomyces cerevisiae*, *Enterococcus faecali*, *Prevotella ruminicolas*, *Debaryomyces hansenii*, *Candida catenulata* VKM Y-5, *C. mycoderma* VKM Y-240, *C. rugosa* VKM Y-67, *C. paludigena* VKM Y-2443, *C. utilis* VKM Y-74, *C. utilis* 766, *C. zeylanoides* VKM Y-6, *C. zeylanoides* VKM Y-14, *C. zeylanoides* VKM

30 Y-2324, *C. zeylanoides* VKM Y-1543, *C. zeylanoides* VKM Y-2595, *C. valida* VKM Y-934, *Kluyveromyces wickerhamii* VKM Y-589, *Pichia anomala* VKM Y-118, *P. besseyi* VKM Y-2084, *P. media* VKM Y-1381, *P. guilliermondii* H-P-4, *P. guilliermondii* 916, *P. inositolovora* VKM Y-2494, *Saccharomyces cerevisiae* VKM Y-381, *Torulopsis candida* 127, *T. candida* 420, *Yarrowia lipolytica* 12a, *Y. lipolytica* VKM Y-47, *Y.*

lipolytica 69, *Y. lipolytica* VKM Y-57, *Y. lipolytica* 212, *Y. lipolytica* 374/4, *Y. lipolytica* 585, *Y. lipolytica* 695, *Y. lipolytica* 704, and mixtures of these organisms.

Many such microbial strains are publicly available, either commercially or through depositories such as the ATCC (American Type Culture Collection, Manassas, Virginia, USA), the NRRL (Agricultural Research Service Culture Collection, Peoria, Illinois, USA), or the DSMZ (Deutsche Sammlung von Mikroorganismen und Zellkulturen GmbH, Braunschweig, Germany), to name a few.

Commercially available yeasts include, for example, RED STAR®/Lesaffre Ethanol Red (available from Red Star/Lesaffre, USA), FALI® (available from Fleischmann's Yeast, a division of Burns Philip Food Inc., USA), SUPERSTART® (available from Alltech, now Lalemand), GERT STRAND® (available from Gert Strand AB, Sweden) and FERMOIL® (available from DSM Specialties).

DISTILLATION

15

After fermentation, the resulting fluids can be distilled using, for example, a "beer column" to separate ethanol and other alcohols from the majority of water and residual solids. The vapor exiting the beer column can be, *e.g.*, 35% by weight ethanol and can be fed to a rectification column. A mixture of nearly azeotropic (92.5%) ethanol and water from the rectification column can be purified to pure (99.5%) ethanol using vapor-phase molecular sieves. The beer column bottoms can be sent to the first effect of a three-effect evaporator. The rectification column reflux condenser can provide heat for this first effect. After the first effect, solids can be separated using a centrifuge and dried in a rotary dryer. A portion (25%) of the centrifuge effluent can be recycled to fermentation and the rest sent to the second and third evaporator effects. Most of the evaporator condensate can be returned to the process as fairly clean condensate with a small portion split off to waste water treatment to prevent build-up of low-boiling compounds.

30

HYDROCARBON-CONTAINING MATERIALS

In other embodiments utilizing the methods and systems described herein, hydrocarbon-containing materials can be processed. Any process described herein can be used to treat any hydrocarbon-containing material herein described. "Hydrocarbon-containing materials," as used herein, is meant to include oil sands, oil shale, tar sands,

35

coal dust, coal slurry, bitumen, various types of coal, and other naturally-occurring and synthetic materials that include both hydrocarbon components and solid matter. The solid matter can include rock, sand, clay, stone, silt, drilling slurry, or other solid organic and/or inorganic matter. The term can also include waste products such as drilling waste
5 and by-products, refining waste and by-products, or other waste products containing hydrocarbon components, such as asphalt shingling and covering, asphalt pavement, etc.

In yet other embodiments utilizing the methods and systems described herein, wood and wood containing produces can be processed. For example, lumber products can be processed, e.g. boards, sheets, laminates, beams, particle boards, composites,
10 rough cut wood, soft wood and hard wood. In addition, cut trees, bushes, wood chips, saw dust, roots, bark, stumps, decomposed wood and other wood containing biomass material can be processed.

CONVEYING SYSTEMS

15

Various conveying systems can be used to convey the biomass material, for example, as discussed, to a vault, and under an electron beam in a vault. Exemplary conveyors are belt conveyors, pneumatic conveyors, screw conveyors, carts, trains, trains or carts on rails, elevators, front loaders, backhoes, cranes, various scrapers and shovels,
20 trucks, and throwing devices can be used. For example, vibratory conveyors can be used in various processes described herein. Vibratory conveyors are described in PCT/US2013/64289 filed October 10, 2013 the full disclosure of which is incorporated by reference herein.

Vibratory conveyors are particularly useful for spreading the material and
25 producing a uniform layer on the conveyor trough surface. For example the initial feedstock can form a pile of material that can be at least four feet high (e.g., at least about 3 feet, at least about 2 feet, at least about 1 foot, at least about 6 inches, at least about 5 inches, at least about, 4 inches, at least about 3 inches, at least about 2 inches, at least about 1 inch, at least about ½ inch) and spans less than the width of the conveyor
30 (e.g., less than about 10%, less than about 20%, less than about 30%, less than about 40%, less than about 50%, less than about 60%, less than about 70%, less than about 80%, less than about 90%, less than about 95%, less than about 99%). The vibratory conveyor can spread the material to span the entire width of the conveyor trough and have a uniform thickness, preferably as discussed above. In some cases, an additional
35 spreading method can be useful. For example, a spreader such as a broadcast spreader, a

drop spreader (e.g., a CHRISTY SPREADER™) or combinations thereof can be used to drop (e.g., place, pour, spill and/or sprinkle) the feedstock over a wide area. Optionally, the spreader can deliver the biomass as a wide shower or curtain onto the vibratory conveyor. Additionally, a second conveyor, upstream from the first conveyor (e.g., the first conveyor is used in the irradiation of the feedstock), can drop biomass onto the first conveyor, where the second conveyor can have a width transverse to the direction of conveying smaller than the first conveyor. In particular, when the second conveyor is a vibratory conveyor, the feedstock is spread by the action of the second and first conveyor. In some optional embodiments, the second conveyor ends in a bias cross cut discharge (e.g., a bias cut with a ratio of 4:1) so that the material can be dropped as a wide curtain (e.g., wider than the width of the second conveyor) onto the first conveyor. The initial drop area of the biomass by the spreader (e.g., broadcast spreader, drop spreader, conveyor, or cross cut vibratory conveyor) can span the entire width of the first vibratory conveyor, or it can span part of this width. Once dropped onto the conveyor, the material is spread even more uniformly by the vibrations of the conveyor so that, preferably, the entire width of the conveyor is covered with a uniform layer of biomass. In some embodiments combinations of spreaders can be used. Some methods of spreading a feed stock are described in U.S. Patent No. 7,153,533, filed July 23, 2002 and published December 26, 2006, the entire disclosure of which is incorporated herein by reference.

Generally, it is preferred to convey the material as quickly as possible through an electron beam to maximize throughput. For example, the material can be conveyed at rates of at least 1 ft/min, e.g., at least 2 ft/min, at least 3 ft/min, at least 4 ft/min, at least 5 ft/min, at least 10 ft/min, at least 15 ft/min, at least 20 ft/min, at least 25 ft/min, at least 30 ft/min, at least 40 ft/min, at least 50 ft/min, at least 60 ft/min, at least 70 ft/min, at least 80 ft/min, at least 90 ft/min. The rate of conveying is related to the beam current and targeted irradiation dose, for example, for a ¼ inch thick biomass spread over a 5.5 foot wide conveyor and 100 mA, the conveyor can move at about 20 ft/min to provide a useful irradiation dosage (e.g. about 10 Mrad for a single pass), at 50 mA the conveyor can move at about 10 ft/min to provide approximately the same irradiation dosage.

The rate at which material can be conveyed depends on the shape and mass of the material being conveyed, and the desired amount. Flowing materials e.g., particulate materials, are particularly amenable to conveying with vibratory conveyors. Conveying speeds can, for example be, at least 100 lb/hr (e.g., at least 500 lb/hr, at least 1000 lb/hr, at least 2000 lb/hr, at least 3000 lb/hr, at least 4000 lb/hr, at least 5000 lb/hr, at least

10,000 lb/hr, at least 15,000 lb/hr, or even at least 25,000 lb/hr). Some typical conveying speeds can be between about 1000 and 10,000 lb/hr, (e.g., between about 1000 lb/hr and 8000 lb/hr, between about 2000 and 7000 lb/hr, between about 2000 and 6000 lb/hr, between about 2000 and 5000 lb/hr, between about 2000 and 4500 lb/hr, between about 1500 and 5000 lb/hr, between about 3000 and 7000 lb/hr, between about 3000 and 6000 lb/hr, between about 4000 and 6000 lb/hr and between about 4000 and 5000 lb/hr).

Typical conveying speeds depend on the density of the material. For example, for a biomass with a density of about 35 lb/ft³, and a conveying speed of about 5000 lb/hr, the material is conveyed at a rate of about 143 ft³/hr, if the material is 1/4" thick and is in a trough 5.5 ft wide, the material is conveyed at a rate of about 1250 ft/hr (about 21 ft/min). Rates of conveying the material can therefore vary greatly. Preferably, for example, a 1/4" thick layer of biomass, is conveyed at speeds of between about 5 and 100 ft/min (e.g. between about 5 and 100 ft/min, between about 6 and 100 ft/min, between about 7 and 100 ft/min, between about 8 and 100 ft/min, between about 9 and 100 ft/min, between about 10 and 100 ft/min, between about 11 and 100 ft/min, between about 12 and 100 ft/min, between about 13 and 100 ft/min, between about 14 and 100 ft/min, between about 15 and 100 ft/min, between about 20 and 100 ft/min, between about 30 and 100 ft/min, between about 40 and 100 ft/min, between about 2 and 60 ft/min, between about 3 and 60 ft/min, between about 5 and 60 ft/min, between about 6 and 60 ft/min, between about 7 and 60 ft/min, between about 8 and 60 ft/min, between about 9 and 60 ft/min, between about 10 and 60 ft/min, between about 15 and 60 ft/min, between about 20 and 60 ft/min, between about 30 and 60 ft/min, between about 40 and 60 ft/min, between about 2 and 50 ft/min, between about 3 and 50 ft/min, between about 5 and 50 ft/min, between about 6 and 50 ft/min, between about 7 and 50 ft/min, between about 8 and 50 ft/min, between about 9 and 50 ft/min, between about 10 and 50 ft/min, between about 15 and 50 ft/min, between about 20 and 50 ft/min, between about 30 and 50 ft/min, between about 40 and 50 ft/min). It is preferable that the material be conveyed at a constant rate, for example, to help maintain a constant irradiation of the material as it passes under the electron beam (e.g., shower, field).

The vibratory conveyors described can include screens used for sieving and sorting materials. Port openings on the side or bottom of the troughs can be used for sorting, selecting or removing specific materials, for example, by size or shape. Some conveyors have counterbalances to reduce the dynamic forces on the support structure. Some vibratory conveyors are configured as spiral elevators, are designed to curve around surfaces and/or are designed to drop material from one conveyor to another (e.g.,

in a step, cascade or as a series of steps or a stair). Along with conveying materials conveyors can be used, by themselves or coupled with other equipment or systems, for screening, separating, sorting, classifying, distributing, sizing, inspection, picking, metal removing, freezing, blending, mixing, orienting, heating, cooking, drying, dewatering, cleaning, washing, leaching, quenching, coating, de-dusting and/or feeding. The conveyors can also include covers (e.g., dust-tight covers), side discharge gates, bottom discharge gates, special liners (e.g., anti-stick, stainless steel, rubber, custom steal, and or grooved), divided troughs, quench pools, screens, perforated plates, detectors (e.g., metal detectors), high temperature designs, food grade designs, heaters, dryers and or coolers. In addition, the trough can be of various shapes, for example, flat bottomed, vee shaped bottom, flanged at the top, curved bottom, flat with ridges in any direction, tubular, half pipe, covered or any combinations of these. In particular, the conveyors can be coupled with an irradiation systems and/or equipment.

The conveyors (e.g., vibratory conveyor) can be made of corrosion resistant materials. The conveyors can utilize structural materials that include stainless steel (e.g., 304, 316 stainless steel, HASTELLOY® ALLOYS and INCONEL® Alloys). For example, HASTELLOY® Corrosion-Resistant alloys from Hynes (Kokomo, Indiana, USA) such as HASTELLOY® B-3® ALLOY, HASTELLOY® HYBRID-BC1® ALLOY, HASTELLOY® C-4 ALLOY, HASTELLOY® C-22® ALLOY, HASTELLOY® C-22HS® ALLOY, HASTELLOY® C-276 ALLOY, HASTELLOY® C-2000® ALLOY, HASTELLOY® G-30® ALLOY, HASTELLOY® G-35® ALLOY, HASTELLOY® N ALLOY and HASTELLOY® ULTIMET® alloy.

The vibratory conveyors can include non-stick release coatings, for example, TUFFLON™ (Dupont, Delaware, USA). The vibratory conveyors can also include corrosion resistant coatings. For example, coatings that can be supplied from Metal Coatings Corp (Houston, Texas, USA) and others such as Fluoropolymer, XYLAN®, Molybdenum Disulfide, Epoxy Phenolic, Phosphate- ferrous metal coating, Polyurethane- high gloss topcoat for epoxy, inorganic zinc, Poly Tetrafluoro ethylene, PPS/Ryton®, fluorinated ethylene propylene, PVDF/DYKOR®, ECTFE/HALAR® and Ceramic Epoxy Coating. The coatings can improve resistance to process gases (e.g., ozone), chemical corrosion, pitting corrosion, galling corrosion and oxidation.

Optionally, in addition to the conveying systems described herein, one or more other conveying systems can be enclosed. When using an enclosure, the enclosed conveyor can also be purged with an inert gas so as to maintain an atmosphere at a reduced oxygen level. Keeping oxygen levels low avoids the formation of ozone which

in some instances is undesirable due to its reactive and toxic nature. For example, the oxygen can be less than about 20% (*e.g.*, less than about 10%, less than about 1%, less than about 0.1%, less than about 0.01%, or even less than about 0.001% oxygen).

Purging can be done with an inert gas including, but not limited to, nitrogen, argon,
5 helium or carbon dioxide. This can be supplied, for example, from a boil off of a liquid source (*e.g.*, liquid nitrogen or helium), generated or separated from air *in situ*, or supplied from tanks. The inert gas can be recirculated and any residual oxygen can be removed using a catalyst, such as a copper catalyst bed. Alternatively, combinations of purging, recirculating and oxygen removal can be done to keep the oxygen levels low.

10 The enclosed conveyor can also be purged with a reactive gas that can react with the biomass. This can be done before, during or after the irradiation process. The reactive gas can be, but is not limited to, nitrous oxide, ammonia, oxygen, ozone, hydrocarbons, aromatic compounds, amides, peroxides, azides, halides, oxyhalides, phosphides, phosphines, arsines, sulfides, thiols, boranes and/or hydrides. The reactive
15 gas can be activated in the enclosure, *e.g.*, by irradiation (*e.g.*, electron beam, UV irradiation, microwave irradiation, heating, IR radiation), so that it reacts with the biomass. The biomass itself can be activated, for example by irradiation. Preferably the biomass is activated by the electron beam, to produce radicals which then react with the activated or unactivated reactive gas, *e.g.*, by radical coupling or quenching.

20 Purging gases supplied to an enclosed conveyor can also be cooled, for example below about 25°C, below about 0°C, below about -40°C, below about -80°C, below about -120°C. For example, the gas can be boiled off from a compressed gas such as liquid nitrogen or sublimed from solid carbon dioxide. As an alternative example, the gas can be cooled by a chiller or part of or the entire conveyor can be cooled.

25

OTHER EMBODIMENTS

Any material, processes or processed materials discussed herein can be used to make products and/or intermediates such as composites, fillers, binders, plastic additives,
30 adsorbents and controlled release agents. The methods can include densification, for example, by applying pressure and heat to the materials. For example, composites can be made by combining fibrous materials with a resin or polymer. For example, radiation cross-linkable resin, *e.g.*, a thermoplastic resin can be combined with a fibrous material to provide a fibrous material/cross-linkable resin combination. Such materials can be, for
35 example, useful as building materials, protective sheets, containers and other structural

materials (*e.g.*, molded and/or extruded products). Absorbents can be, for example, in the form of pellets, chips, fibers and/or sheets. Adsorbents can be used, for example, as pet bedding, packaging material or in pollution control systems. Controlled release matrices can also be the form of, for example, pellets, chips, fibers and or sheets. The controlled
5 release matrices can, for example, be used to release drugs, biocides, fragrances. For example, composites, absorbents and control release agents and their uses are described in International Serial No. PCT/US2006/010648, filed March 23, 2006, and U.S. Patent No. 8,074,910 filed November 22, 2011, the entire disclosures of which are herein incorporated by reference.

10 In some instances the biomass material is treated at a first level to reduce recalcitrance, *e.g.*, utilizing accelerated electrons, to selectively release one or more sugars (*e.g.*, xylose). The biomass can then be treated to a second level to release one or more other sugars (*e.g.*, glucose). Optionally, the biomass can be dried between treatments. The treatments can include applying chemical and biochemical treatments to
15 release the sugars. For example, a biomass material can be treated to a level of less than about 20 Mrad (*e.g.*, less than about 15 Mrad, less than about 10 Mrad, less than about 5 Mrad, less than about 2 Mrad) and then treated with a solution of sulfuric acid, containing less than 10% sulfuric acid (*e.g.*, less than about 9%, less than about 8%, less than about 7%, less than about 6%, less than about 5%, less than about 4%, less than
20 about 3%, less than about 2%, less than about 1%, less than about 0.75%, less than about 0.50 %, less than about 0.25%) to release xylose. Xylose, for example, that is released into solution, can be separated from solids and optionally the solids washed with a solvent/solution (*e.g.*, with water and/or acidified water). Optionally, the solids can be dried, for example in air and/or under vacuum optionally with heating (*e.g.*, below about
25 150 deg C, below about 120 deg C) to a water content below about 25 wt.% (below about 20 wt.%, below about 15 wt.%, below about 10 wt.% and even below about 5 wt.%). The solids can then be treated with a level of less than about 30 Mrad (*e.g.*, less than about 25 Mrad, less than about 20 Mrad, less than about 15 Mrad, less than about 10 Mrad, less than about 5 Mrad, less than about 1 Mrad or even not at all) and then treated
30 with an enzyme (*e.g.*, a cellulase) to release glucose. The glucose (*e.g.*, glucose in solution) can be separated from the remaining solids. The solids can then be further processed, for example, utilized to make energy or other products (*e.g.*, lignin derived products).

FLAVORS, FRAGRANCES AND COLORANTS

Any of the products and/or intermediates described herein, for example, produced by the processes, systems and/or equipment described herein, can be combined with flavors, fragrances, colorants and/or mixtures of these. For example, any one or more of
5 (optionally along with flavors, fragrances and/or colorants) sugars, organic acids, fuels, polyols, such as sugar alcohols, biomass, fibers and composites can be combined with (*e.g.*, formulated, mixed or reacted) or used to make other products. For example, one or more such product can be used to make soaps, detergents, candies, drinks (*e.g.*, cola, wine, beer, liquors such as gin or vodka, sports drinks, coffees, teas), syrups,
10 pharmaceuticals, adhesives, sheets (*e.g.*, woven, none woven, filters, tissues) and/or composites (*e.g.*, boards). For example, one or more such product can be combined with herbs, flowers, petals, spices, vitamins, potpourri, or candles. For example, the formulated, mixed or reacted combinations can have flavors/fragrances of grapefruit, orange, apple, raspberry, banana, lettuce, celery, cinnamon, chocolate, vanilla,
15 peppermint, mint, onion, garlic, pepper, saffron, ginger, milk, wine, beer, tea, lean beef, fish, clams, olive oil, coconut fat, pork fat, butter fat, beef bouillon, legume, potatoes, marmalade, ham, coffee and cheeses.

Flavors, fragrances and colorants can be added in any amount, such as between about 0.001 wt.% to about 30 wt.%, *e.g.*, between about 0.01 to about 20, between about
20 0.05 to about 10, or between about 0.1 wt.% to about 5 wt.%. These can be formulated, mixed and or reacted (*e.g.*, with any one of more product or intermediate described herein) by any means and in any order or sequence (*e.g.*, agitated, mixed, emulsified, gelled, infused, heated, sonicated, and/or suspended). Fillers, binders, emulsifier, antioxidants can also be utilized, for example protein gels, starches and silica.

25 In one embodiment the flavors, fragrances and colorants can be added to the biomass immediately after the biomass is irradiated such that the reactive sites created by the irradiation may react with reactive compatible sites of the flavors, fragrances, and colorants.

The flavors, fragrances and colorants can be natural and/or synthetic materials.
30 These materials can be one or more of a compound, a composition or mixtures of these (*e.g.*, a formulated or natural composition of several compounds). Optionally, the flavors, fragrances, antioxidants and colorants can be derived biologically, for example, from a fermentation process (*e.g.*, fermentation of saccharified materials as described herein). Alternatively, or additionally these flavors, fragrances and colorants can be harvested
35 from a whole organism (*e.g.*, plant, fungus, animal, bacteria or yeast) or a part of an

organism. The organism can be collected and or extracted to provide color, flavors, fragrances and/or antioxidant by any means including utilizing the methods, systems and equipment described herein, hot water extraction, supercritical fluid extraction, chemical extraction (*e.g.*, solvent or reactive extraction including acids and bases), mechanical
 5 extraction (*e.g.*, pressing, comminuting, filtering), utilizing an enzyme, utilizing a bacteria such as to break down a starting material, and combinations of these methods. The compounds can be derived by a chemical reaction, for example, the combination of a sugar (*e.g.*, as produced as described herein) with an amino acid (Maillard reaction). The flavor, fragrance, antioxidant and/or colorant can be an intermediate and or product
 10 produced by the methods, equipment or systems described herein, for example and ester and a lignin derived product.

Some examples of flavor, fragrances or colorants are polyphenols. Polyphenols are pigments responsible for the red, purple and blue colorants of many fruits, vegetables, cereal grains, and flowers. Polyphenols also can have antioxidant properties
 15 and often have a bitter taste. The antioxidant properties make these important preservatives. One class of polyphenols are the flavonoids, such as Anthocyanidines, flavanols, flavan-3-ols, s, flavanones and flavanonols. Other phenolic compounds that can be used include phenolic acids and their esters, such as chlorogenic acid and polymeric tannins.

20 Among the colorants inorganic compounds, minerals or organic compounds can be used, for example titanium dioxide, zinc oxide, aluminum oxide, cadmium yellow (*E.g.*, CdS), cadmium orange (*e.g.*, CdS with some Se), alizarin crimson (*e.g.*, synthetic or non-synthetic rose madder), ultramarine (*e.g.*, synthetic ultramarine, natural ultramarine, synthetic ultramarine violet), cobalt blue, cobalt yellow, cobalt green,
 25 viridian (*e.g.*, hydrated chromium(III)oxide), chalcophyllite, conichalcite, cornubite, cornwallite and licronite. Black pigments such as carbon black and self-dispersed blacks may be used.

Some flavors and fragrances that can be utilized include ACALEA TBHQ, ACET C-6, ALLYL AMYL GLYCOLATE, ALPHA TERPINEOL, AMBRETTOLIDE,
 30 AMBRINOL 95, ANDRANE, APHERMATE, APPLELIDE, BACDANOL®, BERGAMAL, BETA IONONE EPOXIDE, BETA NAPHTHYL ISO-BUTYL ETHER, BICYCLONONALACTONE, BORNAFIX®, CANTHOXAL, CASHMERAN®, CASHMERAN® VELVET, CASSIFFIX®, CEDRAFIX, CEDRAMBER®, CEDRYL ACETATE, CELESTOLIDE, CINNAMALVA, CITRAL DIMETHYL ACETATE,
 35 CITROLATE™, CITRONELLOL 700, CITRONELLOL 950, CITRONELLOL

COEUR, CITRONELLYL ACETATE, CITRONELLYL ACETATE PURE,
 CITRONELLYL FORMATE, CLARYCET, CLONAL, CONIFERAN, CONIFERAN
 PURE, CORTEX ALDEHYDE 50% PEOMOSA, CYCLABUTE, CYCLACET®,
 CYCLAPROP®, CYCLEMAX™, CYCLOHEXYL ETHYL ACETATE, DAMASCOL,
 5 DELTA DAMASCONI, DIHYDRO CYCLACET, DIHYDRO MYRCENOL,
 DIHYDRO TERPINEOL, DIHYDRO TERPINYL ACETATE, DIMETHYL
 CYCLORMOL, DIMETHYL OCTANOL PQ, DIMYRCETOL, DIOLA, DIPENTENE,
 DULCINYL® RECRYSTALLIZED, ETHYL-3-PHENYL GLYCIDATE,
 FLEURAMONE, FLEURANIL, FLORAL SUPER, FLORAL OZONE, FLORITOL,
 10 FRAISTONE, FRUCTONE, GALAXOLIDE® 50, GALAXOLIDE® 50 BB,
 GALAXOLIDE® 50 IPM, GALAXOLIDE® UNDIUTED, GALBASCONI,
 GERALDEHYDE, GERANIOL 5020, GERANIOL 600 TYPE, GERANIOL 950,
 GERANIOL 980 (PURE), GERANIOL CFT COEUR, GERANIOL COEUR,
 GERANYL ACETATE COEUR, GERANYL ACETATE, PURE, GERANYL
 15 FORMATE, GRISALVA, GUAIYL ACETATE, HELLIONAL™, HERBAC,
 HERBALIME™, HEXADECANOLIDE, HEXALON, HEXENYL SALICYLATE CIS
 3-, HYACINTH BODY, HYACINTH BODY NO. 3, HYDRATROPIC
 ALDEHYDE.DMA, HYDROXYOL, INDOLAROMI, INTRELEVEN ALDEHYDE,
 INTRELEVEN ALDEHYDE SPECIAL, IONONE ALPHA, IONONE BETA, ISO
 20 CYCLO CITRAL, ISO CYCLO GERANIOL, ISO E SUPER®, ISOBUTYL
 QUINOLINE, JASMAI, JESSEMAL®, KHARISMAI®, KHARISMAI® SUPER,
 KHUSINIL, KOAVONE®, KOHNOOL®, LITFAROMI™, LIMOXAL,
 LINDENOL™, LYRAL®, LYRAME SUPER, MANDARIN ALD 10% TRI ETH,
 CTR, MARTIMA, MCK CHINESE, MEIJIT™, MELAFLEUR, MELOZONE,
 25 METHYL ANTHRANILATE, METHYL IONONE ALPHA EXTRA, METHYL
 IONONE GAMMA A, METHYL IONONE GAMMA COEUR, METHYL IONONE
 GAMMA PURE, METHYL LAVENDER KETONE, MONTAVERDI®, MUGUESIA,
 MUGUET ALDEHYDE 50, MUSK Z4, MYRAC ALDEHYDE, MYRCENYL
 ACETATE, NECTARATE™, NEROL 900, NERYL ACETATE, OCIMENL,
 30 OCTACETAL, ORANGE FLOWER ETHER, ORIVONE, ORRINIF 25%,
 OXASPIRANE, OZOFLEUR, PAMPLEFLEUR®, PEOMOSA, PHENOXANOL®,
 PICONIA, PRECYCLEMONE B, PRENYL ACETATE, PRISMANTOL, RESEDA
 BODY, ROSALVA, ROSAMUSK, SANJINOL, SANTALIF™, SYVERTAL,
 TERPINEOL, TERPINOLENE 20, TERPINOLENE 90 PQ, TERPINOLENE RECT.,
 35 TERPINYL ACETATE, TERPINYL ACETATE JAX, TETRAHYDRO, MUGUOL®,

TETRAHYDRO MYRCENOL, TETRAMERAN, TIMBERSILK™, TOBACAROL,
 TRIMOFIX® O TT, TRIPLAL®, TRISAMBER®, VANORIS, VERDOX™,
 VERDOX™ HC, VERTENEX®, VERTENEX® HC, VERTOPIX® COEUR,
 VERTOLIFF, VERTOLIFF ISO, VIOLIFF, VIVALDIE, ZENOLIDE, ABS INDIA 75
 5 PCT MIGLYOL, ABS MOROCCO 50 PCT DPG, ABS MOROCCO 50 PCT TEC,
 ABSOLUTE FRENCH, ABSOLUTE INDIA, ABSOLUTE MD 50 PCT BB,
 ABSOLUTE MOROCCO, CONCENTRATE PG, TINCTURE 20 PCT, AMBERGRIS,
 AMBRETTE ABSOLUTE, AMBRETTE SEED OIL, ARMOISE OIL 70 PCT
 THUYONE, BASIL ABSOLUTE GRAND VERT, BASIL GRAND VERT ABS MD,
 10 BASIL OIL GRAND VERT, BASIL OIL VERVEINA, BASIL OIL VIETNAM, BAY
 OIL TERPENELESS, BEESWAX ABS N G, BEESWAX ABSOLUTE, BENZOIN
 RESINOID SIAM, BENZOIN RESINOID SIAM 50 PCT DPG, BENZOIN RESINOID
 SIAM 50 PCT PG, BENZOIN RESINOID SIAM 70.5 PCT TEC, BLACKCURRANT
 BUD ABS 65 PCT PG, BLACKCURRANT BUD ABS MD 37 PCT TEC,
 15 BLACKCURRANT BUD ABS MIGLYOL, BLACKCURRANT BUD ABSOLUTE
 BURGUNDY, BOIS DE ROSE OIL, BRAN ABSOLUTE, BRAN RESINOID,
 BROOM ABSOLUTE ITALY, CARDAMOM GUATEMALA CO2 EXTRACT,
 CARDAMOM OIL GUATEMALA, CARDAMOM OIL INDIA, CARROT HEART,
 CASSIE ABSOLUTE EGYPT, CASSIE ABSOLUTE MD 50 PCT IPM, CASTOREUM
 20 ABS 90 PCT TEC, CASTOREUM ABS C 50 PCT MIGLYOL, CASTOREUM
 ABSOLUTE, CASTOREUM RESINOID, CASTOREUM RESINOID 50 PCT DPG,
 CEDROL CEDRENE, CEDRUS ATLANTICA OIL REDIST, CHAMOMILE OIL
 ROMAN, CHAMOMILE OIL WILD, CHAMOMILE OIL WILD LOW LIMONENE,
 CINNAMON BARK OIL CEYLAN, CISTE ABSOLUTE, CISTE ABSOLUTE
 25 COLORLESS, CITRONELLA OIL ASIA IRON FREE, CIVET ABS 75 PCT PG,
 CIVET ABSOLUTE, CIVET TINCTURE 10 PCT, CLARY SAGE ABS FRENCH
 DECOL, CLARY SAGE ABSOLUTE FRENCH, CLARY SAGE C'LESS 50 PCT PG,
 CLARY SAGE OIL FRENCH, COPAIBA BALSAM, COPAIBA BALSAM OIL,
 CORIANDER SEED OIL, CYPRESS OIL, CYPRESS OIL ORGANIC, DAVANA OIL,
 30 GALBANOL, GALBANUM ABSOLUTE COLORLESS, GALBANUM OIL,
 GALBANUM RESINOID, GALBANUM RESINOID 50 PCT DPG, GALBANUM
 RESINOID HERCOLYN BHT, GALBANUM RESINOID TEC BHT, GENTIANE
 ABSOLUTE MD 20 PCT BB, GENTIANE CONCRETE, GERANIUM ABS EGYPT
 MD, GERANIUM ABSOLUTE EGYPT, GERANIUM OIL CHINA, GERANIUM OIL
 35 EGYPT, GINGER OIL 624, GINGER OIL RECTIFIED SOLUBLE, GUAIAACWOOD

- HEART, HAY ABS MD 50 PCT BB, HAY ABSOLUTE, HAY ABSOLUTE MD 50
PCT TEC, HEALINGWOOD, HYSSOP OIL ORGANIC, IMMORTELLE ABS YUGO
MD 50 PCT TEC, IMMORTELLE ABSOLUTE SPAIN, IMMORTELLE ABSOLUTE
YUGO, JASMIN ABS INDIA MD, JASMIN ABSOLUTE EGYPT, JASMIN
5 ABSOLUTE INDIA, ASMIN ABSOLUTE MOROCCO, JASMIN ABSOLUTE
SAMBAC, JONQUILLE ABS MD 20 PCT BB, JONQUILLE ABSOLUTE France,
JUNIPER BERRY OIL FLG, JUNIPER BERRY OIL RECTIFIED SOLUBLE,
LABDANUM RESINOID 50 PCT TEC, LABDANUM RESINOID BB, LABDANUM
RESINOID MD, LABDANUM RESINOID MD 50 PCT BB, LAVANDIN ABSOLUTE
10 II, LAVANDIN ABSOLUTE MD, LAVANDIN OIL ABRIAL ORGANIC,
LAVANDIN OIL GROSSO ORGANIC, LAVANDIN OIL SUPER, LAVENDER
ABSOLUTE H, LAVENDER ABSOLUTE MD, LAVENDER OIL COUMARIN
FREE, LAVENDER OIL COUMARIN FREE ORGANIC, LAVENDER OIL
MAILLETTE ORGANIC, LAVENDER OIL MT, MACE ABSOLUTE BB,
15 MAGNOLIA FLOWER OIL LOW METHYL EUGENOL, MAGNOLIA FLOWER
OIL, MAGNOLIA FLOWER OIL MD, MAGNOLIA LEAF OIL, MANDARIN OIL
MD, MANDARIN OIL MD BHT, MATE ABSOLUTE BB, MOSS TREE ABSOLUTE
MD TEX IFRA 43, MOSS-OAK ABS MD TEC IFRA 43, MOSS-OAK ABSOLUTE
IFRA 43, MOSS-TREE ABSOLUTE MD IPM IFRA 43, MYRRH RESINOID BB,
20 MYRRH RESINOID MD, MYRRH RESINOID TEC, MYRTLE OIL IRON FREE,
MYRTLE OIL TUNISIA RECTIFIED, NARCISSE ABS MD 20 PCT BB, NARCISSE
ABSOLUTE FRENCH, NEROLI OIL TUNISIA, NUTMEG OIL TERPENELESS,
OEILLET ABSOLUTE, OLIBANUM RESINOID, OLIBANUM RESINOID BB,
OLIBANUM RESINOID DPG, OLIBANUM RESINOID EXTRA 50 PCT DPG,
25 OLIBANUM RESINOID MD, OLIBANUM RESINOID MD 50 PCT DPG,
OLIBANUM RESINOID TEC, OPOPONAX RESINOID TEC, ORANGE BIGARADE
OIL MD BHT, ORANGE BIGARADE OIL MD SCFC, ORANGE FLOWER
ABSOLUTE TUNISIA, ORANGE FLOWER WATER ABSOLUTE TUNISIA,
ORANGE LEAF ABSOLUTE, ORANGE LEAF WATER ABSOLUTE TUNISIA,
30 ORRIS ABSOLUTE ITALY, ORRIS CONCRETE 15 PCT IRONE, ORRIS
CONCRETE 8 PCT IRONE, ORRIS NATURAL 15 PCT IRONE 4095C, ORRIS
NATURAL 8 PCT IRONE 2942C, ORRIS RESINOID, OSMANTHUS ABSOLUTE,
OSMANTHUS ABSOLUTE MD 50 PCT BB, PATCHOULI HEART N°3,
PATCHOULI OIL INDONESIA, PATCHOULI OIL INDONESIA IRON FREE,
35 PATCHOULI OIL INDONESIA MD, PATCHOULI OIL REDIST, PENNYROYAL

HEART, PEPPERMINT ABSOLUTE MD, PETITGRAIN BIGARADE OIL TUNISIA,
 PETITGRAIN CITRONNIER OIL, PETITGRAIN OIL PARAGUAY TERPENELESS,
 PETITGRAIN OIL TERPENELESS STAB, PIMENTO BERRY OIL, PIMENTO LEAF
 OIL, RHODINOL EX GERANIUM CHINA, ROSE ABS BULGARIAN LOW
 5 METHYL EUGENOL, ROSE ABS MOROCCO LOW METHYL EUGENOL, ROSE
 ABS TURKISH LOW METHYL EUGENOL, ROSE ABSOLUTE, ROSE ABSOLUTE
 BULGARIAN, ROSE ABSOLUTE DAMASCENA, ROSE ABSOLUTE MD, ROSE
 ABSOLUTE MOROCCO, ROSE ABSOLUTE TURKISH, ROSE OIL BULGARIAN,
 ROSE OIL DAMASCENA LOW METHYL EUGENOL, ROSE OIL TURKISH,
 10 ROSEMARY OIL CAMPHOR ORGANIC, ROSEMARY OIL TUNISIA,
 SANDALWOOD OIL INDIA, SANDALWOOD OIL INDIA RECTIFIED,
 SANTALOL, SCHINUS MOLLE OIL, ST JOHN BREAD TINCTURE 10 PCT,
 STYRAX RESINOID, STYRAX RESINOID, TAGETE OIL, 'TEA TREE HEART',
 TONKA BEAN ABS 50 PCT SOLVENTS, TONKA BEAN ABSOLUTE, TUBEROSE
 15 ABSOLUTE INDIA, VETIVER HEART EXTRA, VETIVER OIL HAITI, VETIVER
 OIL HAITI MD, VETIVER OIL JAVA, VETIVER OIL JAVA MD, VIOLET LEAF
 ABSOLUTE EGYPT, VIOLET LEAF ABSOLUTE EGYPT DECOL, VIOLET LEAF
 ABSOLUTE FRENCH, VIOLET LEAF ABSOLUTE MD 50 PCT BB, WORMWOOD
 OIL TERPENELESS, YLANG EXTRA OIL, YLANG III OIL and combinations of
 20 these.

The colorants can be among those listed in the Color Index International by the
 Society of Dyers and Colourists. Colorants include dyes and pigments and include those
 commonly used for coloring textiles, paints, inks and inkjet inks. Some colorants that
 can be utilized include carotenoids, arylyde yellows, diarylyde yellows, β -naphthols,
 25 naphthols, benzimidazolones, disazo condensation pigments, pyrazolones, nickel azo
 yellow, phthalocyanines, quinacridones, perylenes and perinones, isoindolinone and
 isoindoline pigments, triarylcarbonium pigments, diketopyrrolo-pyrrole pigments,
 thioindigoids. Carotenoids include, for example, alpha-carotene, beta-carotene, gamma-
 carotene, lycopene, lutein and astaxanthin, Annatto extract, Dehydrated beets (beet
 30 powder), Carthaxanthin, Caramel, β -Apo-8'-carotenal, Cochineal extract, Carmine,
 Sodium copper chlorophyllin, toasted partially defatted cooked cottonseed flour, Ferrous
 gluconate, Ferrous lactate, Grape color extract, Grape skin extract (enocianina), Carrot
 oil, Paprika, Paprika oleoresin, Mica-based pearlescent pigments, Riboflavin, Saffron,
 Titanium dioxide, Tomato lycopene extract, tomato lycopene concentrate, Turmeric,
 35 Turmeric oleoresin, FD&C Blue No. 1, FD&C Blue No. 2, FD&C Green No. 3, Orange

B, Citrus Red No. 2, FD&C Red No. 3, FD&C Red No. 40, FD&C Yellow No. 5, FD&C Yellow No. 6, Alumina (dried aluminum hydroxide), Calcium carbonate, Potassium sodium copper chlorophyllin (chlorophyllin-copper complex), Dihydroxyacetone, Bismuth oxychloride, Ferric ammonium ferrocyanide, Ferric ferrocyanide, Chromium

5 hydroxide green, Chromium oxide greens, Guanine, Pyrophyllite, Talc, Aluminum powder, Bronze powder, Copper powder, Zinc oxide, D&C Blue No. 4, D&C Green No. 5, D&C Green No. 6, D&C Green No. 8, D&C Orange No. 4, D&C Orange No. 5, D&C Orange No. 10, D&C Orange No. 11, FD&C Red No. 4, D&C Red No. 6, D&C Red No. 7, D&C Red No. 17, D&C Red No. 21, D&C Red No. 22, D&C Red No. 27, D&C Red

10 No. 28, D&C Red No. 30, D&C Red No. 31, D&C Red No. 33, D&C Red No. 34, D&C Red No. 36, D&C Red No. 39, D&C Violet No. 2, D&C Yellow No. 7, Ext. D&C Yellow No. 7, D&C Yellow No. 8, D&C Yellow No. 10, D&C Yellow No. 11, D&C Black No. 2, D&C Black No. 3 (3), D&C Brown No. 1, Ext. D&C, Chromium-cobalt-aluminum oxide, Ferric ammonium citrate, Pyrogallol, Logwood extract, 1,4-Bis[(2-

15 hydroxy-ethyl)amino]-9,10-anthracenedione bis(2-propenoic)ester copolymers, 1,4-Bis[(2-methylphenyl)amino]-9,10-anthracenedione, 1,4-Bis[4-(2-methacryloxyethyl)phenylamino] anthraquinone copolymers, Carbazole violet, Chlorophyllin-copper complex, Chromium-cobalt-aluminum oxide,, C.I. Vat Orange 1, 2-[[2,5-Diethoxy-4-[(4-methylphenyl)thiol] phenyl]azo]-1,3,5-benzenetriol, 16,23-Dihydrodinaphtho [2,3-

20 a:2',3'-i] naphth [2',3':6,7] indolo [2,3-c] carbazole- 5,10,15,17,22,24-hexone, N,N'-(9,10-Dihydro- 9,10-dioxo- 1,5-anthracenediyl) bisbenzamide, 7,16-Dichloro- 6,15-dihydro- 5,9,14,18-anthrazinetetrone, 16,17-Dimethoxydinaphtho (1,2,3-cd:3',2',1'-lm) perylene- 5,10-dione, Poly(hydroxyethyl methacrylate) -dye copolymers(3), Reactive Black 5, Reactive Blue 21, Reactive Orange 78, Reactive Yellow 15, Reactive Blue No. 19,

25 Reactive Blue No. 4, C.I. Reactive Red 11, C.I. Reactive Yellow 86, C.I. Reactive Blue 163, C.I. Reactive Red 180, 4-[(2,4-dimethylphenyl)azo]- 2,4-dihydro- 5-methyl-2-phenyl- 3H-pyrazol-3-one (solvent Yellow 18), 6-Ethoxy-2- (6-ethoxy-3-oxobenzo[b]thien-2(3H)- ylidene) benzo[b]thiophen- 3(2H)-one, Phthalocyanine green, Vinyl alcohol/methyl methacrylate-dye reaction products, C.I. Reactive Red 180, C.I. Reactive

30 Black 5, C.I. Reactive Orange 78, C.I. Reactive Yellow 15, C.I. Reactive Blue 21, Disodium 1-amino-4-[[4-(2-bromo-1-oxoallyl)amino]-2-sulphonatophenyl]amino]-9,10-dihydro-9,10-dioxoanthracene-2-sulphonate (Reactive Blue 69), D&C Blue No. 9, [Phthalocyaninato(2-)] copper and mixtures of these.

Other than in the examples herein, or unless otherwise expressly specified, all of the numerical ranges, amounts, values and percentages, such as those for amounts of materials, elemental contents, times and temperatures of reaction, ratios of amounts, and others, in the following portion of the specification and attached claims may be read as if prefaced by the word “about” even though the term “about” may not expressly appear with the value, amount, or range. Accordingly, unless indicated to the contrary, the numerical parameters set forth in the following specification and attached claims are approximations that may vary depending upon the desired properties sought to be obtained by the present invention. At the very least, and not as an attempt to limit the application of the doctrine of equivalents to the scope of the claims, each numerical parameter should at least be construed in light of the number of reported significant digits and by applying ordinary rounding techniques.

Notwithstanding that the numerical ranges and parameters setting forth the broad scope of the invention are approximations, the numerical values set forth in the specific examples are reported as precisely as possible. Any numerical value, however, inherently contains error necessarily resulting from the standard deviation found in its underlying respective testing measurements. Furthermore, when numerical ranges are set forth herein, these ranges are inclusive of the recited range end points (i.e., end points may be used). When percentages by weight are used herein, the numerical values reported are relative to the total weight.

Also, it should be understood that any numerical range recited herein is intended to include all sub-ranges subsumed therein. For example, a range of “1 to 10” is intended to include all sub-ranges between (and including) the recited minimum value of 1 and the recited maximum value of 10, that is, having a minimum value equal to or greater than 1 and a maximum value of equal to or less than 10. The terms “one,” “a,” or “an” as used herein are intended to include “at least one” or “one or more,” unless otherwise indicated.

Any patent, publication, or other disclosure material, in whole or in part, that is said to be incorporated by reference herein is incorporated herein only to the extent that the incorporated material does not conflict with existing definitions, statements, or other disclosure material set forth in this disclosure. As such, and to the extent necessary, the disclosure as explicitly set forth herein supersedes any conflicting material incorporated herein by reference. Any material, or portion thereof, that is said to be incorporated by reference herein, but which conflicts with existing definitions, statements, or other

disclosure material set forth herein will only be incorporated to the extent that no conflict arises between that incorporated material and the existing disclosure material.

While this invention has been particularly shown and described with references to preferred embodiments thereof, it will be understood by those skilled in the art that
5 various changes in form and details may be made therein without departing from the scope of the invention encompassed by the appended claims.

CLAIMS

1. A method of processing a biomass material, the method comprising;
providing a biomass material to a first treatment cell equipped with a first electron beam device, irradiating the biomass material with electron beams using the first electron beam device, and cooling and conveying the biomass material with a screw conveyor from the first treatment cell;
conveying the biomass material to a second treatment cell equipped with an second electron beam device and irradiating the biomass material with an electron beam using the second electron beam device.
2. The method of claim 1, wherein the screw conveyor comprises interior portions that are cooled.
3. The method of claim 2, wherein the interior portions are cooled using a chilled liquid.
4. The method of any one of claims 1-3, wherein the cooling reduces the temperature of the biomass material by between about 1°C and 110 °C.
5. The method of any one of claims 1-3, wherein the cooling reduces the temperature of the biomass material by between about 10°C and about 75 °C.
6. The method of any one of claims 1-3, wherein the cooling reduces the temperature of the biomass material by between about 10°C and about 50 °C.
7. The method of any one of claims 1-6, wherein a total dose delivered is between about 1 and 200 Mrad.
8. The method of any one of claims 1-6, wherein a total dose delivered is between about 10 Mrad and about 50 Mrad.

9. The method of any one of claims 1-6, wherein a total dose delivered is between about 20 Mrad and about 40 Mrad.
10. The method of any one of claims 1-9, wherein the temperature of the biomass material during the irradiation does not exceed about 160 °C.
11. The method of any one of claims 1-9, wherein the temperature of the biomass material during irradiation increases by between about 75 °C and about 150 °C.
12. The method of any one of claims 1-11, wherein the biomass comprises a lignocellulosic material.
13. The method of any one of claims 1-11, wherein the biomass is selected from the group consisting of wood, particle board, sawdust, agricultural waste, sewage, silage, grasses, rice hulls, bagasse, cotton, jute, hemp, flax, bamboo, sisal, abaca, straw, corn cobs, corn stover, switchgrass, alfalfa, hay, coconut hair, seaweed, algae, and mixtures thereof.
14. The method of any one of claims 1-13, wherein the screw conveyor comprises two or more screws.
15. The method of any one of claims 1-14, wherein irradiating with the first electron beam delivers a dose at a rate of at least 1 Mrad per second to the biomass material.
16. The method of any one of claims 1-15, wherein irradiating with the second electron beam device delivers a dose at a rate of at least 1 Mrad per second to the biomass material.
17. The method of any one of claims 1-16, wherein the screw conveyor has a material inlet and a material discharge, and wherein a difference in temperature of the biomass material between the material at the inlet and at the discharge is less than about 110 °C.
18. The method of any one of claims 1-17, wherein the biomass material is comminuted while it is conveyed.

19. The method of claim 3, wherein the interior portions are cooled using water or glycol water mixtures.