



(43) International Publication Date
30 May 2013 (30.05.2013)

(10) International Publication Number
WO 2013/075216 A1

- (51) International Patent Classification:
C08J 11/18 (2006.01) *C08C 19/08* (2006.01)
- (21) International Application Number:
PCT/CA2012/001063
- (22) International Filing Date:
19 November 2012 (19.11.2012)
- (25) Filing Language: English
- (26) Publication Language: English
- (30) Priority Data:
13/304,509 25 November 2011 (25.11.2011) US
- (71) Applicant: **WATSON BROWN HSM LTD.** [CA/CA];
6074 Shawson Drive, Mississauga, Ontario L5T 1E6 (CA).
- (72) Inventor: **FISHER, James F.**; 2953 Concession 11 South,
Singhampton, Ontario N0C 1M0 (CA).
- (74) Agents: **MITCHELL, Richard** et al.; c/o Marks & Clerk
Canada, PO Box 957, Station B, Ottawa, Ontario K1P 5S7
(CA).
- (81) Designated States (*unless otherwise indicated, for every
kind of national protection available*): AE, AG, AL, AM,

AO, AT, AU, AZ, BA, BB, BG, BH, BN, BR, BW, BY,
BZ, CA, CH, CL, CN, CO, CR, CU, CZ, DE, DK, DM,
DO, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT,
HN, HR, HU, ID, IL, IN, IS, JP, KE, KG, KM, KN, KP,
KR, KZ, LA, LC, LK, LR, LS, LT, LU, LY, MA, MD,
ME, MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI,
NO, NZ, OM, PA, PE, PG, PH, PL, PT, QA, RO, RS, RU,
RW, SC, SD, SE, SG, SK, SL, SM, ST, SV, SY, TH, TJ,
TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, ZA,
ZM, ZW.

- (84) Designated States (*unless otherwise indicated, for every
kind of regional protection available*): ARIPO (BW, GH,
GM, KE, LR, LS, MW, MZ, NA, RW, SD, SL, SZ, TZ,
UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, RU, TJ,
TM), European (AL, AT, BE, BG, CH, CY, CZ, DE, DK,
EE, ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT, LU, LV,
MC, MK, MT, NL, NO, PL, PT, RO, RS, SE, SI, SK, SM,
TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW,
ML, MR, NE, SN, TD, TG).

Published:

— with international search report (Art. 21(3))

(54) Title: METHOD OF DEVULCANIZING A CROSS-LINKED ELASTOMERIC MATERIAL

(57) Abstract: A thermoset cross-linked elastomer material, such as scrap tire rubber, is devulcanized by subjecting the material to a mechanical mixing process in the presence of 0.5 to 2% by wt. of an organic catalyst having a thiol terminus.



WO 2013/075216 A1