

CELL CONNECTORPOLE BRIDGE FOR A BATTERY

The invention relates to a cell connectorpole bridge for a battery in conjunction with at least one damping element, in particular for absorbing the vertical forces, which are
5 caused by the impact of shocks, wherein the cell connectorpole bridge is connected to the positive or negative electrodes at one end, which are received receivedallocated in a housing cell container cell container with a housing covercell lid, jointly forming the battery box being together the box, and at the other end, comprisinges at least one terminal, projecting from the housing cover cell lid.

10

Cell connectorPole bridges s of this kind for batteries are required in order to connect all positive and negative electrodes amongst each other and to simultaneously provide the capability to perform an electrical connection outside of the battery housing box. For this purpose, a positive and also a negative cell connectorpole bridge are being used,
15 forming a positive and a negative terminal with their terminal.

20

Batteries are mostly used in land- and watercraft, wherein they are used for starting an engine, as an energy supply or energy source for an electric drive system. Depending on the application, these batteries are subject to considerable mechanical stress caused
20 by the impacts of shocks. This can e.g. be the case when driving cross country, or due to external impacts. Such external impacts e.g. in military vehicles, in particular submarines, can also be the stresses caused by explosions, proximal to the vehicle or submarine. The shockwaves created can expose an automobile and also a submarine to short, but considerable impact acceleration. In submarines, this can also be caused
25 e.g. by water bombs or similar, wherein not only loose equipment of a submarine, but also components mounted to the submarine, like e.g. batteries, are exposed to considerable shock impacts. This e.g. leads to the electrode plates and their cell connectorpole bridges installed in housing battery boxes, performing a stroke of several centimeters, since the housing battery box is typically mounted to the submarine in a
30 fixed manner. In an extreme case, this means that the electrode plates within the

- housing battery box are moved downwards, and also upwards, relative to the housing battery box, and thus also the cell connectorpole bridges perform a vertical movement. For damping this vertical movement, it is known to provide thin elastic rubber disks between the cell connectorpole bridges and the housing covercell lid, in order to
- 5 cushion the shock impact. Furthermore, solutions are known wherein hard and brittle materials are used, which fracture due to the applied pressure, thus allowing a compensation movement of the electrode plates. In this embodiment, it is disadvantageous that typically only a single shock effect can be absorbed, and in case of a reoccurrence, the electrode plates can perform a vertical movement within the
- 10 battery housingbox, which is not dampened, or where the damping effect is only very small. This typically leads to considerable damages in to the cellbattery housing container and the cellbattery cover lid and typically of the electrode plates, so that the batteries are rendered useless.
- 15 DE 23 56 465 A1 teaches a damping system for electrode plates in a battery, which is achieved through an elastic support of the cell connectorpole bridge in the cover of the housingcell lid. For this purpose, the shaft of the terminal is surrounded by an elastic element on both sides of the housing covercell lid, wherein the two elastic elements on the outside and inside of the housing covercell lid establish the force transfer between
- 20 the cell lidhousing cover and the cell connectorpole bridge . This type of suspension, however, causes the housing covercell lid to deform in the immediate proximity of the terminal shaft under a shock impact, or that the cylindrical damping elements deform under shock impact, so that a multiple shock impacts cannot be safely absorbed.
- 25 Furthermore, it is provided in known solutions according to the state of the art for the damping elements to form a narrow collar around the terminal shafts, which is supported at the housing covercell lid of the battery. In spite of the damping, the forces transferred by the damping element under shock impact are so high that the housing covercell lid fractures in the portion of the damping elements.

It is the objective of the invention to provide a solution, allowing improved damping of the electrode plates, and maintaining the damping properties also under multiple shock impacts without the housing covercell lid of the battery fracturing under strong shock impact.

5

According to the invention it is provided in order to achieve the object, that the at least one terminal connection is provided with an integral support shoulder within the housingbattery boxcontainer, wherein the at least one damping element is provided, so that it contacts the support shoulder with a smaller planar surface, and contacts below
10 the inner housing cover cell lid of the battery with a larger planar surface. Further advantageous embodiments of the invention can be derived from dependent claims.

In order to dampen a possible vertical force of the electrode plates within the battery housingbox, a novel cell connectorpole bridge is proposed comprising an integral
15 support shoulder within the housingbattery box. This support shoulder in conjunction with at least one damping element serves for elastically receiving vertical forces caused by shock effects without the electrode plates getting damaged. Through the support shoulder, thus a support surface is created, on which the at least one damping element is supported, and thus occurring vertical forces e.g. through an impact, can be inducted
20 into the at least one damping element through a large surface. For this purpose, the at least one damping element can be slid onto the terminal in a loose manner, and is disposed within the housingbattery box, wherein the at least one damping element contacts the support shoulder with one end and is supported below the housing covercell lid, which is connected to the housingcell container, at the other end. The
25 housing cell container and the housing covercell lid are manufactured from fiberglass material in a known manner, and provided with a rubber coating on their inside, so that the battery acid present in the housing battery box cannot destroy the fiberglass housingcell container, or the fiberglass covercell lid. In the transition area between the housing cell container and the housing covercell lid, additionally a connection of the
30 inner housing covercell lid with the interior housingcell container wall is performed through gluing, vulcanization, and other comparable connection techniques.

Thus, the support shoulder of the terminal connection has a large surface and the at least one damping element has an approximately equal size planar surface, so that said damping element contacts the support shoulder with its entire surface, in order to
5 transfer the occurring compression forces on a surface, which is as large as possible. The shape of the at least one damping element and also of the support shoulder can thus be selected freely and can e.g. be round, oval, or polygon, in particular square.

The at least one damping element furthermore comprises a second planar surface,
10 which contacts directly below the inner housing covercell lid, wherein in a particularly advantageous embodiment the at least one damping element is provided conically tapered downward towards the cell connectorpole bridge . By this measure it is accomplished that, on the one hand, a large scale transfer of the occurring pressure is performed into the housing covercell lid and, on the other hand, it is prevented through
15 the conical shape that the at least one damping element is deformed too much and experiences e.g. a bulging in the center portion. Through the transfer of the forces onto the cover cell lid of the battery housing box through a large surface, it is accomplished that the surface load on the material of the battery housing covercell lid is maintained small under shock impact and as a consequence, the battery covercell lid does not
20 fracture.

In a further embodiment of the invention it is provided that the at least one damping element is comprised of an elastic natural rubber material, preferably Butyl natural rubber, which has the required mechanical stability and transfers the occurring
25 compression forces into thermal energy. Hereby, an increased damper effect is accomplished, since a larger percentage of the occurring kinetic energy can be absorbed.

In another embodiment of the invention, it is provided that the upper support surface of
30 the at least one damping element has a cutout, into which a protrusion of the housing

covercell lid, which is preferably comprised of a housing covercell lid with an internally disposed interior rubber cover, protrudes. Hereby, assembly is facilitated and furthermore an improved guidance of the terminal connections is accomplished.

5 In order to compensate for the different expansion coefficients of the cell connectorpole bridge, on the one hand, and of the at least one damping element, on the other hand, a seal element is advantageously disposed between them, wherein the support shoulder can have a cutout for the seal disk. In order to improve the sealing effect, the parallel seal surfaces of at least one damping element and of the seal element can at least
10 partially be lubricated with silicon grease.

The at least one damping element used, thus can have a height of 40 to 80 mm, preferably 60 mm, and a first support surface of 3,000 to 4,000 mm², preferably 3,600 mm², and a second support surface of 5,000 to 7,000 mm², preferably 5,800 mm². By
15 means of the support surfaces, it is assured, that an optimum transfer of the occurring pressure forces into the at least one damping element occurs, wherein through the height of the at least one damping element an elastic vertical movement of the electrode plates is possible, also over a larger travel distance. The electrode plates themselves are supported relative to the floor of the battery housing cell container by means of
20 additional damper strips, comprising a thickness of 40 to 50 mm, so that the electrode plates are cushioned downwards, and also upwards, in a damping manner.

In another particular embodiment, it is provided, that the housing covercell lid comprises a cutout for a seal ring on the outside, which rests in the cutout in disk shape, and
25 through which the terminal connection protrudes to the outside, wherein a metal disk rests on the damper ring, and wherein it is clamped by means of bolts, which are supported in grooves provided in the pole connection. While the at least one damping element is used for cushioning a vertical element of the electrode stack upward against the housing covercell lid, the seal ring is provided for supporting the electrode stack
30 downward and can thus be designated as an outer damping element, wherein said

damping element engages with the damper strip in the floor portion in order to cushion the electrode stack in an elastic manner. The seal ring thus comprises a height of approximately 25 to 40 mm, preferably 30 mm, with a diameter of 50 to 70 mm, preferably 60 mm. In an advantageous manner, the seal ring is inserted in a cutout of the housing covercell lid, in order not to increase the height of the battery, or in order not to reduce the interior volume of the battery.

Typically, the terminal is comprised of copper, in order to assure a high current inflow and outflow with minimum loss. The integral support shoulder formed at the terminal in the cell connectorpole bridge according to the invention, is also comprised of copper, wherein a high form stability is accomplished, and thus the forces can be transferred into the at least one damping element in an optimum manner. For protection against the present acid, the support shoulder is encased with lead, wherein the terminal is at least partially encased in lead, preferably up to the elevation of the housing cover, so that even splashes of acid due to rocking motions cannot damage the terminal, or the cell connectorpole bridge. Thus, it is avoided, that acid creeping up at the cell connectorpole bridge and at the terminal can cause damage. As an additional seal means, the silicon grease and the seal disk are provided, which is provided below the at least one damping element, wherein in the upper area, the at least one damping element directly contacts the housing covercell lid, which is e.g. comprised of rubber or natural rubber, and additionally provides the possibility that the at least one damping element can be connected with the housing cover cell lid in a sealing manner, e.g. by means of vulcanizing. The housing covercell lid and the housing cell container itself are connected amongst each other, so that a separation of both components can only be performed under great force, which typically means that the battery housing box is destroyed.

The main novel idea of the invention is to cushion shock impacts by means of a reinforced cell connectorpole bridge with an integrally formed support shoulder and at least one large surface damping element, and thus to dampen a vertical movement of the electrode plates, wherein preferably elastic materials are used, which can absorb

multiple shock impacts without permanent deformation. Thus, it is provided that through the at least one large surface damping element, the forces, which are transferred through the damping element onto the housing cover, are distributed, far enough, so that the housing cover does not fracture under shock impact.

5

The invention is subsequently described in more detail with reference to figures, showing in:

Fig. 1 an upper battery cover portion in two sectional side views;

10

Fig. 2 a cell connector pole bridge according to the invention in three views;

Fig. 3 a damping element according to the invention in two views;

15 Fig. 4 a seal element in two views;

Fig. 5 the housing cover cell lid in three views;

Fig. 6 the housing cover interior cell lid in three views; and

20

Fig. 7 a seal element according to the invention in three two views.

Figs. 1.1 and 1.2 illustrate two sectional views of the upper portion of a battery 1, comprised of a housing cell container wall 2, a housing cover cell lid 3, and internal

positive and negative electrode plates 4, 5 and a cell connectorpole bridge 6, connecting the electrode plates 4, 5 amongst each other, and thus respectively the positive and negative electrode plates 4, 5. By means of a terminal 7, 8, which protrudes from the upper housing covercell lid 3, and which is provided for connecting the battery 1, the battery can be connected. The cell connectorpole bridge 6 can be seen in detail from the Figs. 2.1, 2.2, and 2.3, and a damping element 9 according to the invention can be seen in Figs. 3.1 and 3.2. A seal element located between the damping element 9 and the cell connectorpole bridge 6 can be seen from the Figs. 4.1 and 4.2, the housing covercell lid is evident from the Figs. 5.1, 5.2, and 5.3 and the interior housing covercell lid is evident from the Figs. 6.1, 6.2, and 6.3, and a seal ring is evident above the housing cover from the Figs. 7.1 and 7.2.

The cell container housing box 2 of the battery 1 is typically comprised of fiberglass material and provided with a rubber lining on the inside, and thus the housing cell container 2 and the housing covercell lid 3 are protected from damages due to acid impact after filling with acid. In the illustrated embodiment, the housing covercell lid 3 is comprised of an outer cover cell lid 3 from fiberglass material and an interior cover cell lid 12, which is typically made from rubber, or a material similar to rubber, and glued together, or vulcanized with the inner wall of the housing cell container 2 after assembly. Above the electrode plates 4, 5, the cell connectorpole bridge 6 is disposed, comprising a bridge like connection element 10 on the side facing the electrode plates 4, 5 in order to facilitate contacting the positive or negative electrode plates 4, 5. Above the electrode plates 4, 5, the cell connectorpole bridge 6 is widened in a trapezoid shape so that a support shoulder 11 is created. The damping element 9 according to the invention rests on the support shoulder 11, which at the one end rests on the support shoulder 11, and on the other end, contacts below the inner housing covercell lid 12. The cell connectorpole bridge 6 itself protrudes through the housing covercell lid 3 and the inner housing covercell lid 12 upward out of the housing cell containerbox 2 with the respective terminal 7, 8. In order to support the cell connectorpole bridge 6 in a damping manner relative to the housing covercell lid 3, the mounting of the damping element 9 according to the invention is performed below the housing covercell lid 3 and the inner housing covercell lid 12. Furthermore, a seal ring 13 is slid onto the terminal

7, 8 from the outside, which is directly placed in an indentation of the housing covercell lid 3, and covered by a steel washer 14. In order to clamp the lower damping element 9 with the seal ring 13, wherein between the seal ring 13 and the damping element 9 the inner housing covercell lid 12 and the outer housing covercell lid 3 is located, the seal
5 ring 13 and the damping element 9 are compressed during assembly, so that two lateral notches of the terminal 7, 8 are exposed, in order to insert a safety pin 16 on two sides of the terminal connection 7, 8. The safety pin 16 rests in a depression of the steel washer 14 and is pressed into the depression of the steel washer 14 after loosening the assembly pressure, so that the inner housing covercell lid 12 and the housing covercell
10 lid 3 are compressed between the damping element 9 and the seal ring 13. In the housing covercell lid further cutouts are provided, which e.g. are used for checking or displaying the acid level, and to supply air, or turn over to agitate the electrolyte. Feeding air is performed e.g. by a hose 17, which is illustrated in the left and right half of the figure.

15

The Figs. 2.1, 2.2, and 2.3 show the cell connectorpole bridge 6 according to the invention in three views with a lower bridge shaped connection element 10, which is simultaneously provided for connecting the positive or negative electrode plates. Above the connection element 10, the cell connectorpole bridge 6 widens in upward direction
20 in trapeze shape in the illustrated embodiment and leads to a square support shoulder 11. Instead of a square, also an oval, round, or polygonal support shoulder 11 can be provided. An indentation 20 is provided in the support surface of the support shoulder 11, so that a washer is positioned between the support shoulder 11 of the cell connectorpole bridge 6 and the damping element 9, which can be slid on here, but
25 which is not shown. Above the support shoulder 11, the cell connectorpole bridge 6 transitions into a rectangular or possibly square terminal 7, 8. As can be seen from the partial sectional view, the cell connectorpole bridge 6 is comprised of an inner core 21 and an outer jacket 22. The core 21 is comprised of copper, while the jacket 22 is provided as a lead jacket, so that the copper is protected from the electrolyte. For this
30 purpose, the bridge shaped connection element 10, the cell connectorpole bridge 6 with the support shoulder 11, and the terminals 7, 8 are clad with lead up to the height of the housing covercell lid 3. The housing covercell lid, which is not shown, can be slid

up to the elevation of the provided shoulder 23 onto the terminals 7, 8 during assembly. Above the housing covercell lid, the cell connectorpole bridge 6 with its terminals 7, 8 protrudes from the housing cover cell lid 3 without lead cladding. In order to load the damping element and the upper seal washer, safety pins are provided as already
 5 illustrated in the Figs. 1.1 and 1.2, which are disposed respectively in a notch 15 of the terminal 7, 8. The lateral bore hole 24 in the terminals 7, 8 is used for cooling the cell connectorpole bridge 6 with water through a flow channel 25, wherein said water is inducted through a bore hole 24 and fed through the flow channel 25 to the second bore hole 24, so that a water circulation is facilitated.

10

Figures 3.1 and 3.2 show the damping element 9 according to the invention in two views, wherein said damping element in the illustrated embodiment comprises two square planar surfaces 30, 31, and an opening 32, which leads into a cutout 33. The damping element 9 with the smaller planar surface 31 contacts the support shoulder of
 15 the cell connectorpole bridge 6 after assembly, wherein a seal element is inserted into the cutout 20. The other planar surface 31 directly contacts the inner housing cover cell lid 12, wherein a protruding portion of the inner housing covercell lid 12 protrudes into the recess 33, so that the damping element precisely abuts to the elastic rubber inner housing covercell lid 12. All contact surfaces of the damping element 9 and of the inner
 20 housing covercell lid 12 can additionally be coated with silicon grease in order to improve the sealing properties. In the opening 32 the upper part of the cell connectorpole bridge and thus the terminal 7 or 8 have to be received, this means the damping element 9 is slid onto the terminal 7, 8 until the planar surface 31 contacts the support shoulder 11.

25

Figs. 4.1 and 4.2 show a seal disk 3535 in two views, wherein said seal disk is provided square in the illustrated embodiment, and is disposed in the recess 20 of the cell connectorpole bridge 6. Therefore, the seal disk 36 has a recess 37, so that the seal disk 36 can be slid over the terminal 7, 8 and contacts the support shoulder 11.

30 According to the shape of the support shoulder 11 of the terminal pole bridge 6, the seal

disk 36 can deviate from the illustrated embodiment, this means a rectangular, oval, circular, or polygon shape can also be used.

Figures 5.1, 5.2, and 5.3 show the housing covercell lid 3 in three views, wherein two views are shown as sectionals. The housing covercell lid 3 is provided rectangular in the illustrated embodiment and is comprised of a base body 40, which has four symmetrical openings 41 for receiving the pole connections, and additional bore holes and openings 42, 43, which are partially provided for venting the interior and for receiving closure plugs or control indicators for the acid level. On the bottom of the housing covercell lid 3, there is a circumferential rim 44, which is disposed flush in a recess of the inner housing covercell lid 12. Furthermore, the housing covercell lid 3 is provided with a step shaped contour 45 on the bottom side, comprising four planar surfaces 46, on which similar shaped planar surfaces of the inner housing covercell lid 12 contact, in order to transfer the occurring forces into them, which impact the housing covercell lid through the damping element, over a large area. Through an opening 47, these terminals 7, 8 reach upward out of the housing covercell lid 3, wherein the openings 47 on the outside transition into a larger recess, into which a seal ring is inserted.

Figures 6.1, 6.2, and 6.3 show the inner housing covercell lid 12, which is comprised of a rubber elastic material. The upper contour 50 of the inner cover cell lid 12 is mostly adapted to the contour 45 of the housing covercell lid 3. In a cavity 51, e.g. the rim 44 of the housing covercell lid 3 is received, while integrally shaped tubular walls 52 protrude into the opening 47 of the housing covercell lid 3, and are pressed in, so that not only the bottom side of the housing covercell lid 3, but also the present openings, are covered with rubber elastic material. On the bottom side 53 of the inner cover cell lid 12, four integrally shaped protrusions 54 are provided, which protrude into the corresponding recesses 33 of the damping element 9, thus facilitating a secure mounting of the damping element 9 relative to the inner housing covercell lid 12, thus avoiding a subsequent sliding of the damping element 9. Thus, it furthermore has to be taken into account that the terminals 7, 8 protrude through the center opening 55

outward and thus assure a precisely fitted assembly of cell connectorpole bridge 6 with damping element 9, inner housing covercell lid 12 and housing covercell lid 3. Other available openings 56 or 57 with partially collar shaped protrusions 58, 59 also protrude into the existing openings 42, 43 of the housing cover 3 and assure a complete
5 encasement of the housing covercell lid 3 from the inside.

Figures 7.1 and 7.2 show a seal ring 13, which is disposed in the recess 48 of the housing covercell lid 3. The seal ring 13 comprises a rectangular opening 60, through which the terminal 7, 8 of the cell connectorpole bridge 6 protrudes from the housing
10 cell containerbox 2. In the illustrated embodiment, the seal ring 13 is provided circular. There certainly is the possibility of changing the recess 48 in the housing covercell lid 3, and to select another shape of the seal element.

In the present invention, a damping of the electrode plates 4, 5 is achieved by means of
15 the novel cell connectorpole bridge 6 by the cell connectorpole bridge 6 transmitting the forces into an existing elastic damping element 9 by means of a large sized support shoulder 11. The damping element 9 on the one hand directly rests on the support shoulder 11 of the cell connectorpole bridge 6, or on a seal element, while the other end contacts below the inner housing covercell lid 12. Through the damping element 9,
20 the inner housing covercell lid 12 and the outer housing covercell lid 3 of the respective terminal 7, 8 protrudes from the housing cell containerbox 2, allowing the connection of the battery for supplying a piece of equipment or a drive motor with electric energy. In an advantageous manner several batteries 1 are connected into larger units, in order to either achieve a voltage increase, or higher electrical power. In order to achieve a
25 sufficient damping effect of the assembly according to the invention, furthermore the housing covercell lid 3 or the inner housing covercell lid 12 is wedged between the inner damping element 9 and an outer seal ring 13. The wedging is accomplished through the two elastic elements being compressed during assembly and by a steel washer contacting the outer seal ring being secured by means of two safety pins 16 at the
30 respective terminal connections 7, 8. The safety pins 16 thus rest in a provided cavity of the steel washer and in a notch 15 of the terminal 7, 8.

In case of an occurring shock impact upon the battery, preferably by vertical forces, thus the movement of the electrode plates 4, 5 within the housing cell containerbox 2, due to the available damping element 9, is slowed down far enough, so that only a small
5 movement occurs relative to the housingcell containerbox. For this purpose, it is necessary that the occurring forces are initially transferred through a large size support shoulder 11 of the cell connectorpole bridge 6 into the damping element 9, and this damping element, on the other hand, is supported through an also large sized support surface relative to the housing covercell lid 3, or the inner housing covercell lid 12. By
10 means of the large surface force transfer into the housing covercell lid it is avoided that the housing covercell lid fractures under shock impact. By means of selecting a respective plastic material, a deformation of the damping element 9 is only permitted within certain limits, and in particular, the occurring kinetic energy is transferred into heat. The particular advantage of this assembly is that the pole connector bridge 6 with
15 the damping element 9 can not only cushion one jolt, but several jolts caused by shock impact. For this purpose, furthermore, a damper strip is used, which is disposed below the electrodes 4, 5, which cushions the electrodes relative to the bottom of the cell housing container in a known manner.

DESIGNATIONS

	1	battery
5	2	cell containerhousing wall
	3	cell lidhousing cover
	4	electrode plate
	5	electrode plate
	6	cell connectorpole bridge
10	7	terminal
	8	terminal
	9	damping element
	10	connection element
	11	support shoulder
15	12	inner cell lidhousing cover
	13	seal ring
	14	steel washer
	15	notch
	16	safety pin
20	17	hose
	20	cutout
	21	core
	22	jacket
	23	shoulder
25	24	bore hole
	25	flow channel / cooling channel
	30	planare face
	31	planare face
	32	opening
30	33	recess
	35	seal disk
	36	seal disk

	37	recess
	40	core body
	41	opening
	42	opening
5	43	opening
	44	rim
	45	contour
	46	planar surface
	47	opening
10	48	recess
	50	contour
	51	cavity
	52	wall
	53	bottom side
15	54	protrusion
	55	opening
	56	opening
	57	opening
	58	bulge
20	59	bulge
	60	opening

PATENT CLAIMS

What is claimed is:

5

1. A cell connectorpole bridge (6) for a battery in conjunction with at least one damping element (9, 13), especially for absorbing the vertical forces that are caused by the impacts of shocks, wherein the cell connectorpole bridge (6), at one end, is connected to the positive or negative electrodes (4, 5), which are received in a cell containerhousing box (2) having a housing cover cell lid (3), and at the other end, comprises at least one terminal (7, 8), projecting from the housing cover cell lid (3), wherein the at least one terminal (7, 8) has a supporting shoulder (11), integrally molded thereto, within the housing cell container box (2), wherein the at least one damping element (9) is formed so that it is supported at the support shoulder (11) with a smaller planare face (31) and with a larger planare face (30) below the inner housing coverlid (12) of the battery.

15

2. A cell connectorpole bridge (6) in conjunction with at least one damping element (9, 13) according to claim 1, wherein the at least one damping element (9) is provided, so it can be slid onto the terminal (7, 8).

20

3. A cell connectorpole bridge (6) in conjunction with at least one damping element (9, 13) according to claim 2, wherein the support shoulder (11) is sized with a large surface and the at least one damping element (9) is supported with an approximately equal size plane face (31) at the support shoulder (11).

25

4. A cell connectorpole bridge (6) in conjunction with at least one damping element (9, 13) according to claim 1, 2, or 3, wherein the at least damping element (9) is round, oval or polygon, in particular square shaped, and comprises at least one such support surface.

30

5. A cell connectorpole bridge (6) in conjunction with at least one damping element (9, 13) according to claim 1, 2, 3, or 4, wherein the at least one damping element (9) is provided conically tapered downward, in direction towards the cell connectorpole bridge (6).
- 5
6. A cell connectorpole bridge (6) in conjunction with at least one damping element (9, 13) according to at least one of the claims 1 through 5, wherein the at least one damping element (9) is comprised of an elastic natural rubber material, preferably Butyl rubber material, which comprises the required form stability and converts occurring pressure forces into thermal energy.
- 10
7. A cell connectorpole bridge (6) in conjunction with at least one damping element (9, 13) according to at least one of the claims 1 through 6, wherein the upper support surface of the at least one damping element (9) comprises a recess (33), into which a protrusion of the housing covercell lid (3) protrudes, preferably comprised of a housing covercell lid (3), having an inner housing covercell lid (12) comprised of rubber.
- 15
8. A cell connectorpole bridge (6) in conjunction with at least one damping element (9, 13) according to at least one of the claims 1 through 7, wherein between the support shoulder (11) and the at least one damping element (9), a seal element (36) is disposed.
- 20
9. A cell connectorpole bridge (6) in conjunction with at least one damping element (9, 13) according to at least one of the claims 1 through 8, wherein the support shoulder (11) comprises a recess (20) for a seal element (36) between support shoulder (11) and the at least one damping element (9) within the lead jacket.
- 25
10. A cell connectorpole bridge (6) in conjunction with at least one damping element (9, 13) according to at least one of the claims 1 through 9, wherein the parallel seal surfaces (30, 31) of the at least one damping element (9) are at least partially lubricated with silicon grease.
- 30

11. A cell connectorpole bridge (6) in conjunction with at least one damping element (9, 13) according to at least one of the claims 1 through 10, wherein the at least one damping element (9) has a height of 40 to 80 mm, preferably 60 mm.
- 5 12. A cell connectorpole bridge (6) in conjunction with at least one damping element (9, 13) according to at least one of the claims 1 through 11, wherein the at least one damping element (9) comprises a first support surface with 3,000 to 4,000 mm², preferably 3,600 mm², and a second support surface of 5,000 to 7,000 mm², preferably 5,800 mm².
- 10 13. A cell connectorpole bridge (6) in conjunction with at least one damping element (9, 13) according to at least one of the claims 1 through 12, wherein the housing covercell lid (3) comprises a recess (48) on its outside for a seal ring (13), which is disposed in disk shape in the recess (48), and through which the terminal (7, 8)
- 15 protrudes to the outside, wherein a metal disk rests on the seal ring (13), and is clamped by means of the safety pins (16), which are disposed in the provided recesses (20) of the terminal (7, 8).
14. A cell connectorpole bridge (6) in conjunction with at least one damping element
- 20 (9, 13) according to at least one of the claims 1 through 13, wherein a seal ring (13) is provided as a second seal element, which comprises a height of 25 to 40 mm, preferably 30mm.
15. A cell connectorpole bridge (6) in conjunction with at least one damping element
- 25 (9, 13) according to claim 14, wherein the second damping element (13) can be slid onto the terminal from above.
16. A cell connectorpole bridge (6) in conjunction with at least one damping element
- 30 (9, 13) according to claim 14 or 15, wherein the seal ring (13) comprises a diameter of 50 to 70 mm, preferably 60 mm.

17. A cell connectorpole bridge (6) in conjunction with at least one damping element (9, 13) according to at least one of the claims 1 through 16, wherein the terminal (7, 8) is comprised of copper.
- 5 18. A cell connectorpole bridge (6) in conjunction with at least one damping element (9, 13) according to at least one of the claims 1 through 17, wherein the cell connectorpole bridge (6) and, in particular, the portion of the support shoulder (11) is clad with lead.
- 10 19. A cell connectorpole bridge (6) in conjunction with at least one damping element (9, 13) according to at least one of the claims 1 through 18, wherein the terminal (7, 8) is at least partially, preferably up to the elevation of the housing coverlid (3), clad with lead.