

PATENT SPECIFICATION

(11) 1 499 333



- (21) Application No. 42399/74 (22) Filed 30 Sept. 1974
(21) Application No. 54553/74 (22) Filed 17 Dec. 1974
(21) Application No. 9698/75 (22) Filed 7 March 1975
(23) Complete Specification filed 22 Sept. 1975
(44) Complete Specification published 1 Feb. 1978
(51) INT CL² C11B 7/00
(52) Index at acceptance C5C 4 5A1 5A3 5A4
(72) Inventors ONG SOON HOCK and CHUAH CHONG-CHENG

(54) OLEIN-STEARIN SEPARATION

(71) We, THE UNIVERSITY OF SCIENCE OF MALAYSIA, a Malaysian Body Corporate, of Minden, Penang, Malaysia, do hereby declare the invention, for which we pray that a patent may be granted to us, and the method by which it is to be performed, to be particularly described in and by the following statement:—

This invention relates to an improved process for separating the olein and stearin fractions of vegetable, animal and fish oils. Such oils include palm oil, rice bran oil, tallow, lard, herring oil, cotton seed oil and olive oil.

The olein fraction of an oil is liquid and generally contains a higher proportion of unsaturated components than the starting oil. The stearin fraction is generally solid and contains a lower proportion of unsaturated components.

Palm oil production is increasing all the time and now constitutes a significant proportion of the edible oils produced in the world. It has also been found that palm oil has an advantage over other oils in deep frying and at the moment there is a demand for the olein fraction. In the case of rice bran oil which can be extracted from rice it is likely to be an important source of edible oil as the world production of rice is likely to increase since it is the staple food of that part of the world whose population is increasing rapidly.

The various methods of olein-stearin separation are known:—

- a) Winterisation
- b) Crystallisation with hexane
- c) Crystallisation with acetone
- d) Detergent process
- e) Crystallisation with isopropyl alcohol which contains a natural additive.

All these processes have certain disadvantages. In the first process, there is oil loss through occlusion, thus affecting the efficiency of separation. In those processes which use organic solvents, there is the danger of flammability and there arises the costly process of recovering the solvents. In the fourth process, there is a possibility of a health hazard and this process is still not acceptable in certain countries.

According to the present invention there is provided a process for separating olein and stearin fractions from an oil containing olein and stearin which process comprises providing a fluid comprising

- a) the oil concerned, and
- b) a liquid single phase mixture of two components;
 - i) at least one liquid polyhydroxy compound or water, with
 - ii) at least one polar organic liquid,

which liquid single phase mixture is substantially insoluble in the oil and has a composition defined by the equation:

$$XD_1 + (100-X)D_2 = B$$

where X is the percentage of component (i),

D_1 is the specific gravity of component (i) at 25°C,

D_2 is the specific gravity of component (ii) at 25°C, and

B depends on the specific gravity of the oil and varies between 87 and 97, and separating the oil into olein and stearin fractions by utilisation of their different densities, e.g. by either centrifuging the said fluid or allowing the said fluid to stand.

The olein and stearin thus separated can be recovered by standard techniques.

Preferably the fluid is allowed to stand at ambient temperature.

When herring oil is used the separation may be carried out at a temperature lower than that used for other oils.

The preferred polyhydroxy compounds are selected from propylene glycol and glycerine, and the preferred polar organic liquids are selected from acetone, butanone, ethyl alcohol, n-propyl alcohol and isopropyl alcohol.

It has been found that when the oil/liquid mixture phase is subjected to centrifugation, two or three phases separate out, depending on the ratio of oil to liquid mixture, namely olein (top) and stearin/liquid mixture (bottom) or olein (top), liquid mixture (middle) and stearin/liquid mixture (bottom), their relative positions being determined by their relative densities.

The solubility of the liquid mixture, particularly in the case of water and isopropyl alcohol mixture, in the olein fraction is less than 0.5%, for example about 0.26%, and the solubility of the oil, particularly in the case of palm oil, in the liquid mixture is less than 0.5%, for example about 0.25%.

The ranges of values for B have been calculated as follows:

	B	
	min.	max.
Crude Palm Oil	87	92
Refined Palm Oil	87	92
Rice Bran Oil	87	93
Tallow	87	96
Lard	87	97
Herring Oil	88	93
Palm Kernel Oil	89	95

The composition of the liquid mixture is determined within quite close limits by the need for it to be less dense than the stearin fraction but more dense than the olein fraction of the oil. The optimum value of B in the equation given above varies somewhat in different systems and with different oils as indicated above. For example in the case of a liquid mixture of water and isopropyl alcohol with palm oil, the preferred range of B extends from 87 to 91 and the optimum figure is 89. The relative volumes of liquid mixture to oil may vary from 10:1 to 1:10 particularly 10:1 to 1:5 where separation is effected by allowing the fluid to stand. It has been found that the best separation, when using centrifugation, is obtained by using a volume ratio of oil to liquid mixture of 1:1 although good separation can be obtained by using ratios of oil to liquid mixture 3:2, 7:3 and 4:1. Where the fluid is allowed to stand the best separation is obtained by using a volume ratio of oil to liquid mixture of 1:3 although good separation can be obtained using a ratio of oil to liquid mixture of 1:1. As the proportion of the liquid mixture in the fluid decreases, the time required for complete separation increases considerably.

Good separation can be achieved using centrifugation at as low as 900 g although centrifugation at 2000 g or more is preferred in the case of palm oil using water and isopropyl alcohol mixture. The best condition for lard and tallow is 2500 g.

In fact with a continuous process it has been found most practical to use a centrifugation of 5800 g (8000 rpm) and a gravity disc of 53 mm with an Alfa-Laval Laboratory Separator LAPX202.

2

3

1,499,333

3

The ratio of oil to liquid mixture seems to affect both the yield of olein and the number of phases resulting from the separation. Although fractionation can be achieved in the separator without the use of a liquid mixture, the yield was found to be low. However, using a ratio of palm oil to liquid mixture of 1.6:1, the yield is approximately 70% representing over 90% of the available oil. Three phases result from this condition in which one contains the olein phase, and the others the liquid mixture phase and the stearin phase. On increasing the ratio of palm oil to liquid mixture to 4:1 the best yield is provided and under this condition only two layers result.

In the Alfa-Laval Laboratory Separator referred to, there are three exits and under the condition of low ratio of palm oil to solvents e.g. 1.6:1, olein, liquid mixture and stearin with some liquid mixture come off through the three different exits. However, under a higher ratio of palm oil to liquid mixture e.g. 4:1, olein comes off one exit, stearin with some liquid mixture through another exit but no liquid mixture leaves the third exit. There is no question of the liquid mixture dissolving in the oil. It was also found that careful crystallisation of the palm oil from 52° to 22°C with $\Delta t = 2^\circ$ (where Δt = temperature difference of the palm oil and cooling bath) and making use of the ratio 4:1, one obtains about 70% yield of olein having better properties. The properties of the fractions resulting from this method of fractionation of crude palm oil were found to be as follows:

	Iodine Value	Free Fatty Acid	β -Carotene	Tocopherols	Cloud Point	Melting Point
Olein	60	2.2	744 p.p.m.	999	9.5°C	
Stearin	47	1.7	498 p.p.m.	630		51.0—53.0°C
Crude Palm Oil	54	2.3	698 p.p.m.	946		

	Lauric Acid	Myristic Acid	Palmitic Acid	Oleic Acid	Stearic Acid	Linoleic Acid	Arachidic Acid	Linolenic Acid
	%	%	%	%	%	%	%	%
Olein	0.10	1.0	39	43	4.5	12	0.35	0.41
Stearin	0.06	1.4	52	34	4.1	9.0	0.40	0.31
Crude Palm Oil	0.05	1.0	44	40	4.1	10	0.30	0.20

The liquid mixtures from the continuous separations were collected and studied. They were first found to have dissolved some nonglyceride components. These have been identified as phosphatides particularly lecithin, sterols, some free fatty acids and tocopherols. The recovered liquid mixtures can be used again after distillation and it has been estimated by NMR analysis that they consist of about 17% water which can be reconstituted for use again as a component for the liquid mixture. Another way of recovering the liquid mixture is to dilute it with water resulting in the precipitation of the nonglyceride components which can then be filtered using a bed of activated carbon or Fuller's earth. The filtrate could be used again by adding the appropriate volume of component (ii).

The process may be performed in a continuous manner by mixing the oil and the liquid single phase mixture in a column, allowing the fluid to stand and withdrawing the olein from the top of the column and the stearin from the bottom of the column. The column containing the remaining liquid mixture is continuously or intermittently replenished with oil and the process continued. In this way there is saving in the use of the liquid single phase mixture.

The process of the present invention has several applications:

13

4

5

10

5

10

- (1) It can be used as an industrial separation of olein and stearin formed under different cooling conditions for vegetable, animal and fish oils.
- (2) Besides concentrating the β -carotene of the oil, it can be used to selectively extract nonglyceride components particularly tocopherols, phosphatides and sterols.
- (3) Since the method is simple and fast, it can be adopted as an analytical method for the estimation of the olein-stearin ratio of oils particularly palm oil. Since an ordinary centrifuge is required for this analytical work, this process could be easily adopted as an analytical method.

The following Tables I, II and III show the conditions under which separation of olein and stearin fractions from oils was achieved using the process according to the invention.

TABLE I.
Conditions for Effecting Olein-Stearin Separation
of Oils by Centrifugation

Liquid Single Phase Mixture	A Crude Palm Oil	B Refined Palm Oil	C Rice Bran Oil	D Tallow	E Lard	F Herring Oil
1. Water:Acetone	42:58 (v/v)	33:67 (v/v)	34:66 (v/v)	35:65 (v/v)	38:62 (v/v)	35:65 (v/v)
2. Water:Ethyl alcohol	42:58	43:57	42:58	46:54	44:56	41:59
3. Water:Propyl alcohol	42:58	44:56	44:56	47:53	46:54	46:54
4. Water:Isopropyl alcohol	45:55	44:56	46:54	45:55	45:55	47:53
5. Propylene Glycol:Acetone	34:66	38:62	38:62	33:67	35:65	34.5:65.5
6. Propylene Glycol:Butanone	30:70	29:71	—	—	32:68	—
7. Propylene Glycol:Ethyl alcohol	46:54	47:53	46:54	48:52	48:52	44.5:55.5
8. Propylene Glycol:n-Propyl alcohol	44:56	45:55	47:53	46:54	45:55	45:55
9. Propylene Glycol:Isopropyl alcohol	48:52	47:53	50:50	48:52	48:52	50:50
10. Glycerine:Ethyl alcohol	22:78	25:75	23:77	25:75	25:75	21:79
11. Glycerine:n-Propyl alcohol	20:80	24:76	22:78	21:79	22:78	25:75
12. Glycerine:Isopropyl alcohol	20:80	25:75	25:75	22:78	24:76	23:77

Centrifugation Conditions

- A. 2000 g for 5 minutes.
- B. 2500 g for 5 minutes.
- C. 2500 g for 5 minutes.
- D. 2500 g for 15 minutes.
- E. 2500 g for 5 minutes.
- F. 2000 g for 5 minutes.

The volume ratio of oil to liquid single phase mixture in each case is 1:1.

TABLE II.
Conditions for Effecting Olein-Stearin Separation of
Palm Oil by Gravity¹

Liquid Single Phase Mixture	Time for Complete Separation	
	Refined Palm Oil	Crude Palm Oil
13. Propylene Glycol:Butanone (30:70 v/v)	5 mins.	15 mins.
14. Propylene Glycol:Acetone (37:63 v/v)	10 mins.	30 mins.
15. Water:Acetone (33:67 v/v)	15 mins.	—
16. Glycerine:Isopropyl alcohol (23:77 v/v)	4 hrs.	—
17. Glycerine:n-Propyl alcohol (22:78 v/v)	48 hrs.	—
18. Water:Isopropyl alcohol (45:55 v/v)	48 hrs.	72 hrs.

1. Volume ratio of palm oil to liquid single phase mixture is 1:3.

TABLE III.
Conditions for Effecting Olein-Stearin Separation of
Palm Kernel Oil by Centrifugation

Liquid Single Phase Mixture	Ratio (v/v)	Centrifugation Conditions
19. Water:Isopropyl alcohol	48:52	ca. 14,900 g for 15 mins. Temperature: 25°C
20. Water:Propyl alcohol	50:50	
21. Propylene Glycol:Propyl alcohol	46:54	
22. Glycerine:Ethyl alcohol	24:76	
23. Glycerine:Propyl alcohol	26:74	

WHAT WE CLAIM IS:—

1. A process for separating olein and stearin fractions from an oil containing olein and stearin which process comprises providing a fluid comprising

- a) the oil concerned, and
- b) a liquid single phase mixture of two components,
 - i) at least one liquid polyhydroxy compound or water, with
 - ii) at least one polar organic liquid,
 which liquid single phase mixture is substantially insoluble in the oil and has a composition defined by the equation:

$$XD_1 + (100-X)D_2 = B$$

where X is the percentage of component (i),
 D_1 is the specific gravity of component (i) at 25°C,
 D_2 is the specific gravity of component (ii) at 25°C, and
 B depends on the specific gravity of the oil and varies between 87 and 97 and separating the oil into olein and stearin fractions by utilisation of their different densities.

TABLE II.
Conditions for Effecting Olein-Stearin Separation of
Palm Oil by Gravity¹

Liquid Single Phase Mixture	Time for Complete Separation	
	Refined Palm Oil	Crude Palm Oil
13. Propylene Glycol:Butanone (30:70 v/v)	5 mins.	15 mins.
14. Propylene Glycol:Acetone (37:63 v/v)	10 mins.	30 mins.
15. Water:Acetone (33:67 v/v)	15 mins.	—
16. Glycerine:Isopropyl alcohol (23:77 v/v)	4 hrs.	—
17. Glycerine:n-Propyl alcohol (22:78 v/v)	48 hrs.	—
18. Water:Isopropyl alcohol (45:55 v/v)	48 hrs.	72 hrs.

1. Volume ratio of palm oil to liquid single phase mixture is 1:3.

TABLE III.
Conditions for Effecting Olein-Stearin Separation of
Palm Kernel Oil by Centrifugation

Liquid Single Phase Mixture	Ratio (v/v)	Centrifugation Conditions
19. Water:Isopropyl alcohol	48:52	ca. 14,900 g for 15 mins.
20. Water:Propyl alcohol	50:50	
21. Propylene Glycol:Propyl alcohol	46:54	
22. Glycerine:Ethyl alcohol	24:76	Temperature: 25°C
23. Glycerine:Propyl alcohol	26:74	

WHAT WE CLAIM IS:—

1. A process for separating olein and stearin fractions from an oil containing olein and stearin which process comprises providing a fluid comprising

- a) the oil concerned, and
- b) a liquid single phase mixture of two components,
 - i) at least one liquid polyhydroxy compound or water, with
 - ii) at least one polar organic liquid,
 which liquid single phase mixture is substantially insoluble in the oil and has a composition defined by the equation:

$$XD_1 + (100-X)D_2 = B$$

where X is the percentage of component (i),
 D_1 is the specific gravity of component (i) at 25°C,
 D_2 is the specific gravity of component (ii) at 25°C, and
 B depends on the specific gravity of the oil and varies between 87 and 97 and separating the oil into olein and stearin fractions by utilisation of their different densities.



(15)

2. A process as claimed in claim 1, wherein the oil and the value of B are selected as follows:—

	Oil	B	
	crude palm oil	87—92	
5	refined palm oil	87—92	5
	rice bran oil	87—93	
	tallow	87—96	
	lard	87—97	
	herring oil	88—93	
10	palm kernel oil	89—95	10

3. A process as claimed in claim 1 or claim 2, wherein the oil is a palm oil which has been refined by partial crystallisation.

4. A process as claimed in any one of claims 1 to 3 wherein the fluid is allowed to stand at ambient temperature.

5. A process as claimed in any one of claims 1 to 4 wherein the volume ratio of liquid mixture to oil varies from 10:1 to 1:10. 15

6. A process as claimed in any one of claims 1 to 5 wherein in the case where separation is effected by allowing the fluid to stand the volume ratio of liquid mixture to oil varies from 10:1 to 1:5.

7. A process as claimed in any one of claims 1 to 6 wherein the volume ratio of liquid mixture to oil is 1:1. 20

8. A process as claimed in any one of claims 1 to 3, 5 and 7 wherein the fluid is centrifuged at at least 900 g.

9. A process as claimed in any one of claims 1 to 3, 5, 7 and 8 wherein the fluid is centrifuged at 2500 g or more. 25

10. A process as claimed in any one of claims 1 to 9 wherein the polyhydroxy compounds are selected from propylene glycol and glycerine.

11. A process as claimed in any one of claims 1 to 10 wherein the polar organic liquids are selected from acetone, butanone, ethyl alcohol, n-propyl alcohol and isopropyl alcohol. 30

12. A process as claimed in any one of claims 1 to 11 and substantially as hereinbefore described with reference to any one of Tables I to III.

13. Olein and stearin fractions whenever separated by a process as claimed in any one of the preceding claims.

For the Applicants,
STEVENS, HEWLETT & PERKINS,
Chartered Patent Agents,
5 Quality Court,
Chancery Lane,
London WC2A 1HZ.

Printed for Her Majesty's Stationery Office by the Courier Press, Leamington Spa, 1978.
Published by the Patent Office, 25 Southampton Buildings, London, WC2A 1AY, from
which copies may be obtained.

