

5 **SUBSEA EXCAVATION SYSTEMS AND METHODS**

TECHNICAL FIELD

The present invention relates generally to subsea excavation and mining.

10

BACKGROUND

Seabed excavation using equipment deployed from surface support vessels is well known. This general technique is routinely used by the marine dredging industry and subsea mining industry. Prior art in these fields is discussed below.

15

The dredging industry uses a range of excavation tools. The tools are generally suspended from surface support vessels by means of lowering equipment, such as winches or hydraulic elevators, which are located on the deck of the surface support vessel.

20

There are many different kinds of excavation tools and figures 1 and 2 illustrate two of the most common, a trailer suction dredger and a cutter suction dredger respectively. However the common factor linking the tools in the prior art is that they all steered according to the required excavation trajectory using a combination of the one or both of: i) surface support vessel steering track, ii) winching across seabed using winches located on deck in combination with sheaves on or near the seabed.

25

The majority of marine dredging activity takes place in shallow water coastal waters. In deep water conditions (over 300m water depth say) control over the excavation trajectory using these prior art techniques becomes increasingly difficult due to the practical limitations of distance between the surface support vessel and excavation tool on the seabed. In ultra-deep water conditions (over 1,000m water depth say) efficient control using these techniques is likely to be almost impossible.

30

The subsea mining industry has developed alternative methods compared to the marine dredging industry. One of the drivers for new methods has been the requirement of this industry to operate in open water further from the coastline, and in rather greater water depths compared to the marine dredging industry. Some of the prior art in this field is discussed below.

5 Seabed drilling systems are used from drill ships by De Beers for diamond mining in South Africa and Namibia. These drills use the “reverse circulation” technique in which the excavated seabed material is drilled with a very large diameter drill bit and sucked up through the riser pipe **52**. Apart from that aspect, the drilling technique is relatively conventional with a drill pipe suspended vertically from a deck-mounted derrick tower **39** and hoist **51**. Figure 3
10 illustrates this technique.

One of the major drawbacks of this technique is that drilling trajectory is purely vertical and there is no ability to steer the drill bit in a horizontal direction. As such the drill bit must be continually inserted, withdrawn following drilling, and then re-positioned on the seabed so the excavation takes place in a discrete and inefficient “cookie cutter” pattern. The circular nature of
15 the drill bit makes it difficult to join the excavated holes together to make a contiguous excavation.

Another disadvantage is the difficulty in accurately controlling the position of the drill bit. If the mining operation is to be done efficiently, the location of the drill hole must be accurately controlled. Such accuracy can be difficult to achieve, particularly in deep water and
20 in locations where the terrain is rugged (such as in most seabed massive sulphide ore deposits).

A further disadvantage in deep water is due to the fact that the power transfer to the drill bit is mechanically provided by the drill string. The downward force on the drill bit must be provided by the weight of the drill string, and this weight must be accurately controlled. Furthermore, the high torque requirements for the large diameter drill bit must also be provided
25 through the drill string.

As an improvement over the drill ship method, De Beers have also developed a seabed crawler vehicle technique. This is illustrated in Figure 4. In this technique the excavation tool **54** is mounted on a self propelled crawler vehicle **53** which can drive along the seabed **23**. The surface support vessel **18** simultaneously following the track of the vehicle along the seabed **23**.
30 In this way the disadvantages of the drill ship technique described above are largely overcome. Firstly, it is possible to make the excavation in a continuous trajectory in the horizontal plane – with obvious advantages in excavation efficiency. Secondly, the location of the excavation tool **54** is controlled locally on the seabed by the location and orientation of the crawler vehicle **53**. Thirdly, the crawler vehicle **53** provides its own power source, and it can easily control the
35 interaction forces between the excavation tool and the rock being excavated.

5 An important distinction between different seabed crawlers is the number of degrees of freedom between the crawler vehicle **53** and the excavation tool **54**. If the number of degrees of freedom is low, then the crawler vehicle **53** can make continuous horizontal cuts as it moves about the terrain. If the machine has enough degrees of freedom, it can sit in one place and make 3-dimensional cuts in its local vicinity. However, because a seabed crawler **53** must provide
10 counter-balancing forces, it will be much heavier than a machine of similar production rate and have fewer degrees of freedom.

 The seabed crawler vehicle technique has its own disadvantages. One of the key disadvantages being that the surface support vessel **18** is connected to the seabed crawler vehicle **53** by means of a flexible pipe **30** as opposed to a fixed steel pipe. Such flexible pipes are
15 specialist products and extremely expensive to manufacture. Furthermore it is often difficult to adjust the length of this flexible pipe because such pipes are generally manufactured in fixed lengths. This can make it correspondingly more difficult to adjust the seabed crawler technique to account for varying water depths, when compared to techniques which use fixed steel pipes which can be routinely and cheaply made up as required in conventional multi-joint lengths.

20 Another disadvantage of the seabed crawler vehicle is that it relies on competent and flat seabed terrain for stability during steering. There are notorious examples of severe instability occurring on unstable and sloping seabeds, which has caused the failure of entire mining projects. For example, the terrain around the richest type of mining deposits, seabed massive sulphides, is notoriously rugged.

25 The third disadvantage of the seabed crawler is that, in order to achieve high production rates, the crawler becomes very large. This is due to the relationship between production rate and excavation tool size, and the further relationship between excavation tool size and crawler size. Because the crawler must provide its own counter-balancing forces, only a fraction of the weight of the crawler can be applied to the excavation tool.

30 A further example of a method from the subsea mining industry is the use of a vertically-suspended trench cutter type excavator which is hung from a surface support vessel. Figures 5 and 6 illustrate a trench cutting system developed by Bauer Maschinen GmbH.

 Figure 6 shows the cutting frame and all the components of the trench cutter type excavator. It consists of a frame **1** with counter-rotating cutter wheels **5** at the base. The cutter
35 wheels **5** inject the cuttings into the suction of a slurry pump **3** which provides power for hoisting

5 the slurry a short distance, tens of meters. In examples of the present invention this would be sufficient to supply the excavation slurry to the bottom of a lift pipe which would have airlift or mechanical pumps or other lift methods to provide most of the power for lifting the excavation slurry potentially thousands of meters to the surface.

10 An advantage of the vertically-suspended trench cutter compared to the drill ship technique described above is that the section excavated in each cut is rectangular in plan (rather than circular as provided by the drill) and a continuous excavation plan is more efficiently formed. Like the seabed crawler, the trench cutter decouples the power transfer from the surface support vessel and provides it locally. A particular advantage is that the machine is very weight-efficient. The weight of the entire machine stands on the cutters, so the machine can be made
15 much lighter than a seabed crawler with the same production rate. However the key disadvantage is that it is a one-dimensional excavator; there is no included means for creating a horizontal excavation trajectory.

Another technique that has been used is steering the drill bit **61** in a horizontal trajectory by means of tugger lines **62** from the deck of the surface support vessel **18**. This technique is
20 shown in *Kuntz*, United States Patent No. 3,763,580 “Apparatus for Dredging in Deep Ocean,” see Figure 7. In this technique the tugger lines **62** act through sheave blocks **63** anchored into the seabed **23**.

However, it is noted that the use of the tugger lines deployed from the deck of the surface support vessel will have practical limitations and will represent a disadvantage in ultra-deep
25 water as described above in relation to techniques used by the marine dredging industry.

Yu United States Patent No. 7,690,135 “Deep Sea Mining Riser and Lift System,” describes a variation on the seabed crawler vehicle technique that replaces the flexible pipe **30** for lifting the slurry with rigid pipe **38** for the majority of length connecting the seabed crawler vehicle **53** to the surface support vessel **18**. This patent describes that the use of flexible pipe **30**
30 is now limited to a far shorter fixed length “jumper” section connecting between the crawler vehicle **53** and bottom of the rigid pipe **38**. See Figure 8.

5 DISCLOSURE OF THE INVENTION

It is an object of the present invention to provide methods and systems for efficiently excavating or mining the seabed. The excavation process requires positioning and stabilizing the excavator relative to the seabed and exerting force between the excavator and the soil, rock, ore,
10 or other material to be excavated. Examples of the present invention address this process by exerting force between a subsea anchor point and an excavator using a subsea actuator. In some examples the subsea actuator is attached to an anchor point on the seabed and the excavator directly. In other examples, a guide frame is anchored to the seabed to provide anchor points fixed relative to the seabed and the subsea actuators are attached to the guide frame and the
15 excavator. In further examples, the subsea actuators can be attached to the excavator through a carrier frame or other excavator guides rather than directly to the excavator.

According to a first example of the invention, a subsea excavation apparatus is provided. The apparatus comprises: an excavator; a first anchor point in a first fixed location relative to the
20 seabed; a first subsea actuator attached to the excavator and the first anchor point for converting power to mechanical force between the first anchor point and the excavator; wherein the subsea actuator exerts force in response to actuator control signals. In some systems, the first subsea actuator is positioned and arranged to exert force primarily horizontally. In some other systems, the first subsea actuator is positioned and arranged to exert force primarily vertically. In many
25 systems, the first subsea actuator is for converting electrical power to mechanical force. In some other systems, the first subsea actuator is for converting hydraulic power to mechanical force. In some systems, the first subsea actuator comprises a unidirectional actuator. In some other systems, the first subsea actuator comprises a bidirectional actuator. In many systems, the first subsea actuator is responsive to actuator control signals to manage the location of the excavator
30 on an excavation face. In many systems, the excavator is responsive to excavator control signals. In some systems, excavator control signals and actuator control signals are provided interdependently to manage excavation location and rate.

According to a further example of the invention, a subsea excavation apparatus is provided that further comprises: a second anchor point in a second fixed location relative to the
35 seabed; a third anchor point in a third fixed location relative to the seabed; a second subsea

5 actuator attached to the excavator and the second anchor point for converting power to mechanical force between the second anchor point and the excavator; a third subsea actuator attached to the excavator and the third anchor point for converting power to mechanical force between the third anchor point and the excavator; wherein the second and third subsea actuator exert force in response to actuator control signals. In some such example systems, the first,
10 second, and third subsea actuators are responsive to actuator control signals to manage the location of the excavator on an excavation face in three dimensions. In some examples, the actuator control signals are used to manage the orientation of the excavator on an excavation face. In some examples, the actuator control signals are used to manage the location and orientation of the excavator on an excavation face.

15 According to another example of the invention, a method for controlling a subsea excavator is provided. The method comprises: maintaining a plurality of anchor points at a fixed locations relative to the seabed; providing power to a plurality of subsea actuators; converting the power to a mechanical force with each subsea actuator; applying the mechanical forces between
20 the subsea excavator and the plurality of anchor points; providing actuator control signals to the plurality of subsea actuators. In some such methods, the actuator control signals control the forces and moments on the excavator in three dimensions. In some example methods, the actuator control signals control the forces and moments exerted by the plurality of subsea actuators. In some such methods, the actuator control signals control the movement of the
25 plurality of subsea actuators. In many example methods, the actuator control signals are used to manage the location of the excavator on an excavation face. In many example methods, the power is provided by a support vessel. In some example methods, the plurality of subsea actuators comprises unidirectional actuators. In other example methods, the plurality of subsea actuators comprises bidirectional actuators.

30 In a further example of the invention, a method for controlling a subsea excavator is provided that further comprises providing excavator control signals to the excavator.

5 BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 is a side view of a trailer suction dredger.

FIG. 2 is a perspective view of a cutter suction dredger.

FIG. 3 is a side view of a drill ship used for seabed mining.

10 FIG. 4 is a side view of a drill ship and seabed crawler vehicle used for seabed mining.

FIG. 5 is a side view of a surface support vessel and vertical trench cutter used for seabed mining.

FIG. 6 is a side view of a vertical trench cutter used for seabed mining.

15 FIG. 7 is a side view of apparatus for dredging in deep ocean using tugger lines and sheaves on the seabed.

FIG. 8 is a side view of a seabed crawler type apparatus using a combination of flexible and rigid pipe for lifting excavated slurry.

FIG. 9 is a side view of an underwater cable burial system.

FIG. 10 is a perspective view of lateral reaction forces applied to an excavator.

20 FIG. 11A is a side view of an excavator attached to anchor points using cables.

FIG. 11B is a side view of an excavator attached to anchor points using cables.

FIG. 11C is a side view of an excavator attached to anchor points using cables.

FIG. 11D is a side view of an excavator attached to anchor points using cables.

FIG. 12 is a side view of an excavator attached to a guide frame attached to anchor points.

25 FIG. 13 is a side view of an excavator attached to a guide frame with a vertical actuator.

FIG. 14 is a perspective view of an excavator within a carrier frame attached to anchor points using cables.

FIG. 15 is a side view illustrating forces on an excavator in lateral mining.

FIG. 16 is a side view of an excavator in lateral mining.

30 FIG. 17 is a side view of an excavator in lateral mining and associated lift system and support vessel.

FIG. 18 is a side view of an excavator in a guide frame for lateral mining and associated lift system and support vessel.

35 FIG. 19 is a side view of an excavator in a guide frame for lateral mining and associated lift system and support vessel.

- 5 FIG. 20 is a plan view of an excavator in a guide frame for lateral mining.
FIG. 21 is a plan view of a lateral mining operation.

5 MODES FOR CARRYING OUT THE INVENTION

Examples embodiments of the present invention overcome the disadvantages in the prior art as described above and consequently provide more efficient systems and methods for Seabed Excavation particularly in ultra-deep water conditions. The example embodiments provide economic advantages compared to previous techniques.

These example embodiments can utilize existing, weight-efficient excavating and cutting technology, for example the Bauer trench cutter (Figure 6), but is not limited to this particular type of excavator. For example, other excavators such as roadheaders, vertical miners, hydromills, jet cutters, and rotating drums could be used in these examples.

These example embodiments can use a wide variety of existing actuators, including unidirectional actuators such as winches and cables and/or bidirectional actuators such as hydraulic cylinders, electromechanical actuators, screw drives, rack and pinion drives, and gear drives.

These example embodiments can also use a wide variety of seabed anchor technologies to provide anchor points including: gravity anchors, drilled and grouted piles, suction piles, drag embedment anchors, torpedo anchors, and screw anchors.

In at least one example embodiment of the invention, a subsea excavation apparatus is provided that includes an excavator that is positioned by subsea actuators in response to actuator control signals. The actuator control signals can command either or both a specific force or position from the actuator. Each subsea actuator converts power into mechanical force and is mounted between an anchor point in a fixed location relative to the seabed and the excavator. In various example embodiments, the subsea actuator receives either electric or hydraulic power from a surface support vessel. By providing a subsea actuator that is attached to an anchor point, these examples increase efficiency of deep sea operation and require less costly surface support vessels and/or platforms than previous methods. Because the excavator is positioned relative to an anchor point that is fixed relative to the seabed, costly support vessel station keeping and motion compensation systems are not required. Additionally, the necessity for long mechanical linkages between the surface and seabed are replaced with more efficient means of providing power to the seabed, such as electrical or hydraulic transmission.

5 In further examples, the actuator control signals to multiple subsea actuators can manage excavation rate and location by controlling the position of the excavator relative to the seabed in three dimensions and controlling the force exerted on the excavation face by the excavator.

 In further example embodiments, the excavator may be responsive to excavator control signals to control the rate of excavation and/or extraction of excavated materials.

10 In further example embodiments, the actuator and excavator control signals are adjusted in concert to control the rate of extraction. The excavator and actuator control signals may operate in a feedback loop where each is adjusted in response to the other, or in response to feedback from either the excavator or actuators. For example, if the torque requirements on THE excavator's rotating cutter start to exceed its capabilities, the excavation rate could be reduced by
15 either reducing the force exerted on the excavator by the actuators toward the excavation face and thereby reducing the effective depth of the cut, or by reducing the force exerted on the excavator by the actuators along the excavation face thereby reducing the advance rate of the excavator.

 In further example embodiments, the system can contain three or more subsea actuators
20 to exert force on the excavator in three dimensions.

 In other example embodiments, a method for controlling a subsea excavator is provided where anchor points are maintained in fixed locations relative to the seabed, power is provided to a subsea actuator, the subsea actuator exerts force between an anchor point and the excavator in response to actuator control signals. This method can be applied with the example system
25 embodiments described. By providing a subsea anchor point and subsea actuator, these examples increase efficiency of deep sea operation and require less costly surface support vessels and/or platforms than previous methods. Costly support vessel station keeping and motion compensation systems are not required because the excavator is positioned relative to the seabed rather than a surface support vessel or platform. Additionally, the necessity for long mechanical
30 linkages between the surface and seabed can be replaced with more efficient means of providing power to the seabed, such as electrical or hydraulic transmission.

 One example embodiment is a method to utilize existing excavators to efficiently mine in the deep sea. This involves the use of remotely controlled equipment, coupled with the weight of the machine, to accurately control the excavation trajectory of the machine, in three dimensions,
35 over large areas.

5 One example embodiment uses subsea winches as actuators, flexible and rigid pipe (for lifting of an excavated slurry), a controllable lowering winch for the excavator and vertical actuator, Remotely Operated Vehicles, and possibly a submerged, suspended guide frame to facilitate control of the excavator.

10 As mentioned above, the means for guiding subsea excavating equipment has traditionally been one of the following means: 1) maneuvering the support vessel **18** by means of anchor lines or thrusters to control a suspended pipe or cable (see e.g. Figure 1, Figure 3); 2) using winches **19** mounted on the surface vessel **18** together with sheaves **63** on the seabed **23** to apply a horizontal force to a suspended excavator (Figure 7); 3) using winches on a surface vessel **18** pulling on a fixed point to apply horizontal forces to a seabed trencher **64** (Figure 9); 4) using a seabed crawler vehicle **53** to control the movements of an excavation tool **54** on an extended arm (Figure 4).

15 Examples of the present invention introduce the use of subsea actuators (such as winches and hydraulic cylinders), ROVs, cable supported excavators and seabed anchors to allow for efficient extraction of minerals from the seabed. This approach has not been used previously for a variety of reasons. First, it has been stated that solutions involving a winch anchored to a fixed point as in Figure 7 could not be applicable over a wide area of the seabed (see U.S. Patent No. 6,273,642).

20 This objection is overcome in examples of the present invention by allowing the use of a fixed point relative to the seabed as the anchoring point in combination with a subsea actuator. In some examples this anchor point is a gravity anchor, a drilled and grouted pile, a driven pile, a suction pile, a drag embedment, a torpedo anchor, a screw anchor, or a subsea drilled anchor.

25 Placing a fixed anchor point on the seabed in the deep sea is constrained by the magnitude of the lateral forces required to cut the rock. In some examples of the invention, this objection is overcome by minimizing these forces through the use of an excavator which provides the primary cutting forces by its own weight. Two excavating scenarios are envisioned. In one case the excavator, similar to Figure 6, makes essentially vertical cuts and may mine a deposit by cutting a series of vertical holes. The vertical cuts do not require any lateral forces to be applied for cutting. Experience in surface and shallow water excavation has shown vertical trench cutting to be an extremely weight-efficient means of excavating soil, rock, and ore.

5 Examples of the invention may be used for either vertical excavation (similar to trench cutting), or lateral excavation (similar to strip mining).

 According to some examples embodiments, it is possible to completely excavate a deposit by vertical cutting alone. A vertical cutting machine type excavator can excavate a trench in one direction using the weight of the excavator alone to stabilize the cut. The weight of the
10 device can be sufficient to provide cutting forces without any external forces being applied. Inclination of the cutter is arrested by bearing pads **2** on the outside of the cutter frame **1** which bear against the walls of the trench. Mining an open pit with such a device is more complicated. Various hole-patterns for an open pit process using a trench cutter are possible. The cutter may be rotary (creating a circular hole) or rectangular (creating a rectangular hole). As the pit is
15 expanded, the cuts are made without the aid of trench walls for support. Lateral reaction forces **44** are provided to maintain the stability of the excavator **16**, shown in Figure 10.

 Figures 11A-D show example embodiments involving the use of cables **7** to stabilize the vertical excavator **16**. Figure 11A is one embodiment of the invention whereby the cables **7** are attached to an anchor point **8** on the seabed **23**. The operation of this example embodiment
20 would employ a submerged winch **9** as a subsea actuator on the excavator **16** powered by an electric or electro-hydraulic motor. The winch cable **7** would be drawn from the winch **9** and attached to the anchor point **8** by means of a remotely operated vehicle (ROV) **10**. The anchor points **8** may be either permanently or temporarily fixed in the seabed with piles **11**, clump weights **12**, gravity anchors, drilled and grouted piles, suction piles, drag embedment anchors,
25 torpedo anchors, and/or screw anchors.

 In the example embodiment shown in Figure 11A, the use of cables to stabilize a cut limits the depth of the cut **13** because of interference with the walls of the trench. Alternate embodiments which mitigate this limitation are shown in Figures 11 B-D and 15.

 In the example embodiment shown in Figure 11B, carrier frame **14** encases the vertical
30 excavator **16** and is held in position with cables **7**. In this embodiment winches **9** would be attached to the carrier frame **14** and connected to the anchor points **8**. The ROV **10** would be used to attach the cables **7** to the anchor points **8**.

 The example embodiment shown in Figure 11C utilizes a sliding collar **17** to position the bottom of the excavator **16**. In this embodiment the wire would be deployed from winches **9** on

5 the sliding collar **17** and the excavator **16**. Cable **7** would be deployed from these winches **9** to the anchor points **8** in the same manner as described above.

The example embodiment shown in Figure 11D utilizes bridle lines **32** to stabilize the tilting of the excavator **16** and lateral cable actuators **7** provide horizontal control..

10 Figure 12 shows another example embodiment where a guide frame **21** is supported on cables **20** from a support vessel or platform **18**. The length of cables **20** may be adjusted with winches **19** on the support vessel **18** to change the angle of the guide frame **21** in order to conform to the slope of the seabed **23**. The guide frame **21** is connected to the seabed **23** with cables **7** attached to anchor points **8**. The guide frame **21** is thus stably suspended from the support vessel **18** with cables **20**, and connected to the seabed with cables **24** attached to anchor points **8**. The excavator **16** is supported from the surface platform **18** by riser pipe or cable **22**. It is further guided as in other example embodiments by cables **7** which connect the excavator to the guide frame **21** for support. In this example, the cables **7** are stored on winches **9** which are connected to the excavator **16**. In operation the cables **7** are attached to the frame **21** using an ROV in a manner similar to the use of the ROV to connect the cables **7** to anchor points **8** in the example embodiment shown in Figures 11A-D. The winches **9** could alternately be attached to the frame **21** in which case the cable **7** would be connected to a fixed point on the excavator **16**.

15 In the example embodiment shown in Figure 13, an excavator is attached to a guide frame **21**. The guide frame **21** is supported from the surface vessel **18** by cables **20** and anchored to the seabed **23** by cables **24**. This arrangement allows the frame to provide vertical and horizontal reaction forces to the excavator **16**. For example, the vertical cutting force may be reacted by the vertical component of the forces in the cable **7**. The excavator **16** is positioned horizontally within the guide frame **21** by subsea actuators (not shown) acting in a generally horizontal plane. The vertical position of the excavator **16** is controlled by a vertical subsea actuator **46** and rigid strut **47**. The vertical actuator **46** can therefore control the force between the excavation face and the excavator **16**. In this example, the guide frame **21** acts as intermediary anchor points between the excavator **16** and the seabed anchors **8**, which ultimately provide reaction points for the forces acting on the excavator **16**. In a further example embodiment, the anchor cables **20** are replaced by rigid legs between the guide frame **21** and the seabed **23**.

5 Figure 14 shows perspective view of an example embodiment similar to that shown in Figure 11B. Several cables **7** are attached to a carrier frame **14**. The cable lengths **7** may be adjusted to achieve a desired position and orientation of the carrier frame **14** and excavator **16** for making a new excavation to expand a pit **72**.

10 The above examples pertain primarily to vertical excavation which may be the most efficient available for irregular sea beds, pillars and very narrow deep deposits. As noted those examples require guidance of the cutter during pit expansion, which may be difficult with a cable guided system. The following examples illustrate how the same basic cutting machine may be extended for lateral cutting similar to surface mining using cable and winch guidance.

15 Figure 15 shows an excavator **16** which is inclined at a non-orthogonal angle with respect to the seabed **23**. To achieve stable lateral mining the horizontal forces **27**, vertical forces **28** and moment **29** on the cutter frame must be in equilibrium as follows: 1) sum of horizontal forces **27** must be equal to zero; 2) sum of vertical forces **28** must be equal to zero; 3) moment **29** resulting from all of the vertical and horizontal forces must be zero. This means that subsea actuators and the weight of the excavator must provide forces on the excavator sufficient to excavate the rock.
20 A typical example scenario is provided by Figure 15 and parameters corresponding to computations performed utilizing a Bauer BC50 cutter used on a typical massive sulfide rock deposit. These parameters are: UCS average 20 Mpa (up to 80), Density of 2.4; footprint 840 x 3200 mm; load on bit 5-20 tons; machine weight 40 tons; 500 kW hydraulic power; .4 cubic meter per minute production; tooth replacement every 16 hours of excavation. In this example
25 calculation the horizontal force applied to the excavator is 141 kN; the vertical force applied to the excavator is 220 kN; and the weight of the excavator is 40 kN.

30 This principle of static equilibrium is well known in engineering mechanics. The values in this example are only for illustration and specific values will vary from application to application due to different cutter head weights and dimensions, and different rock cutting forces. In order to maintain equilibrium for different cutting forces the external applied loads will need adjustment.

35 Figure 16 shows an example embodiment which may achieve control over the orientation and of the cutter at a suitable cutting angle using three winches **34**, **35**, and **36** on the excavator **16**. One winch **34** is connected to a cable **31** (the “drag line”) which attached to an anchor **8** fixed to the seabed **23**. This winch **34** and drag line **31** are used to apply a force between the cutter

5 heads **37** and the seabed rock **23**, and to control the forward advance of the excavator **16**.
Winches **35** and **36** are used to control the respective bridle lines **32** attached to the lifting lines
33. The lifting line **33** is supported by a support vessel or platform **18** or a guide frame **21**. By
controlling these bridle lines **32** attached to winches **35** and **36** respectively the moment on the
frame may be adjusted to achieve the desired excavator angle. Sensors on the excavator frame,
10 including inclinometers and tension gauges (for the lines), can be used to establish control of the
excavator **16**.

Figure 17 shows how this example system may be integrated with the support vessel **18**
and the lift pipe **38**. The excavator **16** is supported by a bridle **32** and a cable **33** by a motion
compensated winch **19** on board the support vessel **18**. When the excavator **16** is first lowered to
15 the sea floor **23** the individual lines of the bridle **32** are adjusted to achieve the correct excavator
angle (as shown in Figure 16). The drag line **31** is attached to anchor point **8** using a remotely
operated vehicle (ROV). A flexible pipe **30** for the lift system is also attached by the ROV
between the excavator **16** and the rigid lift pipe **38**. The rigid lift pipe **38** is supported by a
derrick **39** or other supporting structure. Pumping of fluid through the flexible pipe **30** and rigid
20 lift pipe **38** commences using either a mechanical pump or airlift. Next a slurry booster pump on
the excavator **16** is started and finally the cutting wheels **37** are activated. Power for the cutting
wheels **37** and slurry pump are provided by a separate umbilical (not shown) which is run with
the lifting line **33**. The anchor point **8** for the drag line **31** may be a clump weight which may be
preset by the same lifting line **33** used for the excavator **16**, a piled anchor drilled by a subsea
25 drill, gravity anchor, drilled and grouted pile, suction pile, drag embedment anchor, torpedo
anchor, and/or screw anchor.

Figure 18 shows an example embodiment for lateral mining using the guide frame **21**
previously discussed in relation to Figures 12 and 13. This may be advantages for topographies
where the drag line **31** cannot ride along the bottom, or if the lifting line **33** is not stiff enough to
30 control the dynamics of the excavator **16**. The subsea guide frame **21** can be anchored and
suspended from the support vessel/platform **18** as shown, or it can be attached to the seabed **23**.
In this example embodiment, the drag line **31** is affixed to an anchor point on the guide frame **21**
instead of an anchor point directly on the seabed **8**. The guide frame **21** is controlled by cables **24**
which are attached to the seabed at anchor points **8**, and winches **9** attached to the frame. The
35 entire guide frame is suspended on cables **20** from the support vessel/platform **18**. Excavation is

5 controlled by the drag line **31** and winch **34** (see Figure 16). In this case the position of the guide frame **21** may be moved by adjusting the length of lines **24** using winches **9**, and at the same time adjusting the position of the surface platform by adjusting the lengths of mooring lines **41** using winches **40**.

Another embodiment using the submerged frame is shown in Figures 19 and 20. The
10 anchor lines **24** between the guide frame **21** and an anchor point **8** on the seabed **23** are capable of reacting to the vertical cutting forces. Here they are also used to provide horizontal reaction forces as the excavator **16** is moved horizontally across the seabed **23**. The control of the horizontal motion is affected by control lines **42** between the excavator **16** and the guide frame **21**, which is in a fixed position relative to the seabed **23** by virtue of the anchor lines **24**. The
15 plan view of Figure 20 shows the guide frame **21** with the control lines **42** and anchor lines **24**.

Figure 21 shows a plan view of an example of the lateral/surface excavation embodiment. The seabed rock **23** is cut in approximate 0.8 – 1.6 m wide strips **43** (depending on the cutter arrangement) approximately 2.0 m deep. The excavator **16** needs to be stabilized as it cuts adjacent rows. This figure shows lateral control lines **7** which are attached to the excavator **16**
20 and to an anchor point **8** on the seabed. Control lines **7** are controlled by winches **9** which may be attached to the cutting excavator **16** or the anchor point **8** in the same manner as the control lines **7** are used for the vertical mining tool embodiments discussed above.

Note that the cutter is not restricted to making passes of equal depth, whether it is dragged by anchor points attached to a guide frame or to the seabed - the depth of cut can be
25 varied to “sculpt” the seabed, e.g. to excavate a rounded pit to follow an orebody. Furthermore, the heading orientation of the machine can be changed, e.g. using cables as shown in Figure 13 or through other means, e.g. by modifying a carrier frame such as shown Figure 11 to be cylindrical, then rotating the excavator or cutter head inside the cylinder. By changing the heading orientation of the cutter and by using three or more drag lines, the cutter can be used to
30 sculpt an excavation in three dimensions. Examples of the invention therefore include the ability to use a combination of vertical and horizontal forces to excavate a pit of arbitrary shape on large areas of rugged terrain.

Also note that, if a frame as shown in Figure 18 is used, the means of generating lateral forces are not restricted to winches. For example, a rack-and-pinion mechanism could be used to
35 drive a gantry to which the cutters are attached. The gantry can also include means by which to

5 tilt and steer the excavator. The excavator can be attached to the gantry by lines, or it can be
fixed to the gantry by bi-directional mechanical means. Such mechanical means may include a
vertical actuation. In the former case, the downward forces will be generated solely by the
weight of the excavator, but the lateral forces can be provided by means other than winches. In
the latter case, the vertical force is provided by the combination of the weight of the excavator
10 and the reaction force against the gantry assembly above the machine.

Calculations have been performed for the performance of the system shown in Figure 21
utilizing the Bauer BC50 trench cutter:

Cutting depth: 2 m Cutting width: 0.84 m Rock production: 0.4 cu m / min Forward
Speed: 0.25 m/min

15 Assumed track length: 200 m Cycle time (per track): 800 m (13.3 hours)

The track length could be shortened or extended as appropriate for the topography. Many
tracks should be possible to achieve with a single drag line/anchor placement, provided lateral
guidance is provided.

Experience with trench cutters would suggest about a 16 hour cycle on changing out of
20 teeth. This might argue for two units on separate hoist lines with one ready to commence a
second pass when the first machine completes a pass and is retrieved.

The foregoing description is presented for purposes of illustration and description, and is
not intended to limit the invention to the forms disclosed herein. Consequently, variations and
modifications commensurate with the above disclosures and the disclosure of the relevant art are
25 within the spirit of the invention. Such variations will readily suggest themselves to those skilled
in the relevant art. Further, the examples described are also intended to explain the best mode for
carrying out the invention, and to enable others skilled in the art to utilize the invention and such
or other embodiments and with various modifications required by the particular applications or
uses of the invention. It is intended that the appended claims be construed to include alternative
30 embodiments to the extent that is permitted by prior art.

5 What is claimed is:

1. A subsea excavation apparatus comprising:

an excavator;

a first anchor point in a first fixed location relative to the seabed;

10 a first subsea actuator attached to the excavator and the first anchor point for converting
power to mechanical force between the first anchor point and the excavator;
wherein the subsea actuator exerts force in response to actuator control signals.

2. The subsea excavation apparatus of claim 1 wherein the first subsea actuator is positioned
and arranged to exert force primarily horizontally.

15 3. The subsea excavation apparatus of claim 1 wherein the first subsea actuator is positioned
and arranged to exert force primarily vertically.

4. The subsea excavation apparatus of claim 1 wherein the first subsea actuator is for
20 converting electrical power to mechanical force between the first anchor point and the
excavator.

5. The subsea excavation apparatus of claim 1 wherein the first subsea actuator is for
25 converting hydraulic power to mechanical force between the first anchor point and the
excavator.

6. The subsea excavation apparatus of claim 1 wherein the first subsea actuator comprises a
unidirectional actuator.

30 7. The subsea excavation apparatus of claim 1 wherein the first subsea actuator comprises a
bidirectional actuator.

8. The subsea excavation apparatus of claim 1 wherein the first subsea actuator is
35 responsive to actuator control signals to manage the location of the excavator on an
excavation face.

5

9. The subsea excavation apparatus of claim 1 wherein the excavator is responsive to excavator control signals.

10

10. The subsea excavation apparatus of claim 9 wherein the excavator control signals and actuator control signals are provided interdependently to manage excavation location and rate.

- 5 11. The subsea excavation apparatus of claim 1, further comprising:
a second anchor point in a second fixed location relative to the seabed;
a third anchor point in a third fixed location relative to the seabed;
a second subsea actuator attached to the excavator and the second anchor point for
converting power to mechanical force between the second anchor point and the
10 excavator;
a third subsea actuator attached to the excavator and the third anchor point for converting
power to mechanical force between the third anchor point and the excavator;
wherein the second and third subsea actuator exert force in response to actuator control
signals.
- 15
12. The subsea excavation apparatus of claim 11 wherein the first, second, and third subsea
actuators are responsive to actuator control signals to manage the location of the
excavator on an excavation face in three dimensions.
- 20 13. The subsea excavation apparatus of claim 11 wherein the first, second, and third anchor
points are located on a guide frame that is anchored to the seabed.

- 5 14. A method for controlling a subsea excavator comprising:
maintaining a plurality of anchor points at a fixed locations relative to the seabed;
providing power to a plurality of subsea actuators;
converting the power to a mechanical force with each subsea actuator;
applying the mechanical forces between the subsea excavator and the plurality of anchor
10 points;
providing actuator control signals to the plurality of subsea actuators.
- 15 15. The method for controlling a subsea excavator of claim 14 wherein the actuator control signals control the forces and moments on the excavator in three dimensions.
- 16 16. The method for controlling a subsea excavator of claim 14 wherein the actuator control signals control the forces and moments exerted by the plurality of subsea actuators.
- 20 17. The method for controlling a subsea excavator of claim 14 wherein the actuator control signals control the movement of the at least one subsea actuator.
18. The method for controlling a subsea excavator of claim 14 wherein the actuator control signals are used to manage the location of the excavator on an excavation face.
- 25 19. The method for controlling a subsea excavator of claim 14 wherein the actuator control signals are used to manage the orientation of the excavator on an excavation face.
20. The method for controlling a subsea excavator of claim 14 wherein the actuator control signals are used to manage the location and orientation of the excavator on an excavation
30 face.
21. The method for controlling a subsea excavator of claim 14 wherein the power is provided by a support vessel.

- 5 22. The method for controlling a subsea excavator of claim 14 wherein the plurality of subsea
actuators comprise unidirectional actuators.
23. The method for controlling a subsea excavator of claim 14 wherein the plurality of
actuators comprise bidirectional actuators.
- 10 24. The method for controlling a subsea excavator of claim 14 further comprising providing
excavator control signals to the excavator.
25. The method for controlling a subsea excavator of claim 14 wherein the plurality of
15 anchor points are maintained on a guide frame that is anchored to the seabed.