

METHOD FOR ACCESSING INFORMATION

BACKGROUND OF THE INVENTION

The present invention relates to an information accessing method for accessing information held in a server unit included in a client-server system, and
5 more particularly to the information accessing method that is effective when a client unit located in a client-server system accesses information held in a server unit located in another client-server system through a network having two or more client-server
10 systems connected therein.

As a method for accessing information held in a data file to be tightly secured, a method has been proposed for restricting access to such a data file with a user ID or a password. With this method, a client-
15 server system takes the steps of registering in a server unit a user ID or a password with which access is permitted in a client-server system having the server unit, comparing a user ID or a password which the user inputs with the user ID or the password registered in
20 the client-server system, and permitting access to a data file contained in the server unit only if both of the user ID and the password are matched to each other. If a user or a user group of specific users belonging to a section of a company makes access to a data file, some
25 access levels are set according to the position of each

1-4521100

user in the company. Each access level may reach the corresponding portion of the data file to be accessed. Those access levels are used for access restriction such as disability to access the data file, ability only to
5 access a data file, and ability to update a data file.

When a data file registered in a client-server system is accessed by a client unit of another client-server system in a network such as a communication tool having two or more client-server systems connected
10 therethrough, the client unit pre-registers a guide ID in the client-server system having the data file to be accessed so that the client unit may access the data file in the different client-server system from the system to which the client unit belongs.

15 SUMMARY OF THE INVENTION

If the foregoing client-server system is applied to a system for managing a schedule, the information to be secured is a schedule of each user.

For example, a person who would hold a
20 meeting, a host of the meeting needs to access a schedule on the meeting day of each meeting participant for the purpose of checking if each participant's schedule is open. If, however, any one of the participants belongs to the management of a different client-
25 server system from the system of the host, in the current state, the client-server system of the participant is configured to unconditionally permit the

host to access to his or her schedule or prohibit the host to do so.

The personal schedule contains one portion that is open to any user of the client-server system
5 such as appointed day and hours and the other portion that is not open to all the users of the system such as a destination of a business trip or a dealer. The current system does not provide a capability of fine restricting the data to a portion to be accessed or a
10 portion not to be accessed according to the relation between the user to be accessed and the user who would access the data.

It is an object of the present invention to provide an information accessing method that permits a
15 user of a client-server system to access the user data of another client-server system under proper security.

It is another object of the present invention to provide an information accessing method that controls permission to access the user data according to the
20 corresponding relation of a security rank between a user to be accessed and a user who would access the user data.

Later, the term "system" means a system having a function of storing user data for each user, registering as a user ID an ID of a user permitted to access the
25 user data and specifying the range of the registered user ID as the managing range of the system itself. The present invention is characterized to offer a security

method that is arranged to convert a first user ID belonging to the managing range of a first system into a second user ID (guest ID) belonging to the managing range of a second system and permit the user to access
5 the user data if the second user ID and a third user ID for an owner of the user data belong to the second system.

Further, the information accessing method according to the present invention is configured to set
10 one of plural security ranks to each user, set a table for determining if the access to the user data is permitted from a security rank of a user for requesting the access to the user data and a security rank of a user whose data is accessed by the former user, and
15 determine if the access to the user data is permitted by referencing this table if requested to access the user data.

When the user with the first user ID logs in the first system or issues a request for access to the
20 user data, the first user ID is checked by the first system. When the user with the first user ID issues a request for accessing the user data of a second system, it is checked if the first user ID is registered in the ID conversion table. When the request for access is
25 passed to the second system, it is checked if a second user ID is registered in the ID conversion table. That is, three checks are executed until the user of one system is permitted to access the data of the user

belonging to the other system. After these checks are done, the user with the first ID enables to access the whole user data managed by the second system. Further, the use of the security rank makes it possible to
5 determine if the access to at least part of the user data is permitted on the basis of the security rank of the user for issuing a request for access and the security rank of the user whose data is to be accessed.

BRIEF DESCRIPTION OF THE DRAWINGS

10 Fig. 1 is a block diagram showing an overall configuration of a system according to the present invention;

Fig. 2 is a table showing a data format of an ID conversion table 14 according to an embodiment of the
15 present invention;

Fig. 3 is a table showing a data format of a user ID table 11 according to an embodiment of the present invention;

Fig. 4 is a table showing a data format of a
20 security table 12 according to an embodiment of the present invention;

Fig. 5 is a table showing a data format of user data 13 according to an embodiment of the present invention; and

25 Fig. 6 is a flowchart showing a flow of process located between the systems according to an embodiment of the present invention.

DESCRIPTION OF THE PREFERRED EMBODIMENT

Later, the description will be oriented to a schedule management to which an embodiment of the present invention is applied with reference to the
5 drawings.

Fig. 1 is a block diagram showing a basic system arrangement for describing an embodiment of the present invention. In the present invention, a term "client-server system" means a system configured to
10 connect at least one client unit (20) to at least one server unit (10) so that the server unit of this system manages data (41) of the user who uses the client unit of this system.

Fig. 1 shows a system configuration having two
15 such client-server systems (100, 500) connected through a network 90. A numeral 10 denotes a server unit for managing a schedule of a user. A numeral 20 denotes a personal computer (PC) that is a client unit for accessing the server unit 1 through a local area network 30
20 (LAN). In Fig. 1, one PC 20 is connected to the LAN 30. In actual, two or more PCs may be connected to the LAN 30. A numeral 41 denotes a user data registration unit for registering a schedule of each user. The schedule registered in the registration unit 41 comprises an open
25 portion 411 and a closed portion 412, both of which are shown in Fig. 5 and will be discussed below. A numeral 43 denotes a user ID table for registering a user ID that is permitted to access the user data held in the

client-server system to which the user with the user ID belongs. A numeral 42 denotes a security table registering unit for registering a security table for determining if the closed portion 412 of the schedule of
5 the target user is to be accessed according to the security ranks of the user who would like to access the data and the user to be accessed, which will be discussed in detail with reference to Figs. 3 and 4. A numeral 44 denotes an ID conversion table registering
10 unit for registering an ID conversion table for registering the corresponding relation between the user ID and the guest ID (which belongs to another schedule managing system). A numeral 11 denotes a LAN control unit for controlling communication between the server 10
15 and the PC 20 through the LAN 30. A numeral 90 denotes a network such as a public line, a private line, and a trunk LAN connected to two schedule management systems (100, 500). A numeral 16 denotes a gateway for controlling communication between the two schedule
20 managing systems through the network 90. A numeral 12 denotes a user ID management unit that is operated to reference the user ID table registering unit 43 for checking the user ID sent from the PC 20 and the guest ID sent from the other schedule management system and to
25 obtain an address of the PC from the user ID. A numeral 13 denotes a security check unit that determines if the access to the closed portion 412 of the schedule of the target user is permitted by referring to the security

table registering unit 42. A numeral 14 denotes a user data management unit that is operated to read schedule information of the user requested by the PCs (20, 60) and send the data permitted as a result of the determination of the security check unit 13 to the PC 20 or the other system 500 through the user ID management unit 12 or the gateway 16. A numeral 15 denotes an ID conversion unit for converting the user ID into the guest ID by referring to the ID conversion table 44. In Fig. 1, the network 90 is served to connect the schedule management system (100) shown in the left hand with the other schedule management system (500) shown in the right hand, each of which has the same functional configuration as each other. The server unit 10 is an information processing apparatus such as a PC or a workstation. The user ID management unit 3, the security check unit 4, the user data management unit 5, the ID conversion unit 6 and the like are realized by executing a program stored in a storage unit (not shown) of this information processing apparatus.

Fig. 2 shows an example of a data format of the ID conversion tables (44, 84). The ID conversion table (44 or 84) has a corresponding relation set between the user ID and the guest ID. The user ID is a user identifier registered in the user ID table registering unit 43 included in the client-server system (for example, 100) to which the user belongs. The guest

ID is a user identifier registered as a user ID in the user ID table registering unit 84 included in the other client-server system (for example, 500). If one client-server system includes as a participant the user permitted to access the other client-server system, the guest ID is registered as a guest ID in the ID conversion table included in the latter client-server system. If one client-server system does not include the user permitted to access the other client-server system, the guest ID is not registered in the ID conversion table of the latter system. The guest ID may be used in duplicate. Hence, two or more users may use one guest ID.

Fig. 3 shows an example of a data format of the user ID table 430 registered in the user ID table registering unit 43. This table is used for registering the user(s) permitted to access the user data registering unit 41. The table contains the identifiers of the users belonging to the managing range of the schedule management system. Each entry is composed of a user ID 431, a security rank 432 and attribute information 433 of a user. The security rank 432 indicates a rank or a level of the security. In this example, the entry having the user ID 431 of "B001" and "B002" indicates the registration of the guest ID as the user ID.

Fig. 4 shows an example of a data format of the security table 420 registered in the security table registering unit 42. The security table 420 indicates an access right to the closed portion of the schedule

for each security rank 432. An alphabet on an abscissa axis indicates a security rank of a user to be accessed, while an alphabet on an ordinate axis indicates a security rank of a user who wants to access the user data. In the access right, a value of "1" indicates access enabled, while a value of "0" indicates access disabled. In this table, assuming that the top rank is A and the rank goes down one by one from A to Z, this table is an example of a common security management, in which if (the security rank of the user who wants to access the data) $\geq$ (the security rank of the user to be accessed), the user who wants to access the data is always permitted to access the data, while if not, he or she is not permitted to access the data. In actual, this data format does not need the table, because the access right can be obtained by comparing the security rank of both of the users with each other. However, if the access right is obtained from the security ranks of the user who wants to access the data and the other user to be accessed in a complicated manner, the security table 420 is necessary.

Fig. 5 shows an example of a data format of the user data 410. The user data 410 stores the schedules of the users as the user data of two or more users. The user ID 431 is an ID number indicating an owner of the user data to be accessed. In the schedule information of each user, the open portion 411 is a portion to be accessed by any user irrespective of the

access right. Concretely, the open portion 411 corresponds to a day and a time portion of the schedule. In particular, the open portion 411 indicates to any user only a free time on the schedule of the user to be
5 accessed. The closed portion 412 indicates the data to only the user who has an access right and contains private information or information about a trade secret such as a destination of a business trip and an important matter on business.

10 Herein, the description will be oriented to the actual procedure for accessing the schedule data.

 At first, the description will be oriented to the procedure about how the user of the PC 20 served as a client unit of the client-server system 100 makes
15 access to a schedule of the user registered in the system 100 itself.

 The user of the PC 20 (User ID: C003) issues a request for accessing the schedule data included in his or her own system to the LAN control unit 11 of the
20 server unit 10 through the LAN 30 by transmitting the data for specifying the user ID of his or her own and the user to be accessed (such as an employee number, a name or a user ID of his or her own). The user ID management unit 12 is operated to check if the received
25 user ID is the data of the user managed by the client-server system to which the management unit 12 belongs by referring to the user ID management unit 12. In this case, the user ID indicates a user registered in that

client-server system. Hence, the security rank (B) for the user ID is read from the server unit, and the data for specifying the ID of the user who wants to access the data, the corresponding security rank and the user
5 to be accessed are passed to the security check unit 13. Then, the security check unit 13 operates to determine if the access to the closed portion 412 of the requested schedule is permitted by referring to the security table registering unit 42 and then pass the determined result
10 to the user data registering unit 14. The user data managing unit 14 operates to access the user data registering unit 41 for reading the schedule data of the user to be requested to be accessed and transmitting the permitted portion to the PC 20 through the user ID
15 management unit 12, the LAN control unit 11, and the LAN 30.

In turn, the description will be oriented to the procedure about how a user of one schedule management system issues a request for access to a user of the
20 other schedule management system.

Fig. 6 shows this procedure and a flow of process from when the PC (20) issues a request for accessing a schedule of another user to when the PC (20) obtains the requested schedule information. The PC (20)
25 operates to issue to a server unit (10) a request for accessing a schedule with a user ID for issuing a request and the other user ID to be accessed of the other system (step 31). The user ID management unit 12

receives this request through the LAN 30 and the LAN control unit 11 (step 32), and stores the correspondence between the requested user ID and the physical address of the PC 20. Next, the user ID management unit 5 12 operates to check the ID of the user for giving an accessing request by referring to the user ID table 43 (step 33) and then pass the control to the ID conversion unit 15 if the user to be accessed belongs to the different system from the system of the user who wants 10 to access the data. The ID conversion unit 15 operates to convert the user ID into the guest ID by referring to the ID conversion table (44) (step 34) and transfer a request for access to the server unit 50 of the different client-server system 500 through the gateway 15 16 and the network 90 (step 35). If the user ID is not registered in the ID registration table 44, the ID conversion unit 15 rejects the request for access. The request for access contains a guest ID, a user ID and a user ID of a user to be accessed. The user ID management 20 unit 52 of the server unit 50 receives the request for access (step 36) and checks if the guest ID and the user ID 431 of the user to be accessed are registered in a user ID table registration unit 83 (step 37). If both of the IDs are not registered in the unit 83, the user 25 ID management unit 52 rejects the request for access. The user ID management unit 52 rejects the request for access containing the guest ID without through the gateway 56. If both of the IDs are registered in the

registration unit 83, the user ID of the user for giving a request for access, its security rank 432, the user ID of the user to be accessed, and its security rank 432 are passed to the security check unit 53. The security
5 check unit 53 operates to obtain an access right for the user for giving a request for access by referring to the security table 82 (step 38) and pass the user ID of the user for giving a request for access, the user ID of the user to be accessed and the access right to the user
10 data management unit 54. The user data management unit 54 operates to retrieve the data stored in the user data registering unit 81 and read the user data registered under the user ID 431 of the user to be accessed (step 39). If the access right is enabled, the overall
15 schedule information is transferred to the server unit 10 through the gateway 56 and the network 90, while if the access right is disabled, only the open portion 411 of the schedule information is transferred to the server unit 10 (steps 40 and 41). This schedule information
20 contains the user IDs of the user for giving an access request and the user to be accessed. The user ID management unit 12 receives this schedule information (step 42) and obtains a physical address of the PC 20 from the user ID of the user for giving an access
25 request and transmits the schedule information to the PC 20 which issues an access request through the LAN control unit 11 and the LAN 30 (step 43). The PC 20 receives this schedule information (step 44) and

displays it on the display unit.

In the foregoing embodiment, when the PC (20) makes access to the server unit, the user ID of the requester is sent with the information for specifying the user to be accessed (such as an employee number, a name and a user ID). Instead, the user ID of the requester is sent to the server unit. Then, the state of the client-server system permitted to be accessed by the user ID is checked (Concretely, the indexes such as a name and an employee number about the user data permitted to be accessed are output to the client unit.) Next, the information for specifying the user to be accessed may be input to the server unit.

Further, in the foregoing embodiment, the gateway (16, 56) is provided inside of the server unit (10, 50). In place, the gateway (16, 56) may be located independently of the server unit (10, 50). In place of the gateway (16, 56), another inter-network connecting unit such as a router may be selected according to the type of the network 90. Or, a simple communication control mechanism of the network may be utilized.

Moreover, in the foregoing embodiment, the user ID of the requester is transferred from the server unit 10 to the server unit 50 and then returns to the server unit 10. This is an ID for taking correspondence with the PC 20. In place of the user ID, it may be replaced with a transaction ID numbered by the user ID management unit 12. The content of the user data 431 is not limited to

the information about the schedule of the user. It may be any data. The user data 431 is divided into the open portion 411 and the closed portion 412. In actual, all of the user data 431 may be the open portion. In this
5 case, the security rank 432, the security table 420 and the security check unit 13 are not necessary. On the contrary, all of the user data may be the closed portion.

In the foregoing embodiment, one schedule
10 management system is configured of just one server unit. In place, it may employ a multi-server system and therefore be configured of two or more server units. The schedule management system configured as described above has two or more server units connected through one
15 LAN, one of which server units has a gateway and the others of which server units do not have gateways. The content of the user ID table 430 is the same in any server unit included in the system. Each server unit takes the responsibility of the corresponding user
20 group. The flow of process of the multi-server type schedule management system is the same as the flow of process shown in Fig. 6 from the steps 31 to 36. At a step 37, it is checked if the guest ID and the user ID 431 of the user to be accessed are registered by
25 referring to the user ID table 430. If both of the IDs are registered, it is determined if the user ID of the user to be accessed belongs to the user group to be processed by the server unit. If the request for

accessing the schedule may be processed by the server unit, the flow of process from the subsequent steps 38 to 44 is the same as the flow of process shown in Fig. 6. If the user ID of the user to be accessed belongs to a user group to be processed by another server unit included in the same information management system, the user ID and its security rank are sent to that server through the LAN control unit and the LAN. Then, this server is operated to perform the process from the steps 38 to 40 and then send the schedule information to the server 1-2. The server unit operates to just relay the schedule information and then send it to the server unit through the gateway. The flow of process from the subsequent steps 42 to 44 is the same as the flow of process shown in Fig. 6. As mentioned above, the multi-server type information management system enables to distribute the user data 410 and the processing load to two or more server units.

As set forth above, according to the present invention, the user who passes the checking gates of the user ID and the guest ID can make access to all the user data belonging to the other system. Further, the system provides a capability of fine controlling the access right to the closed portion of the user data according to the security ranks of the user to be accessed and the user for giving an access request.



WHAT IS CLAIMED IS:

1. A method for accessing information in an overall system having two or more client-server systems connected through communication means, each of said client-server systems having at least one server unit and at least one client unit connected to said server unit, and said server unit holding information of said client unit, comprising the steps of:

storing data of each user in the client-server system to which said user belongs in a separate manner to each user;

registering a user ID in each client-server system so that a user of said client unit included in the subject client-server system can make access to the data of the client unit included in the same client-server system;

if a user included in the client-server system is permitted to access information included in the other client-server system, registering an ID permitted to access the data of the client unit included in the other client-server system as a guest ID in a manner to correspond to a user ID of the client-server system to which the user belongs; and

when a user in the system desires to access user data included in the other system, converting the input user ID into the guest ID and accessing the user data included in the other system.



2. An information accessing method as claimed in claim 1, wherein said user data includes an open portion to which all the users can access and a closed portion to which all the users cannot access.

3. An information accessing method as claimed in claim 1, wherein an index of the user data permitted to be accessed by said input user ID is output to the client unit in which said user inputs said user ID so that said user data is accessed by specifying a desired piece of said user data in said output index.

4. A method for accessing information taking the steps of storing user data in a separate manner to each user, registering an ID of a user permitted to access said user data as a user ID, specifying said registered user ID as a managing range in one client-server system, and accessing the user data of another user over two or more client-server systems, comprising the steps of:

converting a first user ID to which the managing range of the first client-server system belongs into a second user ID to which the managing range of the second system belongs; and

if both said second user ID and a third user ID corresponding to a user of said user data belong to the managing range of said second system, permitting said user to access said user data.

5. A method for accessing information taking the step of storing user data for each user, comprising the steps of:



specifying one of plural security ranks for users;

specifying a table for determining whether or not said user data is to be accessed from the security rank of the user who requests to access said user data and the security rank of the user whose data is accessed; and

determining whether or not access to said user data is permitted by referring to said table if the request for access is issued.

6. A method for accessing information as claimed in claim 5, wherein said user data includes a portion that is open to any other user and a portion that is not open to any other user and said non-open portion of said user data is permitted to be accessed by a specific user.




FIG.2

440 ID CONVERSION TABLE

USER ID	GUEST ID
A001	B001
A002	B001
A003	B001
A004	B001
A005	B002
A006	B002

FIG.3

430 USER ID TABLE

431 USER ID	432 SECURITY RANK	433 ATTRIBUTE OF ANOTHER USER
C001	A	BELONGING, POSITION AND THE LIKE OF USER
C002	A	BELONGING, POSITION AND THE LIKE OF USER
C003	B	BELONGING, POSITION AND THE LIKE OF USER
C004	C	BELONGING, POSITION AND THE LIKE OF USER
C005	C	BELONGING, POSITION AND THE LIKE OF USER
B001	C	GUEST
B002	D	GUEST

FIG.4

420 SECURITY TABLE

432

	A	C	D	E	F	G	H	I	J	...	T	U	V	W	X	Y	Z
A	1	1	1	1	1	1	1	1	1	...	1	1	1	1	1	1	1
B	0	1	1	1	1	1	1	1	1	...	1	1	1	1	1	1	1
C	0	0	1	1	1	1	1	1	1	...	1	1	1	1	1	1	1
D	0	0	0	1	1	1	1	1	1	...	1	1	1	1	1	1	1
E	0	0	0	0	1	1	1	1	1	...	1	1	1	1	1	1	1
F	0	0	0	0	0	1	1	1	1	...	1	1	1	1	1	1	1
				...						...				...			
S	0	0	0	0	0	0	0	0	0	...	1	1	1	1	1	1	1
T	0	0	0	0	0	0	0	0	0	...	1	1	1	1	1	1	1
U	0	0	0	0	0	0	0	0	0	...	0	1	1	1	1	1	1
V	0	0	0	0	0	0	0	0	0	...	0	0	1	1	1	1	1
W	0	0	0	0	0	0	0	0	0	...	0	0	0	1	1	1	1
X	0	0	0	0	0	0	0	0	0	...	0	0	0	0	1	1	1
Y	0	0	0	0	0	0	0	0	0	...	0	0	0	0	0	1	1
Z	0	0	0	0	0	0	0	0	0	...	0	0	0	0	0	0	1

432

FIG.5

410 USER DATA

C001		431	411	412		
OPEN PORTION		CLOSED PORTION				
7 / 7 / 95	10 : 30 TO 12 : 00	FIRST MEETING ROOM	ARRANGEMENT	DISTRIBUTION OF DATA ON THE DAY		
8 / 7 / 95	9 : 00 TO 10 : 00	THIRD CONFERENCE ROOM	RECEPTION OF GUEST	IMPORTANT CUSTOMER		
8 / 7 / 95	14 : 30 TO 15 : 45	SEMINOR ROOM	TRAINING	PROGRAM DEVELOPMENT		
9 / 7 / 95	15 : 10 TO 17 : 00	SYSTEM ROOM	SYSTEM CHECK	SST		
10 / 7 / 95	20 : 30 TO 21 : 50	RESTAURANT ON 2F	WELCOME PARTY	PERSON IN CHARGE		


C002		431	411	412		
OPEN PORTION		CLOSED PORTION				
3 / 7 / 95	14 : 00 TO 16 : 00	HALL ON 3F	INTRODUCTION OF PRODUCT	ARRANGED MANAGEMENT		
4 / 7 / 95	13 : 00 TO 19 : 40	SHOW ROOM	DEMONSTRATION	THREE SHIFT		
9 / 7 / 95	15 : 30 TO 15 : 45	OWN SEAT	DRILL OF ANNOUNCEMENT	CULTIVATION		
9 / 7 / 95	17 : 50 TO 21 : 00	POOL	SWIMMING	REFRESH		
13 / 7 / 95	10 : 30 TO 13 : 50	FIRST MEETING ROOM	PROMOTION FOR SALES	BRINGING BUSSINESS RESULTS		

PC 20

SERVER 10

SERVER 50

FIG. 6



ABSTRACT

METHOD FOR ACCESSING INFORMATION

An information accessing method permits the user data belonging to a client-server system to be accessed by a user belonging to the other client-server system under proper security and controls the permission for accessing the user data according to the security ranks of the user to be accessed and the user who wants to access the data. When a client unit issues a request for accessing the user data of the user belonging to the other client-server system, the request for access is sent to an ID conversion unit through a user ID management unit. The ID conversion unit operates to convert a user ID into a guest ID by referring to an ID conversion table and then send the request for access to a user ID management unit. The user ID management unit makes sure that the guest ID is registered by referring to the user ID table. Then, the request for access is sent to the user data management unit through security check units, so that the whole or the open portion of the user data specified on the user data is allowed to be accessed.

(Figure 1)

1-4521122