

IDENTIFICATION CARD VERIFICATION SYSTEM AND METHOD **BACKGROUND OF THE INVENTION**

Cross Reference to Related Application

This application is related to another U. S. Patent
5 Application, Serial No.08/395,547 entitled "Self-Verifying
Identification Card" (Kristol 2-12), with this application
being concurrently filed with the present application,
having the same inventors, and being incorporated herein
by reference.

10 **Field of the Invention**

This invention relates to an identification card
verification system, and in particular to one in which the
identification card carries an image which is scanned for
optical values which are compared to an image signature to
15 verify that there have been no alterations to the card.
The verification can be made at the point of transaction
or by reference to a central data base.

Description of Related Art

The use of identification cards is proliferating in
20 commercial transactions such as check cashing and credit
cards, security applications to gain access to premises,
licenses of various kinds, and passports, which may be
considered one of the first uses of an identification
card.

25 In structure, the cards usually contain a photograph
of a person. Recently additional features are sometimes
added such as a signature, fingerprint, or even the image
of the person's retina. Each of these is a characteristic
which is unique to each human being, and their addition
30 reflects attempts to mitigate the possibility of forged
identification cards. As greater reliance has been placed
upon these cards, their value to unauthorized users and to
unauthorized purveyors of false identification cards has
also increased significantly. Counterfeiters routinely

REPLACED SHEETS	SG
☐ Description : paged to paged	
☒ Claim(s) : paged to paged25	
☐ Drawing(s) : paged to paged	
☒ Abstract : paged24 to paged	
DATE OF RECEIPT	

obtain or make passport and driver license blanks and affix a photograph for a small fee.

With the increased number and variety of identification cards, automated methods of their manufacture have been developed. U.S. Pat. 4,999,065 to Wilfert describes a method of transferring a video image of a person, signature, or fingerprint into digital form, adding data from a keyboard, and laser printing the composite.

10 U.S. Pat. 5,157,424 to Craven et al. teaches a method to superimpose a signature over a portrait wherein the signature is scaled in size and printed in a tone which is reverse to that of the portrait. So the signature would appear white if applied over dark hair. This is an
15 example of a card which is harder to counterfeit.

U.S. Pat. 4,737,859 to VanDaele shows a bi-level recording device which produces a composite half-tone record in which images of different subjects remain visually distinguishable. Digital information from the
20 two images is fed into an EXOR gate which drives a print engine to produce a composite of a portrait and line work. This is quite similar to the previous patent.

U. S. Pat. 5,321,751 to Ray et al. describes a method and apparatus for credit card verification wherein a
25 picture accompanies an application for the card. The picture information is converted into a digital image which is stored centrally or at the point of a transaction. The digital image is also stored in a medium like a magnetic stripe used by many cards or into an
30 electronic storage system such as in "smart cards". At the point of sale the digital image of the presenter is converted to a video monitor display. The card administration agency also receives a verification request together with an identification code provided by the
35 presenter which selects an algorithm to translate the stored digital information into a video display. In this

invention the photograph is not on the card.

Accordingly, there is a need for an identification card verification system which accepts data from a broad variety of scanners. The system and the verification process also need to be robust, in that the verification should be insensitive to noise caused by imperfections or dust on the card. In particular, they should be resistant to any attempt at tampering or counterfeiting.

Summary of the Invention

10 The present invention relates to a self-verifying identification card system and its operation, and in particular to a system which carries information which is used to verify that there have been no alterations to the card. The verification can be made at the point of a transaction or by reference to a central data base.

15 The identification card contains an image area which typically contains the photographic portrait of a human being. However, other characteristics which are unique to that person may also be used, such as: a fingerprint, a signature, or an image of the person's retina, or any combination of these. The card also contains an image signature, which is prepared from optical values sampled from or about selected reference points within the image area. The values may be taken from gray scale, color, or they may be taken from a mathematical transformation, such as, a Fourier Transform. The card thus contains information on itself which indicates whether attempts have been made to substitute the image in the image area. For noise free and robust operation several optical values are determined in a cluster around each reference point and averaged. To accommodate the variations in commercial scanning devices which read the optical value, a functional relationship of the average optical value around a reference point to other optical values at reference points near the former one is used to create the

20
25
30
35

image signature which is provided on the card.

A registration feature may be designated on the identification card, described above, which provides information regarding the orientation of the card in the scanning device. The placement of the registration feature, or other indicia on the card, can also provide information regarding the selection of a mathematical translation function which may be used to translate the optical value information to an encoded format of the information on the card. The mathematical translation function may include: an encryption scheme, a one-way hash, a compression algorithm, or a truth table, used separately or in combination. These functions are well known in the art of computer science.

In one embodiment of the invention, a self-verifying identification card system employs a card with an image area and an image signature area, both being readable by means for scanning the information on the card, and a computer which is linked to the scanner which compares the optical value information on the presented card to the information recorded in the image signature and indicates whether these data match. The image signature is mathematically translated so that a counterfeiter cannot code a forged photograph since he does not have the secret key needed for translation. The computer may also be linked to a data base which exchanges information with the computer.

In another embodiment of the invention, a network links scanners and a computer to a data base which contains image signatures. Optical values from the identification card are read by a scanner, transmitted to the computer which calculates and image signature, and compares it to the image signature in the data base associated with the card. The image signature may be mathematically transformed, for security, as before.

In yet another embodiment, a self-verifying

identification card system is described wherein the image and a first image signature are scanned from the identification card. A computer is adapted to compare the first image signature to a second one which it computes
5 from optical values read from the card. The computer is also linked to a data base which contains a third image signature. A comparison of these image signatures is made and the results are transmitted to indicating means. The image signatures may be in a mathematically transformed
10 format, and the selection of the format may be determined from indicia on the card.

In still another embodiment of the invention, a method is described which employs the identification card defined above to verify the validity of the card. Digital
15 information, including optical values, reference features, and a first image signature is read by a scanner. A second image signature is computed from the optical values and compared to the first image signature. A successful match is indicated. Alphanumeric or bar code information
20 may also be read from the card and compared to the image signature.

In a further embodiment, an image signature is computed from optical values read from the image area of the card and a comparison is made to an image signature
25 stored in a data base. Alphanumeric or bar code information may also be read from the card and compared to the image signature.

In yet another embodiment, optical values and a first image signature are read from the identification card, a
30 second image signature is computed from the optical values, a comparison is made of these image signatures, and the presence of a match is indicated. A third image signature associated with the card is retrieved from a data base, and the first and third image signatures are
35 compared, and a match is indicated. Alphanumeric or bar code information may also be read from the card and

compared to the image signature. Attempts made to verify the card and transactions made after verification, may also be recorded.

- These and other features and advantages of the invention will be better understood with consideration of the following detailed description of the preferred embodiments taken in conjunction with the accompanying drawings.

Brief Description of the Drawings

- 10 FIG. 1A, is a front view of a self-verifying identification card;
- FIG. 1B shows a coordinate system for reference points within one area of the card;
- FIG. 1C shows a cluster of pixels which are sampled
15 around a reference point;
- FIG. 1D shows nearest neighbor reference points surrounding a reference point;
- FIG. 1E shows another embodiment of the identification card;
- 20 FIG. 2 is a block diagram of components for a self-verifying identification card system;
- FIG. 3 shows a network for verifying an identification card; and
- FIG. 4 shows a network utilizing a self-verifying
25 identification card.
- The drawings are not to scale.

Detailed Description of the Preferred Embodiments

- Referring now to FIG. 1A, there is shown apparatus 100 which is an identification card having an image area
30 30 occupying a portion of the card. Also provided on the card is an area 50 containing an image signature 51. The remaining area of the card may be used for alphanumeric text which describes the issuer, type, and purpose of the card, together with any state seal or corporate logo.

The image area typically contains a photographic portrait of a human being, but it could also contain a fingerprint, a signature, the image of the human's retina, or any combination of these. The image area is mathematically
5 divided into a matrix of reference points which are more clearly shown in FIG. 1B. The matrix is constructed with a series of parallel horizontal and vertical lines labeled 1, 2, etc. in each direction. The intersection of the first horizontal and first vertical line determining
10 reference point (1,1), and so on. To prepare the card, an image of a portrait, signature, fingerprint, or retinal image which is to be printed within the image area is scanned by devices which are well known in the art such as a Hewlet-Packard Scanjet or Logitech Scanner. These
15 devices can read both the optical values in the image area and the characters or bar code in the image signature. A typical scanning resolution is 300 dots per inch (dpi) which is also typical of laser printer output. Each of the 300 dots being defined as a pixel. The optical value
20 of whatever image is scanned is taken at each reference point, and commercial scanners provide gray scale or color values ranging from 0 to 250 in arbitrary units. To provide a more robust system which is less sensitive to noise which is created by dust or bubbles which can occur
25 on the card or by noise in the scanning device, an array of optical values about each reference point may be taken and the values averaged to represent the optical value at the reference point. One such scheme is shown in FIG. 1C, where a 5 X 5 array is selected about reference point
30 (2,2). Each of the dots being about 0.0033 inches in diameter for 300 dpi resolution. Reference point (2,2) may be separated from its nearest neighbors (1,2), (2,3), (3,2), and (2,1) by 0.1 inch or any other distance determined by the algorithm selecting the reference
35 points. The nearest neighbors are indicated in FIG. 1D.

To accommodate the different gain characteristics of

various printer models, experience has shown that a functional relationship describing the optical value at a reference point (or its average value as determined from an array such as shown in FIG. 1C) compared to other optical values in the image area, provides a value which is a more reliable and reproducible indicator of the optical value at the reference point. The functional relationship may be derived from any truth table which relates the optical value to others in the image area. It may also be the ratio of the value at a point to others in the image area. In a preferred embodiment, the optical value at a reference point is quantified into a three level function wherein optical values greater than, equal to, or less than surrounding optical values are ascribed values of "1", "0.5", or "0", respectively. The process is repeated for each reference point, and the series of values becomes the image signature which is imprinted on the card combined with any other information the card issuer wants. The information may further describe the cardholder and add items such as citizenship, corporate permission codes, health profiles, or financial details. This information may be in encrypted format anywhere on the card, but in a preferred embodiment it is placed within a specified area, such as area 50.

In FIG. 1E, registration features 40 may be used to determine the orientation, location, and scale of the card as it is inserted into a commercial scanner. They are shown as round dots approximately 0.1 inches in diameter which are easily recognized by the algorithm searching the digital information from the scanner. Preferably the alignment features are placed away from any axis of symmetry so that the orientation of the card is unmistakable. Other indicia 41 and 42 may also be added to the card and their length may indicate a different encryption scheme for each card, to add another level of security. The perimeter of the image area may also serve

as a registration feature to orient and scale the card, and any alphanumeric character on the card, such as a particular letter in a person's name may be used as an indicator of a particular encryption function.

5 The result is a card which is self-verifying because any tampering with the image in the image area cannot correspond to the image signature containing optical values of the original image. By using the average of optical values of a cluster of pixels around each
10 reference point, noise caused by dust or imperfections in the card or the scanner is reduced to provide a robust and reliable verification. By using a functional relationship to describe the optical value at one reference point compared with others in the image area, the card becomes
15 less sensitive to the characteristics of commercial scanners.

Referring now to FIG. 2, there is shown system 200 in accordance with another embodiment of the invention. Identification card 100, described above, is shown
20 partially inserted into scanning means 210. Commercial scanners operate by raster scanning every pixel on the card with resolutions that are adjustable from 100 dpi to 600 dpi. A resolution of 200 dpi to 300 dpi is preferred in this application. Scanning means 210 could also be a
25 scanner developed for this application wherein the whole card is not scanned at high resolution, but only areas around the reference points, the image signature, and the alignment features are scanned at high resolution under computer control. Preferential scanning, as described,
30 would enhance throughput.

The optical values are communicated to computing means 220 which contains an algorithm or a set of algorithms which operate on the optical value at each reference point in the image area of the card, the average
35 of a cluster of readings around the reference point, or the three-level function of the average optical value

around the reference point compared to the same values of nearby neighbors. Computing means 220 compares whatever optical value is associated with each reference point to the image signature read from the identification card. If
5 a match is determined, the card is verified and the computer sends a signal to indicating means 222, which may be a screen display, a simple light, or a tone. Similarly, a rejection signal is sent if no match is found.

10 Since the card is self-verifying, a standalone embodiment of the invention needs only an identification card with an image area and image signature, a scanner which reads the optical value of a gray scale or color image in at least one position in the image area and which
15 reads the information in the image signature, computing means which compares these data, and indicating means which report the result.

Clearly, one or more standalone embodiments may be linked to a network having additional computing means,
20 algorithms, and data bases which can perform the functions of verification, as above, or provide additional verification or more extensive functions relating to a transaction at the point of scanning. The distribution of these functions around the network may be optimized for
25 increased speed, lower cost, or to match preexisting functions, which is common to the design of local and wide-area network installations.

The verification process may be recorded in data base 230, and where a match is found further exchanges between
30 the data base and the computer are enabled. Computing means 220 may also have input means 224 which may enter details of a transaction such as a charge for a sale. Where the card is not verified, the existence of a defective card may also be recorded. Input means 224 may
35 be an input from a cash register, bar code reader or similar device, or a typical keyboard.

Referring now to FIG. 3, there is shown a network to verify an identification card. Identification card 302 comprises an image area 330 displaying a characteristic which is unique to each human being, such as, a portrait, a signature, a fingerprint, or a retinal image, used singularly or in combination, together with alphanumeric or bar code information which is also imprinted upon the identification card by the issuer which further describes characteristics such as height, weight, age, account number, and the like.

A series of scanning means 310 are adapted to read optical values and alphanumeric or bar code information from the identification card. These scanners may be commercial scanners such as a Hewlet-Packard Scanjet, or a Logitech Scanner, or they may be specifically developed for this application as described in the discussion of FIG. 2. Each scanner is linked via a network to computing means 320 which contains an algorithm which operates upon the optical values from the image area read by the scanner and compares these data to an image signature, associated with the identification card, which is stored in data base 330. The steps to create the image signature have been discussed in the description of FIG. 2 and are incorporated here. The image signature may also be in a mathematically translated format, also described before, and indicia on the card may also indicate the kind of translation which links optical values to the image signature. Computing means 320 sends a signal through the network to indicating means 322 which provides the result of the comparison. Indicating means 322 may be a screen, a light, or a tone generator.

Referring now to FIG. 4, there is shown a self-verifying identification card system which is in accordance with another embodiment of the invention. In this case, the identification card 100 has been prepared according to the description provided for FIG. 1A to FIG.

1E. A first image signature is on the card. A series of scanning means 310 are as described for FIG. 3. The scanners are linked to computing means 420 comprising input means 424 and indicating means 422. The computing means may be hard-wired or programmable and the input means may be keys, a bar code reader, or a cash register. Data base 430 contains a second image signature which is associated with the identification card and which was prepared from optical values associated with at least one reference point in the image area. Network 450, which may also contain additional computing means, provides bi-directional access to the data base and all the computing means 420. The computing means contain an algorithm which compares optical values determined by the scanning means to the first image signature on the card and the second image signature stored in the data base. The image area of the card may contain a portrait, a signature, a fingerprint or a retinal image, used singly or in combination. The image signature may be derived from average optical values around a reference point, and a function which may be a three-level function, a ratio, or one derived from a truth table as described before. The image signature may also be in a mathematically translated format, such as, a one-way hash function, an encryption scheme, a compression algorithm, or a truth table, used separately or in combination. These functions are well known in computer science. The selection of the format may be determined by indicia on the card for an added level of security.

30 The invention also includes a method of verifying an identification card which comprises an image area and a first image signature which is derived from optical values from within the image area. In this embodiment, the card is scanned to obtain digital information which is entered into computing means, which computes the digital information regarding the optical values at selected

reference points within the image area to get a second image signature which compared to digital information from the image signature. The discussion above regarding the preparation of the image signature and its mathematical translations is repeated here. Other steps in the verification process may include reading alphanumeric or bar code information from the identification card, comparing this to information within the image signature, and indicating whether these data match.

10 Another embodiment of the invention is a method of verifying an identification card comprising an image area having an image of a human characteristic, one or more reference points within the image area, and at least one registration feature which is adapted to determine the
15 orientation and scale of the identification card, where the steps are: scanning the identification card to obtain digital information, computing a first image signature from an optical value associated with each reference point, comparing the first image signature to a second
20 image signature which is stored in a data base, and indicating whether the first image signature matches the second image signature. Additional steps may include reading alphanumeric information from the identification card, comparing this information to information stored
25 within the data base, and, indicating whether the alphanumeric information read from the card matches information from within the data base. The creation of the image signature and the functions which may mathematically transform it have been described and are
30 incorporated here.

A further embodiment is a method of verifying an identification card comprising an image area having an image of a human characteristic, one or more reference points within the image area, at least one registration
35 feature which is adapted to determine the orientation and scale of the identification card, and a first image

signature derived from optical values associated with each reference point. The steps include: scanning the identification card to obtain digital information, computing a second image signature from the digital
5 information associated with at least one optical value about at least one reference point, comparing the computed second image signature to the first image signature which was scanned from the identification card, indicating whether the first image signature matches the second image
10 signature, retrieving a third image signature associated with the identification card from a data base, comparing the first image signature to the third image signature, and indicating whether the first image signature matches the third image signature. Additional steps may include
15 reading alphanumeric information from the identification card, comparing this information to information stored within the data base, and, indicating whether the alphanumeric information read from the card matches information from within the data base. The creation of
20 the image signature and the functions which may mathematically transform it have been described and are incorporated here.

Further steps may include recording information regarding attempts to verify the information card and
25 recording transactions made after the identification card is verified.

The previously described embodiments of the invention provide advantages including methods and networks wherein an identification card is accepted by a broad variety of
30 scanners and one which is compatible with a many picture based identification cards as they are renewed. The card and the verification process are insensitive to noise. The various functions which create the image signature and the mathematical transformations through which the image
35 signature is recorded make the network and process resistant to tampering or counterfeiting.

Changes and modifications in the specifically described embodiments can be carried out without departing from the scope of the invention. In particular, the number and location of the reference points within the
5 image area can be varied without departing from the spirit of the invention and the number of pixels used in determining an average optical value around each reference point can be varied. The placement of data storage and computing means around the network may be varied to
10 optimize the parameters of the network.



CLAIMS:

1. A self-verifying identification card system comprising:

an identification card having an image area and an
5 image signature;

means for scanning the identification card adapted to detect the optical values associated with at least one reference point in the image area and to read the information provided by the image signature; and

10 means for computing, containing an algorithm and linked to the scanning means, being adapted to compare optical values determined by the scanning means from the image area to information from the image signature on the card and to indicate the result of the comparison.

15 2. The identification card of claim 1 wherein the image area contains an image of a characteristic which is unique to each human being.

3. The identification card of claim 1 wherein the image signature is derived from an optical value
20 associated with at least one reference point within the image area.

4. The self-verifying identification card of claim 3 wherein the average of a group of optical values at points located near a reference point defines the optical
25 value at that reference point which is used to derive the image signature.

5. The self-verifying identification card of claim 4 wherein the image signature is derived from a function relating the optical value at a reference point to other
30 optical values within the image area.

6. The self-verifying identification card of claim

This Sheet Has Been Replaced





4 wherein the image signature is in a mathematically transformed format upon the identification card.

7. The self-verifying identification card of claim 5 wherein the function is a three-level function.

5 8. The self-verifying identification card of claim 5 wherein the function is a ratio.

9. The self-verifying identification card of claim 5 wherein the function is derived from a truth table.

10 10. The self-verifying identification card of claim 6 wherein mathematical transformation function is determined from indicia on the card.

15 11. The self-verifying identification card of claim 1 further comprising means for indicating the result of the comparison of the image signature to optical values from the image area.

12. The self-verifying identification card of claim 1 further comprising a registration feature which is an edge of the image area.

20 13. The self-verifying identification card of claim 1 wherein the image signature comprises optical values from the image area and data selected by the issuer of the card.

25 14. The self-verifying identification card of claim 1 further comprising a data base adapted to exchange information with one or more computing means.

15. An identification card verification system comprising:





an identification card having an image area comprising a portrait of a human being, one or more reference points within the image area, and at least one registration feature which is adapted to determine the orientation, location, and scale of the identification card;

an image signature which contains information derived from optical values associated with each reference point, one or more means for scanning the identification card adapted to detect the optical values associated with at least one reference point in the image area;

one or more means for computing, containing an algorithm and linked to the scanning means, being adapted to compare optical values determined by the scanning means from the image area on the card to information from the image signature;

a data base adapted to store the image signature and exchange information with one or more computing means; and means for indicating the result of the comparison; whereby the scanning means feeds data into the computing means, which provides an indication as to whether optical value data match the image signature to the indicating means.

16. The identification card verification system of claim 15 wherein the image area contains a fingerprint.

17. The identification card verification system of claim 15 wherein the image area contains a signature.

18. The identification card verification system of claim 15 wherein the image area contains a retinal image.

19. The identification card verification system of claim 15 wherein the wherein the average of a group of optical values at points located near a reference point





defines the optical value at that reference point which is used to derive the image signature.

20. The identification card verification system of claim 15 wherein the image signature is derived from a function relating the optical value at a reference point to other optical values within the image area.

21. The identification card verification system of claim 20 wherein the function is a three-level function.

22. The identification card verification system of claim 20 wherein the function is a ratio.

23. The identification card verification system of claim 20 wherein the function is derived from a truth table.

24. The identification card verification system of claim 19 wherein the image signature is in a mathematically translated format.

25. The identification card verification system of claim 24 wherein the mathematically translated format is determined from indicia on the card.

26. A self-verifying identification card system comprising:

an identification card having an image area comprising a portrait of a human being, one or more reference points within the image area, and at least one registration feature which is adapted to determine the orientation, location and scale of the identification card, and a first image signature which contains information derived from optical values associated with each reference point,





one or more means for scanning the identification card adapted to detect the optical values associated with at least one reference point in the image area and to read the first image signature;

- 5 a data base containing a second image signature derived from optical values associated with at least one reference point in the image area, being adapted to exchange information with one or more computing means;

- 10 one or more means for computing, containing an algorithm and linked to the scanning means, being adapted to compare optical values determined by the scanning means from the image area on the card to information from the first image signature and to compare said optical values to the second image signature; and

- 15 means for indicating the result of the comparisons; whereby the scanning means feeds data into the computing means, which provides an indication as to whether optical value data match the information in first image signature, and whether optical value data match the
20 information in the second image signature.

27. The self-verifying identification card system of claim 26 wherein the image area contains a fingerprint.

28. The self-verifying identification card system of claim 26 wherein the image area contains a signature.

- 25 29. The self-verifying identification card system of claim 26 wherein the image area contains a retinal image.

- 30 30. The self-verifying identification card system of claim 26 wherein the wherein the average of a group of optical values at points located near a reference point
30 defines the optical value at that reference point which is used to derive the image signature.

This Sheet Has Been Replaced





31. The self-verifying identification card system of claim 26 wherein the image signature is derived from a function relating the optical value at a reference point to other optical values within the image area.

5 32. The self-verifying identification card system of claim 31 wherein the function is a three-level function.

33. The self-verifying identification card system of claim 31 wherein the function is a ratio.

10 34. The self-verifying identification card system of claim 31 wherein the function is derived from a truth table.

35. The self-verifying identification card system of claim 30 wherein the image signature is in a mathematically translated format.

15 36. The self-verifying identification card system of claim 35 wherein the mathematically translated format is determined from indicia on the card.

20 37. A method of verifying an identification card comprising an image area having an image of a human characteristic, one or more reference points within the image area, at least one registration feature which is adapted to determine the orientation, location and scale of the identification card, and a first image signature which is derived from optical values associated with a reference point, the steps comprising:

scanning the identification card for obtaining digital information;

25 computing a second image signature from the digital information associated with at least one optical value about at least one reference point;





comparing the computed second image signature to the first image signature which was scanned from the identification card; and

indicating whether the first image signature matches
5 the second image signature.

38. The method of claim 37 wherein the image signature is derived from the average of a group of optical values around a reference point.

39. The method of claim 37 wherein the image
10 signature is derived from a function relating the optical value at a reference point to other optical values within the image area.

40. The method of claim 39 wherein the function is a three-level function.

15 41. The method of claim 39 wherein the function is a ratio.

42. The method of claim 39 wherein the function is derived from a truth table.

43. The method of claim 37 further comprising the
20 steps of:

reading alphanumeric information from the identification card;

comparing said information to information within the image signature; and

25 indicating whether the alphanumeric information read from the card matches information from within the image signature.

44. A method of verifying an identification card comprising an image area having an image of a human





characteristic, one or more reference points within the image area, and at least one registration feature which is adapted to determine the orientation, location and scale of the identification card, the steps comprising:

- 5 scanning the identification card for obtaining digital information;
 computing a first image signature from an optical value associated with each reference point;
 comparing the first image signature to a second image
10 signature which is stored in a data base; and
 indicating whether the first image signature matches the second image signature.

45. The method of claim 44 further comprising the steps of:

- 15 reading alphanumeric information from the identification card;
 comparing said information to information stored within the data base; and
 indicating whether the alphanumeric information read
20 from the card matches information from within the data base.

46. The method of claim 44 wherein an image signature is derived from the average of a group of optical values around a reference point.

- 25 47. The method of claim 44 wherein the image signature is derived from a function relating the optical value at a reference point to other optical values within the image area.

48. The method of claim 47 wherein the function is a
30 three-level function.

49. The method of claim 47 wherein the function is a

This Sheet Has Been Replaced





ratio.

50. A method of verifying an identification card comprising an image area having an image of a human characteristic, one or more reference points within the image area, at least one registration feature which is adapted to determine the orientation, location and scale of the identification card, and a first image signature derived from optical values associated with each reference point, the steps comprising:
- 10 scanning the identification card for obtaining digital information;
computing a second image signature from the digital information associated with at least one optical value about at least one reference point;
 - 15 comparing the computed second image signature to the first image signature which was scanned from the identification card;
indicating whether the first image signature matches the second image signature;
 - 20 retrieving a third image signature associated with the identification card from a data base;
comparing the first image signature to the third image signature; and
indicating whether the first image signature matches
25 the third image signature.

51. The method of claim 50 wherein the image signatures are derived from the average of a group of optical values around a reference point.

52. The method of claim 50 wherein the image
30 signature is derived from a function relating the optical value at a reference point to other optical values within the image area.





53. The method of claim 52 wherein the function is a three-level function.

54. The method of claim 52 wherein the function is a ratio.

5 55. The method of claim 52 wherein the function is derived from a truth table.

56. The method of claim 50 further comprising the steps of:

reading alphanumeric information from the
10 identification card;
comparing said information to information within the first image signature;
comparing said information to a third image signature stored in a data base; and
15 indicating whether the alphanumeric information read from the card matches information from within the first image signature and within the third image signature.

57. The method of claim 50 further comprising recording information regarding attempts to verify the
20 information card.

58. The method of claim 50 further comprising recording transactions made after the identification card is verified.

