

CLAIMS

1. A communication method, comprising:
 - generating, by a terminal device, terminal capability information, the terminal capability information indicating a terminal capability of the terminal device under the condition that a first parameter is configured and/or a support capability of the terminal device for a second parameter; and
 - sending, by the terminal device, the terminal capability information to a network device.
2. The communication method of claim 1, wherein the first parameter comprises at least one of first basic parameter sets or first carrier bandwidths, and/or the second parameter comprises at least one of second basic parameter sets or second carrier bandwidths.
3. The communication method of claim 2, wherein the second basic parameter sets comprise M basic parameter sets, the terminal capability information comprises first information for indicating a support capability of the terminal device for each set of the M basic parameter sets, where $M \geq 1$.
4. The communication method of claim 2 or 3, wherein the second carrier bandwidths comprise N carrier bandwidths, the terminal capability information comprises second information for indicating a support capability of the terminal device for each of the N carrier bandwidths, where $N \geq 1$.
5. The communication method of any one of claims 2-4, wherein the terminal capability information comprises third information for indicating a support capability of the terminal device for a second parameter combination and the second parameter combination comprises the second basic parameter set and the second carrier bandwidth.
6. The communication method of any one of claims 2-5, wherein the terminal capability information comprises fourth information for indicating a terminal capability of the

terminal device under the condition that a first parameter combination is configured and the first parameter combination comprises the first basic parameter set and the first carrier bandwidth.

7. The communication method according to any one of claims 1-6, wherein sending, by the terminal device, the terminal capability information to the network device comprises:

sending, by the terminal device, the terminal capability information through Radio Resource Control (RRC) signaling.

8. A communication method, comprising:

sending, by a network device, an indication message to a terminal device, the indication message indicating the terminal device to send terminal capability information, the terminal capability information indicating a terminal capability of the terminal device under the condition that a first parameter is configured and/or a support capability of the terminal device for a second parameter; and

receiving, by the network device, terminal capability information from the terminal device.

9. The communication method of claim 8, wherein the first parameter comprises at least one of first basic parameter sets or first carrier bandwidths, and/or the second parameter comprises at least one of second basic parameter sets or second carrier bandwidths.

10. The communication method of claim 9, wherein the second basic parameter sets comprise M basic parameter sets, the indication message comprises first indication information for indicating the terminal device to send a support capability for each set of the M basic parameter sets, where $M \geq 1$.

11. The communication method of claim 9 or 10, wherein the second carrier bandwidths comprise N carrier bandwidths, the indication message comprises second indication information for indicating the terminal device to send a support capability

for each of the N carrier bandwidths, where $N \geq 1$.

12. The communication method of any one of claims 9-11, wherein the indication message comprises third indication information for indicating the terminal device to send a support capability for a second parameter combination and the second parameter combination comprises the second basic parameter set and the second carrier bandwidth.

13. The communication method of any one of claims 9-12, wherein the indication message comprises fourth indication information for indicating the terminal device to send a terminal capability of the terminal device under the condition that a first parameter combination is configured and the first parameter combination comprises the first basic parameter set and the first carrier bandwidth.

14. The communication method according to any one of claims 8-13, wherein receiving, by the network device, the terminal capability information from the terminal device comprises:

receiving, by the network device, the terminal capability information through Radio Resource Control (RRC) signaling.

15. A terminal device, comprising:

a generation module, configured to generate terminal capability information, the terminal capability information indicating a terminal capability of the terminal device under the condition that a first parameter is configured and/or a support capability of the terminal device for a second parameter; and

a sending module, configured to send the terminal capability information to a network device.

16. The terminal device of claim 15, wherein the first parameter comprises at least one of first basic parameter sets or first carrier bandwidths, and/or the second parameter comprises at least one of second basic parameter sets or second carrier bandwidths.

17. The terminal device of claim 16, wherein the second basic parameter sets comprise

M basic parameter sets, the terminal capability information comprises first information for indicating a support capability of the terminal device for each set of the M basic parameter sets, where $M \geq 1$.

18. The terminal device of claim 16 or 17, wherein the second carrier bandwidths comprise N carrier bandwidths, the terminal capability information comprises second information for indicating a support capability of the terminal device for each of the N carrier bandwidths, where $N \geq 1$.

19. The terminal device of any one of claims 16-18, wherein the terminal capability information comprises third information for indicating a support capability of the terminal device for a second parameter combination and the second parameter combination comprises the second basic parameter set and the second carrier bandwidth.

20. The terminal device of any one of claims 16-19, wherein the terminal capability information comprises fourth information for indicating a terminal capability of the terminal device under the condition that a first parameter combination is configured and the first parameter combination comprises the first basic parameter set and the first carrier bandwidth.