



- (51) International Patent Classification: Not classified
- (21) International Application Number:
PCT/GB2012/052460
- (22) International Filing Date:
4 October 2012 (04.10.2012)
- (25) Filing Language: English
- (26) Publication Language: English
- (30) Priority Data:
1117049.5 4 October 2011 (04.10.2011) GB
- (71) Applicant: **ECOLOK LIMITED** [GB/GB]; Larchwood,
Murlaggan, Roy Bridge Inverness-shire PH31 4AP (GB).
- (72) Inventor: **WALMSLEY, Owen**; Larchwood, Murlaggan,
Roy Bridge Inverness-shire PH31 4AP (GB).
- (74) Agent: **MURGITROYD & COMPANY**; Scotland House,
165-169 Scotland Street, Glasgow Strathclyde G5 8PL
(GB).
- (81) Designated States (*unless otherwise indicated, for every
kind of national protection available*): AE, AG, AL, AM,
AO, AT, AU, AZ, BA, BB, BG, BH, BN, BR, BW, BY,

BZ, CA, CH, CL, CN, CO, CR, CU, CZ, DE, DK, DM,
DO, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT,
HN, HR, HU, ID, IL, IN, IS, JP, KE, KG, KM, KN, KP,
KR, KZ, LA, LC, LK, LR, LS, LT, LU, LY, MA, MD,
ME, MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI,
NO, NZ, OM, PA, PE, PG, PH, PL, PT, QA, RO, RS, RU,
RW, SC, SD, SE, SG, SK, SL, SM, ST, SV, SY, TH, TJ,
TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, ZA,
ZM, ZW.

- (84) Designated States (*unless otherwise indicated, for every
kind of regional protection available*): ARIPO (BW, GH,
GM, KE, LR, LS, MW, MZ, NA, RW, SD, SL, SZ, TZ,
UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, RU, TJ,
TM), European (AL, AT, BE, BG, CH, CY, CZ, DE, DK,
EE, ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT, LU, LV,
MC, MK, MT, NL, NO, PL, PT, RO, RS, SE, SI, SK, SM,
TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW,
ML, MR, NE, SN, TD, TG).

Published:

— without international search report and to be republished
upon receipt of that report (Rule 48.2(g))

(54) Title: METHOD & APPARATUS FOR GRIPPING




FIG. 7

(57) Abstract: A method and apparatus for gripping, especially a method and apparatus for gripping elongate pieces, such as pipes, bars, beams, etc., are disclosed. The apparatus comprises a body, the body having an inner cavity for receiving a piece to be gripped, the inner cavity having a sidewall, a recess provided around at least a portion of the sidewall, a clamping member disposed within the recess, wherein the recess is adjustable from a first dimension, where the clamping member is located substantially within the recess, to a second dimension where the clamping member is urged out of the recess and into the inner cavity. The gripping method comprises the steps of locating a clamping member around a piece to be gripped, locating two clamping shoulders such that they flank the clamping member, compressing the clamping member by urging the clamping shoulders together, the clamping member being arranged such that axial compression of it translates to radial compression.

