

PROCESSES FOR THE PREPARATION OF 2,5-FURANDICARBOXYLIC ACID AND INTERMEDIATES AND DERIVATIVES THEREOF

CROSS-REFERENCE TO RELATED APPLICATIONS

This application claims the benefit of priority to U.S. Provisional Application No. 62/278,332, filed January 13, 2016, which is hereby expressly incorporated by reference in its entirety.

FIELD

The present disclosure relates to novel processes for preparing 2,5-furandicarboxylic acid pathway products, as well as related esters, amides, polymers, and compositions thereof.

BACKGROUND

Low cost, renewably-derived 2,5-furandicarboxylic acid (FDCA) and its derivatives harbor considerable potential for commercial applications. *See, e.g.*, "Top Value Added Chemicals from Biomass," Volume I – Results of Screening for Potential Candidates from Sugars and Synthesis Gas, produced by Staff at Pacific Northwest National Laboratory (PNNL), National Renewable Energy Laboratory (NREL), Office of Biomass Program (EERE); Eds. T. Werpy and G. Petersen (2003). In certain applications, they have the potential to displace aromatic dicarboxylic acids such as terephthalic and isophthalic acid. A. Corma, et al., *Chem. Rev.*, 107:2411 (2007). FDCA and its derivatives are also useful in the production of other commodity chemicals. *Id.* For example, FDCA may be hydrogenated to adipic acid, which is utilized in the production of nylon. *Id.* Aromatic dicarboxylic acids are used for the production of polyesters and polyamides in the scale of tens of millions of tons per year. *See, e.g.*, "Modern Polyesters: Chemistry and Technology of Polyesters and Copolyesters," Eds. J. Scheirs and T. Long; Wiley (2013).

Methods of producing FDCA have been reported in the literature. For example, Corma, et al., report that FDCA can be produced by direct oxidation of 5-hydroxymethylfurfural (HMF) with nitric acid, though with low selectivity and yield. A. Corma, et al., *supra*. Verdeguer, et al. describe another process in which HMF is oxidized catalytically to FDCA using 5% Pt supported on carbon in the presence of sodium or potassium hydroxides with yields reported to be 70%. *J. Mol. Catal.* 85:327 (1993). They

reported achieving FDCA yields of up to 80% using a 5% Pt/5% Pb catalyst formulation on carbon in the presence of 1.25 M base solution. *Id.* When the amount of base was reduced to a concentration of 0.1 M, the authors reported that no conversion of HMF to FDCA was achieved, suggesting high concentrations of base are an important requirement for achieving higher FDCA yields. *See Id.* In another reported method, Besson, et al., report that Pt/Bi catalysts supported on carbon can produce FDCA with close to 100% selectivity under reaction conditions of a high base (Na_2CO_3) to HMF ratio of 2 to 4. *See* WO 2014/122319. An ancillary result of adding a base (e.g., NaOH, KOH, Na_2CO_3) to the reaction is the formation of salts (e.g., sodium or potassium salts) of FDCA. The formation of FDCA salts may be advantageous given that FDCA salts are reported to be more water-soluble than FDCA itself, thereby affording the potential opportunity to carry out the conversion process at higher HMF concentrations. *Id.* However, a disadvantage of such salt production is the need for further processing (e.g., further separation and/or conversion of the salt form of FDCA to FDCA) in the recovery of FDCA.

U.S. Patent No. 8,338,626 describes the production of FDCA and its esters by oxidation of mono- or dialkoxymethylfurfural in the presence of a homogeneous catalytic system that is similar to the system used in terephthalic acid production (Co/Mn/Br). The patent reports a maximum total yield of furandicarboxylics (with FDCA as a major constituent) of 82%. *Id.* U.S. Pat. No. 7,700,788 describes a method of HMF oxidation to FDCA under high oxygen (air) pressure using a 5% Pt/ ZrO_2 catalyst, prepared by a specific procedure from Pt acetylacetonate. In this process, HMF at a concentration of three weight percent, in the presence of base, and oxygen at a pressure of 150 psi resulted in the production of FDCA at a yield of 90%.

U.S. Pat. No. 4,977,283 describes the oxidation of HMF at concentrations around 10% in a base-free solution of water and diethylene glycol dimethyl ether in the presence of a Pt (5%) on activated carbon catalyst. The process provided only low yields (8%) of FDCA with the major product being 5-formylfuran-2-carboxylic acid.

In view of its potential as a biorenewable-derived replacement for petroleum-derived compounds that are used in the production of plastics and other materials, a commercially viable process for the production of large volumes of FDCA at high yields would be desirable.

SUMMARY

In one aspect, the present disclosure is directed to a process for producing a 2,5-furandicarboxylic acid (FDCA) pathway product from a furanic oxidation substrate, the process comprising:

5 (a) contacting an oxidation feedstock comprising a furanic oxidation substrate and an oxidation solvent with oxygen in the presence of a heterogeneous oxidation catalyst under conditions sufficient to form a reaction mixture for oxidizing the furanic oxidation substrate to an FDCA pathway product, and producing the FDCA pathway product,

wherein the oxidation solvent is a solvent selected from the group consisting of an
10 organic solvent and a multi-component solvent,

wherein the reaction mixture is substantially free of added base,

wherein the heterogeneous oxidation catalyst comprises a solid support and a noble metal, and

wherein the heterogeneous oxidation catalyst comprises a plurality of pores and a
15 specific surface area in the range of from 20 m²/g to 500 m²/g. The noble metal can be platinum, gold, or a combination thereof. The oxidation solvent can be a multi-component solvent comprising water and a water-miscible aprotic organic solvent.

The water-miscible organic solvent can be a water-miscible aprotic organic solvent.

The water-miscible aprotic organic solvent can be selected from the group consisting of
20 tetrahydrofuran, a glyme, dioxane, a dioxolane, dimethylformamide, dimethylsulfoxide, sulfolane, acetone, *N*-methyl-2-pyrrolidone ("NMP"), methyl ethyl ketone ("MEK"), and gamma-valerolactone. The glyme can be selected from the group consisting of a monoglyme (1,2-dimethoxyethane), ethyl glyme, diglyme (diethylene glycol dimethyl ether), ethyl diglyme, triglyme, butyl diglyme, tetraglyme, and a polyglyme. The water-miscible organic
25 solvent can be selected from the group consisting of a light water-miscible organic solvent and a heavy water-miscible organic solvent. The water and the water-miscible organic solvent can be present in a ratio of from or any number in between 1:6 to 6:1 v/v water:water-miscible organic solvent. The water and the water-miscible organic solvent can be present in a ratio of 1:1 v/v water:water-miscible organic solvent. The water-miscible
30 organic solvent can be at least 10 vol % of the multi-component solvent.

The oxidation solvent can be a multi-component solvent comprising water and two different water-miscible organic solvents. The water-miscible organic solvents both can be water-miscible aprotic organic solvents. Each of the water-miscible aprotic organic solvents can be independently selected from the group consisting of tetrahydrofuran, a glyme, dioxane, a dioxolane, dimethylformamide, dimethylsulfoxide, sulfolane, acetone, *N*-methyl-2-pyrrolidone ("NMP"), methyl ethyl ketone ("MEK"), and gamma-valerolactone,

The furanic oxidation substrate can be 5-(hydroxymethyl)furfural (HMF). The furanic oxidation substrate can be selected from the group consisting of diformylfuran (DFF), hydroxymethylfurancarboxylic acid (HMFCA), and formylfurancarboxylic acid (FFCA).

The oxidation feedstock can include the furanic oxidation substrate at a concentration of at least 5% by weight. The furanic oxidation substrate can be present in the oxidation feedstock at a concentration of at least 10% by weight.

The heterogeneous oxidation catalyst can comprise the metal at a loading in the range of from or any number in between 0.3% to 5% by weight of the heterogeneous oxidation catalyst. The heterogeneous oxidation catalyst can further comprise a promoter.

The solid support can comprise a material selected from the group consisting of a metal oxide, a carbonaceous material, a polymer, a metal silicate, a metal carbide, and any combination of two or more thereof. The metal oxide can be selected from the group consisting of silica, zirconia, and alumina. The carbonaceous material can be carbon black.

The solid support can be a composite material comprising a binder and a material selected from the group consisting of a metal oxide, a carbonaceous material, a polymer, a metal silicate, and a metal carbide.

The heterogeneous oxidation catalyst can comprise a specific surface area in the range of from or any number in between 25 m²/g to 350 m²/g, from or any number in between 25 m²/g to 250 m²/g, from or any number in between 25 m²/g to 225 m²/g, from or any number in between 25 m²/g to 200 m²/g, from or any number in between 25 m²/g to 175 m²/g, from or any number in between 25 m²/g to 150 m²/g, from or any number in between 25 m²/g to 125 m²/g, or from or any number in between 25 m²/g to 100 m²/g. The heterogeneous oxidation catalyst can comprise a pore volume wherein at least 50% of the pore volume is from pores having a pore diameter in the range of from or any number in between 5 nm to 100 nm. The heterogeneous oxidation catalyst can comprise a pore volume

wherein no more than 10% of the pore volume of the heterogeneous oxidation catalyst is from pores having a pore diameter less than 10 nm but not zero. The heterogeneous oxidation catalyst can comprise a pore volume where no more than 10% of the pore volume of the heterogeneous oxidation catalyst is from pores having a pore diameter ranging from or any number in between 0.1 nm to 10 nm. The heterogeneous oxidation catalyst can comprise a pore volume where no more than 5% of the pore volume of the heterogeneous oxidation catalyst is from pores having a pore diameter less than 10 nm but not zero. The pore volume of the heterogeneous oxidation catalyst can be no more than 5% of the pores having a pore diameter ranging from or any number in between 0.1 nm to 10 nm. The pore volume of the heterogeneous oxidation catalyst can be no more than 2.5% of the pores having a pore diameter less than 10 nm but not zero. The pore volume of the heterogeneous oxidation catalyst can be no more than 2.5% of the pores having a pore diameter ranging from or any number in between 0.1 nm to 10 nm. The plurality of pores can be characterized by a mean pore diameter in the range of from or any number in between 10 nm to 100 nm.

The heterogeneous oxidation catalyst can comprise a second plurality of pores, where at least one of the first or second pluralities of pores is characterized by a mean pore diameter in the range of from or any number in between 10 nm to 100 nm. Each of the first and second plurality of pores can be characterized by a mean pore diameter in the range of from or any number in between 10 nm to 100 nm.

The heterogeneous oxidation catalyst can comprise a specific pore volume that is in the range of from or any number in between $0.1 \text{ cm}^3/\text{g}$ to $1.5 \text{ cm}^3/\text{g}$.

The oxygen can be present at a molar ratio of oxygen:furanic oxidation substrate in the range of from or any number in between 2:1 to 10:1. The molar ratio of oxygen:furanic oxidation substrate can be in the range of from or any number in between 2:1 to 5:1. The oxygen can be present at a pressure (p_{O_2}) in the range of from or any number in between 50 psig to 1000 psig. The oxygen can be present at a pressure (p_{O_2}) in the range of from or any number in between 50 psig to 200 psig.

The contacting step can be carried out at a temperature in the range of from or any number in between 50°C to 200°C , in the range of from or any number in between 80°C to 180°C , or in the range of from or any number in between 100°C to 160°C . The FDCA pathway product can be produced at a yield of at least 80%. The FDCA pathway product can

be produced at a selectivity of at least 90%. The contacting step can be carried out for a time sufficient to produce a product solution comprising the oxidation solvent and the FDCA pathway product at a concentration of at least 5% by weight. The contacting step can produce a product solution comprising the oxidation solvent and the FDCA pathway product at a concentration of at least 5% by weight.

The process can comprise a second oxidation step, wherein the second oxidation step comprises:

(b) contacting a second oxidation feedstock comprising a second furanic oxidation substrate and a second oxidation solvent with oxygen in the presence of a second heterogeneous oxidation catalyst under conditions sufficient to form a second reaction mixture for oxidizing the second furanic oxidation substrate to produce a second FDCA pathway product, and producing the second FDCA pathway product,

wherein (the first) contacting step (a) produces a first FDCA pathway product that is an FDCA pathway intermediate compound, either alone or together with FDCA,

wherein the second furanic oxidation substrate is the first FDCA pathway product,

wherein the second reaction mixture is substantially free of added base, and

wherein the second heterogeneous oxidation catalyst comprises a second solid support and a second noble metal, that may be the same or different from the (first) noble metal in step (a), and

wherein the second heterogeneous oxidation catalyst comprises a plurality of pores and a specific surface area in the range of from or any number in between 20 m²/g to 500 m²/g.

The second noble metal can be selected from the group consisting of platinum, gold, and a combination thereof. The second heterogeneous oxidation catalyst can be the same as the (first) heterogeneous oxidation catalyst of step (a). The second heterogeneous oxidation catalyst can be different from the (first) heterogeneous oxidation catalyst of step (a). The second heterogeneous oxidation catalyst can comprise a second metal that is not the same as the (first) metal in the (first) heterogeneous oxidation catalyst of step (a). The (first) oxidation solvent in step (a) can be the same as the second oxidation solvent in step (b).

The process may recover the FDCA pathway product from the oxidation solvent in step (a). The process may recover the second FDCA pathway product from the second

oxidation solvent in step (b). The process may involve purifying the FDCA pathway product from step (a). The process may involve purifying the second FDCA pathway product from step (b). The purifying step can comprise a crystallization process. The crystallization process can comprise providing a crystallization solution comprising the FDCA pathway product and a crystallization solvent at a first temperature in the range of from or any number in between 50°C to 220°C, and cooling the crystallization solution to a second temperature that is lower than the first temperature to form a plurality of FDCA pathway product crystals of different particle sizes. The crystallization solvent can be the (first) oxidation solvent in step (a). The crystallization process can comprises providing a crystallization solution comprising the second FDCA pathway product and a crystallization solvent at a first temperature in the range of from or any number in between 50°C to 220°C, and cooling the crystallization solution to a second temperature that is lower than the first temperature to form a plurality of second FDCA pathway product crystals of different particle sizes. The crystallization solvent can be selected from the group consisting of the first oxidation solvent of step (a) and the second oxidation solvent of step (b).

The process can include a crystallization process that comprises providing a first crystallization solution comprising the FDCA pathway product and a first crystallization solvent selected from the group consisting of water, an organic solvent, and combinations thereof; and removing a first portion of the first crystallization solvent from the first crystallization solution to produce a first FDCA pathway product slurry, wherein the first FDCA pathway product slurry comprises a first plurality of FDCA pathway product crystals of different particle sizes and a second portion of the first crystallization solvent. The crystallization process can further include dissolving the first plurality of FDCA pathway product crystals in a second crystallization solvent to produce a second crystallization solution comprising the FDCA pathway product and the second crystallization solvent; removing a first portion of the second crystallization solvent from the second crystallization solution to produce a second FDCA pathway product slurry comprising a second plurality of FDCA pathway product crystals of different particle sizes and a second portion of the second crystallization solvent; and separating the second plurality of FDCA pathway product crystals from the second portion of the second crystallization solvent.

The process can include a crystallization process that comprises providing a first crystallization solution comprising the second FDCA pathway product and a first crystallization solvent selected from the group consisting of water, an organic solvent, and combinations thereof; and removing a first portion of the first crystallization solvent from the first solution to produce a first FDCA pathway product slurry, wherein the first FDCA pathway product slurry comprises a first plurality of second FDCA pathway product crystals of different particle sizes and a second portion of the first crystallization solvent; and optionally separating the first plurality of second FDCA pathway product crystals from the second portion of the first crystallization solvent. The crystallization process can further include dissolving the first plurality of second FDCA pathway product crystals in a second crystallization solvent to produce a second crystallization solution comprising the second FDCA pathway product and the second crystallization solvent; removing a first portion of the second crystallization solvent from the second crystallization solution to produce a second FDCA pathway product slurry comprising a second plurality of the second FDCA pathway product crystals of different particle sizes and a second portion of the second crystallization solvent; and separating the second plurality of the second FDCA pathway product crystals from the second portion of the second crystallization solvent.

The process can further comprise converting FDCA to an ester of FDCA by contacting the FDCA with an alcohol under conditions sufficient to produce a corresponding ester of FDCA. The alcohol can be an aliphatic alcohol, a diol, ethylene glycol, or an aromatic alcohol. The ester of FDCA can be a diester of FDCA. The alcohol can be methanol and the diester of FDCA can be the dimethyl ester of FDCA. The process can further comprise converting FDCA or an FDCA ester to an FDCA amide by contacting the FDCA or FDCA ester with an amino-substituted compound under conditions sufficient to produce a corresponding FDCA amide. The amino-substituted compound can be 1,6-hexamethylenediamine. The FDCA amide can be an FDCA diamide. The process can further comprise converting FDCA to an FDCA halide by contacting the FDCA with a hydrohalic acid having the formula HX, wherein X is a halide, under conditions sufficient to produce the corresponding FDCA halide. The halide can be chloride and the FDCA halide can be FDCA chloride. The FDCA chloride can be FDCA dichloride.

The process can further comprise polymerizing FDCA or derivative thereof under conditions sufficient to produce an FDCA-based polymer. The FDCA derivative can be selected from the group consisting of an FDCA diester, an FDCA dihalide, and an FDCA diamide. The FDCA diester can be dimethyl FDCA ester. The FDCA diester can be di(ethylene glycol) FDCA ester. The polymerizing step can be a polycondensation reaction. The process can comprise a transesterification reaction that precedes the polycondensation reaction. The polymerizing step can comprise contacting the FDCA derivative with a second monomer. The second monomer can be a polyol.

The process can further comprise:

(a^o) prior to step (a), contacting a carbohydrate feedstock comprising a sugar and a dehydration solvent with a catalyst under conditions sufficient to form a reaction mixture for dehydrating the sugar to produce the furanic oxidation substrate, wherein the furanic oxidation substrate is present in a dehydration product solution that comprises the furanic oxidation substrate and the dehydration solvent.

The sugar can be fructose and the furanic oxidation substrate can be HMF. The oxidation feedstock of step (a) can comprise the dehydration product solution of step (a^o). With respect to the (first) heterogeneous oxidation catalyst, (1) the noble metal can be platinum; (2) the solid support can be selected from the group consisting of silica and a carbonaceous material; and (3) the plurality of pores can be characterized by a mean pore diameter in the range of from or any number in between 10 nm to 100 nm. With respect to the (second) heterogeneous oxidation catalyst: (1) the noble metal can be platinum; (2) the solid support can be selected from the group consisting of silica and a carbonaceous material; and (3) the plurality of pores can be characterized by a mean pore diameter in the range of from or any number in between 10 nm to 100 nm.

In another aspect, the present disclosure is directed to a process for producing a crystalline FDCA pathway product composition, the method comprising:

providing a crystallization solution comprising an FDCA pathway product and a crystallization solvent that is a multi-component solvent comprising water and a water-miscible organic solvent;

initiating crystallization of the FDCA pathway product; and

producing a plurality of FDCA pathway product crystals of different particle sizes. In certain embodiments, the water-miscible organic solvent is a water-miscible aprotic organic solvent.

The water-miscible organic solvent can be a water-miscible aprotic organic solvent.

5 The water-miscible aprotic organic solvent can be selected from the group consisting of tetrahydrofuran, a glyme, dioxane, a dioxolane, dimethylformamide, dimethylsulfoxide, sulfolane, acetone, *N*-methyl-2-pyrrolidone ("NMP"), methyl ethyl ketone ("MEK"), and gamma-valerolactone. The water-miscible organic solvent can be selected from the group consisting of a light water-miscible organic solvent and a heavy water-miscible organic
10 solvent.

The multi-component solvent can comprise the water and the water-miscible organic solvent in a ratio of from or any number in between 1:6 to 6:1 v/v. The multi-component solvent can comprise the water and the water-miscible organic solvent in a ratio within a range defined by 1:6 to 6:1 v/v. The multi-component solvent can comprise at least 10 vol%
15 water-miscible organic solvent.

The crystallization can be initiated by cooling the crystallization solution to a temperature below 60°C. The crystallization can be initiated by cooling the crystallization solution to a temperature below 50°C. The crystallization can be initiated by removing a portion of the crystallization solvent to produce a first FDCA pathway product slurry,
20 wherein the first FDCA pathway product slurry comprises a first plurality of FDCA pathway product crystals and a second portion of crystallization solvent or component thereof. The seed crystals can be added to the crystallization solution.

The plurality of FDCA pathway product crystals can be characterized by a median (D50) particle size in the range of from or any number in between 50 µm to 5000 µm or in
25 the range of from or any number in between 50 µm to 2000 µm. The plurality of FDCA pathway product crystals can be characterized by a median (D50) particle size in the range of from or any number in between 150 µm to 750 µm.

The process for producing a crystalline FDCA pathway product composition can further comprise dissolving the first plurality of FDCA pathway product crystals in a second
30 crystallization solvent to produce a second crystallization solution comprising a second plurality of FDCA pathway product crystals and a second crystallization solvent; removing a

first portion of the second crystallization solvent from the second crystallization solution to produce a second FDCA pathway product slurry that comprises a second plurality of FDCA crystals and a second portion of the second crystallization solvent; and separating the second plurality of FDCA pathway product crystals from the second portion of the second

5 crystallization solvent. Seed crystals can be added to the second crystallization solution.

The dissolving step can be carried out at a temperature in the range of from or any number in between 80°C to 220°C, or in the range of from or any number in between 60°C to 180°C, or in the range of from or any number in between 80°C to 150°C. In a still further aspect,

the present disclosure is directed to a crystalline FDCA composition wherein the composition
10 comprises a plurality of FDCA crystal particles of different particles sizes, wherein the plurality is characterized by a median particle size (D50) in the range of from 50 µm to 5000 µm, such as 50, 75, 100, 200, 300, 400, 500, 600, 700, 800, 900, 1000, 1500, 2000, 2500, 3000, 3500, 4000, 4500, or 5000 µm or within a range defined by any two of the aforementioned sizes.

15 In another aspect, the present disclosure is directed to a process for converting FDCA to an FDCA derivative selected from the group consisting of an FDCA salt, an FDCA ester, an FDCA amide, and an FDCA halide.

In a still further aspect, the present disclosure is directed to process for producing an FDCA-based polymer selected from the group consisting of an FDCA-based polyester and an
20 FDCA-based polyamide.

In some embodiments, the present disclosure is directed to a composition comprising:
(a) an oxidation feedstock comprising a furanic oxidation substrate and an oxidation solvent;
(b) oxygen; (c) a heterogeneous oxidation catalyst; (d) an FDCA pathway product; wherein
the oxidation solvent is a solvent selected from the group consisting of an organic solvent
25 and a multi-component solvent; wherein the heterogeneous oxidation catalyst comprises a solid support and a noble metal; wherein the heterogeneous oxidation catalyst comprises a plurality of pores and a specific surface area in the range of from or any number in between 20 m²/g to 500 m²/g; and wherein the composition is substantially free of added base.

The noble metal can be selected from the group consisting of platinum, gold, and a
30 combination thereof. The oxidation solvent can be a multi-component solvent comprising water and a water-miscible organic solvent. The water-miscible organic solvent can be a

water-miscible aprotic organic solvent. The water-miscible aprotic organic solvent can be selected from the group consisting of tetrahydrofuran, a glyme, dioxane, a dioxolane, dimethylformamide, dimethylsulfoxide, sulfolane, acetone, *N*-methyl-2-pyrrolidone (“NMP”), methyl ethyl ketone (“MEK”), and gamma-valerolactone. The water-miscible organic solvent can be selected from the group consisting of a light water-miscible organic solvent and a heavy water-miscible organic solvent.

The water and the water-miscible organic solvent can be present in a ratio of from or any number in between 1:6 to 6:1 v/v water:water-miscible organic solvent. The water and the water-miscible organic solvent can be present in a ratio within a range defined by 1:6 to 6:1 v/v water:water-miscible organic solvent. The water and the water-miscible organic solvent can be present in a ratio of 1:1 v/v water:water-miscible organic solvent. The water-miscible organic solvent can comprise at least 10 vol % of the multi-component solvent.

The furanic oxidation substrate can be 5-(hydroxymethyl)furfural (HMF). The furanic oxidation substrate can be selected from the group consisting of diformylfuran (DFF), hydroxymethylfurancarboxylic acid (HMFA), and formylfurancarboxylic acid (FFCA).

The oxidation feedstock can comprise the furanic oxidation substrate at a concentration of at least 5% by weight. The furanic oxidation substrate can be present in the oxidation feedstock at a concentration of at least 10% by weight.

The heterogeneous oxidation catalyst can comprise the metal at a loading in the range of from or any number in between 0.3% to 5% by weight of the heterogeneous oxidation catalyst. The heterogeneous oxidation catalyst can further comprise a promoter.

The solid support can comprise a material selected from the group consisting of a metal oxide, a carbonaceous material, a polymer, a metal silicate, a metal carbide, and any combination of two or more thereof. The metal oxide can be selected from the group consisting of silica, zirconia, and alumina. The carbonaceous material can be carbon black. The solid support can be a composite material comprising a binder and a material selected from the group consisting of a metal oxide, a carbonaceous material, a polymer, a metal silicate, and a metal carbide.

The heterogeneous oxidation catalyst can comprise a specific surface area in the range of from or any number in between 25 m²/g to 350 m²/g, from or any number in between 25 m²/g to 250 m²/g, from or any number in between 25 m²/g to 225 m²/g, from or

any number in between 25 m²/g to 200 m²/g, from or any number in between 25 m²/g to 175 m²/g, from or any number in between 25 m²/g to 150 m²/g, from or any number in between 25 m²/g to 125 m²/g, or from or any number in between 25 m²/g to 100 m²/g. The heterogeneous oxidation catalyst can comprise a pore volume wherein at least 50% of the pore volume is from pores having a pore diameter in the range of from or any number in between 5 nm to 100 nm. The heterogeneous oxidation catalyst can comprise a pore volume wherein no more than 10% of the pore volume of the heterogeneous oxidation catalyst is from pores having a pore diameter less than 10 nm. The heterogeneous oxidation catalyst can comprise a pore volume wherein no more than 10% of the pore volume of the heterogeneous oxidation catalyst is from pores having a pore diameter ranging from or any number in between 0.1 nm to 10 nm. The pore volume of the heterogeneous oxidation catalyst can be no more than 2.5% of the pores having a pore diameter less than 10 nm but not zero. The pore volume of the heterogeneous oxidation catalyst can be no more than 2.5% of the pores having a pore diameter ranging from or any number in between 0.1 nm to 10 nm. The plurality of pores can be characterized by a mean pore diameter in the range of from or any number in between 10 nm to 100 nm. The heterogeneous oxidation catalyst can comprise a specific pore volume that is in the range of from or any number in between 0.1 cm³/g to 1.5 cm³/g.

The heterogeneous oxidation catalyst can comprise a second plurality of pores, wherein at least one of the first or second pluralities of pores is characterized by a mean pore diameter in the range of from or any number in between 10 nm to 100 nm. Each of the first and second plurality of pores can be characterized by a mean pore diameter in the range of from or any number in between 10 nm to 100 nm.

The oxygen can be present at a molar ratio of oxygen:furanic oxidation substrate in the range of from or any number in between 2:1 to 10:1. The molar ratio of oxygen:furanic oxidation substrate can be in the range of from or any number in between 2:1 to 5:1. The oxygen can be present at a pressure (p_{O_2}) in the range of from or any number in between 50 psig to 1000 psig. The oxygen can be present at a pressure (p_{O_2}) in the range of from or any number in between 50 psig to 200 psig.

In some embodiments, the present disclosure is directed to an apparatus comprising: (a) an oxidation reaction zone; (b) an oxygen feed stream comprising oxygen; (c) an

oxidation feedstock stream comprising a furanic oxidation substrate and an oxidation solvent; wherein the oxidation solvent is a solvent selected from the group consisting of an organic solvent and a multi-component solvent; (d) a pathway product stream comprising an FDCA pathway product; wherein the oxygen feed stream and oxidation feedstock stream are passed
5 into the oxidation reaction zone and react to produce an FDCA pathway product; wherein the oxidation reaction zone contains a heterogeneous oxidation catalyst, oxygen, a furanic oxidation substrate, and an oxidation solvent; wherein the FDCA pathway product stream exits the oxidation reaction zone; wherein the heterogeneous oxidation catalyst comprises a solid support and a noble metal; wherein the heterogeneous oxidation catalyst comprises a
10 plurality of pores and a specific surface area in the range of from or any number in between $20 \text{ m}^2/\text{g}$ to $500 \text{ m}^2/\text{g}$; wherein the oxidation reaction zone is substantially free of added base.

The apparatus can further comprise a recycle stream wherein the recycle stream comprises unreacted furanic oxidation substrate; wherein the recycle stream exits the oxidation reaction zone; and wherein the apparatus contains a means for optionally passing
15 the recycle stream back into the oxidation reaction zone.

The apparatus can further comprise (e) a second oxidation reaction zone; (f) a second oxygen feed stream comprising oxygen; (g) a second pathway product stream comprising an FDCA pathway product; wherein the pathway product stream from element (d) and the second oxygen feed stream are passed into the second oxidation reaction zone and react to
20 produce an FDCA pathway product; wherein the second pathway product stream exits the second oxidation reaction zone; wherein the second oxidation reaction zone contains a second heterogeneous oxidation catalyst, oxygen, and the pathway product stream from element (d); wherein the second heterogeneous oxidation catalyst comprises a solid support and a noble metal; wherein the second heterogeneous oxidation catalyst comprises a plurality
25 of pores and a specific surface area in the range of from or any number in between $20 \text{ m}^2/\text{g}$ to $500 \text{ m}^2/\text{g}$; wherein the second oxidation reaction zone is substantially free of added base. The apparatus can further comprise a recycle stream wherein the recycle stream comprises unreacted pathway product stream from element (d); wherein the recycle stream exits the second oxidation reaction zone; and wherein the apparatus contains a means for optionally
30 passing the recycle stream into the oxidation reaction zone from element (a).

In some embodiments, the present disclosure is directed to a process for producing a furanic oxidation substrate, the process comprising contacting a carbohydrate feedstock comprising a sugar and a dehydration solvent with an acid catalyst under conditions sufficient to form a dehydration reaction mixture for dehydrating the sugar to produce a furanic oxidation substrate, wherein the acid catalyst is an acid selected from the group consisting of HBr, H₂SO₄, HNO₃, HCl, HI, H₃PO₄, triflic acid, methansulfonic acid, benzenesulfonic acid, and p-toluene sulfonic acid, wherein when the acid catalyst is not HBr, the dehydration reaction mixture further comprises a bromide salt, and wherein the dehydration solvent comprises N-methyl-pyrrolidone (NMP).

The acid catalyst can be HBr. The acid catalyst can be selected from the group consisting of H₂SO₄, HNO₃, HCl, HI, H₃PO₄, triflic acid, methansulfonic acid, benzenesulfonic acid, and p-toluene sulfonic acid, and wherein the dehydration reaction mixture comprises a bromide salt. The bromide salt can be selected from the group consisting of LiBr, NaBr, KBr, MgBr₂, CaBr₂, ZnBr₂, tetramethylammonium bromide, tetraethylammonium bromide, tetrapropylammonium bromide, tetrabutylammonium bromide, and any combination of two or more thereof. The acid catalyst can further comprise a Lewis acid. The Lewis acid can be selected from the group consisting of a boron trihalide, an organoborane, an aluminum trihalide, a phosphorus pentafluoride, an antimony pentafluoride, a rare earth metal triflate, a metal halide, a metal trifluoroacetate, or a metal cation ether complex. The Lewis acid can be a metal halide. The metal halide can be ZnCl₂ or ZnBr₂.

The yield of furanic oxidation substrate can be at least 60%, or at least 70%, or at least 80%, or at least 90% or at least 95%, or at least 98% or at least 99%. The sugar can be fructose. The furanic oxidation substrate can be HMF.

The dehydration reaction mixture can be maintained at a temperature in the range of from or any number in between 80°C and 160°C, or 80°C and 150°C, or 80°C and 140°C, or 80°C and 130°C, or 80°C and 120°C, or 80°C and 110°C, or 80°C and 100°C.

The dehydration solvent can further comprise water. The dehydration solvent can comprise water and NMP in a range from or any number in between 1-5 wt% water and 99-95% NMP, or 5-10 wt% water and 95-90 wt% NMP, or 10-15 wt% water and 90-85 wt% NMP, or 15-20 wt% water and 85-80 wt% NMP, or 20-25 wt% water and 80-75 wt% NMP,

or 25-30 wt% water and 75-70 wt% NMP, or 30-35 wt% water and 70-65 wt% NMP, or 35-40 wt% water and 65-60 wt% NMP, or 40-45 wt % water and 60-55 wt% NMP, or 45-50 wt% water and 55-50 wt% NMP, or 50-55 wt% water and 50-45 wt% NMP, or 55-60 wt% water and 45-40 wt% NMP, or 60-65 wt% water and 40-35 wt% NMP, or 65-70 wt% water and 35-30 wt% NMP, or 70-75 wt% water and 30-25 wt% NMP, or 75-80 wt% water and 25-20 wt% NMP, or 80-85 wt% water and 20-15 wt% NMP, or 85-90 wt% water and 15-10 wt% NMP, or 90-95 wt% water and 10-5 wt% NMP, or 95-99 wt% water and 5-1 wt% NMP.

The dehydration solvent can further comprise a second organic solvent species. The second organic solvent species can be a water-miscible organic solvent that is not N-methylpyrrolidone (NMP). Each of the water-miscible aprotic organic solvent can be selected from the group consisting of tetrahydrofuran, a glyme, dioxane, a dioxolane, dimethylformamide, dimethylsulfoxide, sulfolane, acetone, methyl ethyl ketone ("MEK"), and gamma-valerolactone,

The furanic oxidation substrate can be present in a dehydration product solution that comprises the furanic oxidation substrate and the dehydration solvent. The dehydration product solution further can comprise an unreacted sugar. The dehydration product solution can be a mixture that includes humins. The dehydration product solution or the mixture that includes humins can be subjected to one or more membranes to effect separation of the furanic oxidation substrate from one or more components selected from the group consisting of a humin, an unreacted sugar, or a combination thereof. The one or more membranes can be selected from the group consisting of an ultrafiltration, a nanofiltration membrane, and a combination thereof.

BRIEF DESCRIPTION OF THE FIGURES

Figure 1 depicts the net conversion of 5-(hydroxymethyl)furfural (HMF) (I) to 2,5-furandicarboxylic acid (FDCA) (V).

Figure 2 depicts potential FDCA pathway intermediates that may be generated by the oxidation of HMF. These intermediates are diformylfuran (II), hydroxymethylfurancarboxylic acid (III), and formylfurancarboxylic acid (IV). The final oxidation product in the pathway is FDCA (V).

Figure 3 depicts the solubility of FDCA (weight percent) in H₂O (▲), dioxane (◆), diglyme (■), 1:1 v/v diglyme:H₂O (○), and 4:1 v/v dioxane:H₂O (●) at temperatures in the range of from 22°C to 140 °C.

Figure 4 is a schematic of a single oxidation reaction zone process for converting a furanic oxidation substrate to a desired FDCA pathway product.

Figure 5 is a schematic of an integrated multi-oxidation reaction zone process for converting a furanic oxidation substrate to a desired FDCA pathway product.

Figure 6 depicts an integrated crystallization process for producing refined crystalline FDCA product from a feedstock that is the product stream of an oxidation reaction zone. The oxidation reaction zone product stream comprises FDCA and a multi-component solvent of water and a water-miscible light organic solvent. The process utilizes a solvent switch from the co-solvent to water between the first and second crystallization steps.

Figure 7 depicts an integrated crystallization process for producing refined crystalline FDCA from a feedstock that is the product stream of an oxidation reaction zone. The process utilizes a multi-component solvent comprising water and a water-miscible light organic solvent.

Figure 8 depicts an integrated crystallization process for producing refined crystalline FDCA from a feedstock that is the product stream of an oxidation reaction zone. The oxidation reaction zone product stream comprises FDCA and a co-solvent of water and a water-miscible heavy organic solvent. The process utilizes a solvent switch from the co-solvent to water between the first and second crystallization steps.

Figure 9 depicts an integrated crystallization process for producing refined crystalline FDCA from a feedstock that is the product stream of an oxidation reaction zone. The oxidation reaction zone product stream comprises FDCA and a multi-component solvent of water and a water-miscible heavy organic solvent.

Figure 10 depicts an integrated process for producing a purified dimethylester of FDCA by distillation.

Figure 11 depicts an integrated process for producing a purified dimethylester of FDCA by crystallization.

Figure 12 depicts the temperature dependence of FDCA solubility in Dioxane/H₂O solvent compositions.

Figure 13 depicts the temperature dependence of FDCA solubility in DME/H₂O solvent compositions.

Figure 14 depicts a plot of percent HMF yield versus percent conversion for the conversion of fructose to HMF using HBr and H₂SO₄ in NMP and H₂O.

5 Figure 15 depicts a plot of percent HMF yield versus percent conversion for the conversion of fructose to HMF using HBr and HCl in NMP and H₂O.

Figure 16 depicts a plot of percent HMF yield versus percent conversion for the conversion of fructose to HMF using HBr in NMP and H₂O.

10

DETAILED DESCRIPTION

I. Processes for Producing FDCA Pathway Products

In one embodiment, the present disclosure provides novel processes for producing desired furandicarboxylic acid (FDCA) pathway products at high yields and high selectivities from the oxidation of a furanic oxidation substrate. Significantly, these results are achieved without the need for any added base. The base-free (and substantially base-free) oxidative processes of the present disclosure are attractive as compared to existing processes for producing FDCA and related pathway products because, *inter alia*, they do not require further downstream processing to remove added base, or any by-products generated as a result of the base addition. As used herein, the terms "furandicarboxylic acid pathway product" and "FDCA pathway product" are used interchangeably herein to refer to 2,5-furandicarboxylic acid (FDCA) or a 2,5-furandicarboxylic acid pathway intermediate compound. The net conversion of HMF to FDCA is shown in Figure 1. The term "furandicarboxylic acid pathway" is used herein to refer to the pathway depicted in Figure 2. As used herein, the terms "2,5-furandicarboxylic acid pathway intermediate compound" and "FDCA pathway intermediate compound" are used interchangeably to refer to any one of diformylfuran (DFF), hydroxymethylfurancarboxylic acid (HMFCA), and 5-formylfurancarboxylic acid (FFCA), which correspond to compounds II, III, and IV in Figure 2, respectively.

More specifically, the present disclosure provides a process for producing an FDCA pathway product from a furanic oxidation substrate, the process comprising:

30

(a) contacting an oxidation feedstock comprising a furanic oxidation substrate and an oxidation solvent with oxygen in the presence of a heterogeneous oxidation catalyst under conditions sufficient to form a reaction mixture for oxidizing the furanic oxidation substrate to an FDCA pathway product, and producing the FDCA pathway product,

5 wherein the oxidation solvent is a solvent selected from the group consisting of an organic solvent and a multi-component solvent, wherein the reaction mixture is substantially free of added base, and wherein the heterogeneous oxidation catalyst comprises a solid support and a noble metal, and

10 wherein the heterogeneous oxidation catalyst comprises a plurality of pores and a specific surface area in the range of from or any number in between 20 m²/g to 500 m²/g, such as e.g., 20, 30, 40, 50, 60, 70, 80, 90, 100, 120, 140, 160, 180, 200, 225, 250, 275, 300, 325, 350, 375, 400, 425, 450, 475, or 500 m²/g or is within a range defined by any two of the aforementioned surface areas.

15 The term "substantially free of added base" is used herein to refer to the lack of any base added to the reaction mixture (i.e., no added base), or the addition of a de minimis quantity of base. The term "de minimis quantity of base" refers herein to an amount of base which, when added to a reaction mixture employed in the practice of the present disclosure, does not alter the oxidation reaction by more than 1% with respect to product yield or product selectivity, as compared to the same oxidation reaction performed under the same
20 conditions with the exception that no base is added to the reaction mixture. Typically, the processes of the present disclosure are carried out under base-free conditions, i.e., no base is added to the reaction mixture during the contacting (i.e., oxidation) step.

Oxidation processes of the present disclosure result in the production of the desired FDCA pathway product at a yield that is typically at least 80% and a selectivity that is
25 typically at least 90% (both on a molar basis). In some embodiments, the yield is at least 85%, and in other embodiments, it is at least 90%, at least 95%, and often, at least 98% or at least 99%. In some embodiments, the yield ranges from between 85-90%, 87-92%, 90-95%, 92-97%, 95-98%, or 97-99%, or is within a range defined by any of two of the aforementioned percentages. The selectivity with respect to production of the desired FDCA
30 pathway product is more typically at least 91% or at least 92% or at least 93% or at least 94% or at least 95% or at least 96% or at least 97% or at least 98% or at least 99%. In some

embodiments, the selectivity with respect to the desired FDCA pathway product ranges from between 91-93%, 92-94%, 93-95%, 94-96%, 95-97%, 96-98%, 97-99%, or is within a range defined by any of two of the aforementioned percentages. The desired FDCA pathway product is usually FDCA.

5 The term "oxidation feedstock" refers herein to a source material for the furanic oxidation substrate. As used herein, the term "furanic oxidation substrate" refers to a compound that is HMF or an FDCA intermediate compound (i.e., DFF, HMFCa, FFCA, or combination thereof) or a combination thereof. Oxidation feedstocks employed in the practice of the processes described herein may be employed in any of a variety of forms, including, for example, a solution, a suspension, a dispersion, an emulsion, and the like. Typically, the oxidation feedstock comprises the furanic oxidation substrate in solution with the oxidation solvent.

 In the oxidation processes described herein, the FDCA pathway product is typically FDCA. In certain embodiments, the furanic oxidation substrate is typically HMF. However, 15 it may be desirable to use a furanic oxidation substrate that is an FDCA pathway intermediate compound or mixture of FDCA pathway intermediate compounds, i.e., DFF, HMFCa, FFCA, or a mixture of any two or more thereof. This may be an attractive option in situations where HMF has been previously oxidized to an FDCA pathway intermediate compound or mixture of intermediate compounds, and the intermediate compound(s) is (are) 20 available for use as a raw material. When such intermediates are used as furanic oxidation substrates in the oxidative processes of the present disclosure, the resulting FDCA pathway product is typically FDCA, but it may also be a different FDCA pathway intermediate compound that is "downstream" (from an oxidation standpoint) in the FDCA pathway, of the FDCA pathway intermediate employed as the furanic oxidation substrate.

25 The oxidation feedstock may contain other agents or residual components that are soluble or insoluble in the oxidation feedstock. For example, the oxidation feedstock may be a crude oxidation feedstock of HMF, or other furanic oxidation substrate, and the oxidation solvent. The term "crude feedstock" refers herein to a feedstock that, in addition to comprising the desired furanic oxidation substrate, also comprises impurities and/or by- 30 products related to the production, isolation, and/or purification of the desired furanic oxidation substrate. For example, the oxidation feedstock, may, in addition, comprise certain

biomass-related components that originate from biomass or are by-products which are generated in the conversion of biomass to a sugar (by, for example, thermal, chemical, mechanical, and/or enzymatic degradative means), where such sugar is subsequently converted to HMF. Thus, the oxidation feedstock may also comprise a component selected
5 from the group consisting of a polysaccharide (including, for example, a cellulose (e.g., a lignocellulose, a hemicellulose, and the like), starch, and the like), an oligosaccharide (e.g., a raffinose, a maltodextrin, a cellodextrin, and the like), a monosaccharide (e.g., glucose, fructose, galactose, mannose, xylose, rabinose, and the like), a disaccharide (e.g., sucrose, lactose, maltose, cellobiose and the like), furanic substrates such as furfural, oligomeric or
10 polymeric humin by-products (humins) and residual mineral acids. Similarly, the oxidation feedstock may be a crude feedstock of HMF oxidation products comprising HMF and/or FDCA pathway intermediate compounds.

In addition to the high yields and high selectivities observed, oxidation processes of the present disclosure produce FDCA pathway products, such as, for example, FDCA at
15 relatively high concentrations in a resulting product solution. The high productivity levels obtained from the processes described herein are believed to be due to the combined use of the novel heterogeneous oxidation catalysts employed and the properties of the oxidation solvent.

As used herein, the term, "oxidation solvent" refers to a solvent that is an organic
20 solvent or a multi-component solvent in which the furanic oxidation substrate and the desired FDCA pathway product are each separately soluble at a minimum level of at least 2% by weight at the temperature at which the contacting (oxidation) step is conducted. Typically, the oxidation solvent is one in which the FDCA pathway product has a solubility of at least 3 wt%, at least 4 wt%, and more typically, at least 5 wt%, at least 6 wt%, at least 7 wt%, at
25 least 8 wt%, at least 9 wt%, at least 10 wt%, at least 11 wt%, at least 12 wt%, at least 13 wt%, at least 14 wt%, or at least 15 wt%, as measured at the temperature at which the contacting step is carried out. In some embodiments, the FDCA pathway product has a solubility that ranges from between 2-4 wt%, 3-5 wt%, 4-6 wt%, 5-7 wt%, 6-8 wt%, 7-9 wt%, 8-10 wt%, 9-11 wt%, 10-12 wt%, 11-13 wt%, 12-14 wt%, or 13-15% or is within a
30 range defined by any of two of the aforementioned weight percentages. The solubility of the FDCA pathway product in a candidate organic solvent or candidate multi-component solvent

can be readily determined using known methods, as well as the method described in Example 1.

Without wishing to be bound by theory, the oxidation solvents employed in the present disclosure are believed to facilitate the efficient conversion of furanic oxidation substrate to FDCA pathway product (catalyzed by the high performing catalysts of the present disclosure) by, among other things, eliminating product precipitation that may lead to reactor/catalyst fouling. Moreover, the relatively high concentrations of FDCA and FDCA intermediate compounds that may be achieved in the processes of the present disclosure results in high process productivity and less costly solvent removal, in contrast to processes that employ poor solvents such as, for example water or the acetic acid-water mixtures described in U.S. Pat. No. 7,700,788. Thus, the present disclosure provides processes that are particularly attractive for the commercial scale production of FDCA, and related intermediates.

When carrying out the oxidation processes of the present disclosure, the furanic oxidation substrate may be present in the oxidation feedstock at any concentration up to its solubility limit, in circumstances where the feedstock is a solution. In some embodiments, the concentration of furanic oxidation substrate in the oxidation feedstock is at least 1 wt%, at least 2 wt%, at least 3 wt%, at least 4 wt%, at least 5 wt%, at least 6 wt%, at least 7 wt%, at least 8 wt%, at least 9 wt%, at least 10 wt%, at least 11 wt%, at least 12 wt%, at least 13 wt%, at least 14 wt%, or at least 15 wt% by weight of the oxidation feedstock. In some embodiments, the concentration of furanic oxidation substrate in the oxidation feedstock ranges from 1-3 wt%, 2-4 wt%, 3-5 wt%, 4-6 wt%, 5-7 wt%, 6-8 wt%, 7-9 wt%, 8-10 wt%, 9-11 wt%, 10-12 wt%, 11-13 wt%, 12-14 wt%, or 13-15% or is within a range defined by any of two of the aforementioned weight percentages. Typically, the furanic oxidation substrate is present in the oxidation feedstock at a concentration of at least 5 wt%. More typically, the furanic oxidation substrate is present in the oxidation feedstock at a concentration of at least 6 wt%, or at least 7 wt%, or at least 8 wt%, or at least 9 wt%, or at least 10 wt%, or at least 11 wt%, or at least 12 wt%, or at least 13 wt%, or at least 14 wt%, or at least 15 wt% at the temperature at which the contacting (oxidation) step is conducted. In some embodiments, the furanic oxidation substrate is present in the oxidation feedstock at the temperature at which the contacting (oxidation) step is conducted in a concentration that

ranges from between 6-8 wt%, 7-9 wt%, 8-10 wt%, 9-11 wt%, 10-12 wt%, 11-13 wt%, 12-14 wt%, or 13-15% or is within a range defined by any of two of the aforementioned weight percentages.

Organic solvents that exhibit the requisite minimal solvating requirements for the furanic oxidation substrate and FDCA are suitable for use in the practice of the present disclosure, either alone or as a component of a multi-component solvent. Applicants have discovered, in particular, that the use of aprotic organic solvents, in combination with the catalysts and conditions described herein, appear to facilitate the high productivities observed with respect to the processes of the present disclosure. Therefore, in some embodiments, the oxidation solvent comprises an aprotic organic solvent (e.g., an ether, an ester, a ketone, and the like) either alone (i.e., as a single-component solvent) or as a component of a multi-component solvent. When used in a multi-component solvent, the aprotic organic solvent is typically miscible with the other component(s) of the multi-component solvent. The term "multi-component solvent" refers herein to a mixture of two, three, or more solvent species. Multi-component solvents employed in the practice of the present disclosure may comprise two or more solvent species selected from the group consisting of a first organic solvent species, a second organic solvent species, and water. When the multi-component solvent comprises water and an organic solvent, the organic solvent is a water-miscible organic solvent. Typically, the water-miscible organic solvent is a water-miscible aprotic organic solvent.

With respect to the processes of the present disclosure, it should be noted that candidate component solvents for the multi-component solvent should not be limited to solvents in which the furanic oxidation substrate and desired FDCA pathway product are highly soluble. Applicants have discovered that multi-component solvents may exhibit a synergistic solvating effect with respect to FDCA, even when FDCA is poorly soluble in each component solvent. For example, FDCA has poor solubility in water. Applicants have discovered that, even when paired with a water-miscible organic solvent having poor FDCA-solvating capabilities, the combination of water and the water-miscible organic solvent exhibits enhanced FDCA-solvating capability.

Illustrative multi-component solvents that exhibit this effect include those that comprise water and a water-miscible aprotic organic solvent. Exemplary water-miscible

aprotic solvents suitable for use in the practice of the present disclosure include tetrahydrofuran, a glyme, dioxane, a dioxolane, dimethylformamide, dimethylsulfoxide, sulfolane, acetone, *N*-methyl-2-pyrrolidone ("NMP"), methyl ethyl ketone ("MEK"), gamma-valerolactone, and the like. Preferably, the water-miscible aprotic organic solvent is an ether, such as, for example, a glyme, dioxane (1,4-dioxane), a dioxolane (e.g., 1,3-dioxolane), tetrahydrofuran, and the like. Glymes that are suitable for use in the practice of the present disclosure include, for example, monoglyme (1,2-dimethoxyethane, "DME"), ethyl glyme, diglyme (diethylene glycol dimethyl ether), ethyl diglyme, triglyme, butyl diglyme, tetraglyme, a polyglyme, a highly ethoxylated diether of a high molecular weight alcohol ("higlyme"), and the like. Often, the oxidation solvent is a multi-component solvent comprising water and a water-miscible aprotic organic solvent that is glyme, diglyme, or dioxane.

In some embodiments, the multi-component solvent comprises water and dioxane. In some embodiments, the multi-component solvent comprises water and DME. In some embodiments, the multi-component solvent comprises water and diglyme. In some embodiments, the multi-component solvent comprises water and triglyme. In some embodiments, the multi-component solvent comprises water and tetraglyme. In some embodiments, the multi-component solvent comprises water and higlyme. In some embodiments, the multi-component solvent comprises water and NMP. In some embodiments, the multi-component solvent comprises water and MEK. In some embodiments, the multi-component solvent comprises water and gamma-valerolactone.

Example 1 describes a solubility study that examined the solubility of FDCA in: (1) diglyme only; (2) dioxane only; (3) water only; (4) a multi-component solvent made up of 4:1 (v/v) dioxane:H₂O; and (5) a multi-component solvent made up of 1:1 (v/v) glyme:H₂O. The results are depicted in a plot of FDCA solubility as a function of temperature in Figure 3. Although FDCA exhibits relatively low solubilities in water (less than 2% by weight at temperatures in the range of from 22°C to 140°C), dioxane (less than 2% by weight at temperatures in the range of from 22°C to 100°C), and diglyme (less than 2% by weight at temperatures in the range of from 22°C to 100°C), it surprisingly exhibits high solubilities in multi-component solvents of, for example, 4:1 dioxane:H₂O (v:v) (from 4% by weight to 11% by weight at temperatures in the range of from 22°C to 140°C) and 1:1 diglyme:water

(v:v) (from just below 2% by weight to 9% by weight at temperatures in the range of from 22°C to 140°C). These multi-component solvents are desirable because they facilitate the production of greater quantities of FDCA pathway product with relatively less solvent (for example, as compared to water only as a solvent) that would typically need to be removed during product recovery operations.

Organic solvents and additional multi-component solvents suitable for use as an oxidation solvent in the practice of the present disclosure can be readily identified using the assay method described in Example 1.

In some embodiments, the composition of the oxidation solvent may take into consideration the requirements of further downstream processes (e.g., to facilitate product recovery, purification, and the like), or upstream processes (e.g., the conversion of a sugar to the furanic oxidation substrate). For example, in certain embodiments it may be desirable to employ an oxidation solvent that is a multi-component solvent comprising a light solvent and a heavy solvent. The term "light solvent" refers to a solvent having a boiling point at a certain pressure that occurs at a temperature that is less than the boiling point (temperature) of the heavy solvent at the same pressure. Conversely, the term "heavy solvent" refers to a solvent having a boiling point at a certain pressure that occurs at a temperature that is higher than the boiling point (temperature) of the light solvent at the same pressure. When the multi-component solvent comprises water and a water-miscible organic solvent, the water-miscible organic solvent may be a light water-miscible organic solvent (i.e., a water-miscible organic solvent having a boiling point that occurs at a temperature less than the boiling point of water) or it may be a heavy water-miscible organic solvent (i.e., a water-miscible organic solvent having a boiling point that occurs at a temperature higher than the boiling point of water). Typically, the light and heavy water-miscible organic solvent are a light and heavy aprotic organic solvent, respectively. Exemplary light water-miscible (and aprotic) organic solvents employed with water in a multi-component solvent include, for example, glyme, a dioxolane (e.g., 1,3-dioxolane), and tetrahydrofuran, and the like. Exemplary heavy water-miscible (and aprotic) organic solvents employed with water in a multi-component solvent include, for example, dioxane, ethyl glyme, diglyme (diethylene glycol dimethyl ether), ethyl diglyme, triglyme, butyl diglyme, tetraglyme, a polyglyme, and the like. In some embodiments (e.g., continuous reactor systems), all or a portion of the oxidation solvent or

component thereof may be removed from the production solution (e.g., via distillation) and recycled to the reaction mixture. In such embodiments, it may be desirable to employ a multi-component solvent having a composition that corresponds to an azeotrope or which is capable of forming an azeotrope (i.e., an "azeotropic composition") at a temperature employed during the oxidation step (i.e., contacting step), or at a temperature employed during a process that is upstream or downstream of the oxidation step. Use of such multi-component solvents having an azeotropic composition may facilitate the recycling of the oxidation solvent (as part of the azeotropic composition) to the oxidation step, or to processes that occur upstream and/or downstream of the oxidation step.

In some embodiments, the water-miscible organic solvent species is at least 5 volume % (vol%), at least 10 vol%, at least 15 vol%, at least 20 vol%, at least 25 vol%, at least 30 vol%, at least 35 vol%, at least 40 vol%, at least 45 vol%, at least 50 vol%, at least 55 vol%, at least 60 vol%, at least 65 vol%, at least 70 vol%, at least 75 vol%, at least 80 vol%, at least 85 vol%, at least 90 vol%, or at least 95 vol% of the multi-component solvent; and correspondingly, water is typically less than 95 vol%, less than 90 vol%, less than 85 vol%, less than 80 vol%, less than 75 vol%, less than 70 vol%, less than 65 vol%, less than 60 vol%, less than 55 vol%, less than 50 vol%, less than 45 vol%, less than 40 vol%, less than 35 vol%, less than 30 vol%, less than 25 vol%, less than 20 vol%, less than 15 vol%, less than 10 vol%, or less than 5 vol%, respectively, of the multi-component system.

In some embodiments, the multi-component solvent comprises water in a range from or any number in between 1-5 wt% and a water-miscible organic solvent in a range from or any number in between 99-95 wt%. In some embodiments, the multi-component solvent comprises water in a range from or any number in between 5-10 wt% and a water-miscible organic solvent in a range from or any number in between 95-90 wt%. In some embodiments, the multi-component solvent comprises water in a range from or any number in between 10-15 wt% and a water-miscible organic solvent in a range from or any number in between 90-85 wt%. In some embodiments, the multi-component solvent comprises water in a range from or any number in between 15-20 wt% and a water-miscible organic solvent in a range from or any number in between 85-80 wt%. In some embodiments, the multi-component solvent comprises water in a range from or any number in between 20-25 wt% and a water-miscible organic solvent in a range from or any number in between 80-75 wt%.

In some embodiments, the multi-component solvent comprises water in a range from or any number in between 25-30 wt% and a water-miscible organic solvent in a range from or any number in between 75-70 wt%. In some embodiments, the multi-component solvent comprises water in a range from or any number in between 30-35 wt% and a water-miscible organic solvent in a range from or any number in between 70-65 wt%. In some embodiments, the multi-component solvent comprises water in a range from or any number in between 35-40 wt% and a water-miscible organic solvent in a range from or any number in between 65-60 wt%. In some embodiments, the multi-component solvent comprises water in a range from or any number in between 40-45 wt% and a water-miscible organic solvent in a range from or any number in between 60-55 wt%. In some embodiments, the multi-component solvent comprises water in a range from or any number in between 45-50 wt% and a water-miscible organic solvent in a range from or any number in between 65-50 wt%. In some embodiments, the multi-component solvent comprises water in a range from or any number in between 50-55 wt% and a water-miscible organic solvent in a range from or any number in between 50-45 wt%. In some embodiments, the multi-component solvent comprises water in a range from or any number in between 55-60 wt% and a water-miscible organic solvent in a range from or any number in between 45-40 wt%. In some embodiments, the multi-component solvent comprises water in a range from or any number in between 60-65 wt% and a water-miscible organic solvent in a range from or any number in between 40-35 wt%. In some embodiments, the multi-component solvent comprises water in a range from or any number in between 65-70 wt% and a water-miscible organic solvent in a range from or any number in between 35-30 wt%. In some embodiments, the multi-component solvent comprises water in a range from or any number in between 70-75 wt% and a water-miscible organic solvent in a range from or any number in between 30-25 wt%. In some embodiments, the multi-component solvent comprises water in a range from or any number in between 75-80 wt% and a water-miscible organic solvent in a range from or any number in between 25-20 wt%. In some embodiments, the multi-component solvent comprises water in a range from or any number in between 80-85 wt% and a water-miscible organic solvent in a range from or any number in between 20-15 wt%. In some embodiments, the multi-component solvent comprises water in a range from or any number in between 85-90 wt% and a water-miscible organic solvent in a range from or any number in between 15-10 wt%. In some

embodiments, the multi-component solvent comprises water in a range from or any number in between 90-95 wt% and a water-miscible organic solvent in a range from or any number in between 10-5 wt%. In some embodiments, the multi-component solvent comprises water in a range from or any number in between 95-99 wt% and a water-miscible organic solvent in a range from or any number in between 5-1 wt%.

In some embodiments, the volume ratio of water to water-miscible organic solvent is in the range from or any number in between 1:6 to 6:1. In certain embodiments, the volume ratio is from or any number in between 1:4 to 4:1 water:water-miscible organic solvent. In other embodiments, the volume ratio is from or any number in between 1:4 to 3:1

water:water miscible organic solvent. In other embodiments, the volume ratio is from or any number in between 1:3 to 3:1 water:water miscible organic solvent. In certain embodiments, the volume ratio is 1:1 water:water-miscible organic solvent.

In some embodiments, the multi-component solvent comprises water and two different water-miscible organic solvents. Typically both of the water-miscible organic solvents are water-miscible aprotic organic solvents. Each of the two water-miscible aprotic solvents can be independently selected from the group of tetrahydrofuran, a glyme, a dioxane, a dioxolane, dimethylformamide, dimethylsulfoxide, sulfolane, acetone, *N*-methyl-2-pyrrolidone ("NMP"), methyl ethyl ketone ("MEK"), and gamma-valerolactone. One or both of the water-miscible aprotic organic solvent can be an ether, such as, for example, a glyme, dioxane (for example 1,4-dioxane), dioxolane (e.g., 1,3-dioxolane), tetrahydrofuran, and the like. Glymes include, for example, monoglyme (1,2-dimethoxyethane, "DME"), ethyl glyme, diglyme (diethylene glycol dimethyl ether), ethyl diglyme, triglyme, butyl diglyme, tetraglyme, a polyglyme, a highly ethoxylated diether of a high molecular weight alcohol ("higlyme"), and the like.

In some embodiments, the volume ratio of water to the first and second water-miscible organic solvent is approximately 1:1:1 (v:v:v). In some embodiments, the volume ratio of water to the first and second water-miscible organic solvent is approximately 1:2:1 (v:v:v). In some embodiments, the volume ratio of water to the first and second water-miscible organic solvent is approximately 1:2:2 (v:v:v). In some embodiments, the volume ratio of water to the first and second water-miscible organic solvent is approximately 2:1:1 (v:v:v).

In some embodiments, the multi-component solvent comprises water and two different water-miscible organic solvents with the relative amounts of water to the first and second water-miscible organic solvents as shown in Table A.

Table A:

Weight percent of water in multi-component solvent system	Weight percent of first water-miscible organic solvent in multi-component solvent system	Weight percent of second water-miscible organic solvent in multi-component solvent system
1-5%	90-98%	1-5%
1-5%	85-94%	5-10%
1-5%	80-89%	10-15%
1-5%	75-84%	15-20%
1-5%	70-79%	20-25%
1-5%	65-74%	25-30%
1-5%	60-69%	30-35%
1-5%	55-64%	35-40%
1-5%	50-59%	40-45%
1-5%	45-54%	45-50%
1-5%	40-49%	50-55%
1-5%	35-44%	55-60%
1-5%	30-39%	60-65%
1-5%	25-34%	65-70%
1-5%	20-29%	70-75%
1-5%	15-24%	75-80%
1-5%	10-19%	80-85%
1-5%	5-14%	85-90%
1-5%	1-9%	90-94%
5-10%	85-94%	1-5%
5-10%	80-90%	5-10%
5-10%	75-85%	10-15%
5-10%	70-80%	15-20%
5-10%	65-75%	20-25%
5-10%	60-70%	25-30%
5-10%	55-65%	30-35%
5-10%	50-60%	35-40%
5-10%	45-55%	40-45%
5-10%	40-50%	45-50%
5-10%	35-45%	50-55%
5-10%	30-40%	55-60%
5-10%	25-35%	60-65%
5-10%	20-30%	65-70%
5-10%	15-25%	70-75%
5-10%	10-20%	75-80%
5-10%	5-15%	80-85%
5-10%	1-10%	85-89%
10-15%	80-89%	1-5%
10-15%	75-85%	5-10%
10-15%	70-80%	10-15%

Weight percent of water in multi-component solvent system	Weight percent of first water-miscible organic solvent in multi-component solvent system	Weight percent of second water-miscible organic solvent in multi-component solvent system
10-15%	65-75%	15-20%
10-15%	60-70%	20-25%
10-15%	55-65%	25-30%
10-15%	50-60%	30-35%
10-15%	45-55%	35-40%
10-15%	40-50%	40-45%
10-15%	35-45%	45-50%
10-15%	30-40%	50-55%
10-15%	25-35%	55-60%
10-15%	20-30%	60-65%
10-15%	15-25%	65-70%
10-15%	10-20%	70-75%
10-15%	5-15%	75-80%
10-15%	1-10%	80-84%
15-20%	75-84%	1-5%
15-20%	70-80%	5-10%
15-20%	65-75%	10-15%
15-20%	60-70%	15-20%
15-20%	55-65%	20-25%
15-20%	50-60%	25-30%
15-20%	45-55%	30-35%
15-20%	40-50%	35-40%
15-20%	35-45%	40-45%
15-20%	30-40%	45-50%
15-20%	25-35%	50-55%
15-20%	20-30%	55-60%
15-20%	15-25%	60-65%
15-20%	10-20%	65-70%
15-20%	5-15%	70-75%
15-20%	1-10%	75-79%
20-25%	70-79%	1-5%
20-25%	65-75%	5-10%
20-25%	60-70%	10-15%
20-25%	55-65%	15-20%
20-25%	50-60%	20-25%
20-25%	45-55%	25-30%
20-25%	40-50%	30-35%
20-25%	35-45%	35-40%
20-25%	30-40%	40-45%
20-25%	25-35%	45-50%
20-25%	20-30%	50-55%
20-25%	15-25%	55-60%
20-25%	10-20%	60-65%
20-25%	5-15%	65-70%
20-25%	1-10%	70-74%
25-30%	65-74%	1-5%

Weight percent of water in multi-component solvent system	Weight percent of first water-miscible organic solvent in multi-component solvent system	Weight percent of second water-miscible organic solvent in multi-component solvent system
25-30%	60-70%	5-10%
25-30%	55-65%	10-15%
25-30%	50-60%	15-20%
25-30%	45-55%	20-25%
25-30%	40-50%	25-30%
25-30%	35-45%	30-35%
25-30%	30-40%	35-40%
25-30%	25-35%	40-45%
25-30%	20-30%	45-50%
25-30%	15-25%	50-55%
25-30%	10-20%	55-60%
25-30%	5-15%	60-65%
25-30%	1-10%	65-69%
30-35%	60-69%	1-5%
30-35%	55-65%	5-10%
30-35%	50-60%	10-15%
30-35%	45-55%	15-20%
30-35%	40-50%	20-25%
30-35%	35-45%	25-30%
30-35%	30-40%	30-35%
30-35%	25-35%	35-40%
30-35%	20-30%	40-45%
30-35%	15-25%	45-50%
30-35%	10-20%	50-55%
30-35%	5-15%	55-60%
30-35%	1-10%	60-64%
35-40%	55-64%	1-5%
35-40%	50-60%	5-10%
35-40%	45-55%	10-15%
35-40%	40-50%	15-20%
35-40%	35-45%	20-25%
35-40%	30-40%	25-30%
35-40%	25-35%	30-35%
35-40%	20-30%	35-40%
35-40%	15-25%	40-45%
35-40%	10-20%	45-50%
35-40%	5-15%	50-55%
35-40%	1-10%	55-59%
40-45%	50-59%	1-5%
40-45%	45-55%	5-10%
40-45%	40-50%	10-15%
40-45%	35-45%	15-20%
40-45%	30-40%	20-25%
40-45%	25-35%	25-30%
40-45%	20-30%	30-35%
40-45%	15-25%	35-40%

Weight percent of water in multi-component solvent system	Weight percent of first water-miscible organic solvent in multi-component solvent system	Weight percent of second water-miscible organic solvent in multi-component solvent system
40-45%	10-20%	40-45%
40-45%	5-15%	45-50%
40-45%	1-10%	50-54%
45-50%	45-54%	1-5%
45-50%	40-50%	5-10%
45-50%	35-45%	10-15%
45-50%	30-40%	15-20%
45-50%	25-35%	20-25%
45-50%	20-30%	25-30%
45-50%	15-25%	30-35%
45-50%	10-20%	35-40%
45-50%	5-15%	40-45%
45-50%	1-10%	45-49%
50-55%	40-49%	1-5%
50-55%	35-45%	5-10%
50-55%	30-40%	10-15%
50-55%	25-35%	15-20%
50-55%	20-30%	20-25%
50-55%	15-25%	25-30%
50-55%	10-20%	30-35%
50-55%	5-15%	35-40%
50-55%	1-10%	40-44%
55-60%	35-44%	1-5%
55-60%	30-40%	5-10%
55-60%	25-35%	10-15%
55-60%	20-30%	15-20%
55-60%	15-25%	20-25%
55-60%	10-20%	25-30%
55-60%	5-15%	30-35%
55-60%	1-10%	35-39%
60-65%	30-39%	1-5%
60-65%	25-35%	5-10%
60-65%	20-30%	10-15%
60-65%	15-25%	15-20%
60-65%	10-20%	20-25%
60-65%	5-15%	25-30%
60-65%	1-10%	30-34%
65-70%	25-34%	1-5%
65-70%	20-30%	5-10%
65-70%	15-25%	10-15%
65-70%	10-20%	15-20%
65-70%	5-15%	20-25%
70-75%	20-29%	1-5%
70-75%	15-25%	5-10%
70-75%	10-20%	10-15%
70-75%	5-15%	15-20%

Weight percent of water in multi-component solvent system	Weight percent of first water-miscible organic solvent in multi-component solvent system	Weight percent of second water-miscible organic solvent in multi-component solvent system
75-80%	15-24%	1-5%
75-80%	10-20%	5-10%
75-80%	5-15%	10-15%

The contacting step is often carried out for a time sufficient to produce a product solution comprising (soluble) FDCA pathway product at a concentration of at least 2 wt%, at least 3 wt%, at least 4 wt%, at least 5 wt%, at least 6 wt%, at least 7 wt%, at least 8 wt%, at least 9 wt%, at least 10 wt%, at least 11 wt%, at least 12 wt%, at least 13 wt%, at least 14 wt%, or at least 15 wt% or at a concentration that is within a range defined by any two of the
5 aforementioned values. Correspondingly, when a product solution is produced that comprises the (soluble) FDCA pathway product it is produced at a concentration of at least 2 wt%, at least 3 wt%, at least 4 wt%, at least 5 wt%, at least 6 wt%, at least 7 wt%, at least 8 wt%, at least 9 wt%, at least 10 wt%, at least 11 wt%, at least 12 wt%, at least 13 wt%, at least 14 wt%, or at least 15 wt%) or a at concentration that is within a range defined by any
10 two of the aforementioned values. The term "product solution" refers herein to a solution of soluble FDCA pathway product and other soluble components of the reaction mixture in the oxidation solvent. The phrase "a time sufficient to produce a product solution comprising the FDCA pathway product at a concentration of" is used herein to refer to a minimum amount
15 of time required to produce the specified concentration of the FDCA pathway product in the product solution.

More typically, the contacting step is carried out for a time sufficient to produce a product solution comprising the FDCA pathway product at a concentration of at least 6 wt%, at least 7 wt%, at least 8 wt%, at least 9 wt%, at least 10 wt%, at least 11 wt%, at least 12 wt%, at least 13 wt%, at least 14 wt%, or at least 15 wt% or at a concentration that is within a
20 range defined by any two of the aforementioned values. Correspondingly, when a product solution is produced that comprises the FDCA pathway product it is produced at a concentration of at least 6 wt%, at least 7 wt%, at least 8 wt%, at least 9 wt%, at least 10 wt%, at least 11 wt%, at least 12 wt%, at least 13 wt%, at least 14 wt%, or at least 15 wt%,
25 respectively or a concentration that is within a range defined by any two of the aforementioned values.

Heterogeneous oxidation catalysts employed in the practice of the present disclosure typically have the noble metal dispersed on the internal and external surfaces of the support. The term "noble metal" refers herein to ruthenium, rhodium, palladium, silver, osmium, iridium, platinum or gold. In certain preferred embodiments, the metal is selected from the group consisting of platinum, gold, and a combination thereof. Typically, the metal is platinum. In some embodiments, the metal is gold. The heterogeneous oxidation catalyst may further include a promoter to enhance the performance of the heterogeneous oxidation catalyst. When the metal is platinum, gold, or combination thereof, suitable promoters include, for example, Pd, Ir, Mo, or W, and the like.

The heterogeneous oxidation catalyst typically comprises the noble metal at a total metal loading in the range of from or any number in between 0.3% to 5% by weight. In some embodiments, the metal loading is in the range of from or any number in between 0.5% to 4% by weight. In some embodiments, the metal loading ranges from or any number in between 2-4 wt%. In some embodiments, the metal loading is 2 wt%. In some embodiments, the metal loading is 3 wt%. In some embodiments, the metal loading is 4 wt%. When two or more metals are employed, the heterogeneous oxidation catalyst may comprise a plurality of heterogeneous oxidation catalyst particles, each comprising the two or more metals, or the heterogeneous oxidation catalyst may comprise a mixture of heterogeneous oxidation catalyst metal-particle species, e.g., a first plurality of heterogeneous oxidation catalyst particles comprising a first metal species and a second plurality of heterogeneous oxidation catalyst particles comprising a second metal species. Methods for preparing the heterogeneous oxidation catalysts employed in the practice of the present disclosure are described in detail in section II, herein below, as well as in the Examples.

The solid support component of the heterogeneous oxidation catalyst may comprise any type of material known by those having ordinary skill in the art as being suitable for use as a catalytic support that also has the specific surface area requirement described herein. Suitable materials include, for example, a metal oxide, a carbonaceous material, a polymer, a metal silicate, a metal carbide, or any composite material prepared therefrom. Exemplary metal oxides include silicon oxide (silica), zirconium oxide (zirconia), titanium oxide (titania), or aluminum oxide (alumina), and the like. As used herein, the term "carbonaceous" refers to graphite and carbon black. Exemplary metal silicates include, for

example, an orthosilicate, a borosilicate, or an aluminosilicate (e.g., a zeolite), and the like. Exemplary metal carbides include, for example, silicon carbide, and the like. Suitable polymeric solid support materials include polystyrene, polystyrene-co-divinyl benzene, polyamides, or polyacrylamides, and the like.

5 Suitable solid support materials also include a composite material prepared from, or comprising a binder and a material selected from the group consisting of a metal oxide, a carbonaceous material, a polymer, a metal silicate, and a metal carbide. In some embodiments, the binder is a resin. In other embodiments, the composite material comprises a carbonized binder and a material selected from the group consisting of a metal oxide, a
10 carbonaceous material, a metal silicate, and a metal carbide. In one embodiment, the composite material comprises a carbonized binder and carbon black. Methods for making such carbon-based composite materials is described in PCT Application No. PCT/US15/28358, which is expressly incorporated herein by reference in its entirety. Illustrative support materials are described in the Examples herein.

15 In some embodiments, the solid support comprises a carbon black material selected from the group consisting of Aditya Birla CDX-KU, Aditya Birla CSCUB, Aditya Birla R2000B, Aditya Birla R2500UB, Aditya Birla R3500B, Aditya Birla R5000U2, Arosperse 5-183A, Asbury 5302, Asbury 5303, Asbury 5345, Asbury 5348R, Asbury 5358R, Asbury 5365R, Asbury 5368, Asbury 5375R, Asbury 5379, Asbury A99, Cabot Monarch 120, Cabot Monarch 280, Cabot Monarch
20 570, Cabot Monarch 700, Cabot Norit Darco 12x20L1, Cabot Vulcan XC72, Continental N120, Continental N234, Continental N330, Continental N330-C, Continental N550, Norit ROX 0.8, Orion Arosperse 138, Orion Arosperse 15, Orion Color Black FW 2, Orion Color Black FW 255, Orion HiBlack 40B2, Orion Hi-Black 50 L, Orion Hi-Black 50 LB, Orion Hi-Black 600 L, Orion HP-160, Orion Lamp Black 101, Orion N330, Orion Printex L6, Sid Richardson Ground N115,
25 Sid Richardson Ground SR155, Sid Richardson SC159, Sid Richardson SC419, Timcal Ensaco 150G, Timcal Ensaco 250G, Timcal Ensaco 260G, and Timcal Ensaco 350G.

 Metal impregnation of the solid support typically results in a negligible change in the specific surface, pore diameters, and specific volume of the solid support. Heterogeneous oxidation catalysts that are suitable for use in the present disclosure are typically prepared
30 using a solid support that comprises a plurality of pores and a specific surface area in the range of from 20 m²/g to 500 m²/g, such as e.g., 20, 30, 40, 50, 60, 70, 80, 90, 100, 120, 140, 160, 180, 200, 225, 250, 275, 300, 325, 350, 375, 400, 425, 450, 475, or 500 m²/g or is

within a range defined by any two of the aforementioned surface areas. Specific surface area can be determined using known methods, such as, for example, the method of Bruanauer, Emmett and Teller (*J. Am. Chem. Soc.* 1938, 60:309-311) and/or mercury porosimetry. See e.g., ASTM Test Methods D3663, D6556, and D4567, each of which is incorporated by
5 reference in its entirety. Typically, heterogeneous oxidation catalysts (and solid supports) employed in the practice of the present disclosure have a specific surface area in the range of from or any number in between $25 \text{ m}^2/\text{g}$ to $250 \text{ m}^2/\text{g}$, and sometimes in the range of from or any number in between $25 \text{ m}^2/\text{g}$ to $225 \text{ m}^2/\text{g}$, or from or any number in between $25 \text{ m}^2/\text{g}$ to $200 \text{ m}^2/\text{g}$, or from or any number in between $25 \text{ m}^2/\text{g}$ to $175 \text{ m}^2/\text{g}$, or from or any number in
10 between $25 \text{ m}^2/\text{g}$ to $150 \text{ m}^2/\text{g}$, or from or any number in between $25 \text{ m}^2/\text{g}$ to $125 \text{ m}^2/\text{g}$, or from or any number in between $25 \text{ m}^2/\text{g}$ to $100 \text{ m}^2/\text{g}$. These specific surface areas are relatively low when compared to highly porous catalytic support materials that are more typically used in the art, such as, for example, activated carbon. The relatively low surface area of the heterogeneous oxidation catalysts employed in the oxidative processes of the
15 present disclosure is believed to favorably contribute to the high selectivity and yields observed with respect to the conversion of the furanic oxidation substrates to FDCA and FDCA pathway intermediate compounds under substantially base-free conditions.

Commensurate with the relatively low specific surface areas, the heterogeneous oxidation catalysts (and solid support components thereof) employed in the practice of the
20 present disclosure also typically have relatively moderate to low specific pore volumes when compared to other oxidation catalysts. Heterogeneous oxidation catalysts (and solid support components thereof) employed in the practice of the present disclosure typically have a specific pore volume (determined on the basis of pores having a diameter of 1.7 nm to 100 nm) that is, from or any number in between $0.1 \text{ cm}^3/\text{g}$ to $1.5 \text{ cm}^3/\text{g}$, from or any number in
25 between $0.1 \text{ cm}^3/\text{g}$ to $0.8 \text{ cm}^3/\text{g}$, from or any number in between $0.1 \text{ cm}^3/\text{g}$ to $0.7 \text{ cm}^3/\text{g}$, from or any number in between $0.1 \text{ cm}^3/\text{g}$ to $0.6 \text{ cm}^3/\text{g}$, from or any number in between $0.1 \text{ cm}^3/\text{g}$ to $0.5 \text{ cm}^3/\text{g}$, from or any number in between $0.2 \text{ cm}^3/\text{g}$ to $0.8 \text{ cm}^3/\text{g}$, from or any number in between $0.2 \text{ cm}^3/\text{g}$ to $0.7 \text{ cm}^3/\text{g}$, from or any number in between $0.2 \text{ cm}^3/\text{g}$ to $0.6 \text{ cm}^3/\text{g}$, from
30 or any number in between $0.2 \text{ cm}^3/\text{g}$ to $0.5 \text{ cm}^3/\text{g}$, from or any number in between $0.3 \text{ cm}^3/\text{g}$ to $1 \text{ cm}^3/\text{g}$, from or any number in between $0.3 \text{ cm}^3/\text{g}$ to $0.9 \text{ cm}^3/\text{g}$, from or any number in between $0.3 \text{ cm}^3/\text{g}$ to $0.8 \text{ cm}^3/\text{g}$, from or any number in between $0.3 \text{ cm}^3/\text{g}$ to $0.7 \text{ cm}^3/\text{g}$, from

or any number in between $0.3 \text{ cm}^3/\text{g}$ to $0.6 \text{ cm}^3/\text{g}$, or from or any number in between $0.3 \text{ cm}^3/\text{g}$ to $0.5 \text{ cm}^3/\text{g}$ or within a range defined by any two of the aforementioned values, as measured by a method for determining pore diameters and specific pore volumes, such as that described in E.P. Barrett, L.G. Joyner, P.P. Halenda, *J. Am. Chem. Soc.* (1951) 73:373-380 and ASTM D4222-03 (2008) (the method referred to herein as the "BJH method"), both of which are expressly incorporated herein by reference in their entireties, and by the method of mercury porosimetry (e.g., using a mercury porosimeter, such as, for example, the Micromeritics Autopore V 9605 Mercury Porosimeter (Micromeritics Instrument Corp., Norcross, GA) in accordance with the manufacturer's instructions). See e.g., ASTM 3663, ASTM D-4284-12 and D6761-07 (2012), all of which are incorporated herein by reference.

Typically, the heterogeneous oxidation catalyst has a mean pore diameter in the range of from or any number in between 10 nm to 100 nm, as measured by the BJH method and/or mercury porosimetry. More typically, the heterogeneous oxidation catalyst has a mean pore diameter in the range of from or any number in between 10 nm to 90 nm, as measured by the BJH method and/or mercury porosimetry. In some embodiments, the mean pore diameter is in the range of from or any number in between 10 nm to 80 nm, or from or any number in between 10 nm to 70 nm, or from or any number in between 10 nm to 60 nm, and often from or any number in between 10 nm to 50 nm, as determined by the BJH method and/or mercury porosimetry. In some embodiments, the mean pore diameter is in the range of from or any number in between 20 nm to 100 nm, as measured by the BJH method and/or mercury porosimetry. In certain of these embodiments, the mean pore diameter is in the range from or any number in between 20 nm to 90 nm, or from or any number in between 20 nm to 80 nm, or from or any number in between 20 nm to 70 nm, or from or any number in between 20 nm to 60 nm, or from or any number in between 10 nm to 50 nm, as determined by the BJH method and/or mercury porosimetry. The catalysts employed in the practice of the present disclosure typically have a relatively high concentration of pores in the size ranges described above.

In some embodiments, the heterogeneous oxidation catalyst comprises a second plurality of pores. In this embodiment, the pore size distribution of the heterogeneous oxidation catalyst and underlying solid support is bimodal, having a first distribution made up of a first plurality of pore diameters and a second distribution made up of a second

plurality of pore diameters, with each plurality having a mean pore diameter associated with it. The second plurality of pores has a mean pore diameter that is different from the mean pore diameter of the second plurality, yet is typically still in the range of from or any number in between 10 nm to 100 nm, as determined by the BJH method and/or mercury porosimetry.

5 Typically, the heterogeneous oxidation catalysts comprise a pore volume, wherein at least 50% of the pore volume is attributable to pores having a pore diameter in the range of from or any number in between 5 nm to 100 nm (as determined by the BJH method and/or mercury porosimetry on the basis of pores having a diameter of from 1.7 nm to 100 nm). Typically, the heterogeneous oxidation catalyst has a pore volume, wherein at least 60%, and
10 in some embodiments, at least 70%, or at least 80%, or at least 90% of the pore volume is attributable to pores having pore diameter of from or any number in between 10 nm to 100 nm (as determined by the BJH method and/or mercury porosimetry on the basis of pores having a diameter of from 1.7 nm to 100 nm).

In some embodiments, at least 35%, at least 40%, at least 45%, or at least 50% of the
15 pore volume of the heterogeneous oxidation catalysts employed in the practice of the present disclosure (as measured by the BJH method and/or mercury porosimetry on the basis of pores having a diameter from 1.7 nm to 100 nm) is attributable to pores having a pore diameter of from or any number in between 10 nm to 50 nm. For example, from or any number in between 35% to 80%, from or any number in between 35% to 75%, from or any number in
20 between 35% to 65%, from or any number in between 40% to 80%, from or any number in between 40% to 75%, or from or any number in between 40% to 70% of the pore volume of the heterogeneous oxidation catalyst is attributable to pores having a mean pore diameter in the range from or any number in between 10 nm to 50 nm (as measured by the BJH method and/or mercury porosimetry on the basis of pores having a diameter from 1.7 nm to 100 nm).

25 Typically, no more than 2.5 % of the pore volume of the heterogeneous oxidation catalyst is attributable to pores having a pore diameter of less than 10 or 5 nm. More typically, no more than 3%, or no more than 4%, or no more than 5%, or no more than 10% or no more than a value that is within a range defined by any two of the aforementioned percentages of the pore volume of the heterogeneous oxidation catalyst is attributable to
30 pores having a pore diameter of less than 10 or 5 nm, as determined by the BJH method and/or mercury porosimetry. To prepare heterogeneous oxidation catalysts that are suitable

for use in the practice of the present disclosure, solid supports are selected which possess the foregoing physical properties. The pore structure of the support material is typically retained in the finished heterogeneous oxidation catalyst after metal impregnation.

In certain preferred embodiments, the noble metal in the heterogeneous oxidation catalyst comprises or consists essentially of platinum, and in some embodiments consists of platinum, and in each case, wherein the solid support is selected from the group consisting of silica and a carbonaceous material. In these preferred embodiments, the heterogeneous oxidation catalyst typically comprises a mean pore diameter in the range of from or any number in between 10 nm to 100 nm, and often in the range of from or any number in between 20 nm to 100 nm, as determined by the BJH method and/or mercury porosimetry.

In carrying out the processes of the present disclosure, oxygen may be provided in neat form (i.e., O₂ only, with no other gases) or as a component of a mixture of gases (e.g., air, oxygen-enriched air, and the like). The molar ratio of oxygen to the furanic oxidation substrate during the contacting step is typically in the range of from 2:1 to 10:1. In some embodiments, the molar ratio of oxygen to the furanic oxidation substrate is from 2:1 to 10:1, or from 3:1 to 5:1. During the contacting step, oxygen is typically present at a partial pressure in the range of from or any number in between 50 psig to 1000 psig. More typically, oxygen is present at a partial pressure in the range of from or any number in between 50 psig to 200 psig. In some embodiments, oxygen is present at a partial pressure in the range from or any number in between 50-200 psig, 100-300 psig, 200-400 psig, 300-500 psig, 400-600 psig, 500-700 psig, 600-800 psig, 700-900 psig, or 800-1000 psig, or within a range defined by any two of the aforementioned partial pressures.

The contacting (oxidation) step is typically carried out at a temperature in the range of from or any number in between 50°C to 200°C. In some embodiments, the contacting step is carried out at a temperature in the range of from or any number in between 80°C to 180°C, and in other embodiments, the contacting step carried out at a temperature in the range from or any number in between 90°C to 160°C or from or any number in between 100°C to 160°C. In certain preferred embodiments, the contacting step is carried out at a temperature in the range of from or any number in between 90°C to 180°C, and sometimes it is carried out at a temperature in the range of from or any number in between 110°C to 160°C.

An illustrative process for carrying out the production of the desired FDCA pathway

product from a furanic oxidation substrate is depicted in Figure 4. In this process, which utilizes a single oxidation reaction zone, an oxygen feed stream **110** comprising O₂ (in neat form or as a component of a mixture of gases) and a furanic oxidation substrate feedstock stream **100** are passed into an oxidation zone **10** to produce an FDCA pathway product stream **127** and an optional recycle stream **115**, which comprises unreacted furanic oxidation substrate.

In some embodiments, it may be desirable to carry out the oxidation of the furanic oxidation substrate to the desired FDCA pathway product in a series of two or more oxidation steps, where the first oxidation step is as described above, and where the second oxidation step comprises:

(b) contacting a second oxidation feedstock comprising a second furanic oxidation substrate and a second oxidation solvent with oxygen in the presence of a second heterogeneous oxidation catalyst under conditions sufficient to form a second reaction mixture for oxidizing the second furanic oxidation substrate to produce a second FDCA pathway product,

wherein (the first) contacting step (a) produces a first FDCA pathway product that is an FDCA pathway intermediate compound, either alone or together with FDCA,

wherein the second furanic oxidation substrate is the first FDCA pathway product,

wherein the second reaction mixture is substantially free of added base, and

wherein the second heterogeneous oxidation catalyst comprises a second solid support and a noble metal that may be the same or different from the (first) noble metal in step (a), and

wherein the second heterogeneous oxidation catalyst comprises a plurality of pores and a specific surface area in the range of from or any number in between 20 m²/g to 500 m²/g, such as e.g., 20, 30, 40, 50, 60, 70, 80, 90, 100, 120, 140, 160, 180, 200, 225, 250, 275, 300, 325, 350, 375, 400, 425, 450, 475, or 500 m²/g or is within a range defined by any two of the aforementioned surface areas.

The second FDCA pathway product is a downstream oxidation product of the first FDCA pathway product, and is typically FFCA, or FDCA. Typically, the second FDCA pathway product is FDCA. Usually, the second oxidation step is free of added base.

Noble metals, catalyst metal loadings, solid support materials, and reaction conditions (e.g., reaction temperatures, oxygen (partial) pressure, molar ratio of oxygen to furanic oxidation substrate, and the like) that are suitable for using in the first oxidation process are also suitable for using in the second oxidation process. The second heterogeneous oxidation catalyst may be the same or different than that used in the first oxidation process (i.e., the "first" heterogeneous oxidation catalyst). Oxidation solvents that are suitable for use in the second oxidation feedstock are the same as those that are suitable for use in the first oxidation process (i.e., the "first oxidation solvent"). The multi-stage oxidation process format may be desirable if optimal production of the desired FDCA pathway product requires a change in reaction conditions during the course of conversion from the furanic oxidation substrate to the desired FDCA pathway product. For example, it may be desirable to carry out the second oxidation reaction at a higher or lower temperature than the first oxidation reaction, or maintain the molar ratio of oxygen to feedstock component in the second oxidation reaction at a higher or lower ratio than in the first oxidation reaction, or maintain the partial pressure of oxygen in the second oxidation reaction at a higher or lower partial pressure than in the first oxidation reaction. The composition of the second oxidation solvent may be the same as the composition of the first oxidation solvent or it may be different. If it is different, it may still have in common one or more of the same solvent species component. The noble metal in the second heterogeneous oxidation catalyst is typically platinum, gold, or a combination thereof. Usually, the noble metal used in the second heterogeneous oxidation catalyst is platinum.

In certain preferred embodiments, the noble metal in the second heterogeneous oxidation catalyst comprises or consists essentially of platinum, and in some embodiments consists of platinum, and in each case, wherein the second solid support is selected from the group consisting of silica and a carbonaceous material. In these preferred embodiments, the second heterogeneous oxidation catalyst typically comprises a mean pore diameter in the range of from or any number in between 10 nm to 100 nm, and often in the range of from or any number in between 20 nm to 100 nm, such as e.g., 10, 20, 30, 40, 50, 60, 70, 80, 90, or 100 nm or within a range defined by any two of the aforementioned mean pore diameters.

Figure 5 provides an illustrative integrated process for carrying out the production of the desired FDCA pathway product in two stages, using two oxidation reaction zones in

series: oxidation reaction zone 1 **20** and oxidation reaction zone 2 **30**. In this integrated process, an oxidant feed stream **110** comprising O₂, and a furanic oxidation substrate feedstock stream **100** are passed into oxidation reaction zone **20** to produce oxidation reaction zone 1 product stream **120**. Oxidation reaction zone 1 product stream comprises an FDCA pathway intermediate compound and the oxidation solvent. Product stream **120**, and oxidant feed stream **112** comprising O₂ are then passed into a oxidation reaction zone 2 **30** to produce oxidation reaction zone product stream **130** and an optional recycle stream **125** which comprises unreacted furanic oxidation substrate. Oxidation reaction zone product stream **130** comprises an oxidized product of the FDCA pathway intermediate compound from oxidation reaction zone **30**, which may be FDCA and/or an FDCA pathway intermediate that, in either case, is an oxidation product of the FDCA pathway intermediate present in oxidation reaction zone 1 product stream **120**.

The processes of the present disclosure may be carried out in batch, semi-batch, or continuous reactor format using reactors known in the art, such as, for example, fixed bed reactors, trickle bed reactors, slurry phase reactors, moving bed reactors, and the like. The relatively high solubilities of reactants and products (particularly, the FDCA pathway product) in the oxidation solvent facilitate the use of all such reactor formats, and particularly the fixed bed reactor format.

FDCA pathway product(s) produced by the oxidation processes described herein may be recovered from the reaction mixture by separating the heterogeneous oxidation catalyst from a product solution comprising the FDCA pathway product(s) and the oxidation solvent. The product solution includes the oxidation solvent and soluble components of the reaction mixture and excludes the heterogeneous oxidation catalyst. The product solution may be further concentrated with respect to the soluble components by removal of a portion of the oxidation solvent. Oxidation solvent removal may be accomplished by evaporation (e.g., by using an evaporator), distillation, and the like.

Alternatively, or further to the isolation step, the FDCA pathway product may be purified. Preferably, the FDCA pathway product is purified by crystallization. Thus, in one embodiment, the present disclosure provides a process for producing a crystalline FDCA pathway product composition, the method comprising:

providing a crystallization solution comprising an FDCA pathway product and a crystallization solvent that is a solvent selected from the group consisting of an organic solvent and a multi-component solvent; initiating crystallization of the FDCA pathway product; and producing a plurality of FDCA pathway product crystals of different particle sizes.

As used herein, the term "crystallization solvent" refers to a solvent from which the FDCA pathway product can be crystallized when conditions are imposed that cause a reduction in solubility of the FDCA pathway product in the crystallization solvent (e.g., temperature reduction (cooling) or solvent removal). The crystallization solvent may be water, an organic solvent, or a multi-component solvent comprising water and a water-miscible organic solvent or two or more organic solvent species. The crystallization process may directly follow the oxidation process (e.g., either a single stage oxidation process or multi-stage oxidation process), or it may follow other unit operations downstream of the oxidation process.

When crystallization follows FDCA pathway product generation, the crystallization solution is typically a product solution comprising the FDCA pathway product and the oxidation solvent. In such embodiment, therefore, the crystallization solvent is the same as the oxidation solvent (e.g., the first oxidation solvent (single stage oxidation) or the second oxidation solvent (for two-stage oxidation)). Some solvents that are suitable for use in the oxidation solvent are also suitable for use as the crystallization solvent.

Industrial solution phase crystallizations are typically performed by introducing a saturated (or super-saturated) solution of the product into a crystallizer in which the solution is subjected to crystallization conditions, and crystallization is initiated by, for example, lowering the temperature or concentrating the solution by solvent evaporation (i.e., solvent removal), or a combination of both. Solvent evaporation may be used to concentrate the solution to initiate crystallization, and may also be used to adjust the solvent composition to lower the solubility of the FDCA pathway product. As used herein, the term "crystallization conditions" refers to an adjustment in temperature and/or adjustment in crystallization solution concentration and/or adjustment in crystallization solution composition that causes the initiation of crystallization of the FDCA pathway product.

In one embodiment where crystallization conditions include a temperature adjustment, the present disclosure provides a process for producing a crystalline FDCA preparation, the method comprising:

providing a crystallization solution comprising the FDCA pathway product and a crystallization solvent at a first temperature in the range of or any number in between 50 °C to 220 °C, such as e.g., 50, 60, 70, 80, 90, 100, 110, 120, 130, 140, 150, 160, 180, 190, 200, 210, or 220 °C or within a range defined by any two of the aforementioned temperatures; and

cooling the crystallization solution to a second temperature that is lower than the first temperature to form a plurality of FDCA pathway product crystals of different particle sizes.

Cooling reduces the solubility of the FDCA pathway product in the crystallization solvent, causing crystals of FDCA pathway product to form in the solution. The first temperature is typically in the range of from or any number in between 60°C to 180°C, such as e.g., 60, 70, 80, 90, 100, 110, 120, 130, 140, 150, 160, or 180 °C or within a range defined by any two of the aforementioned temperatures. In some embodiments, the first temperature is in the range from or any number in between 70°C to 150°C such as e.g., 70, 80, 90, 100, 110, 120, 130, 140, or 150 °C or within a range defined by any two of the aforementioned temperatures. When the crystallization solution is cooled, it is typically cooled to a temperature that is at or below 60°C, such as e.g., equal to or less than 60, 50, 40, 30, 20, 10, 5, or 0 °C or within a range defined by any two of the aforementioned temperatures. More typically, it is cooled to a temperature at or below 50°C or at or below 40°C such as, e.g., equal to or less than 50, 40, 30, 20, 10, 5, or 0 °C or within a range defined by any two of the aforementioned temperatures.

In an embodiment where solvent removal (evaporation) is used to initiate crystallization, the present disclosure provides a method for producing a crystalline FDCA preparation, the method comprising:

(a) providing a first crystallization solution comprising FDCA and a first crystallization solvent selected from the group consisting of water, an organic solvent, and combinations thereof;

(b) removing a first portion of the first crystallization solvent from the first crystallization solution to produce a first FDCA pathway product slurry, wherein the first

FDCA pathway product slurry comprises a first plurality of FDCA pathway product crystals and a second portion of the first crystallization solvent; and

(c) separating the first plurality of FDCA pathway product crystals from the second portion of the first crystallization solvent.

5 In a further embodiment, the first plurality of FDCA pathway product crystals are recrystallized, by conducting the following additional steps:

(d) dissolving the first plurality of FDCA crystals in a second crystallization solvent to produce a second crystallization solution comprising FDCA and the second crystallization solvent; and

10 (e) removing a first portion of the second crystallization solvent from the second crystallization solution to produce a second FDCA pathway product slurry, wherein the second FDCA pathway product slurry comprises a second plurality of FDCA pathway product crystals and a second portion of the second crystallization solvent; and

(f) separating the second plurality of FDCA pathway product crystals from the
15 second portion of the second crystallization solvent.

Removal of a portion of the crystallization solvent can be accomplished using known methods for removing solvents from a solution, such as, for example, evaporation, or distillation, and the like. Solvent removal may be facilitated by raising the temperature of the crystallization solution to effect vaporization of the crystallization solvent, or component
20 thereof, resulting in one portion of the crystallization solvent being in a liquid phase and another portion being in a vapor phase, which is removed. Solvent removal results in an increase in concentration of the FDCA pathway product causing it to crystallize, thereby resulting in a slurry of FDCA pathway product crystals in a continuous liquid phase. Often, one or both of the first and second crystallization solvents is/are a multi-component solvent,
25 where removing a first portion of the first and/or second crystallization solvents may involve removing all or part of one of the components of the multi-component solvent, and less or none of the other components. In these embodiments, the multi-component solvent may comprise one organic solvent species that is a light organic solvent and a second organic species that is a heavy organic solvent; or alternatively, it may comprise water and an
30 organic solvent that is either a heavy or light, water-miscible organic solvent.

Separation of the first plurality of FDCA pathway product crystals and the second plurality of FDCA pathway product crystals from the second portion of the first crystallization solvent and the second portion of the second crystallization solvent, respectively, can be accomplished using known methods for separating solids from liquids, such as, for example, filtration, centrifugation, and the like.

The dissolving step (step (c)) is typically carried out at an elevated temperature to facilitate the dissolution of the first plurality of FDCA pathway product crystals in the second crystallization solvent. The temperature will depend on the crystallization solvent employed, but can be readily determined by raising the temperature, and optionally adding more second crystallization solvent, until the first plurality of FDCA pathway product crystals has dissolved completely. Typically, the dissolving step is carried out at a temperature in the range from or any number in between 50°C to 220°C, such as e.g., 50, 60, 70, 80, 90, 100, 110, 120, 130, 140, 150, 160, 180, 190, 200, 210, or 220 °C or within a range defined by any two of the aforementioned temperatures. Often, the dissolving step is carried out at a temperature in the range from or any number in between 60°C to 180°C, or in the range from or any number in between 70°C to 150°C such as e.g., 60, 70, 80, 90, 100, 110, 120, 130, 140, 150, 160, 170, or 180 °C or within a range defined by any two of the aforementioned temperatures. In some embodiments, the dissolving step is carried out at the higher end of these ranges, such as, for example, in the range from or any number in between 100°C to 220°C, or from or any number in between 150°C to 220°C, such as e.g., 100, 110, 120, 130, 140, 150, 160, 180, 190, 200, 210, or 220 °C or within a range defined by any two of the aforementioned temperatures.

The first and second crystallization solvent may be the same or different. In certain embodiments, at least one of the first and second crystallization solvents is a multi-component solvent that comprises a component solvent species common to both crystallization solvents. In some embodiments, the first crystallization solution comprising the FDCA pathway product is a product solution comprising the FDCA pathway product that results from the oxidation of the furanic oxidation substrate as described hereinabove. In other embodiments, the first crystallization solvent is not the same as the oxidation solvent used in the prior oxidation step. In these embodiments, all or a portion of the oxidation solvent may be removed prior to the crystallization step, by, for example, evaporation, and

the like. The resulting solids can be dissolved in a different solvent (e.g., water or a different organic solvent species) or different multi-component solvent (i.e., a solvent that does not have the same composition as the oxidation solvent) to prepare the first crystallization solution.

5 In a specific embodiment, the crystallization solvent is a multi-component solvent comprising water and a water-miscible organic solvent. Thus, in a further embodiment, the present disclosure provides a process for producing a crystalline preparation of an FDCA pathway product, the process comprising:

10 providing a crystallization solution comprising an FDCA pathway product and a crystallization solvent that is a multi-component solvent comprising water and a water-miscible organic solvent;

initiating crystallization of the FDCA pathway product; and

producing a plurality of FDCA pathway product crystals of different particle sizes.

15 In this embodiment, the water-miscible organic solvent is typically a water-miscible aprotic organic solvent. In an exemplary embodiment, the water-miscible aprotic organic solvent is an ether, such as, for example dioxane, dioxolane, diglyme, and the like. To illustrate the benefit of such solvent system, Figure 3 shows the FDCA solubility relationship in representative solvent compositions of the disclosure in comparison to water, dioxane, dioxolane (e.g., 1,3-dioxolane), and diglyme. The high solubility of FDCA in the solvent compositions of the disclosures enables the preparation of saturated solutions of FDCA in
20 preparation for purification by crystallization. Figure 3 also shows that, by adjusting the solvent composition by removing water or the organic solvent (or an azeotropic mixture of water and the organic solvent), it is possible to produce a solvent composition that is organic solvent rich (in the cases in which the chosen organic solvent is less volatile than water), or a
25 solvent composition that is water rich (in the case that the chosen organic solvent is more volatile than water). Figure 3 demonstrates that FDCA is considerably less soluble in water or organic solvents than the solvent compositions of the disclosure. The saturated solutions of FDCA may be subjected to crystallization conditions by lowering the temperature or by solvent evaporation to adjust the solvent composition, or both.

30 Exemplary water-miscible aprotic solvents that are suitable for use in the crystallization processes of the present disclosure include tetrahydrofuran, a glyme, a

dioxane, a dioxolane, dimethylformamide, dimethylsulfoxide, sulfolane, acetone, *N*-methyl-2-pyrrolidone ("NMP"), methyl ethyl ketone ("MEK"), gamma-valerolactone, and the like. Preferably, the water-miscible aprotic organic solvent is an ether, such as, for example, a glyme, dioxane (for example 1,4-dioxane), dioxolane (e.g., 1,3-dioxolane), tetrahydrofuran, and the like. Glymes that are suitable for use in the practice of the present disclosure include, for example, monoglyme (1,2-dimethoxyethane, "DME"), ethyl glyme, diglyme (diethylene glycol dimethyl ether), ethyl diglyme, triglyme, butyl diglyme, tetraglyme, a polyglyme, a highly ethoxylated diether of a high molecular weight alcohol ("higlyme"), and the like. Often, the water-miscible aprotic organic solvent is glyme, diglyme, or dioxane.

In some embodiments, the water-miscible organic solvent species is at least 5 vol%, at least 10 vol%, at least 15 vol%, at least 20 vol%, at least 25 vol%, at least 30 vol%, at least 35 vol%, at least 40 vol%, at least 45 vol%, at least 50 vol%, at least 55 vol%, at least 60 vol%, at least 65 vol%, at least 70 vol%, at least 75 vol%, at least 80 vol%, at least 85 vol%, at least 90 vol%, or at least 95 vol% of the multi-component solvent or within a range defined by any two of the aforementioned values; and correspondingly, water is typically less than 95 vol%, less than 90 vol%, less than 85 vol%, less than 80 vol%, less than 75 vol%, less than 70 vol%, less than 65 vol%, less than 60 vol%, less than 55 vol%, less than 50 vol%, less than 45 vol%, less than 40 vol%, less than 35 vol%, less than 30 vol%, less than 25 vol%, less than 20 vol%, less than 15 vol%, less than 10 vol%, or less than 5 vol%, respectively, of the multi-component system or within a range defined by any two of the aforementioned values.

In some embodiments, the multi-component solvent comprises water in a range from or any number in between 1-5 wt% and a water-miscible organic solvent in a range from or any number in between 99-95 wt%. In some embodiments, the multi-component solvent comprises water in a range from or any number in between 5-10 wt% and a water-miscible organic solvent in a range from or any number in between 95-90 wt%. In some embodiments, the multi-component solvent comprises water in a range from or any number in between 10-15 wt% and a water-miscible organic solvent in a range from or any number in between 90-85 wt%. In some embodiments, the multi-component solvent comprises water in a range from or any number in between 15-20 wt% and a water-miscible organic solvent in a range from or any number in between 85-80 wt%. In some embodiments, the multi-

component solvent comprises water in a range from or any number in between 20-25 wt% and a water-miscible organic solvent in a range from or any number in between 80-75 wt%. In some embodiments, the multi-component solvent comprises water in a range from or any number in between 25-30 wt% and a water-miscible organic solvent in a range from or any number in between 75-70 wt%. In some embodiments, the multi-component solvent comprises water in a range from or any number in between 30-35 wt% and a water-miscible organic solvent in a range from or any number in between 70-65 wt%. In some embodiments, the multi-component solvent comprises water in a range from or any number in between 35-40 wt% and a water-miscible organic solvent in a range from or any number in between 65-60 wt%. In some embodiments, the multi-component solvent comprises water in a range from or any number in between 40-45 wt% and a water-miscible organic solvent in a range from or any number in between 60-55 wt%. In some embodiments, the multi-component solvent comprises water in a range from or any number in between 45-50 wt% and a water-miscible organic solvent in a range from or any number in between 55-50 wt%. In some embodiments, the multi-component solvent comprises water in a range from or any number in between 50-55 wt% and a water-miscible organic solvent in a range from or any number in between 50-45 wt%. In some embodiments, the multi-component solvent comprises water in a range from or any number in between 55-60 wt% and a water-miscible organic solvent in a range from or any number in between 45-40 wt%. In some embodiments, the multi-component solvent comprises water in a range from or any number in between 60-65 wt% and a water-miscible organic solvent in a range from or any number in between 40-35 wt%. In some embodiments, the multi-component solvent comprises water in a range from or any number in between 65-70 wt% and a water-miscible organic solvent in a range from or any number in between 35-30 wt%. In some embodiments, the multi-component solvent comprises water in a range from or any number in between 70-75 wt% and a water-miscible organic solvent in a range from or any number in between 30-25 wt%. In some embodiments, the multi-component solvent comprises water in a range from or any number in between 75-80 wt% and a water-miscible organic solvent in a range from or any number in between 25-20 wt%. In some embodiments, the multi-component solvent comprises water in a range from or any number in between 80-85 wt% and a water-miscible organic solvent in a range from or any number in between 20-15 wt%. In some embodiments, the multi-component

solvent comprises water in a range from or any number in between 85-90 wt% and a water-miscible organic solvent in a range from or any number in between 15-10 wt%. In some embodiments, the multi-component solvent comprises water in a range from or any number in between 90-95 wt% and a water-miscible organic solvent in a range from or any number in between 10-5 wt%. In some embodiments, the multi-component solvent comprises water in a range from or any number in between 95-99 wt% and a water-miscible organic solvent in a range from or any number in between 5-1 wt%.

More typically, the volume ratio of water to water-miscible organic solvent is typically in the range of from or any number in between 1:6 to 6:1 (v:v). In some embodiments, the volume ratio is from or any number in between 1:4 to 4:1 (v:v). In some embodiments, the volume ratio is from or any number in between 1:4 to 3:1 (v:v) water:water-miscible organic solvent. In other embodiments, the volume ratio is from or any number in between 1:4 to 1:3 (v:v) water:water miscible organic solvent. In certain embodiments, the volume ratio is 1:1 (v:v) water:water-miscible organic solvent.

Crystallization can be initiated using either temperature reduction (cooling) or solvent removal methods described above. When temperature reduction is used to initiate crystallization, the temperature of the crystallization solution is typically reduced from a first temperature that is typically in the range of from or any number in between 60°C to 220°C, such as e.g., 60, 70, 80, 90, 100, 110, 120, 130, 140, 150, 160, 180, 190, 200, 210, or 220 °C or within a range defined by any two of the aforementioned temperatures. When water is a component of the crystallization solvent, the first temperature is often at the upper end of this range, e.g., in the range of from or any number in between 100°C to 220°C or in the range of from or any number in between 150°C to 220°C such as e.g., 100, 110, 120, 130, 140, 150, 160, 180, 190, 200, 210, or 220 °C or within a range defined by any two of the aforementioned temperatures. In some embodiments, the first temperature is in the range of from or any number in between 60°C to 180°C, such as e.g., 60, 70, 80, 90, 100, 110, 120, 130, 140, 150, 160, or 180 °C or within a range defined by any two of the aforementioned temperatures to a second temperature that is lower than the first temperature. In other embodiments, the first temperature is in the range of from or any number in between 70°C to 150°C, such as e.g., 70, 80, 90, 100, 110, 120, 130, 140, or 150 °C or within a range defined by any two of the aforementioned temperatures. When the crystallization solution is cooled,

it is typically cooled to a second temperature that is below 60°C, such as e.g., equal to or less than 60, 50, 40, 30, 20, 10, 5, or 0 °C or within a range defined by any two of the aforementioned temperatures. More typically, it is cooled to a second temperature below 50°C or below 40°C such as, e.g., equal to or less than 50, 40, 30, 20, 10, 5, or 0 °C or within
5 a range defined by any two of the aforementioned temperatures.

Crystallization can also be initiated by removing a first portion of the crystallization solvent from the crystallization solution to produce an FDCA pathway product slurry, wherein the FDCA pathway product slurry comprises a first plurality of FDCA pathway product crystals of different particle sizes and a second portion of the crystallization solvent;
10 and separating the plurality of FDCA pathway product crystals from the second portion of the first crystallization solvent. The first plurality of FDCA pathway product crystals may be optionally dissolved in the same or different crystallization solvent, and the process repeated to obtain a second plurality of FDCA pathway product crystals of different particle sizes.

Seed crystals of the FDCA pathway product may be added to further promote the
15 initiation of crystallization. Other additives, such as anti-foaming agents or crystallization aids, may be added to the crystallization solution to promote the crystallization process, and enable the formation of a suspension containing FDCA crystals. Anti-foaming agents that are suitable for use in the practice of the present disclosure include, for example, silicones, surfactants, phosphates, alcohols, glycols, stearates and the like. Additives such as
20 surfactants or electrolyte polymers may also influence the morphology and composition of the crystals formed. *See, e.g.*, US 5,296,639 and US 6,534,680, which are incorporated herein by reference in their entireties. Other additives may function as a flow improver to prevent agglomeration of the crystalline product on storage (see for example US 6,534,680).

FDCA pathway product crystals produced by the processes described herein can be
25 separated from the solution (mother liquor) by centrifugation, filtration, or other suitable process for separating solids from liquids. The crystals can then be washed and dried using any suitable process known to those having ordinary skill in the art.

The crystallization processes described herein can be carried out as part of an integrated process for preparing FDCA pathway product crystals from a raw feed that
30 comprises the FDCA pathway product. The set of process steps can be carried out in at least a first crystallization zone, a dissolution zone, and a second (refined) crystallization zone.

The crystallization processes can also be carried out as part of an integrated process for preparing FDCA pathway product crystals from an oxidation feedstock comprising the furanic oxidation substrate and the oxidation solvent. In this process, the integrated crystallization process is further integrated with the oxidation reaction processes described
5 herein. In this integrated process, effluent from at least one oxidation reaction zone is passed, as feedstock, into the integrated crystallization process. In the crystallization processes described herein, crystal separation operations (such as the use of a centrifuge) may optionally be deployed after each crystallization zone (for example between the crystallization zone and the next dissolution zone). Illustrative integrated processes for
10 producing a crystalline FDCA preparation are depicted in Figures 6-9.

When the oxidation reaction zone product stream comprises a multi-component solvent that comprises water and a light organic solvent, the integrated process shown in Figure 6 may be used. This process utilizes a solvent switch to water in the second (refined) crystallization zone. In this integrated process, an oxidation zone product stream **105**
15 comprising water, a light organic solvent, and FDCA is passed into a first crystallization zone **200**, to produce a solid crude FDCA crystal product stream **205**, a water/light organic solvent vapor recycle stream **211** that is optionally recycled to an oxidation reaction zone, and a liquid water/light organic solvent recycle stream **207** that is also optionally recycled to an oxidation reaction zone. An optional purge stream **209** may be used to remove impurities
20 from the liquid recycle stream **207**. Solid crude FDCA crystal product stream **205** is fed into a dissolution zone **220** where solid crude FDCA crystal product is redissolved. Water **115** is fed into the solid crude FDCA crystal product stream **205** prior to passage of the latter into the dissolution zone **220** to produce a dissolution zone product stream **225** comprising solubilized FDCA in water. Dissolution zone product stream **225** is passed into a second
25 (refined) crystallization zone **230** to produce a water vapor recycle stream **222**, a liquid water recycle stream **236**, and a refined crystallization product stream **235** that comprises refined FDCA crystals. Water vapor and liquid water recycle streams, **222** and **236**, respectively, are both optionally fed into the solid crude FDCA crystal product stream **205**.

When the oxidation reaction zone product stream comprises a multi-component
30 solvent that comprises water and a light organic solvent, the integrated process shown in Figure 7 may be used. In this integrated process, an oxidation zone product stream **105**

comprising water, a light organic solvent, and FDCA is passed into a first crystallization zone **200**, to produce crude FDCA crystal product stream **205**, a water/light organic solvent vapor recycle stream **213** that is fed into the solid crude FDCA crystal product stream **205**; and a water/light organic solvent liquid recycle stream **207** that is optionally recycled to an upstream oxidation reaction zone. An optional purge stream **209** may be used to remove impurities from the liquid recycle stream **207**. Crude FDCA crystal product stream **205** is fed into a dissolution zone **220** where solid crude FDCA crystal product is redissolved. Make-up co-solvent (which may be water, the organic light solvent, or a solvent composition comprising both water and the light organic solvent) stream **125** is fed into the solid crude FDCA crystal product stream **205** prior to passage of the latter into the dissolution zone **220** to produce a dissolution zone product stream **226** comprising solubilized FDCA in the multi-component solvent. Dissolution zone product stream **226** is passed into a second (refined) crystallization zone **230** to produce a co-solvent vapor recycle stream **237**, and a refined crystallization product stream **235** that comprises refined FDCA crystals. Co-solvent vapor recycle stream **237** is optionally recycled to the oxidation reaction zone. Co-solvent liquid recycle stream **233** is optionally fed into the solid crude FDCA crystal product stream **205**.

In a further integrated process, when the oxidation reaction zone product stream comprises a multi-component solvent that comprises water and a heavy organic solvent, the process depicted in Figure 8 may be used. This process utilizes a solvent switch to water in the second (refined) crystallization zone. In this integrated process, an oxidation zone product stream **105** comprising water, a heavy organic solvent, and FDCA is passed into a first crystallization zone **200**, to produce a solid crude FDCA crystal product stream **205**, a water vapor recycle stream **212** that is optionally recycled to an oxidation reaction zone, and a liquid water/heavy organic solvent recycle stream **207** that is also optionally recycled to an oxidation reaction zone. An optional purge stream **209** may be used to remove impurities from the liquid recycle stream **207**. Solid crude FDCA crystal product stream **205** is fed into a dissolution zone **220** where solid crude FDCA crystal product is redissolved. Water stream **115** is fed into the solid crude FDCA crystal product stream **205** prior to passage of the latter into the dissolution zone **220** to produce a dissolution zone product stream **223** comprising solubilized FDCA in water. Dissolution zone product stream **223** is passed into a second (refined) crystallization zone **230** to produce a water vapor recycle stream **245**, a liquid water

recycle stream **236**, and a refined crystallization product stream **235** that comprises refined FDCA crystals. Water vapor and liquid water recycle streams, **245** and **236**, respectively, are both optionally fed into the solid crude FDCA crystal product stream **205**.

When the oxidation reaction zone product stream comprises a multi-component solvent (i.e., co-solvent) that comprises water and a heavy organic solvent, the integrated process shown in Figure 9 may be used. In this integrated process, an oxidation zone product stream **105** comprising water, a heavy organic solvent, and FDCA is passed into a first crystallization zone **200**, to produce a solid crude FDCA crystal product stream **205**, a water vapor recycle stream **211** that is optionally passed into the solid crude FDCA crystal product stream **205**, and a liquid water/heavy organic solvent recycle stream **207** that is optionally recycled upstream to an oxidation reaction zone. An optional purge stream **209** may be used to remove impurities from the liquid recycle stream **207**. Solid crude FDCA crystal product stream **205** is fed into a dissolution zone **220** where solid crude FDCA crystal product is redissolved. Make up solvent stream **125** comprising water and heavy organic solvent is fed into the solid crude FDCA crystal product stream **205** prior to passage of the latter into the dissolution zone **220** to produce a dissolution zone product stream **223** comprising solubilized FDCA in water and heavy organic solvent. Dissolution zone product stream **223** is passed into a second (refined) crystallization zone **230** to produce a water vapor recycle stream **245**, a liquid water/heavy organic solvent recycle stream **236**, and a refined crystallization product stream **235** that comprises refined FDCA crystals. Water vapor stream **245** is optionally recycled upstream to an oxidation reaction zone. Liquid water/heavy organic solvent recycle stream **236** is optionally recycled to the solid crude FDCA crystal product stream **205**. An optional purge stream **239** may be used to remove impurities from stream **236**. The processes described herein are illustrative and variations to the processes are possible (e.g., process streams may be re-routed to alternative points in the processes)

The crystalline product produced by the processes described herein exhibit desirable bulk properties. Thus, in a further embodiment, the present disclosure provides a crystalline FDCA composition comprising a plurality of FDCA crystals characterized by a distribution of particle sizes, wherein the distribution has a D50 in the range of from 50 μm up to 5000 μm . The crystalline FDCA preparation can be produced using the methods described above.

As used herein, the term “D50” refers to the median diameter of the particle size distribution. In some embodiments, the D50 is in the range of from or any number in between 50 μm to 2000 μm , or in the range of from or any number in between 100 μm to 3500 μm , and often in the range of from or any number in between 100 μm to 3000 μm .

5 Typically the D50 of the particle size distribution is in the range of from or any number in between 100 μm to 750 μm , and more typically, the D50 in the range of from or any number in between 125 μm to 500 μm , and sometimes in the range of from or any number in between 125 μm to 450 μm , or from or any number in between 125 μm to 400 μm , and in some embodiments, in the range of from or any number in between 200 μm to 500 μm .

10 In some embodiments of the above, the crystalline FDCA preparation comprises less than 1 weight % FDCA crystals having a particle size less than 10 μm . In other embodiments, the crystalline FDCA preparation comprises less than 10 wt%, and more typically less than 9 wt%, less than 8 wt%, less than 7 wt%, less than 6 wt%, or less than 5 wt % FDCA crystals having a particle size less than 10 μm . In further embodiments, the
15 crystalline FDCA preparations of the present disclosure typically comprise less than 10 wt%, less than 9 wt%, less than 8 wt%, less than 7 wt%, less than 6 wt%, less than 5 wt%, less than 4 wt%, less than 3 wt%, less than 2 wt%, or less than 1 wt % FDCA crystals having a particle size less than 4 μm .

Typically, the crystalline FDCA preparation comprises at least 98 wt% FDCA, and
20 more typically, it comprises at least 99 wt% FDCA, and in some embodiments, it comprises greater than 99 wt% FDCA.

The crystallization processes of the present disclosure may be carried out using known industrial crystallizer systems that are suitable for carrying out solution phase crystallizations. Suitable systems include for example, batch crystallizers, continuous
25 crystallizers (e.g., forced circulation crystallizers, draft-tube crystallizers, draft-tube-baffled crystallizers, or Oslo-type crystallizers, and the like), and other such crystallizer systems.

The crystalline FDCA preparations of the present disclosure are typically dry, and comprise less than 1 wt% water. Often, they comprise less than 0.9 wt%, or less than 0.8 wt%, or less than 0.7 wt%, or less than 0.6 wt%, or less than 0.5 wt%, or less than 0.4 wt%,
30 or less than 0.3 wt%, or less than 0.2 wt% water or an amount of water that is within a range defined by any two of the aforementioned amounts.

In a further embodiment, the present disclosure provides a composition comprising FDCA and a multi-component solvent, wherein the multi-component solvent comprises water and a water-miscible aprotic organic solvent, and wherein the FDCA is present at a concentration of at least 5 wt%. In some embodiments, the FDCA is present at a concentration of at least 6 wt%, or at least 7 wt%, or at least 8 wt%, or at least 9 wt%, or at least 10 wt%, or at least 11 wt%, or at least 12 wt%, or at least 13 wt%, or at least 14 wt%, or at least 15 wt%. The composition comprising FDCA and a multi-component solvent can be a solution. The solution can contain FDCA that is solubilized such that the solution does not contain FDCA solids. The composition comprising FDCA and a multi-component solvent can be a solution (such that the solution does not contain FDCA solids) at room temperature or at a temperature up to 160°C (such as e.g., 20, 30, 40, 50, 60, 70, 80, 90, 100, 110, 120, 130, 140, 150, or 160 °C or within a range defined by any two of the aforementioned temperatures). These compositions are useful in carrying out various unit operations that occur downstream of the oxidation step, including, for example, transesterification, polycondensation, or crystallization, and other downstream processes involved in the production of FDCA-based products. Typically, the water-miscible aprotic organic solvent is NMP or an ether, such as, for example, a glyme or dioxane.

In some embodiments, the water-miscible aprotic organic solvent species is at least 5 vol%, at least 10 vol%, at least 15 vol%, at least 20 vol%, at least 25 vol%, at least 30 vol%, at least 35 vol%, at least 40 vol%, at least 45 vol%, at least 50 vol%, at least 55 vol%, at least 60 vol%, at least 65 vol%, at least 70 vol%, at least 75 vol%, at least 80 vol%, at least 85 vol%, at least 90 vol%, or at least 95 vol% of the multi-component solvent system; and correspondingly, water is typically less than 95 vol%, less than 90 vol%, less than 85 vol%, less than 80 vol%, less than 75 vol%, less than 70 vol%, less than 65 vol%, less than 60 vol%, less than 55 vol%, less than 50 vol%, less than 45 vol%, less than 40 vol%, less than 35 vol%, less than 30 vol%, less than 25 vol%, less than 20 vol%, less than 15 vol%, less than 10 vol%, or less than 5 vol%, respectively, of the multi-component solvent or within a range defined by any two of the aforementioned amounts.

More typically, the volume ratio of water to water-miscible aprotic organic solvent is typically in the range of from 1:6 to 6:1. In some embodiments, the volume ratio is from 1:4

to 4:1 (v:v) or from 1:4 to 3:1 (v:v) water:water-miscible aprotic organic solvent. In certain embodiments, the volume ratio is 1:1 (v:v) water:water-miscible aprotic organic solvent.

II. Catalyst Preparation

5 Heterogeneous oxidation catalysts employed in the processes described herein may be prepared by any one of a number of methods. For example, noble metals can be deposited onto the exterior and interior surfaces of the support material using methods such as, for example, incipient wetness, ion exchange, deposition-precipitation, and/or vacuum impregnation. When more than one metal is deposited onto the support, they may be
10 deposited sequentially or simultaneously. After depositing the metals onto the surfaces of the catalyst support, the catalyst is typically dried at a temperature in the range of 20°C to 120°C (such as e.g., 20, 30, 40, 50, 60, 70, 80, 90, 100, 110, or 120 °C or within a range defined by any two of the aforementioned temperatures for a period of time that is in the range of from one hour up to twenty four hours e.g., 1, 2, 3, 4, 5, 6, 7, 8, 9, 10, 11, 12, 13, 14, 15, 16, 17,
15 18, 19, 20, 21, 22, 23, or 24 hours or within a range defined by any two of the aforementioned time periods. The catalyst can be dried under sub-atmospheric pressure conditions. In some embodiments, the catalyst is reduced after drying (e.g., by flowing 5% H₂ in N₂ at a temperature of at least 200°C for a period of time (e.g., at least three hours). The catalyst may also be calcined in air at a temperature of at least 200°C for a period of time
20 of at least three hours.

When the heterogeneous oxidation catalyst comprises gold, the gold may be added to the support material as a solubilized constituent in a liquid. When the gold-liquid solution is mixed with the support material, a suspension of support material in the solubilized gold-containing liquid phase is formed. In this method, a base is then added to the suspension in
25 order to form a precipitant of insoluble gold complex which deposits on the surfaces of the support material in a uniform fashion. In this deposition method, the solubilized gold constituent may be in the form of a gold salt (e.g., HAuCl₄, and the like). Although any base that can promote the formation of the insoluble gold complex is suitable, bases such as potassium hydroxide (KOH) and sodium hydroxide (NaOH), are typically employed. The
30 resulting solids may be collected by known methods for separating solids from liquids, including, for example, filtration, centrifugation, and the like. The collected solids may be

optionally washed, then optionally heated to dry. Heating may also be employed to reduce the gold complex on the support to gold (0). Heating may be conducted at temperatures in the range of from 60°C to dry, and from 150°C for reduction up to 500°C, at which temperature the gold can be effectively reduced (such as e.g., 60, 70, 80, 90, 100, 110, 120, 130, 140, 150, 160, 180, 190, 200, 210, 220, 230, 240, 250, 300, 350, 400, 450, or 500°C or within a range defined by any two of the aforementioned temperatures). In various embodiments, the heating step may be conducted in the presence of a reducing atmosphere in order to promote the reduction of the complex to deposit the gold onto the support as gold (0). The duration of heating may vary from a few hours to a few days depending on various factors, including, for example, the objective of the heating step and the decomposition rate of the base which is added to form the insoluble complex. Typically, the heating time for the purpose of drying is in the range of from 2 to 24 hours (e.g., 2, 3, 4, 5, 6, 7, 8, 9, 10, 11, 12, 13, 14, 15, 16, 17, 18, 19, 20, 21, 22, 23, or 24 hours or within a range defined by any two of the aforementioned time periods), and for reducing the gold complex, in the range of from 1 to 4 hours (e.g., 1, 2, 3, or 4 hours or within a range defined by any two of the aforementioned time periods).

When the heterogeneous oxidation catalyst comprises platinum, the platinum is typically added to the support material by contacting the support material with a solution containing a soluble platinum precursor compound or with a platinum-containing colloid. Platinum may be deposited on the support material in the form of any one of a variety of compounds, such as, for example, platinum (II) nitrate, platinum (IV) nitrate, platinum oxynitrate, platinum (II) acetylacetonate (acac), tetraamineplatinum (II) nitrate, tetraamineplatinum (II) hydrogenphosphate, tetraamineplatinum (II) nitrate, tetraamineplatinum (II) hydrogenphosphate, tetraamineplatinum (II) nitrate, tetraamineplatinum (II) hydrogenphosphate, tetraamineplatinum (II) hydrogencarbonate, tetraamineplatinum (II) hydroxide, H_2PtCl_6 , PtCl_4 , Na_2PtCl_4 , K_2PtCl_4 , $(\text{NH}_4)_2\text{PtCl}_4$, $\text{Pt}(\text{NH}_3)_4\text{Cl}_2$, mixed $\text{Pt}(\text{NH}_2)_x\text{Cl}_y$, $\text{K}_2\text{Pt}(\text{OH})_6$, $\text{Na}_2\text{Pt}(\text{OH})_6$, $(\text{NMe}_4)_2\text{Pt}(\text{OH})_6$, and $[(\text{C}_2\text{H}_7\text{NO})_2]\text{Pt}(\text{OH})_6$, and the like. Typically, platinum is added to the support material as platinum (II) nitrate, platinum (IV) nitrate, platinum (II) acetylacetonate (acac), tetraamine platinum (II) hydroxide, K_2PtCl_4 , or $\text{K}_2\text{Pt}(\text{OH})_6$.

If a gold- and platinum-containing heterogeneous oxidation catalyst is desired, the platinum can be deposited onto the surfaces of the support material either before or after gold has been deposited, or alternatively, the platinum and gold can be deposited together. When platinum is added to a gold-containing heterogeneous oxidation catalyst, it can be added after
5 deposition of the gold, and either before or after drying or after drying, and before or after reduction of the gold. When platinum is added to the catalyst support prior to the deposition of gold, the platinum employed is one which will not be re-dissolved upon addition of the base used to promote the deposition of gold onto the support.

After the platinum compound is added to the support material, the resulting platinum-
10 containing support material is dried. Drying may be conducted at room temperature or at a temperature up to 120°C (such as e.g., 20, 30, 40, 50, 60, 70, 80, 90, 100, 110, or 120, °C or within a range defined by any two of the aforementioned temperatures. Typically, drying is conducted at a temperature in the range of or any number in between 40°C to 80°C, and often at a temperature of 60°C (such as e.g., 40, 50, 60, 70, or 80°C or within a range defined by
15 any two of the aforementioned temperatures. Drying typically proceeds over a period of time in the range of from a few minutes to a few hours. Typically, the platinum-containing support material is dried over a period of time in the range of from or any number in between 6 hours to 24 hours (e.g., 6, 7, 8, 9, 10, 11, 12, 13, 14, 15, 16, 17, 18, 19, 20, 21, 22, 23, or 24 hours or within a range defined by any two of the aforementioned time periods). The drying
20 can be conducted with a continuous or a staged temperature increase of from or any number in between 60°C to 120°C (such as e.g., 60, 70, 80, 90, 100, 110, or 120, °C or within a range defined by any two of the aforementioned temperatures) on a band calciner or belt dryer.

After drying the platinum-containing support material, the material is subjected to at least one thermal treatment in order to reduce the platinum (which is deposited as platinum
25 (II) or platinum (IV)) to platinum (0). In certain embodiments, the thermal treatment(s) may be conducted under a forming gas atmosphere. Alternatively, a liquid reducing agent may be employed to reduce the platinum. For example, hydrazine or formaldehyde or formic acid or a salt thereof (e.g., sodium formate) or NaH_2PO_2 may be employed to effect the reduction of platinum.

30 The temperature(s) at which the thermal treatment(s) is (are) typically conducted in the range of from or any number in between 150°C to 600°C (such as e.g., 150, 200, 250,

300, 350, 400, 450, 500, 550, or 600°C or within a range defined by any two of the
aforementioned temperatures). In some embodiments, the temperatures of the thermal
treatment(s) is (are) in the range of from or any number in between 200°C to 500°C, and,
more typically, in the range of from or any number in between 200°C to 400°C (such as e.g.,
5 200, 250, 300, 350, or 400 °C or within a range defined by any two of the aforementioned
temperatures). The thermal treatment is typically conducted for a period of time in the range
of from or any number in between 1 hour to 8 hours or in some embodiments, in the range of
from or any number in between 1 hour to 3 hours (e.g., 1, 2, 3, 4, 5, 6, 7, or 8 or within a
range defined by any two of the aforementioned time periods).

10

III. Preparation of FDCA Derivatives and FDCA Polymers

Derivatives of FDCA can be readily prepared from the FDCA produced using the
processes of the present disclosure. For example, in some embodiments, it may be desirable
to further convert the FDCA pathway product(s) to an FDCA salt (e.g., by adding a base,
15 such as, for example, sodium hydroxide, potassium hydroxide, sodium hydroxide, ammonia,
and the like), an ester, an amide, a halide, and the like.

The dicarboxylic acid functionality of the FDCA makes it useful as a monomer, either
as is or in derivatized form. FDCA derivatives that are useful as monomers for further
polymerization, include FDCA esters, FDCA amides, FDCA halides, and the like. The
20 resulting FDCA derivatives may be optionally purified by, for example, distillation,
crystallization, and the like.

In one embodiment, the present disclosure provides a process for converting the
FDCA to an ester of FDCA, the converting step comprising contacting the FDCA produced
by the processes of the present disclosure with an alcohol under conditions sufficient to
25 produce a corresponding FDCA monoester or FDCA diester. Alcohols suitable for use in the
practice of the present disclosure include branched or unbranched, C₁-C₂₀ alcohols (e.g.,
aliphatic alcohols or aromatic C₅-C₂₀ alcohols and including, for example, diols or polyols).
In some embodiments, the alcohol is a branched or unbranched, C₁-C₁₀ alcohol, C₁-C₆
alcohol, or a branched or unbranched, C₁-C₄ (i.e., methyl alcohol, ethyl alcohol, n-propyl
30 alcohol, iso-propyl alcohol, 2-methylpropan-1-ol (i.e., isobutyl alcohol), 2-methyl-2-propanol
(i.e., t-butyl alcohol), or n-butyl, and the like. C₁-C₁₂ polyols, including diols and other

polyols, are also suitable for use in these processes. These include, for example, ethanediol (ethylene glycol), 1,3-propanediol, 1,4-butanediol, 2,3-butanediol, a hexanediol (e.g., 1,6-hexanediol, 1,2-hexanediol, 1,5-hexanediol, 2,5-hexanediol, and the like), a hexanetriol (e.g., 1,2,6-hexanetriol, 1,2,3-hexanetriol, 1,3,6-hexanetriol, and the like),

5 bis(hydroxymethyl)benzene, 1,8-octanediol, 4-octene-1,8-diol, 1,9-nonanediol, 2-nonene-1,4-diol, 7-nonene-1,5-diol, 7-nonene-1,5-diol, 1,10-decanediol, or 1,12-dodecanediol, and the like, as well as any combination thereof. Conditions sufficient for promoting the formation of a mono- or di-ester of FDCA (i.e., "esterifying conditions") include, for example, contacting the FDCA with the desired alcohol in the presence of a catalyst, such as,
10 for example, a mineral acid (such as, for example, HCl, or H₂SO₄, and the like) at a temperature in the range of from 50°C to 150°C (such as e.g., 50, 60, 70, 80, 90, 100, 110, 120, 130, 140, or 150 °C or within a range defined by any two of the aforementioned temperatures). Often, the alcohol is methanol and the ester of FDCA is the methyl ester of FDCA, and typically, it is the dimethyl ester of FDCA. In other embodiments, the alcohol is
15 ethanol, and the ester of FDCA is the ethyl ester of FDCA, and typically, it is the diethyl ester of FDCA.

An illustrative integrated process for producing purified dimethyl ester of FDCA by distillation is provided in Figure 10. With reference to Figure 10, a solid crude FDCA feedstock stream **205** is mixed with a methanol stream **250** and optionally a methanol/water
20 vapor stream **265** prior to being passed into an esterification zone **280** where FDCA and methanol are subjected to conditions that promote esterification to produce an esterification zone product stream **285**, which comprises the dimethyl ester of FDCA. Esterification zone product stream **285** is passed into a flash distillation zone, which comprises a flash distillation column, to produce a methanol/water vapor recycle stream **265** and a flash zone
25 product stream **263** which comprises the dimethyl ester of FDCA. A portion of the water produced in the esterification zone may be removed from the methanol/water vapor recycle stream **265** in a water vapor purge stream **267**. The methanol or methanol/water vapor recycle stream **265** is recycled to the FDCA feedstock stream **205**. The flash zone product stream **263** is passed into a distillation column zone **270** to product an impurity stream **273**
30 and a light stream **275** comprising purified dimethyl ester of FDCA.

An alternative integrated process for producing purified dimethyl ester of FDCA that

utilizes crystallization as the purification step is provided in Figure 11. In this process, a solid crude FDCA feedstock stream **205** is mixed with a methanol make up stream **265** and optionally a vapor methanol/water stream **297** and subsequently passed into an esterification zone **280** where FDCA and methanol are subjected to conditions that promote esterification to produce an esterification zone product stream **285**, which comprises the dimethyl ester of FDCA. Esterification zone product stream **285** is passed into a diester crystallizer zone **290**, to produce a diester crystallizer zone product stream **295** that comprises the dimethyl ester of FDCA in crystalline form, a liquid recycle stream **293** that comprises methanol and water, and a vapor methanol/water stream **297**. Liquid recycle stream **293** is passed into the vapor methanol/water stream **297**. A portion of the water in the vapor methanol/water stream **297** may be removed in a water vapor purge stream **281**. Optional purge stream **294** facilitates removal of impurity components from the vapor methanol/water stream **293**.

In another embodiment, the present disclosure provides a process for converting the FDCA or an FDCA ester to an FDCA amide, wherein the converting step comprises contacting the FDCA or FDCA ester produced by the processes of the present disclosure with an amino-substituted compound under conditions sufficient to produce a corresponding FDCA mono-amide or FDCA diamide. Conditions sufficient for promoting the formation of the mono- or di-amide of FDCA (i.e., amidation conditions") include, for example, contacting the FDCA or FDCA ester with the amine under conditions that are known to convert carboxylic acids or esters into amides. *See, e.g.,* March's Advanced Organic Chemistry Eds. M. B. Smith and J. March, Wiley (2013), which is incorporated herein by reference. Amino-substituted compounds suitable for use in the practice of the present disclosure include, for example, C₁-C₂₀ aliphatic or aromatic amines. Typically, the amino-substituted compound is a C₁-C₁₀, or C₁-C₆ mono- or di-amine. Suitable amino-substituted compounds include, for example, 1,6-hexamethylenediamine, 1,5-pentamethylenediamine or 1,4-tetramethylenediamine, and the like.

In a further embodiment, the present disclosure provides a process for converting the FDCA to an FDCA halide, the converting step comprising contacting the FDCA produced by the processes of the present disclosure with a halogenating agent (e.g. SOCl₂) under conditions that are known to convert carboxylic acids into acyl halides. See for example

March's Advanced Organic Chemistry Eds. M. B. Smith and J. March; Wiley (2013), which is incorporated herein by reference in its entirety.

Certain FDCA derivatives may be employed as FDCA-monomers, which are useful for producing polymers, such as, for example, polyesters, polyamides, and the like. As used
5 herein, the term "FDCA-based monomers" refers to FDCA, as well as FDCA derivatives that have the ability to react with other monomers to form a polymer. Thus, in a further embodiment, the present disclosure provides a process for producing an FDCA-based polymer, the method comprising polymerizing an FDCA-based monomer of the present disclosure under conditions sufficient to produce the FDCA-based polymer. In some
10 embodiments, the FDCA-based monomer is an FDCA derivative selected from the group consisting of an FDCA ester (i.e., a monoester or diester), an FDCA amide (i.e., an FDCA monoamide or an FDCA diamide), and an FDCA halide (e.g., an FDCA monochloride, an FDCA dichloride, and the like), and the like. In certain embodiments, the FDCA-based monomer is polymerized with a second monomer that is not the same as the first monomer.
15 Second monomers that are suitable for use in the practice of the present disclosure include a polyol that has at least two hydroxyl groups.

Exemplary polyols that can be used as a suitable co-monomer include ethanediol (ethylene glycol), 1,3-propanediol, 1,4-butanediol, 2,3-butanediol, a hexanediol (e.g., 1,6-hexanediol, 1,2-hexanediol, 1,5-hexanediol, 2,5-hexanediol, and the like), a hexanetriol (e.g.,
20 1,2,6-hexanetriol, 1,2,3-hexanetriol, 1,3,6-hexanetriol, and the like), bis(hydroxymethyl)benzene, 1,8-octanediol, 4-octene-1,8-diol, 1,9-nonanediol, 2-nonene-1,4-diol, 7-nonene-1,5-diol, 7-nonene-1,5-diol, 1,10-decanediol, or 1,12-dodecanediol, and the like, as well as any combination thereof. Typically, the polyol is a diol. Exemplary dicarboxylic acids include, for example, succinic acid, or adipic acid, and the like.

Exemplary hydroxyacids include, for example, lactic acid, succinic acid, malic acid, salicylic acid, syringic acid, or ferulic acid, and the like. Exemplary sugar alcohols include, for example, isosorbide, isomannide, or isoidide, and the like. Typically, the FDCA-based monomer is selected from the group consisting of FDCA and dimethyl FDCA ester and a second monomer is employed that is a polyol.

When the FDCA-based monomer is FDCA, the second monomer can be an aliphatic or aromatic diamine or an aliphatic or aromatic polyol (e.g., a diol, or a triol, and the like).

Suitable diamines include, for example, 1,6-hexamethylenediamine, 1,5-pentamethylenediamine, or 1,4-tetramethylenediamine, and the like. Suitable polyols include those described above.

The FDCA-based polymers of the present disclosure are typically produced using a polycondensation reaction, either in a solution polymerization or melt polymerization. In some embodiments, the polymerization step is preceded by a transesterification step. The polycondensation reactions are typically carried out in the presence of a catalyst, such as, for example, dibutyltin (IV) oxide, titanium (IV) isopropoxide, antimony (III) oxide (*see, e.g.,* G.-J. M. Gruter, et al., *Comb. Chem. High Throughput Screening* (2012) 15:180-188, which is incorporated herein by reference.

In a specific embodiment, the present disclosure provides a method for producing an FDCA-based polyester, the method comprising contacting an FDCA-monomer selected from the group consisting of FDCA and FDCA dimethyl ester with a C₁-C₂₀ polyol at a temperature in the range of from 120°C to 225°C (such as e.g., 120, 130, 140, 150, 160, 180, 190, 200, 210, or 225 °C or within a range defined by any two of the aforementioned temperatures) to form a reaction mixture for producing the corresponding dihydroxy C₁-C₂₀ FDCA ester (in an esterification or transesterification step, respectively), then increasing the temperature of the reaction mixture to a temperature in the range of from 180°C to 250°C (such as e.g., 180, 190, 200, 210, 220, 230, 240, or 250 °C or within a range defined by any two of the aforementioned temperatures) to produce the corresponding FDCA-based polyester (in a polycondensation step). Typically, the C₁-C₂₀ FDCA polyol is a diol selected from the group consisting of ethylene glycol, 1,3-propanediol, 1,4-butanediol, 2,3-butanediol, and 1,6-hexanediol. In certain embodiments the molecular weight of the resultant polyester can be further increased by a third stage solid state polymerization in which the polymeric material (in the form of pellets, granules, flakes or chips and the like) is subjected to a certain amount of time, such as 1-24 hours (e.g., 1, 2, 3, 4, 5, 6, 7, 8, 9, 10, 11, 12, 13, 14, 15, 16, 17, 18, 19, 20, 21, 22, 23, or 24 hours or within a range defined by any two of the aforementioned time periods)) at elevated temperatures above the glass transition temperature and below the melting temperature of the polyester. The polycondensation methods are typically conducted at pressures below 1 atmosphere.

IV. Production of Furanic Oxidation Substrate

While furanic oxidation substrate material can be readily purchased, it may be desirable in certain circumstances to produce the furanic oxidation substrate. The present disclosure provides a process for producing a furanic oxidation substrate, the process comprising:

(a⁰) contacting a carbohydrate feedstock comprising a sugar and a dehydration solvent with a catalyst under conditions sufficient to form a (dehydration) reaction mixture for dehydrating the sugar to produce the furanic oxidation substrate (referred to herein as the "dehydration process"). Typically, the sugar is a hexose, such as, for example, glucose, galactose, mannose, idose, a ketohexose, fructose, levulose, sorbose, tagatose, or allose, and the like. Usually, the sugar is glucose or fructose. Often, the sugar is fructose.

The term "dehydration solvent" refers to a solvent in which both the sugar and the furanic oxidation substrate are each separately soluble at a minimum level of at least 2% by weight at the temperature at which the dehydration reaction is carried out. Typically, the dehydration solvent is one in which the furanic oxidation substrate has a solubility of at least 3 wt%, at least 4 wt%, at least 5 wt%, at least 6 wt%, at least 7 wt%, at least 8 wt%, at least 9 wt%, at least 10 wt%, at least 11 wt%, at least 12 wt%, at least 13 wt%, at least 14 wt%, at least 15 wt%, at least 17%, at least 19%, at least 21%, at least 23%, or at least 25% as measured at the temperature at which the dehydration reaction is carried out. In some embodiments, the concentration of furanic oxidation substrate in the dehydration solvent ranges from or any number in between 2-4 wt%, 3-5 wt%, 4-6 wt%, 5-7 wt%, 6-8 wt%, 7-9 wt%, 8-10 wt%, 9-11 wt%, 10-12 wt%, 11-13 wt%, 12-14 wt%, 13-15wt%, 14-16 wt%, 15-17 wt%, 16-18 wt%, 17-19 wt%, 18-20 wt%, 19-21 wt%, 20-22 wt%, 21-23 wt%, 22-24 wt%, or 23-25wt% or within a range defined by any of two of the aforementioned weight percentages. Typically, the dehydration solvent comprises water and/or a water-miscible organic solvent. More typically, the dehydration solvent is a multi-component solvent. Usually, the multi-component solvent employed in the dehydration process comprises water and a water-miscible aprotic organic solvent. Water-miscible aprotic organic solvents and multi-component solvent compositions that are suitable for use in the dehydration process are the same as those that are suitable for use in the FDCA pathway product-generating processes as described hereinabove. In some embodiments, the water-miscible aprotic

organic solvent is *N*-Methyl-2-Pyrrolidone (NMP). In some embodiments, the carbohydrate feedstock comprises fructose and the furanic oxidation substrate comprises HMF.

Exemplary water-miscible aprotic solvents suitable for use in dehydration solvent include tetrahydrofuran, a glyme, dioxane, a dioxolane, dimethylformamide, dimethylsulfoxide, sulfolane, acetone, *N*-methyl-2-pyrrolidone ("NMP"), methyl ethyl ketone ("MEK"), gamma-valerolactone, and the like. Preferably, the water-miscible aprotic organic solvent is an ether, such as, for example, a glyme, dioxane (1,4-dioxane), a dioxolane (e.g., 1,3-dioxolane), tetrahydrofuran, and the like. Glymes that are suitable for use in the practice of the present disclosure include, for example, monoglyme (1,2-dimethoxyethane, "DME"), ethyl glyme, diglyme (diethylene glycol dimethyl ether), ethyl diglyme, triglyme, butyl diglyme, tetraglyme, a polyglyme, a highly ethoxylated diether of a high molecular weight alcohol ("higlyme"), and the like. Often, the dehydration solvent is a multi-component solvent comprising water and a water-miscible aprotic organic solvent that is glyme, diglyme, or dioxane.

In some embodiments, the water-miscible organic solvent species is at least 5 volume % (vol%), at least 10 vol%, at least 15 vol%, at least 20 vol%, at least 25 vol%, at least 30 vol%, at least 35 vol%, at least 40 vol%, at least 45 vol%, at least 50 vol%, at least 55 vol%, at least 60 vol%, at least 65 vol%, at least 70 vol%, at least 75 vol%, at least 80 vol%, at least 85 vol%, at least 90 vol%, or at least 95 vol% of the multi-component solvent; and correspondingly, water is typically less than 95 vol%, less than 90 vol%, less than 85 vol%, less than 80 vol%, less than 75 vol%, less than 70 vol%, less than 65 vol%, less than 60 vol%, less than 55 vol%, less than 50 vol%, less than 45 vol%, less than 40 vol%, less than 35 vol%, less than 30 vol%, less than 25 vol%, less than 20 vol%, less than 15 vol%, less than 10 vol%, or less than 5 vol%, respectively, of the multi-component system.

In some embodiments, the multi-component solvent comprises water in a range from or any number in between 1-5 wt% and a water-miscible organic solvent in a range from or any number in between 99-95 wt%. In some embodiments, the multi-component solvent comprises water in a range from or any number in between 5-10 wt% and a water-miscible organic solvent in a range from or any number in between 95-90 wt%. In some embodiments, the multi-component solvent comprises water in a range from or any number in between 10-15 wt% and a water-miscible organic solvent in a range from or any number in

between 90-85 wt%. In some embodiments, the multi-component solvent comprises water in a range from or any number in between 15-20 wt% and a water-miscible organic solvent in a range from or any number in between 85-80 wt%. In some embodiments, the multi-component solvent comprises water in a range from or any number in between 20-25 wt%
5 and a water-miscible organic solvent in a range from or any number in between 80-75 wt%. In some embodiments, the multi-component solvent comprises water in a range from or any number in between 25-30 wt% and a water-miscible organic solvent in a range from or any number in between 75-70 wt%. In some embodiments, the multi-component solvent comprises water in a range from or any number in between 30-35 wt% and a water-miscible
10 organic solvent in a range from or any number in between 70-65 wt%. In some embodiments, the multi-component solvent comprises water in a range from or any number in between 35-40 wt% and a water-miscible organic solvent in a range from or any number in between 65-60 wt%. In some embodiments, the multi-component solvent comprises water in a range from or any number in between 40-45 wt% and a water-miscible organic solvent in a range
15 from or any number in between 60-55 wt%. In some embodiments, the multi-component solvent comprises water in a range from or any number in between 45-50 wt% and a water-miscible organic solvent in a range from or any number in between 65-50 wt%. In some embodiments, the multi-component solvent comprises water in a range from or any number in between 50-55 wt% and a water-miscible organic solvent in a range from or any number in
20 between 50-45 wt%. In some embodiments, the multi-component solvent comprises water in a range from or any number in between 55-60 wt% and a water-miscible organic solvent in a range from or any number in between 45-40 wt%. In some embodiments, the multi-component solvent comprises water in a range from or any number in between 60-65 wt% and a water-miscible organic solvent in a range from or any number in between 40-35 wt%.
25 In some embodiments, the multi-component solvent comprises water in a range from or any number in between 65-70 wt% and a water-miscible organic solvent in a range from or any number in between 35-30 wt%. In some embodiments, the multi-component solvent comprises water in a range from or any number in between 70-75 wt% and a water-miscible organic solvent in a range from or any number in between 30-25 wt%. In some embodiments,
30 the multi-component solvent comprises water in a range from or any number in between 75-80 wt% and a water-miscible organic solvent in a range from or any number in between 25-

20 wt%. In some embodiments, the multi-component solvent comprises water in a range from or any number in between 80-85 wt% and a water-miscible organic solvent in a range from or any number in between 20-15 wt%. In some embodiments, the multi-component solvent comprises water in a range from or any number in between 85-90 wt% and a water-miscible organic solvent in a range from or any number in between 15-10 wt%. In some
5 embodiments, the multi-component solvent comprises water in a range from or any number in between 90-95 wt% and a water-miscible organic solvent in a range from or any number in between 10-5 wt%. In some embodiments, the multi-component solvent comprises water in a range from or any number in between 95-99 wt% and a water-miscible organic solvent in a
10 range from or any number in between 5-1 wt%.

In some embodiments, the volume ratio of water to water-miscible organic solvent is in the range from or any number in between 1:6 to 6:1. In certain embodiments, the volume ratio is from or any number in between 1:4 to 4:1 water:water-miscible organic solvent. In other embodiments, the volume ratio is from or any number in between 1:4 to 3:1
15 water:water miscible organic solvent. In other embodiments, the volume ratio is from or any number in between 1:3 to 3:1 water:water miscible organic solvent. In certain embodiments, the volume ratio is 1:1 water:water-miscible organic solvent.

In some embodiments, the multi-component solvent comprises water and two different water-miscible organic solvents. Typically both of the water-miscible organic
20 solvents are water-miscible aprotic organic solvents. Each of the two water-miscible aprotic solvents can be independently selected from the group of tetrahydrofuran, a glyme, a dioxane, a dioxolane, dimethylformamide, dimethylsulfoxide, sulfolane, acetone, *N*-methyl-2-pyrrolidone ("NMP"), methyl ethyl ketone ("MEK"), and gamma-valerolactone. One or both of the water-miscible aprotic organic solvent can be an ether, such as, for example, a
25 glyme, dioxane (for example 1,4-dioxane), dioxolane (e.g., 1,3-dioxolane), tetrahydrofuran, and the like. Glymes include, for example, monoglyme (1,2-dimethoxyethane, "DME"), ethyl glyme, diglyme (diethylene glycol dimethyl ether), ethyl diglyme, triglyme, butyl diglyme, tetraglyme, a polyglyme, a highly ethoxylated diether of a high molecular weight alcohol ("higlyme"), and the like.

30 In some embodiments, the volume ratio of water to the first and second water-miscible organic solvent is approximately 1:1:1 (v:v:v). In some embodiments, the volume

ratio of water to the first and second water-miscible organic solvent is approximately 1:2:1 (v:v:v). In some embodiments, the volume ratio of water to the first and second water-miscible organic solvent is approximately 1:2:2 (v:v:v). In some embodiments, the volume ratio of water to the first and second water-miscible organic solvent is approximately 2:1:1 (v:v:v).

In some embodiments, the multi-component solvent for the dehydration solvent comprises water and two different water-miscible organic solvents with the relative amounts of water to the first and second water-miscible organic solvents as shown in Table B.

Table B:

Weight percent of water in multi-component solvent system	Weight percent of first water-miscible organic solvent in multi-component solvent system	Weight percent of second water-miscible organic solvent in multi-component solvent system
1-5%	90-98%	1-5%
1-5%	85-94%	5-10%
1-5%	80-89%	10-15%
1-5%	75-84%	15-20%
1-5%	70-79%	20-25%
1-5%	65-74%	25-30%
1-5%	60-69%	30-35%
1-5%	55-64%	35-40%
1-5%	50-59%	40-45%
1-5%	45-54%	45-50%
1-5%	40-49%	50-55%
1-5%	35-44%	55-60%
1-5%	30-39%	60-65%
1-5%	25-34%	65-70%
1-5%	20-29%	70-75%
1-5%	15-24%	75-80%
1-5%	10-19%	80-85%
1-5%	5-14%	85-90%
1-5%	1-9%	90-94%
5-10%	85-94%	1-5%
5-10%	80-90%	5-10%
5-10%	75-85%	10-15%
5-10%	70-80%	15-20%
5-10%	65-75%	20-25%
5-10%	60-70%	25-30%
5-10%	55-65%	30-35%
5-10%	50-60%	35-40%
5-10%	45-55%	40-45%
5-10%	40-50%	45-50%
5-10%	35-45%	50-55%
5-10%	30-40%	55-60%

Weight percent of water in multi-component solvent system	Weight percent of first water-miscible organic solvent in multi-component solvent system	Weight percent of second water-miscible organic solvent in multi-component solvent system
5-10%	25-35%	60-65%
5-10%	20-30%	65-70%
5-10%	15-25%	70-75%
5-10%	10-20%	75-80%
5-10%	5-15%	80-85%
5-10%	1-10%	85-89%
10-15%	80-89%	1-5%
10-15%	75-85%	5-10%
10-15%	70-80%	10-15%
10-15%	65-75%	15-20%
10-15%	60-70%	20-25%
10-15%	55-65%	25-30%
10-15%	50-60%	30-35%
10-15%	45-55%	35-40%
10-15%	40-50%	40-45%
10-15%	35-45%	45-50%
10-15%	30-40%	50-55%
10-15%	25-35%	55-60%
10-15%	20-30%	60-65%
10-15%	15-25%	65-70%
10-15%	10-20%	70-75%
10-15%	5-15%	75-80%
10-15%	1-10%	80-84%
15-20%	75-84%	1-5%
15-20%	70-80%	5-10%
15-20%	65-75%	10-15%
15-20%	60-70%	15-20%
15-20%	55-65%	20-25%
15-20%	50-60%	25-30%
15-20%	45-55%	30-35%
15-20%	40-50%	35-40%
15-20%	35-45%	40-45%
15-20%	30-40%	45-50%
15-20%	25-35%	50-55%
15-20%	20-30%	55-60%
15-20%	15-25%	60-65%
15-20%	10-20%	65-70%
15-20%	5-15%	70-75%
15-20%	1-10%	75-79%
20-25%	70-79%	1-5%
20-25%	65-75%	5-10%
20-25%	60-70%	10-15%
20-25%	55-65%	15-20%
20-25%	50-60%	20-25%
20-25%	45-55%	25-30%
20-25%	40-50%	30-35%

Weight percent of water in multi-component solvent system	Weight percent of first water-miscible organic solvent in multi-component solvent system	Weight percent of second water-miscible organic solvent in multi-component solvent system
20-25%	35-45%	35-40%
20-25%	30-40%	40-45%
20-25%	25-35%	45-50%
20-25%	20-30%	50-55%
20-25%	15-25%	55-60%
20-25%	10-20%	60-65%
20-25%	5-15%	65-70%
20-25%	1-10%	70-74%
25-30%	65-74%	1-5%
25-30%	60-70%	5-10%
25-30%	55-65%	10-15%
25-30%	50-60%	15-20%
25-30%	45-55%	20-25%
25-30%	40-50%	25-30%
25-30%	35-45%	30-35%
25-30%	30-40%	35-40%
25-30%	25-35%	40-45%
25-30%	20-30%	45-50%
25-30%	15-25%	50-55%
25-30%	10-20%	55-60%
25-30%	5-15%	60-65%
25-30%	1-10%	65-69%
30-35%	60-69%	1-5%
30-35%	55-65%	5-10%
30-35%	50-60%	10-15%
30-35%	45-55%	15-20%
30-35%	40-50%	20-25%
30-35%	35-45%	25-30%
30-35%	30-40%	30-35%
30-35%	25-35%	35-40%
30-35%	20-30%	40-45%
30-35%	15-25%	45-50%
30-35%	10-20%	50-55%
30-35%	5-15%	55-60%
30-35%	1-10%	60-64%
35-40%	55-64%	1-5%
35-40%	50-60%	5-10%
35-40%	45-55%	10-15%
35-40%	40-50%	15-20%
35-40%	35-45%	20-25%
35-40%	30-40%	25-30%
35-40%	25-35%	30-35%
35-40%	20-30%	35-40%
35-40%	15-25%	40-45%
35-40%	10-20%	45-50%
35-40%	5-15%	50-55%

Weight percent of water in multi-component solvent system	Weight percent of first water-miscible organic solvent in multi-component solvent system	Weight percent of second water-miscible organic solvent in multi-component solvent system
35-40%	1-10%	55-59%
40-45%	50-59%	1-5%
40-45%	45-55%	5-10%
40-45%	40-50%	10-15%
40-45%	35-45%	15-20%
40-45%	30-40%	20-25%
40-45%	25-35%	25-30%
40-45%	20-30%	30-35%
40-45%	15-25%	35-40%
40-45%	10-20%	40-45%
40-45%	5-15%	45-50%
40-45%	1-10%	50-54%
45-50%	45-54%	1-5%
45-50%	40-50%	5-10%
45-50%	35-45%	10-15%
45-50%	30-40%	15-20%
45-50%	25-35%	20-25%
45-50%	20-30%	25-30%
45-50%	15-25%	30-35%
45-50%	10-20%	35-40%
45-50%	5-15%	40-45%
45-50%	1-10%	45-49%
50-55%	40-49%	1-5%
50-55%	35-45%	5-10%
50-55%	30-40%	10-15%
50-55%	25-35%	15-20%
50-55%	20-30%	20-25%
50-55%	15-25%	25-30%
50-55%	10-20%	30-35%
50-55%	5-15%	35-40%
50-55%	1-10%	40-44%
55-60%	35-44%	1-5%
55-60%	30-40%	5-10%
55-60%	25-35%	10-15%
55-60%	20-30%	15-20%
55-60%	15-25%	20-25%
55-60%	10-20%	25-30%
55-60%	5-15%	30-35%
55-60%	1-10%	35-39%
60-65%	30-39%	1-5%
60-65%	25-35%	5-10%
60-65%	20-30%	10-15%
60-65%	15-25%	15-20%
60-65%	10-20%	20-25%
60-65%	5-15%	25-30%
60-65%	1-10%	30-34%

Weight percent of water in multi-component solvent system	Weight percent of first water-miscible organic solvent in multi-component solvent system	Weight percent of second water-miscible organic solvent in multi-component solvent system
65-70%	25-34%	1-5%
65-70%	20-30%	5-10%
65-70%	15-25%	10-15%
65-70%	10-20%	15-20%
65-70%	5-15%	20-25%
70-75%	20-29%	1-5%
70-75%	15-25%	5-10%
70-75%	10-20%	10-15%
70-75%	5-15%	15-20%
75-80%	15-24%	1-5%
75-80%	10-20%	5-10%
75-80%	5-15%	10-15%

The concentration of sugar in the carbohydrate feedstock is typically in the range of from or any number in between 2 wt% to 80 wt% or from or any number in between 5 wt% to 80 wt%. In various embodiments, the concentration of sugar is in the range of from or any number in between 20 wt% to 80 wt%. In some embodiments, the concentration of sugar in the carbohydrate feedstock is in the range of from or any number in between 5 wt% to 20 wt%. In other embodiments, the concentration of sugar in the carbohydrate feedstock is in the range of from or any number in between 5 wt% to 40 wt%. In some embodiments, the concentration of sugar in the carbohydrate feedstock ranges from or any number in between 5-15 wt%, 10-20 wt%, 15-25 wt%, 20-30 wt%, 25-35 wt%, 30-40 wt%, 35-45 wt%, 40-50 wt%, 45-55 wt%, 50-60 wt%, 55-65 wt%, 60-70 wt%, 65-75 wt% or 70-80 wt%, or within a range defined by any two of the aforementioned weight percentages.

Catalysts that are suitable for use in the dehydration process include homogeneous catalysts, including, for example, homogeneous acid catalysts, and the like, as well as heterogeneous catalysts. Suitable homogeneous acid catalysts include, for example, an inorganic acid, such as, for example, a mineral acid (e.g., H_2SO_4 , HNO_3 , HCl , HBr , or HI , and the like, as well as any combination of two or more thereof), a Brønsted acid (e.g., HCl , HI , H_2SO_4 , HNO_3 , H_3PO_4 , oxalic acid, methanesulfonic acid, or trifluoromethanesulfonic acid, and the like, as well as any combination of any two or more thereof), a Lewis acid (e.g., a boron trihalide, an organoborane, an aluminum trihalide, a phosphorus pentafluoride, an antimony pentafluoride, a rare earth metal triflate, a metal halide (e.g., ZnCl_2 and ZnBr_2), a metal trifluoroacetate or a metal cation ether complex, and the like, as well as any

combination of two or more thereof), an organic acid (e.g., triflic acid, methansulfonic acid, benzenesulfonic acid, p-toluene sulfonic acid, oxalic acid, or levulinic acid, and the like, as well as any combination of two or more thereof), and any combination thereof.

Quantities of homogeneous catalyst employed are typically in the range of from or
5 any number in between 0.1 to 25 mol%, and more typically in the range of from or any number in between 0.5 to 5 mol% (wherein, mol% is calculated on the basis of moles of sugar, e.g., hexose). Heterogeneous catalysts that are suitable for use in the practice of the present disclosure include an acid-functionalized resin, an acidified carbon, a zeolite, a micro- and/or meso-porous metal oxide, a sulfonated metal oxide, a phosphonated metal
10 oxide, a clay, or a polyoxometallate, and combinations thereof. Preferred heterogeneous catalysts include acid-functionalized resins. The heterogeneous catalyst loading is typically in the range of from or any number in between 1 g/L to 20 g/L in a slurry reactor, (such as e.g., 1, 2, 3, 4, 5, 6, 7, 8, 9, 10, 11, 12, 13, 14, 15, 16, 17, 18, 19 or 20 g/L) and in the range of from or any number in between 200 g/L to 1500 g/L (such as e.g., 200, 300, 400, 500, 600, 700,
15 800, 900, 1000, 1100, 1200, 1300, 1400, or 1500 g/L) in a fixed bed reactor. The skilled artisan will recognize that the heterogeneous catalyst loading will vary depending on the specific type of reactor used, but can readily determine the loading based on these guidelines.

In a further specific embodiment, the present disclosure provides a process for producing a furanic oxidation substrate, the process comprising:

20 (a⁰) contacting a carbohydrate feedstock comprising a sugar and a dehydration solvent with an acid catalyst under conditions sufficient to form a (dehydration) reaction mixture for dehydrating the sugar to produce a furanic oxidation substrate, wherein the acid catalyst is an acid selected from the group consisting of HBr, H₂SO₄, HNO₃, HCl, HI, H₃PO₄, triflic acid, methansulfonic acid, benzenesulfonic acid, and p-toluene sulfonic acid,

25 wherein when the acid catalyst is not HBr, the reaction mixture further comprises a bromide salt, and

wherein the dehydration solvent comprises NMP. Typically, the acid catalyst is a homogeneous acid catalyst. Suitable organic acids include those mentioned hereinabove. Suitable bromide salts include LiBr, NaBr, KBr, MgBr₂, CaBr₂, ZnBr₂, or ammonium
30 bromide salts having the chemical structure of R₄N⁺Br⁻, where R is a C₁-C₆ alkyl group. Exemplary ammonium bromide salts include, but are not limited to, tetramethylammonium

bromide, tetraethylamminium bromide, tetrapropylammonium bromide, or tetrabutylammonium bromide, and the like. The quantity of bromide salt employed is typically in molar excess of the acid present in the reaction mixture.

Quantities of acid catalyst employed are typically in the range of from or any number in between 0.1 to 25 mol%, and more typically in the range of from or any number in between 0.5 to 5 mol% (wherein, mol% is calculated on the basis of moles of sugar, e.g., hexose). In some embodiments, the amount of acid catalyst in the reaction mixture for dehydrating the sugar results in the reaction mixture having an acidic pH. In some embodiments, the amount of acid catalyst in the reaction mixture for dehydrating the sugar results in the reaction mixture having a pH of less than 6. In some embodiments, the amount of acid catalyst in the reaction mixture for dehydrating the sugar results in the reaction mixture having a pH of less than 5. In some embodiments, the amount of acid catalyst in the reaction mixture for dehydrating the sugar results in the reaction mixture having a pH of less than 4. In some embodiments, the amount of acid catalyst in the reaction mixture for dehydrating the sugar results in the reaction mixture having a pH of less than 3. In some embodiments, the amount of acid catalyst in the reaction mixture for dehydrating the sugar results in the reaction mixture having a pH of less than 2. In some embodiments, the amount of acid catalyst in the reaction mixture for dehydrating the sugar results in the reaction mixture having a pH of less than 1.

The dehydration reaction mixtures described hereinabove are typically maintained at a temperature in the range of from or any number in between 50°C to 250°C, (such as e.g., 50, 60, 70, 80, 90, 100, 110, 120, 130, 140, 150, 160, 180, 190, 200, 210, 220, 230, 240, or 250 °C or within a range defined by any two of the aforementioned temperatures) and a pressure in the range of from or any number in between 1 atm to 15 atm, or from or any number in between 2 atm to 15 atm (such as e.g., 1, 2, 3, 4, 5, 6, 7, 8, 9, 10, 11, 12, 13 14, or 15 atm). More typically, the dehydration reaction mixture is maintained at a temperature in the range of from or any number in between 80°C to 180°C (such as e.g., 80, 90, 100, 110, 120, 130, 140, 150, 160, 180 °C or within a range defined by any two of the aforementioned temperatures). In some embodiments, the dehydration mixture is maintained at a temperature in the range of from or any number in between 80°C and 160°C, or 80°C and 150°C, or 80°C and 140°C, or 80 and 130°C, or 80°C and 120°C, or 80°C and 110°C, or 80°C and 100°C. In

some embodiments, the dehydration mixture is maintained at a temperature that is less than 110°C, or less than 100°C. Applicants have discovered that the dehydration mixture of the present disclosure can provide surprisingly high yields of furanic oxidation substrate at relatively low temperatures of less than 110°C, such as less than 100°C.

5 To minimize production of undesired products, and maximize yield of the furanic oxidation substrate, it may be desirable to carry out the dehydration reaction to a partial conversion endpoint, as described in WO 2015/113060 (which is incorporated herein by reference), by quenching the reaction, and separating and recycling unconverted sugar, by, for example, filtration. When the furanic oxidation substrate is generated by the dehydration
10 reaction, it is present in a dehydration product solution. As used herein, the term "dehydration product solution" refers to a solution comprising the furanic oxidation substrate and the dehydration solvent. The dehydration product solution can be a mixture that includes dissolved furanic oxidation substrate and one or more components that are not dissolved, wherein the one or more components that are not dissolved are selected from humin and
15 unreacted sugar. The furanic oxidation substrate may be optionally separated from one or more components selected from the group consisting of a humin and an unreacted sugar and/or isolated from the dehydration product solution, and optionally further purified. In one such embodiment, the dehydration product solution is subjected to a membrane to effect the separation of the furanic oxidation substrate from one or more components selected from the
20 group consisting of a humin and an unreacted sugar. Membranes suitable for use for such separation include nanofiltration membranes, ultrafiltration membranes, and combination thereof.

The dehydration product solution may be used as a feedstock for producing an FDCA pathway product or derivative thereof, or another subsequent process that utilizes the furanic
25 oxidation substrate. Typically, the furanic oxidation substrate is HMF.

The dehydration of the carbohydrate feedstock to produce the furanic oxidation substrate can produce the furanic oxidation substrate in yield that is typically at least 60% (on a molar basis). In some embodiments, the yield is at least 70%, and in other embodiments, it is at least 80%, at least 90%, at least 95%, at least 98% or at least 99%. In some
30 embodiments, the yield ranges from between 60-65%, 62-67%, 65-70%, 67-72%, 70-75%,

72-77%, 75-80%, 77-82%, 80-85%, 82-87%, 85-90%, 87-92%, 90-95%, 92-97%, 95-98%, or 97-99%, or is within a range defined by any of two of the aforementioned percentages.

In a specific embodiment, prior to step (a) of the FDCA pathway product-generating oxidation processes of the present disclosure, step (a⁰) is carried out to produce a furanic oxidation substrate in a dehydration product solution. The dehydration product solution can be used either directly or indirectly (i.e., with one or more intervening pre-treatment step(s)), as the oxidation feedstock for step (a). The pre-treatment step(s) may include a separation step (e.g., filtration or membrane separation step (such as, for example ultrafiltration or nanofiltration), chromatography, ion exchange, and the like), a distillation step (to remove all or a portion of a component solvent), or other similar step/process suitable for amending the composition of the dehydration product solution to conform to a desired composition or form of the oxidation feedstock to be used in step (a). In this embodiment, the dehydration solvent typically comprises at least one solvent species in common with the oxidation solvent. One or more additional solvent species may be added to the dehydration product solution during a pre-treatment step to formulate the dehydration product solution into a desired oxidation feedstock composition for use in step (a). To illustrate, the dehydration solvent may be a water-miscible aprotic organic solvent. After conducting step (a⁰), but before performing step (a), water can be added to the dehydration product solution in a pre-treatment step, and the resulting oxidation feedstock, comprising the furanic oxidation substrate and oxidation solvent (i.e., in this example, a multi-component solvent made up of the water-miscible aprotic organic solvent and water) can be used in step (a). Alternatively, the dehydration product solution can be used directly (i.e., as is) as the oxidation feedstock for step (a). In this embodiment, the dehydration production solution comprises a dehydration solvent that is typically a multi-component solvent comprising water and an aprotic organic solvent (i.e., a multi-component solvent that is suitable for use as the oxidation solvent).

The foregoing and other aspects of the disclosure may be better understood in connection with the following non-limiting examples.

EXAMPLES

EXAMPLE 1FDCA Solubility Characterization

Solvents were screened for the ability to dissolve FDCA. 10 ml of a candidate
5 solvent was heated to a certain temperature and FDCA (Product No. F0710, TCI America)
was added by small portions to the heated candidate solvent until the FDCA amount
exceeded the solubility limit. After that, small volumes of solvent were added until the
excess solids were completely dissolved. The experiment was repeated two times at each
temperature and the average was taken as FDCA solubility. Five solvents were tested: (1)
10 deionized water; (2) diglyme; (3) dioxane; (4) a 1:1 by volume mixture of diglyme with
deionized water; and (5) a 4:1 by volume mixture of dioxane with deionized water. The
results are depicted in Figure 3 as a plot of FDCA Solubility (Weight %) as a function of
temperature (°C). The results show that FDCA appears to have relatively low solubilities in
each of water, diglyme, and dioxane in the temperature range of 25°C to 100°C. However,
15 when each of the organic solvents was combined with water, the resulting co-solvent
appeared to provide a synergistic enhancement in FDCA solubilizing capability. For
example, at 100°C, although FDCA solubility in water and diglyme individually was less
than 1% (by weight) and less than 2% (by weight), respectively, FDCA solubility reached
9% (by weight) when the two solvents were combined in a co-solvent system of 1:1 ratio of
20 deionized water:diglyme, by volume. Similarly, at 100°C, although FDCA solubility in
water and dioxane individually was less than 1% (by weight) and less than 2% (by weight),
respectively, the FDCA solubility trend line for the co-solvent system of 1:4 ratio of
deionized water:dioxane, by volume, indicates 9% (by weight) FDCA solubility.

25

EXAMPLE 2Preparation of Heterogeneous Oxidation Catalyst (3 wt% Pt/silica)

A metal precursor solution was first prepared by mixing 0.152 ml of a solution of
Pt(NH₃)₄(OH)₂ (containing 101.8 mg Pt/ml) with 0.047 ml of de-ionized water. This solution
was used to impregnate 0.5 g of silica (Cariact Q-50, BET specific surface area 80 m²/g,
30 mean pore diameter 50 nm, particle size 75-150 µm, Fuji Silysia Corporation). After
impregnation, the material was dried at 120°C for two hours, then reduced under a flow of

6% H₂ in argon at 300°C for two hours. After cooling, the material was passivated under a flow of 0.5% O₂ in nitrogen for 15 minutes. The resultant material, containing a 3 wt% Pt loading, was used for catalytic activity testing, as described in Example 11, without any further pretreatment.

5

EXAMPLES 3 AND 4

Preparation of Heterogeneous Oxidation Catalyst (2.5 wt% Pt/silica and 4 wt% Pt/silica)

Heterogeneous oxidation catalysts were prepared as described in Example 2 except that 0.204 ml of Pt(NH₃)₄(OH)₂ solution (containing 62.8 mg Pt/ml) and 0.546 ml of deionized water, was used to prepare heterogeneous oxidation catalysts with platinum loadings of 2.5 wt% (Example 3) and 0.205 ml of Pt(NH₃)₄(OH)₂ solution (containing 101.8 mg Pt/ml) and 0.42 ml de-ionized water were used to prepare catalyst with a platinum loading of 4 wt% (Example 4). The resultant materials were used for catalytic activity testing as described in Example 11.

15

EXAMPLE 5

Preparation of Heterogeneous Oxidation Catalyst (3 wt% Pt/ZrO₂)

A metal precursor solution was first prepared by mixing 0.152 ml of a solution of Pt(NH₃)₄(OH)₂ (containing 101.8 mg Pt/ml) with 0.048 ml of deionized water. This solution was used to impregnate 0.5 g ZrO₂ (SZ31163, BET specific surface area 55 m²/g, bimodal pore size distributions with mean pore diameters of 16 and 60 nm, particle size < 150 μm, Saint Gobain). After impregnation, the material was dried at 120°C for 2 hours and then reduced under a flow of 6% H₂ in argon at 300°C for 2 hours. After cooling, the material was passivated under a flow of 0.5% O₂ in nitrogen for 15 minutes. The resultant material, containing a 3 wt% Pt loading, was used for catalytic activity testing, as described in Example 11, without any further pretreatment.

25

EXAMPLE 6

Preparation of Heterogeneous Oxidation Catalyst (4 wt% Pt/ZrO₂)

The heterogeneous oxidation catalyst was prepared as described in Example 5 except 0.205 ml of the same Pt(NH₃)₄(OH)₂ solution was used to prepare a material with a platinum

30

loading of 4 wt%. The resultant material was used for catalytic testing as described in Example 11.

EXAMPLE 7

Preparation of Heterogeneous Oxidation Catalyst (3 wt% Pt/Al₂O₃)

A metal precursor solution was first prepared by mixing 0.152 ml of a solution of Pt(NH₃)₄(OH)₂ (containing 101.8 mg Pt/ml) with 0.298 ml of deionized water. This solution was used to impregnate 0.5 g Al₂O₃ (SA 31132, BET specific surface area 55 m²/g, bimodal with mean pore diameters of 25 and 550 nm, particle size <150 μm, Saint Gobain). After impregnation, the material was dried at 120°C for 2 hours. Finally, the material was reduced under flow of 6% H₂ in argon at 300°C for 2 hours. After cooling, the material was passivated under a flow of 0.5% O₂ in nitrogen for 15 minutes. The resultant material, containing a 3 wt% Pt loading, was used for catalytic activity testing, as described in Example 11, without any further pretreatment.

EXAMPLE 8

Preparation of Heterogeneous Oxidation Catalyst (4 wt% Pt/Al₂O₃)

The heterogeneous oxidation catalyst in this example was prepared in the manner described in Example 7, except that 0.205 ml of the same Pt(NH₃)₄(OH)₂ solution and 0.245 ml of de-ionized water were used to prepare a metal precursor solution that was used to prepare material with a platinum loading of 4 wt%. The resultant material was used for catalytic activity testing as described in Example 11.

EXAMPLES 9 and 10

Preparation of Heterogeneous Oxidation Catalysts

(2 wt% Pt, 1 wt% Au /silica; 1 wt% Pt, 2 wt% Au/silica)

A metal precursor solution was first prepared by mixing 0.018 ml of a solution of PtONO₃ (containing 100 mg Pt/ml) with 0.009 ml of a solution of (NH₄)₂AuO₂ (containing 100 mg Au/ml) and 0.09 ml of deionized water (Example 9), and correspondingly mixing 0.009 ml of the PtONO₃ solution (containing 100 mg Pt/ml) with 0.018 ml of (NH₄)₂AuO₂ solution (containing 100 mg Au/ml) and 0.09 ml deionized water (Example 10). Each

solution was used to impregnate 0.1 g of silica (Cariact Q-50, particle size 75-150 μm , specific surface area 80 m^2/g , mean pore diameter 50 nm, Fuji Silisia Corporation). After impregnation, material was reduced under flow of 6% H_2 in argon at 350 $^\circ\text{C}$ for 3 hours. After cooling, the material was passivated under a flow of 0.5% O_2 in nitrogen for 15 minutes. The resultant materials, containing a 2 wt% Pt loading and a 1 wt% Au loading (Example 9) and containing a 1 wt% Pt, 2 wt% Au loading (Example 10) were used for catalytic activity testing, as described in Example 11, without any further pretreatment.

EXAMPLE 11

Catalyst Performance Assay and Production of FDCA Pathway Products

Catalyst testing was conducted within 1 ml glass vials housed in a 96-well insert situated in a high pressure high throughput reactor. See Diamond, G. M., Murphy, V., Boussie, T. R., in *Modern Applications of High Throughput R&D in Heterogeneous Catalysis*, (eds, Hagemeyer, A. and Volpe, A. Jr. Bentham Science Publishers 2014, Chapter 8, 299-309); see also US 8,669,397, both of which are incorporated herein by reference. 20 mg of each catalyst was placed into the reactor along with 0.8 ml of a 0.5 M HMF solution prepared in a 4:1 (v/v) dioxane: H_2O mixture (this corresponds to 6 wt% of HMF). The 1 ml reaction vials within the insert were each covered with a Teflon sheet, a silicon mat and a steel gas diffusion plate each containing pin-holes to enable gas entry. The insert was placed within a pressure vessel which was leak tested under nitrogen pressure. The atmosphere within the reactor was then replaced by oxygen and the reactor was heated to 90 $^\circ\text{C}$ and shaken at 500 rpm for 20 hours, and at 200 psig oxygen pressure. After the reaction was completed, the shaking was stopped and the reactor was cooled down to room temperature. Samples were prepared for HPLC analysis by sampling from each reactor and diluting the sample by a factor of 200 with a 4:1 dioxane: H_2O mixture. Reaction products were hydroxymethylfurancarboxylic acid (HMFA), formylfurancarboxylic acid (FFCA), diformylfuran (DFF) and FDCA. The results are shown in Table 1.

Table 1. Catalyst Composition and Performance.

Example	BET Specific Surface Area	Mean Pore Diameter	Support	Pt, wt%	Au, wt%	HMFCA Yield %	DEF Yield %	FFCA Yield %	FDCA Yield %
2	75	50 nm	SiO ₂	3	0	0	0	1	91
3	75	50 nm	SiO ₂	4	0	0	0	2	81
4	75	50 nm	SiO ₂	2.5	0	0	0	4	85
5	55	Bimodal 16 nm & 60 nm	ZrO ₂	3	0	0	0	31	52
6	55	Bimodal 16 nm & 60 nm	ZrO ₂	4	0	0	0	21	56
7	55	Bimodal 25 nm & 550 nm	Al ₂ O ₃	3	0	0	0	32	37
8	55	Bimodal 25 nm & 550 nm	Al ₂ O ₃	4	0	0	0	30	36
9	75	50 nm	SiO ₂	2	1	0	0	30	43
10	75	50 nm	SiO ₂	1	2	2	10	40	10

At the relatively low metal loadings reported above, the BET specific surface areas of the solid support materials are believed to remain unchanged in the formulated heterogeneous oxidation catalyst.

EXAMPLE 12

Preparation and Testing of Carbon-Supported Catalysts

An aqueous solution (0.10 ml) containing 10 mg/ml Au added in the form of Me₄NAuO₂ and 20 mg/ml Pt added in the form of PtO(NO₃) was added to carbon black powder (100 mg) of Cabot Monarch 570. The mixture was agitated to impregnate the carbon black support and was dried in a 70°C oven overnight under a dry air purge. The sample was then reduced at 350°C under forming gas (5% H₂ and 95% N₂) atmosphere for 2 hours with 5°C/min temperature ramp rate. The final catalyst was composed of ca. 1.0 wt% Au and 2.0

wt% Pt. By using other carbon black and adjusting amount of Au and Pt in solution, different catalysts with various Au and Pt loadings on a variety of commercial carbon black powders or particles from extrudates were prepared in a similar manner. The compositions for these catalysts are listed in Table 2, hereinbelow.

5 These catalysts were tested for hydroxymethylfurfural (HMF) oxidation using the following testing protocol. Catalyst (10 mg) was weighed into a glass vial insert followed by addition of an aqueous HMF solution (250 μ l of 0.50 M or 6.0 wt% in 1,4-dioxane:water (4:1 v/v)). The glass vial insert was loaded into a reactor and the reactor was closed. The atmosphere in the reactor was replaced with oxygen and pressurized to 200 psig at room
10 temperature. The reactor was heated to 110°C and maintained at the respective temperature for 4 hours, or 90°C and maintained at the respective temperature for 20 hours, while the vial was shaken. After that, shaking was stopped and reactor was cooled to 40°C. The pressure in the reactor was then slowly released. The glass vial insert was removed from the reactor and centrifuged. The solution was diluted with 1,4-dioxane: water (4:1 v/v) and analyzed by
15 HPLC with a UV detector to determine the yield of 2,5-furandicarboxylic acid (FDCA). The results are presented in Table 2.

Table 2. Catalyst Composition and Performance.

Carbon Support	BET Surface Area m ² /g	Mean Pore Diameter (nm)	Screening Condition	Metal Loading	FDCA Yield (mol%)
Cabot Monarch 120	23	28	90°C/20h	3.0 wt% Pt	82
Cabot Monarch 280	30	18	90°C/20h	3.0 wt% Pt	88
Cabot Monarch 280	30	18	90°C/20h	1.0 wt% Au 2.0 wt% Pt	60
Cabot Monarch 570	102	14	90°C/20h	3.0 wt% Pt	84
Cabot Monarch 570	102	14	90°C/20h	1.0 wt% Au 2.0 wt% Pt	68
Cabot Monarch 700	181	12	90°C/20h	3.0 wt% Pt	81
Cabot Monarch 700	181	12	90°C/20h	1.0 wt% Au 2.0 wt% Pt	73
Sid Richardson SC159	231	13	90°C/20h	3.0 wt% Pt	70
Timcal Ensaco 150G	47	14	90°C/20h	3.0 wt% Pt	82
Timcal Ensaco 250G	64	14	90°C/20h	3.0 wt% Pt	79
Cabot Monarch 120	23	28	110°C/4h	3.0 wt% Pt	65

Carbon Support	BET Surface Area m ² /g	Mean Pore Diameter (nm)	Screening Condition	Metal Loading	FDCA Yield (mol%)
Cabot Monarch 280	30	18	110°C/4h	3.0 wt% Pt	73
Cabot Monarch 570	102	14	110°C/4h	3.0 wt% Pt	62
Cabot Monarch 700	181	12	110°C/4h	3.0 wt% Pt	67
Timcal Ensaco 150G	47	14	110°C/4h	3.0 wt% Pt	71

EXAMPLE 13

Crystallization of FDCA from a Multi-component Solvent Comprising Water and an Aprotic Organic Solvent

5 0.5 g FDCA was weighed into 2 vials with magnetic stirrers. In Vial 1, 3 ml H₂O and 2 ml glyme were added. In Vial 2, 2 ml H₂O and 3 ml glyme was added. Insoluble milky white suspensions formed at room temperature. The vials were heated with stirring to 140°C in an oil bath. The suspension in Vial 1 turned into a clear solution with full apparent FDCA solubility at ~130°C. The suspension in Vial 2 turned into a clear solution with full apparent
10 FDCA solubility at ~110°C. As the temperature of the clear solutions were slowly reduced to room temperature, FDCA crystallized to produce purified FDCA.

Description of Analytical Method

The analytical instrumentation used in the following examples was a Thermo
15 Scientific Dionex Ultimate System fitted with a Thermo Scientific Hypercarb 3 µm 3x50 mm analytical column and a 3000 RS Variable Wavelength UV/Vis Detector.

EXAMPLE 14

Preparation of 40 g Heterogeneous Oxidation Catalyst (3.0 wt.% Pt /carbon)

20 A metal precursor solution was first prepared by mixing 5.64 ml of a solution of platinum nitrate (containing 219 mg Pt/ml from Heraeus Group) and 94.4 ml of deionized water. This solution was used to impregnate 40.0 g of carbon powder (Continental N234 carbon black powder, BET surface area 117 m²/g, average pore diameter 14 nm). After impregnation, the material was dried at 100°C for 3 hours and then reduced under a flow of
25 5% H₂ in nitrogen at 350°C for 3 hours with 5°C/min temperature ramp rate. After cooling,

the material was passivated under a flow of 0.5% O₂ in nitrogen for 15 minutes. The resultant material, containing a 3.0 wt.% Pt loading, was used for catalytic activity testing as described in Example 15, without any further pretreatment.

5

EXAMPLE 15

Testing of Carbon-Supported Catalyst in Parr Pressure Reactor

Catalyst testing was conducted in a 300 ml Parr stainless steel autoclave pressure reactor. Catalyst was weighed (e.g., 8.00 g of 3.0 wt.% Pt / Continental N234 carbon black powder) and placed into reactor, along with a substrate HMF (5-(hydroxymethyl)furfural) solution (100 g 6.0 wt.% prepared in either a 65wt.% DME/35wt.% H₂O solvent mixture or a 60wt.% 1,4-Dioxane/40wt.% H₂O solvent mixture). The reactor was assembled and a magnetic drive coupled stirrer was attached.

The reactor was pressurized with process gas (O₂) to desired pressure with stirring (1000 rpm) at ambient temperature, followed by heating to target temperature and holding at that temperature for the planned reaction time. After the ascribed reaction time, the reactor was cooled with stirring lowered to *ca.* 200 rpm, and vented slowly at 30°C.

Dimethyl sulfoxide (DMSO) was added to the reactor for the first step dilution. After stirring for *ca.* 30 min, the product solution was centrifuged and further diluted with de-ionized water for HPLC analysis.

The reaction products were 5-Hydroxymethyl-furan-2-carboxylic acid (HMFCFA), 2,5-Furandicarboxaldehyde (DFF), 5-Formylfuran-3-carboxylic acid (FFCA), and 2,5-Furandicarboxylic Acid (FDCA). Each of above products as well as any remaining HMF was quantified through a calibration curve for each analyte by plotting the relative concentration vs. the relative detector response of calibration standard samples and fit to a parabolic expression. Results are summarized in Table 3.

Table 3. Catalyst Performance in Parr Pressure Reactor.

Run No.	Catalyst (g)	Temp. (°C)	O ₂ Pressure (psig)	Reaction Time (min)	Solvent	FFCA Yield (mol%)	FDCA Yield (mol%)	Mass Balance (mol%)
1	8.00	120	200	90	65wt.%DME/ 35wt.%H ₂ O	1.1	90.0	91.1

3	8.00	110	250	90	65wt.%DME/ 35wt.%H ₂ O	4.9	91.3	96.2
4	8.00	110	250	120	60wt.%Dioxane/ 40wt.%H ₂ O	2.7	92.4	95.1

Mass balance represent the sum of the mol% yields of HMF, HMFCa, DFF, FFCA and FDCA.

5

EXAMPLE 16

Preparation and Testing of a Variety of Carbon-Supported Catalysts

An aqueous solution (0.60 ml) containing 10 mg/ml Pt in the form of platinum nitrate was added to carbon black powder (200 mg), and the resultant material was agitated to impregnate the supports. The samples were then dried in an oven at 70°C overnight, and reduced at 350°C under a forming gas (5% H₂ and 95% N₂) atmosphere for 3 hours with 5°C/min temperature ramp rate to produce catalyst with a composition of 3.0 wt.% Pt. By using other carbon black supports, Pt precursors, and adjusting amount of Pt in solution, different catalysts with various Pt loadings on a variety of commercial carbon black powders, particles from extrudates, or extrudates can be prepared in a similar manner.

These catalysts were tested for 5-(Hydroxymethyl)furfural (HMF) oxidation using the following testing protocol. Catalyst (10 mg) was weighed into a 1 ml glass vial insert followed by addition of an HMF solution (250 µl of 6.0 wt.% or 0.50 M in 23wt.% Diglyme/77wt.% H₂O). The glass vial insert was loaded into a reactor and the reactor was closed. The atmosphere in the reactor was replaced with oxygen and pressurized to 200 psig at ambient temperature. The reactor was heated to 110°C and maintained at the respective temperature for 3 hours while the vial was shaken. After that, shaking was stopped and reactor was cooled to 40°C. Pressure in the reactor was then slowly released. The glass vial insert was removed from the reactor and centrifuged. The solution was diluted with dimethyl sulfoxide (DMSO) followed by 1,4-dioxane : water (2:1 v/v) and analyzed by HPLC with a UV detector to determine the yield of 2,5-furandicarboxylic acid (FDCA). Results are presented in Table 4.

Table 4. Catalyst Performance.

Carbon Support	BET Surface Area (m ² /g)	FDCA Yield (mol%)
Orion Arosperse 15	9	66
Asbury A99	19	44
Orion Lamp Black 101	20	82
Cabot Monarch 120	23	80
Cabot Monarch 280	30	82
Asbury 5375R	30	77
Asbury 5365R	34	81
Asbury 5345	37	80
Continental N550	38	80
Continental N120	39	80
Arosperse 5-183A	42	79
Timcal Ensaco 150G	47	77
Timcal Ensaco 250G	56	80
Timcal Ensaco 260G	63	79
Asbury 5348R	65	80
Asbury 5358R	67	81
Orion N330	76	78
Continental N330-C	77	80
Cabot Monarch 570	102	77
Orion HiBlack 40B2	109	58
Continental N234	117	81
Orion Arosperse 138	120	74
Sid Richardson Ground N115	128	70
Sid Richardson SC419	136	76
Sid Richardson Ground SR155	146	63
Orion HP-160	158	59
Aditya Birla CDX-KU	167	63
Aditya Birla CSCUB	169	64
Cabot Monarch 700	181	65
Orion Hi-Black 50 LB	183	69
Aditya Birla R2000B	187	67
Orion Hi-Black 50 L	193	73
Asbury 5302	211	68
Asbury 5303	219	65
Cabot Vulcan XC72	231	62
Sid Richardson SC159	231	51
Orion Hi-Black 600 L	235	70

Carbon Support	BET Surface Area (m ² /g)	FDCA Yield (mol%)
Aditya Birla R2500UB	247	46
Orion Printex L 6	250	54
Asbury 5379	271	52
Asbury 5368	303	68
Aditya Birla R3500B	320	60
Orion Color Black FW 2	350	61
Aditya Birla R5000U2	583	61
Cabot Norit Darco 12x20L1	592	12
Orion Color Black FW 255	650	58
Timcal Ensaco 350G	770	31

EXAMPLE 17

Testing of Carbon-Supported Powder Catalysts in a Variety of Solvent Compositions

A selection of above catalysts were tested for 5-(Hydroxymethyl)furfural (HMF) oxidation with very similar testing protocol by using 10 mg 3.0 wt.% Pt on carbon black powder (prepared from platinum nitrate) in an HMF solution (250 μ l of 6.0 wt.% or 0.50 M in a variety of solvent mixtures of water with DME, 1,4-dioxane and diglyme). The glass vial insert was loaded into a reactor and the reactor was closed. The atmosphere in the reactor was replaced with oxygen and pressurized to 200 psig at ambient temperature. The reactor was heated to 110°C and maintained at the respective temperature for 3 hours while the vial was shaken. After that, shaking was stopped and reactor was cooled to 40°C. The pressure in the reactor was then slowly released. The glass vial insert was removed from the reactor and centrifuged. The solution was diluted with dimethyl sulfoxide (DMSO) followed by 1,4-dioxane : water (2:1 v/v) and analyzed by HPLC with a UV detector to determine the yield of 2,5-furandicarboxylic acid (FDCA). The results are presented in Table 5.

Table 5. Powder Catalyst Performance in Various Solvent Compositions

Carbon Support	BET Surface Area (m ² /g)	Solvent	FDCA Yield (mol%)
Asbury 5358R	67	50wt.% DME/50wt.% H ₂ O	81
Asbury 5375R	30	50wt.% DME/50wt.% H ₂ O	72
Cabot Monarch 280	30	50wt.% DME/50wt.% H ₂ O	79
Continental N234	117	50wt.% DME/50wt.% H ₂ O	81
Continental N330	77	50wt.% DME/50wt.% H ₂ O	81

Carbon Support	BET Surface Area (m ² /g)	Solvent	FDCA Yield (mol%)
Orion Arosperse 5-183A	42	50wt.% DME/50wt.% H ₂ O	79
Orion Lamp Black 101	20	50wt.% DME/50wt.% H ₂ O	81
Timcal Ensaco 250G	56	50wt.% DME/50wt.% H ₂ O	80
Asbury 5358R	67	90wt.% DME/10wt.% H ₂ O	51
Asbury 5375R	30	90wt.% DME/10wt.% H ₂ O	31
Cabot Monarch 280	30	90wt.% DME/10wt.% H ₂ O	50
Continental N234	117	90wt.% DME/10wt.% H ₂ O	50
Continental N330	77	90wt.% DME/10wt.% H ₂ O	54
Orion Arosperse 5-183A	42	90wt.% DME/10wt.% H ₂ O	50
Orion Lamp Black 101	20	90wt.% DME/10wt.% H ₂ O	51
Timcal Ensaco 250G	56	90wt.% DME/10wt.% H ₂ O	50
Asbury 5358R	67	50wt.% Dioxane/50wt.% H ₂ O	73
Asbury 5375R	30	50wt.% Dioxane/50wt.% H ₂ O	60
Cabot Monarch 280	30	50wt.% Dioxane/50wt.% H ₂ O	73
Continental N234	117	50wt.% Dioxane/50wt.% H ₂ O	71
Continental N330	77	50wt.% Dioxane/50wt.% H ₂ O	74
Orion Arosperse 5-183A	42	50wt.% Dioxane/50wt.% H ₂ O	72
Orion Lamp Black 101	20	50wt.% Dioxane/50wt.% H ₂ O	74
Timcal Ensaco 250G	56	50wt.% Dioxane/50wt.% H ₂ O	76
Asbury 5358R	67	82wt.% Dioxane/18wt.% H ₂ O	53
Asbury 5375R	30	82wt.% Dioxane/18wt.% H ₂ O	30
Cabot Monarch 280	30	82wt.% Dioxane/18wt.% H ₂ O	54
Continental N234	117	82wt.% Dioxane/18wt.% H ₂ O	48
Continental N330	77	82wt.% Dioxane/18wt.% H ₂ O	52
Orion Arosperse 5-183A	42	82wt.% Dioxane/18wt.% H ₂ O	48
Orion Lamp Black 101	20	82wt.% Dioxane/18wt.% H ₂ O	53
Timcal Ensaco 250G	56	82wt.% Dioxane/18wt.% H ₂ O	50
Asbury 5358R	67	23wt.% Diglyme/77wt.% H ₂ O	75
Asbury 5375R	30	23wt.% Diglyme/77wt.% H ₂ O	73
Cabot Monarch 280	30	23wt.% Diglyme/77wt.% H ₂ O	77
Continental N234	117	23wt.% Diglyme/77wt.% H ₂ O	75
Continental N330	77	23wt.% Diglyme/77wt.% H ₂ O	77
Orion Arosperse 5-183A	42	23wt.% Diglyme/77wt.% H ₂ O	76
Orion Lamp Black 101	20	23wt.% Diglyme/77wt.% H ₂ O	79
Timcal Ensaco 250G	56	23wt.% Diglyme/77wt.% H ₂ O	76
Asbury 5358R	67	50wt.% Diglyme/50wt.% H ₂ O	75
Asbury 5375R	30	50wt.% Diglyme/50wt.% H ₂ O	68
Cabot Monarch 280	30	50wt.% Diglyme/50wt.% H ₂ O	73
Continental N234	117	50wt.% Diglyme/50wt.% H ₂ O	74

Carbon Support	BET Surface Area (m ² /g)	Solvent	FDCA Yield (mol%)
Continental N330	77	50wt.% Diglyme/50wt.% H ₂ O	74
Orion Arosperse 5-183A	42	50wt.% Diglyme/50wt.% H ₂ O	73
Orion Lamp Black 101	20	50wt.% Diglyme/50wt.% H ₂ O	74
Timcal Ensaco 250G	56	50wt.% Diglyme/50wt.% H ₂ O	73

EXAMPLE 18

Preparation and Testing of Carbon-Based Extrudate Catalysts in a Variety of Solvent Mixtures

5 An aqueous solution (0.25 ml) containing 60 mg/ml Pt in the form of platinum nitrate was added to carbon extrudates (average 3 mm length and 0.75 mm diameter, 500 mg, prepared as described in WO 2015/168327, which is incorporated herein by reference), and the resultant material was agitated to impregnate the supports. The samples were then dried in an oven at 100°C for 3 hours, and reduced at 350°C under a forming gas (5% H₂ and 95%
10 N₂) atmosphere for 3 hours with 5°C/min temperature ramp rate to produce catalyst with a composition of 3.0 wt.% Pt. By using other carbon-based extrudate supports, Pt precursors, and adjusting the amount of Pt in solution, different catalysts with various Pt loadings on a variety of carbon-based extrudate supports were prepared in a similar manner.

Above catalysts were tested for 5-(Hydroxymethyl)furfural (HMF) oxidation with a
15 very similar testing protocol by using 15 mg 3.0 wt.% Pt on extrudates of average 3 mm length and 0.75 mm diameter in an HMF solution (250 µl of 6.0 wt.% or 0.50 M in a variety of solvent mixtures of water with DME, 1,4-dioxane, diglyme, triglyme, tetraglyme and higylyme). The glass vial insert was loaded into a reactor and the reactor was closed. The atmosphere in the reactor was replaced with oxygen and pressurized to 200 psig at ambient
20 temperature. The reactor was heated to 120°C and maintained at the respective temperature for 2 hours while the vial was shaken. After that, shaking was stopped and reactor was cooled to 40°C. Pressure in the reactor was then slowly released. The glass vial insert was removed from the reactor and centrifuged. The solution was diluted with dimethyl sulfoxide (DMSO) followed by 1,4-dioxane : water (2:1 v/v) and analyzed by HPLC with a UV
25 detector to determine the yield of 2,5-furandicarboxylic acid (FDCA). The results are presented in Table 6.

Table 6. Extrudate Catalyst (average 3 mm length and 0.75 mm diameter) Performance in Various Solvent Mixtures.

Carbon Support	BET Surface Area (m ² /g)	Solvent	FDCA Yield (mol%)
Timcal Ensaco 250G	123	50wt.% Dioxane/50wt.% H ₂ O	65
Orion Arosperse 5-183A	91	50wt.% Dioxane/50wt.% H ₂ O	59
Continental N120	98	50wt.% Dioxane/50wt.% H ₂ O	52
Continental N234	137	50wt.% Dioxane/50wt.% H ₂ O	39
Continental N330	115	50wt.% Dioxane/50wt.% H ₂ O	59
Continental N550	88	50wt.% Dioxane/50wt.% H ₂ O	56
Timcal Ensaco 250G	123	50wt.% Diglyme/50wt.% H ₂ O	62
Orion Arosperse 5-183A	91	50wt.% Diglyme/50wt.% H ₂ O	24
Continental N234	137	50wt.% Diglyme/50wt.% H ₂ O	24
Continental N330	115	50wt.% Diglyme/50wt.% H ₂ O	43
Timcal Ensaco 250G	123	50wt.% Triglyme/50wt.% H ₂ O	38
Timcal Ensaco 250G	123	50wt.% Tetraglyme/50wt.% H ₂ O	18
Timcal Ensaco 250G	123	50wt.% H ₂ O/50wt.% H ₂ O	16

EXAMPLE 19

5 Testing of Carbon-Supported Powder Catalysts in a Variety of Solvent Mixtures

5, 10, 15, or 20 mg 3.0 wt.% Pt on Continental N234 carbon black powder (prepared from platinum nitrate) was tested for 5-(Hydroxymethyl)furfural (HMF) oxidation using a very similar testing protocol to Example 5 in an HMF solution (250 μ l of 6.0 wt.% or 0.50 M in a variety of solvent mixtures of water and 1,4-dioxane with different ratios). The glass vial insert was loaded into a reactor and the reactor was closed. The atmosphere in the reactor was replaced with oxygen and pressurized to 200 psig at ambient temperature. The reactor was heated to 110°C and maintained at the respective temperature for 3 hours while the vial was shaken. After that, shaking was stopped and the reactor was cooled to 40°C. Pressure in the reactor was then slowly released. The glass vial insert was removed from the reactor and centrifuged. The solution was diluted with dimethyl sulfoxide (DMSO) followed by 1,4-dioxane : water (2:1 v/v) and analyzed by HPLC with a UV detector to determine the yield of 2,5-furandicarboxylic acid (FDCA). Results are presented in Table 7.

Table 7. Powder Catalyst Performance in Various Dioxane/H₂O Solvent Mixtures.

Catalyst (mg)	Solvent	FDCA Yield (%)
5	100wt.% Dioxane	0
10	100wt.% Dioxane	3
15	100wt.% Dioxane	7
20	100wt.% Dioxane	11
5	90wt.% Dioxane/10wt.% H ₂ O	14
10	90wt.% Dioxane/10wt.% H ₂ O	38
15	90wt.% Dioxane/10wt.% H ₂ O	54
20	90wt.% Dioxane/10wt.% H ₂ O	64
5	80wt.% Dioxane/20wt.% H ₂ O	24
10	80wt.% Dioxane/20wt.% H ₂ O	56
15	80wt.% Dioxane/20wt.% H ₂ O	72
20	80wt.% Dioxane/20wt.% H ₂ O	81
5	70wt.% Dioxane/30wt.% H ₂ O	34
10	70wt.% Dioxane/30wt.% H ₂ O	65
15	70wt.% Dioxane/30wt.% H ₂ O	79
20	70wt.% Dioxane/30wt.% H ₂ O	84
5	60wt.% Dioxane/40wt.% H ₂ O	37
10	60wt.% Dioxane/40wt.% H ₂ O	74
15	60wt.% Dioxane/40wt.% H ₂ O	84
20	60wt.% Dioxane/40wt.% H ₂ O	88
5	50wt.% Dioxane/50wt.% H ₂ O	43
10	50wt.% Dioxane/50wt.% H ₂ O	76
15	50wt.% Dioxane/50wt.% H ₂ O	87
20	50wt.% Dioxane/50wt.% H ₂ O	89
5	40wt.% Dioxane/60wt.% H ₂ O	46
10	40wt.% Dioxane/60wt.% H ₂ O	79
15	40wt.% Dioxane/60wt.% H ₂ O	89
20	40wt.% Dioxane/60wt.% H ₂ O	91
5	20wt.% Dioxane/80wt.% H ₂ O	55
10	20wt.% Dioxane/80wt.% H ₂ O	84
15	20wt.% Dioxane/80wt.% H ₂ O	87
20	20wt.% Dioxane/80wt.% H ₂ O	86
5	100wt.% H ₂ O	68
10	100wt.% H ₂ O	82
15	100wt.% H ₂ O	82
20	100wt.% H ₂ O	79

EXAMPLE 20Testing of Carbon-Supported Extrudate Catalysts

10 or 20 mg 2.0 wt.% Pt on Continental N234 carbon black extrudates (average
 5 length 3 mm and diameter 1.5 mm or 0.75 mm prepared from PtO(NO₃)) was tested for 5-
 (Hydroxymethyl)furfural (HMF) oxidation using a very similar testing protocol in an HMF
 solution (250 µl of 6.0 wt.% or 0.50 M in a 50wt.%Dioxane/50wt.% H₂O). The glass vial
 insert was loaded into a reactor and the reactor was closed. The atmosphere in the reactor
 was replaced with oxygen and pressurized to 100, 200, or 400 psig at ambient temperature.
 10 The reactor was heated to 120°C and maintained at the respective temperature for 2 hours
 while the vial was shaken. After that, shaking was stopped and reactor was cooled to 40°C.
 Pressure in the reactor was then slowly released. The glass vial insert was removed from the
 reactor and centrifuged. The solution was diluted with dimethyl sulfoxide (DMSO) followed
 by 1,4-dioxane : water (2:1 v/v) and analyzed by HPLC with a UV detector to determine the
 15 yield of 2,5-furandicarboxylic acid (FDCA). The results are presented in Table 8.

Table 8. Extrudate Catalyst Performance in 50wt.% Dioxane/50wt.% H₂O Solvent Mixtures.

Extrudate Diameter (mm)	O ₂ Pressure (psig)	Catalyst (mg)	FDCA Yield (mol%)
0.75	100	10	35
0.75	100	20	67
1.5	100	10	25
1.5	100	20	48
0.75	200	20	76
1.5	200	20	77
0.75	400	10	55
0.75	400	20	76
1.5	400	10	49
1.5	400	20	77

EXAMPLE 21Testing of Carbon-Supported Extrudate Catalysts

20 20 mg 2.0 wt.% or 3.0wt.% Pt on carbon black extrudates (average length 3 mm and
 diameter 1.5 mm or 0.75 mm prepared from PtO(NO₃)) was tested for 5-(Hydroxymethyl)-

furfural (HMF) oxidation using very similar testing protocol in an HMF solution (250 μ l of 6.0 wt.% or 0.50 M in a 50wt.% Dioxane/50wt.% H₂O). The glass vial insert was loaded into a reactor and the reactor was closed. The atmosphere in the reactor was replaced with oxygen and pressurized to 200 psig at ambient temperature. The reactor was heated to 120°C and maintained at the respective temperature for 2 hours while the vial was shaken. After that, shaking was stopped and the reactor was cooled to 40°C. The pressure in the reactor was then slowly released. The glass vial insert was removed from the reactor and centrifuged. The solution was diluted with dimethyl sulfoxide (DMSO) followed by 1,4-dioxane : water (2:1 v/v) and analyzed by HPLC with a UV detector to determine the yield of 2,5-furandicarboxylic acid (FDCA). The results are presented in Table 9.

Table 9. Extrudate Catalyst Performance in 50wt.% Dioxane/50wt.% H₂O Solvent Mixtures.

Support	Carbon Black Surface Area (m ² /g)	Extrudate Surface Area (m ² /g)	Extrudate Diameter (mm)	Extrudate Mercury Porosimetry Pore Area (m ² /g)	Pt Loading (wt.%)	FDCA Yield (mol%)
Orion Lamp Black 101	20	87	0.75	10	2.0	30
Asbury 5365R	34	92	0.75	18	2.0	12
Continental N550	38	88	0.75	21	2.0	67
Continental N120	39	98	0.75	19	2.0	68
Orion Arosperse 5-183A	42	91	0.75	20	2.0	69
Continental N330	77	115	0.75	38	2.0	76
Continental N234	117	137	0.75	54	2.0	75
Cabot Monarch 700	181	177	0.75	53	2.0	75
Norit ROX 0.8 (Activated Carbon)	1323	1323	0.75	24	2.0	42
Orion Lamp Black 101	20	87	0.75	10	3.0	37
Asbury 5365R	34	92	0.75	18	3.0	45
Continental N550	38	88	0.75	21	3.0	61
Continental N120	39	98	0.75	19	3.0	59
Orion Arosperse 5-183A	42	91	0.75	20	3.0	66
Continental N330	77	115	0.75	38	3.0	76
Continental N234	117	137	0.75	54	3.0	79
Cabot Monarch 700	181	177	0.75	53	3.0	77
Norit ROX 0.8	1323	1323	0.75	24	3.0	41

Support	Carbon Black Surface Area (m ² /g)	Extrudate Surface Area (m ² /g)	Extrudate Diameter (mm)	Extrudate Mercury Porosimetry Pore Area (m ² /g)	Pt Loading (wt.%)	FDCA Yield (mol%)
(Activated Carbon)						

EXAMPLE 22

Testing of Carbon-Supported Powder and Extrudate Catalysts in *N*-Methyl-2-

Pyrrolidone/H₂O Solvent Compositions

10 or 20 mg 3.0 wt.% Pt on Continental N234 carbon black powder (prepared from platinum nitrate) or extrudates (average length 3 mm and diameter 1.5 mm or 0.75 mm prepared from PtO(NO₃)) was tested for 5-(Hydroxymethyl)furfural (HMF) oxidation using very similar testing protocol in an HMF solution (250 μ l of 6.0 wt.% or 0.50 M in a solvent mixture of *N*-Methyl-2-Pyrrolidone (NMP) and H₂O). The glass vial insert was loaded into a reactor and the reactor was closed. The atmosphere in the reactor was replaced with oxygen and pressurized to 200 psig at ambient temperature. The reactor was heated to 110°C and maintained at the respective temperature for 3 hours while the vial was shaken. After that, shaking was stopped and the reactor was cooled to 40°C. The pressure in the reactor was then slowly released. The glass vial insert was removed from the reactor and centrifuged. The solution was diluted with dimethyl sulfoxide (DMSO) followed by 1,4-dioxane : water (2:1 v/v) and analyzed by HPLC with a UV detector to determine the yield of 2,5-furandicarboxylic acid (FDCA). The results are presented in Table 10.

Table 10. Powder and Extrudate Catalyst Performance in NMP/H₂O Solvent Mixtures.

Solvent Composition	Catalyst Size	Catalyst Amount (mg)	FDCA Yield (mol%)
100wt.% NMP	Powder	10	1
98wt.% NMP/2wt.% H ₂ O	Powder	10	1
95wt.% NMP/5wt.% H ₂ O	Powder	10	1
90wt.% NMP/10wt.% H ₂ O	Powder	10	4
85wt.% NMP/15wt.% H ₂ O	Powder	10	7
80wt.% NMP/20wt.% H ₂ O	Powder	10	15
70wt.% NMP/30wt.% H ₂ O	Powder	10	23
60wt.% NMP/40wt.% H ₂ O	Powder	10	32

Solvent Composition	Catalyst Size	Catalyst Amount (mg)	FDCA Yield (mol%)
50wt.% NMP/50wt.% H ₂ O	Powder	10	42
40wt.% NMP/60wt.% H ₂ O	Powder	10	44
20wt.% NMP/80wt.% H ₂ O	Powder	10	44
100wt.% H ₂ O	Powder	10	80
100wt.% NMP	Powder	20	1
98wt.% NMP/2wt.% H ₂ O	Powder	20	2
95wt.% NMP/5wt.% H ₂ O	Powder	20	4
90wt.% NMP/10wt.% H ₂ O	Powder	20	13
85wt.% NMP/15wt.% H ₂ O	Powder	20	22
80wt.% NMP/20wt.% H ₂ O	Powder	20	32
70wt.% NMP/30wt.% H ₂ O	Powder	20	51
60wt.% NMP/40wt.% H ₂ O	Powder	20	57
50wt.% NMP/50wt.% H ₂ O	Powder	20	66
40wt.% NMP/60wt.% H ₂ O	Powder	20	66
20wt.% NMP/80wt.% H ₂ O	Powder	20	71
100wt.% H ₂ O	Powder	20	78
100wt.% NMP	0.75 mm x 3 mm	20	10
98wt.% NMP/2wt.% H ₂ O	0.75 mm x 3 mm	20	11
95wt.% NMP/5wt.% H ₂ O	0.75 mm x 3 mm	20	11
90wt.% NMP/10wt.% H ₂ O	0.75 mm x 3 mm	20	12
85wt.% NMP/15wt.% H ₂ O	0.75 mm x 3 mm	20	14
80wt.% NMP/20wt.% H ₂ O	0.75 mm x 3 mm	20	16
70wt.% NMP/30wt.% H ₂ O	0.75 mm x 3 mm	20	22
60wt.% NMP/40wt.% H ₂ O	0.75 mm x 3 mm	20	32
50wt.% NMP/50wt.% H ₂ O	0.75 mm x 3 mm	20	36
40wt.% NMP/60wt.% H ₂ O	0.75 mm x 3 mm	20	46
20wt.% NMP/80wt.% H ₂ O	0.75 mm x 3 mm	20	51
100wt.% H ₂ O	0.75 mm x 3 mm	20	79

EXAMPLE 23

FDCA Solubility Studies in Various Solvent Compositions

A series of samples containing various amounts of FDCA and mixed solvent compositions were prepared in sealed pressure ampules (typically containing 2 - 5 g material (FDCA and solvent composition)). For example, 200 mg FDCA, 900 mg NMP, and 900 mg de-ionized water were added to an 8 mL glass vial with a stir bar inside, corresponding to a

5 mixture containing 10 wt% FDCA. Other samples corresponding to different wt% FDCA samples in various mixed solvent compositions were prepared in a similar manner. These vials were sealed and heated at a desired temperature for ca. 60 minutes with stirring, and samples were then visually inspected to determine if FDCA had totally dissolved (a clear solution represented dissolution of the FDCA, while a cloudy solution suggested incomplete dissolution). The reported FDCA solubility in Table 11 represents the maximum wt% FDCA that can be dissolved in the given solvent composition using this testing method.

Table 11. FDCA Solubilities in Various Solvent Compositions.

Organic solvent	Solvent (wt.%)	H ₂ O (wt.%)	Temperature (°C)	FDCA solubility (wt.%)
NMP	50	50	23	2.5
NMP	50	50	100	14.5
NMP	50	50	120	19.5
NMP	35	65	23	0.5
NMP	35	65	100	9.0
NMP	35	65	120	13.5
NMP	20	80	23	0.3
NMP	20	80	100	4.0
NMP	20	80	120	7.5
Bu ^t OH	50	50	100	7.0
Bu ^t OH	75	25	100	7.5
MEK	25	75	100	5.5
MEK	90	10	100	4.0
gamma-valerolactone	25	75	100	4.0
gamma-valerolactone	50	50	100	7.0
gamma-valerolactone	75	25	100	6.5

10

EXAMPLE 24FDCA Solubility in Various Dioxane/H₂O and DME/H₂O Solvent Compositions at Different Temperatures

A protocol similar to that described in Example 23 was used to generate solubility data for FDCA in various Dioxane/H₂O and DME/H₂O solvent compositions. The results for

Dioxane/H₂O solvent compositions are shown in Figure 12. The results for DME/H₂O solvent compositions are shown in Figure 13.

EXAMPLE 25

Conversion of fructose to HMF using HBr in NMP

Analytical Conditions

Fructose remaining was quantified by HPLC using a Rezex RCU-USP column (Ca⁺² form, 4 x 250 mm, 8 μm) and a refractive index detector (RID). Fructose was eluted isocratically with a mobile phase of H₂O.

Isomeric forms of difructose anhydrides, collectively referred to as intermediates, were quantified by HPLC using a Thermo Scientific Hypercarb column (3 x 50 mm, 3 μm) and a Charged Aerosol Detector (CAD). Intermediates were eluted by employing a mobile phase gradient of up to 15% CH₃CN in H₂O containing 0.1 % TFA.

5-Hydroxymethylfurfural (HMF) was quantified by HPLC with UV detection at 254 nm using a Thermo Scientific Hypercarb column (3 x 50 mm, 3 μm). HMF was eluted by employing a mobile phase gradient of up to 15% CH₃CN in H₂O containing 0.1 % TFA.

Fructose and HMF were quantified by fitting to calibration curves generated from pure standards. Intermediates were quantified by fitting to a calibration curve generated from di-D-fructofuranose-1,2':2,3'-dianhydride (DFA-III). DFA-III was purchased from Wako Chemicals.

Screening Conditions

General Procedure A. For reactions carried out using microwave heating.

Reaction stock solutions were prepared by first dissolving fructose in N-methyl-2-pyrrolidone (NMP) and H₂O. Acid catalyst was added last using either concentrated aqueous HBr (48 wt%) or concentrated H₂SO₄ (97 wt%). The final composition of each stock solution contained 0.6M fructose, 0.1M acid, and 2.0M H₂O.

Reactions were carried out using a Biotage Initiator Microwave reactor. The wattage output of the reactor was varied by the instrument in order to maintain a target temperature. Microwave vials, equipped with a magnetic stir bar, were charged with 3g of stock solution and sealed.

General Procedure B. For reactions carried out using conventional heating.

Reaction stock solutions were prepared by first dissolving fructose in N-methyl-2-pyrrolidone (NMP) and H₂O. Acid catalyst was added last using either concentrated aqueous HBr (48 wt%) or concentrated HCl (37 wt%). Each stock solution prepared contained 0.6M fructose. Acid and H₂O concentration was varied for these experiments. The concentrations tested are listed below in Tables 13 and 14.

Reactions were carried out in 8 mL glass vials using conventional heating with magnetic stirring. Reaction vials, equipped with a magnetic stir bar, were charged with 3g of stock solution and sealed. Vials were placed in a pre-heated aluminum block set to the desired temperature.

Example 25.1: Comparison of HBr and H₂SO₄ as catalyst using General Procedure A.

Conditions tested along with results are listed in Table 12 and depicted graphically in Figure 14. These results show that a higher yield of HMF can be achieved using HBr as catalyst compared to H₂SO₄. The yield of HMF was not sensitive to a change in reaction temperature within the range of 120 – 160°C.

Table 12. Conditions tested and results using General Procedure A.

Entry	Catalyst	Temperature (°C)	Heating Time (min) ¹	% Conversion ²	% HMF	Selectivity ³
1	HBr	120	5	93.3	81.9	87.8
2	HBr	120	10	95.9	83.8	87.4
3	HBr	120	20	98.6	83.6	84.8
4	HBr	140	1	94.9	82.9	87.3
5	HBr	140	2	98.3	83.9	85.3
6	HBr	140	4	99.3	84.3	84.9
7	HBr	160	0.5	99.3	84.1	84.6
8	HBr	160	1	99.6	84.8	85.1
9	HBr	160	2	100	83.9	83.9
10	H ₂ SO ₄	120	10	71.2	63.6	89.4
11	H ₂ SO ₄	120	30	85.2	74.7	87.7
12	H ₂ SO ₄	120	50	89.2	76.1	85.4
13	H ₂ SO ₄	140	2	79.9	70	87.6
14	H ₂ SO ₄	140	5	87.6	76	86.7
15	H ₂ SO ₄	140	10	92.8	78.3	84.4
16	H ₂ SO ₄	160	1	88.4	77.1	87.2
17	H ₂ SO ₄	160	2	94.5	79.7	84.4
18	H ₂ SO ₄	160	4	97.8	81.8	83.6

¹ Does not include ramp time to target temperature.

² % Conversion = 100 - (% Fructose + % Intermediates).

³ Selectivity = (% HMF / %Conversion)*100.

Example 25.2: Comparison of HBr and HCl as catalyst at 120°C using General Procedure B.

Conditions tested along with results are listed in Table 13 and depicted graphically in Figure 15. These results show that higher HMF yield can be achieved using HBr as catalyst compared to HCl.

Table 13. Results of conditions tested at 120°C using General Procedure B.

Entry	Catalyst	[Catalyst] (M)	[H ₂ O] (M)	Heating Time (min)	% Conversion ¹	% HMF	Selectivity ²
1	HBr	0.06	0.29	30	94.6	83.4	88.2
2	HBr	0.06	0.29	30	93.3	83.1	89.1
3	HBr	0.06	0.29	60	97.8	85.0	87.0
4	HBr	0.06	0.29	60	97.5	85.8	88.0
5	HBr	0.06	0.29	90	98.2	85.3	86.9
6	HBr	0.06	0.29	90	98.6	85.1	86.2
7	HBr	0.06	2	30	93.9	82.2	87.6
8	HBr	0.06	2	60	96.7	85.5	88.4
9	HBr	0.06	2	90	97.2	85.2	87.7
10	HCl	0.045	0.29	30	90.1	73.1	81.1
11	HCl	0.045	0.29	60	93.9	73.8	78.6
12	HCl	0.045	0.29	90	95.2	74.3	78.0
13	HCl	0.045	2	30	92.3	74.8	81.1
14	HCl	0.045	2	60	95.3	76.2	79.9
15	HCl	0.045	2	90	95.9	76.7	79.9

¹ % Conversion = 100 - (% Fructose + % Intermediates).

² Selectivity = (% HMF / %Conversion)*100.

Example 25.3: Comparison of 100°C and 120°C reaction temperature using General Procedure B.

Conditions tested along with results are listed in Table 14 and depicted graphically in Figure 16. These results show an increase in HMF yield when the reaction temperature is reduced from 120°C to 100°C.

Table 14. Results of conditions tested using General Procedure B.

Entry	[HBr] (M)	[H ₂ O] (M)	Temperature (°C)	Heating Time (min)	% Conversion ¹	% HMF	Selectivity ²
1	0.12	0.58	100	18	86.8	80.8	93.2
2	0.12	0.58	100	27	88.1	82.6	93.7

Entry	[HBr] (M)	[H ₂ O] (M)	Temperature (°C)	Heating Time (min)	% Conversion ¹	% HMF	Selectivity ²
3	0.12	0.58	100	36	90.2	84.1	93.2
4	0.12	0.58	100	57	93.0	85.6	92.0
5	0.14	0.68	100	60	94.8	86.9	91.7
6	0.14	0.68	100	75	95.7	87.6	91.5
7	0.14	0.68	100	90	96.5	87.6	90.8
8	0.14	2	100	25	87.4	81.9	93.8
9	0.14	2	100	35	91.7	84.3	92.0
10	0.14	2	100	45	91.7	85.3	93.0
11	0.14	2	100	65	93.9	86.0	91.6
12	0.16	4	100	37	88.9	82.2	92.5
13	0.16	4	100	53	91.8	84.5	92.1
14	0.2	4	100	60	93.9	86.0	91.5
15	0.16	4	100	70	93.4	85.6	91.7
16	0.2	4	100	75	95.0	86.5	91.0
17	0.16	4	100	90	94.4	87.1	92.3
18	0.2	4	100	90	95.5	87.6	91.8
19	0.06	0.29	120	30	94.6	83.4	88.2
20	0.06	0.29	120	30	93.3	83.1	89.1
21	0.06	0.29	120	60	97.8	85.0	87.0
22	0.06	0.29	120	60	97.5	85.8	88.0
23	0.06	0.29	120	90	98.2	85.3	86.9
24	0.06	0.29	120	90	98.6	85.1	86.2
25	0.06	2	120	30	93.9	82.2	87.6
26	0.06	2	120	60	96.7	85.5	88.4
27	0.06	2	120	90	97.2	85.2	87.7

¹ % Conversion = 100 - (% Fructose + % Intermediates).

² Selectivity = (% HMF / %Conversion)*100.

While preferred embodiments of the disclosure have been illustrated and described, it
5 will be appreciated that various changes can be made therein without departing from the
spirit and scope of the disclosure.

Claims

1. A process for producing a 2,5-furandicarboxylic acid (FDCA) pathway product from a furanic oxidation substrate, the process comprising:

(a) contacting an oxidation feedstock comprising a furanic oxidation substrate and an oxidation solvent with oxygen in the presence of a heterogeneous oxidation catalyst under conditions sufficient to form a reaction mixture for oxidizing the furanic oxidation substrate to an FDCA pathway product, and producing the FDCA pathway product,

wherein the oxidation solvent is a multi-component solvent comprising water and a water-miscible aprotic organic solvent,

wherein no base is added to the reaction mixture during contacting step (a),

wherein the heterogeneous oxidation catalyst comprises a solid support and a noble metal, and

wherein the solid support comprises a plurality of pores and a specific surface area in the range of from or any number in between 20 m²/g to 500 m²/g.

2. The process of claim 1, wherein the noble metal is selected from the group consisting of platinum, gold, and a combination thereof.

3. The process of claim 1, wherein the water-miscible aprotic organic solvent is selected from the group consisting of tetrahydrofuran, a glyme, dioxane, a dioxolane, dimethylformamide, dimethylsulfoxide, sulfolane, acetone, N-methyl-2-pyrrolidone ("NMP"), methyl ethyl ketone ("MEK"), and gamma-valerolactone;

and, if the water-miscible aprotic organic solvent is a glyme, then the glyme is selected from the group consisting of a monoglyme (1,2-dimethoxyethane), ethyl glyme, diglyme (diethylene glycol dimethyl ether), ethyl diglyme, triglyme, butyl diglyme, tetraglyme, and a polyglyme.

4. The process of claim 1, wherein the oxidation feedstock comprises the furanic oxidation substrate at a concentration of at least 5% by weight.

5. The process of claim 1, wherein the heterogeneous oxidation catalyst comprises the metal at a loading in the range of from or any number in between 0.3% to 5% by weight of the heterogeneous oxidation catalyst.

6. The process of claim 1, wherein the solid support comprises a material selected from the group consisting of a metal oxide, a carbonaceous material, a polymer, a metal silicate, a metal carbide, and any combination of two or more thereof.

7. The process of claim 1, wherein the solid support comprises a specific surface area in the range of from or any number in between 25 m²/g to 350 m²/g.

8. The process of claim 1, wherein the solid support comprises a pore volume wherein at least 50% of the pore volume is from pores having a pore diameter in the range of from or any number in between 5 nm to 100 nm.

9. The process of claim 1, wherein the oxygen is present at a molar ratio of oxygen:furanic oxidation substrate in the range of from or any number in between 2:1 to 10:1.

10. The process of claim 1, wherein the contacting step is carried out at a temperature in the range of from or any number in between 50°C to 200°C.

11. The process of claim 1, wherein the FDCA pathway product is produced at a yield of at least 80%.

12. The process of claim 1, further comprising a second oxidation step, wherein the second oxidation step comprises:

(b) contacting a second oxidation feedstock comprising a second furanic oxidation substrate and a second oxidation solvent with oxygen in the presence of a second heterogeneous oxidation catalyst under conditions sufficient to form a second reaction mixture for oxidizing the second furanic oxidation substrate to produce a second FDCA pathway product, and producing the second FDCA pathway product,

wherein (the first) contacting step (a) produces a first FDCA pathway product that is an FDCA pathway intermediate compound, either alone or together with FDCA,

wherein the second furanic oxidation substrate is the first FDCA pathway product,

wherein the second reaction mixture is substantially free of added base, and

wherein the second heterogeneous oxidation catalyst comprises a second solid support and a second noble metal, that may be the same or different from the (first) noble metal in step (a), and

wherein the second solid support comprises a plurality of pores and a specific surface area in the range of from or any number in between 20 m²/g to 500 m²/g.

13. The process of claim 12, wherein the noble metal is selected from the group consisting of platinum, gold, and a combination thereof.

14. The process of claim 1, wherein the FDCA pathway product is FDCA.

15. The process of claim 1, further comprising:

5 (a^o) prior to step (a), contacting a carbohydrate feedstock comprising a sugar and a dehydration solvent with a catalyst under conditions sufficient to form a reaction mixture for dehydrating the sugar to produce the furanic oxidation substrate, wherein the furanic oxidation substrate is present in a dehydration product solution that comprises the furanic oxidation substrate and the dehydration solvent.

10 16. A process for producing a furanic oxidation substrate, the process comprising:
contacting a carbohydrate feedstock comprising a sugar and a dehydration solvent with an acid catalyst under conditions sufficient to form a dehydration reaction mixture for dehydrating the sugar to produce a furanic oxidation substrate, wherein the acid catalyst is an acid selected from the group consisting of HBr, H₂SO₄, HNO₃, HCl, HI, H₃PO₄, triflic acid,
15 methansulfonic acid, benzenesulfonic acid, and p-toluene sulfonic acid,

wherein when the acid catalyst is not HBr, the dehydration reaction mixture further comprises a bromide salt, and

wherein the dehydration solvent comprises N-methyl-pyrrolidone (NMP).

20 17. The process of claim 16, wherein the sugar is fructose and the furanic oxidation substrate is HMF.

18. The process of claim 16, further comprising contacting the carbohydrate feedstock comprising the sugar and the dehydration solvent with the acid catalyst and ZnCl₂ or ZnBr₂ under conditions sufficient to form a dehydration reaction mixture for dehydrating the sugar to produce a furanic oxidation substrate.

25 19. The process of claim 1, wherein the solid support comprises a specific surface area in the range of from or any number in between 20 m²/g to 50 m²/g.

20. The process of claim 19, wherein the solid support comprises a specific surface area in the range of from or any number in between 20 m²/g to 40 m²/g.

30 21. The process of claim 4, wherein the water-miscible aprotic organic solvent is a glyme.

22. The process of claim 21, wherein the water-miscible aprotic organic solvent is 1,2-dimethoxyethane ("DME").

23. The process of claim 21, wherein the water-miscible aprotic organic solvent is diglyme.

5 24. The process of claim 3, wherein the water-miscible aprotic organic solvent is dioxane.

25. The process of claim 3, wherein the water-miscible aprotic organic solvent is NMP.

10 26. The process of claim 3, wherein the water-miscible aprotic organic solvent is MEK.

27. The process of claim 1, wherein the weight percent ratio of water-miscible aprotic organic solvent:water is in the range of from or any number in between 70:30 to 20:80.

28. The process of claim 27, wherein the weight percent ratio of water-miscible aprotic organic solvent:water is in the range of from or any number in between 60:40 to 40:60.

15 29. The process of claim 16, wherein the contacting step is carried out at a temperature of less than 110°C.