WHAT IS CLAIMED IS:

1. A carrier for holding a plurality of containers, the carrier comprising:

a plurality of panels comprising a top panel, at least one central panel, and at least one attachment panel configured to receive a portion of one or more containers of the plurality of containers, the at least one central panel is for being positioned between and attached to adjacent containers of the plurality of containers, the at least one central panel comprises a first row of openings and a second row of openings spaced apart from the first row of openings; and

at least one access feature that is positionable for allowing access to at least one container of the plurality of containers, the at least one access feature comprises a marginal portion of the top panel and a marginal portion of the at least one attachment panel.

2. The carrier of claim 1, wherein the at least one central panel is for being adhered to adjacent containers of the plurality of containers.

3. The carrier of claim 1, wherein the at least one access feature is reconfigurable between a first configuration in which the marginal portion of the top panel is generally perpendicular to the at least one central panel, and a second configuration in which the marginal portion of the top panel and the marginal portion of the at least one attachment panel are raised to allow access to at least one container of the plurality of containers.

4. The carrier of claim 3, wherein the access feature further comprises a side panel foldably connected to the marginal portion of the top panel and the marginal portion of the at least one attachment panel.

5. The carrier of claim 4, wherein the marginal portion of the top panel overlaps the marginal portion of the at least one attachment panel.

6. The carrier of claim 4, wherein the marginal portion of the top panel is a first marginal portion of the top panel and the carrier further comprises a second marginal portion of the top panel, the at least one attachment panel is a front attachment panel and the carrier further comprises a back attachment panel, the at least one side panel is a front side panel and the carrier further comprises a back side panel foldably connected to the back attachment panel, the top panel

comprises a central portion, the at least one access feature is a first access feature foldably connected to the central portion of the top panel at a first fold line, and the carrier further comprises a second access feature comprising the second marginal portion of the top panel and a marginal portion of the back attachment panel, the second access feature is foldably connected to the central portion of the top panel at a second fold line.

7. The carrier of claim 6, wherein the at least one central panel is a front central panel foldably connected to the front attachment panel, and the carrier further comprises a back central panel in at least partial face-to-face contact with the front central panel and foldably connected to the back attachment panel.

~~8. The carrier of claim 1, wherein the at least one central panel comprises a plurality of openings.~~

~~9. The carrier of claim 8, wherein the plurality of openings comprises a first row of openings and a second row of openings spaced apart from the first row of openings.~~

~~10~~8. The carrier of claim ~~9~~ 1, wherein the first row of openings is spaced a first distance from a bottom edge of the at least one central panel, and the second row of openings is spaced a second distance from the bottom edge of the at least one central panel, the second distance is greater than the first distance.

~~11~~9. The carrier of claim ~~10~~8, wherein the at least one central panel is a front central panel, the plurality of panels further comprises a back central panel in face-to-face contact with the front central panel, the at least one attachment panel is a front attachment panel foldably connected to the front central panel, and the plurality of panels further comprises a back attachment panel foldably connected to the back central panel, the plurality of openings is a first plurality of openings in the front central panel, and the back central panel comprises a second plurality of openings such that the first plurality of openings are in communication with the back central panel and the second plurality of openings are in communication with the front central panel.

~~12~~10. The carrier of claim 1, wherein at least one of the at least one central panel and the at least one attachment panel includes at least one handle opening.

~~13~~11. The carrier of claim ~~12~~10, wherein the top panel comprises at least one handle feature, the at least one handle feature is aligned with the at least one handle opening.

~~14~~12. A blank for forming a carrier for holding a plurality of containers, the blank comprising:

a plurality of panels comprising a top panel, at least one central panel, and at least one attachment panel, and

at least one access feature comprising a marginal portion of the top panel and a marginal portion of the at least one attachment panel, the at least one access feature is for being positionable for allowing access to at least one container of the plurality of containers when the carrier is formed from the blank,

the at least one central panel is for being positioned between and attached to adjacent containers of the plurality of containers when the carrier formed from the blank, the at least one central panel comprises a first row of openings and a second row of openings spaced apart from the first row of openings.

~~15~~13. The blank of claim ~~14~~12, wherein the at least one central panel is for being adhered to adjacent containers of the plurality of containers.

~~16~~14. The blank of claim ~~14~~12, wherein, when the carrier is formed from the blank, the at least one access feature is reconfigurable between a first configuration in which the marginal portion of the top panel is generally perpendicular to the at least one central panel, and a second configuration in which the marginal portion of the top panel and the marginal portion of the at least one attachment panel are raised to allow access to at least one container of the plurality of containers.

~~17~~15. The blank of claim ~~16~~14, wherein the access feature further comprises a side panel foldably connected to the marginal portion of the top panel and the marginal portion of the at least one attachment panel.

~~18~~16. The blank of claim ~~17~~15, wherein the marginal portion of the top panel is a first marginal portion of the top panel and the carrier further comprises a second marginal portion of the top panel, the at least one attachment panel is a front attachment panel and the carrier further comprises a back attachment panel, the at least one side panel is a front side panel and the carrier further comprises a back side panel foldably connected to the back attachment panel, the top panel comprises a central portion, the at least one access feature is a first access feature foldably connected to the central portion of the top panel at a first fold line, and the carrier further comprises a second access feature comprising the second marginal portion of the top panel and a marginal portion of the back attachment panel, the second access feature is foldably connected to the central portion of the top panel at a second fold line.

~~19~~17. The blank of claim ~~18~~16, wherein the at least one central panel is a front central panel foldably connected to the front attachment panel, and the carrier further comprises a back central panel foldably connected to the back attachment panel.

~~20. The blank of claim 14, wherein the at least one central panel comprises a plurality of openings.~~

~~21. The blank of claim 20, wherein the plurality of openings comprises a first row of openings and a second row of openings spaced apart from the first row of openings.~~

~~22~~18. The blank of claim ~~21~~ 14, wherein the first row of openings is spaced a first distance from a bottom edge of the at least one central panel, and the second row of openings is spaced a second distance from the bottom edge of the at least one central panel, the second distance is greater than the first distance.

~~23~~19. The blank of claim ~~22~~18, wherein the at least one central panel is a front central panel, the plurality of panels further comprises a back central panel, the at least one attachment panel is a front attachment panel foldably connected to the front central panel, and the plurality of panels further comprises a back attachment panel foldably connected to the back central panel, the plurality of openings is a first plurality of openings in the front central panel, and the back central panel comprises a second plurality of openings such that, when the carrier is formed from the

blank, the first plurality of openings are in communication with the back central panel and the second plurality of openings are in communication with the front central panel.

~~24~~20. The blank of claim ~~14~~12, wherein at least one of the at least one central panel and the at least one attachment panel includes at least one handle opening.

~~25~~21. The blank of claim ~~24~~20, wherein the top panel comprises at least one handle feature for being aligned with the at least one handle opening when the carrier is formed from the blank.

~~26~~22. A method of forming a carrier for holding a plurality of containers, the method comprising:

obtaining a blank comprising a plurality of panels comprising a top panel, at least one central panel, and at least one attachment panel, and at least one access feature comprising a marginal portion of the top panel and a marginal portion of the at least one attachment panel, the at least one central panel comprises a first row of openings and a second row of openings spaced apart from the first row of openings;

folding the plurality of panels such that the at least one central panel is positioned between adjacent containers of the plurality of containers; and

attaching at least one container of the plurality of ~~panels~~ containers to the at least one central panel, the at least one access feature is positionable for allowing access to at least one container of the plurality of containers.

~~27~~23. The method of claim ~~26~~22, wherein the at least one central panel is for being adhered to adjacent containers of the plurality of containers.

~~28~~24. The method of claim ~~26~~22, wherein the at least one access feature is reconfigurable between a first configuration in which the marginal portion of the top panel is generally perpendicular to the at least one central panel, and a second configuration in which the marginal portion of the top panel and the marginal portion of the at least one attachment panel are raised to allow access to at least one container of the plurality of containers.

~~29~~25. The method of claim ~~28~~24, wherein the access feature further comprises a side panel foldably connected to the marginal portion of the top panel and the marginal portion of the at least one attachment panel.

~~30~~26. The method of claim ~~29~~25, wherein the marginal portion of the top panel overlaps the marginal portion of the at least one attachment panel.

~~31~~27. The method of claim ~~29~~25, wherein the marginal portion of the top panel is a first marginal portion of the top panel and the carrier further comprises a second marginal portion of the top panel, the at least one attachment panel is a front attachment panel and the carrier further comprises a back attachment panel, the at least one side panel is a front side panel and the carrier further comprises a back side panel foldably connected to the back attachment panel, the top panel comprises a central portion, the at least one access feature is a first access feature foldably connected to the central portion of the top panel at a first fold line, and the carrier further comprises a second access feature comprising the second marginal portion of the top panel and a marginal portion of the back attachment panel, the second access feature is foldably connected to the central portion of the top panel at a second fold line.

~~32~~28. The method of claim ~~31~~27, wherein the at least one central panel is a front central panel foldably connected to the front attachment panel, and the carrier further comprises a back central panel in at least partial face-to-face contact with the front central panel and foldably connected to the back attachment panel.

~~33. The method of claim 26, wherein the at least one central panel comprises a plurality of openings.~~

~~34. The method of claim 33, wherein the plurality of openings comprises a first row of openings and a second row of openings spaced apart from the first row of openings.~~

~~35~~29. The method of claim ~~34~~ 26, wherein the first row of openings is spaced a first distance from a bottom edge of the at least one central panel, and the second row of openings is spaced a second distance from the bottom edge of the at least one central panel, the second distance is greater than the first distance.

~~36~~30. The method of claim ~~35~~29, wherein the at least one central panel is a front central panel, the plurality of panels further comprises a back central panel in face-to-face contact with the front central panel, the at least one attachment panel is a front attachment panel foldably connected to the front central panel, and the plurality of panels further comprises a back attachment panel foldably connected to the back central panel, the plurality of openings is a first plurality of openings in the front central panel, and the back central panel comprises a second plurality of openings such that the first plurality of openings are in communication with the back central panel and the second plurality of openings are in communication with the front central panel.

~~37~~31. The method of claim ~~26~~22, wherein at least one of the at least one central panel and the at least one attachment panel includes at least one handle opening.

~~38~~32. The method of claim ~~37~~31, wherein the top panel comprises at least one handle feature, the at least one handle feature is aligned with the at least one handle opening.

~~39~~33. A package comprising:

a plurality of containers; and

a carrier holding the plurality of containers, the carrier comprising:

a plurality of panels comprising a top panel, at least one central panel, and at least one attachment panel receiving a portion of one or more containers of the plurality of containers, the at least one central panel is positioned between and attached to adjacent containers of the plurality of containers, the at least one central panel comprises a first row of openings and a second row of openings spaced apart from the first row of openings; and

at least one access feature that is positionable for allowing access to at least one container of the plurality of containers, the at least one access feature comprises a marginal portion of the top panel and a marginal portion of the at least one attachment panel.

~~40~~34. The package of claim ~~39~~33, wherein the at least one central panel is adhered to adjacent containers of the plurality of containers.

~~41~~35. The package of claim ~~39~~33, wherein the at least one access feature is reconfigurable between a first configuration in which the marginal portion of the top panel is generally perpendicular to the at least one central panel, and a second configuration in which the marginal portion of the top panel and the marginal portion of the at least one attachment panel are raised to allow access to at least one container of the plurality of containers.

~~42~~36. The package of claim ~~41~~35, wherein the access feature further comprises a side panel foldably connected to the marginal portion of the top panel and the marginal portion of the at least one attachment panel.

~~43~~37. The package of claim ~~42~~36, wherein the marginal portion of the top panel overlaps the marginal portion of the at least one attachment panel.

~~44~~38. The package of claim ~~42~~36, wherein the marginal portion of the top panel is a first marginal portion of the top panel and the carrier further comprises a second marginal portion of the top panel, the at least one attachment panel is a front attachment panel and the carrier further comprises a back attachment panel, the at least one side panel is a front side panel and the carrier further comprises a back side panel foldably connected to the back attachment panel, the top panel comprises a central portion, the at least one access feature is a first access feature foldably connected to the central portion of the top panel at a first fold line, and the carrier further comprises a second access feature comprising the second marginal portion of the top panel and a marginal portion of the back attachment panel, the second access feature is foldably connected to the central portion of the top panel at a second fold line.

~~45~~39. The package of claim ~~44~~38, wherein the at least one central panel is a front central panel foldably connected to the front attachment panel, and the carrier further comprises a back central panel in at least partial face-to-face contact with the front central panel and foldably connected to the back attachment panel.

~~46. The package of claim 39, wherein the at least one central panel comprises a plurality of openings.~~

~~47. The package of claim 46, wherein the plurality of openings comprises a first row of openings and a second row of openings spaced apart from the first row of openings.~~

~~48~~40. The package of claim ~~47~~39, wherein the first row of openings is spaced a first distance from a bottom edge of the at least one central panel, and the second row of openings is spaced a second distance from the bottom edge of the at least one central panel, the second distance is greater than the first distance.

~~49~~41. The package of claim ~~48~~40, wherein the at least one central panel is a front central panel, the plurality of panels further comprises a back central panel in face-to-face contact with the front central panel, the at least one attachment panel is a front attachment panel foldably connected to the front central panel, and the plurality of panels further comprises a back attachment panel foldably connected to the back central panel, the plurality of openings is a first plurality of openings in the front central panel, and the back central panel comprises a second plurality of openings such that the first plurality of openings are in communication with the back central panel and the second plurality of openings are in communication with the front central panel.

~~50~~42. The package of claim ~~39~~33, wherein at least one of the at least one central panel and the at least one attachment panel includes at least one handle opening.

~~51~~43. The package of claim ~~51~~42, wherein the top panel comprises at least one handle feature, the at least one handle feature is aligned with the at least one handle opening.