(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization
International Bureau

(43) International Publication Date
10 December 2009 (10.12.2009)

PCT

(10) International Publication Number
WO 2009/149082 A3

(51) International Patent Classification:
G05F 1/56 (2006.01) *H04B 1/16* (2006.01)

(21) International Application Number:
PCT/US2009/045971

(22) International Filing Date:
2 June 2009 (02.06.2009)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
12/131,800 2 June 2008 (02.06.2008) US

(71) Applicant *(for all designated States except US)*: **QUALCOMM INCORPORATED** [US/US]; Attn: International IP Administration, 5775 Morehouse Drive, San Diego, CA 92121 (US).

(72) Inventors; and

(75) Inventors/Applicants *(for US only)*: **GUDEM, Prasad, S.** [IN/US]; 5775 Morehouse Drive, San Diego, CA 92121 (US). **CICCARELLI, Steven, C.** [US/US]; 5775 Morehouse Drive, San Diego, CA 92121 (US). **MOK, Ken Tsz Kin** [CN/US]; 5775 Morehouse Drive, San Diego, CA 92121 (US). **KWOK, Sai, C.** [US/US]; 5775 Morehouse Drive, San Diego, CA 92121 (US).

(74) Agent: **HOOKS, William, M.**; Attn: International IP Administration, 5775 Morehouse Drive, San Diego, CA 92121 (US).

(81) Designated States *(unless otherwise indicated, for every kind of national protection available)*: AE, AG, AL, AM, AO, AT, AU, AZ, BA, BB, BG, BH, BR, BW, BY, BZ, CA, CH, CL, CN, CO, CR, CU, CZ, DE, DK, DM, DO, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT, HN, HR, HU, ID, IL, IN, IS, JP, KE, KG, KM, KN, KP, KR, KZ, LA, LC, LK, LR, LS, LT, LU, LY, MA, MD, ME, MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RS, RU, SC, SD, SE, SG, SK, SL, SM, ST, SV, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, ZA, ZM, ZW.

(84) Designated States *(unless otherwise indicated, for every kind of regional protection available)*: ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT, LU, LV, MC, MK, MT, NL, NO, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Declarations under Rule 4.17:

— *as to applicant's entitlement to apply for and be granted a patent (Rule 4.17(ii))*

— *as to the applicant's entitlement to claim the priority of the earlier application (Rule 4.17(iii))*

Published:

— *with international search report (Art. 21(3))*

[Continued on next page]

(54) **Title**: METHODS AND APPARATUS FOR POWER REDUCTION IN A TRANSCEIVER




FIG. 1

(57) **Abstract**: An integrated circuit for achieving power reduction in a transceiver may include a jammer detector that determines an interference level corresponding to a received signal, and a transmit power detector that determines a required transmit power level for a transmitted signal. The integrated circuit may also include at least one of the following: a process monitor that determines process corners of components within the receiver and/or the transmitter, and a temperature monitor that determines a temperature of the receiver and/or the transmitter. The integrated circuit may also include a state machine. The state machine may transition the receiver from a high linearity mode to a low linearity mode if a set of operating conditions is satisfied. Similarly, the state machine may transition the transmitter from a high power mode to a low power mode if a set of operating conditions is satisfied.

WO 2009/149082 A3

— *before the expiration of the time limit for amending the claims and to be republished in the event of receipt of amendments (Rule 48.2(h))*

(88) Date of publication of the international search report:
28 January 2010