

1 ATTACHMENT FITTING FOR WALL OF FLEXIBLE STRUCTURE

2

3

4 BACKGROUND OF THE INVENTION

5

6 Field of the Invention

7

8 The invention relates to the field of flexible structures and, in
9 particular, to a design for an attachment fitting for such structures. The
10 attachment fitting is particularly useful on pressurized structures such a
11 lighter-than-air vehicles and inflatable boats.

12

13 Description of Related Art

14

15 On flexible structures, attachment fittings and the like are normally
16 just sewn directly thereon much like a button on a shirt. Sometime the
17 reinforcements are sewn or bonded on both sides to add support.
18 However, such fittings stitched or bonded in such a manner tend to "rip"
19 away from the structure when under high tension loads, again much like a
20 button ripping off from a shirt. For example in U.S. Patent No. 4,125,233,
21 "Tethered Aerodynamic Balloon With Integral Fins" by J. A. Winker, et.al.
22 an attachment fitting is disclosed in the form of a loop with end portions
23 bonded to the outer surface of a balloon. The end portions are "criss-
24 crossed" with reinforcing strips bonded thereover. U.S. Patent No.
25 3,108,765, "Balloon Having an External Ballonet" by V. H. Stone
26 discloses a somewhat similar design. In addition, the V. H. Stone
27 attachment fitting incorporates a load distributing fitting in the end of loop
28 with the sides of the loop reinforced and joined together. Because the
29 fitting is subject to cyclic tension loads there is always the tendency to
30 Peel away the reinforcements. Thus it is important to distribute such
31 tension loads into the main structure. Additionally, if the flexible structure

1 is pressurized, stitching the attachment fitting thereon will create an
2 unacceptable leakage path.

3
4 Also of interest is U.S. Patent No. 4,267,989, "Toy Hot Air Balloon"
5 by K. D. Skaggs. K. D. Skaggs disclosed an attachment fitting that
6 includes a hole in the wall of the structure perpendicular to the specific
7 direction of the tension load. A first flexible member is included having a
8 center portion folded in half forming a loop extending through the slot.
9 Attached to the loop are end portions bonded to the inside surface of the
10 wall of the structure. Second flexible members are bonded over these
11 end portions of the first flexible member. This design better distributes
12 the tension load from the loop to the flexible structure, via shear load
13 through the bond between the end portions of the first flexible members.
14 However, the hole in the structure is not sealed; thus it is unusable in a
15 pressurized structure. As used in the toy balloon, it is attached to an un-
16 pressurized cap at the top thereof. However, others have modified the K.
17 D. Skaggs design by extending the second flexible member to completely
18 cover the first flexible member so that the attachment fitting can be used
19 on pressurized structures. However, these designs do not provide for
20 optimizing the distribution of loads into the structure eliminating or
21 reducing local stress concentrations. Furthermore, if the flexible structure
22 is an inflatable boat or the gas bag of a lighter-than-air vehicle, failure of
23 the joint should not cause a leak therein.

24
25 Thus it is a primary object of the subject invention to provide an
26 attachment fitting for a flexible structure.

27
28 It is another primary object of the subject invention to provide an
29 attachment fitting for a flexible structure wherein stress loads are
30 distributed into the structure, eliminating local stress concentrations.

31

1 It is a further object of the subject invention to provide an
2 attachment fitting for a pressurized flexible walled structure.

3

4 **SUMMARY OF THE INVENTION**

5

6 The invention is an attachment fitting for use on a flexible wall of a
7 structure for distributing a tension load therein. In detail, the fitting
8 includes a slot in the wall of the structure. In order to reduce the
9 possibility of stress induced loads from ripping the structure at the ends of
10 the slot, stress concentration reducing cutouts are included on either end
11 thereof; preferably, these stress concentration reducing cutouts are
12 circular shaped. A first flexible member is included having a center
13 portion folded over on its self forming a loop extending from a first side of
14 the wall through the slot and out from the second side. The first flexible
15 member further includes fan shaped outer portions on each end of the
16 center portion bonded to the inner surface of the wall of the structure
17 adjacent to the slot.

18

19 The first flexible member further includes a plurality unidirectional
20 reinforcing filaments in a matrix material with the filaments being parallel
21 to each other in the center portion and fanning or spreading uniformly in
22 each of the outer portions. The filamentary material could be any high
23 strength filamentary material such as KEVLARTM, or DACRONTM, with are
24 available from the I. E. du Pont de Nemours and Company, Wilmington,
25 Delaware. VECTRANTM filamentary material manufactured by Hoechst-
26 Celanses, Somerville, New Jersey, as well as graphite and fiberglass can
27 also be used. A wide variety of resins can be used as the matrix material,
28 for example, urethane thermoplastic. In a lighter-than-air gas bag made
29 up of various layers of VECTRANTM and KEVLARTM using a urethane
30 resin matrix material, the first flexible member could made from
31 KEVLARTM filamentary material with a similar urethane resin matrix

1 material. With such a combination, the first flexible member could be
2 easily bonded by heat and pressure to the structure. Again, a wide
3 variety of filamentary and resin matrix materials are commercially
4 available.

5
6 The fan shaped outer portions insure that the tension load is
7 uniformly distributed into the structure over a wide area; thus, their size
8 will be a function of the load. However, the outer portions need not
9 necessarily be the same size. For example, if the tension load were
10 primarily directed at an acute angle to one of the outer portions, then the
11 tension load would be primarily distributed into the opposite outer portion
12 and it would be proportionally larger the first mentioned outer portion. In
13 a pressurized structure it is important that the attachment fitting fail
14 without causing a leak in the structure. Thus the fitting should be
15 designed to have the loop or center portion fail prior to failure of the bond
16 between the fan shaped outer portions, that is, before, the bond between
17 the outer portions and flexible structure. The use of the fan shaped outer
18 portions which better distributes the tension load into the flexible structure
19 helps to insure that this requirement met. The fans shaped outer
20 portions also better absorb "off axis" loads.

21
22 A second flexible member having a periphery extending about the
23 slot and the outer portions of the first flexible member is bonded thereover
24 and to the adjacent surface of the flexible wall of the structure. This
25 second flexible member serves a dual purpose. The first is to provide
26 additional strength to the attachment fitting by reinforcing the attachment
27 of the first flexible member to the wall of the structure. Secondly, if the
28 structure is pressurized, such as the gas bag of a lighter-than-air vehicle
29 or an inflatable boat or raft, it acts as a seal preventing gas from leaking
30 through the slot. Material used in the second flexible member must be
31 compatible with and bondable to the structure and first flexible member.

1 In some applications, it may be desirable to have a portion of the
2 sides of the loop extending from a point in proximity to the second side of
3 the wall toward the free end joined together. This can be accomplished
4 by cross stitching the sides together. Reinforcing members (either ridged
5 or flexible) can be positioned over the joined portions of the sides of the
6 loop to add strength. Additionally, a load distributing member can be
7 installed into the end of the loop to better distribute the tension load
8 thereto. For example, a metal shaft having end fittings for securing the
9 ends of a clevis attached to a cable such as a mooring line. Alternately, a
10 hollow shaft can be installed for supporting a load carry pin.

11

12 The novel features which are believed to be characteristic of the
13 invention, both as to its organization and method of operation, together
14 with further objects and advantages thereof, will be better understood
15 from the following description in connection with the accompanying
16 drawings in which the presently preferred embodiment of the invention is
17 illustrated by way of example. It is to be expressly understood, however,
18 that the drawings are for purposes of illustration and description only and
19 are not intended as a definition of the limits of the invention.

20

21 **BRIEF DESCRIPTION OF THE DRAWINGS**

22

23 Figure 1 is perspective view of a lighter-than-air vehicle.

24

25 Figure 2 is partial perspective view of the vehicle gas bag
26 illustrating the attachment fitting.

27

28 Figure 3 is a cross-sectional view of the attachment fitting shown in
29 Figure 2 taken along the line 3-3.

30

1 Figure 4 is front view of the first flexible member prior to forming the
2 center portion into a loop illustrating the distribution of filamentary material
3 therein.

4

5 Figure 5 is a partial is view of the attachment fitting shown in Figure
6 3, illustrating the addition of reinforcements to the sides of the loop and
7 the installation of a metal attachment tube within the loop.

8

9 Figure 6 is a partial is view of the attachment fitting shown in Figure
10 2, illustrating a center loop portion as formed without reinforcements or
11 the installation of an attachment fitting therein.

12

13 **DESCRIPTION OF THE PREFERRED EMBODIMENT**

14

15 Illustrated in Figure 1 is a non-ridged lighter-than-air vehicle,
16 generally indicated by numeral 10. The vehicle 10 includes a flexible gas
17 bag 12 having a gondola 14 suspended from the bottom thereof and
18 thrust producing assemblies 16 attached to the gondola. The vehicle
19 further includes a plurality of fins 17 mounted on the rear thereof
20 supported by bracing wires 18. The vehicle 10 is shown docked on a
21 platform 18, secured thereto at its nose to a tower 20 and by a plurality of
22 mooring lines 22 along its length directly to the platform. These mooring
23 lines 22, as well as the bracing wires 18 are attached directly to the gas
24 bag by the subject attachment fittings, indicated by numeral 24. It is
25 important to note that the example application is for purposes of
26 illustration only and the attachment fitting can be used on any flexible wall
27 structure; however, it is most useful on pressurized flexible structures,
28 such as the gas bag illustrated above.

29

30 Referring now to figures 2 and 3, it can be seen that the wall 30 of
31 the gas bag 12 has an inner side 32 and outer side 34 with a slot 36

1 extending therethrough. The slot 36 has circular cut outs 38A and 38B at
2 either end thereof that act as rip "stoppers". By having such a cutout at
3 the end of the slot 36 there is far less tendency to tear under load. Of
4 course other cutout shapes can be used as long as they have the effect
5 of distributing stress loads over a wide area. A first flexible member 40,
6 that acts as the primary attach point, includes a center portion 42 in the
7 form of a loop having sides 42A and 42B. The loop extends through the
8 slot 36 from the inner side 32 and beyond the outer side 34. The first
9 flexible member 40 also includes fan shaped outer portions 44A and 44B
10 on either end thereof that are bonded to the inner side 32 of the wall 30
11 adjacent to the slot 36.

12

13 Figure 4 is a view of the first flexible member 40 prior to the forming
14 of the center portion 42 into a loop. The member 40 is made of strands of
15 unidirectional filamentary material 48 embedded in a flexible resin matrix
16 material 49. The filamentary material 48 is closely packed in the center
17 portion 42 (indicated by numeral 48A) and uniformly spread out into the
18 fan shaped outer portions 44A and 44B (indicated by numeral 48B). The
19 filamentary material can be selected from any of the high strength
20 structural fibers, such as KEVLAR™, DACRON™, VECTRAN™ graphite,
21 fiberglass, etc. The member 40 can also be made in any number of
22 ways. For example, the filamentary material could be laid up in a mold
23 having the shape of the member with a plurality of pins equally spaced
24 about the peripheral ends of the fan shaped end portions. The
25 filamentary material could be laid up in the mold with the ends tied off in
26 tension about the pins. The unidirectional filamentary material could
27 incorporated harness weaving to maintain filament spacing. Thereafter a
28 resin could be injected into the mold. A suitable resin is thermoplastic
29 urethane. This would allow bonding to the inner side 32 of the wall 30 by
30 the application of pressure and heat; however, any resin selected must
31 be bondable to the wall.

1 Referring back to Figures 2 and 3, a second flexible member 50 is
2 bonded over the first flexible member 40 and extends about the periphery
3 52 thereof and the slot 36 and is bonded to the inner side 32 of the wall
4 30. Thus the second flexible member provides a gas tight seal about the
5 slot 36 and the first flexible member 40 as well as providing additional
6 strength to the fitting. The loop formed by center portion 42 contains a
7 load distribution member 54 mounted therein. A clevis 56 is attached to
8 the end of the mooring line 22 (also see Figure 1). Additionally the sides
9 42A and 42B of the loop are joined together by stitching 58 to prevent
10 independent movement of the sides and to secure the member 54 in its
11 proper position at the end thereof.

12
13 Note that in this particular version of the attachment fitting 24 the
14 tension load, indicated by numeral 57, is always in a predominately
15 downward position. Thus the major portion of the tension load 57
16 induced into the first flexible member will be absorbed by the outer portion
17 44B. Therefore, it is proportionally larger than side portion 44A; the
18 actual size, of course, being dependent on the actual tension load. The
19 fan shape, with the filamentary material evenly distributed therein,
20 provides for the distribution of the load into the wall 30 of the gas bag 12
21 and can even distribute "off axis" loads. Note also that tension loads are
22 primarily distributed from the first flexible 40 member to the wall 30 in
23 shear along the bond line therebetween. There is very little tendency to
24 "rip" along the slot 36. Of course, if the tension load is predominately
25 perpendicular to the structure, the outer portions 44A and 44B would be
26 equal in size. In such pressurized structures, it is always important to
27 design the attachment fitting such that the loop fails in tension, rather
28 than in a shear failure along the bond between the outer portions and the
29 structure, thus insuring that a leak path is not generated upon failure.

1 Figure 5 illustrates the addition of reinforcing members 60 to the
2 stitched together loop to add additional support. Also, note that a
3 reinforcing member 62 installed in the end of the loop is tapered on one
4 end. This shape aids in distributing the tension load. Additionally, in
5 Figure 6 there is shown a center portion with an un-joined loop and no
6 reinforcing member therein to illustrate that the sides of the loop need not
7 be joined together, nor is a reinforcing member required in many
8 applications.

9
10 While the invention has been described with reference to a
11 particular embodiment, it should be understood that the embodiment is
12 merely illustrative as there are numerous variations and modifications
13 which may be made by those skilled in the art. Thus, the invention is to
14 be construed as being limited only by the spirit and scope of the
15 appended claims.

16 17 **INDUSTRIAL APPLICABILITY**

18
19 The invention has applicability to the aircraft industry and also to
20 any industry that manufactures flexible structures.

CLAIMS

- 1 1. An attachment fitting for use on the flexible wall of a structure for
2 supporting a tension load, said fitting comprising:
3 a slot in the wall of the structure;
4 a first flexible member having a center portion folded in half forming
5 a loop extending from a first side of the wall through said slot and out
6 from the second side, and outer fan shaped portions on each end of said
7 center portion bonded to the first side of the wall of the structure adjacent
8 to said slot, said first flexible member comprising a plurality unidirectional
9 reinforcing filaments in a matrix material with the filaments being parallel
10 to each other in the center portion and fanning out from each other in
11 each of said outer portions; and
12 a second flexible member having a periphery extending about said
13 slot and said outer portions of said first flexible member, said second
14 flexible member bonded to said outer portions of said first flexible
15 member and to the first side of the flexible wall of the structure extending
16 about the periphery of said outer portions of said first flexible member.
- 1 2. The attachment fitting as set forth in Claim 1 further comprising
2 stress concentration reducing cutouts on either end of said slot and said
3 second flexible member extends beyond and about said cutouts.
- 1 3. The attachment fitting as set forth in Claim 2 wherein said stress
2 concentration reducing cutouts are circular shaped.



1 4. The attachment fitting as set forth in Claim 1, or 2, or 3 wherein a
2 portion of the loop extending from a point in proximity to the second side
3 of the wall toward the free end of the loop are joined together.

1 5. The attachment fitting as set forth in Claim 4 wherein reinforcing
2 members are joined to said joined portions of the sides of said loop.

1 6. The attachment fitting as set forth in Claim 5 wherein said
2 reinforcing members are flexible.

1 7. The attachment fitting as set forth in Claim 6 wherein a load
2 distributing member is mounted in the un-joined portion of said loop.



FIG. 1

1/3





FIG. 4

FIG. 2

