

Title: Heat Exchanger for use in Cooling Liquids

Field of the Invention

5

[0001] The present invention relates to heat exchangers for cooling liquids.

Background of the Invention

10

[0002] Ice making machines and chillers are well known. These types of machines are used in a number of industries including the food processing, plastics, fishing, and general cooling applications. Chillers cool liquids generally to a point above their freezing temperature, while ice making machines generally cool water or a solution below its freezing point. Ice machines and chillers use a heat exchanger that is generally cooled by refrigerant that flows through internal passages. Water, or any other liquid to be cooled, is introduced onto the surface of the heat exchanger. If the liquid is frozen, a variety of methods are then used to remove the ice from the heat exchange surface, including using a scraping device, or heating the surface temporarily to release the ice. Slurry ice differs from flake ice in that the water that is frozen usually has mixed with it salt, or some other substance, for altering the freezing point. The resulting slurry product has a slush consistency and may be pumped, making it preferred for many applications where the end product must be conveyed. Furthermore, its energy storage and transfer characteristics are superior to other types of ice.

[0003] US Pat. Nos. 5,157,939 and 5,363,659 by Lyon, as well as US 5,632,159 and US 5,918,477 by Gall disclose heat exchangers in the shape of a disk with internal passageways for the refrigerant to travel along the interior of the disk. The disk rotates in contact with a fixed scraping mechanism which removes ice formed on its surface. In Lyon the disk is formed with two mating disk halves, each of which includes a plurality of grooves on its internal surface. The pattern of the grooves in the two halves

are mirror images, so that when the halves are mated and brazed together, corresponding grooves mate to form passages. The manufacturing of this heat exchanger involves chemically etching each separate half of the disk, which is expensive.

5 **[0004]** The two devices by Gall disclose a heat exchanging device that is formed by cutting fluid passages into a thick metal plate using a milling machine. Once the passages are cut, a thin flat plate is joined to the milled plate to complete the disk. Although milling the plate is not as expensive as chemically etching it, and in this process only one plate is being machined as
10 opposed to both, this is still a lengthy and expensive process. In the prior art flat disk heat exchangers, the refrigerant does not come into contact with a significant portion of the heat exchange surface. The reason for this is that there needs to be sufficient material between the channels to provide a large enough surface area for brazing in order to withstand pressure.

15 **[0005]** The refrigerant in heat exchangers disclosed in prior art is introduced into the heat exchanger through a single inlet and removed through a single outlet. The refrigerant is driven by the compressor through the internal passages. There is an optimal range of velocity for the refrigerant: If velocity is too small, the heat transfer efficiency decreases, and there will
20 not be sufficient velocity to carry oil, which is picked up from the compressor, back to the reservoir of the compressor. If velocity is too large, the compressor will waste energy.

[0006] Having a single inlet and single outlet forces all of the mass of the refrigerant to pass through a small cross sectional area. For a fixed mass
25 flow of refrigerant, a smaller cross sectional flow area corresponds to a larger velocity. Thus, by having a single inlet and outlet, the channel length and the velocity are increased, and therefore the work of the compressor which moves the refrigerant in the ice machine system is significantly increased. In the heat exchanger of the prior art, the only way to reduce the refrigerant velocity is to
30 increase the cross-sectional area, which increases the cost of manufacturing.

[0007] It would therefore be advantageous to have an ice making machine with a heat exchanger that has a lower pressure drop across it, as well as a velocity of the refrigerant that can be reduced to an optimal range.

[0008] It would be further advantageous to have a heat exchanger for use in a chiller or ice machine that can be made in an inexpensive manner.

[0009] It would be further advantageous to have a heat exchanger in which the refrigerant passageways allow for the refrigerant to come into a greater degree of thermal contact with the majority of the disk surface, to improve heat transfer.

[0010] It would be further advantageous to have a flat plate heat exchanger in which the outer walls were thin so as to provide high heat transfer, but were still able to withstand high pressures of the refrigerant.

[0011] Another need is to provide an ice making machine with flat plate heat exchangers that allow simultaneous scraping of several heat exchange surfaces with a single driving motor and little additional power for each additional surface.

[0012] There is yet a further need to provide a scraping mechanism for an ice making machine that is simple, robust and easy to service, and requires little clearance to service.

20

Summary of the Invention

[0013] In another aspect, the invention is directed to an apparatus for heat exchange, comprising at least one fluid inlet, at least one fluid outlet, a first outer plate and a second outer plate, and an inner layer. The inner layer is sealedly sandwiched between the first and second outer plates. The inner layer at least in part defines at least one series of fluid channels. Each fluid channel is defined in part by the inner surface of one of the outer plates and by the inner layer. The at least one series of fluid channels makes up at least one flow path between the at least one fluid inlet and the at least one fluid outlet.

[0014] In another aspect, the invention is directed to an apparatus for heat exchange, comprising at least one fluid inlet, at least one fluid outlet, a first outer plate and a second outer plate, and an inner layer. The inner layer is sealedly sandwiched between the first and second outer plates. The inner layer at least in part defines at least one flow path between the at least one fluid inlet and the at least one fluid outlet. The inner layer may optionally include a plurality of sections that each define one or more segments of the flow path. The sections mate together in a puzzle-like configuration to make up a flow portion of the inner layer.

[0015] In one aspect, an embodiment of the invention comprises a chiller or ice machine with an apparatus for heat exchange. The heat exchange apparatus includes flat top and bottom plates of generally the same shape, at least one fluid inlet and at least one fluid outlet, each located at a point near or on the edge of the plates, as well as a plurality of sections in a puzzle-type arrangement between the top and bottom plates. Each of the sections comprises a thin piece of material with parallel flow channels. The puzzle-type arrangement of the sections allows for the fluid to flow continuously from the inlet, through the different sections, and out the outlet. An additional feature of this embodiment is that the sections are configured so that the majority of the inner surfaces of the top and bottom plate come in to contact with the fluid flowing through the sections. In one embodiment of the invention, the sections of parallel flow channels are corrugated material, and the puzzle-type arrangement is symmetrical within the plates. Additionally, each inlet and outlet is dimensioned so that the fluid flows through a significant number of flow channels. In an advantageous embodiment, there are two inlets and two outlets, each of which is evenly spaced along the edge of the top or bottom plate. In the aforementioned embodiment, the top and bottom plates each include an inner ring and outer ring portion, where the inner and outer ring extend beyond the sections of flow channels. The flow path of the fluid through the sections preferably includes the fluid flowing in through the inlet and in towards the inner ring, then flowing around the inner ring towards the outlet, before being directed back and forth, first towards the

inlet, then towards the outlet, along paths successively closer to the outer ring and finally, through the outlet.

[0016] Another feature of the present invention is an apparatus for scraping material from between two plates, which comprises a shaft passing perpendicularly through the centre of the plates, a hollow carrier positioned
5 between the plates with a length sufficient to reach the edge of the plates, a plurality of scrapers positioned along the length of the carrier, an inner carrier with means to secure it to the shaft and positioned so the inner carrier is in sliding engagement within the hollow carrier, means for rotating the shaft, and
10 removable means to connect the inner carrier to the hollow carrier. In one embodiment the securing means is a plate welded to the inner carrier and bolted to the shaft. As well, the removable connecting means may be a bolt that can be removed so the hollow carrier may slide out. The shape of the scraping apparatus is preferably such that the apparatus is reversible so that
15 when the edge that is in contact with the heat exchange surface wears out, the opposite edge may be used, thereby extending the life of the scraping mechanism.

[0017] In another aspect, the invention is an ice making apparatus that comprises a frame, a plurality of flat plate heat exchangers arranged parallel
20 within the frame, means for continuously supplying a solution over the heat exchangers, and scraping means for removing ice crystals that form on the surface of the heat exchangers. In one embodiment, insulation panels are secured to the frame to create a generally sealed compartment.

[0018] In another aspect, the present invention relates to a method for
25 establishing an overall continuous flow path from an inlet to an outlet through an apparatus for heat exchange, occupying substantially all of the surface area between the inlet and outlet, comprising the steps of: providing a plurality of sections, where each section is made up of a parallel set of flow channels; cutting each section at one or more angles to selected groups of parallel flow
30 channels; abutting edges of each section to one or more other sections, thereby causing the flow path to change direction; and assembling the sections in a puzzle-like configuration. Each section may include all

contiguous and parallel channels at any given point, whereby a section may include parallel flow paths in opposite directions to one another.

[0019] Other aspects and advantages of the device will become apparent from the following Detailed Description and the accompanying drawings.

Brief Description of Drawings

[0020] Fig. 1 is a transparent front view of a heat exchanger in accordance with an embodiment of the present invention.

[0021] Figure 1a is a transparent view of the heat exchanger shown in Figure 1, with individual flow channels removed for clarity to illustrate flow paths taken by refrigerant through the heat exchanger.

[0022] Fig. 2 is a front view, partially in phantom, of an ice making machine in accordance with another embodiment of the present invention, incorporating the heat exchanger shown in Figure 1.

[0023] Fig. 3 is a cross-sectional view taken along line 3-3 in Fig. 2.

[0024] Fig. 4 is a side view of a scraping device for scraping one side of a plate.

[0025] Fig. 5 is an end view of a base plate, connecting the scraping device to the shaft.

[0026] Fig. 6A is a top view of the top web from the scraping device in Fig 4 with a scraper connected to it.

[0027] Fig. 6B is a top view of the top web from Fig. 6A without the scrapers.

[0028] Fig. 6C is a top view of a middle web of a scraper.

[0029] Fig. 6D is a top view of the bottom web of a scraper.

[0030] Fig. 7 is a side view of a pivot shaft, connecting the scraper to the web.

[0031] Fig. 8 is a side view of the scraping device used between two plates.

[0032] Fig. 9A is a top view of the web from the scraping device in Fig 7 with a pair of scrapers connected to it.

5 **[0033]** Fig. 9B is a top view of the web from Fig. 9A without the scrapers.

[0034] Fig. 10 is a side view of the spray tube used with the scraping device in Fig. 8.

10 **[0035]** Fig. 11 is a top view of the sections in an alternative puzzle-type arrangement between the plates.

[0036] Figure 11a is a transparent view of the heat exchanger shown in Figure 11, with individual flow channels removed for clarity to illustrate flow paths taken by refrigerant through the heat exchanger.

15 **[0037]** Fig. 12a is a magnified sectional side view of a portion of the heat exchanger shown in Figure 1.

[0038] Fig. 12b is a magnified sectional side view of an alternative configuration of the portion of the heat exchanger shown in Figure 12a.

[0039] Fig. 13 is a top view of the sections of another alternative puzzle-type arrangement between the plates.

20 **[0040]** Fig. 14 is a top view of the sections in puzzle type arrangement when the device has only one inlet and one outlet.

[0041] Figure 14a is a transparent view of the heat exchanger shown in Figure 14, with individual flow channels removed for clarity to illustrate flow paths taken by refrigerant through the heat exchanger.

25 **[0042]** Fig. 15 is a top view of another puzzle-type arrangement of the sections when there is only one inlet and outlet.

[0043] Fig. 16 is a front view of an alternative embodiment of the ice machine where the heat exchangers are situated horizontally.

30 **[0044]** Fig. 17 is a top view of the collection pan and sweeper arrangement of the horizontal embodiment.

[0045] Fig. 18 is a top view of the scraping device for use with horizontal plates.

[0046] Fig. 19 is a side view of one pair of scrapers for simultaneously scraping two horizontal plates.

5 **[0047]** Fig. 20 is a side view of a single scraping element for scraping a horizontal plate.

[0048] Fig. 21 is a top view of the scraping element that is in contact with the horizontal plate.

[0049] Fig. 22 is a perspective partially transparent view of an ice-making machine in accordance with another embodiment of the present invention,

[0050] Fig. 22a is a side view of the housing shown in Figure 22.

Detailed Description of the Embodiment

15

[0051] Reference is made to Figure 3, which shows an ice-making machine 10 in accordance with a first embodiment of the present invention. The ice making machine 10 comprises a plurality of flat plate heat exchangers 12 within a support frame 14, a scraping system 15 and a liquid supply system 17. Referring to Figure 12a, each heat exchanger is made up of a first outer plate 42, a second outer plate 44 and an inner layer 45 positioned between the first and second outer plates 42 and 44. The inner layer 45 includes a plurality of wall portions 47 each of which has two longitudinal edges 49. Along one or both of the longitudinal edges 49, a foot portion 51 may be integrally joined to the wall portion 47. The one or two foot portions 51 join the wall portions 47 to one or both of the outer plates 42 and 44. When joined to the outer plates 42 and 44, the wall portions 47 separate and define flow channels 53, which are used for the transport of a refrigerant through the heat exchanger 12. The channels 53 are arranged to provide a flow path of the refrigerant between one or more refrigerant inlets 32 and one or more refrigerant outlets 34. In the exemplary embodiment shown in Figure

1, the heat exchanger 12 is shown having two inlets 32 and two outlets 34, however, it is alternatively possible for the heat exchanger 12 to have fewer or more inlets 32 and outlets 34.

[0052] A flow path is understood to comprise the all of channels formed by the sandwich between the outer plates and inner layer that lead from a fluid inlet to a cooperating fluid outlet. By contrast, the term flow path “segment” is use to define a portion of the flow path between an inlet and outlet, it being understood that only a series of adjacent channels that are aligned in parallel arrangement throughout the length the flow path (through all of the inner layer sections participating in the flow path segment) belong to the same segment.

[0053] Reference is made to Figure 1a. By joining the wall portion 47 to the outer plates 42 and 44 using the foot portions 51, several advantages are obtained. One advantage is that the wall portion 47 may be made relatively thin, so that a relatively greater number of wall portions 47 and associated foot portions 51 may be positioned between the outer plates 42 and 44. This in turn provides a relatively greater number of structural members between the first and second outer plates 42 and 44. This, in turn, configures the heat exchanger 12 to resist deformation of the heat exchanger when refrigerant is circulated through the channels 53 under pressure.

[0054] The heat exchanger 12 may be expected to be pressurized to between about 30 psig (207 kPa) and about 300 psig (2070 kPa), and may thus be configured to withstand at least up to about 300 psig (2070 psi). However, in some jurisdictions, the heat exchanger 12 may be required to withstand pressures that are higher than their expected maximum internal pressure during use. For example, the heat exchanger 12 may be configured to withstand as much as approximately 450 psig (3100 kPa) to meet local regulations in some jurisdictions.

[0055] By having relatively thin wall portions 47, the overall surface areas of the plates 42 and 44 that are in contact with the wall portions 47 are relatively low. This permits relatively greater contact surface area between the plates 42 and 44 and the channels 53, which facilitates maintaining the

plates 42 and 44 at selected temperatures. The thickness of the wall portions 47 is shown at T_w . The thickness T_w may be, for example, approximately 0.008" (0.2 mm). The channel width between adjacent channel-defining pairs of wall portions 47, is shown at W_c , and may be approximately 3/16" (4.8 mm). It is understood that the channel width W_c need not be uniform and that term "channel width" refers to the portion of the channel 53 wherein there is a fluid contact interface with the outer plates 42 and 44.

[0056] The ratio of the wall portion thickness T_w to the channel width W_c may be less than approximately 1:8, is more preferably between approximately 1:18 and approximately 1:25, more preferably less than approximately 1:20, and may be between approximately 1:20 and approximately 1:25, such as for example approximately 1:22.5.

[0057] By having a relatively greater number of structural members (ie. the wall portions 47) between the first and second plates 42 and 44, the thicknesses of the first and second plates 42 and 44 may be kept relatively low. The thicknesses of the first and second plates 42 and 44 are shown at T_{p1} and T_{p2} respectively. The thicknesses T_{p1} and T_{p2} may each be approximately 0.120" (3 mm) or less.

[0058] The foot portions 51 that are connected to the wall portions 47 have a thickness T_f , that may be the same as the thickness T_w of the wall portions 47. The foot portions 51 are preferably relatively thin so that they interfere relatively little in the cooling of material deposited on the outer surfaces of the outer plates 42 and 44. The foot portions 51 permit the joining of the wall portions 47 to the first and second outer plates 42 and 44 over a relatively large surface area, thus providing a relatively secure and sealed joint, while simultaneously permitting the wall portions 47 to be relatively thin.

[0059] The wall portions 47 and foot portions 51 may be integrally formed together in a section 40 of corrugated sheet material. A plurality of such sections 40 may be mated together so that the channels 53 direct the refrigerant along a set of selected parallel flow paths between the inlets 32 and the outlets 34. The flow paths may be made to be generally serpentine to increase the amount of heat transfer that takes place per unit volume of

refrigerant that flows through the heat exchanger 12. The term 'serpentine' is used to refer to a flow path segment wherein the direction is gradually (using a plurality of 90 to 180 degree interfaces at the section borders) or immediately (using at least one acute angle section interface) partially reversed at least once in a v-like pattern, and usually multiple times in an undulating pattern. For example, as shown in Figure 13, the v-like pattern of channels at the section interfaces may be repeated multiple times in a single flow path segment.

[0060] Making the inner layer 45 from a plurality of mating sections 40 of corrugated sheet material provides a selected routing for the flow paths, provides a relatively thin walled structure, both in terms of the wall portions 47 and in terms of the outer plates 42 and 44, and also provides a relatively inexpensive way of incorporating these advantageous features into the heat exchanger 12. The sections 40 mate together in a puzzle-like configuration, though their shapes in plan view are not limited in any way to traditional puzzle-piece shapes.

[0061] The term "corrugated" is used broadly to define an undulating pattern of bends which serve to define the height and width of the channels through which fluid flows through the heat exchanger. The shape formed by the bends is important to the extent that it defines the dimensions of the channel including an at least partially coplanar surface relative to the outer plates 42 and 44. This coplanar surface, referred to herein as the foot portions 51 of the channel walls, has a width W_f that relates to an available contact surface sufficient to form a joint with the outer plates 42 and 44, when the corrugated sheet material layer is sealedly joined to the outer plates, for example by brazing. This contact area is maximized when the bends are formed at 90 degrees, however it will be appreciated that bends having a partially curvilinear profile could be used to advantage albeit with a somewhat lesser contact surface. It will be appreciated that the smaller the foot portions 51 are, the greater the surface area of contact that exists directly between the refrigerant and the outer plate 42 or 44 (see Figure 12b). Thus, the configuration of the corrugations can be selected to provide a selected

tradeoff between the amount of sealing surface area and the amount of direct fluid-to-outer plate contact that is desired.

[0062] A selected configuration of sections 40 is provided in Figure 1. Additional configurations of sections 40 which provide different flow paths between one or more inlets 32 and one or more outlets 34 are shown in Figures 11, 13, 14 and 15. More specifically, Figures 1, 11 and 13 show a heat exchanger 12 with a set of flow paths between two inlets 32 and two outlets 34. Figures 14 and 15 show a heat exchanger 12 with a set of flow paths between one inlet 32 and one outlet 34.

[0063] Each section 40 may be cut at a non-zero angle relative to one or more adjacent sections 40, so that when the sections are mated together along their outer edges, the channels 53 formed by the corrugations change direction from one section 40 to the other section 40. The second section 40 is abutted to another section 40 to change the flow direction again, and so on, to establish an overall flow path from the inlet 32 to the outlet 34. Each section 40 may include all contiguous and parallel channels at any given point, or a section 40 may include parallel flow paths in opposite directions to one another.

[0064] The inner layer 45 may include an outer ring 48 to sealedly join the first and second plates 42 and 44 together about their outer peripheries to prevent the leakage of refrigerant out from the outer peripheries of the heat exchanger 12. Apertured mounting tabs 50 may be provided about the outer ring 48 for the mounting of the heat exchanger 12 on the support frame 14. The tabs 50 may receive therethrough tie rods 100 (Figure 3) which mount to the frame 14. Spacers 22 may be provided on the tie rods 50 between adjacent pairs of heat exchangers 12 and between the heat exchangers 12 and the frame 14 to fix the one or more heat exchangers 12 in selected positions. The outer ring 48 may extend around the channel portion of the inner layer 45 (i.e. the sections 40), and also around the inlets 32 and outlets 34.

[0065] The term "sealedly" is used to refer to a property of a three layer sandwich (i.e. the two outer plates 42 and 44 and the inner layer 45) which

precludes escape of the heat exchange medium (eg. refrigerant) from the three-layer sandwich when at high pressures, such as pressures in the range of between about 50 psig (340 kPa) to about 300 psig (2070 kPa). Particularly when the medium is a refrigerant it is important to join the layers in such a sealed manner so as to preclude environmental concerns about refrigerant escape out of the heat exchanger 12.

[0066] The heat exchanger 12 may have a shaft pass-through aperture 55 therethrough, which permits the drive shaft 16 that is part of the scraper system 15 to pass therethrough for connection to scrapers 26 on both sides of the heat exchanger 12. It is contemplated that for some embodiments, eg. when the heat exchanger is used as a chiller, then the heat exchanger 12 need not have the shaft pass-through aperture 55.

[0067] The inner layer 45 includes an inner ring 46 that sealedly joins the first and second plates 42 and 44 together along their inner peripheries about the pass-through aperture 55, to prevent the leakage of refrigerant out from the inner peripheries of the heat exchanger 12.

[0068] Each of the heat exchanger components, including the first and second plates 42 and 44, the inner and outer rings 46 and 48 and the sections 40, may be made from a suitable material, such as a metallic material.

[0069] The joining of the outer ring 48, the inner ring 46 and the foot portions 51 to the outer plates 42 and 44 may be carried out by any suitable means, such as brazing.

[0070] An exemplary flow path through the puzzle-type arrangement of the sections 40 may be described as follows, with reference to Figures 1 and 1a: Refrigerant enters the heat exchanger 12 through the inlet shown at 32a and travels along section 40a towards inner ring 46. After travelling through section 40a, a portion of the refrigerant is directed from the end of the channels 53 in section 40a into section 40b, changing direction and travelling alongside the inner ring 46. From section 40b the refrigerant flows into section 40c, and on through into section 40d, where the fluid changes direction and flows away from the inner ring 46 for a brief period. The refrigerant flows from

section 40d back into section 40c along a different set of channels than were taken through section 40c towards section 40d. From section 40c, the refrigerant flows back into section 40b and then back into section 40a. As can be seen by the flow arrows 52, the refrigerant continues passing through the sections 40 until it reaches the outlet shown at 34a. The flow path shown between the inlet 32a and 34a runs through one quarter of the heat exchanger 12 shown in Figure 1. It will be noted that some portion of the refrigerant that enters the heat exchanger 12 also flows to the outlet shown at 34b in another quarter of the heat exchanger 12. Refrigerant also flows in a similar pattern through the inlet shown at 32b, to each of the outlets 34a and 34b.

[0071] It will be noted that in at least some of the sections 40, such as section 40b, the refrigerant travels along some channels 53 in one direction, and along other channels in the opposite direction.

[0072] Additionally, it will be noted that, in the joints between at least some pairs of adjacent sections, such as the joint between a portion of sections 40d and 40c, the channels 53 meet at acute angles, such that the refrigerant flows back on itself to some extent. By providing at least some of the joints between adjacent sections whereby the channels 53 meet up at acute angles, a serpentine flow path can be provided.

[0073] It will also be noted that, in some other joints between at least some pairs of adjacent sections, such as the joint between sections 40b and 40c, the channels 53 meet at obtuse angles. Such joints can be provided between successive pairs of adjacent sections 40 to permit a relatively gradual change of direction in the flow path of the refrigerant from one direction to another. For example, the flow path provided by the heat exchanger 12 in Figures 14 and 14a includes only obtuse angle joints between adjacent pairs of sections 40. In the heat exchanger 12 shown in Figures 14 and 14a, the overall flow path has a shape that follows the generally annular shape of the heat exchanger 12 and does not double back on itself. By providing at least some joints where channels 53 meet at obtuse angles in adjacent sections 40, the pressure drop incurred in the overall change in flow direction is reduced.

[0074] By providing two inlets 32 and two outlets 34, the total distance traversed by each one quarter of the refrigerant is limited to a single quadrant of the heat exchanger. This reduces the overall pressure drop experienced by the total refrigerant flow across the heat exchanger since pressure drop varies proportionally with the path length travelled by the refrigerant.

[0075] There are tradeoffs well known in the art when increasing the path length of the refrigerant. On one hand, longer path lengths increase the time the refrigerant has to remove heat from the material it contacts, making its heat transfer more efficient. Shorter paths reduce the pressure required to move the refrigerant and hence make the compressor or whatever is driving the refrigerant flow work less hard. Many puzzle-type arrangements of the sections 40 may be used in the heat exchanger 12. The arrangements shown in Figure 1 and Figure 13 have been found to optimize the tradeoff between shorter and longer path lengths for various size units, while providing full coverage of the surface area of the plate.

[0076] The inner layer 45 comprises a outer boundary portion, which is made up of the outer ring 48, a flow portion, which may be made up of the sections 40 of corrugated sheet metal, and optionally an inner boundary portion, which is made up of the optionally provided inner ring 46. The flow portion may cover an area that is between approximately 50% to approximately 95% of the area of inner layer 45, depending on certain factors, such as whether or not the heat exchanger 12 has a shaft pass-through aperture 55 and the overall size of the heat exchanger 12. In some embodiments, the flow portion may cover between approximately 75% to approximately 90% of the area of the inner layer 45, and preferably at least approximately 85% of the area of the inner layer 45, and more preferably at least 88% of the area of inner layer 45.

[0077] The scraper system 15 will now be described. Passing through the heat exchangers 12 which may be aligned vertically in a generally parallel position is a central shaft 16, which may be supported on the outside of the frame 14, by a pair of bearings 18. The shaft 16 is driven by a motor 102 through a gearbox 103. A plurality of threaded rods 100 pass through apertures 101 in the apertured tabs 50 which are mounted to supporting

brackets 20. The rods 100, brackets 20, and spacers 22, may hold the heat exchangers 12 in a vertical position as shown in Figure 3, and are locked in place by nuts 24.

5 **[0078]** Between the outermost heat exchanger and the frame 14 is positioned an outer scraping device 26, shown in Figure 4, while the inner scraping device 28 shown in Figure 8 is positioned between two heat exchangers 12.

10 **[0079]** The refrigerant enters the machine 10 through a plurality of connections 30 (Figure 3), and is then pumped into each heat exchanger 12 through the inlets 32 (Figure 2). Once the refrigerant has passed through the heat exchanger 12, it then exits through outlets 34 (Figure 2) and back out through connections 30 (Figure 3). Fresh water, salt water or any other liquid to be cooled is pumped into the machine 10 through the shaft 16, then sprayed over the surface of the heat exchangers 12 from nozzles 36. For a
15 scraping device 26 that scrapes the outermost heat exchanger, nozzles 36 are disposed on the rear section of the scraper 26. While it is possible to place nozzles 36 on a scraping mechanism 28 that scrapes two plates simultaneously, it is preferable to place them on a separate spraying tube 92. The scraping devices 26, 28 are then rotated by the shaft 16, removing the
20 ice-water mixture from the surface of the heat exchangers 12 and causing it to fall down into the hood 38. Once in the hood 38, the ice-water mixture is then pumped into the storage tank (not shown), where the ice is separated, and the water is pumped back into the ice machine 10. A plurality of insulation panels 60 are bolted to the frame, creating a thermally insulated compartment.

25 **[0080]** With reference to Figures 4-10, embodiments of the scraping devices are shown. Figure 4 shows an outer scraping device 26 which comprises a carrier tube 54 that is bolted to the shaft 16 by use of base plate 56 (shown in Figure 5). Welded at the end of the carrier tube 54 is top web 62, shown in Fig 6B, while middle webs 64 (shown in Fig 6C) are spaced
30 evenly along the tube 54, and bottom web 66 (Figure 6D) is welded at the base of the tube 54, near the shaft 16. A plurality of scrapers 58 extend along the length of the carrier tube 54, secured to the webs, by a pivot shaft 68,

shown in Figure 7, where its shoulder 70 secures it in place. The scrapers 58 are preferably plastic for producing slurry ice, and metal for flake ice.

[0081] Referring to Figures 6A and 6B, resting in the slot 72 in each web is a first bar 74, which has a second bar 76 welded to both the first bar 74 and the web. Resting between the first bar 74 and the second bar 76 is a rubber bumper 78. This rubber bumper 78 pushes the scraper 58 away from bar 74, and pushes the scraper corner 80 against the flat plate heat exchanger 12. The shape of the scraper 58 allows it to be simply reversed when corner 80 wears off and use a second corner, thereby extending the life of the scraper. Along the opposite side of the carrier tube 54 from the scrapers 58, is a plurality of nozzles 36. As the water is pumped into the shaft 16, it travels up through the interior of the carrier tube 54, and is sprayed out the nozzles 36, as the tube 54 rotates with the shaft.

[0082] Figure 8 shows an inner scraping device 28, which is used between two flat plate heat exchangers 12. There is an inner carrier 82, which is welded to the base plate 56 (Figure 5) and bolted to the shaft 16. An additional, hollow carrier 84 slides over the inner carrier 82, encasing it. A removable bolt 86 secures the hollow carrier 84 to the inner carrier 82, and by doing so, to the shaft 16. A plurality of webs 88 are welded to the hollow carrier 84. There are two groups of scrapers 58, which are secured to the web 88 by two separate pivoted shafts 68 (shown in Fig 7). Each pair of scrapers 58 along the length of the carrier 84 are separated by a bumper 78. A bar 90 is welded to the webs 88 and secures bumpers 78 in place. The bumpers 78 push the scrapers 58 away from each other and towards their respective heat exchange plates 12. This design allows for easy maintenance of the inner scraping devices. Rather than remove the flat plate heat exchangers 12, all that is needed is to remove the bolt 86 and the hollow carrier 84 may be slid out from between the heat exchangers. Furthermore, because the carrier 84 is less than half of the diameter of the heat exchanger 12, the necessary service area around the ice machine is small.

[0083] Shown in Figure 10, on the opposite side of the shaft 16 from the inner carrier 82 is a spray tube 92 which is welded to a base plate 56 and bolted to the shaft 16. Along the length of the spray tube 92 is a plurality of

nozzles 36. As the water flows into the shaft 16, it flows through the spray tube 92, and out through the nozzles 36, spraying water on the heat exchanger 12 surfaces.

[0084] Figure 16 shows an alternative embodiment of the ice making machine with plates situated horizontally. This is advantageous in situations where height is limited, for example on board a fishing vessel. Referring to Figure 16, where like parts have been numbered similarly, ice making machine 210 comprises a plurality of flat plate heat exchangers 12 within a top frame 209 supported by a bottom frame 208. Passing through the heat exchangers 12 which are aligned horizontally in a generally parallel position is a central shaft 16, which is supported on the outside of the top frame 209 and under the collection pan 206 by a pair of bearing housings 18.

[0085] Between the outermost heat exchange plate and the top frame 209 is located an outer scraping device 201, while the inner scraping device 202 is located between two heat exchange plates 12. The refrigerant enters the machine 210 through a plurality of connections, and is then pumped into each heat exchanger 12. Fresh water, salt water or any other liquid to be frozen is pumped into the machine 210 through the shaft 16, then sprayed over the surface of the heat exchangers 12 from nozzles in the scraping devices 201, 202. The scraping devices 201, 202 are then rotated by the shaft 16, removing the ice-water mixture from the surface of the heat exchangers 12. The ice is pushed in an outward direction directed by orienting the scraping devices 202, 201 towards the outside. When the ice passes the outermost edge of the plate 12, it falls down into the pan 206. Figure 17 shows a top view of the pan 206. In the pan 206 is a sweeping device 203 attached to the shaft 16, which rotates together with the shaft 16, sweeping the ice that has fallen into the pan 206. The pan has a perforated section 212. As the sweeper 203 passes the perforated section 212, the ice falls through the perforated section 212 and lands in the sump 205. Ice is then pumped out of the ice machine through outlet 204 into the storage tank (not shown), where the ice is separated, and the water is pumped back into the ice machine 210. Bevelled corners 207 ensure that when the ice falls into the pan 206, it slides down into the section of the pan 206 reached by the sweeper 203.

[0086] Scraping devices 201, 202 are shown in Figure 18, and comprise a carrier with a plurality of scrapers 220. Each scraper 220 has a holder 223 with a top section 226, a rear section 224, and a front section 225, and two side sections 222 for holding a scraping element 221. A
5 compressible bumper 230 maintains outward pressure on the scraping element 221 keeping it in contact with the heat exchange plate 12.

[0087] Scrapers 220 are spaced along the carrier such that successive scrapers 220 are separated by approximately the width of a single scraper 220. Scrapers 220 on opposite sides of the shaft are aligned along the carrier
10 such that a circular path traced by any scraper 220 would pass through the scrapers on the opposite side. Scraping elements 221 have scraping edges 229 that are angled outwardly so as to push the ice towards, and finally over, the edge of the plate 12. Successive scraping elements may be angled increasingly outward such that those close to the shaft are angled closer to
15 parallel to the direction of the length of the carrier, and those close to the edge of the plate 12 are aligned closer to perpendicular to the direction of the length of the carrier. The differently angled scraping elements is not essential to the design. Pin 227 is used to connect scraping element to the holder 223, while a screw secured in thread 228 keeps the pin 227 in place.

[0088] In the case of an outer scraping device 201 that scrapes the outermost side of an outer plate 12, the scrapers 220 would be welded to a carrier bolted to the shaft. Inner scraping devices 202, that are situated between two plates and scrape the sides of those plates simultaneously, have the scrapers 220 welded to a hollow carrier, which is then slid over an inner
20 carrier 82 which is bolted to the shaft. Nozzles (not shown) are directed at the plates 12 from the carrier in order to spray the liquid to be frozen.
25

[0089] In the figures, the inner layer is shown as being made up of a plurality of sections, which fit together in a puzzle-like fashion. Each section is described as including a plurality of wall portions and foot portions, defining a
30 plurality of flow channels all of which are integrally joined as part of that section. It is alternatively possible for each wall portion 47 to be an individual piece, which has a foot portion 51 integrally connected thereto along one or both longitudinal edges 49. In other words, it is optionally possible for each

wall portion with its associated one or two foot portions 51 to be an individual piece that is individually connected to the outer plates.

[0090] In the figures, the ice making machine includes scrapers for scraping both sides of each heat exchanger. It is alternatively possible for one or more heat exchangers to have only a single scraper for scraping one side thereof.

[0091] In the figures, the ice-making machine has been shown to include a plurality of heat exchangers 12. It is alternatively possible for any of the ice making machines to include a single heat exchanger 12. In such an alternative, the machine may include an outer scraper 26 on one or both outer surfaces, however, it will be understood that the inner scraper 28 would not be included.

[0092] The ice-making machine 10 has been described as providing liquid to be frozen via a liquid source through the liquid supply system 17 to be ejected from the nozzles 36. It is alternatively possible to provide the liquid to be frozen in another way. For example, referring to Figure 22, a sealed housing 97 may be provided that defines an internal chamber 99, in which is positioned the heat exchangers 12 and the scrapers 26 and 28. Liquid to be frozen may be introduced into the chamber 99 via a chamber inlet 101 that may be positioned anywhere suitable, such as on one side wall of the housing 97. The chamber 99 may be substantially filled with the liquid to be frozen. Thus, the heat exchangers 12 are submerged in the liquid to be frozen. As ice forms on the heat exchangers 12, the scrapers 26 and 28 scrape off the ice. The ice may be collected by any suitable means, such as by collecting it in a suitable conduit connected at the top of the chamber 99.

[0093] Referring to Figure 22a, the sealed housing 97 may be generally cylindrical in shape, and may be comprised of one or two sheets 301 of flat, preferably insulated material bent into a cylindrical shape and sealed at its edges. The chamber 99 is sealed at its ends by two preferably insulated end panels 302 (Figure 22). Alternatively, the sealed housing may be generally rectangular in shape.

[0094] The housing 97 seals about the rotating shaft 16 that passes therethrough to prevent leakage of the liquid to be frozen. This seal can be accomplished by any suitable means, such as by a plurality of packing rings.

[0095] Alternative configurations of the machine 10 are possible. When
5 configured as a chiller, which cools but does not freeze the liquid, the scraper system 15 is not required. Liquid may brought into contact with the heat exchangers 12 by pumping the liquid into and out of the chamber 99. The rate of pumping determines the degree to which the liquid is cooled by the heat exchangers 12.

10 **[0096]** While the above description constitutes embodiments of the present invention, it will be appreciated that the present invention is susceptible to modification and change without departing from the fair meaning of the accompanying claims.

Claims:

What is claimed is:

1. An apparatus for heat exchange, comprising:
 - a) At least one fluid inlet;
 - b) At least one fluid outlet;
 - c) A first outer plate and a second outer plate, wherein each outer plate has an inner surface and an outer surface; and
 - d) An inner layer, wherein the inner layer is sealedly sandwiched between the first and second outer plates, and wherein the inner layer at least in part defines at least one series of fluid channels, and wherein each fluid channel is defined in part by the inner surface of one of the outer plates and by the inner layer, and wherein the at least one series of fluid channels makes up at least one flow path between the at least one fluid inlet and the at least one fluid outlet.
2. An apparatus according to claim 1, wherein said fluid is a refrigerant.
3. An apparatus according to claim 2, wherein the inner layer is sealedly sandwiched to withstand a pressure of 450 psi.
4. An apparatus according to claim 1, 2 or 3, wherein the inner layer joined with the outer plates defines a series of channels constituting at least part of the at least one flow path, the channels defined by inner layer wall portions that provide barriers between pairs of adjacent channels and integral foot portions for joining the inner layer to the outer plates.
5. An apparatus according to claim 1, 2, 3, 4 or 5, wherein the inner layer comprises a flow portion, wherein the flow portion includes a corrugated sheet material.

6. An apparatus according to claim 1, 2, 3, 4, or 5, wherein the inner layer comprises an outer boundary portion and a corrugated sheet metal portion, and optionally an inner boundary portion, and wherein the sheet metal portion of the inner layer covers an area that is between approximately 50% to approximately 95% of the area of inner layer, for example approximately 75% to approximately 90% of the area of the inner layer, optionally at least approximately 85% of the area of the area of inner layer, optionally at least approximately 88% of the area of inner layer.
7. An apparatus according to claim 5, wherein each channel has a channel width, and wherein each wall portion has a wall portion thickness, and wherein the ratio of the wall portion thickness to the channel width is less than 1:8.
8. An apparatus according to claim 7, wherein the ratio of the wall portion thickness to the channel width is less than 1:20
9. An apparatus according to claim 6, wherein the approximate ratio of the wall portion thickness to the channel width is between 1:25 and 1:20.
10. An apparatus according to claim 6, wherein the approximate ratio of the wall portion thickness to the channel width is between 1:18 and 1:25.
11. An apparatus according to claim 6, wherein the approximate ratio of the wall portion thickness to the channel width is approximately 1:22.5.
12. An apparatus according to claim 6, wherein the thickness of each outer plate is uniform over the entire span of the plate.
13. An apparatus according to claim 3, 6 or 12, wherein the thicknesses are the same for the portions of the first and second outer plates that are in surface communication with the corrugated sheet material.

14. An apparatus according to claim 3, 6, 12 or 13 wherein the thickness of the outer plates in surface communication with the corrugated sheet material is not more than approximately 0.12" (3 mm).
15. An apparatus according to claim 6 or 9, wherein said inner layer comprises an outer boundary portion and wherein the corrugated sheet material is seated within the outer boundary portion.
16. An apparatus according to claim 7, wherein said inner layer comprises an inner boundary portion and wherein the corrugated sheet material is seated within the outer boundary portion and the inner boundary portion.
17. An apparatus according to claim 15, wherein the heights of the outer boundary portion and corrugated sheet material are substantially the same and wherein the corrugated sheet material is seated flush within the outer boundary portion.
18. An apparatus according to claim 1, 2 or 3, wherein at least part of the inner layer is constituted by a plurality of inner layer sections joined in a puzzle-type arrangement, and wherein the arrangement substantially aligns at least one series of adjacent channels formed in each of at least two adjacent sections and wherein the aligned channels at least in part define a continuous flow path between the at least one fluid inlet and the at least one fluid outlet.
19. An apparatus according to claim 1, 2 or 6, comprising a plurality of inlets and outlets and wherein each fluid inlet is in fluid communication with at least one fluid outlet.
20. An apparatus according to claim 1, 2 or 6, wherein each fluid inlet is in substantial fluid communication with a single fluid outlet, wherein a series of channels defined by the inner layer wall portions define a different flow path for each respective fluid inlet and outlet pair.

21. An apparatus according to claim 1 or 6, wherein the flow path is constituted by a plurality of different flow path segments.
22. An apparatus according to claim 18, further comprising at least one inner layer section in which the channels are in substantial alignment with at least two adjacent inner layer sections.
23. An apparatus according to claim 18 or 22, wherein the channels constituting at least one inner layer section are aligned with the channels of at least one adjacent inner layer section in at least two different flow path segments.
24. An apparatus according to claim 23, wherein the flow path segments defined by the channels constituting said at least one inner layer section directs the fluid in one direction in at least one flow path segment and in the opposite direction in at least one other flow path segment.
25. An apparatus according to claim 18, wherein the channels constituting at least one flow path segment through a plurality of contiguous inner layer sections define a substantially circular flow path between said at least one fluid inlet and said at least one fluid outlet.
26. An apparatus according to claim 18, wherein the channels constituting at least one flow path segment through a plurality of contiguous inner layer sections define at least one serpentine flow path segment.
27. An apparatus according to claim 26, wherein the channels constituting at least one flow path segment through at least two adjacent inner layer sections are aligned at 90 degrees or less at the interface between the sections.
28. An apparatus according to claim 25, wherein the channels constituting at least one flow path segment through a plurality of contiguous

inner layer sections are aligned at obtuse angles at the interface between said sections.

29. An apparatus according to claim 26, wherein the channels constituting at least one flow path segment through all of the inner layer sections are aligned at obtuse angles at the interface the sections.

30. An apparatus according to claim 18, wherein the channels constituting at the flow path segment through the inner layer sections are aligned as shown in any one of figures 1, 11, 13, 14 and 15.

31. An apparatus for heat exchange, comprising:

- a) At least one fluid inlet;
- b) At least one fluid outlet;
- c) a first outer plate and a second outer plate; and
- d) an inner layer, wherein the inner layer at least in part defines at least one flow path between the at least one fluid inlet and the at least one fluid outlet, wherein the inner layer is sealedly sandwiched between the first and second outer plates.

32. The apparatus of claim 31 wherein the sections are configured so that the majority of the inside surface of the top and bottom plate come in to contact with the fluid flowing through the sections.

33. The apparatus as claimed in claim 31, wherein the puzzle-type arrangement of the sections is symmetric.

34. The apparatus as claimed in claim 31, wherein the parallel flow paths are corrugated material.

35. The apparatus of claim 34 wherein the corrugation consists of bends which are substantially right angles.

36. The apparatus as claimed in claims 31 through 35, wherein there are two inlets and two outlets.
37. The apparatus as claimed in claim 36, wherein the inlets and outlets are equally spaced along the edge of the plate.
38. The apparatus as claimed in claims 31 - 37, wherein the inlet and outlet are dimensioned so the fluid flows into a significant number of flow paths.
39. The apparatus as claimed in claims 31 - 38, wherein the top and bottom plates each include an outer ring and an inner ring.
40. 9. The apparatus as claimed in claim 39, wherein the inner and outer rings extend beyond the sections of flow paths.
41. The apparatus as claimed in claims 31 - 40, wherein the puzzle-type configuration of the sections of flow paths directs the fluid to flow through the inlet and in towards the inner ring, then flow around the inner ring towards the outlet, before being directed one or more times back and forth along paths around the inner ring, in directions first towards the inlet then towards the outlet, each such path being successively closer to the outer ring, and then directed through the outlet.
42. The apparatus as claimed in claims 33 - 41, wherein the puzzle-type configuration of the sections of flow paths is as appears in Figure 1.
43. The apparatus as claimed in claims 31- 40 wherein the puzzle-type configuration of the sections of flow paths is as appears in Figure 13.
44. The apparatus of claim 31 wherein the inlets and outlets are located proximate the edge of the plate.
45. An apparatus for scraping material from a plate, comprising:

- a) a shaft passing perpendicularly through the centre of the plate;
 - b) a carrier connected to the shaft, wherein the carrier extends parallel to the plate;
 - c) a plurality of scrapers positioned along the length of the carrier;
- and
- d) means for keeping the scrapers in contact with the plate.

46. The apparatus as claimed in claim 45, wherein the carrier further comprises a plurality of nozzles for spraying a liquid on the plate.

47. The apparatus as claimed in claim 45 wherein the means for keeping the scrapers in contact with the plate comprises a rubber bumper.

48. The apparatus as claimed in claim 45, further comprising means for rotating the carrier.

49. The apparatus as claimed in claim 48, wherein the rotating means is a motor.

50. The apparatus as claimed in any one of claims 45 to 49, wherein the scrapers are plastic.

51. The apparatus as claimed in any one of claims 45 to 49, wherein the scrapers are metal.

52. The apparatus as claimed in any one of claims 45 to 51, wherein the scrapers include a first and second edge, and where the scrapers are reversible to permit use of either edge.

53. An apparatus for scraping material from two parallel plates, comprising:

- e) a carrier positioned between the plates;

- f) at least one scraper positioned along the length of the carrier;
- g) means for keeping the scraper in contact with both plates; and
- h) means for rotating the carrier in a plane parallel to the plates.

54. The apparatus of claim 53, wherein the carrier is connected to a shaft passing perpendicularly through the plates.

55. The apparatus of claim 53, wherein the carrier contains at least two scrapers, each one of which is in contact with one of the plates.

56. An apparatus for scraping material from two parallel plates, comprising:

- i) a shaft passing perpendicularly through the plates;
- j) an inner carrier with means to secure it to the shaft and positioned perpendicular to the shaft parallel to the plates
- k) a hollow outer carrier positioned between the plates so the inner carrier is in sliding engagement within the hollow carrier;
- l) at least one scraper positioned along the length of the hollow outer carrier;
- m) means for keeping the scrapers in contact with the plates; and
- n) removable means to connect the inner carrier to the hollow outer carrier.

57. The apparatus as claimed in claim 56, further comprising a plurality of nozzles for spraying a liquid on the plates.

58. The apparatus as claimed in claim 56, further comprising means for rotating the carrier.

59. The apparatus as claimed in claim 58, wherein the rotating means is a motor.

60. The apparatus as claimed in claim 53 or 56, further comprising a tube secured to the shaft on the opposite side of the carrier with a plurality of nozzles for spraying a liquid on the plates.

61. The apparatus as claimed in claim 56, wherein the securing means is a plate welded to the inner carrier and bolted to the shaft.

62. The apparatus as claimed in claim 56, wherein the removable connecting means is a bolt.

63. The apparatus as claimed in any one of claims 56 to 62, wherein the scrapers are plastic.

64. The apparatus as claimed in any one of claims 56 to 62, where said scrapers are metal.

65. The apparatus as claimed in any one of 53 to 64, wherein the scrapers include a first and second edge, and where the scrapers are reversible to permit use of either edge.

66. An apparatus for cooling liquids, comprising:

- o) a frame;
- p) a plurality of flat plate heat exchangers arranged in parallel within the frame;
- q) means for continuously bringing a liquid into contact with the heat exchangers;

67. An apparatus for making ice, comprising:

- r) a frame;
- s) a plurality of flat plate heat exchangers arranged in parallel within the frame;

t) means for continuously bringing a liquid into contact with the heat exchangers;

u) scraping means for removing any ice crystals that form on the surface of the heat exchangers.

68. The apparatus as claimed in claims 66 or 67, wherein each heat exchanger comprises:

v) a top plate and a bottom plate of generally the same shape,

w) at least one fluid inlet located at an edge of the plates,

x) at least one fluid outlet located at an edge of the plates,

y) a plurality of sections between the top and bottom plate wherein each section comprises a narrow length of material with parallel flow paths and the sections are in puzzle-type arrangement with each other so that the flow paths from each piece allow for continuous flow of the fluid from the inlet through the sections and out the outlet

69. The apparatus as claimed in claims 66 or 67, wherein the means for bringing the liquid into contact with the heat exchanger is a sprayer.

70. The apparatus as claimed in claims 66 or 67, wherein a plurality of insulation panels is secured to the frame to create a sealed compartment.

71. The apparatus of claim 70, wherein the sealed compartment is rectangular.

72. The apparatus of claim 70 wherein the sealed compartment is cylindrical.

73. The apparatus as claimed in any of claims 67 to 70, wherein the scraping device consists of at least one outer scraper, and if more than one plate heat exchanger is present, at least one inner scraper, wherein said outer scraper comprises:

z) a carrier connected perpendicular to the shaft parallel to the plate

aa) a plurality of scrapers positioned along the length of the carrier;

bb) means for keeping the scrapers in contact with the plate;
and said inner scraper comprises:

cc) an inner carrier with means to secure it to the shaft and positioned perpendicular to the shaft parallel to the plates;

dd) a hollow outer carrier positioned between the plates so the inner carrier is in sliding engagement within the hollow carrier;

ee) a plurality of scrapers positioned along the length of the hollow carrier;

ff) means for keeping the scrapers in contact with the plates;
and

gg) means for releasably connecting the inner carrier to the hollow outer carrier.

74. The apparatus of any of claims 66-73 wherein the heat exchange plates are situated vertically.

75. The apparatus of any of claims 66 through 73, wherein the heat exchange plates are situated horizontally, further comprising a pan below the flat plate heat exchangers for collecting the ice removed by the scraping device.

76. The apparatus as claimed in claim 75, wherein the pan comprises:

hh) a flat area;

ii) a perforated area within the flat area through which collected ice may fall further; and

jj) means for sweeping the ice collected in the flat area across the perforated area.

77. The apparatus as claimed in claim 76, wherein the pan has raised corners for deflecting fallen ice towards the sweeping means.

78. The apparatus as claimed in any of claims 75 through 78 further comprising a sump below the pan into which ice can fall.

79. A method for establishing an overall continuous flow path from an inlet to an outlet through an apparatus for heat exchange, occupying substantially all of the surface area between the inlet and outlet, comprising the steps of:

- a) providing a plurality of sections, where each section is made up of a parallel set of flow channels;
- b) cutting each section at one or more angles to selected groups of parallel flow channels;
- c) abutting edges of each section to one or more other sections, thereby causing the flow path to change direction; and
- d) assembling the sections in a puzzle-like configuration.

80. The method as claimed in claim 79, wherein each section may include all contiguous and parallel channels at any given point, whereby a section may include parallel flow paths in opposite directions to one another.

81. An apparatus for heat exchange, comprising:

- a) a top plate and a bottom plate of generally the same shape;
- b) at least one fluid inlet located at an edge of the plates;
- c) at least one fluid outlet located at an edge of the plates; and
- d) a plurality of sections between the top and bottom plate wherein each section comprises a length of material with parallel flow paths and the sections are in puzzle-type arrangement with each other so that the flow paths from each piece allow for continuous flow of the fluid in through the inlet, through the sections and out the outlet.

82. The apparatus as claimed in claim 81, wherein the sections are configured so that the majority of the inside surface of the top and bottom plate come in to contact with the fluid flowing through the sections.

83. The apparatus as claimed in claim 81, wherein the puzzle-type arrangement of the sections are configured symmetrically.

84. The apparatus as claimed in claim 81, wherein the parallel flow paths are corrugated material.

85. The apparatus as claimed in claim 81, wherein there are two inlets and two outlets.

86. The apparatus as claimed in claim 85, wherein the inlets and outlets are equally spaced along the edge of the plate.

87. The apparatus as claimed in claim 81, wherein the inlet and outlet are dimensioned so the fluid flows into a significant number of flow paths.

88. The apparatus as claimed in claim 81, wherein the top and bottom plates each include an outer ring and an inner ring.

89. The apparatus as claimed in claim 88, wherein the inner and outer ring extend beyond the sections of flow paths.

90. The apparatus as claimed in claim 88, wherein the puzzle-type configuration of the sections of flow paths directs the fluid to flow through the inlet and in towards the inner ring, then flow around the inner ring towards the outlet, before being directed one or more times back and forth along paths around the inner ring, in directions first towards the inlet then towards the outlet, each such path being successively closer to the outer ring, and then directed through the outlet.

91. An apparatus for scraping material from a plate, comprising:

- a) a shaft passing perpendicularly through the centre of the plate;
- b) a carrier connected perpendicular to the shaft parallel to the plate;
- c) a plurality of scrapers positioned along the length of the carrier; and
- d) means for keeping the scrapers in contact with the plate.

92. The apparatus as claimed in claim 91, wherein the carrier further comprises a plurality of nozzles for spraying a liquid on the plate.

93. The apparatus as claimed in claim 91, wherein the means for keeping the scrapers in contact with the plate comprises a rubber bumper.

94. The apparatus as claimed in claim 91, further comprising means for rotating the shaft.

95. The apparatus as claimed in claim 94, wherein the rotating means is a motor.

96. The apparatus as claimed in any one of claims 91 to 95, wherein the scrapers are plastic.

97. The apparatus as claimed in any one of claims 91 to 95, wherein the scrapers are metal.

98. The apparatus as claimed in any one of claims 91 to 97, wherein the scrapers include a first and second edge, and where the scrapers are reversible to permit use of either edge.

99. An apparatus for scraping material from two parallel plates, comprising:

- a) a carrier positioned between the plates;

- b) at least one scraper positioned along the length of the carrier;
- c) means for keeping the scraper in contact with both plates; and
- d) means for rotating the carrier in a plane parallel to the plates.

100. The apparatus of claim 99 where the carrier is connected to a shaft passing perpendicularly through the plates.

101. The apparatus of claim 99 where the carrier contains at least two scrapers, each one of which is in contact with one of the plates.

102. An apparatus for scraping material from two parallel plates, comprising:

- a) a shaft passing perpendicularly through the centre of the plates;
- b) an inner carrier with means to secure it to the shaft and positioned perpendicular to the shaft parallel to the plates
- c) a hollow outer carrier positioned between the plates so the inner carrier is in sliding engagement within the hollow carrier;
- d) a plurality of scrapers positioned along the length of the hollow outer carrier;
- e) means for keeping the scrapers in contact with the plates; and
- f) removable means to connect the inner carrier to the hollow outer carrier.

103. The apparatus as claimed in claim 102, further comprising a plurality of nozzles for spraying a liquid on the plates.

104. The apparatus as claimed in claim 102, further comprising means for rotating the shaft.

105. The apparatus as claimed in claim 104, wherein the rotating means is a motor.

106. The apparatus as claimed in claim 102, further comprising a tube secured to the shaft on the opposite side of the carrier with a plurality of nozzles for spraying a liquid on the plates.

107. The apparatus as claimed in claim 102, wherein the securing means is a plate welded to the inner carrier and bolted to the shaft.

108. The apparatus as claimed in claim 102, wherein the removable connecting means is a bolt.

109. The apparatus as claimed in any one of claims 102 to 108, wherein the scrapers are plastic.

110. The apparatus as claimed in any one of claims 102 to 108, where said scrapers are metal.

111. The apparatus as claimed in any one of claims 102 to 110, wherein the scrapers include a first and second edge, and where the scrapers are reversible to permit use of either edge.

112. An ice making apparatus, comprising:

- a) a frame;
- b) a plurality of flat plate heat exchangers arranged in parallel within the frame;
- c) spraying means for continuously supplying a solution over the heat exchangers; and
- d) scraping means for removing any ice crystals that form on the surface of the heat exchangers.

113. The apparatus as claimed in claim 112, wherein a plurality of insulation panels are secured to the frame to create a sealed compartment.

114. An ice making apparatus, comprising:

- a) a frame;
- b) a plurality of flat plate heat exchangers arranged vertically and parallel within the frame with each heat exchanger comprising,
 - i) a top plate and a bottom plate of generally the same shape,
 - ii) at least one fluid inlet located at an edge of the plates,
 - iii) at least one fluid outlet located at an edge of the plates,
 - iv) a plurality of sections between the top and bottom plate wherein each section comprises a narrow length of material with parallel flow paths and the sections are in puzzle-type arrangement with each other so that the flow paths from each piece allow for continuous flow of the fluid from the inlet through the sections and out the outlet, and
 - v) the sections are configured so that the majority of the inside surface of the top and bottom plate come in to contact with the fluid flowing through the sections;
- c) a shaft passing perpendicularly through the centre of the plates;
- d) spraying means for continuously supplying a solution over the heat exchangers;
- e) a scraping device connected to the shaft for removing any ice crystals that form on the surface of the heat exchangers;
- f) means to rotate the shaft; and
- g) a plurality of insulation panels secured to the frame to create a sealed compartment.

115. The apparatus as claimed in claim 114, wherein the scraping device consists of at least one outer scraper, and if more than one plate heat exchanger is present, at least one inner scraper, wherein said outer scraper comprises:

- a) a carrier connected perpendicular to the shaft parallel to the plate
- b) a plurality of scrapers positioned along the length of the carrier;

- c) means for keeping the scrapers in contact with the plate;
and said inner scraper comprises:
 - d) an inner carrier with means to secure it to the shaft and positioned perpendicular to the shaft parallel to the plates;
 - e) a hollow outer carrier positioned between the plates so the inner carrier is in sliding engagement within the hollow carrier;
 - f) a plurality of scrapers positioned along the length of the hollow carrier;
 - g) means for keeping the scrapers in contact with the plates; and
 - h) means for releasably connecting the inner carrier to the hollow outer carrier.

116. An ice making apparatus, comprising:

- a) a frame;
- b) a plurality of flat plate heat exchangers arranged horizontally and parallel within the frame;
- c) a shaft passing perpendicularly through the centre of the plates;
- d) spraying means for continuously supplying a solution over the heat exchangers;
- e) a scraping device connected to the shaft for removing any ice crystals that form on the surface of the heat exchangers;
- f) means to rotate the shaft; and
- g) a pan below the flat plate heat exchangers for collecting the ice removed by the scraping device.

117. The apparatus as claimed in claim 116, wherein the pan comprises:

- a) a flat area;
- b) a perforated area within the flat area through which collected ice may fall further; and
- c) means for sweeping the ice collected in the flat area across the perforated area.

118. The apparatus as claimed in claim 117, wherein the pan has raised corners for deflecting fallen ice towards the sweeping means.

119. The apparatus as claimed in any of claims 111, 117, or 118 further comprising a sump below the pan into which ice can fall.

120. A method for establishing an overall continuous flow path from an inlet to an outlet through an apparatus for heat exchange, occupying substantially all of the surface area between the inlet and outlet, comprising the steps of:

- e) providing a plurality of plates, where each plate is made up of a parallel set of flow channels;
- f) cutting each plate at one or more angles to selected groups of parallel flow channels;
- g) abutting edges of each plate to one or more other plates, thereby causing the flow path to change direction; and
- h) assembling the plates in a puzzle-like configuration.

121. The method as claimed in claim 120, wherein each plate may include all contiguous and parallel channels at any given point, whereby a plate may include parallel flow paths in opposite directions to one another.