

Heave compensated crane

The present invention relates to a heave compensated crane
5 comprising a lower vertical beam and an upper vertical
beam which are mutually connected via an articulated
piece, as the vertical beam is connected, at the bottom,
to a base which in turn comprises a slew ring for rotation
of the crane about a vertical axis, and a strut is
10 arranged between the base and the articulated piece at a
distance from the vertical beam and largely in parallel
with this in a normal position for the crane, and that the
vertical beam is driven by, at least, one cylinder and the
upper crane beam in its movement in relation to the lower
15 beam is driven by an intermediate cylinder arrangement.

From prior art reference is made to NO 151757 which
describes a device for compensation and distance
variations between a suspended item from a floating
20 carrier and the ocean bed. In more detail the document
shows a device in the form of a piston and cylinder
arrangement that is suspended in a cable that runs from a
tower or a crane and down to a load that hangs at the end
of the cable, to reduce the heave of the load that is to
25 be placed on the ocean bottom.

Furthermore, EP 1433922 shows a hoisting apparatus in the
form of cables and blocks fastened to a mast, and where a
pneumatic or hydraulic cylinder is used to dampen
30 movements of the vessel onto which the apparatus is
mounted.

DE 3433104 relates to a hydraulic control mechanism for
load estimations.

Common for the described documents is that they relate to heave compensation with the use of a winch and a compensator system, where the compensator system either regulates the winch or the compensator system is arranged
5 between the winch and the load.

The compensator systems that appear in the documents can comprise both passive and active cylinders, and also single working and double working cylinders.

10

Also known are heave compensating systems that are placed on the deck of a vessel and which are used in combination with existing deck winches. The cable runs from the winch and via guiding discs on the deck and to the crane. A
15 movement detector system registers heave and compensates with the help of a cylinder arrangement.

A problem that shall be solved in relation to the above mentioned technique can then be regarded to be "how to
20 achieve heave compensation without the use of a winch system?" According to the present invention this is solved by integrating the heave compensation with the "normal" hoisting cylinders of the crane so that it is not necessary with an advanced heave compensating system on
25 the winch.

With regard to NO 151757 it shall be pointed out that it is shown clearly a device for heave compensation that is suspended in a cable. The compensation takes place between
30 this and the load cable that is coupled to the load. With the present solution an arrangement is shown where the hydraulic cylinders lift the crane beam with a wire disc. The compensation occurs in that the cylinders hoist and lower the beam in relation to the horizontal starting
35 position.

One consequence is that in the embodiment of NO 151757 the load will hang in the cylinders, so that these experience a tension load, in contrast to the present crane where the cylinders work with a pressure load.

Another further consequence is that the single working, passive draw, cylinder in NO 151757 must be constructed as a double working cylinder where the piston sides have no role. The active part is made up of two double working cylinders that are in contrast to the present crane where the active part lifts the load with the help of a single working cylinder, while the active lowering of the load is carried out with the help of the rod side of, for example, two other cylinders. With this arrangement the cylinders can be adapted so that there will be an equal active area for the hoisting and lowering.

The whole of the heave compensating unit in NO 151757 is superfluous and without any use as soon as the heave-compensation operation is carried out. It represents an unfavourable additional weight which is a strain on the crane it is suspended from. It is also impossible to remove it as long as the load hangs in it. It also requires supply of hydraulic pressure and/or electric power from the ship. As the device is shown in fig. 4 in NO 151757, the lifting of the load is hindered by the device hitting the disc housing of the cable, and the lowering of the load is limited by the ocean level, and the length of the hydraulic/electrical supply from the ship. With the present crane all hydraulic cylinders can be in use with normal operation of the crane also. The single working cylinder can be used to increase the lifting capacity beyond what the crane has during the heave compensation.

Reference is also made to WO 2010/024689 A1 and US
5,381,909 A, where the former document is related to a
crane built up by the corresponding crane construction as
the present crane. US 5,381,909 A relates to a
compensating system for a winch arm onboard a boat, where
the arm rotates with the help of a double working cylinder
in parallel with a single working cylinder. The aim of the
solution in the document US 5,381,909 A is to adjust the
angle of the winch arm and thereby the stretch tension on
the load carrying cable. It is a single working load
cylinder for normal operation of the winch arm and a
double working servo cylinder for the regulation of the
angle and thereby also the movement of the outer end of
the winch arm, where the cylinders are placed in parallel
and connected to an accumulator. An angle sensor system is
used to provide inputs to the regulation of the angle.

Consequently, it is an object of the present invention to
provide a crane where the above mentioned disadvantages
are avoided, or at least reduced.

Another object of the invention is to provide a crane with
a considerably improved working area for the crane.

The above mentioned problems and objects are solved by a
heave compensating crane as given in the independent claim
1, in that the cylinder arrangement comprises, at least,
one single working cylinder and, at least, one double
working cylinder.

Alternative embodiments are given in the dependent claims
2-9.

During heave compensation the single working cylinder can be arranged to lift the crane beam and, at least, the one double working cylinder can be arranged for the lowering of the crane beam by the use of the rod side of the double
5 working cylinder.

The cylinder arrangement can comprise a centrally placed single working cylinder and two side mounted double working cylinders, where the double working cylinders are
10 connected to a respective accumulator. Said accumulators and any associated gas reservoir can be integrated with respective cylinders.

During normal operation the connection between the double
15 working cylinders to said accumulators is preferably closed by a respective closing valve, whereby the whole of the cylinder arrangement is arranged for operation of the crane beam. Furthermore, during normal operation the piston side of all the cylinders can be pressurised in the
20 normal way.

During heave compensated operation the connection between the double working cylinders to said accumulators is preferably open, as a respective closing valve is open and
25 a respective closing valve between the double working cylinders and the hydraulic control valve is shut.

Furthermore, during heave compensated operation the piston side of the single working cylinder can be pressurised in
30 the normal way, and the piston side of the double working cylinders can be passive, while the rod side is active. The rod side of the double working cylinders can be connected via a pipe.

The invention shall now be described in more detail with reference to the enclosed figures, in which:

Figure 1 shows a heave compensated crane according to the invention.

5 Figure 2 shows a cylinder arrangement for the crane during normal operation.

Figure 3 shows a cylinder arrangement for the crane during heave compensated operation.

10 Figure 1 shows the crane according to the invention. It is possible to use, for example, the crane described in the Norwegian patent application NO 20083654.

15 An aim of the crane construction is that the crane point will be held at largely the same horizontal level during the whole of the crane operating range, due to the design of the crane.

20 As shown, the crane comprises two main parts, a vertical beam 10 and a horizontal beam 12. The vertical beam 10 is mounted at the bottom in a "king" or base part 14 that can rotate about a vertical axis on a bearing on the top of a bottom base. The vertical beam 10 can be moved with the help of, at least, one cylinder 18 which is mounted
25 between a point on the base 14 and a point on the vertical beam 10. At the top end of the vertical beam 10 an articulated piece 20 is mounted. The articulated piece 20 can be, seen from the side, shaped with a "triangular" construction. The horizontal beam 12 is mounted in the
30 articulated piece 20.

35 The articulated piece is held up and controlled with the help of a strut 22 which, at its lower end, is mounted in the base or the foundation 14 and, at its upper end, in the articulated piece 20.

The crane can rotate with the help of a slew ring on a pedestal as normal.

5 The horizontal beam 12 is held up with the help of a cylinder arrangement 16 mounted between the articulated piece and the horizontal beam 12. A wire disc 24 is fastened at the outer end of the horizontal beam 12. This guides a wire 26 from a winch mounted onto, or outside,
10 the crane itself.

The crane moves between the largest and the smallest radius (reach) in that the vertical beam 10 is moved forwards and backwards in relation to the vertical
15 starting position with the help of the cylinder(s) 18. During this movement the vertical beam 10 has, as its main task, regulation of the work radius of the crane. The horizontal beam 12 will compensate for the height difference that arises during this movement, so that the
20 wire disc 24 is held at a constant height. This occurs without the cylinder arrangement 16 having to be moved and consequently the horizontal beam 12 will follow the movement of the articulated piece 20. It is the strut 22 that controls this movement. By estimating optimal mutual
25 placing of components and connecting points, a compensation that leads to an approximately constant (horizontal) height of the wire disc 24 is achieved. It is possible to achieve a height variation of only a few percent of the radial movement.

30 In connection with operations offshore, for example, when the crane is mounted on a vessel, the movement of the vessel will influence the movement of the horizontal crane beam 12 and consequently also the movement of the wire
35 disc 24. The present crane is therefore equipped with a

cylinder arrangement 16 with heave compensation and which will be described in more detail in the following.

Figure 2 shows a cylinder arrangement 16 during normal operation, while figure 3 shows a cylinder arrangement during heave compensated operation. As can be seen in the figures the embodiment example of the cylinder arrangement shown comprises a centrally placed, single working cylinder 30 (which can also be a double working cylinder) connected to a hydraulic control valve 50 and associated pump/motor 44 via a pipe 48. At the side of the single working cylinder 16, a double working cylinder 32 (only one double working cylinder may be used) is placed, which is connected at its piston side 32a to the same hydraulic control valve 50 via a pipe 42. A closing valve 42a is connected to the pipe 42. At the piston side 32a of the double working cylinders 32 a pipe 40 is connected with a closing valve 40a, and which leads to an accumulator 34 which in turn is connected to a gas container 36 or reservoir. A pipe 46 can run between the rod side 32b of the double working cylinders 32.

For normal lifting operation the piston side 32a of the two double working cylinders is used, but in heave compensation they are used as passive cylinders for compensation of the load. During the active function during heave compensating, the single working cylinder 30 is used for lifting, while the rod side 32b of the two double working cylinders 32 is used for the lowering.

During normal operation the connection between the double working cylinders to said accumulators is closed by the respective closing valve 40a, so that the whole of the cylinder arrangement 16 is arranged for the operation of

the crane beam 12. Furthermore, the piston side of all the cylinders 30, 32 are pressurised in the normal way.

During heave compensated operation the connection between
5 the double working cylinders 32 to said accumulators 34 is
open, as the respective closing valve 40a is open and the
respective closing valve 42a between the double working
cylinders 32 and the hydraulic control valve 50 is closed.
This leads to that during heave compensated operation the
10 piston side 30a of the single working cylinder 30 is
pressurised in the normal way and the piston side 32a of
the double working cylinders 32 is passive, while the rod
side 32b is active. During heave compensated operation the
rod side of the double working cylinders 32 is preferably
15 connected via a pipe 46.

Furthermore, the piston accumulators can be considered to
be mounted together with the double working cylinders so
that a compact, integrated design is provided.

20

C L A I M S

1. Heave compensated crane mounted on a vessel,
comprising a lower vertical beam (10) and an upper
5 horizontal beam (12) which are mutually connected via an
articulated piece (20), as the vertical beam is connected
at the bottom to a base (14), which in turn comprises a
slew ring for rotation of the crane about a vertical axis,
and a strut (22) is arranged between the base (14) and the
10 articulated piece (20), at a distance from the vertical
beam (10) and largely in parallel with this in a normal
position for the crane, and that the vertical beam (10) is
driven by, at least, one cylinder (18), and the upper
crane beam (12) in its movement in relation to the lower
15 beam (10) is driven by an intermediate cylinder
arrangement (16), c h a r a c t e r i s e d i n t h a t
the cylinder arrangement (16) comprises at least one
single working cylinder (30) and at least one double
working cylinder (32), adapted for heave compensating of
20 the crane due to vessel movement,
during heave compensated operation a connection
between the double working cylinders (32) to an
accumulator (34) is open, as a closing valve (40a) between
the cylinder (32) and the accumulator (34) is open, and a
25 closing valve (42a) between the double working cylinder
(32) and a hydraulic control valve (50) is closed, while
during normal operation the closing valve (40a) is closed,
wherein all of the cylinder arrangement (16) is arranged
for operation of the beam (12), and
30 during heave compensated operation a piston side of
the single working cylinder (30) is pressurised, and a
piston side of the double working cylinders (32) is
passive while the rod side is active, while during normal
operation the piston side of all cylinders (30,32) are
35 pressurised.

2. Crane according to claim 1,
c h a r a c t e r i s e d i n that during heave
compensation the single working cylinder (30) is arranged
to lift the crane beam (12) and the at least one double
5 working cylinder (32) is arranged to lower the crane beam,
(12) by activating the rod side (32b) of the double
working cylinder.

3. Crane according to claim 1,
10 c h a r a c t e r i s e d i n that the cylinder
arrangement (16) comprises a centrally placed single
working cylinder (30) and two side mounted double working
cylinders (32), where the double working cylinders are
connected to a respective accumulator (34).

15

4. Crane according to claim 3,
c h a r a c t e r i s e d i n that said accumulators
(34) and any associated gas reservoir (36) are integrated
with respective cylinders (30, 32).

20