

Description

Background of the Invention

1. Field of the Invention

The present invention pertains to apparatus for extracting corks from bottles. A number of features are desirable in such an apparatus. One of the most important of these is that the corkscrew portion of the apparatus be well centred in the cork during operation, so as to ensure the removal of the entire cork, and minimize the possibility of breaking the cork and permitting the resulting fragments to fall into the wine in the bottle. Another important consideration is that the corkscrew must be pulled in a substantially straight line along its own axis when the cork is being removed, and this axis should ordinarily be substantially aligned with that of the bottle, so as to facilitate removal. Another desirable feature in cork-extracting apparatus is the provision of means to reduce the manual force required to drive the corkscrew into the cork and/or to extract the cork from the bottle. There is also a need for preventing small cork fragments from breaking off even when the corkscrew is driven completely through the cork.

2. Description of the Prior Art

GB-A-2027681 and DE-A-2929026, and their counterpart applications, disclose cork extractors which meet the above needs. These applications describe a simple, inexpensive apparatus for extracting a cork from a bottle as well as an improved corkscrew proper which may be used to advantage in said apparatus as well as in virtually any other type of corkscrew or cork extractor. The apparatus includes a holder and a cork-engaging member. The cork-engaging member includes the corkscrew per se and abutment means, such as a handle, carried on the corkscrew and engageable with the holder to limit downward movement of the cork-engaging member with respect to the holder in use. The holder includes guide means having a guide passageway extending generally longitudinally therethrough. The guide passageway has guide surface means facing generally radially inwardly and is sized to lie closely adjacent the outer diameter of the corkscrew helix, the corkscrew being rotatably and longitudinally movable in the guide passage. The holder further includes stop means engageable with the bottle to limit downward movement of the holder with respect to the bottle as well as grip means spaced downwardly from the guide means and engageable with the bottle to radially align the guide means with the bottle. Thus, the grip means in conjunction with the stop means of the holder serve to generally radially center and coaxially align the guide means, and thus the corkscrew received therein, with the bottle and its cork.

By rotating the cork-engaging member and, at least initially, simultaneously exerting a downward force thereon, the corkscrew may be driven into the cork while still properly centered and

aligned therewith by the holder. When the abutment means of the cork-engaging member comes into abutment with the holder, thereby preventing further downward movement of the cork-engaging member, continued rotation of that member in the same direction will cause the cork to rise on the helical corkscrew, the guide means being spaced above the top of the bottle by a sufficient distance to permit such movement.

The corkscrew itself is improved by the provision of a central body, e.g. of high tensile metal, covered by an outer layer of friction-reducing material, such as polytetrafluoroethylene, on at least one portion of the downwardly facing surfaces of the central body. This greatly enhances the ease with which the corkscrew may be driven into the cork. This friction-reducing expedient not only virtually eliminates any problem in easily penetrating a tight cork, but also permits the use of design features in the central body which could not be used without the friction-reducing layer and which themselves enhance the ease of insertion and otherwise improve the corkscrew. Accordingly, the friction-reducing layer on the corkscrew is largely instrumental in making the relatively simple apparatus described above effective in easily penetrating and properly removing even extremely hard and/or tight corks.

The corkscrew also has an improved lower pointed tip portion which is formed in such a way that it eliminates the tendency for small cork fragments to be broken away, even when the corkscrew is driven completely through the cork. This effect is further enhanced by the friction-reducing layer mentioned above so that the possibility of contamination of wine by cork fragments is virtually eliminated.

The cork extractors of GB-A-2027681 and DE-A-2929026 are modern examples of cork extractors of the so-called "self-puller type", being a type of cork extractor which has been known for a very long time (the literature shows examples made as early as the 18th century). A cork extractor of self-puller type is one in which the corkscrew of the device is driven into the cork by rotation of the corkscrew in one direction and the upward pulling action on the cork is exerted solely by the corkscrew itself by its continued rotation in the same direction, causing the cork to climb the screw.

DE-C-55574 discloses a cork extractor which comprises the usual helical corkscrew and a spring which is mounted above the corkscrew in such a way that as the corkscrew is driven into a cork to be withdrawn the spring is increasingly compressed until the point is reached when the spring is able to lift the screw and cork jointly from the bottle. Ribs are provided within the casing of the cork extractor to hold the cork stationary while the corkscrew is unscrewed off the cork after completion of the cork withdrawal process. The principle on which this cork-extractor operates is thus quite different from that of the aforementioned GB-A-2027681 and DE-A-2929026, and in particular the cork

extractor does not rely on the cork climbing threadedly upwardly on the corkscrew to effect withdrawal nor does the ribs assist the cork withdrawal process accomplished by the spring.

Summary of the Invention

The present invention relates to a cork-extracting apparatus as specified in the precharacterising part of claim 1. Such an apparatus is, for example, disclosed in the aforementioned prior GB-A-2027681 and DE-A-2929026. Like these and other known cork extractors of self-puller type, that of the present invention comprises a corkscrew, and preferably also a handle secured to the upper end of the corkscrew, and a holder. The holder engages the corkscrew and permits rotation thereof relative to the holder, while restricting downward movement of the corkscrew relative to the holder. The holder comprises bottle engaging means and spacer means. The bottle-engaging means position the holder and the engaged corkscrew in generally coaxial alignment with the neck of the bottle. The bottle-engaging means includes stop means for limiting downward movement of the holder with respect to the bottle. The spacer means define an opening for receipt of the cork as it emerges from the bottle. As in prior apparatus of the self-puller type, the corkscrew is of a length such that it may extend into the cork receiving opening whereby the cork may move in self-puller fashion threadedly upwardly on the corkscrew as the corkscrew is rotated to withdraw the cork from the bottle.

Thus, like known apparatus of self-puller type, the apparatus of the present invention is operated by engaging the bottle neck with the bottle-engaging means and exerting a downward force on the corkscrew with simultaneous rotation to begin driving the corkscrew into the cork. Continued rotation of the corkscrew will drive into the cork, until a point is reached when further downward movement of the corkscrew is prevented. Thereafter, with continued rotation of the corkscrew in the same direction the cork will begin to climb upwardly out of the bottle on the corkscrew.

The self-pulling climbing action of the cork is dependent upon the presence of greater frictional forces between the exterior of the cork and the bottle neck than between the corkscrew and the surface of the helical passage which it has formed through the cork. In the apparatus of GB-A-2027681 and DE-A-2929026, because of the relatively small diameter of the metal core of the corkscrew, this relationship is usually maintained at least until the cork has been raised a substantial distance out of the bottle neck, particularly where the corkscrew has the aforementioned friction-reducing coating taught in these references. However, as the ratio decreases, the cork will begin to turn slightly, albeit at a much slower rate than the corkscrew, as it rises. This subjects the cork to combined shear and tension forces which, on an extremely old or fragile cork, might cause damage. Furthermore, if, after the cork has been

raised a substantial distance, the frictional forces between the cork and the bottle neck decrease to less than or equal to those between the cork and the corkscrew, the cork will begin to rotate with the corkscrew and cease moving longitudinally. Should this occur with the apparatus as disclosed in said prior application, removal of the cork is completed by simply pulling upwardly on the holder to draw the lower portion of the cork from the bottle. Ordinarily, this does not require a great amount of force, unless the device is one which lacks a friction-reducing coating on the corkscrew. However, even so, it can be somewhat undesirable for the cork to be left in the bottle in that a novice operator of the apparatus simply may not realise that an upward pull on the apparatus is then necessary, but may instead continue to rotate the handle and corkscrew to no avail.

The present invention seeks to provide a solution to the problem of ensuring complete cork withdrawal in cork extracting apparatus of self-puller type. More particularly, in accordance with the present invention, catch means are provided adjacent the spacer means in the cork receiving opening and positioned in the path of travel of a cork as it rises with respect to the bottle. The corkscrew is adapted to draw corks upwardly to the catch means in self-puller fashion, and the catch means is engageable with the cork, as it is being thus drawn upwardly, to maintain relative rotation between the corkscrew and the cork, whereby the cork may be completely withdrawn from the bottle in this self-puller fashion. The length of the catch means is adapted to the length of the cork to ensure the desired complete cork withdrawal.

With the improved apparatus of the present invention, by the time the cork has emerged from the bottle neck a sufficient distance to substantially reduce the frictional forces therebetween, the catch means will have engaged the cork to prevent rotation thereof and thus permit the cork to continue moving threadedly upwardly on the corkscrew until it is completely removed from the bottle neck. Indeed, the catch means is so effective in preventing rotation of the cork that complete removal can be achieved in the manner described above even if the cork is slightly longer than the opening in the holder into which the cork moves as it emerges from the bottle. In such an instance, when the top of the cork reaches the top of said opening, the cork will compress longitudinally to allow its lower end to continue moving upwardly and out of the bottle.

The catch means define catch surfaces, preferably including sharp edges, which are embeddable in the cork as it emerges from the bottle to prevent rotation as explained above. In a preferred embodiment, the catch means project generally radially into the path of travel of the cork for engagement with its sides. These latter catch means may include at least two relatively sharp edges extending generally longitudinally along the sides of the cork-receiving opening. By proper selection of the length of such catch

(12)

means, it is possible to allow for engagement of even the shortest cork while still providing an opening long enough to accommodate even the longest cork without compression thereof. This has the advantage of minimizing damage to and distortion of the cork, in case it should be desired to reuse it.

A preferred embodiment of the apparatus of this invention provides a holder which includes guide means for receiving the corkscrew and permitting longitudinal and rotative movement thereof. This guide means is interconnected with the bottle-engaging means by the spacer means which serves to space the guide means upwardly from the bottle-engaging means. In this embodiment the corkscrew carries abutment means for limiting downward movement of the corkscrew with respect to the guide means to a lower position of the corkscrew.

Another improvement according to preferred embodiments of the present invention involves the bottle-engaging portion of the apparatus. As in the apparatus of the prior related applications GB-A-2027681 and DE-A-2929026, the holder preferably includes a pair of generally diametrically opposed and longitudinally extending legs. Shoulders are formed intermediate the ends of these legs for engaging the top of the bottle and thereby limiting downward movement of the holder on the bottle. The portion of the legs extending downwardly from these shoulders form a pair of gripping elements for engaging the neck of the bottle. The opposed, radially inner surfaces of these gripping elements are concave inwardly, and more specifically, define circular arcs when viewed in transverse cross section. In accord with the present invention, the centres of these arcs are offset radially outwardly from the longitudinal centerline of the apparatus. If the radius of these arcs corresponds generally to that of the drip ring of the smallest bottle with which the apparatus is expected to be used, this expedient provides for engagement of each gripping element with the grip ring of virtually any size bottle at least two points while still permitting the inclusion of a relatively large shoulder surface area for engagement with the top of the bottle. These factors in turn provide more stable seating of the holder on the bottle.

In another improvement according to specific embodiments of the invention, connection means join the corkscrew and the holder. The connection means is mounted for longitudinal but generally non-rotating movement on the holder, the corkscrew in turn being mounted in the connection means for rotative but generally non-longitudinal movement. In these embodiments, the connection means may include rails having longitudinal slots for receiving pins on the holder. In use, as the guide means move downwardly with the corkscrew as it is being driven into the cork, the rails move into the cork-receiving opening, and their side edges are positioned to serve as the longitudinally extending

edges of the catch surfaces. The edges of the slots in the rails may also serve this function.

In the preferred embodiments wherein the holder includes a pair of legs extending downwardly from the guide means, with the upper portions of the legs forming the spacer means and the lower portions of the legs forming the bottle gripping elements, emplacement of the holder on a very large necked bottle can cause substantial radial deflection not only of the gripping elements but also of the spacer means. Then, if the catch means are formed on the spacer means and project radially inwardly therefrom, such deflection might interfere with proper engagement of the cork by the catch means. This can also occur with bottles of an unusual shape, e.g. bottles having relatively short necks which flare outwardly quite near the top. To ensure effective operation of the catch means in such cases, and in accord with still another modification of the invention, each of the legs may have a longitudinal split extending upwardly from the shoulder which abuts the top of the bottle. The radially outer portion of the spacer elements can then be deflected radially outwardly from the inner portion adjacent such split while the radially inner portion of the leg above the shoulder remains in an undeflected position. Thus, the catch means which are carried on said radially inner portion remain in proper position to engage the cork when it has emerged the desired distance from the bottle neck.

Brief Description of the Drawings

Figure 1 is a longitudinal cross-sectional view of a first embodiment of cork-extracting apparatus in operating position on a bottle neck and with some parts being shown in elevation.

Figure 2 is a view similar to Fig. 1 showing the apparatus at a subsequent stage of the cork extracting process.

Figure 3 is a transverse cross-sectional view taken on the line 3—3 of Fig. 2.

Figure 4 is a transverse cross-sectional view taken along the line 4—4 in Fig. 1.

Figure 5 is a side elevational view taken along the line 5—5 in Fig. 2.

Figure 6 is a detailed sectional view through the corkscrew taken along the line 6—6 in Fig. 1.

Figure 7 is a view similar to that of Fig. 1 of a second embodiment of cork-extracting apparatus.

Figure 8 is a transverse cross-sectional view taken along the line 8—8 in Fig. 7.

Figure 9 is a view similar to that of Fig. 1 showing a third embodiment of cork-extracting apparatus.

Figure 10 is a transverse cross-sectional view taken along the line 10—10 in Fig. 9.

Figure 11 is a view similar to that of Fig. 9 showing the apparatus in a subsequent stage of the cork extracting process.

Figure 12 is a partial longitudinal view similar to those of Figs. 9 and 11 showing the cork

completely removed from the bottle neck.

Figure 13 is a view similar to that of Fig. 1 showing the fourth embodiment of cork-extracting apparatus.

Figure 14 is a transverse cross-sectional view taken along the line 14—14 in Fig. 13.

Figure 15 is a view similar to that of Figure 13 showing the apparatus in a subsequent stage of the cork extracting process.

Figure 16 is a transverse cross-sectional view taken along the line 16—16 in Fig. 15.

Description of the Preferred Embodiments

Figs. 1—6 illustrate a first embodiment of cork extracting apparatus according to the invention. The apparatus generally comprises two main portions, namely a holder and a cork-engaging member. The holder includes main body member 10 which, in the embodiment shown, is integrally molded from a suitable plastic. The main body member 10 includes a pair of diametrically opposed, circumferentially spaced apart, longitudinally extending flexible legs 12, each of which comprises an upper portion 12a and a lower portion 12b. The main body member 10 of the holder includes an annulus 14 interconnecting and extending upwardly from the upper ends of legs 12. Annulus 14 serves as the foundation portion of the guide means of the holder, said guide means further including a bushing member 16 rigidly mounted within annulus 14 in any suitable manner. Bushing member 16 is preferably formed of a friction-reducing material such as polytetrafluoroethylene and is in the form of a sleeve which extends longitudinally along the inner surface of annulus 14 and has an annular flange extending radially outwardly from the upper end and abutting the uppermost surface of annulus 14. It is noted that, as used herein, terms such as "upper", "lower", "upwardly", and "downwardly" refer to the apparatus as shown in the drawings and as it would be positioned for use on an upright bottle. Such terms are used for convenience, and should not be construed in a limiting sense. Also, terms such as "radial", "longitudinal", "circumferential", etc. are used with reference to the corkscrew when in place in the holder unless otherwise noted.

The other major portion of the cork-extracting apparatus is a cork-engaging member including a helical corkscrew 18 and a handle 20. The corkscrew 18 serves as the guide portion of the cork-engaging member and is removably receivable in bushing 16 of the guide means of the holder. Corkscrew 18 is longitudinally movable in the bore defined by surface 16a either with or without simultaneous rotation. The outer diameter of the helix of corkscrew 18 is sized to lie closely adjacent the cylindrical radially inwardly facing surface 16a of the bushing 16 of the guide means. Additionally, the length of cylindrical surface 16a is at least as long as, and preferably longer than, the pitch of the helix of corkscrew 18. Accordingly, surface 16a serves as the guide surface of the holder, defining a guide passageway for cork-

screw 18 and maintaining it in substantial coaxial alignment with the guide means 14, 16.

The handle 20 includes a lowermost annular hub 20a and a pair of diametrically opposed radially extending arms 20b. Hub 20a is sized and positioned to abut the upper surface of bushing 16 as corkscrew 18 moves downwardly therein to thereby limit downward movement of the cork-engaging member 18, 20 with respect to the holder 12, 14, 16.

To use the apparatus, the holder 12, 14, 16 is emplaced over the top of the bottle 22. Legs 12 have respective opposed radially inner surfaces, and each of the legs 12 has a downwardly facing shoulder 12c on its inner surface adjacent the juncture of the upper and lower portions 12a and 12b respectively of the leg. The shoulders 12c lie in a common plane transverse to the longitudinal axis of the holder. Thus, the shoulders 12c define stop means which abut the top of the bottle 22 and thereby limit downward movement of the holder with respect thereto. Accordingly, when the holder has been thus placed on the bottle 22, as shown in Fig. 1, the holder legs 12 are positioned with the upper portions 12a thereof extending upwardly from the top of the bottle 22. Upper leg portions 12a thus serve as spacer means spacing the guide means 14, 16 from lower leg portions 12b and from the top of the bottle. A cork-receiving opening 25 is formed between the upper portions 12a of the two holder legs for receiving the cork 24 as it emerges from bottle 22.

The lower portions 12b of holder legs 12 extend downwardly along the neck of bottle 22. These portions 12b serve as the gripping elements of the holder. Legs 12 are formed of a suitable lightweight material such as plastic, aluminum, or the like and have sufficient inherent flexibility and resiliency to permit gripping elements 12b to be flexed either inwardly or outwardly from the radially unflexed position shown in Fig. 1. Thus, the gripping elements 12b may be grasped and squeezed inwardly by the user with one hand to grip the neck of bottle 22 and firmly position the holder thereon. The apparatus as shown in Figs. 1 and 2 is sized to engage bottle 22 without substantial flexing of legs 12. However, the flexibility of holder legs 12 also permits the holder to accommodate bottles of large or smaller neck diameters. Gripping elements 12b, along with shoulders 12c form the bottle-engaging means of the apparatus.

Because holder legs 12 are formed of the same material, are substantially identical in size and configuration, and are symmetrically positioned with respect to annulus 14, there are substantially equally biased to the normal unflexed radial position shown in Fig. 1. Accordingly, when they are urged radially inwardly by the user, they tend to maintain the guide means 14, 16 in a position which is substantially centered with respect to the bottle 22 and its cork 24, even if the diameter of the drip ring 22a of the bottle neck differs from the distances between the adjacent portions of the

(14)

gripping elements 12b. Furthermore, such equal resilient biasing further helps to prevent canting of the holder on the bottle and thereby maintain the axis of the guide means 14, 16 substantially coaxially aligned with that of the bottle 22. However, the apparatus is provided with additional features for even more positive stabilizing of the holder on the bottle.

When the gripping elements are thus employed, they will engage and grip the bottle neck at least at the drip ring 22a. It is primarily the flexibility of the upper portions or spacer means 12a of the holder legs which permits radial flexing of gripping elements 12b to accommodate drip rings of differing sizes. However, gripping elements 12b are additionally flexible and resilient within themselves. Thus, depending upon the diameter of the bottle to be gripped and the length and degree of flexibility of gripping elements 12b, the lower ends of the gripping elements 12b may be fixed inwardly to further engage and grip the bottle neck at a second location spaced downwardly from drip ring 22a. It has been observed that the tapered necks of most wine bottles reach an outer diameter approximately equal to that of their drip rings at a location around 2 to 2.5 inches (about 5 to 6.5 cm) below the top of the bottle. The inner surfaces of gripping elements 12b have portions 12d which, when legs 12 are in their unflexed position as shown, lie straight with respect to the longitudinal axis of the apparatus. Accordingly, if surfaces 12d of the gripping elements 12b are about 2 to 2.5 inches (5.08 to 6.35 cm) long, the aforementioned double gripping action may be more readily achieved with a minimum of distortion of the gripping elements. Such gripping action in turn provides a high degree of stability to prevent wobbling of the holder on the bottle. In any event, it is desirable to make the gripping elements 12b at least long enough to enable the user to firmly grip the holder in an area primarily surrounding and aligned with the bottle neck, as opposed to an area located generally thereabove.

Even where the aforementioned double gripping is not possible, due to the size of the bottle and/or the length of gripping elements 12b, proper alignment of the guide means 14, 16 with the cork 24 can still be maintained by the combined action of engaging the upper edge of bottle 22 with shoulders 12c and gripping drip rings 22a with gripping elements 12b. Referring to Fig. 4, it can be seen that the opposed inner surfaces 12d of gripping elements of 12b, when viewed in transverse cross section, define circular arcs. However, the centers of the arcs, located at C1 and C2 respectively, are not coincident with the longitudinal centerline of the apparatus, but rather are offset radially outwardly therefrom. It can be seen that, if the radius of the arcs defined by surfaces 12d were relatively large, then in gripping a relatively small diameter drip ring, each of such surfaces would essentially have only point contact with the drip ring. Accordingly, it is preferable to choose an arc radius for surfaces

12d which generally corresponds to that of the drip ring of the smallest size bottle with which the apparatus is expected to be used. A radius of 1-3/16 inches (3.016 cm) has been found suitable for average use.

When the holder is placed on a relatively small bottle, in which the radius of curvature of the drip ring corresponds generally to that of the arcs defined by surfaces 12d, and the gripping elements 12b are urged radially inwardly to grip the bottle, surfaces 12d will engage the drip ring over substantially their full circumferential extent. This provides a high degree of stability of the holder on the bottle, particularly when coupled with the engagement of the bottle top with the substantially planar surfaces defined by shoulders 12c. If a larger bottle is engaged, the surfaces 12d, having a smaller radius than the bottle drip ring, will each engage that drip ring at at least two points, again providing greater stability than with an oversized arc. The offsetting of the centers of the arcs defined by surfaces 12d allows the use of the relatively smaller radius in those arcs, with the aforementioned advantages in holder stability, while avoiding both undue reduction in the surface area provided by shoulders 12c and the need to deflect legs 12b radially outwardly in order to grip an ordinary size bottle.

Referring to Figs. 1 and 2 together, the operation of the cork extractor is as follows. After the holder has been emplaced on the bottle as shown in Fig. 1 and described hereinabove, the corkscrew 18 is inserted in the bushing 16 so that its lower end abuts the top of the cork 24. The user grasps gripping elements 12b with one hand urging them radially inwardly and downwardly to grip the bottle neck. With the other hand, the user grasps the handle 20 and rotates the cork-engaging member 18, 20 clockwise as viewed from the top while simultaneously bearing downwardly on it to begin driving the corkscrew 18 into the cork. After the corkscrew 18 has started into the cork, it can be driven farther into and through the cork by continued rotation without the need to exert downward force.

The length of the corkscrew 18 is such that when hub 20a comes into engagement with the upper surface of bushing 16 thereby limiting further downward movement of the cork engaging member, the corkscrew 18 ordinarily will have been driven through the lower end of cork 24. With a larger cork, the screw may not pass through the lower end of the cork when the cork-engaging member ceases its downward movement. However, it will, in any event, have penetrated a substantial portion of the length of the cork. The user then continues to rotate the cork-engaging member 18, 20 in the same direction. Since the abutment of hub 20a with bushing 16 prevents further downward movement of the cork-engaging member, such rotation will cause cork 24 to climb upwardly on the corkscrew 18 in self-puller fashion.

The climbing movement of cork 24 as described

(13)

above is possible due to the presence of greater frictional forces between the exterior of cork 24 and the interior of the neck of bottle 22 than those between corkscrew 18 and cork 24. In order to facilitate the driving of corkscrew 18 into cork 24, and also to ensure low enough frictional forces therebetween to permit a substantial climbing of the cork, corkscrew 18 is comprised of a wire or central body 19 coated with a layer 27 of friction-reducing material, as shown in Fig. 6. The friction-reducing material of layer 27 may comprise polytetrafluoroethylene or any other suitable material bonded to central body 19 by techniques known in the art. As used herein, the term "friction-reducing" will be construed to cover any material which reduces the friction between the corkscrew and the cork to a significantly greater degree than could be achieved by merely polishing the central body. Although polytetrafluoroethylene, and similar plastics, produce particularly striking results, other materials such as silicone coatings could also be used.

The coating 27 sufficiently reduces the friction between corkscrew 18 and cork 24 that it will remain less than that between the cork and bottle neck until the cork has been raised almost completely out of the bottle neck, e.g. to at least about the position shown in Fig. 2. However, as the cork rises, thereby decreasing the amount of contact area between the cork and the bottle neck and therefore the relative friction between those surfaces as compared to that between the cork and the corkscrew, the cork will, in the absence of preventative measures, begin to rotate slightly. However, as long as the friction between the cork and bottle neck remains significantly greater than that between the cork and corkscrew, such rotation of the cork will be at a relatively slower rate than that of the corkscrew, and the cork will continue to rise. This rotation is not ordinarily a problem with the construction disclosed. However, in the case of an extremely old, fragile, and/or damaged cork, which is placed under combined shear and tension loads by the aforementioned movements, some breakage or the like could occur.

Furthermore, when a cork has risen to about the position shown in Fig. 2, if the amount of surface area of cork 24 in contact with the bottle neck is reduced so that the friction between the cork and corkscrew begins to exceed that between the cork and the bottle neck, the cork would, in the absence of the catch means to be described below, simply begin rotating in the bottle neck along with the corkscrew and cease moving longitudinally. The amount of cork remaining in the bottle neck at that point would be so small that removal could be completed by simply lifting up on holder 10 with relatively little effort. However, this simple expedient may not be readily apparent to all users. In any event, it does slightly complicate what would otherwise be an essentially one step process whereby the cork could be completely removed by continued rotation of handle 20 in the same direction.

Accordingly, the present invention provides catch means on holder 10 in the cork-receiving opening 25 for engaging the cork as it emerges from the bottle neck and preventing rotation thereof. In the embodiment of Figs. 1—6, the catch means are in the form of a pair of projections 26 each integrally formed on the radially inner surface of a respective one of the spacer elements 12a. The distance between spacer elements 12a is approximately equal to the outer diameter of a standard wine cork. Thus, insofar as they project radially inwardly from spacer elements 12a into the cork-receiving opening 25, projections 26 extend into the path of travel of cork 24 as it emerges from bottle 22. Projections 26 extend longitudinally along the upper portion of opening 15. Because the projections 26 extend longitudinally along opening 25, they can, if sufficiently long, engage the shortest of corks even though the length of opening 25 is sufficient to accommodate the longest corks. Furthermore, sufficiently long catch means can engage a cork soon enough in the extraction process to prevent any substantial rotation thereof and thereby prevent damage to a fragile cork. With a cork-receiving opening 25 of about 2 inches (5.08 cm) in length projections 26 extending downwardly to about 1.25 inch (3.18 cm) from the bottom of opening 25, i.e. from shoulders 12c have been found acceptable.

As best seen in Fig. 3, projections 26 form a pair of diametrically opposed sharp edges extending longitudinally along opening 25 for embedment into cork 24. Each projection 26 is symmetrical about a radius of the apparatus. Thus, projections 26 tend to resist rotation of cork 24 in both clockwise and counterclockwise directions, as viewed in Fig. 3.

Accordingly, when cork 24 has emerged a substantial distance from the neck of bottle 22, as shown in Fig. 2, its upper end will be engaged by catch means 26. This prevents rotation of cork 24 so that, when it emerges to the point where its frictional engagement with bottle 22 provides insufficient resistance to rotation of the cork, the catch means will take over this function permitting the cork to continue to climb upwardly on corkscrew 18 in self-puller fashion as described above until it is completely removed from bottle 22.

The extractor apparatus can then be used to assist in removal of cork 24 from the corkscrew 18. By grasping the holders legs 12 and urging them radially inwardly, the user can grip the cork 24 with projections 26. He can then rotate handle 20 in a direction opposite to that used to initially drive the corkscrew 18 into cork 24 while continuing to urge handle 20 against holder 10. Since projections 26 will prevent cork 24 from rotating with the corkscrew, this will cause cork 24 to move downwardly on the corkscrew to partially eject it therefrom. The cork can then simply be gripped by the user's fingers through the space between legs 12, the corkscrew unthreaded therefrom, and the cork removed from the holder.

(16)

From the foregoing it can be seen that the apparatus of Figs. 1—6 provides a relatively simple and economical means by which a user can easily and accurately guide the corkscrew into the cork in a centered and coaxially aligned orientation. The holder of the apparatus permits the user to get a firm grip on the bottle while maintaining the guide means steadily aligned with the cork. The guide means in turn properly directs the corkscrew by guiding it via the outside diameter of its own helix. Furthermore, it can be seen that the apparatus substantially reduces the force which must be exerted in extracting the cork from the bottle.

The fact that the cork-engaging member 18, 20 is removable from the holder results in additional advantages. Not only does this removability permit the cork-engaging member to be used as an ordinary corkscrew, if and when desired, but also allows the sharp end portion thereof to be used to sever the foil covering the top of the bottle before removal of the cork. Furthermore, the separability of the two major portions of the apparatus permits both portions to be more easily cleaned and permits one cork-engaging member 18, 20 to be used alternatively with different holders.

The friction-reducing coating 27 has been found to dramatically increase the ease with which the corkscrew may be driven into a cork as well as the ease with which the cork is pulled from the bottle. Indeed, the reduction in friction is so great as to permit the use, in central body 19, of design features and parameters which would not be practicable without layer 27. For example, the wire of which body 19 is formed may be thinner than in conventional screws, and a wider range of helix leads is available. Such design features in turn may even further enhance the ease of operation. Thus, for example, the use of layer 27, especially in cooperation with other friction-reducing features made possible thereby, substantially ensures the capability of removing even a cork which is relatively hard and/or tightly engaged in the bottle neck, and even though the central body 19 of the corkscrew might be so flexible that it would, in the absence of layer 27, be unwound or otherwise distorted in an attempt to drive it into the cork.

Figs. 7 and 8 show a second embodiment of the invention. It can be seen that, if the holder 10 of Figs. 1—6 were emplaced on a bottle having an extremely wide neck or an irregularly shaped neck which began to flare outwardly a much shorter distance from the top of the bottle than in most cases, the legs 12, being integral, might be flexed radially outwardly so far as to separate the projections 26 and interfere with their proper engagement with the emerging cork, particularly if the cork were relatively short. Because such wide neck bottles are relatively rare, and because the embodiment of Figs. 1—6 provides a simple, and therefore attractive and relatively inexpensive holder usable with most wine bottles, this embodiment is generally suitable for most consumer use. However, for those who may have a

significant number of occasions to open relatively wide neck bottles, the embodiment of Figs. 7 and 8 provides for engagement of such bottles without separation of the two projections which form the catch means.

The cork extractor of Figs. 7 and 8 includes a cork-engaging member comprising a corkscrew 28 and an attached handle 30 substantially identical to those of the first embodiment. This extractor further comprises a holder generally designated by the number 32. Holder 32 is substantially identical to holder 10 in general external configuration. However, holder 32 differs from holder 10 in that its guide means is formed by the generally tubular upper portion 34 of the plastic main body of the holder without a separate bushing such as 16 in the first embodiment. Rather, the aperture 36 through portion 34 is sized to slidably receive corkscrew 28 and define the guide surface for aligning the corkscrew with the cork while allowing rotation and longitudinal movement of the corkscrew in the guide means.

Holder 32 also has a pair of diametrically opposed legs 38 integral with and extending downwardly from tubular portion 34. Legs 38 have upper portions 38a and lower portions 38b with inner, downwardly facing shoulders 38c located at the juncture of portions 38a and 38b. Shoulders 38c serve as stop means for abutting the top of a bottle such as 40 whereby portions 38a thereabove serve as spacer means for spacing the guide means 34 from the upper end of the bottle. Lower portions 38b extend downwardly along the neck of bottle 40 and are radially deflectable whereby they serve as gripping elements for gripping the bottle neck. The upper portions or spacer means 38a of legs 38 define a cork-receiving opening 42 therebetween. A pair of opposed radial projections 44 are integrally carried by and extend longitudinally along the upper portions of spacer elements 38a whereby they project into the path of travel of cork 46 as it emerges from the bottle. Projections 44 differ from projections 26 of the first embodiment in that they are not symmetrical about radii of the apparatus. Rather, each projection 44 has a sharp edge 44a extending generally longitudinally and is formed by a first surface 44b, which lies generally in a radial plane with respect to cork 46, and a second surface 44c, which intersects surface 44b at edge 44a and is inclined circumferentially and radially outwardly therefrom. Surfaces 44b face in diametrically opposite directions. Thus, projections 44 tend to resist rotation of cork 46 in a clockwise direction, as viewed from the top, more so than in a counterclockwise direction. This configuration, unlike that of projections 26 of the first embodiment, is not intended to provide substantial assistance in ejecting the cork, once it has been removed from the bottle, from the apparatus. However, the configuration of projection 44 offers less impedance to ordinary manual disengagement of the cork from the apparatus.

Legs 38 differ from legs 12 of the first embodiment in that they have splits 38d extending

(17)

longitudinally upwardly from the radially outer extremities of respective shoulders 38c to a point intermediate the ends of spacer elements 38a. Thus, the portions of spacer elements 38a located radially outwardly of splits 38d are continuous with gripping elements 38b and may be deflected radially outwardly as shown in Fig. 7 to grip a large bottle neck without spreading the radially inner portions of spacer elements 38a on which shoulders 38c and catch means 44 are formed. Thus, a large bottle such as 40 can be properly gripped while the catch means 44 remain entirely disposed within the path of travel of the emerging cork 46.

Figs. 9—12 illustrate a third embodiment of the invention. This embodiment includes a cork-engaging member including a corkscrew 48 and a handle 50 rigidly affixed thereto. The holder 52 is formed of a single piece of molded plastic and includes an upper tubular guide portion 54 having a central cylindrical aperture 56 sized to slidably receive corkscrew 48. A pair of diametrically opposed legs 58 extend downwardly from the guide portion 54. Each leg 58 has an upper portion or spacer element 58a for spacing the guide portion upwardly from the top of a bottle 60. Each leg 58 further includes a lower portion 58b which extends downwardly along the sides of the bottle neck to form a gripping element. Each leg 58 has a downwardly facing shoulder 58c on its inner side at the juncture between the upper and lower portions 58a and 58b respectively to serve as a stop means for abutting the top of bottle 60. Upper portions or spacer elements 58a define a cork-receiving opening 62 therebetween. Since legs 58 are substantially identical to legs 12 of the embodiment of Figs. 1—6, except for the catch means carried thereby, they will not be described in further detail.

The upper corners of cork-receiving opening 62, defined generally at the juncture between legs 58 and guide portion 54 of the holder, are curved as shown. A pair of recesses or pockets 66 are formed at those corners. Pockets 66 have sharp edges 68 to serve as the catch means of the extractor. While the edges 68 extend somewhat radially into the path of the cork 70 as it emerges from the bottle 60, their longitudinal extent along opening 62 is not very great. However, they do also project generally downwardly into the path of the emerging cork for engagement with its upper end.

The operation of the extractor of Figs. 9—12 is similar to that of the other embodiments described above. Fig. 9 shows the extractor as the corkscrew 48 is just starting into cork 70. Fig. 11 shows the extractor after the corkscrew 48 has been driven downwardly to its full extent and the cork 70 has begun to rise on corkscrew 48. Because of the limited longitudinal extent of catch means 68, whereby their primary engagement is with the end — rather than the sides — of cork 70, the length of opening 62 should be chosen so that even a relatively short cork will have engaged catch means 68 before the frictional resistance to

rotation of the cork by the bottle has become insufficient to permit continued climbing action of the cork on the corkscrew 48. Nevertheless, the use of such a short opening will not preclude complete removal of longer corks. This is because, after the upper end of such a long cork has reached the upper extremities of opening 62 and been forced into recesses 66, the resistance to rotation of the cork will be great enough to permit the lower end to continue climbing on the corkscrew 48. The cork will compress longitudinally during such movement, said compression in turn being permitted by the spaces between upper leg portions 58a which allow the cork to expand laterally. By comparing Figs. 11 and 12, it can be seen that a cork longer than window 62 has been compressed into the opening 62 and completely removed from the neck of bottle 60. The same principles can be applied to other types of catch means such as small pointed prongs or the like which might extend downwardly from the guide means of the holder into the cork-receiving opening. Such catch means, again due to their limited longitudinal extent, may not completely prevent rotation of the cork as it rises, but will enable it to be completely extracted by rotation of handle 50.

Referring finally to Figs. 13—16, a fourth embodiment of the invention is illustrated. In this embodiment, the cork-engaging member is not separable from the holder. Rather, connection means are provided interconnecting the cork-engaging member and the holder. More specifically, the cork-engaging member includes the corkscrew 72 and a carrier 74 rigidly affixed to the upper end of corkscrew 72. Carrier 74 is generally cylindrical but has a radially outwardly extending annular flange 74a at its lower end. The cork-engaging member further includes a handle 76 having arms 76a and 76b and a central hub portion 76c. Handle 76 has a central aperture in which the upper portion of carrier 74 is rigidly affixed, as by a suitable adhesive, with flange 74a spaced downwardly from the lower end of hub 76c. The connection means, generally indicated at 78 includes an uppermost annular portion 78a. The opening through annular portion 78a is sized to rotatably receive carrier 74. The upper cylindrical portion of carrier 74 is placed through the aperture of annulus 78a prior to fixing of carrier 74 to handle 76. The space between hub 76c and flange 74a is only slightly greater than the thickness of annulus 78a. Thus, the cork-engaging member 72, 74, 76 is mounted in connection means 78 for rotative but generally non-longitudinal movement.

Connection means 78 further includes a pair of diametrically opposed rails 78b extending downwardly from annular portion 78a. As shown in Figs. 14 and 16, rails 78b are arcuate, concave inwardly, in transverse cross section. These rails are spaced apart by a distance slightly less than the diameter of a standard cork.

The apparatus further comprises a holder 80 including a tubular upper portion 82 and a pair of

diametrically opposed legs 84 extending downwardly therefrom. The legs 84 have upper portions 84a and lower portions 84b with inwardly extending flanges 84c being formed at the juncture between upper and lower portions 84a and 84b respectively. Flanges 84c define downwardly facing shoulders 84d serving as stop means to abut the upper end of a bottle 86. Thus, the upper leg portions 84a may serve as spacer elements for spacing tubular portion 82 of holder 80 upwardly from the top of bottle 86, while lower leg portions 84b may serve as gripping elements extending downwardly along the sides of the bottle neck.

Upper leg portions or spacer elements 84a define an opening 88 therebetween. This opening is wider than the corresponding cork-receiving openings of the preceding embodiments so as to permit rails 78b to move downwardly into the opening 88 in use while still allowing sufficient space for upward movement of cork 90. Flanges 84c are also spaced apart by a distance sufficient to allow cork 90 to pass therebetween.

A generally tubular guide member 92 is rigidly fixed within tubular portion 82 as by a suitable adhesive. By comparison of Figs. 13 and 14, it can be seen that guide member 92 has a pair of longitudinally extending, diametrically opposed, external recesses 94. When guide member 92 is affixed to tubular portion 92, recesses 94 cooperate with the inner diameter of tubular portion 92 to define longitudinal passageways for receipt of rails 78b. Thus, the connection means 78 is mounted for longitudinal but generally non-rotative movement on holder 80. To further guide and stabilize connection means 78 in such movement, each rail 78b has a longitudinal slot 96. Guide member 92 carries a pair of pins 98 extending radially outwardly in recesses 94 for sliding receipt in respective slots 96.

In use, the handle 76 is pulled upwardly to raise the interconnected cork-engaging member 72, 74, 76 and connection means 78 to their uppermost position with respect to holder 80, and the holder is emplaced on bottle 86 with shoulders 84d abutting the top of the bottle as shown in Fig. 13. The user then squeezes inwardly on gripping elements 84b to grip the bottle neck while rotating handle 76 and exerting a slight downward force thereon. Once the point of corkscrew 72 has begun to penetrate cork 90, the downward force may be discontinued and handle 76 is simply rotated. This will drive the corkscrew 72 into and through cork 90. As the corkscrew moves downwardly, the attached connection means 78 will also move downwardly, rails 78b moving into opening 88 until their lower ends abut the upwardly facing shoulders 84c defined by flanges 84c. The rotative mounting of the cork-engaging member in the connection means 78, with the latter in turn being mounted for longitudinal movement on the holder, could suffice to guide and center the corkscrew 72 with respect to cork 90. However, further guidance and stability is provided by the cylindrical

passageway 93 in guide member 92 which slidably receives corkscrew 72 for longitudinal and rotative movement.

After the cork-engaging member and connection means have reached their lowermost position on holder 80, continued rotation of handle 76 will cause cork 90 to climb upwardly on corkscrew 72 as shown in Fig. 15. As previously mentioned, the distance between rails 78b of the connection means, which by this time is disposed well within opening 88, is slightly less than the outer diameter of the cork 90. Thus, as shown Fig. 16, the longitudinally extending lateral edges 100 of rails 78b, along with the longitudinally extending edges 102 of slots 96, serve as the catch means which embed themselves into cork 90 to prevent rotation thereof. Accordingly, even when the cork has been raised a distance such that the bottle neck 86 no longer offers sufficient frictional resistance to rotation of the cork, such rotation will be prevented by the edges 100 and 102 so that the cork can be completely removed from bottle 86.

Because rails 78b and their edges 100 and 102 prevent rotation of cork 90 in both clockwise and counterclockwise directions, the apparatus shown in Figs. 13—16 can be used to eject cork 90 from such apparatus after the cork has been removed from the bottle. This is accomplished by rotating handle 76 in the opposite direction from that which was used to extract the cork while urging handle 76 downwardly with respect to holder 80. Since longitudinal movement of corkscrew 72 will be prevented by pushing downwardly on handle 76, and rotation of cork 90 will be prevented by catch means 100 and 102, the cork 90 will then be caused to move downwardly on corkscrew 72 with a threading action. Once the cork has moved downwardly to area between gripping elements 84b, it can readily be grasped by the user and removal completed either by rotating the cork itself or rotating the handle 76 while pulling upwardly thereon.

Claims

1. Apparatus of the self-puller type for extracting a cork from a bottle comprising:

a corkscrew (18, 28, 48, 72);

a holder (10, 32, 52, 80) engaging said corkscrew (18, 28, 48, 72), and permitting rotation of said corkscrew (18, 28, 48, 72) relative to said holder (10, 32, 52, 80) and restricting downward movement of said corkscrew (18, 28, 48, 72) relative to said holder (10, 32, 52, 80), said holder (10, 32, 52, 80) comprising —

bottle-engaging means (12b, 12c, 38b, 38c, 58b, 58c, 84b, 84d) for positioning said holder (10, 32, 52, 80) and the engaged corkscrew (18, 28, 48, 72) in generally coaxial alignment with the neck of said bottle, said bottle-engaging means (12b, 12c, 38b, 38c, 58b, 58c, 84b, 84d) including stop means (12c, 38c, 58c, 84d) for limiting downward movement of said holder (10, 32, 52, 80) with respect to said bottle; and

18

diametrically opposed legs 84 extending downwardly therefrom. The legs 84 have upper portions 84a and lower portions 84b with inwardly extending flanges 84c being formed at the juncture between upper and lower portions 84a and 84b respectively. Flanges 84c define downwardly facing shoulders 84d serving as stop means to abut the upper end of a bottle 86. Thus, the upper leg portions 84a may serve as spacer elements for spacing tubular portion 82 of holder 80 upwardly from the top of bottle 86, while lower leg portions 84b may serve as gripping elements extending downwardly along the sides of the bottle neck.

Upper leg portions or spacer elements 84a define an opening 88 therebetween. This opening is wider than the corresponding cork-receiving openings of the preceding embodiments so as to permit rails 78b to move downwardly into the opening 88 in use while still allowing sufficient space for upward movement of cork 90. Flanges 84c are also spaced apart by a distance sufficient to allow cork 90 to pass therebetween.

A generally tubular guide member 92 is rigidly fixed within tubular portion 82 as by a suitable adhesive. By comparison of Figs. 13 and 14, it can be seen that guide member 92 has a pair of longitudinally extending, diametrically opposed, external recesses 94. When guide member 92 is affixed to tubular portion 92, recesses 94 cooperate with the inner diameter of tubular portion 92 to define longitudinal passageways for receipt of rails 78b. Thus, the connection means 78 is mounted for longitudinal but generally non-rotative movement on holder 80. To further guide and stabilize connection means 78 in such movement, each rail 78b has a longitudinal slot 96. Guide member 92 carries a pair of pins 98 extending radially outwardly in recesses 94 for sliding receipt in respective slots 96.

In use, the handle 76 is pulled upwardly to raise the interconnected cork-engaging member 72, 74, 76 and connection means 78 to their uppermost position with respect to holder 80, and the holder is emplaced on bottle 86 with shoulders 84d abutting the top of the bottle as shown in Fig. 13. The user then squeezes inwardly on gripping elements 84b to grip the bottle neck while rotating handle 76 and exerting a slight downward force thereon. Once the point of corkscrew 72 has begun to penetrate cork 90, the downward force may be discontinued and handle 76 is simply rotated. This will drive the corkscrew 72 into and through cork 90. As the corkscrew moves downwardly, the attached connection means 78 will also move downwardly, rails 78b moving into opening 88 until their lower ends abut the upwardly facing shoulders 84c defined by flanges 84c. The rotative mounting of the cork-engaging member in the connection means 78, with the latter in turn being mounted for longitudinal movement on the holder, could suffice to guide and center the corkscrew 72 with respect to cork 90. However, further guidance and stability is provided by the cylindrical

passageway 93 in guide member 92 which slidably receives corkscrew 72 for longitudinal and rotative movement.

After the cork-engaging member and connection means have reached their lowermost position on holder 80, continued rotation of handle 76 will cause cork 90 to climb upwardly on corkscrew 72 as shown in Fig. 15. As previously mentioned, the distance between rails 78b of the connection means, which by this time is disposed well within opening 88, is slightly less than the outer diameter of the cork 90. Thus, as shown Fig. 16, the longitudinally extending lateral edges 100 of rails 78b, along with the longitudinally extending edges 102 of slots 96, serve as the catch means which embed themselves into cork 90 to prevent rotation thereof. Accordingly, even when the cork has been raised a distance such that the bottle neck 86 no longer offers sufficient frictional resistance to rotation of the cork, such rotation will be prevented by the edges 100 and 102 so that the cork can be completely removed from bottle 86.

Because rails 78b and their edges 100 and 102 prevent rotation of cork 90 in both clockwise and counterclockwise directions, the apparatus shown in Figs. 13—16 can be used to eject cork 90 from such apparatus after the cork has been removed from the bottle. This is accomplished by rotating handle 76 in the opposite direction from that which was used to extract the cork while urging handle 76 downwardly with respect to holder 80. Since longitudinal movement of corkscrew 72 will be prevented by pushing downwardly on handle 76, and rotation of cork 90 will be prevented by catch means 100 and 102, the cork 90 will then be caused to move downwardly on corkscrew 72 with a threading action. Once the cork has moved downwardly to area between gripping elements 84b, it can readily be grasped by the user and removal completed either by rotating the cork itself or rotating the handle 76 while pulling upwardly thereon.

Claims

1. Apparatus of the self-puller type for extracting a cork from a bottle comprising:

a corkscrew (18, 28, 48, 72);

a holder (10, 32, 52, 80) engaging said corkscrew (18, 28, 48, 72), and permitting rotation of said corkscrew (18, 28, 48, 72) relative to said holder (10, 32, 52, 80) and restricting downward movement of said corkscrew (18, 28, 48, 72) relative to said holder (10, 32, 52, 80), said holder (10, 32, 52, 80) comprising —

bottle-engaging means (12b, 12c, 38b, 38c, 58b, 58c, 84b, 84d) for positioning said holder (10, 32, 52, 80) and the engaged corkscrew (18, 28, 48, 72) in generally coaxial alignment with the neck of said bottle, said bottle-engaging means (12b, 12c, 38b, 38c, 58b, 58c, 84b, 84d) including stop means (12c, 38c, 58c, 84d) for limiting downward movement of said holder (10, 32, 52, 80) with respect to said bottle; and



(19)

spacer means (12a, 38a, 58a, 84a) defining an opening (25, 42, 62, 88) for receipt of said cork as it emerges from said bottle;

said corkscrew (18, 28, 48, 72) being of a length such that it may extend into said cork-receiving opening (25, 42, 62, 88) whereby said cork may move in self-puller fashion threadedly upwardly on said corkscrew (18, 28, 48, 72) as said corkscrew (18, 28, 48, 72) is rotated to draw said cork upwardly with respect to said bottle; characterized in that:

there are catch means (26, 44, 68, 100, 102) adjacent said spacer means (12a, 38a, 58a, 84a) in said opening (25, 42, 62, 88) and positioned in the path of travel of said cork as it rises with respect to said bottle;

said corkscrew (18, 28, 48, 72) is adapted to so draw corks upwardly to said catch means (26, 44, 68, 100, 102) in said self-puller fashion;

and said catch means (26, 44, 68, 100, 102) is engageable with said cork, as it is being thus drawn upwardly in said self-puller fashion, to maintain relative rotation between said corkscrew (18, 28, 48, 72) and said cork, whereby said cork may be completely withdrawn from said bottle in said self-puller fashion, the length of said catch means being adapted to the length of said cork.

2. The apparatus of Claim 1, characterized in that said catch means (26, 44, 68, 100, 102) define surfaces embeddable in said cork.

3. The apparatus of Claim 2, characterized in that said catch means (26, 44, 68, 100, 102) project generally radially into the path of travel of said cork for engagement with the sides of said cork.

4. The apparatus of Claim 3, characterized in that said catch surfaces include at least two relatively sharp edges extending generally longitudinally along the sides of said opening (25, 42, 88).

5. The apparatus of Claim 4, characterized in that said catch means (26, 44) comprise two flanges (26, 44) projecting generally radially inwardly from said spacer means (12a, 38a) and terminating in said sharp edges.

6. The apparatus of any preceding claim, characterized in that said corkscrew (18, 28, 48, 72) comprises a central body (19), and an outer layer (27) of friction-reducing material.

7. The apparatus of Claim 6, characterized in that said friction-reducing material is polymeric.

8. The apparatus of Claim 6 or Claim 7 when appendant to Claim 4, characterized in that said edges extend along the upper portion of said opening (25, 42) and terminate a substantial distance from the lower extremity of said opening (25, 42, 88).

9. The apparatus of Claim 6 or Claim 7 when appendant to Claim 2, characterized in that said catch means (68) project longitudinally downwardly into the path of travel of said cork for engagement with the upper end of said cork.

10. The apparatus of any preceding claim, characterized in that said holder (10, 32, 52, 80) further comprises guide means (14, 16, 34, 54, 72) for such relative rotation and also for relative

longitudinal movement between said corkscrew (18, 28, 48, 72) and said holder (10, 32, 52, 80), said spacer means (12a, 38a, 58a, 84a) interconnects said guide means (14, 16, 34, 54, 92) and said bottle-engaging means (12b, 12c, 38b, 38c, 58b, 58c, 84b, 84d) and spaces said guide means (14, 16, 34, 54, 92) upwardly from said bottle-engaging means (12b, 12c, 38b, 38c, 58b, 58c, 84b, 84d), and said apparatus further comprises abutment means (20a, 30, 50, 78a) carried by said corkscrew (18, 28, 48, 72) and engageable with said holder (10, 32, 52, 80) for limiting downward movement of said corkscrew (18, 28, 48, 72) with respect to said guide means (14, 16, 34, 54, 92) to a lower position in which said corkscrew (18, 28, 48, 72) so extends into said cork-receiving opening (25, 42, 62, 88).

11. The apparatus of Claim 10, characterized in that said apparatus includes a plurality of legs (12, 38, 58, 84) extending downwardly from said guide means (14, 16, 34, 54, 92), the upper portions (12a, 38a, 58a, 84a) of said legs (12, 38, 58, 84) comprising said spacer means (12a, 38a, 58a, 84a), and the lower portions (12b, 12c, 38b, 38c, 58b, 58c, 84b, 84d) of said legs (12, 38, 58, 84) comprising said bottle-engaging means (12b, 12c, 38b, 38c, 58b, 58c, 84b, 84d).

12. The apparatus of Claim 11, characterized in that said stop means (12c, 38c, 58c, 84d) comprise downwardly facing shoulders (12c, 38c, 58c, 84d) formed on the radially inner surfaces of said legs (12, 38, 58, 84) adjacent the lower extremity of said spacer means (12a, 38a, 58a, 84a), the portions of said legs (12, 38, 58, 84) below said shoulders (12c, 38c, 58c, 84d) comprising radially deflectable gripping elements (12b, 38b, 58b, 84b) for engagement with the outer side surface of the neck of said bottle.

13. The apparatus of Claim 12, characterized in that the radially inner surfaces (12d) of said gripping elements (12b), in transverse cross section, define respective circular arcs, the respective centers (C1, C2) of said arcs being offset radially outwardly from the longitudinal centerline of said apparatus.

14. The apparatus of Claim 13, characterized in that said radially inner surfaces (12d) of said gripping elements (12b) are, in an unflexed position, disposed generally straight with respect to the longitudinal centerline of said apparatus along at least a major portion of their lengths.

15. The apparatus of Claim 12, characterized in that each of said legs (38) has a longitudinal split (38d) extending upwardly from said shoulder (38c), the radially outer portion of said leg (38) being separable from the radially inner portion of said leg (38) adjacent said split (38d).

16. The apparatus of Claim 11, characterized in that said apparatus includes a pair of legs (12, 38, 58, 84) extending downwardly from said guide means (14, 16, 34, 54, 92), said stop means (12c, 38c, 58c, 84d) comprising downwardly facing shoulders (12c, 38c, 58c, 84d) formed on the radially inner surfaces of said legs (12, 38, 48, 84), portions (12a, 38a, 58a, 84a) of said legs (12, 38,



58, 84) above said shoulders (12c, 38c, 58c, 84d) comprising said spacer means (12a, 38a, 58a, 84b) and portions (12b, 38b, 58b, 84b) of said legs (12, 38, 58, 84) below said shoulders (12c, 38c, 58c, 84d) comprising radially deflectable gripping elements (12b, 38b, 58b, 84b) for engagement with the outer side surface of the neck of said bottle, and said gripping elements (12b, 38b, 58b, 84b) having opposed radially inner surfaces (12d) which, when said gripping elements (12b, 38b, 58b, 84b) are in an unflexed position, are disposed generally straight with respect to the longitudinal centerline of said apparatus along at least a major portion of their lengths.

17. The apparatus of Claim 3 or of Claim 6 or Claim 7 when appendant to Claim 3, characterized in that the apparatus comprises connection means (78) interconnecting said corkscrew (72) and said holder (80), said connection means (78) being mounted for longitudinal but generally non-rotative movement on said holder (80) and said corkscrew (72) being mounted for rotative but generally non-longitudinal movement in said connection means (78).

18. The apparatus of Claim 17, characterized in that said connection means (78) includes a generally tubular portion (78a) having said corkscrew (72) rotatably mounted therein and rail means (78b) extending downwardly from said tubular portion (78a), said rail means (78b) and said holder (80) of said apparatus having interengaging formations (44, 78b, 96, 98) connecting said rail means (78b) and said holder (80) for relative longitudinal movement, said rail means (78b) being so longitudinally movable into said opening (88) and having longitudinally extending edges (100), said catch means (100, 102) comprising said lateral edges (100).

19. The apparatus of Claim 18, characterized in that said interengaging formations (44, 78b, 96, 98) comprise longitudinal slots (96) in said rail means (78b) and pint (98) fixedly mounted on said holder (80) and extending into said slots (96), said catch means (100, 102) further comprising longitudinally extending edges (102) of said slots (100).

Patentansprüche

1. Vorrichtung vom Selbstziehertyp zum Herausziehen eines Korkens aus einer Flasche, mit:

einer Korkenzieherwendel (18, 28, 48, 72);

einem Halter (10, 32, 52, 80), der mit der Wendel (18, 28, 48, 72) in Eingriff steht und eine Drehung der Wendel (18, 28, 48, 72) im Verhältnis zu dem Halter (10, 32, 52, 80) erlaubt und eine abwärtsgerichtete Bewegung der Wendel (18, 28, 48, 72) im Verhältnis zu dem Halter (10, 32, 52, 80) begrenzt, wobei der Halter (10, 32, 52, 80) aufweist —

eine Flaschenangriffseinrichtung (12b, 12c, 38b, 38c, 58b, 58c, 84b, 84d) zum Positionieren des Halters (10, 32, 52, 80) und der im Eingriff befindlichen Korkenzieherwendel (18, 28, 48, 72) in im wesentlichen koaxialer Ausrichtung mit dem Flaschenhals, wobei die Flaschenangriffseinrich-

tung (12b, 12c, 38b, 38c, 58b, 58c, 84b, 84d) einen Anschlag (12c, 38c, 58c, 84d) zum Begrenzen der nach unten gerichteten Bewegung des Halters (10, 32, 52, 80) im Verhältnis zur Fläche einschließt; und

einen Abstandshalter (12a, 38a, 58a, 84a), der eine Öffnung (25, 42, 62, 88) zur Aufnahme des Korkens definiert, wenn dieser aus der Flasche heraustritt;

wobei die Korkenzieherwendel (18, 28, 48, 72) eine solche Länge besitzt, daß sie in die zur Aufnahme des Korkens vorgesehene Öffnung (25, 42, 62, 88) hineinragen kann, wodurch der Korken wie bei einem Selbstzieher auf der Korkenzieherwendel (18, 28, 48, 72) nach oben geschraubt werden kann indem die Wendel (18, 28, 48, 72) gedreht wird, um den Korken im Verhältnis zu der Flasche nach oben zu ziehen; dadurch gekennzeichnet,

daß Fangeinrichtungen (26, 44, 68, 100, 102) neben dem Abstandshalter (12a, 38a, 58a, 84a) in der Öffnung (25, 42, 62, 88) vorgesehen und in der Bewegungsbahn des Korkens angeordnet sind, wenn dieser relativ zur Flasche aufsteigt;

daß die Korkenzieherwendel (18, 28, 48, 72) dazu eingerichtet ist, Korken nach Art eines Selbstziehers aufwärts zu den Fangeinrichtungen (26, 44, 68, 110, 102) zu ziehen;

und daß die Fangeinrichtungen (26, 44, 68, 100, 102) mit dem Korken, wenn er nach Art eines Selbstziehers nach oben gezogen wird, in Eingriff bringbar ist, um eine relative Drehung zwischen der Wendel (18, 28, 48, 72) und dem Korken aufrechtzuerhalten, wodurch der Korken nach Art eines Selbstziehers vollständig aus der Flasche herausgezogen werden kann, wobei die Länge der Fangeinrichtungen an die Länge des Korkens angepaßt ist.

2. Vorrichtung nach Anspruch 1, dadurch gekennzeichnet, daß die Fangeinrichtungen (26, 44, 68, 100, 102) Oberflächen definieren, die in den Korken eingebettet werden können.

3. Vorrichtung nach Anspruch 2, dadurch gekennzeichnet, daß die Fangeinrichtungen (26, 44, 68, 100, 102) im wesentlichen radial in die Bewegungsbahn des Korkens vorstehen zum Eingriff mit den Seiten des Korkens.

4. Vorrichtung nach Anspruch 3, dadurch gekennzeichnet, daß die Oberflächen der Fangeinrichtungen mindestens zwei Verhältnismäßig scharfe Kanten einschließen, die sich im wesentlichen in Längsrichtung an den Seiten der Öffnung (25, 42, 88) erstrecken.

5. Vorrichtung nach Anspruch 4, dadurch gekennzeichnet, daß die Fangeinrichtungen (26, 44) zwei Flansche (26, 44) aufweisen, die im wesentlichen radial einwärts von dem Abstandshalter (12a, 38a) vorstehen und in den scharfen Kanten enden.

6. Vorrichtung nach einem der voranstehenden Ansprüche, dadurch gekennzeichnet, daß die Wendel (18, 28, 48, 72) einen zentralen Körper (19) und eine äußere Schicht (27) aus reibungsverminderndem Material aufweist.

7. Vorrichtung nach Anspruch 6, dadurch ge-



(24)

kennzeichnet, daß das reibungsvermindernde Material polymerisch ist.

8. Vorrichtung nach Anspruch 6 oder 7, wenn auf Anspruch 4, bezogen, dadurch gekennzeichnet, daß die Kanten sich längs des oberen Abschnittes der Öffnung (25, 42) erstrecken und in einem wesentlichen Abstand von dem unteren Ende der Öffnung (25, 42, 88) enden.

9. Vorrichtung nach Anspruch 6 oder 7 wenn auf Anspruch 2 bezogen, dadurch gekennzeichnet, daß die Fangeinrichtungen (86) in Längsrichtung nach unten in die Bewegungsbahn des Korkens vorstehen zum Eingriff mit dem oberen Ende des Korkens.

10. Vorrichtung nach einem der voranstehenden Ansprüche, dadurch gekennzeichnet, daß der Halter (10, 32, 52, 80) außerdem Führungseinrichtungen (14, 16, 34, 54, 72) für eine derartige relative Drehung und auch für eine relative Längsverschiebung zwischen der Wendel (18, 28, 48, 72) und dem Halter (10, 32, 52, 80) aufweist, wobei der Abstandshalter (12a, 38a, 58a, 84a) die Führungseinrichtungen (14, 16, 34, 54, 92) und die Flaschenangriffseinrichtung (12b, 12c, 38b, 38c, 58b, 58c, 84b, 84d) verbindet und die Führungseinrichtungen (14, 16, 34, 54, 92) oberhalb der Flaschenangriffseinrichtung (12b, 12c, 38b, 38c, 58b, 58c, 84b, 84d) anordnet, und daß die Vorrichtung außerdem eine Anlagefläche (20a, 30, 50, 78a) aufweist, die von der Wendel (18, 28, 48, 72) getragen wird und in Eingriff bringbar ist mit dem Halter (10, 32, 53, 80), um eine Abwärtsbewegung der Wendel (18, 28, 48, 72) im Verhältnis zu der Führungseinrichtung (14, 16, 34, 54, 92) in eine untere Position zu begrenzen, in der die Wendel (18, 28, 48, 72) sich derart in die zur Aufnahme des Korkens vorgesehene Öffnung (25, 42, 62, 88) erstreckt.

11. Vorrichtung nach Anspruch 10, dadurch gekennzeichnet, daß die Vorrichtung eine Mehrzahl von Schenkeln (12, 38, 48, 84) aufweist, die sich nach unten von der Führungseinrichtung (14, 16, 34, 54, 92) erstrecken, wobei die oberen Abschnitte (12a, 38a, 58a, 84a) dieser Schenkel (12, 38, 58, 84) den Abstandshalter (12a, 38a, 58a, 84a) aufweisen und die unteren Abschnitte (12b, 12c, 38b, 38c, 58b, 58c, 84b, 84d) der Schenkel (12, 38, 58, 84) die Flaschenangriffseinrichtung (12b, 12c, 38b, 38c, 58b, 58c, 84b, 84d) aufweisen.

12. Vorrichtung nach Anspruch 11, dadurch gekennzeichnet, daß die Anschlageinrichtung (12c, 38c, 58c, 84d) nach unten gerichtete Schultern (12c, 38c, 58c, 84d) aufweist, die an den radial inneren Flächen der Schenkel (12, 38, 58, 84) neben dem unteren Ende der Abstandshalter (12a, 38a, 58a, 84a) ausgebildet sind, wobei die Abschnitte der Schenkel (12, 38, 58, 84) unterhalb der Schultern (12c, 38, 58c, 84d) radial auslenkbare Greifelemente (12b, 38b, 58b, 84b) zum Angriff an der äußeren Seitenfläche des Flaschenhalses aufweisen.

13. Vorrichtung nach Anspruch 12, dadurch gekennzeichnet, daß die radial inneren Flächen (12d) der Greifelemente (12b) in einer querliegenden Schnittfläche jeweils Kreisbögen definie-

ren, deren jeweiliges Zentrum (C1, C2) von der in Längsrichtung verlaufenden Mittellinie der Vorrichtung radial nach außen versetzt ist.

14. Vorrichtung nach Anspruch 13, dadurch gekennzeichnet, daß die radial inneren Flächen (12d) der Greifelemente (12b) in einer nicht ausgelenkten Stellung zumindest auf einem Hauptteil ihrer Länge im wesentlichen gerade in Bezug zu der in Längsrichtung verlaufenden Mittellinie der Vorrichtung ihrer Länge angeordnet sind.

15. Vorrichtung nach Anspruch 12, dadurch gekennzeichnet, daß jeder dieser Schenkel (38) einen in Längsrichtung verlaufenden Spalt (38d) aufweist, der sich von der Schulter (38c) aufwärts erstreckt, wobei der radial äußere Abschnitt des Schenkels (38) von dem radial inneren Abschnitt des Schenkels (38) im Bereich des Spaltes (38d) separierbar ist.

16. Vorrichtung nach Anspruch 11, dadurch gekennzeichnet, daß die Vorrichtung ein Paar von sich nach abwärts von der Führungseinrichtung (14, 16, 34, 54, 92) erstreckenden Schenkeln (12, 38, 58, 84) einschließt, wobei die Anschlageinrichtung (12c, 38c, 58c, 84d) nach unten weisende Schultern (12c, 38c, 58c, 84d) aufweist, die auf den radial inneren Flächen der Schenkel (12, 38, 48, 84) ausgebildet sind, wobei Abschnitte (12a, 38a, 58a, 94a) der Schenkel (12, 38, 58, 84) oberhalb der Schultern (12c, 38c, 58c, 84d) die Abstandshalter (12a, 38a, 58a, 84b) und Abschnitte (12b, 38b, 58b, 84b) der Schenkel (12, 38, 58, 84) unterhalb der Schultern (12c, 38c, 58c, 84d) radial auslenkbare Greifelemente (12b, 38b, 58b, 84b) zum Angriff an der äußeren Seitenfläche des Flaschenhalses aufweisen, wobei diese Greifelemente (12b, 38b, 58b, 84b) einander radial gegenüberliegende innere Oberflächen (12d) besitzen, die, wenn die Greifelemente (12b, 38b, 58b, 84b) in der nicht ausgelenkten Position sind, im wesentlichen gerade im Verhältnis zu der in Längsrichtung verlaufenden Mittellinie der Vorrichtung über mindestens einen Hauptteil ihrer Länge verlaufen.

17. Vorrichtung nach Anspruch 3 oder 6 oder 7 wenn auf Anspruch 3 bezogen, dadurch gekennzeichnet, daß die Vorrichtung eine Verbindungseinrichtung (78) aufweist, die die Korkenzieherwendel (72) und den Halter (80) verbindet, wobei die Verbindungseinrichtung (78) für eine Längsverschiebung aber im wesentlichen nicht drehende Bewegung auf dem Halter (80) angeordnet ist, und wobei die Korkenzieherwendel (72) für eine drehende, aber im wesentlichen nicht längsverschiebbliche Bewegung in der Verbindungseinrichtung (78) angeordnet ist.

18. Vorrichtung nach Anspruch 17, dadurch gekennzeichnet, daß die Verbindungseinrichtung (78) einen im wesentlichen röhrenförmigen Abschnitt (78a), in dem die Korkenzieherwendel (72) drehbar angeordnet ist, und weiterhin Schienen (28b) einschließt, die sich von dem röhrenförmigen Abschnitt (78b) nach unten erstrecken, wobei die Schienen (78b) und der Halter (80) der Vorrichtung ineinandergreifende Mittel (44, 78b, 96, 98) besitzen, die die Schienen (78b) und den





Halter (80) für eine relative Längsverschiebung verbinden, wobei die Schienen (78b) derart in Längsrichtung in die Öffnung (88) verschieblich sind und in Längsrichtung sich erstreckende Kanten (100) besitzen, wobei die Fangeinrichtungen (100, 102) die seitlichen Kanten (100) umfassen.

19. Vorrichtung nach Anspruch 18, dadurch gekennzeichnet, daß die ineinandergreifenden Mittel (44, 78b, 96, 98) in Längsrichtung verlaufende Schlitz (96) in den Schienen (78b) und Stifte (98b) aufweisen, die fest an dem Halter (80) angeordnet sind und sich in die Schlitz (96) erstrecken, wobei die Fangeinrichtungen (100, 102) außerdem in Längsrichtung sich erstreckende Kanten (102) der Schlitz (100) aufweisen.

Revendications

1. Appareil du type à auto-traction pour l'extraction d'un bouchon d'une bouteille, comprenant:

une vis (18, 28, 48, 72);

une monture (10, 32, 52, 80) en prise avec ladite vis (18, 28, 48, 72) et permettant à ladite vis (18, 28, 48, 72) de tourner par rapport à ladite monture (10, 32, 52, 80) et limitant le mouvement de descente de ladite vis (18, 28, 48, 72) par rapport à ladite monture (10, 32, 52, 80), ladite monture (10, 32, 52, 80) comprenant

des moyens (12b, 12c, 38b, 38c, 58b, 58c, 84b, 84d) de prise de bouteille destinés à positionner ladite monture (10, 32, 52, 80) et la vis en prise (18, 28, 48, 72) en alignement globalement coaxial avec le goulot de ladite bouteille, lesdits moyens (12b, 12c, 38b, 38c, 58b, 58c, 84b, 84d) de prise de bouteille comprenant des moyens d'arrêt (12c, 38c, 58c, 84d) destinés à limiter le mouvement de descente de ladite monture (10, 32, 52, 80) par rapport à ladite bouteille; et

des moyens d'entretoisement (12a, 38a, 58a, 84a) définissant une ouverture (25, 42, 62, 88) destinée à recevoir ledit bouchon lorsqu'il sort de ladite bouteille;

ladite vis (18, 28, 48, 72) étant d'une longueur telle qu'elle peut s'étendre dans ladite ouverture (25, 42, 62, 88) de réception du bouchon afin que ledit bouchon puisse se déplacer en mode d'auto-traction en s'élevant par vissage sur ladite vis (18, 28, 48, 72) pendant que ladite vis (18, 28, 48, 72) est tournée pour tirer ledit bouchon vers le haut par rapport à ladite bouteille; caractérisé en ce que:

des moyens d'accrochage (26, 44, 68, 100, 102) sont adjacents auxdits moyens d'entretoisement (12a, 38a, 58a, 84a) dans ladite ouverture (25, 42, 62, 88) et sont positionnés sur le trajet de la course dudit bouchon lorsqu'il monte par rapport à ladite bouteille;

ladite vis (18, 28, 48, 72) est conçue pour tirer des bouchons vers le haut jusqu'auxdits moyens d'accrochage (26, 44, 68, 100, 102) dans ledit mode d'auto-traction;

et lesdits moyens d'accrochage (26, 44, 68, 100, 102) peuvent entrer en prise avec ledit bouchon, pendant qu'il est ainsi tiré vers le haut dans ledit

mode d'auto-traction, afin de maintenir une rotation relative entre ladite vis (18, 28, 48, 72) et ledit bouchon pour que ledit bouchon puisse être totalement retiré de ladite bouteille dans ledit mode d'auto-traction, la longueur desdits moyens d'accrochage étant adaptée à la longueur dudit bouchon.

2. Appareil selon la revendication 1, caractérisé en ce que lesdits moyens d'accrochage (26, 44, 68, 100, 102) définissent des surfaces encastables dans ledit bouchon.

3. Appareil selon la revendication 1, caractérisé en ce que lesdits moyens d'accrochage (26, 44, 68, 100, 102) font saillie globalement radialement sur le trajet de la course dudit bouchon pour entrer en prise avec les côtés dudit bouchon.

4. Appareil selon la revendication 3, caractérisé en ce que lesdites surfaces d'accrochage présentent au moins deux bords relativement vifs s'étendant globalement longitudinalement le long des côtés de ladite ouverture (25, 42, 88).

5. Appareil selon la revendication 4, caractérisé en ce que lesdits moyens d'accrochage (26, 44) comprennent deux nervures (26, 44) faisant saillie globalement radialement vers l'intérieur à partir desdits moyens d'entretoisement (12a, 38a) et aboutissant auxdits bords vifs.

6. Appareil selon l'une quelconque des revendications précédentes, caractérisé en ce que ladite vis (18, 28, 48, 72) comprend un corps central (19) et une couche extérieure (27) de matière réduisant le frottement.

7. Appareil selon la revendication 6, caractérisé en ce que la matière réduisant le frottement est polymérique.

8. Appareil selon la revendication 6 ou la revendication 7 lorsqu'elle dépend de la revendication 4, caractérisé en ce que lesdits bords s'étendent le long de la partie supérieure de ladite ouverture (25, 42) et aboutissent à une distance importante de l'extrémité inférieure de ladite ouverture (25, 42, 88).

9. Appareil selon la revendication 6 ou la revendication 7 lorsqu'elle dépend de la revendication 2, caractérisé en ce que lesdits moyens d'accrochage (68) font saillie longitudinalement vers le bas jusque sur le trajet de la course dudit bouchon pour entrer en prise avec l'extrémité supérieure dudit bouchon.

10. Appareil selon l'une quelconque des revendications précédentes, caractérisé en ce que ladite monture (10, 32, 52, 80) comprend en outre des moyens de guidage (14, 16, 34, 54, 72) pour une telle rotation relative et également pour un mouvement longitudinal relatif entre ladite vis (18, 28, 48, 72) et ladite monture (10, 32, 52, 80), lesdits moyens d'entretoisement (12a, 38a, 58a, 84a) relient entre eux lesdits moyens de guidage (14, 16, 34, 54, 92) et lesdits moyens (12b, 12c, 38b, 38c, 58b, 58c, 84b, 84d) de prise de bouteille et espacement lesdits moyens de guidage (14, 16, 34, 54, 92) vers le haut desdits moyens (12b, 12c, 38b, 38c, 58b, 58c, 84b, 84d) de prise de bouteille, et ledit appareil comprend en outre des moyens de butée (20a, 30, 50, 78a) portés par ladite vis (18,



28, 48, 72) et pouvant entrer en prise avec ladite monture (10, 32, 52, 80) pour limiter le mouvement de descente de ladite vis (18, 28, 48, 72) par rapport auxdits moyens de guidage (14, 16, 34, 54, 92) à une position inférieure dans laquelle ladite vis (18, 28, 48, 72) s'étend dans ladite ouverture (25, 42, 62, 88) de réception du bouchon.

11. Appareil selon la revendication 10, caractérisé en ce que ledit appareil comprend plusieurs branches (12, 38, 58, 84) s'étendant vers le bas desdits moyens de guidage (14, 16, 34, 54, 92), les parties supérieures (12a, 38a, 58a, 84a) desdites branches (12, 38, 58, 84) comprenant lesdits moyens d'entretoisement (12a, 38a, 58a, 84a) et les parties inférieures (12b, 12c, 38b, 38c, 58b, 58c, 84b, 84d) desdites branches (12, 38, 58, 84) comprenant lesdits moyens de prise de bouteille (12b, 12c, 38b, 38c, 58b, 58c, 84b, 84d).

12. Appareil selon la revendication 11, caractérisé en ce que lesdits moyens d'arrêt (12c, 38c, 58c, 84d) comprennent des épaulements (12c, 38c, 58c, 84d) tournés vers le bas, formés sur les surfaces radialement intérieures desdites branches (12, 38, 58, 84) à proximité immédiate de l'extrémité inférieure desdits moyens d'entretoisement (12a, 38a, 58a, 84a), les parties desdites branches (12, 38, 58, 84) situées au-dessous desdits épaulements (12c, 38c, 58c, 84d) comprenant des éléments de serrage (12b, 38b, 58b, 84b) pouvant fléchir radialement et destinés à entrer en prise avec la surface latérale extérieure du goulot de ladite bouteille.

13. Appareil selon la revendication 12, caractérisé en ce que les surfaces radialement intérieures (12d) desdits éléments de serrage (12b) en section transversale, définissent des arcs de cercle respectifs, les centres respectifs (C1, C2) desdits arcs étant décalés radialement vers l'extérieur de l'axe central longitudinal dudit appareil.

14. Appareil selon la revendication 13, caractérisé en ce que lesdites surfaces radialement intérieures (12d) desdits éléments de serrage (12b) sont, dans une position non fléchie, globalement droites par rapport à l'axe central longitudinal dudit appareil sur au moins une majeure partie de leurs longueurs.

15. Appareil selon la revendication 12, caractérisé en ce que chacune desdites branches (38) présente une fente longitudinale (38d) s'élevant dudit épaulement (38c), la partie radialement extérieure de ladite branche (38) pouvant être séparée de la partie radialement intérieure de ladite branche (38) à proximité immédiate de ladite fente (38d).

16. Appareil selon la revendication 11, caractérisé en ce que ledit appareil comprend une paire de branches (12, 38, 58, 84) s'étendant vers le bas desdits moyens de guidage (14, 16, 34, 54, 92), lesdits moyens d'arrêt (12c, 38c, 58c, 84d) compe-

nant des épaulements (12c, 38c, 58c, 84d) tournés vers le bas, formés sur les surfaces radialement intérieures desdites branches (12, 38, 48, 84), des parties (12a, 38a, 58a, 84a) desdites branches (12, 38, 58, 84) situées au-dessus desdits épaulements (12c, 38c, 58c, 84d) comprenant lesdits moyens d'entretoisement (12a, 38a, 58a, 84b) et des parties (12b, 38b, 58b, 84b) desdites branches (12, 38, 58, 84) situées au-dessous desdits épaulements (12c, 38c, 58c, 84d) comprenant des éléments de serrage (12b, 38b, 58b, 84b) pouvant fléchir radialement et destinés à entrer en prise avec la surface latérale extérieure du goulot de ladite bouteille, et lesdits éléments de serrage (12b, 38b, 58b, 84b) présentant des surfaces intérieures (12b) radialement opposées qui, lorsque lesdits éléments de serrage (12b, 38b, 58b, 84b) sont dans une position non fléchie, sont globalement droites par rapport à l'axe central longitudinal dudit appareil sur au moins une majeure partie de leurs longueurs.

17. Appareil selon la revendication 3 ou la revendication 6 ou la revendication 7 lorsqu'elle dépend de la revendication 3, caractérisé en ce que l'appareil comprend des moyens de liaison (78) reliant entre elles ladite vis (72) et ladite monture (80), lesdits moyens de liaison (78) étant montés de façon à pouvoir exécuter un mouvement longitudinal, mais globalement non rotatif sur ladite monture (80) et ladite vis (72) étant montée de façon à pouvoir effectuer un mouvement rotatif, mais globalement non longitudinal, dans lesdits moyens de liaison (78).

18. Appareil selon la revendication 17, caractérisé en ce que lesdits moyens de liaison (78) comprennent une partie globalement tubulaire (78a) dans laquelle ladite vis (72) est montée de façon à pouvoir tourner et des glissières (78b) s'étendant vers le bas de ladite partie tubulaire (78a), lesdites glissières (78b) et ladite monture (80) dudit appareil comportant des formations d'enclenchement (44, 78b, 96, 98) reliant lesdites glissières (78b) et ladite monture (80) pour leur permettre un mouvement longitudinal relatif, lesdites glissières (78b) pouvant ainsi pénétrer longitudinalement dans ladite ouverture (88) et présentant des bords (100) s'étendant longitudinalement, lesdits moyens d'accrochage (100, 102) comprenant lesdits bords latéraux (100).

19. Appareil selon la revendication 18, caractérisé en ce que lesdites formations d'enclenchement (44, 78b, 96, 98) comprennent des rainures longitudinales (96) ménagées dans lesdites glissières (78b) et des goupilles (98) montées fixement sur ladite monture (80) et pénétrant dans lesdites rainures (96), lesdits moyens d'accrochage (100, 102) comprenant en outre des bords (102) s'étendant longitudinalement desdites rainures (100).

