

Description

The present invention relates to a communication apparatus for communicating between a plurality of lines and a plurality of terminals.

5 In a known communication system, when data communication is performed and, for example, another incoming call is detected, the presence of the detected call is informed to the user, via a data adaptor connected to a data terminal. Furthermore, when information associated with the incoming call or the incoming caller is informed to the user, the user can decide whether to maintain the present communication or process the new incoming call. Thus, a facility is provided for improving the response capabilities of the system. More specifically, in some cases, the user wishes to start a new communication while interrupting the present data communication, in dependence upon the nature of the caller's information. Thus, such a requirement of the user can be satisfied.

10 In a communication network having a function of sending a caller's information to a called party, prior to the start of the communication, the above mentioned operations are available. For example, in an integrated system digital network (ISDN) expected to provide various information communication services, caller's information, including a caller's number, is transmitted to a called party. Therefore, by utilising this information, the identity of a caller may be informed to a user, upon detection of the incoming call.

15 In a conventional communication system accommodating a plurality of lines and a plurality of terminals, on a given terminal response to a new incoming call after a communication line is held or disconnected, or when the given terminal places a line on hold to perform a new communication and then responds to the held call, or responds to a held call which was held by another terminal, a user must change its set up data to match a communication attribute if requested to do so by the incoming call.

20 In a communication system of this type, there is no correlation between a display of an incoming call or a held call on a terminal and a communication capability or communication attribute of the terminal itself which makes the call be displayed. The communication attribute indicates information, such as transmission rate, bit format (stop bit, data bit length, parity bit type and the like), a distinction between synchronous or asynchronous communication, a character type, flow control information, media type (voice/G3, fax/G4, fax/document information and the like) etc. and such information serves as an agreement of a communication format with a communication station on the other end of a line or with a network for transmitting information.

25 The data adaptor is used by a communication system, such as an exchange system, to accommodate the data terminals and to exchange data. Some data adaptors support a sequence such as V.25 bis, X.21, or the like for automatically originating an outgoing call and answering an incoming call, while other adaptors can only match a data terminal with a modem pool in a system configured to the data terminal via an interface port and do not support the communication sequence itself. Furthermore, a section which supports data communication, as some of the functions of a standard terminal, is often called a data adaptor.

30 In the previously identified known systems, a user of a communication system cannot determine a communication capability or a communication attribute of a terminal on the basis of an incoming call display or a held call display. For this reason, the user often responds to the incoming call or held call using a wrong terminal, which cannot be matched with a communication attribute requested by the incoming call or the held call.

35 After the user responds to the incoming call, or held call, using a terminal which cannot be matched with the requested communication attribute, the user often performs wasteful operations, such as looking for a terminal having a communication attribute which can respond to the incoming call or held call and transferring that call or disconnecting the call, because the call cannot be transferred.

40 More specifically, when the user responds to an incoming call, the ongoing call must be temporarily held or disconnected and then the user must change a communication attribute of the terminal and also set up data of a data adaptor to which the terminal is connected. After the set up data are changed, the user responds to the incoming call to cope with the above mentioned new incoming call. However, since a user must hold or disconnect a call, change set up data and then respond to the call, such a sequence is labour intensive and requires time. Even if means capable of disconnecting and responding to a call in a series of operations is adopted, set up data of both the terminal and the data adaptor must be changed as needed, depending upon operations of a user.

45 Such a system is disclosed in the Technical Bulletin entitled "Interface for INS Network Services" edited by Nippon Telegram and Telephone Corporation, and issued by the Telecommunications Association on 1 August 1989.

50 In the known systems, to change the set up data of both the terminal and the data adaptor, if necessary, in addition to operations to hold or disconnect the call and respond to the incoming call these operations are undesirable and troublesome to the user. Therefore, a caller may give up the call during these operations and

if the incoming call to be responded to is stopped, a user cannot start a desired communication and consequently fails to switch communication.

When set up change operations are done by a user, this may lead to an operation error or a set up error. When these errors occur, a communication often fails to start, resulting in disadvantages and inconvenience.

5 Following integration of communication services, like ISDN, terminals tend to have hybrid functions, thus it becomes difficult for known systems to work in an environment of processing calls with various communication attributes on a single line or channel and to cope with incoming calls and held calls having various communication attributes, resulting in a communication system which becomes very inconvenient for a user.

10 Philips Telecommunication and Data Systems Review, Volume 47 (1989) March, No. 1, "The SOPHO-SET family of digital telephone terminals for SOPHO-S PABXs" by C. M. Klik describes a communication apparatus comprising interface means for connecting a communication line from a network, communication means including display means, connecting means for connecting the communication line and the communication means, and control means for controlling the display means dependent on information from the communication line.

15 It is an object of the present invention to provide a communication system where a user can respond to a call regardless of matching between a communication attribute of a terminal and that of a requested call.

According to a first aspect of the present invention, there is provided a communication apparatus comprising:

20 interface means for connecting a communication line from a network;
communication means including display means;
connecting means for connecting the communication line and the communication means; and
control means for controlling said display means based on information from the communication line, characterized in that
the control means are adapted to control the display means so as to enable the display means to indicate
25 both that a communication attribute of said communication means and a communication attribute specified for the information from the communication line are inconsistent, and that the communication line is in a busy state.

According to a second aspect of the present invention there is provided a communication method using a communication apparatus comprising:

30 interface means for connecting a communication line from a network;
communication means including display means; and
connecting means for connecting the communication line and the communication means;
comprising the steps of:
controlling said display means based on information from the communication line,
35 said method being characterized by including the further step of controlling the display means so as to enable the display means to indicate both that a communication attribute of said communication means and a communication attribute specified by the information from the communication line are inconsistent, and that the communication line is in a busy state.

40 The invention will now be described by way of example only, with reference to the accompanying drawings in which:

Fig. 1 is a block diagram of a communication system according to an embodiment of the present invention;
Fig. 2(A) is a schematic view of a panel surface of a data adaptor telephone set, accommodated in a communication system according to the embodiment;
Fig. 2(B) is a perspective view of the data adaptor telephone set;
45 Fig. 3(A) shows a memory format of an extension setting memory in the communication system according to the embodiment;
Fig. 3(B) shows an example of a setup format of the extension setting memory for a key telephone set 9;
Fig. 3(C) shows an example of a setup format of the extension setting memory for a data adapter telephone set 10;
50 Fig. 3(D) shows an example of a setup format of the extension setting memory for a data adapter telephone set 11;
Fig. 4(A) shows a memory format of a call information memory in the communication system according to the embodiment;
Fig. 4(B) shows an example of a held call stored in the call information memory;
55 Fig. 4(C) shows an example of an ongoing call stored in the call information memory;
Fig. 5 is a table showing a correspondence between communication attributes of a terminal accommodated in the communication system and classes according to the embodiment;
Fig. 6(A) shows an example of an incoming call display on a display unit of the terminal accommodated in

the communication system according to the embodiment;

Fig.6(B) shows a display example of an in-communication status;

Fig. 6(C) shows a display example of switching calls in-communication;

Fig. 6(D) shows an example of a held call display;

Fig. 6(E) shows a display example of a changed communication attribute set up; and

Fig. 7(A) to 7(I) are flow charts showing a call processing sequence of a CPU in a communication system according to the embodiment.

A block diagram of the communication system according to the invention is shown in Fig. 1. A central processing unit CPU 1 controls interfaces, terminals and the entire system. A memory 2 stores control data, set up data and the like and a ROM 3 stores a call processing program and various other control programs.

Reference 4 denotes an exchange unit comprising, for example, time division switches and numeral 5 denotes an ISDN interface which accommodates an ISDN line from integrated service digital network (ISDN) 14 via a digital service unit (DSU) 15, having a protocol processing section for ISDN layers "1", "2" and "3" and a V.110 rate adaptation section, and the like; and 6 to 8, extension interfaces for accommodating telephone sets exclusively used for the communication system.

Reference numeral 9 denotes a key telephone set which comprises, e.g., a key pad, a loudspeaker, a handset, a display unit, and the like to process only a voice communication, and is exclusively used for the communication system; and reference numeral 10 denotes a data adapter telephone set which can be connected to a data terminal equipment (DTE) 12 such as a personal computer through an internal RS-232C interface in addition to a voice communication service function of the exclusive key telephone set 9, and can change a transmission rate with the DTE 12 and a communication format such as a bit format in accordance with a command from the CPU 1. As will be described later with reference to Fig.5, the communication format can be changed in the following combinations. That is, the transmission rate can be changed in an asynchronous mode of 300 bps to 9,600 bps; a stop bit length can be selected from 1, 1.5, and 2 bits, a data length can be set within a range of 5 to 8 bits, and a parity type can be selected from an odd parity, an even parity, and none. Reference numeral 11 denotes a data adapter telephone set, incorporating an RS-422 interface, for performing a synchronous communication (transmission rate = 64 Kbps) with a data terminal equipment (DTE) 13 such as a personal computer.

Figs.2A and 2B are schematic views of the data adapter telephone set which is used to be connected to the communication system of this embodiment. Fig.2A shows a panel surface of the data adapter telephone set, and Fig.2B is a perspective view of the data adapter telephone set.

In Fig.2A, reference numeral 21 denotes a main body of the data adapter telephone set; 22, a display unit, comprising, e.g., LCDs, for displaying character information, communication information, and the like; 23, a handset for a voice communication; and 24, outside line buttons each having an LED 24a for the indication of an outside line call status. Reference numeral 25 denotes a data button for initiating or terminating communication; 26, a switching button for switching communications; 27, a dial key pad; and 28, a hold button.

The LED 24a corresponding to each outside line button 24 has the following indication patterns depending on call status:

Unlit:	Indicates a status wherein the corresponding outside line is not busy (not used).
Fast Flashing in Green:	Indicates a status wherein the corresponding outside line is receiving an incoming call, and a response can be made.
Lit in Green:	Indicates a status wherein the terminal equipment with that indication is in communication via the corresponding outside line.
Lit in Red:	Indicates a status wherein other terminal equipment is in communication via the corresponding outside line, and the terminal equipment with that indication can not perform a communication with the call.
Slow Flashing in Green:	Indicates a status wherein the terminal equipment with that indication has placed the corresponding line on hold.
Slow Flashing in Red:	Indicates a status wherein another terminal equipment has placed the corresponding line on hold, and the terminal equipment with that indication can respond to the held line.

In Fig.2B, reference numeral 29 denotes a modular jack connected to one of the extension interfaces 6 to 8 via a modular cord; and 30, a data terminal port having an RS-232C or RS-422 interface and connected to a DTE via a respective cable.

The outer appearance of the key telephone set 9 which exclusively processes a voice communication is substantially the same as that of the data adapter telephone set shown in Fig.2B, the perspective view, except that the data terminal port 30 is omitted from the data adapter telephone set, and its illustration is not shown

here.

Figs.3(A) to 3(D) show a format and setup examples of the extension setting memory in the communication system of this embodiment.

Fig.3(A) shows the memory format of the extension setting memory, which consists of an extension ID, an extension number, a terminal class, and a communication format, e.g., a setup transmission rate as additional information for the corresponding extension in, e.g., a data adapter telephone set. Figs.3(B) to 3(D) show setup examples of the extension setting memory. Fig.3(B) exemplifies a case of the key telephone set 9. In Fig.3(B), the extension ID is set to "a", the extension number is set to "1234", and the terminal class is set to "class 1" exclusively for a voice communication. Fig.3(C) exemplifies a case of the data adapter telephone set 10. In Fig.3(C), the extension ID is set to "b", the extension number is set to "1235", and the terminal class is set to "class 2" which can deal with a voice communication and a DTE having an RS-232C interface. In addition, in the communication format (attribute), the transmission rate is set to a 1,200-bps asynchronous mode, the stop bit is set to "1 bit", the data bit length is set to "7 bits", and a parity is even. Fig.3(D) shows a setup example of the data adapter telephone set 11. In Fig.3(D), the extension ID is set to "c", the extension number is set to "1236", the terminal class is set to "class 3" which can process a voice communication and connection of a DTE having an RS-422 interface, and a communication format (attribute) is set such that a terminal in a synchronous circuit switching mode communicates at a rate of 64 Kbps.

These setup data can be desirably set by a user according to each terminal, or can be automatically set by the CPU of the communication system. The extension number also corresponds to an ISDN subaddress.

Figs.4(A) to 4(C) show a format and examples of stored information of the call information memory in the communication system of this embodiment.

Fig.4(A) shows a memory format of the call information memory, and stores a call status, the extension ID of its own terminal, an outside line type and its number, and additional information (e.g., a communication format) with respect to a call.

Fig.4(B) exemplifies a case of a held call. Fig.4(B) shows call information indicating that a call from a caller which is connected via the 1st channel of the ISDN line is being held by an extension having the extension ID "b", and that, as a communication attribute, "an asynchronous circuit switching mode", "a transmission rate = 9,600 bps", "a stop bit = 1 bit", "a data bit length = 8 bits", and "no parity" are set.

Fig.4(C) exemplifies a case of an ongoing call. Fig.4(C) shows call information indicating that the corresponding terminal with the extension ID "b" is connected to a caller through the 2nd channel of the ISDN line, and that, as a communication attribute, "an asynchronous circuit switching mode", "a transmission rate = 1,200 bps", "a stop bit = 1 bit", "a data bit length = 7 bits", and "an even parity" are set.

Fig.5 shows communication attributes and corresponding classes which can be permitted by the terminals (the exclusive key telephone set and the data adapter telephone sets) of the communication system of this embodiment. "Class 1" corresponds to the exclusive key telephone set 9, "class 2" corresponds to the data adapter telephone set 10, and "class 3" corresponds to the data adapter telephone set 11.

Figs.6(A) to 6(E) show display examples on the display units of the exclusive key telephone set and the data adapter telephone sets.

Fig.6(A) shows a display example of an incoming call in which a caller's number is "123-4567", and the call requests an asynchronous/circuit switching data communication to have "9,600 bps", "a data bit length = 8 bits", "no parity", and "a stop bit = 1 bit". Fig.6(B) shows a display example wherein an asynchronous/circuit switching communication is being performed to have 1,200 bps, "data bit length = 7 bits", "an even parity", and "a stop bit = 1 bit". Fig.6(C) shows a display example wherein a single telephone set processes two types of calls, i.e., a terminal is selectively in communication with one call while the other call is being held.

Fig.6(D) shows a display example of a case wherein the ongoing call shown in Fig.6(B) is held, and Fig.6(E) shows a display example of a case wherein a setup communication attribute of a terminal is automatically changed.

The call processing sequence by the CPU 1 of the communication system of this embodiment will be described below with reference to the flow charts of Figs.7A to 7I. In the following description, a "terminal" indicates both the exclusive key telephone set and the data adapter telephone set unless otherwise specified.

In step S1 in Fig.7A, the presence/absence of an incoming call with respect to the communication system of this embodiment is determined on the basis of a call setup message received by the ISDN interface 5 from the ISDN 14 via the DSU 15. When an incoming call is detected, the CPU 1 sets information of the incoming call in the call information memory in step S2, and confirms a possibility of communication, i.e., whether or not a terminal is accommodated in the communication system which can be matched with the communication attribute of the incoming call. More specifically, it is checked if the incoming call can be matched with terminal attribute classes "1" to "3" shown in Fig.5. For example, when a caller designates "transfer capability = unrestricted digital", "asynchronous 9,600 bps", "stop bit = 1 bit", "data bit length = 8 bits", "no parity", and "V.110

rate adaptation" as transmission capability information elements (or low layer matching information elements), and the received subaddress is "1235" to request a data communication via the data adapter telephone set 10, the required data communication is permitted. However, when a G4 FAX communication is designated although the subaddress is "1235" to designate the data adapter telephone set 10, the corresponding call is not accepted.

If it is determined as a result of confirmation of a communication possibility that there are no terminals which can be matched with the communication attribute of the incoming call and communication is impossible, the reason for the impossible communication is displayed and the incoming call is rejected by a release completion message accompanying an unconformity of terminal attribute in step S3, thus releasing the call information memory and ending processing.

However, if it is determined in step S2 that there are terminals which can permit the communication attribute of the incoming call, the flow advances to step S4, and an LED, corresponding to an incoming outside line, of the permissible terminal are set to a pattern (fast flashing in green) indicating that incoming processing can be executed, and LEDs of other nonpermissible terminals are set to a pattern (lit in red) indicating that another terminal is executing the incoming processing. In step S5, status of all the permissible terminals is checked, and processing according to the detected status is then executed.

As processing for non-busy terminals, an incoming tone is generated in step S70 in Fig.7D, and in steps S71 and S72, a response to an incoming call at a called terminal and a halt of an incoming call by abandonment at a calling side are monitored, respectively. If the terminal (called terminal) responds to the call before the incoming call stops, the flow advances to step S75, and a response message is sent to the ISDN. Then a communication channel is connected to the ISDN, and the incoming tone is stopped in step S76.

In step S77, the outside line LED of the responding terminal is steadily lit in green indicating that the terminal is in communication, and the outside line LEDs of other terminals are lit in red indicating that another terminal is in communication.

However, if the incoming call stops before a response, the incoming tone is turned off in step S73, and flashing or lit LEDs in correspondence with the incoming call are turned off in step S74. Then, the terminals, the interfaces, and call information memory are released to be set in a release state, thus ending processing.

In step S78, an input of the hold button at the terminal in communication is monitored. If the button input is detected, the flow advances to step S79 in Fig.7E; otherwise, a completion of the communication is monitored in step S91. In step S79, the ongoing call is held, and the call information memory is set in correspondence with the hold operation. In step S80, the outside line LED corresponding to the held call of the terminal at which the hold operation is performed is set to a slow flashing in green, and those of other terminals are set to a slow flashing in red or a steady lit in red in correspondence with the communication attributes of the terminals. In step S81, the communication attribute of the held call is displayed on the terminal in hold condition.

In step S82, an input of the outside line button is monitored. It is checked in step S83 if the input of the outside line button corresponds to the held call. If it is determined in step S83 as a result of checking that the input of the outside line button corresponds to the held call, the flow advances to step S84 to check if a terminal responding to the held outside line has a communication attribute which matches with that of the held call. If the communication attribute of the terminal matches, the held call is connected to the terminal in step S89; otherwise, the communication attribute of the terminal is set to match with that of the held call in step S85.

In step S86, a message indicating that the communication attribute of the terminal has been changed is displayed on the terminal which has responded to the held call, and a tone is generated at the terminal. In step S87, the held call is connected to the terminal. In step S88, the display and tone generation executed in step S86 is processed to stop. In step S90, the corresponding outside line LED on the terminal responded to the held call is set to a steady lit in green indicating that the terminal is in communication, and the corresponding LEDs of other terminals are lit in red. The flow then returns to step S78 in Fig.7D.

If it is recognized in step S5 in Fig.7A that the terminal is in communication, an in-communication incoming tone is generated and caller's information (caller's number, transmission rate, bit format, and the like) is displayed at the terminal in step S13 (see the display example in Fig.6(A)). In the following step, step S14 in Fig.7B, depressions of the switching button 26 and the outside line button 24 whose LED is flashing in correspondence with the incoming call are monitored. If these buttons are not depressed, then the depressions of the data button 25 and the outside line button 24 with a flashing LED in correspondence with the incoming call are monitored in the step 14a. As a result, if all these buttons are not depressed, and a halt of the incoming call resulting from abandonment of the call at a calling side is confirmed in step S15, the in-communication incoming tone at the terminal is stopped, and the displayed information is cleared in step S16. In step S17, the outside line LED which has been kept lit in correspondence with the incoming call is turned off, and the call information memory is released, thus ending processing.

If the depressions of the switching button 26 and the outside line button 24 whose LED is flashing in cor-

5
 10
 15
 20
 25
 30
 35
 40
 45
 50
 55

respondence with the incoming call are sequentially detected in step S14, the flow advances to step S18 in Fig.7C, and the present ongoing call is held, and information of the held call is set in the call information memory. In step S19, the corresponding outside line LED is set to a status of flashing in green indicating that its own terminal is in hold condition. If the depressions of the data button 25 and the outside line button 24 with a flashing LED in correspondence with the incoming call are sequentially detected in step 14a, the flow advances to step S18a in Fig.7C where processing of releasing the call information memory of ongoing call and disconnecting the outside line is performed. And, in step S19a, an LED corresponding to the disconnected outside line is turned off and the call information memory of that disconnected call is released.

In step S20, it is determined upon comparison between the contents of the call information memory and the contents of the extension setting memory if the communication attribute (communication format such as a transmission rate, a stop bit count, a data bit length, parity information, and the like) included in the call setup message and requested by the calling side at the time when the incoming call comes is matched with that set in the incoming terminal.

If it is determined as a result of comparison that the communication attributes are matched, the in-communication incoming tone is stopped in step S21, and the display unit is cleared in step S22. In step S23, a response message corresponding to the incoming call is sent onto the ISDN in step S23 to complete a response to the incoming call, and the communication channel of the communication system is connected to the ISDN. In addition, the call information memory is set to an in-communication status.

However, if it is determined in step S20 that the communication attributes are not matched (e.g., a case wherein the incoming call designates the communication attribute including "9,600 bps", "stop bit = 1 bit", "data bit length = 8 bits", and "no parity" when the data adapter telephone set 10 is set with the communication attribute including "1,200 bps", "stop bit = 1 bit", "data bit length = 7 bits", and "even parity" as shown in Fig.3(C)), the setup data of the terminal which is receiving the incoming call (in this case, the terminal is restricted to the data adapter telephone set) are set again in correspondence with the incoming call, and the content of the extension setting memory is also rewritten in step S24. In step S25, in order to inform a change in communication format to a user, a tone is generated at the terminal, and the changed communication format is displayed on the display unit (see Fig.6(E)). In step S26, a response message to the incoming call is sent on to the ISDN to complete a response to the incoming call, and the communication channel of the communication system is connected to the ISDN. In step S27, the tone generated in step S25 is stopped, the display unit is cleared, and the call information memory is set to an in-communication status.

In step S27a, it is determined if there is a call in hold condition. That is, if there is a held call, that means the call was placed on hold in step S18. Therefore, the flow advances to step S28 in Fig.7F to perform processings including processing of the held call and ongoing call. If there are no held calls, however, the flow advances to step S77 in Fig.7D for processing present ongoing call.

In step S28 in Fig.7F, the corresponding outside line LED of the terminal in communication is set to a steady lit in green indicating that its own terminal is being in communication, and the corresponding outside line LEDs of other terminals are set to a steady lit in red indicating that another terminal is in communication. In step S29, information (communication format) associated with the ongoing call and the held call is displayed on the terminal in communication (see Fig.6(C)).

In steps S30 to S33, depression of the switching button 26, disconnection of the held call, disconnection of the in-communication call by the caller, and disconnection of the call at its own terminal (the call is disconnected upon on hook in a voice communication, or upon depression of the data button 25 in a data communication) are monitored. More specifically, if the input of the switching button 26 is detected in step S30, the flow advances to step S34 in Fig.7H, the call in communication is placed on hold and the corresponding information is set in the call information memory. In step S35, the LED of the corresponding outside line button is set to a status indicating that its own terminal is in hold condition, i.e., a slow flashing in green.

In step S36 (See Fig.7H), it is checked if the communication attribute of the call in the call information memory, in which the call has been requested for switching, i.e., the call which has been in hold condition in step S30 (Fig.7F), is matched with the communication attribute in the extension setting memory of the terminal which performs the switching operation. If the communication attributes are matched, the held call requested for switching is connected to the terminal, and the content of the call information memory of the connected held call is rewritten as an in communication status, in step S37 in Fig.7H. The flow then returns to processing in step S28 in Fig.7F.

However, if the result of recognition in step S36 is NO in Fig.7H, the communication attribute of the terminal (data adapter telephone set) which performs the switching operation is set to match with the communication attribute set in the call information memory, and the content of the corresponding extension setting memory is also rewritten, in step S38. In step 39, a change in the communication attribute of this terminal is informed by generation of a tone, and the communication attribute is displayed, in step S39 (see Fig.6(E)). In step S40,

the held call which has been requested for switching is connected to the terminal, the content of the call information memory of the connected held call is changed to indicate an in-communication status, and the flow advances to step S41. In step S41, the tone informing a change in communication attribute is stopped, the display is cleared, and the flow returns to the processing in step S28 in Fig.7F.

5 If it is detected in step S31 in Fig 7F that the held call is disconnected by the caller, the flow advances to step S42 in Fig.7I. In step S42, the call information memory of the disconnected held call is released, and the flashing LED which indicates the call is in hold condition is turned off. In step S43, a tone for informing that the held call is disconnected is generated, and the display of the held call is cleared in step S44. In step S45, the tone for informing that the held call is disconnected is stopped, thus ending processing.

10 If it is detected in step S32 in Fig.7F that the call is disconnected by the calling side, the flow advances to step S62, and a tone for informing that the caller disconnects the call is generated. In step S63, release of its own terminal by disconnection (on hook in a voice communication or depression of the data button 25 in a data communication) is monitored. If disconnection of its own terminal is detected in step S63, the tone generated in step S62 is stopped, and display of the ongoing call is cleared in step S64. In step S47, the LED corresponding to the outside line of the disconnected call is turned off, and the call information memory of the disconnected call is released.

15 If disconnection by its own terminal (on-hook in a voice communication or depression of the data button 25 in a data communication) is detected in step S33, release of the call information memory of the ongoing call, and disconnection/release processing of the outside line are executed in step S46, and the flow then advances to step S47.

20 In step S48, the outside line LED corresponding to the held call of the terminal in hold condition is kept in its own status (slow flashing in green), and LEDs of other terminals which can permit the communication attribute of the held call are set to a status indicating that another terminal is placing the call on hold (slow flashing in red). At the same time, the corresponding LEDs of the nonpermissible terminals are set to a status indicating that another terminal is in communication (lit in red).

25 In step S49 in Fig.7G, information associated with the held call, e.g., a message indicating the existence of the held call and the communication attribute are displayed on the terminal in hold condition and other terminals which can permit the communication attribute of the held call. In step S50, a tone for informing the existence of the held call is generated. In steps S51 and S52, a response to the held call (depression of the outside line button corresponding to the held call after an off-hook operation in a voice communication or depressions of the data button 25 and the outside line button corresponding to the held call in data communication), and disconnection of the held call are monitored. If it is detected in step S52 that the held call is disconnected by the caller, the tone is stopped, and display is cleared in step S60. In step S61, the LED corresponding to the disconnected call is turned off, and the call information memory of the held call is released, thus ending processing.

30 If the response to the held call is detected in step S51, it is confirmed in step S53 if the communication attribute of the held call in the call information memory is matched with that in the extension setting memory of the terminal which has responded to the held call. If it is determined in step S53 that the communication attributes are matched, the responded held call is connected to the terminal in step S54, and the corresponding outside line LED of the terminal is set to a status indicating its own terminal is in communication (lit in green), and LEDs of other terminals are set to a status indicating that another terminal is in communication (lit in red) in step S59. In addition, the call information memory of the connected held call to the terminal is altered to an in-communication status, and the flow then returns to step S78 in Fig.7D.

35 However, if it is determined NO in step S53, the communication attribute of the terminal is set to match with that the call information memory, and the extension setting memory is altered in step S55. In step S56, a tone for informing a change in communication attribute and a message associated with it are displayed in step S56 (see Fig.6(E)). In step S57, the call information memory of the held call is altered to a in-communication status, and the held call requested to respond is connected to the terminal. In step S58, the tone generated to inform a change in communication attribute in step S56 is stopped, and the display is also cleared.

40 As described above, according to this embodiment, a user can easily determine whether a response to an incoming call or held call can be performed at the given terminal based on LED displays corresponding to an incoming call or a held call at the given terminal accommodated in the communication system. Therefore, the user will never be confused in making a response. Since communication attributes of the call and the terminal are matched simultaneously with a response to an incoming call or held call, the user can be free from troublesome setup operations for matching and wasteful call transfer operations, thus avoiding erroneous responses or erroneous disconnections to incoming or held calls.

45 Furthermore, since call information, a communication attribute of a terminal, and the like are displayed on a display unit of the terminal every time an operation to respond to an incoming call or held call is performed,

the detailed communication attribute can be visually confirmed, and an intercommunication upon matching of the communication attributes can be further assured.

In the above embodiment, whether or not a given terminal is matched with a communication attribute of a call is indicated by indication patterns of an LED corresponding to an outside line button.

Alternatively, such LEDs may be arranged independently of the outside line buttons, or communication attributes of the terminal and the call may be distinguished by a plurality of tones, or colors of LEDs, or a voice message.

As a means for recognizing a communication attribute of a held call or incoming call, information elements (transmission capability, low layer matching characteristics, high layer matching characteristics, or the like) included in a message from the ISDN are used. However, a method of uniquely registering a communication attribute in each unit of outside line trunks may be employed.

In the above embodiment, only when communication attributes between a held call or incoming call and a terminal do not match with each other, the communication attribute of the data adapter telephone set is set to match with the corresponding call. Alternatively, if it is determined that a communication attribute of a held call or incoming call falls within an allowable range of setup change of the data adapter telephone set without checking a status of the communication attribute set in the terminal, the communication attribute of the terminal can be unconditionally set to match with that of the held or incoming call.

Furthermore, the CPU may inform only call information to the data adapter telephone set, and setup of a communication attribute and checking of a possibility of communication may be executed by the data adapter telephone set. Only the results of these executions may be informed to the CPU.

Claims

1. Communication apparatus comprising:

interface means (5, 15) for connecting a communication line from a network (14);

communication means (9, 10, 11, 12, 13) including display means (24a);

connecting means (4, 6, 7, 8) for connecting the communication line and the communication means;

and

control means (1, 2, 3) for controlling said display means based on information from the communication line,

characterized in that

the control means (1, 2, 3) are adapted to control the display means (24a) so as to enable the display means (24a) to indicate both that a communication attribute of said communication means (9, 10, 11, 12, 13) and a communication attribute specified by the information from the communication line are inconsistent, and that the communication line is in a busy state.

2. Apparatus according to claim 1, wherein the control means (1, 2, 3) includes means for recognizing a communication attribute of an incoming call on the basis of the information from the communication line.

3. Apparatus according to claim 1, wherein the network to which the interface means (5, 15) is connected via the communication line, includes an ISDN (14).

4. Apparatus according to any preceding claim, wherein the communication means (9, 10, 11) includes an adaptor (29, 30) to connect a data terminal (12, 13).

5. Apparatus according to any of claims 1 to 3, wherein the communication means includes a telephone (10, 11) having an adaptor (29, 30) to connect to a data terminal (12, 13).

6. Apparatus according to claim 1, wherein the communication means includes a telephone (9, 10, 11).

7. Apparatus according to any preceding claim, wherein the display means (24a) includes means for displaying a representation of whether the communication attribute of the communication means (9, 10, 11) and the communication attribute of an incoming call specified by the information are consistent.

8. Apparatus according to any preceding claim, further comprising setting means (1, 2, 3) for setting a communication attribute of said communication means (9, 10, 11).



the detailed communication attribute can be visually confirmed, and an intercommunication upon matching of the communication attributes can be further assured.

In the above embodiment, whether or not a given terminal is matched with a communication attribute of a call is indicated by indication patterns of an LED corresponding to an outside line button.

Alternatively, such LEDs may be arranged independently of the outside line buttons, or communication attributes of the terminal and the call may be distinguished by a plurality of tones, or colors of LEDs, or a voice message.

As a means for recognizing a communication attribute of a held call or incoming call, information elements (transmission capability, low layer matching characteristics, high layer matching characteristics, or the like) included in a message from the ISDN are used. However, a method of uniquely registering a communication attribute in each unit of outside line trunks may be employed.

In the above embodiment, only when communication attributes between a held call or incoming call and a terminal do not match with each other, the communication attribute of the data adapter telephone set is set to match with the corresponding call. Alternatively, if it is determined that a communication attribute of a held call or incoming call falls within an allowable range of setup change of the data adapter telephone set without checking a status of the communication attribute set in the terminal, the communication attribute of the terminal can be unconditionally set to match with that of the held or incoming call.

Furthermore, the CPU may inform only call information to the data adapter telephone set, and setup of a communication attribute and checking of a possibility of communication may be executed by the data adapter telephone set. Only the results of these executions may be informed to the CPU.

Claims

1. Communication apparatus comprising:

interface means (5, 15) for connecting a communication line from a network (14);
communication means (9, 10, 11, 12, 13) including display means (24a);
connecting means (4, 6, 7, 8) for connecting the communication line and the communication means;

and

control means (1, 2, 3) for controlling said display means based on information from the communication line,

characterized in that

the control means (1, 2, 3) are adapted to control the display means (24a) so as to enable the display means (24a) to indicate both that a communication attribute of said communication means (9, 10, 11, 12, 13) and a communication attribute specified by the information from the communication line are inconsistent, and that the communication line is in a busy state.

2. Apparatus according to claim 1, wherein the control means (1, 2, 3) includes means for recognizing a communication attribute of an incoming call on the basis of the information from the communication line.

3. Apparatus according to claim 1, wherein the network to which the interface means (5, 15) is connected via the communication line, includes an ISDN (14).

4. Apparatus according to any preceding claim, wherein the communication means (9, 10, 11) includes an adaptor (29, 30) to connect a data terminal (12, 13).

5. Apparatus according to any of claims 1 to 3, wherein the communication means includes a telephone (10, 11) having an adaptor (29, 30) to connect to a data terminal (12, 13).

6. Apparatus according to claim 1, wherein the communication means includes a telephone (9, 10, 11).

7. Apparatus according to any preceding claim, wherein the display means (24a) includes means for displaying a representation of whether the communication attribute of the communication means (9, 10, 11) and the communication attribute of an incoming call specified by the information are consistent.

8. Apparatus according to any preceding claim, further comprising setting means (1, 2, 3) for setting a communication attribute of said communication means (9, 10, 11).



9. Apparatus according to any preceding claim, wherein the control means (1, 2, 3) includes comparing means for comparing the communication attribute of the communication means and the communication attribute specified by the information.
- 5 10. Apparatus according to any preceding claim, wherein the display means includes means (24a) for performing a display by colour, in accordance with whether the communication attribute of the communication means (9, 10, 11, 12, 13) and the communication attribute specified by the information are consistent.
- 10 11. Apparatus according to any preceding claim, wherein the display means includes means (24a) for displaying by changing a flashing rate in accordance with whether the communication attribute of said communication means (9, 10, 11, 12, 13) and the communication attribute specified by the information are consistent.
- 15 12. Apparatus according to any preceding claim, wherein the display means (24) is provided corresponding to a key (24) for specifying the communication line.
- 20 13. Apparatus according to any preceding claim, wherein the display means (24) includes means for displaying a common display in the case where the communication line is used by another terminal, and in the case where the communication attribute of the communication means (9, 10, 11, 12, 13) and the communication attribute specified by the information are inconsistent.
- 25 14. Apparatus according to any preceding claim, wherein the display means includes means (24) for displaying the existence of an incoming call when the communication attribute of the communication means matches the communication attribute of the incoming call.
- 30 15. A communication method using a communication apparatus comprising:
interface means (5, 15) for connecting a communication line from a network (14);
communication means (9, 10, 11, 12, 13) including display means (24a); and
connecting means (4, 6, 7, 8) for connecting the communication line and the communication means;
comprising the steps of:
controlling said display means (24a) based on information from the communication line,
said method being characterized by including the further step of controlling the display means (24a)
so as to enable the display means (24a) to indicate both that a communication attribute of said communication means (9, 10, 11, 12, 13) and a communication attribute specified by the information from the
35 communication line are inconsistent, and that the communication line is in a busy state.
- 40 16. A method according to claim 15, including the step of recognizing a communication attribute of an incoming call on the basis of the information from the communication line.
- 45 17. A method according to claim 15 or 16, wherein the communication means includes a telephone (9, 10, 11).
- 50 18. A method according to any one of claims 15 to 17, including the step of displaying on the display means (24a) a representation of whether the communication attribute of the communication means (9, 10, 11) and the communication attribute of an incoming call specified by the information are consistent.
- 55 19. A method according to any one of claims 15 to 18, including the step of displaying by means of colour whether the communication attribute of the communication means and the communication attribute specified by the information are consistent.
20. A method according to any one of claims 15 to 19, including the step of displaying by means of changes in a flash rate whether the communication attribute of said communication means (9, 10, 11, 12, 13) and the communication attribute specified by the information are consistent.
21. A method according to any one of claims 15 to 20, including the step of displaying a common display where the communication line is used by another terminal, and in a case where the communication attribute of the communication means and the communication attribute specified by the information are inconsistent.



22. A method according to any one of claims 15 to 21, including the step of displaying the existence of an incoming call when the communication attribute of the communication means (9, 10, 11, 12, 13) matches the communication attribute of the incoming call.

23. A method according to any one of claims 15 to 22, including the steps of setting the communication attribute of the communication means (9, 10, 11, 12, 13) to match a communication attribute specified by information from the communication line by recognizing the communication attribute of an incoming call specified by the information from the communication line.

24. A method according to any one of claims 15 to 23, wherein the network to which the interface means is connected via the communication line, includes an ISDN (14).

25. A method according to any one of claims 15 to 24, wherein the communication means includes a telephone (9, 10, 11).

26. A method according to claim 23, wherein the step of setting includes setting a communication attribute of a communication produced by the data terminal (12, 13).

Patentansprüche

1. Kommunikationsvorrichtung, mit:

Schnittstellenmitteln (5, 15) zur Belegung einer Übertragungsleitung eines Netzes (14);
über Anzeigemittel (24a) verfügende Kommunikationsmittel (9, 10, 11, 12, 13);

Anschaltmitteln (4, 6, 7, 8) zur Verbindung der Übertragungsleitung mit den Kommunikationsmitteln; und mit

Steuermitteln (1, 2, 3) zur Steuerung der Anzeigemittel auf der Grundlage von Informationen aus der Übertragungsleitung,
dadurch gekennzeichnet, daß

die Steuermittel (1, 2, 3) zur Steuerung der Anzeigemittel (24a) eingerichtet sind, die Anzeigemittel (24a) einzuschalten, um anzuzeigen, daß einerseits eine Kommunikationseigenschaft der Kommunikationsmittel (9, 10, 11, 12, 13) mit einer durch die Informationen aus der Übertragungsleitung spezifizierten Kommunikationseigenschaft unvereinbar ist, und daß andererseits die Übertragungsleitung in einem Belegzustand ist.

2. Vorrichtung nach Anspruch 1, deren Steuermittel (1, 2, 3) Mittel zur Erkennung einer Kommunikationseigenschaft eines ankommenden Rufs auf der Grundlage der Information aus der Übertragungsleitung enthält.

3. Vorrichtung nach Anspruch 1, bei der das Netz, an das die Schnittstellenmittel (5, 15) über die Übertragungsleitung angeschlossen sind, ein ISDN (14) beinhaltet.

4. Vorrichtung nach einem der vorstehenden Ansprüche, deren Kommunikationsmittel (9, 10, 11) über einen Adapter (29, 30) zur Belegung eines Datenendgerätes (12, 13) verfügt.

5. Vorrichtung nach einem der Ansprüche 1 bis 3, deren Kommunikationsmittel ein Telefon (10, 11) enthält, das über einen Adapter (29, 30) zur Belegung eines Datenendgerätes (12, 13) verfügt.

6. Vorrichtung nach Anspruch 1, deren Kommunikationsmittel über ein Telefon (9, 10, 11) verfügt.

7. Vorrichtung nach einem der vorstehenden Ansprüche, deren Anzeigemittel (24a) Mittel zur Anzeige einer Aussage darüber enthält, ob die Kommunikationseigenschaft des Kommunikationsmittels (9, 10, 11) mit der Kommunikationseigenschaft eines ankommenden, durch die Information spezifizierten Rufs vereinbar ist.

8. Vorrichtung nach einem der vorstehenden Ansprüche, die des weiteren mit Einstellmitteln (1, 2, 3) zur Einstellung einer Kommunikationseigenschaft des Übertragungsmittels (9, 10, 11) ausgestattet ist.



9. Vorrichtung nach einem der vorstehenden Ansprüche, deren Steuermittel (1, 2, 3) über Vergleichsmittel verfügt, die die Kommunikationseigenschaft des Kommunikationsmittels mit der durch die Information spezifizierten Kommunikationseigenschaft vergleichen.
- 5 10. Vorrichtung nach einem der vorstehenden Ansprüche, deren Anzeigemittel über Mittel (24a) zur Bewirkung einer Farbanzeige in Einklang damit verfügt, daß die Kommunikationseigenschaft des Kommunikationsmittels (9, 10, 11, 12, 13) mit der durch die Information spezifizierten Kommunikationseigenschaft vereinbar ist.
- 10 11. Vorrichtung nach einem der vorstehenden Ansprüche, deren Anzeigemittel über Mittel (24a) zur Anzeige durch Änderung einer Blinkfolge verfügt, wenn die Kommunikationseigenschaft des Kommunikationsmittels (9, 10, 11, 12, 13) mit der durch die Information spezifizierten Kommunikationseigenschaft vereinbar ist.
- 15 12. Vorrichtung nach einem der vorstehenden Ansprüche, deren Anzeigemittel (24) einer Taste (24) zur Spezifizierung der Übertragungsleitung zugeordnet ist.
- 20 13. Vorrichtung nach einem der vorstehenden Ansprüche, deren Anzeigemittel (24) über Mittel zur Anzeige einer gemeinsamen Darstellung für den Fall verfügt, daß die Übertragungsleitung von einem anderen Endgerät belegt ist, und für den Fall, daß die Kommunikationseigenschaft des Kommunikationsmittels (9, 10, 11, 12, 13) mit der durch die Information spezifizierten Kommunikationseigenschaft nicht vereinbar ist.
- 25 14. Vorrichtung nach einem der vorstehenden Ansprüche, deren Anzeigemittel über Mittel (24) zur Anzeige des Anstehens eines ankommenden Rufs verfügt, wenn die Kommunikationseigenschaft des Kommunikationsmittels mit der Kommunikationseigenschaft des ankommenden Rufs vereinbar ist.
- 30 15. Kommunikationsverfahren unter Anwendung einer Kommunikationsvorrichtung, mit:
Schnittstellenmitteln (5, 15) zur Belegung einer Übertragungsleitung eines Netzes (14);
über Anzeigemittel (24a) verfügbare Kommunikationsmittel (9, 10, 11, 12, 13);
Anschaltmitteln (4, 6, 7, 8) zur Verbindung der Übertragungsleitung mit den Kommunikationsmitteln;
mit dem Verfahrensschritt:
Steuern der Anzeigemittel (24a) auf der Grundlage der Information aus der Übertragungsleitung,
35 gekennzeichnet durch den weiteren Verfahrensschritt:
Steuern der Anzeigemittel (24a), um so das Anzeigemittel (24a) zur Anzeige zu befähigen, daß einerseits eine Kommunikationseigenschaft der Kommunikationsmittel (9, 10, 11, 12, 13) mit einer durch die Informationen aus der Übertragungsleitung spezifizierten Kommunikationseigenschaft unvereinbar ist, und daß andererseits die Übertragungsleitung in einem Belegzustand ist.
- 40 16. Verfahren nach Anspruch 15 mit dem Verfahrensschritt des Erkennens einer Übertragungseigenschaft eines ankommenden Rufs auf der Grundlage der Information aus der Übertragungsleitung.
- 45 17. Verfahren nach Anspruch 15 oder 16, bei dem das Übertragungsmittel ein Telefon (9, 10, 11) enthält.
- 50 18. Verfahren nach einem der Ansprüche 15 bis 17, mit dem Verfahrensschritt des Anzeigens auf dem Anzeigemittel (24a) einer Aussage darüber, ob die Kommunikationseigenschaft des Übertragungsmittels (9, 10, 11) mit der Kommunikationseigenschaft eines ankommenden, durch die Information spezifizierten Rufs vereinbar ist.
- 55 19. Verfahren nach einem der Ansprüche 15 bis 18, mit dem Verfahrensschritt der Bewirkung einer Farbanzeige in Einklang damit, daß die Kommunikationseigenschaft des Kommunikationsmittels mit der durch die Information spezifizierten Kommunikationseigenschaft vereinbar ist.
20. Verfahren nach einem der Ansprüche 15 bis 19, mit dem Verfahrensschritt des Anzeigens durch Änderung einer Blinkfolge, wenn die Kommunikationseigenschaft des Kommunikationsmittels (9, 10, 11, 12, 13) mit der durch die Information spezifizierten Kommunikationseigenschaft vereinbar ist.



21. Verfahren nach einem der Ansprüche 15 bis 20, mit dem Verfahrensschritt des Anzeigens einer gemeinsamen Darstellung für den Fall, daß die Übertragungsleitung von einem anderen Endgerät belegt ist, und für den Fall, daß die Kommunikationseigenschaft des Kommunikationsmittels mit der durch die Information spezifizierten Kommunikationseigenschaft nicht vereinbar ist.
22. Verfahren nach einem der Ansprüche 15 bis 21, mit dem Verfahrensschritt der Anzeige des Anstehens eines ankommenden Rufs, wenn die Kommunikationseigenschaft des Kommunikationsmittels (9, 10, 11, 12, 13) mit der Kommunikationseigenschaft des ankommenden Rufs vereinbar ist.
23. Verfahren nach einem der Ansprüche 15 bis 22, mit dem Verfahrensschritt des Einstellens der Kommunikationseigenschaft des Übertragungsmittels (9, 10, 11, 12, 13) zur Anzapassung einer durch die Information aus der Übertragungsleitung spezifizierten Kommunikationseigenschaft durch Erkennen der Kommunikationseigenschaft eines ankommenden Rufes an die durch die aus der Übertragungsleitung spezifizierte Information.
24. Verfahren nach einem der Ansprüche 15 bis 23, bei dem das Netz, an welches das Schnittstellenmittel über die Übertragungsleitung verbunden ist, ein ISDN (14) enthält.
25. Verfahren nach einem der Ansprüche 15 bis 24, bei dem das Kommunikationsmittel ein Telefon (9, 10, 11) enthält.
26. Verfahren nach Anspruch 23, bei dem der Verfahrensschritt des Einstellens das Einstellen einer Kommunikationseigenschaft einer durch das Datenendgerät (12, 13) erzeugten Kommunikation beinhaltet.

Revendications

1. Dispositif de communication comprenant :
des moyens d'interface (5, 15) pour connecter une ligne de communication provenant d'un réseau (14) ;
des moyens de communication (9, 10, 11, 12, 13) comprenant des moyens de visualisation (24a) ;
des moyens de connexion (4, 6, 7, 8) pour connecter la ligne de communication et les moyens de communication ; et
des moyens de commande (1, 2, 3) pour commander les moyens de visualisation sur la base d'une information provenant de la ligne de communication, caractérisé en ce que
les moyens de commande (1, 2, 3) sont adaptés pour commander les moyens de visualisation (24a), de façon à permettre aux moyens de visualisation (24a) d'indiquer à la fois qu'un attribut de communication des moyens de communication (9, 10, 11, 12, 13) et un attribut de communication spécifié par l'information provenant de la ligne de communication ne concordent pas, et que la ligne de communication est dans un état occupé.
2. Dispositif selon la revendication 1, dans lequel les moyens de commande (1, 2, 3) comprennent des moyens pour reconnaître un attribut de communication d'un appel entrant, sur la base de l'information qui provient de la ligne de communication.
3. Dispositif selon la revendication 1, dans lequel le réseau auquel les moyens d'interface (5, 15) sont connectés par l'intermédiaire de la ligne de communication comprend un RNIS (14).
4. Dispositif selon l'une quelconque des revendications précédentes, dans lequel les moyens de communication (9, 10, 11) comprennent un adaptateur (29, 30) pour la connexion d'un terminal de données (12, 13).
5. Dispositif selon l'une quelconque des revendications 1 à 3, dans lequel les moyens de communication comprennent un poste téléphonique (10, 11) ayant un adaptateur (29, 30) pour la connexion d'un terminal de données (12, 13).
6. Dispositif selon la revendication 1, dans lequel les moyens de communication comprennent un poste té-



léphonique (9, 10, 11).

- 5 7. Dispositif selon l'une quelconque des revendications précédentes, dans lequel les moyens de visualisation (24a) comprennent des moyens pour visualiser une représentation indiquant s'il y a concordance entre l'attribut de communication des moyens de communication (9, 10, 11) et l'attribut de communication d'un appel entrant qui est spécifié par l'information.
- 10 8. Dispositif selon l'une quelconque des revendications précédentes, comprenant en outre des moyens de fixation (1, 2, 3) pour fixer un attribut de communication des moyens de communication (9, 10, 11).
9. Dispositif selon l'une quelconque des revendications précédentes, dans lequel les moyens de commande (1, 2, 3) comprennent des moyens de comparaison pour comparer l'attribut de communication des moyens de communication à l'attribut de communication qui est spécifié par l'information.
- 15 10. Dispositif selon l'une quelconque des revendications précédentes, dans lequel les moyens de visualisation comprennent des moyens (24a) pour effectuer une visualisation par couleur, conformément au fait que l'attribut de communication des moyens de communication (9, 10, 11, 12, 13) et l'attribut de communication qui est spécifié par l'information concordent ou non.
- 20 11. Dispositif selon l'une quelconque des revendications précédentes, dans lequel les moyens de visualisation comprennent des moyens (24a) pour effectuer une visualisation par le changement d'une cadence de clignotement, conformément au fait que l'attribut de communication des moyens de communication (9, 10, 11, 12, 13) et l'attribut de communication qui est spécifié par l'information concordent ou non.
- 25 12. Dispositif selon l'une quelconque des revendications précédentes, dans lequel les moyens de visualisation (24) sont établis en correspondance avec une touche (24) pour spécifier la ligne de communication.
- 30 13. Dispositif selon l'une quelconque des revendications précédentes, dans lequel les moyens de visualisation (24) comprennent des moyens pour présenter une visualisation commune dans le cas où la ligne de communication est utilisée par un autre terminal, et dans le cas où l'attribut de communication des moyens de communication (9, 10, 11, 12, 13) et l'attribut de communication qui est spécifié par l'information ne concordent pas.
- 35 14. Dispositif selon l'une quelconque des revendications précédentes, dans lequel les moyens de visualisation comprennent des moyens (24) qui sont destinés à visualiser l'existence d'un appel entrant lorsque l'attribut de communication des moyens de communication concorde avec l'attribut de communication de l'appel entrant.
- 40 15. Un procédé de communication utilisant un dispositif de communication comprenant :
des moyens d'interface (5, 15) pour connecter une ligne de communication provenant d'un réseau (14) ;
des moyens de communication (9, 10, 11, 12, 13) comprenant des moyens de visualisation (24a) ;
et
des moyens de connexion (4, 6, 7, 8) pour connecter la ligne de communication et les moyens de
45 communication ;
comprenant l'étape suivante :
on commande les moyens de visualisation (24a) sur la base d'une information provenant de la ligne de communication,
ce procédé étant caractérisé en ce qu'il comprend
50 l'étape supplémentaire qui consiste à commander les moyens de visualisation (24a) de façon à permettre aux moyens de visualisation (24a) d'indiquer à la fois qu'un attribut de communication des moyens de communication (9, 10, 11, 12, 13) et un attribut de communication spécifié par l'information provenant de la ligne de communication sont discordants, et que la ligne de communication est dans un état occupé.
- 55 16. Un procédé selon la revendication 15, comprenant l'étape qui consiste à reconnaître un attribut de communication d'un appel entrant sur la base de l'information qui provient de la ligne de communication.
17. Un procédé selon la revendication 15 ou 16, dans lequel les moyens de communication comprennent un



poste téléphonique (9, 10, 11).

- 5 18. Un procédé selon l'une quelconque des revendications 15 à 17, comprenant l'étape qui consiste à visualiser sur les moyens de visualisation (24a) une représentation indiquant s'il y a concordance entre l'attribut de communication des moyens de communication (9, 10, 11) et l'attribut de communication d'un appel entrant qui est spécifié par l'information.
- 10 19. Un procédé selon l'une quelconque des revendications 15 à 18, comprenant l'étape qui consiste à visualiser par la couleur si l'attribut de communication des moyens de communication et l'attribut de communication qui est spécifié par l'information concordent.
- 15 20. Un procédé selon l'une quelconque des revendications 15 à 19, comprenant l'étape qui consiste à visualiser au moyen de changements d'une cadence de clignotement si l'attribut de communication des moyens de communication (9, 10, 11, 12, 13) et l'attribut de communication qui est spécifié par l'information concordent.
- 20 21. Un procédé selon l'une quelconque des revendications 15 à 20, comprenant l'étape qui consiste à présenter une visualisation commune lorsque la ligne de communication est utilisée par un autre terminal, et dans un cas dans lequel l'attribut de communication des moyens de communication et l'attribut de communication qui est spécifié par l'information ne concordent pas.
- 25 22. Un procédé selon l'une quelconque des revendications 15 à 21, comprenant l'étape qui consiste à visualiser l'existence d'un appel entrant lorsque l'attribut de communication des moyens de communication (9, 10, 11, 12, 13) concorde avec l'attribut de communication de l'appel entrant.
- 30 23. Un procédé selon l'une quelconque des revendications 15 à 22, comprenant les étapes qui consistent à fixer l'attribut de communication des moyens de communication (9, 10, 11, 12, 13) de façon qu'il concorde avec un attribut de communication spécifié par l'information provenant de la ligne de communication, par la reconnaissance de l'attribut de communication d'un appel entrant qui est spécifié par l'information provenant de la ligne de communication.
- 35 24. Un procédé selon l'une quelconque des revendications 15 à 23, dans lequel le réseau auquel les moyens d'interface sont connectés par la ligne de communication, comprend un RNIS (14).
- 40 25. Un procédé selon l'une quelconque des revendications 15 à 24, dans lequel les moyens de communication comprennent un poste téléphonique (9, 10, 11).
- 45 26. Un procédé selon la revendication 23, dans lequel l'étape de fixation comprend la fixation d'un attribut de communication d'une communication qui est produite par le terminal de données (12, 13).
- 50
- 55