



- (51) **International Patent Classification:**
B25H 5/00 (2006.01) *B62B 11/00* (2006.01)
- (21) **International Application Number:**
PCT/US2012/046009
- (22) **International Filing Date:**
10 July 2012 (10.07.2012)
- (25) **Filing Language:** English
- (26) **Publication Language:** English
- (30) **Priority Data:**
61/510,343 21 July 2011 (21.07.2011) US
- (72) **Inventors; and**
- (71) **Applicants :** BRITTINGHAM, Eric, A. [US/US]; 3664 Willow Court, Clarkston, MI 48348 (US). FERGUSON, Kevin, D. [US/US]; 2041 E. Seymour Lake Road, Ortonville, MI 48462 (US).
- (74) **Agent:** BONDY, Brent, L.; MacMillan, Sobanski & Todd, LLC, One Maritime Plaza; 5th Floor, 720 Water Street, Toledo, OH 43604 (US).
- (81) **Designated States** (*unless otherwise indicated, for every kind of national protection available*): AE, AG, AL, AM,

AO, AT, AU, AZ, BA, BB, BG, BH, BR, BW, BY, BZ, CA, CH, CL, CN, CO, CR, CU, CZ, DE, DK, DM, DO, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT, HN, HR, HU, ID, IL, IN, IS, JP, KE, KG, KM, KN, KP, KR, KZ, LA, LC, LK, LR, LS, LT, LU, LY, MA, MD, ME, MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI, NO, NZ, OM, PE, PG, PH, PL, PT, QA, RO, RS, RU, RW, SC, SD, SE, SG, SK, SL, SM, ST, SV, SY, TH, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, ZA, ZM, ZW.

- (84) **Designated States** (*unless otherwise indicated, for every kind of regional protection available*): ARIPO (BW, GH, GM, KE, LR, LS, MW, MZ, NA, RW, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, RU, TJ, TM), European (AL, AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT, LU, LV, MC, MK, MT, NL, NO, PL, PT, RO, RS, SE, SI, SK, SM, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

— *without international search report and to be republished upon receipt of that report (Rule 48.2(g))*

(54) **Title:** CONVERTIBLE CREEPER ASSEMBLY

(57) **Abstract:** A creeper assembly is provided that includes a frame assembly supported on a plurality of wheels for movement along a support surface. The frame assembly includes a seat and a backrest that extends from the seat. The frame assembly is adjustable between a lowered lying position, wherein the seat and the backrest are in a horizontal position at a first height above the support surface, and a raised seated position, wherein the seat is in a horizontal position at a second height above the support surface and the backrest is inclined in an upright position relative to the seat. An actuator is provided on the frame assembly that is operable for adjusting the frame assembly between the lowered lying position and the raised seated position.



WO 2013/012595 A2