

SERVICE-BASED PROCESSING METHOD, TERMINAL DEVICE, AND NETWORK DEVICE

TECHNICAL FIELD

[0001] The disclosure relates to the technical field of information processing, and particularly to a service-based processing method, a terminal device, a network device and a computer storage medium.

BACKGROUND

[0002] When a network supports a voice service (including emergency call voice, hereinafter a voice service for short), the network may send indication information of supporting the voice service to a terminal device. If the network does not directly support the voice service but supports fallback to another system, the network may indicate to the terminal that fallback to the other system is supported by the network side. If the network neither supports the voice service, nor supports fallback to another system, the problem that a behavior of the terminal is unclear may arise.

SUMMARY

[0003] For solving the technical problem, embodiments of the disclosure provide a service-based processing method, a terminal device, a network device and a computer storage medium.

[0004] The embodiments of the disclosure provide a service-based processing method, which may be applied to a terminal device and include the following operation.

[0005] When the terminal device resides in a New Radio (NR) network, whether to select another system or another domain to initiate a service request for a target service

when the target service is initiated is determined based on capability information reported to a network side and/or based on indication transmitted by the network side.

[0006] The embodiments of the disclosure provide a service-based processing method, which may be applied to a network device and include the following operation.

[0007] When a terminal device resides in an NR network, indication is transmitted to the terminal device.

[0008] The embodiments of the disclosure provide a terminal device, which may include a first communication unit and a first processing unit.

[0009] The first communication unit is configured to report capability information to a network side and/or receive indication transmitted by the network side.

[0010] The first processing unit is configured to, when the terminal device resides in an NR network, determine whether to select another system another domain to initiate a service request for a target service when the target service is initiated, based on the capability information reported to the network side and/or based on the indication transmitted by the network side.

[0011] The embodiments of the disclosure provide a network device, which may include a second processing unit and a second communication unit.

[0012] The second processing unit is configured to, when a terminal device resides in an NR network, transmit indication to the terminal device through the second communication unit.

[0013] The second communication unit is configured to send the indication to the terminal device.

[0014] The embodiments of the disclosure provide a terminal device, which may include a processor and a memory configured to store a computer program capable of running in the processor.

[0015] The processor may be configured to run the computer program to execute the

steps of the abovementioned method.

[0016] The embodiments of the disclosure provide a network device, which may include a processor and a memory configured to store a computer program capable of running in the processor.

[0017] The processor may be configured to run the computer program to execute the steps of the abovementioned method.

[0018] The embodiments of the disclosure provide a computer storage medium, which may store computer-executable instructions, the computer-executable instructions being executed to implement the steps of the abovementioned methods.

[0019] According to the technical solutions of the embodiments of the disclosure, the terminal device may determine, when the service request is initiated, whether to select the other system or the other domain according to its own capability information and/or an indication transmitted by the network side. In this way, the terminal device may determine its own behavior in combination with the capability of the terminal device and the indication information of a network, so that a processing behavior of the terminal device for the target service may be clearly learned in condition that the network side does not support a voice service and also does not support fallback to another system.

BRIEF DESCRIPTION OF THE DRAWINGS

[0020] FIG. 1 is a first flowchart of a service-based processing method according to an embodiment of the disclosure.

[0021] FIG. 2 is second first flowchart of a service-based processing method according to an embodiment of the disclosure.

[0022] FIG. 3 is a composition structure diagram of a terminal device according to an embodiment of the disclosure.

[0023] FIG. 4 is a composition structure diagram of a network device according to an

embodiment of the disclosure.

[0024] FIG. 5 is a schematic diagram of a hardware architecture according to an embodiment of the disclosure.

DETAILED DESCRIPTION

[0025] For making the characteristics and technical contents of the embodiments of the disclosure understood in more detail, implementation of the embodiments of the disclosure will be described below in combination with the drawings in detail. The drawings are only adopted for description as references and not intended to limit the embodiments of the disclosure.

[0026] Embodiment 1

[0027] The embodiment of the disclosure provides a service-based processing method, which is applied to a terminal device and includes the following operation.

[0028] When the terminal device resides in an NR network, whether to select another system or another domain to initiate a service request for a target service when the target service is initiated is determined by the terminal device based on capability information reported to a network side and/or based on indication transmitted by the network side.

[0029] Specifically, the capability information is at least used for indicating whether the terminal device supports a capability of fallback to the another system or the another domain.

[0030] The indication transmitted by the network side includes indication information for indicating whether the network side supports the target service or indication information for indicating whether the network side supports fallback of the target service.

[0031] The another system is one of at least one system except the NR network. For example, it may be a system network such as a Long Term Evolution (LTE) network and

a 5th-Generation (5G), 4th-Generation (4G) or 3rd-Generation (3G) network. Exhaustions are omitted herein.

[0032] The other domain is a domain different from a present domain used by the terminal device and includes a Circuit Switched (CS) domain or a Packet Switched (PS) domain.

[0033] It is also to be understood that the present domain used by the terminal device may be one of the CS domain or the PS domain and, correspondingly, the another domain is a domain except the presently used domain. That is, the above processing further includes that a subsequent operation is executed when the terminal device resides in the NR system and a target domain is selected.

[0034] Furthermore, the operation that whether to select the another system or the another domain to initiate the service request for the target service when the target service is initiated is determined based on the capability information reported to the network side and/or based on the indication transmitted by the network side may include the following multiple implementation scenarios.

[0035] A first scenario

[0036] When the capability information of the terminal device represents that the terminal device does not support fallback to the another system or the another domain and the received indication information from the network side represents that the network side supports fallback of the target service to the another system or the another domain, the terminal device selects the another system or the another domain to initiate the service request for the target service.

[0037] The scenario may be described with reference to FIG. 1. The following steps are included.

[0038] In 101, when a terminal device resides in an NR network, the terminal device reports to a network side capability information for indicating that fallback to another system is not supported by the terminal device.

[0039] In 102, after the network side receives the capability information of the terminal, the network side sends to the terminal device indication information for indicating that the another system or another domain may be directly selected by the terminal device to initiate a target service.

[0040] In 103, when the terminal device requires to initiate a related target service, the another system or the another domain is selected by the terminal device to initiate a service request for the target service.

[0041] A second scenario

[0042] When the capability information of the terminal device represents that the terminal device supports the capability of fallback to the other system or the other domain and the indication transmitted by the network side represents that fallback of the target service to the another system or the another domain is not supported by the network side, or the indication transmitted by the network side is not received by the terminal device,

[0043] the terminal device selects the another system or the another domain to initiate the service request for the target service.

[0044] Specifically, when the terminal resides in the NR network, if the terminal device notifies the network side that it supports fallback to the another system or the another domain, but the indication transmitted by the network side represents that the network side does not support fallback to the another system or the another domain, the terminal device selects the another system or the another domain to initiate the service request for the target service.

[0045] Or,

[0046] when the terminal resides in the NR network, if the terminal device notifies the network side that it supports fallback to the another system or the another domain, but does not receive the indication information transmitted by the network side, the terminal device selects the another system or the another domain to initiate the service request for the target service.

[0047] A third scenario

[0048] When the indication transmitted by the network side for representing that the network side supports fallback of the target service to the another system or the another domain is not received by the terminal device, or indication transmitted by the network side for representing that the network side supports the target service is not received by the terminal device, the terminal device selects the another system or the another domain to initiate the service request for the target service.

[0049] Specifically, when the terminal resides in the NR network, if the terminal does not receive an indication about that the network side supports the service or the indication indicating that the network side supports fallback of the service from the network, when initiation of the related service is required, the terminal device selects the another system or another domain to initiate the service request.

[0050] A fourth scenario

[0051] When the capability information of the terminal device represents that the terminal device supports fallback to the another system or the another domain, if indication information for instructing the terminal device to directly select the another system or the another domain to initiate the service request for the target service is received from the network side, the terminal device selects the another system or the another domain to initiate the service request for the target service.

[0052] For example, referring to FIG. 2, the following steps are included.

[0053] In 201, when a terminal device resides in an NR network, the terminal device reports capability information for indicating that the terminal device supports fallback to another system to a network side.

[0054] In 202, when the network side does not support fallback to the another system, the terminal device receives indication sent to the terminal device by the network side for indicating that the another system or another domain may be directly selected to initiate a service.

- [0055] In 203, when the terminal device receives the indication information sent by the network side and needs to initiate the related service, the terminal device selects the another system or another domain to initiate a service request.
- [0056] A fifth scenario
- [0057] When the indication transmitted by the network side is received, if the terminal device is incapable of parsing the indication or the indication represents that fallback of the target service to the another system or the another domain is not supported by the network side, the terminal device selects the another system or the another domain to initiate the service request for the target service.
- [0058] When the indication transmitted by the network side for representing that the network side supports fallback of the target service is received by the terminal device, if the terminal device is incapable of parsing the indication or the terminal device does not support fallback of the service to another network or another system, the terminal device selects the another system or the another domain to initiate the service request for the target service.
- [0059] That is, when the terminal resides in the NR network, if the terminal receives the indication information for indicating that the network side supports fallback of the service from the network, but the terminal cannot understand the indication information or the terminal does not support fallback of the service to the another network or another system, when the related service is required to be initiated, the terminal device selects the another system or another domain to initiate the service request.
- [0060] Or, when the terminal resides in the NR network, if the indication received by the terminal from the network represents that the network side does not support fallback of the target service to the another system or the another domain, the terminal device selects the another system or the another domain to initiate the service request for the target service.
- [0061] It can be seen that, with adoption of the solution, when the service request is initiated, whether to select another system or another domain may be determined by the terminal device according to its own capability information and/or an indication

transmitted by the network side. In such a manner, the terminal device may determine its own behavior in combination with the capability of the terminal device and the indication of a network, so that a processing behavior of the terminal device for the target service may be clearly learned if the network side does not support a voice service and also does not support fallback to another system.

[0062] Embodiment 2

[0063] The embodiment of the disclosure provides a service-based processing method, which is applied to a network device and includes the following operation.

[0064] When a terminal device resides in an NR network, indication information is transmitted to the terminal device.

[0065] Specifically, the capability information is at least used for indicating whether the terminal device supports fallback to another system or another domain.

[0066] The indication transmitted by the network side includes an indication for indicating whether the network side supports the target service or an indication for indicating whether the network side supports fallback of the target service to another system or another domain.

[0067] The another system is one of at least one system except the NR network. For example, it may be a system network such as an LTE network and a 5G, 4G or 3G network. Exhaustions are omitted herein.

[0068] The another domain is a domain different from a present domain used by the terminal device and includes a CS domain or a PS domain.

[0069] It is also to be understood that the present domain used by the terminal device may be one of the CS domain or the PS domain and, correspondingly, the another domain is a domain except the presently used domain. That is, the above processing further includes that a subsequent operation is executed when the terminal device resides in the NR system and a target domain is selected by the terminal device.

[0070] Furthermore, before the operation that the indication information is transmitted

to the terminal device, the method further includes the following operation.

[0071] The capability information of the terminal device is received by the network device, the capability information being at least configured to indicate whether the terminal device supports fallback to another system or another domain.

[0072] The operation that whether to select another system or another domain to initiate the service request for the target service when the target service is initiated is determined by the terminal device based on the capability information reported to the network side and/or based on the indication transmitted by the network side may include the following multiple implementation scenarios.

[0073] A first scenario

[0074] The scenario may be described with reference to FIG. 1. The following steps are included.

[0075] In 101, when a terminal device resides in an NR network, the terminal device reports to a network side capability information for indicating that the terminal device does not support fallback to another system.

[0076] In 102, after the network side receives the capability information of the terminal, the network side sends to the terminal device indication for indicating that another system or another domain may be directly selected by the terminal device to initiate a target service.

[0077] In 103, when the terminal device is required to initiate a related target service, the terminal device selects the another system or the another domain to initiate a service request for the target service.

[0078] A second scenario

[0079] When the terminal resides in the NR network, if the terminal device notifies the network side that it supports fallback to the another system or another domain, but the indication transmitted by the network side represents that the network side does not support fallback to the another system or another domain, the terminal device selects the

another system or another domain to initiate the service request for the target service.

[0080] When the terminal resides in the NR network, if the terminal device notifies the network side that it supports fallback to the another system or another domain, but does not receive indication transmitted by the network side, the terminal device selects the another system or another domain to initiate the service request for the target service.

[0081] A third scenario

[0082] When the terminal resides in the NR network, if the terminal does not receive an indication about that the network supports the service or the indication about that the network supports fallback of the service from the network, when the related service is required to be initiated, the terminal device selects the another system or domain to initiate the service request.

[0083] A fourth scenario

[0084] Referring to FIG. 2, the following steps are included.

[0085] In 201, when a terminal device resides in an NR network, the terminal device reports to a network side capability information for indicating that fallback to another system is supported.

[0086] In 202, when the network side does not support fallback to the another system, the terminal device receives indication for indicating that the another system or another domain may be directly selected by the terminal device to initiate a service from the network side.

[0087] In 203, After the terminal device receives the indication from the network side, when initiation of the related service is required, the terminal device selects the another system or another domain to initiate a service request.

[0088] A fifth scenario

[0089] When the terminal resides in the NR network, if the terminal receives the indication for indicating that the network supports fallback of the service from the

network, but the terminal may not understand the indication or the terminal does not support fallback of the service to another network or system, when the related service is required to be initiated, the terminal device selects the another system or another domain to initiate the service request.

[0090] Or, when the terminal resides in the NR network, if the indication received by the terminal from the network represents that fallback of the target service to the another system or the another domain is not supported by the network, the terminal device selects the another system or the another domain to initiate the service request for the target service.

[0091] It can be seen that, with adoption of the solution, when the service request is initiated, whether to select the other system or the other domain may be determined by the terminal device according to its own capability information and/or an indication transmitted by the network side. In such a manner, the terminal device may determine its own behavior in combination with the capability of the terminal device and the indication of a network, so that a processing behavior of the terminal device for the target service may be clearly learned if the network side does not support a voice service and also does not support fallback to another system.

[0092] Embodiment 3

[0093] The embodiment of the disclosure provides a terminal device, which, as shown in FIG. 3, includes a first communication unit 31 and a first processing unit 32.

[0094] The first communication unit 31 is configured to report capability information to a network side and/or receive indication transmitted by the network side.

[0095] The first processing unit 32 is configured to, when the terminal device resides in an NR network, determine, when the target service is initiated, whether to select another system or another domain to initiate a service request for a target service, based on the capability information reported to the network side and/or based on the indication transmitted by the network side.

[0096] Specifically, the capability information is at least used for indicating whether

the terminal device supports a capability of fallback to the another system or the another domain.

[0097] The indication information transmitted by the network side includes an indication for indicating whether the network side supports the target service or an indication for indicating whether the network side supports fallback of the target service.

[0098] The another system is one of at least one system except the NR network. For example, it may be another system network such as an LTE network and a 5G, 4G or 3G network. Exhaustions are omitted herein.

[0099] The other domain is a domain different from a present domain used by the terminal device and includes a CS domain or a PS domain.

[00100] It is also to be understood that the present domain used by the terminal device may be one of the CS domain or the PS domain and, correspondingly, the another domain is a domain except the presently used domain. That is, the above processing further includes that a subsequent operation is executed when the terminal device resides in the NR system and after a target domain is selected.

[00101] Furthermore, the operation that whether to select the another system or the another domain to initiate the service request for the target service when the target service is initiated is determined by the terminal device based on the capability information reported to the network side and/or based on the indication transmitted by the network side may include the following multiple implementation scenarios.

[00102] A first scenario

[00103] The first processing unit 32 is configured to, when the capability information reported to the network side represents that the terminal device does not support fallback to another system or another domain and the received indication information transmitted by the network side represents that fallback of the target service to the another system or the another domain is supported, select, by the terminal device, the another system or the another domain to initiate the service request for the target service.

[00104] The scenario may include the following operations: when a terminal device resides in an NR network, the terminal device reports capability information indicating that fallback to another system is not supported to a network side; after the network side receives the capability information of the terminal, the network side sends indication information indicating that the another system or another domain may be directly selected by the terminal device to initiate a target service to the terminal device; and when the terminal device requires to initiate the related target service, the terminal device selects the another system or the another domain to initiate a service request for the target service.

[00105] A second scenario

[00106] The first processing unit 32 is configured to, when the capability information of the terminal device represents that the terminal device supports fallback to another system or another domain, and the received indication from the network side represents that fallback of the target service to the another system or the another domain is not supported or the indication transmitted by the network side is not received by the terminal device,

[00107] select, by the terminal device, the another system or the another domain to initiate the service request for the target service.

[00108] Specifically, when the terminal resides in the NR network, if the terminal device notifies the network side that it supports fallback to the another system or the another domain, but the indication transmitted by the network side represents that the network side does not support fallback to the another system or the another domain, the terminal device selects the another system or the another domain to initiate the service request for the target service.

[00109] Or, when the terminal resides in the NR network, if the terminal device notifies the network side that it supports fallback to the another system or the another domain but does not receive the indication transmitted by the network side, the terminal device selects the another system or the another domain to initiate the service request for the target service.

[00110] A third scenario

[00111] The first processing unit 32 is configured to, when the indication transmitted by the network side for representing that the network side supports fallback of the target service to another system or another domain is not received, or indication transmitted by the network side for representing that the target service is supported is not received, select, by the terminal device, the another system or the another domain to initiate the service request for the target service.

[00112] Specifically, when the terminal resides in the NR network, if the terminal does not receive an indication about that the service is supported or the indication indicating that fallback of the service is supported from the network, when the related service is required to be initiated, the terminal device selects the another system or domain to initiate the service request.

[00113] A fourth scenario

[00114] The first processing unit 32 is configured to, when the capability information of the terminal device represents that the terminal device supports fallback to another system or another domain, if indication information for instructing the terminal device to directly select the another system or the another domain to initiate the service request for the target service is received from the network side, select, by the terminal device, the another system or the another domain to initiate the service request for the target service.

[00115] For example, the following operations are included: when a terminal device resides in an NR network, the terminal device reports capability information indicating that fallback to another system is supported to a network side; when the network side does not support fallback to the another system, the terminal device receives indication for indicating that the another system or another domain may be directly selected by the terminal device to initiate a service from the network side; and when the terminal device receives the indication sent by the network side, when it is required to initiate the related service, the terminal device selects the another system or another domain to initiate a service request.

[00116] A fifth scenario

- [00117] The first processing unit 32 is configured to, when the indication transmitted by the network side is received, if the terminal device is incapable of parsing the indication or the indication represents that fallback of the target service to another system or another domain is not supported, select, by the terminal device, the another system or the another domain to initiate the service request for the target service,
- [00118] and, when the indication for representing that fallback of the target service is supported is received from the network side, if the terminal device is incapable of parsing the indication or the terminal device does not support fallback of the service to another network or system, select, by the terminal device, the other system or the other domain to initiate the service request for the target service.
- [00119] That is, when the terminal resides in the NR network, if the terminal receives the indication indicating that fallback of the service is supported from the network, but the terminal may not understand the indication or the terminal does not support fallback of the service to the another network or system, when the related service is required to be initiated, the terminal device selects the another system or domain to initiate the service request.
- [00120] Or, when the terminal resides in the NR network, if the indication received by the terminal from the network represents that fallback of the target service to the another system or the another domain is not supported, the terminal device selects the another system or another domain to initiate the service request for the target service.
- [00121] It can be seen that, with adoption of the solution, whether to select another system or another domain when the service request is initiated may be determined by the terminal device according to its own capability information and/or an indication transmitted by the network side. In such a manner, the terminal device may determine its own behavior in combination with the capability of the terminal device and the indication information of a network, so that a processing behavior of the terminal device for the target service may be clearly learned if the network side does not support a voice service and also does not support fallback to another system.
- [00122] Embodiment 4

- [00123] The embodiment of the disclosure provides a network device, which, as shown in FIG. 4, includes a second processing unit 41 and a second communication unit 42.
- [00124] The second processing unit 41 is configured to, when a terminal device resides in an NR network, transmit indication information to the terminal device through the second communication unit.
- [00125] The second communication unit 42 is configured to send the indication information to the terminal device.
- [00126] Specifically, the capability information is at least used for indicating whether the terminal device supports fallback to another system or another domain.
- [00127] The indication transmitted by the network side includes an indication for indicating whether the network side supports the target service or an indication for indicating whether the network side supports fallback of the target service.
- [00128] The other system is at least one system except the NR network. For example, it may be another system network such as an LTE network and a 5G, 4G or 3G network. Exhaustions are omitted herein.
- [00129] The other domain is a domain different from a domain presently used by the terminal device and includes a CS domain or a PS domain.
- [00130] It is also to be understood that the domain presently used by the terminal device may be one of the CS domain or the PS domain and, correspondingly, the other domain is the other domain except the presently used domain. That is, the above processing further includes that a subsequent operation is executed when the terminal device resides in the NR system and selects a target domain.
- [00131] Furthermore, before the operation that the indication is transmitted to the terminal device, the method further includes the following operation.
- [00132] The capability information of the terminal device is received, the capability information being at least configured to indicate whether the terminal device supports the capability of fallback to another system or another domain.

[00133] The operation that whether to select another system or another domain to initiate the service request for the target service when the target service is initiated is determined based on the capability information reported to the network side and/or based on the indication transmitted by the network side may include the following multiple implementation scenarios.

[00134] A first scenario

[00135] When a terminal device resides in an NR network, the terminal device reports capability information indicating that fallback to another system is not supported to a network side; after the network side receives the capability information of the terminal, the network side sends indication indicating that another system or another domain may be directly selected by the terminal device to initiate a target service to the terminal device; and when the terminal device requires to initiate the related target service, the terminal device selects the another system or another domain to initiate a service request for the target service.

[00136] A second scenario

[00137] When the terminal resides in the NR network, if the terminal device notifies the network side that it supports fallback to another system or another domain but the indication transmitted by the network side represents that the network side does not support fallback to the another system or the another domain, the terminal device selects the another system or the another domain to initiate the service request for the target service.

[00138] Or, when the terminal resides in the NR network, if the terminal device notifies the network side that it supports fallback to another system or another domain but does not receive indication transmitted by the network side, the terminal device selects the another system or the another domain to initiate the service request for the target service.

[00139] A third scenario

[00140] When the terminal resides in the NR network, if the terminal does not receive an indication about that the service is supported or the indication for indicating that

fallback of the service is supported from the network, when the related service is required to be initiated, the terminal device selects another system or another domain is selected to initiate the service request.

[00141] A fourth scenario

[00142] When a terminal device resides in an NR network, the terminal device reports capability information indicating that fallback to another system is supported to a network side; when the network side does not support fallback to the another system, the terminal device receives indication for indicating that the another system or another domain may be directly selected by the terminal device to initiate a service from the network side; and when the terminal device receives the indication sent by the network side and needs to initiate the related service, the terminal device selects the another system or another domain to initiate a service request.

[00143] A fifth scenario

[00144] When the terminal resides in the NR network, if the terminal receives the indication for indicating that fallback of the service is supported from the network, but the terminal may not understand the indication or the terminal does not support fallback of the service to another network or another system, when the related service is required to be initiated, the terminal device selects the another system or another domain to initiate the service request.

[00145] Or, when the terminal resides in the NR network, if the indication received by the terminal from the network represents that the network does not support fallback of the target service to another system or another domain, the terminal device selects the other system or the other domain to initiate the service request for the target service.

[00146] It can be seen that, with adoption of the solution, whether to select another system or another domain when the service request is initiated may be determined by the terminal device according to its own capability information and/or an indication transmitted by the network side. In such a manner, the terminal device may determine its own behavior in combination with its own capability and the indication information of a network, so that a processing behavior of the terminal device for the target service may

be clearly learned if the network side does not support a voice service and also does not support fallback to another system.

[00147] An embodiment of the disclosure also provides a hardware composition architecture of a terminal device or a network device, which, as shown in FIG. 5, includes at least one processor 51, a memory 52 and at least one network interface 53. Each component is coupled together through a bus system 54. It can be understood that the bus system 54 is configured to implement connection and communication between these components. The bus system 54 includes a data bus and further includes a power bus, a control bus and a state signal bus. However, for clear description, various buses in FIG. 5 are marked as the bus system 54.

[00148] It can be understood that the memory 52 in the embodiment of the disclosure may be a volatile memory or a nonvolatile memory, or may include both the volatile and nonvolatile memories.

[00149] In some implementation modes, the memory 52 stores the following elements, executable modules or data structures, or a subset thereof or an extended set thereof: an operating system 521 and an application program 522.

[00150] Herein, the processor 51 is configured to be capable of processing the steps of the method in embodiment 1 or 2, which will not be elaborated herein.

[00151] An embodiment of the disclosure provides a computer storage medium, which stores computer-executable instructions, the computer-executable instructions being executed to implement the steps of the method in embodiment 1 or 2.

[00152] When being implemented in form of software functional module and sold or used as an independent product, the device of the embodiments of the disclosure may also be stored in a computer-readable storage medium. Based on such an understanding, the technical solutions of the embodiments of the disclosure substantially or parts making contributions to the conventional art may be embodied in form of software product, and the computer software product is stored in a storage medium, including a plurality of instructions configured to enable a computer device (which may be a personal computer, a server, a network device or the like) to execute all or part of the method in each

embodiment of the disclosure. The storage medium includes: various media capable of storing program codes such as a U disk, a mobile hard disk, a Read Only Memory (ROM), a magnetic disk or an optical disk. Therefore, the embodiments of the disclosure are not limited to any specific hardware and software combination.

[00153] Correspondingly, the embodiments of the disclosure also provide a computer storage medium, in which a computer program is stored, the computer program being configured to execute the data scheduling method of the embodiments of the disclosure.

[00154] Although the preferred embodiments of the disclosure have been disclosed for the exemplary purposes, those skilled in the art may realize that it is also possible to make various improvements, additions and replacements. Therefore, the scope of the disclosure should not be limited to the abovementioned embodiments.

CLAIMS

1. A service-based processing method, the method applied to a terminal device and comprising:

when the terminal device resides in a New Radio (NR) network, determining whether to select another system or another domain to initiate a service request for a target service when the target service is initiated, based on capability information reported to a network side and/or based on indication transmitted by the network side.

2. The method of claim 1, wherein

the capability information is at least used for indicating whether the terminal device supports fallback to the another system or the another domain;

the indication transmitted by the network side comprises an indication for indicating whether the network side supports the target service or an indication for indicating whether the network side supports fallback of the target service;

the another system is one of at least one system except the NR network; and

the another domain is a domain different from a present domain used by the terminal device, and comprises a Circuit Switched (CS) domain or a Packet Switched (PS) domain.

3. The method of claim 1, wherein determining whether to select the another system or the another domain to initiate the service request for the target service when the target service is initiated, based on the capability information reported to the network side and/or based on the indication transmitted by the network side comprises:

when the capability information of the terminal device represents that the terminal device does not support fallback to the another system or the another domain, and the

indication transmitted by the network side represents that the network side supports fallback of the target service to the another system or the another domain,

selecting, by the terminal device, the another system or the another domain to initiate the service request for the target service.

4. The method of claim 1, wherein determining whether to select the another system to initiate the service request for the target service when the target service is initiated, based on the capability information reported to the network side and/or based on the indication transmitted by the network side comprises:

when the capability information of the terminal device represents that the terminal device supports fallback to the another system or the another domain, and the indication transmitted by the network side represents that the network side does not support fallback of the target service to the another system or the another domain, or the indication transmitted by the network side is not received,

selecting, by the terminal device, the another system or the another domain to initiate the service request for the target service.

5. The method of claim 1, wherein determining whether to select the another system to initiate the service request for the target service when the target service is initiated, based on the capability information reported to the network side and/or based on the indication transmitted by the network side comprises:

when the indication transmitted by the network side for indicating that the network side supports fallback of the target service to the another system or the another domain is not received, or indication for indicating that the network side supports the target service is not received from the network side,

selecting, by the terminal device, the another system or the another domain to initiate the service request for the target service.

6. The method of claim 1, wherein determining whether to select the another system to initiate the service request for the target service when the target service is initiated, based on the capability information reported to the network side and/or based on the indication transmitted by the network side comprises:

when the capability information of the terminal device represents that the terminal device supports fallback to the another system or the another domain, if indication for instructing the terminal device to directly select the another system or the another domain to initiate the service request for the target service is received from the network side,

selecting, by the terminal device, the another system or the another domain to initiate the service request for the target service.

7. The method of claim 1, wherein determining whether to select the another system to initiate the service request for the target service when the target service is initiated, based on the capability information reported to the network side and/or based on the indication transmitted by the network side comprises:

when the indication transmitted by the network side is received, if the terminal device is incapable of parsing the indication or the indication represents that the network side does not support fallback of the target service to the another system or the another domain,

selecting, by the terminal device, the another system or the another domain to initiate the service request for the target service.

8. The method of claim 1, wherein determining whether to select the another system to initiate the service request for the target service when the target service is initiated, based on the capability information reported to the network side and/or based on the indication transmitted by the network side comprises:

when the indication for representing that the network side supports fallback of the target service is received from the network side, if the terminal device is incapable of parsing the indication or the terminal device does not support fallback of the target service to another network or system,

selecting, by the terminal device, the another system or the another domain to initiate the service request for the target service.

9. A service-based processing method, the method applied to a network device and comprising:

when a terminal device resides in a New Radio (NR) network, transmitting indication to the terminal device.

10. The method of claim 9, wherein

the indication comprises: an indication for indicating whether a network side supports a target service, or an indication for indicating whether the network side supports fallback of the target service;

the another system is one of at least one system except the NR network; and

the another domain is a domain different from a present domain used by the terminal device and comprises a Circuit Switched (CS) domain or a Packet Switched (PS) domain.

11. The method of claim 9, before transmitting the indication to the terminal device, further comprising:

receiving capability information of the terminal device, the capability information being at least used for indicating whether the terminal device supports fallback to the another system or the another domain.

12. A terminal device, comprising:

a first communication unit configured to report capability information to a network side and/or receive indication transmitted by the network side; and

a first processing unit configured to, when the terminal device resides in a New Radio (NR) network, determine whether to select another system or another domain to initiate a service request for a target service when the target service is initiated, based on the capability information reported to the network side and/or based on the indication transmitted by the network side.

13. The terminal device of claim 12, wherein

the capability information is at least used for indicating whether the terminal device supports fallback to the another system or the another domain;

the indication transmitted by the network side comprises an indication for indicating whether the network side supports the target service or an indication for indicating whether the network side supports fallback of the target service;

the another system is one of at least one system except the NR network; and

the another domain is a domain different from a present domain used by the terminal device, and comprises a Circuit Switched (CS) domain or a Packet Switched (PS) domain.

14. The terminal device of claim 12, wherein the first processing unit is configured to:

when the capability information reported to the network side represents that the terminal device does not support fallback to the another system or the another domain, and the indication transmitted by the network side represents that the network side supports fallback of the target service to the another system or the another domain, select the another system or

the another domain to initiate the service request for the target service.

15. The terminal device of claim 12, wherein the first processing unit is configured to:

when the capability information of the terminal device represents that the terminal device supports fallback to the another system or the another domain, and the indication transmitted by the network side represents that the network side does not support fallback of the target service to the another system or the another domain, or the indication transmitted by the network side is not received, select the another system or the another domain to initiate the service request for the target service.

16. The terminal device of claim 12, wherein the first processing unit is configured to:

when the indication for representing that the network side supports fallback of the target service to the another system or the another domain is not received from the network side, or indication for representing that the network side supports the target service is not received from the network side, select the another system or the another domain to initiate the service request for the target service.

17. The terminal device of claim 12, wherein the first processing unit is configured to:

when the capability information reported to the network side represents that the terminal device supports fallback to the another system or the another domain, if indication for instructing the terminal device to directly select the another system or the another domain to initiate the service request for the target service is received from the network side, select the another system or the another domain to initiate the service request for the target service.

18. The terminal device of claim 12, wherein the first processing unit is configured to:

when the indication transmitted by the network side is received, if the terminal device is incapable of parsing the indication or the indication represents that the network side does not support fallback of the target service to the another system or the another domain, select the another system or the another domain to initiate the service request for the target service.

19. The terminal device of claim 12, wherein the first processing unit is configured to:

when the indication transmitted by the network side for representing that the network side supports fallback of the target service is received, if the terminal device is incapable of parsing the indication or the terminal device does not support fallback of the service to another network or system, select, by the terminal device, the another system or the another domain to initiate the service request for the target service.

20. A network device, comprising:

a second processing unit configured to, when a terminal device resides in a New Radio (NR) network, transmit indication to the terminal device through a second communication unit; and

a second communication unit configured to send the indication to the terminal device.

21. The network device of claim 20, wherein

the indication transmitted by the network side comprises an indication for indicating whether a network side supports a target service or an indication for indicating whether the network side supports fallback of the target service;

the another system is one of at least one system except the NR network; and

the another domain is a domain different from a present domain used by the terminal device and comprises a Circuit Switched (CS) domain or a Packet Switched (PS) domain.

22. The network device of claim 20, wherein the second communication unit is configured to receive capability information of the terminal device, the capability information being at least used for indicating whether the terminal device supports fallback to the another system or the another domain.

23. A terminal device, comprising a processor and a memory configured to store a computer program capable of running in the processor,

wherein the processor is configured to run the computer program to execute the steps of the method of any one of claims 1-8.

24. A network device, comprising a processor and a memory configured to store a computer program capable of running in the processor,

wherein the processor is configured to run the computer program to execute the steps of the method of any one of claims 9-11.

25. A computer storage medium, having stored therein computer-executable instructions, wherein the computer-executable instructions, when being executed by a computer, enable the computer to implement the steps of the method of any one of claims 1-11.