

SEAL RING FOR FOIL-SEALING A CONTAINER

The present disclosure relates to seal rings and, more particularly, to seal rings for sealing containers, for example, glass containers.

5 **Background and Summary of the Disclosure**

Glass containers often include a base, a finish, and a body extending therebetween. The container finish, in turn, includes a sealing surface to which a removable foil may be secured in order to seal the container. Prior to securing the foil to the sealing surface, the sealing surface is conventionally prepared by, for example, applying a cold end coating thereto.

0 The coating may be applied in a number of ways including by spray- or roller-coating.

A general object of the present disclosure is to provide a foil-sealed container that does not require that a cold end coating be applied to a sealing surface of the container finish to prepare the sealing surface for securing the foil thereto.

The present disclosure embodies a number of aspects that can be implemented
5 separately from or in combination with each other.

A package, in accordance with one aspect of the present disclosure, includes a container including a longitudinal axis extending therethrough and having a mouth, an axially-facing sealing surface, and an opening in the sealing surface. The package further includes a seal ring having a base with a projection, wherein the projection is received in the sealing surface
0 opening thereby securing the ring to the container. The package still further includes a foil sealingly and removably coupled to the ring.

In accordance with another aspect of the present disclosure, a seal ring for sealing a container includes a base including a longitudinal axis extending therethrough and having a top

surface, an undersurface opposite the top surface, and a projection extending from the undersurface in an axial direction, wherein the projection is configured to be received by a complementary opening in the container.

5 In accordance with a further aspect of the present disclosure, a method of assembling a container and a seal ring includes heating a least a portion of the container to a predetermined temperature sufficient to cause at least a portion of the seal ring to melt when coupled to the container, and coupling the seal ring to the container when the container is at the predetermined temperature such that a portion of the seal ring melts and conforms to a sealing surface of the container. In an embodiment, the coupling step includes aligning a projection of
0 the seal ring with an opening in the sealing surface of the container, and pressing the seal ring in an axial direction onto the container to press the projection into the opening in the sealing surface.

Brief Description of the Drawings

The disclosure, together with additional objects, features, advantages and aspects
5 thereof, will best be understood from the following description, the appended claims and the accompanying drawings, in which:

FIG. 1 is a perspective view of a package in accordance with an illustrative embodiment of the present disclosure, and including a container, a seal ring, and a foil sealingly and removably coupled to the seal ring;

0 FIG. 2 is a perspective view of a container of the package of FIG. 1 having a seal ring assembled therewith;

FIG. 3 is a fragmentary sectional view of one illustrative embodiment of the package of FIG. 1, illustrating the package in an assembled and sealed condition; and

FIG. 4 is a flow chart depicting an illustrative embodiment of a method of assembling a container and a seal ring.

Detailed Description of Preferred Embodiments

FIG. 1 illustrates a package 10 including a container 12, a seal ring 14 coupled to
5 or assembled with the container 12, and a foil 16 sealingly and removably coupled to the seal ring 14. As described in U.S. Patent Application Serial No. 13/892,727, filed on May 13, 2013 (Assignee's Docket No. 19118), assigned to the assignee hereof, and hereby incorporated herein by reference in its entirety, the seal ring 14 and the removable foil 16 are configured to close and seal the container 12 when the foil 16 is assembled with the seal ring 14, and the seal ring 14 is
0 assembled with the container 12. The package 10 may be used to package any number of goods or products. For instance, the package 10 may be used to package food products, for example and without limitation, pickles, baby food, salsa, peppers, spaghetti sauces, and jams, to cite a few possibilities. The package 10 also may be used to package products other than food products, including, but not limited to, liquids, gels, powders, particles, and the like. Each of the
5 container 12 and the seal ring 14 include or define a respective longitudinal axis (i.e., longitudinal axis A, in the case of container 12; and longitudinal axis B, in the case of seal ring 14) that are coincident with each other when the container 12 and the seal ring 14 are assembled together as illustrated in FIGS. 1 and 2.

The container 12 may be composed of glass or any other material suitable for
0 containing food products, and may comprise a bowl, a jar, or a cup, to cite a few possibilities. With reference to FIG. 2, the container 12 includes a base 18 and a body 20 extending from the base 18. In certain embodiments, the container 12 also may include a shoulder (not shown) extending from the body 20 and a neck (not shown) extending from the shoulder or directly from

the body 20. In any event, and with reference to FIG. 3, the container 12 further comprises a finish 22 extending axially from the body 20 that includes an open mouth 24 surrounded by a sealing lip or surface 26. As illustrated in FIG. 3, the sealing surface 26 is an axially-facing surface that faces away from the container body 20, and has one or more openings 28 disposed
5 therein. In one embodiment, the one or more openings 28 comprises a single, continuous annular channel; while in another embodiment, the one or more openings 28 may comprise a plurality of spaced apart channels, grooves, or pockets that together form a discontinuous annular channel or array. In any event, and as will be described in greater detail below, the opening(s) 28 is/are sized and shaped to receive and mate with one or more complementary projections 42 of the seal
0 ring 14. For purposes of illustration, the description below will be with respect to an embodiment wherein the one or more openings 28 comprises a single, continuous annular channel in the sealing surface 26, though the present disclosure is not limited to such an arrangement.

In addition to the mouth 24 and the sealing surface 26, the container finish 22
5 further may include an external or radially outwardly extending engagement element 30 that surrounds the mouth 24 and that, in an embodiment, is configured to engage a portion of the seal ring 14 when the container 12 and seal ring 14 are assembled together. The engagement element 30 may comprise, for example and without limitation, a bead (e.g., crown bead), a flange, a lip, or other suitable feature. The engagement element 30 may extend completely circumferentially
0 around the container finish 22; alternatively, it may comprise multiple discontinuous segments disposed about the circumference of the finish 22. The container finish 22 still further includes an inner, radially inwardly-facing surface 31 that, in an embodiment, is also configured to

engage a portion of the seal ring 14 when the container 12 and the seal ring 14 are assembled together.

The seal ring 14 may be of an integral one-piece construction, or of a multiple-piece construction, and may be composed of metal, plastic, or any other material suitable for closing and sealing a container in the manner described herein. When seal ring 14 is assembled with the container 12, the ring 14 encircles the mouth 24 of the container 12. The seal ring 14 is annular with an inner diameter or opening or radially inner periphery, and an outer diameter or radially outer periphery. Additionally, in an embodiment, the seal ring 14 may be applied to the container 12 when the sealing surface 26 thereof has a tin oxide coating but not a cold end coating that is conventionally required for the foil-sealing of glass containers. In the embodiment illustrated in FIG. 3, the seal ring 14 includes a base 32, a radially outer portion 34, and an inner seal 36.

The base 32 includes a first or top surface 38, and a second or undersurface 40 opposite the top surface 38. The top surface 38 is an axially-facing surface and comprises a sealing surface to which, as will be described below, the foil 16 may be coupled. The undersurface 40 is also an axially-facing surface, however, it faces in an axial direction that is opposite that in which the top surface 38 faces (i.e., the top surface 38 and the undersurface 40 face in opposite directions). The longitudinal axis B of the seal ring 14 extends perpendicular to a plane extending along one of the base surfaces 38, 40, and centrally with respect to the outer radial periphery of the seal ring 14.

In addition to the top surface 38 and the undersurface 40, the base 32 further includes one or more projections 42 extending in an axial direction from the undersurface 40. As used herein, the term “axial” includes oriented generally along an axis but is not limited to a

direction strictly parallel to the axis. In one embodiment, the one or more projections 42 comprises a single, continuous annular projection; while in another embodiment, the one or more projections 42 may comprise a plurality of spaced apart projections that together form, for example, a discontinuous annular projection or an array. In any event, the projection(s) 42 is/are
5 configured to be received within and mated with complementary opening(s) 28 in the container finish sealing surface 26. For purposes of illustration, the description below will be with respect to an embodiment wherein the one or more projections 42 comprises a single, continuous annular projection that is configured for mating with the annular channel in the container finish sealing surface 26, though the present disclosure is not limited to such an arrangement.

0 As shown in the embodiment illustrated in FIG.3, the projection 42 includes one or more barbs or protrusions 44 extending radially therefrom. As used herein, the term “radial” includes oriented generally perpendicular to an axis but is not limited to a direction that is strictly perpendicular to the axis. The barb(s) 44 are configured to engage the inner surface of the channel when the projection 42 is disposed within the opening 28 (i.e., when the seal ring 14 is
5 assembled with the container 12) and act to retain the projection 42 therein. In any event, the mating of the projection 42 and the opening 28 serves to secure the seal ring 14 to the container 12. In addition to the mechanical fit created by the mating of the projection 42 and opening 28 securing the seal ring 14 to the container 12, in an embodiment, an adhesive, for example, and without limitation, plastisol or any other FDA or foodstuff approved material or sealing adhesive
0 material, may also be utilized. This adhesive may be applied to one or both of the container finish sealing surface 26 (which may, but does not necessarily have to, include the inner surfaces of the opening 28), and/or the undersurface 40 of the seal ring 14. In an embodiment, the coupling or assembly of the seal ring 14 with the container 12 renders the seal ring 14

substantially non-removable from the container 12, meaning that, by design intent, the seal ring 14 is not intended to be removed from the container 12 without destroying or at least damaging the container 12 and/or the seal ring 14.

5 The radially outer portion 34 of the seal ring 14 extends away from the base 32 in an axial direction (i.e., in an axial downward direction) such that it is generally perpendicular to the base 32. The outer portion 34 includes an inner surface 46 and an outer surface 48. The inner surface 46 is configured to engage an outer surface of the container finish 22 when the seal ring 14 is assembled with the container 12. In an embodiment, the radially outer portion 34 may be elastically deformable so as to allow for the coupling of seal ring 14 to the container 12 (i.e.,
0 the outer portion 34 may be configured to deflect in the manner described below). In another embodiment, the radially outer portion 34 may take the form of the radially outer portion described in U.S. Patent Application Serial No. 13/892,727, the entire contents of which were incorporated herein by reference above, and as such, may “snap” over the engagement element 30 of the container finish 22. In any case, the radially outer portion 34 may be disposed at the
5 radially outermost point of the base 32, though the present disclosure is not limited to such an arrangement.

The inner seal 36 of the seal ring 14 is operative to provide, at least in part, a seal between the seal ring 14 and the container 12. The seal 36 may comprise any number of seals, for example, a plug seal, a valve seal, or any other suitable seal. For purposes of illustration, the
0 description below will be with respect to an embodiment wherein the inner seal 36 comprises a valve seal (i.e., “inner valve seal 36”), though the present disclosure is not limited to such an embodiment. One benefit of a valve seal, among potentially others, is that it is configured such that the seal created thereby is improved with the application of a vacuum to the interior of the

container 12 (e.g., as the pressure inside the container 12 decreases, the seal formed between the inner valve seal 36 and the container 12 is tightened).

As with the outer portion 34 described above, in an embodiment, the inner valve seal 36 includes an inner surface 50 and an outer surface 52. The inner surface 50 is configured to engage the mouth 24 of the container finish 22 when the seal ring 14 is assembled with the container 12. More specifically, in an embodiment, the inner valve seal 36 may be elastically deformable such that it may be biased into a sealing engagement with the mouth 24 or the inner finish surface 31 of the container 12, thereby forming a liquid and/or air tight seal between the seal ring 14 and the container 12 (i.e., the valve seal 36 may be configured to deflect in the manner described below). In another embodiment, the inner valve seal 36 may take the form of the inner seal described in U.S. Patent Application Serial No. 13/892,727, the entire contents of which were incorporated herein by reference above. In any instance, the inner valve seal 36 may extend from a radially innermost point of the base 32, though the present disclosure is not limited to such an arrangement.

As briefly described above, the package 10 further includes the foil 16 that is sealingly and removably coupled to the seal ring 14 and that serves to seal the container 12 when the seal ring 14 and container 12 are assembled together. The foil 16 may be composed of any number of materials suitable for hermetically sealing the container 12, including, for example and without limitation, a metallic material (e.g., aluminum), a polymeric or plastic material (e.g., polyethylene terephthalate (PET), a paper material (e.g., wax paper), or other material or substrate suitable to form a seal. In the embodiment illustrated in FIG. 3, the foil 16 is removably and sealingly coupled to the base 32 of the seal ring 14, and more particularly, to the top surface 38 of the base 32, which thereby serves as a sealing surface of both the seal ring 14

and the package 10 when the seal ring 14 is assembled with the container 12. The foil 16 and the material of the seal ring 14 are closely matched to achieve optimal performance, and the foil 16 may be coupled to the base 32 of the seal ring 14 using any number of techniques, including, for example, induction and conduction sealing techniques, and/or any other suitable technique
5 known in the art. The foil 16 may be coupled to the seal ring 14 prior to assembling or coupling the seal ring 14 with the container 12, or alternatively, thereafter. As illustrated in FIG. 1, foil 16 may include a tab 54 extending from the periphery thereof that is configured to allow a user to remove the foil 16 from the seal ring 14 by pulling the tab 54 away from the seal ring 14 and the container 12.

0 With reference to FIGS. 3 and 4, an illustrative method of assembling the package 10 will now be described.

In a step 102, the foil 16 is coupled to the base 32 of the seal ring 14. In one embodiment, step 102 is performed prior to the seal ring 14 being coupled to or assembled with the container 12, while in another embodiment step 102 is performed after the seal ring 14 and
5 the container 12 are assembled together.

In any event, in a step 104, the seal ring 14 is aligned with the mouth 24 and the sealing surface 26 of the container finish 22, and is then pressed in an axial direction onto the container finish 22. More particularly, in step 104, the projection 42 of the seal ring 14 is aligned with the opening 28 in the container sealing surface 26. Once properly aligned, the seal
0 ring 14 is pressed in an axial direction onto the container finish 22, and the projection 42 is pressed into the opening 28. As the projection is pressed into the opening, the barbs 44 of the projection 42 engage the inner surface of the opening 28, thereby creating a mechanical fit between the seal ring 14 and the container 12 and securing the seal ring 14 to the container 12.

In an embodiment, as the seal ring 14 is pressed onto the container 12 and the inner valve seal 36 contacts the mouth 24 of the container finish 22, the inner valve seal 36 deflects in a radially inward direction into sealing engagement with the mouth 24 and/or the inner surface 31 of the container finish 22. The valve seal 36 remains biased against the mouth 24 or inner finish surface 31 to create a seal between the seal ring 14 and the container 12. Additionally, in an embodiment, as the seal ring 14 is pressed onto the container 12 and the radially outer portion 34 of the seal ring 14 contacts the container sealing surface 26, the outer portion 34 deflects in a radially outward direction into engagement with an outer surface of the container 12, and more particularly, an outer surface of the container finish 22. In an embodiment, step 104 is performed when the material of the container 12 is at a temperature sufficient to cause at least a portion of the base 32 of the seal ring 14 to melt and more completely conform to the sealing surface 26 of the container finish 22 to form a more complete seal between the seal ring 14 and the container 12 (e.g., the seal ring 14 will conform to imperfections in the sealing surface 26, for example).

Accordingly, in an embodiment, the method 100 further may comprise a step 106 of heating the container 12, or at least a portion thereof that includes the container finish 22, to a predetermined temperature sufficient to cause a desired amount of melting of the seal ring 14 prior to performing step 104. In an embodiment, step 106 may be performed during, or comprise a part of, the container manufacturing process where the residual heat from that process is sufficient to cause at least a portion of the seal ring 14 to melt. In another embodiment, step 106 may be independent of the container manufacturing process and may comprise applying heat to the container 12, or at least a portion thereof, immediately prior to performing step 104 of the method 100. In either case, the particular temperature required to sufficiently and acceptably

melt the seal ring 14 is dependent upon the particular materials of which the seal ring 14 and/or the container 12 is/are formed, and may be empirically derived by testing different materials and combinations of materials to achieve the desired amount of seal ring melting.

5 There thus has been disclosed a package that fully satisfies one or more of the objects and aims previously set forth. The disclosure has been presented in conjunction with an illustrative embodiment, and modifications and variations have been discussed. Other modifications and variations readily will suggest themselves to persons of ordinary skill in the art in view of the foregoing discussion.

Claims

1.

A seal ring (14) for sealing a container (12), and including:

5 a base (32) including a longitudinal axis (B) extending therethrough and
having:

 a top surface (38);

 an undersurface (40) opposite said top surface; and

 a projection (42) extending from said undersurface in an axial
0 direction, said projection configured to be received by a complementary opening (28) in the
container.

2.

 The seal ring set forth in claim 1, wherein said projection comprises an annular
5 projection.

3.

 The seal ring set forth in claim 1, wherein said projection includes one or more
barbs (44) extending outwardly therefrom.

0

4.

A package (10) that includes:

a container (12) including a longitudinal axis (A) extending therethrough and having a mouth (24), an axially-facing sealing surface (26), and an opening (28) in said sealing surface;

the seal ring set forth in claim 1, wherein said projection is received in said sealing surface opening thereby securing said seal ring to said container; and

a foil (16) sealingly and removably coupled to said ring.

5.

The package set forth in claim 4, wherein said opening comprises an annular channel in said sealing surface, and said projection comprises an annular projection received in said annular channel.

6.

The package set forth in claim 4, wherein said foil is coupled to said top surface, and said projection extends from said undersurface in an axial direction.

7.

The package set forth in claim 4, wherein said seal ring further includes an inner seal (36) biased into sealing engagement with said mouth of said container.

8.

The package set forth in claim 4, wherein said seal ring further includes a radially outer portion (34), and further wherein an inner surface (46) thereof is in engagement with an outer surface (30) of said container.

5

9.

The package set forth in claim 4, wherein said container is formed of glass.

10.

0 The package set forth in claim 4, wherein said seal ring is formed of plastic.

11.

The package set forth in claim 4, wherein said seal ring is adhesively affixed to said sealing surface of said container.

5

12.

A method (100) of assembling a container (12) and a seal ring (14), the method including:

0 heating (106) a least a portion of the container to a predetermined temperature sufficient to cause at least a portion of the seal ring to melt when coupled to the container; and

coupling (104) the seal ring to the container when the container is at the predetermined temperature such that a portion of the seal ring melts and conforms to a sealing surface of the container, and wherein said coupling step comprises:

aligning a projection of the seal ring with an opening in the sealing surface
of the container, and

pressing the seal ring in an axial direction onto the container to press the
projection into the opening in the sealing surface.

5

13.

A container and seal ring assembled together by the method of claim 12.

14.

0 A package (10) including said container and seal ring of claim 12 and a foil (16)
removably and sealingly coupled to said seal ring.